Incorporating Explicit and Implicit Chain-of-Thought as Hybrid Reasoning Paradigm with Guided Latent Space Modeling

Abstract

Chain-of-Thought (CoT) has proven effective for eliciting reasoning abilities in large language models, but standard autoregressive decoders treat reasoning and answer tokens uniformly as next-token prediction targets, despite their fundamentally different roles. This homogeneous modeling introduces conflicting inductive biases and significant inference overhead. Latent CoT methods attempt to improve efficiency by removing explicit reasoning tokens, yet often degrade performance, indicating that explicit reasoning supervision remains critical for preserving pretrained reasoning capabilities. To address these challenges, we propose **Pre**^{2}, a phase-aware reasoning framework that decouples thinking and answering while retaining explicit CoT supervision. Our approach introduces a Guided Latent Space and predict independent pre-thinking and pre-answering latent states to guide the model to generate reasoning tokens and answering tokens. We integrates them with explicit token representations through a hybrid latent–token decoding paradigm. This design increases computation along both width and depth dimensions with minimal parameter overhead, enabling stronger reasoning without sacrificing inference efficiency. **Training is conducted exclusively on one in-domain dataset, with direct zero-shot evaluation on six out-of-domain benchmarks**, and experiments demonstrate consistent and significant improvements over strong baselines and robust generalization. Code will be released at `github.com`

1 Introduction

Chain-of-Thought (CoT) prompting, introduced by Wei et al. (2022), has proven effective in enhancing the reasoning abilities of large language models by inducing intermediate reasoning steps, yielding strong gains on mathematical and multi-step reasoning tasks (Guo et al., 2025; OpenAI, 2024; Muennighoff et al., 2025). However, these prompt-based methods rely on explicitly generating reasoning tokens at inference time (Wang et al., 2022; Zhou et al., 2022; Kojima et al., 2022; Zhang et al., 2022). Due to the autoregressive nature of language models, early reasoning errors can propagate through subsequent predictions, often resulting in brittle and unstable reasoning trajectories.

To mitigate this limitation, a line of work has explored test-time scaling strategies that aggregate or refine reasoning paths through increased computation at inference. Representative approaches include self-consistency (Wang et al., 2022), which samples multiple reasoning trajectories and selects the most consistent answer, as well as more structured methods such as Tree-of-Thoughts (ToT, Yao et al. 2023), which explicitly searches over reasoning branches. While effective, these methods significantly increase inference cost, as they require extensive sampling, branching, or search procedures, making them impractical for latency- or budget-constrained settings (Li et al., 2024; Wang et al., 2025).

More recently, latent CoT approaches have emerged as an alternative direction, aiming to bypass explicit reasoning token generation altogether (Wei et al., 2025; He et al., 2025; Liu and Zhang, 2025). Instead of producing natural language reasoning steps, these methods perform reasoning directly in a continuous latent space, thereby reducing inference-time token generation. Representative works such as Coconut (Hao et al., 2024), CoDi (Shen et al., 2025), and SoftCoT (Xu et al., 2025) demonstrate that latent representations can capture certain aspects of reasoning while improving efficiency. Nevertheless, by skipping or discarding explicit reasoning tokens, these approaches often struggle to fully preserve the reasoning capabilities of pretrained models, highlighting a fundamental trade-off between efficiency and reasoning fidelity (Xia et al., 2025; Liu et al., 2025).

Traditional methods uniformly model reasoning

and answer tokens, ignoring their fundamentally different patterns (Nye et al., 2021; Lampinen et al., 2022). While latent reasoning approaches eliminate CoT for efficiency, we argue that CoT provides essential supervision signals aligned with pretraining. Fully eliminating CoT may weaken reasoning ability (Turpin et al., 2023). To address these limitations, we explicitly decouple the modeling of reasoning and answering by introducing independent pre-thinking and pre-answering phases, and our approach preserves explicit reasoning supervision while introducing structured latent phases, balancing inference efficiency and reasoning expressivity. Specifically, instead of forcing the model to autoregressively commit to explicit reasoning tokens, we supervise continuous latent representations that summarize the reasoning-ready and answer-ready states. This separation enables the model to first internalize a structured reasoning abstraction before transitioning into answer generation, thereby strengthening its reasoning capability while reducing reliance on verbose or brittle CoT generation.

We introduce **Pre²**, a novel framework that effectively addresses all of the above-mentioned problems simultaneously. **We model Chain-of-Thought reasoning as a structured latent trajectory composed of a reasoning-ready state and an answer-ready state. Instead of autoregressively generating reasoning tokens, we supervise continuous latent representations aligned with pooled reasoning and answer embeddings, enabling non-autoregressive and controllable reasoning abstraction**. Our contributions are summarized as follows: (1) We propose a phase-aware reasoning framework that independently models the pre-thinking and pre-answering processes, effectively decoupling the conflicting patterns between thinking and answering stages. (2) We introduce a hybrid paradigm that combines latent representations with explicit token-level supervision, requiring only a minimal increase in model parameters while preserving strong performance and high inference efficiency. (3) We conduct extensive experiments on one in-domain dataset and four out-of-domain benchmarks, where our method consistently outperforms strong baselines, demonstrating robust generalization across domains.

2 Related Works

Explicit Chain-of-Thought Reasoning. Explicit Chain-of-Thought (CoT) prompting has become a cornerstone for eliciting reasoning capabilities in large language models (LLMs). Pioneering works demonstrate that explicitly generating intermediate reasoning steps significantly boosts performance on arithmetic and symbolic tasks (Wei et al., 2022; Kojima et al., 2022). Despite the successes, explicit CoT suffers from inherent inefficiency due to the autoregressive generation of long reasoning sequences. Furthermore, treating reasoning tokens and answer tokens as homogeneous prediction targets introduces structural conflicts; reasoning trajectories often require exploratory and verbose patterns, whereas answers demand conciseness (Nye et al., 2021; Lampinen et al., 2022).

Latent Chain-of-Thought Reasoning. To mitigate the inference overhead of explicit tokens, Latent CoT approaches aim to internalize reasoning into continuous hidden states or implicit processes, enabling models to "think before speaking" (Zelikman et al., 2024). Methods like implicit reasoning via stepwise knowledge internalization (Deng et al., 2024) and teacher-student distillation (e.g., CODI, Shen et al. 2025) attempt to transfer reasoning semantics from explicit traces to model embeddings. Other approaches, such as Coconut (Hao et al., 2024) and CCoT (Cheng and Van Durme, 2024), explore reasoning in continuous space by compressing steps into dense vectors or "contemplation tokens". However, purely latent methods face significant challenges: they often suffer from performance degradation on complex tasks due to the lack of fine-grained supervision signals (Hao et al., 2024). Unlike explicit CoT, where every step is verified, methods like Coconut typically rely on answer-level supervision, while distillation methods like CODI focus on trajectory-level alignment, potentially losing critical step-wise logic.

Computational Scaling across Width and Depth Dimensions. Existing computational scaling methods face limitations: width-based approaches (e.g., Pause Tokens, Goyal et al. 2023) often lack explicit semantic guidance, while depth-based methods (e.g., MoR, Bae et al. 2025 and Ouro Zhu et al. 2025) keep reasoning implicit within recursive loops. We bridge these dimensions by scaling width via learnable latent tokens and depth through independent modules.

Our approach leverages a hybrid framework combining explicit and latent Chain-of-Thought reasoning. Unlike pause tokens that operate exclusively with static token-level embeddings, our framework employs learnable sentence-level em-

Figure 1: Overview of the proposed framework. We frozen the embedding layer and adopt pooled reasoning embedding and answering embedding as the supervision signal. Then the predicted pre-thinking emb. and pre-answering emb. from the Guided Latent Space (The bottom right part.) will be fed into the Transformer block together with all explicit embeddings

beddings to capture sequence representations of complete reasoning steps and answer tokens.

3 Methodology

3.1 Preliminary of Pre[2]

Let $\mathcal{V}$ denote a vocabulary of size $V = |\mathcal{V}|$. Given a single training sample, we define a CoT sequence as

$$\mathbf{X} = (\mathbf{Q} := x^{(q)},\ \mathbf{R} := x^{(r)},\ \mathbf{A} := x^{(a)}),$$

where $x^{(q)} = (q_1, \ldots, q_{L_q}) \in \mathcal{V}^{L_q}$, $x^{(r)} = (r_1, \ldots, r_{L_r}) \in \mathcal{V}^{L_r}$, and $x^{(a)} = (a_1, \ldots, a_{L_a}) \in \mathcal{V}^{L_a}$ denote the query, reasoning steps, and answer, respectively.

Our framework introduces a novel approach where three built-in embeddings serve as initialization for the latent states of pre-thinking and pre-answering. We first introduce three continuous latent vectors that have been initialized within our model:

$$\mathbf{z}_{\text{think}}^{(0)} \in \mathbb{R}^d, \mathbf{z}_{\text{ans}}^{(0)} \in \mathbb{R}^d, \mathbf{z}_{\text{boa}}^{(0)} \in \mathbb{R}^d,$$

where $\mathbf{z}_{\text{think}}^{(0)}$, $\mathbf{z}_{\text{ans}}^{(0)}$ and $\mathbf{z}_{\text{boa}}^{(0)}$ are learnable global parameters. Specifically, $\mathbf{z}_{\text{think}}^{(0)}$ is trained to learn a latent representation of the complete reasoning process; $\mathbf{z}_{\text{ans}}^{(0)}$ captures an abstract representation of the answer; and $\mathbf{z}_{\text{boa}}^{(0)}$ serves as an answer indicator that signals the model to transition into answer generation mode.

Our model uses a frozen token embedding matrix $\mathcal{E}$ to get different non-contextualized embeddings for query, reasoning and answer tokens. This approach offers an additional advantage: the frozen embedding layer provides stable training targets while preserving model capacity, thus avoiding performance degradation. Let $\mathcal{E} : \mathcal{V} \to \mathbb{R}^d$ be a shared token embedding function. The embedded sequences are given by:

$$\mathbf{Q} = (\mathbf{q}_1, \ldots, \mathbf{q}_{L_q}) \in \mathbb{R}^{L_q \times d},$$
$$\mathbf{R} = (\mathbf{r}_1, \ldots, \mathbf{r}_{L_r}) \in \mathbb{R}^{L_r \times d},$$
$$\mathbf{A} = (\mathbf{a}_1, \ldots, \mathbf{a}_{L_a}) \in \mathbb{R}^{L_a \times d}.$$

We then define a pooling operator $\mathcal{P}(\cdot)$ to obtain sequence-level representations. And the pooled reasoning and answers representations will be regarded as gold latent representations because we assume that these pooled representations include all necessary information to guide the model to generate complete reasoning tokens and answering tokens.

$$\bar{\mathbf{r}} = \mathcal{P}(\mathbf{R}) \in \mathbb{R}^d,$$
$$\bar{\mathbf{a}} = \mathcal{P}(\mathbf{A}) \in \mathbb{R}^d.$$

3.2 Pre-thinking and Pre-answering Modeling

The modeling of pre-thinking and pre-answering is centered on a key principle: we aim to obtain embeddings that encapsulate holistic information. Specifically: The **pre-thinking embeddings** are

expected to capture complete information about the reasoning steps, encoding the entire reasoning trajectory in a compact representation. The **pre-answering embeddings** should encapsulate the final answer information. With these global representations, the model can provide top-down guidance and predictions throughout the subsequent autoregressive generation of reasoning tokens and answer tokens, rather than relying solely on local, step-by-step predictions. We now address the key question: how are these compressed embeddings learned?

We make a key empirical observation: for a small proportion of complex reasoning tasks, models can produce correct answers directly from the query even when the generated reasoning steps are unreliable or incorrect. Motivated by this observation, we design our approach to leverage query tokens as conditions, using the built-in embeddings as latent state initializations and employing two lightweight Transformer decoder blocks to causally model token-level dependencies. Moreover, recent studies have demonstrated that increasing per-token computation depth yields unique benefits that cannot be achieved by simply scaling the width of sequence modeling, particularly for certain reasoning tasks (Bae et al., 2025; Zhu et al., 2025). To enhance computational and inference efficiency, we selectively allocate additional depth-wise computation exclusively to reasoning and answer tokens.

Let f_{think} denote the pre-thinking module. The input sequence is constructed as

$$\mathbf{H}_{\text{think}}^{(0)} = \big[\mathbf{Q}; \mathbf{z}_{\text{think}}^{(0)}\big],$$

where $[\cdot; \cdot]$ is concatenation operator.

The hidden states are obtained by

$$\mathbf{H}_{\text{think}} = f_{\text{think}}(\mathbf{H}_{\text{think}}^{(0)}).$$

We take the final hidden state as the predicted pre-thinking latent representation:

$$\hat{\mathbf{z}}_{\text{think}} = \mathbf{H}_{\text{think}}[-1].$$

Similarly, we define a pre-answering module f_{ans} with input

$$\mathbf{H}_{\text{ans}}^{(0)} = \big[\mathbf{Q}; \mathbf{z}_{\text{ans}}^{(0)}\big].$$

The predicted pre-answering latent is given by

$$\hat{\mathbf{z}}_{\text{ans}} = f_{\text{ans}}(\mathbf{H}_{\text{ans}}^{(0)})[-1].$$

Specifically, the two modules consist of two Transformer blocks and utilize a causal mask for attention computation. This design enables both $\mathbf{z}_{\text{think}}^{(0)}$ and $\mathbf{z}_{\text{ans}}^{(0)}$ to attend to the complete set of query token embeddings, allowing modeling pre-thinking and pre-answering separately. To enable $\mathbf{z}_{\text{think}}^{(0)}$ and $\mathbf{z}_{\text{ans}}^{(0)}$ to learn representations that can predict the overall architecture encompassing the thinking and answering stages, we let $\bar{\mathbf{r}}$ and $\bar{\mathbf{a}}$ be the supervised signal for pre-thinking modeling and pre-answering modeling, and the loss function will be either smooth L1 or L2 loss. To prevent gradient backpropagation and ensure unidirectional learning flow, we apply a stop-gradient operation ($\mathcal{SG}(\cdot)$) on $\bar{\mathbf{r}}$ and $\bar{\mathbf{a}}$. Thus, the pre-thinking alignment loss (e.g., L2 norm) is defined as

$$\mathcal{L}_{\text{think}} = \|\hat{\mathbf{z}}_{\text{think}} - \mathcal{SG}(\bar{\mathbf{r}})\|_2^2. \tag{1}$$

The pre-answering alignment loss is defined as

$$\mathcal{L}_{\text{ans}} = \|\hat{\mathbf{z}}_{\text{ans}} - \mathcal{SG}(\bar{\mathbf{a}})\|_2^2. \tag{2}$$

3.3 Training of Pre^2

In the following section, we describe the training procedure. Let $\mathbf{e}_{\text{eot}} \in \mathbb{R}^d$ denote the end-of-thought embedding. The decoder input sequence is constructed as

$$\mathbf{H}_{\text{dec}}^{(0)} = \big[\mathbf{Q}; \hat{\mathbf{z}}_{\text{think}}; \mathbf{R}; \mathbf{e}_{\text{eot}}; \hat{\mathbf{z}}_{\text{ans}}; \mathbf{z}_{\text{boa}}; \mathbf{A}\big] \in \mathbb{R}^{T_{\text{dec}} \times d},$$

where $T_{\text{dec}} = L_q + 1 + L_r + 1 + 1 + 1 + L_a$.

And the $\mathbf{e}_{\text{eot}}$ is a special token that is already in the vocabulary of the pre-trained backbone model. And this $\mathbf{e}_{\text{eot}}$ is essential for our inference pipeline because it can provide a proper signal that tells us the reasoning stage is completed.

The decoder f_{dec} produces hidden states

$$\mathbf{H}_{\text{dec}} = f_{\text{dec}}(\mathbf{H}_{\text{dec}}^{(0)}).$$

The corresponding supervision labels are defined as

$$\mathbf{Y} = \big[\underbrace{\texttt{-100}}_{\mathbf{Q}}, \mathbf{R}, \mathbf{e}_{\text{eot}}, \underbrace{\texttt{-100}}_{\hat{\mathbf{z}}_{\text{ans}}}, \underbrace{\texttt{-100}}_{\mathbf{z}_{\text{boa}}}, \mathbf{A}\big],$$

where $\texttt{-100}$ indicates masked positions that do not contribute to the loss.

Let $\mathcal{T}_{\text{sup}} \subset \{1, \ldots, T_{\text{dec}}\}$ denote the set of supervised token positions, given by

$$\mathcal{T}_{\text{sup}} = \mathcal{T}_{\text{cot}} \cup \mathcal{T}_{\text{ans}},$$

where

$$\mathcal{T}_{\text{cot}} = \{\, t \mid x_t \in \mathbf{R} \cup \{e_{\text{eot}}\} \,\}, \mathcal{T}_{\text{ans}} = \{\, t \mid x_t \in \mathbf{A} \,\}.$$

The masked language modeling loss is defined as

$$\begin{aligned}
\mathcal{L}_{\text{LM}} &= -\sum_{t \in \mathcal{T}_{\text{sup}}} \log p_\theta(y_t \mid \mathbf{H}_{\text{dec}}^{(<t)}) \\
&= -\sum_{t \in \mathcal{T}_{\text{cot}}} \log p_\theta(r_t \mid \mathbf{H}_{\text{dec}}^{(<t)}) \qquad (3) \\
&\quad - \sum_{t \in \mathcal{T}_{\text{ans}}} \log p_\theta(a_t \mid \mathbf{H}_{\text{dec}}^{(<t)}).
\end{aligned}$$

The overall training objective is given by

$$\mathcal{L} = (1 - \lambda_{\text{think}} - \lambda_{\text{ans}})\mathcal{L}_{\text{LM}} + \lambda_{\text{think}}\mathcal{L}_{\text{think}} + \lambda_{\text{ans}}\mathcal{L}_{\text{ans}}.$$
$$(4)$$

3.4 Inference of Pre²

The inference procedure differs from vanilla autoregressive decoding in several ways. Notably, we must explicitly maintain: (1) the current query length, and (2) an End-of-Thought (EoT) signal to determine when CoT generation concludes and answer generation should begin. We provide a detailed pseudocode description in Algorithm 1, where $\mathbf{q}$ is query embeddings, $\hat{\mathbf{z}}_t$ is predicted pre-thinking embedding, $\hat{\mathbf{z}}_a$ is predicted pre-answering embedding, $\mathbf{z}_{\text{boa}}$ is the answering indicator embedding that initialized in the model. Specifically, during the prefilling phase, we execute the pre-thinking $f_{\text{think}}(\cdot)$ and pre-answering modules $f_{\text{answer}}(\cdot)$ to generate $\hat{\mathbf{z}}_t$ and $\hat{\mathbf{z}}_a$ before any token generation begins. In the autoregressive generation stages that follow, we dynamically reconstruct the input sequence $\mathbf{X}$ through concatenation operations, ensuring that the model's behavior remains consistent across training and inference.

4 Experimental Design

4.1 Datasets

We train the Pre² framework on GSM8K-Aug (Deng et al., 2024), which augments the original GSM8K (Cobbe et al., 2021) training set with questions. For evaluation, we assess reasoning robustness and generalization across 7 benchmarks categorized into in-domain and out-of-domain settings. The in-domain evaluation uses the standard GSM8K (Cobbe et al., 2021) test split, while out-of-domain evaluation employs four datasets: GSM-Hard (increased arithmetic difficulty through larger integers) (Gao et al., 2022), MultiArith (multi-step sequential reasoning) (Roy and Roth, 2015),

---

Algorithm 1 Inference Process of **Pre**²

Require: Token embeddings $\mathbf{x}$ from frozen embedding layer;
Require: Stage-flags: `is_prefilling`, `is_cot_end`, `is_answering`
Ensure: Updated embeddings $\mathbf{x}$
1: **if** `is_prefilling` **then**
2:     $\hat{\mathbf{z}}_t = f_{\text{think}}([x; \mathbf{z}_{\text{think}}^{(0)}])[-1]$
3:     $\hat{\mathbf{z}}_a = f_{\text{answer}}([x; \mathbf{z}_{\text{answer}}^{(0)}])[-1]$
4:     $\mathbf{x} \leftarrow [\mathbf{x}; \hat{\mathbf{z}}_t]$
5: **else**
6:     **if** `is_cot_end` **then**
7:         **if** $\neg$`is_answering` **then**
8:             $\mathbf{x} \leftarrow [\mathbf{q}; \hat{\mathbf{z}}_t; \text{CoT}; \langle\text{eot}\rangle; \hat{\mathbf{z}}_a; \mathbf{z}_{\text{boa}}]$
9:             `is_answering` $\leftarrow$ True
10:         **else**
11:             $\mathbf{x} \leftarrow [\mathbf{q}; \hat{\mathbf{z}}_t; \text{CoT}; \langle\text{eot}\rangle; \hat{\mathbf{z}}_a; \mathbf{z}_{\text{boa}}; \text{Ans}]$
12:         **end if**
13:     **else**
14:         $\mathbf{x} \leftarrow [\mathbf{q}; \hat{\mathbf{z}}_t; \text{CoT}]$
15:     **end if**
16: **end if**
17: **return** $\mathbf{x}$

SVAMP (structural and textual variations) (Patel et al., 2021), and ASDiv (diverse problem types and linguistic patterns) (Xu et al., 2025), and MMLU (Hendrycks et al., 2021) and ARC-C (Clark et al., 2018). Full dataset details are provided in the Appendix B.

4.2 Baselines

We evaluate **Pre²** against five representative baselines covering different reasoning paradigms: **(1) Zero-shot Pretrained**, which directly evaluates a pretrained model without fine-tuning; **(2) Few-shot In-Context Learning**, where three demonstration examples are provided as prompts without parameter updates; **(3) SFT with Explicit CoT**, which fine-tunes the model to generate the full query–reasoning–answer sequence; **(4) SFT with Frozen Embeddings**, identical to (3) but with the embedding layer fixed to assess the role of input representations; and **(5) Pause Token Baseline** (Goyal et al., 2023), which inserts fixed special tokens around the reasoning sequence following prior "thinking token" approaches, while keeping these tokens non-learnable during training.

4.3 Evaluation Metrics

All evaluations are under multi-sampling evaluation (temperature = 0.1). And we evaluate model performance using three metrics. **(1) Accuracy (Acc.)** measures answer correctness, defined as the percentage of correctly predicted answers. **(2) Generated Sequence Length** quantifies reasoning compactness by computing the average number of

| Model | Method | In-domain | Out-of-domain | | | | Overall |
		GSM8K	GSMHard	MultiArith	ASDiv-AUG	SVAMP	Avg
Qwen2.5-0.5B	Zero-shot	43.06	12.15	82.78	77.55	46.33	52.37
	Few-shot	41.60	10.99	81.83	78.13	45.67	51.64
	Baseline	51.93	12.63	92.80	82.23	52.60	58.44
	Freeze-Baseline	51.93	12.61	92.63	82.19	52.13	58.30
	Pause Token	52.22	12.64	93.39	82.58	52.73	58.71
	Pre^2-1	**53.73**	**12.78**	**94.33**	**83.35**	**53.47**	**59.53**
Qwen2.5-1.5B	Zero-shot	46.90	12.40	90.00	81.31	51.33	56.38
	Few-shot	46.62	13.16	88.50	81.70	49.67	55.93
	Baseline	54.61	13.52	94.66	83.28	57.86	60.79
	Freeze-Baseline	54.45	13.39	94.53	83.27	57.80	60.69
	Pause Token	54.61	13.57	94.74	83.31	57.46	60.74
	Pre^2-1	**55.54**	**13.92**	**95.33**	**83.75**	**59.13**	**61.53**
Qwen2.5-3B	Baseline	68.41	24.76	97.7	88.27	74.33	70.71
	Freeze-Baseline	68.26	24.71	97.50	88.21	74.01	70.54
	Pause Token	68.61	25.12	**97.72**	88.47	75.34	71.05
	Pre^2-1	**70.13**	**26.09**	98.66	**89.53**	**76.33**	**72.15**
Qwen2.5-7B	Baseline	75.28	28.91	98.38	89.56	77.55	73.94
	Freeze-Baseline	75.13	28.83	98.11	89.49	77.33	72.78
	Pause Token	75.58	29.56	98.33	89.62	77.11	74.04
	Pre^2-1	**76.49**	**29.95**	**98.89**	**90.27**	**78.33**	**74.79**
Llama3.2-1B	Baseline	52.91	12.05	95.00	79.19	52.66	58.36
	Freeze-Baseline	52.53	11.75	94.17	79.09	51.00	57.71
	Pause Token	53.14	12.43	94.83	79.28	53.33	58.60
	Pre^2-1	**54.43**	**12.66**	**95.17**	**79.67**	**54.33**	**59.25**

Table 1: Main performance comparison across different model scales and model series on in-domain and out-of-domain reasoning benchmarks. We do significance test ($p < 0.05$) based on Paired t-test significance test with 5 different training seeds, and here are the final results, and Scores being boldfaced means that our model is significantly better than baseline

tokens in the generated reasoning chains across all examples, where shorter sequences indicate higher efficiency. **(3) Inference Throughput** evaluates efficiency by measuring the generation speed in tokens per second, computed as the total number of generated tokens divided by the total inference time. Higher throughput indicates better inference efficiency.

4.4 Research Questions

Our experiments aim to answer the following research questions: (1) Compared to traditional decoder-based models, what magnitude of improvement can our architecture achieve on downstream reasoning tasks? (2) More specifically, do pre-thinking modeling and pre-answering modeling enable the model to predict reasoning tokens and answer tokens with higher accuracy? (3) Does scaling up the pre-thinking module and pre-answering module along the depth dimension yield consistent performance gains? (4) Similarly, does scaling up the pre-thinking scope along the width dimension enhance the model's reasoning capabilities? (5) Compared to the baseline model, we introduce

two prediction modules and three internally initialized embeddings; relative to the baseline size, we add only a modest number of parameters, and our inference mixes autoregressive decoding with latent-space prediction. Will these extra parameters and the new inference paradigm materially impact inference efficiency?

We show the experimental results for the five questions in five subsections of Sec. 5 respectively. Refer to the appendix A for implementation details.

5 Results and Discussions

5.1 Main Results

Our model consistently outperforms baselines across one in-domain and four out-of-domain benchmarks. Table 1 presents a comprehensive comparison between Qwen2.5 series with a wide size models (0.5b, 1.5b, 3b, 7b) (Qwen et al., 2025), and Llama3.2 1b (Grattafiori et al., 2024) across various reasoning benchmarks.

Several key observations emerge from these results: **(1) Consistent superiority of Pre^2-1:** Our proposed Pre^2-1 method consistently outperforms

Figure 2: Ablation study: Pre-thinking module and Pre-answering module. OnlyA means we only adopt Pre-answering module and OnlyT means we only adopt Pre-thinking module.

Model	ARC-C	MMLU
Qwen-0.5B Zero-shot	29.01	47.37
Qwen-0.5B Baseline	29.12	47.38
Qwen-0.5B Freeze-baseline	29.15	47.37
Pause Token	29.37	47.41
Pre^2-1	**29.90**	**47.60**

Table 2: General reasoning performance comparison across different model variants.

Model	GSM8K	GSM_H	Multi	ASDiv	SVAMP	Avg.
Pre^2-1	53.73	12.78	94.33	83.35	53.47	59.53
Pre^2-3	**54.01**	**12.91**	**95.11**	**83.82**	**55.11**	**60.19**
Pre^2-5	53.82	12.78	94.61	83.65	54.44	59.86
Pre^2-7	53.90	12.81	94.44	83.46	53.66	59.65

Table 3: Ablation study on the Depth Dimension based on Qwen-0.5b models.

Base Model	Ours	Size-matched Model	↑ Gain
Qwen-0.5B	53.73	52.01	**+1.72**
Qwen-1.5B	55.54	54.60	**+0.94**
Qwen-3B	70.13	68.51	**+1.62**
Qwen-7B	76.49	75.33	**+1.16**
Average	63.97	62.61	**+1.36**

Table 4: Results on GSM8K. We compare our models with a param-matched transformer. Our method consistently improves performance within the same model-size budget.

all baseline approaches across both model scales. **(2) Strong generalization to out-of-domain tasks:** Notably, Pre^2-1 demonstrates robust performance not only on the in-domain GSM8K benchmark but also across all four out-of-domain datasets. **(3) Comparison with Pause Token baseline:** While the Pause Token method shows marginal improvements over the standard Baseline, it is consistently outperformed by our Pre^2-1 approach. This suggests that our pre-thinking and pre-answering mechanisms provide more effective modeling of the reasoning process than simple pause token insertion. Although both the pause token method and our approach perform equivalent scaling along the sequence width dimension, we hypothesize that this advantage arises because pause tokens employ static embeddings, whereas our pre-thinking and pre-answering embeddings are learnable and dynamic. Our novel training approach further enables these embeddings to encapsulate rich information about future token sequences, providing stronger guidance for reasoning. **(4) Scaling behavior:** The results indicate that our architectural improvements are complementary to model scaling, with benefits observed across from 0.5B to 7B parameter scales, demonstrating the generalizability of our approach. **(5) General reasoning:** We evaluate zero-shot performance on two out-of-domain general reasoning benchmarks, and the results (Table 2) show that our models achieve consistent improvements.

5.2 Impact of Pre-thinking and Pre-answering on Performance

As shown in Figure 2, which presents an ablation study comparing our full model against the baseline and two single-component variants, revealing the individual and synergistic contributions of our architectural components. The full model (Pre^2) achieves 59.532% average accuracy, outperforming the baseline by 1.1 points. Critically, this exceeds both OnlyT (pre-thinking only) and OnlyA (pre-answering only), demonstrating that the combined gain is substantially larger than either component alone, confirming their complementary nature. Besides, both ablated variants independently improve over the baseline.

5.3 Exploring the Depth Scaling of Pre-thinking and Pre-answering Modules

Table 3 investigates the impact of scaling the pre-thinking and pre-answering modules along the depth dimension by varying the number of Transformer layers (1, 3, 5, 7). As the number of lay-

Figure 3: Ablation study on the Width Dimension (Pre-thinking Scope).

Model	GSM8K		GSMHard		MultiArith		SVAMP		ASDiv-Aug	
	Tok	T/s	Tok	T/s	Tok	T/s	Tok	T/s	Tok	T/s
Baseline	47.6	76.7 (1.00)	78.9	76.6 (0.36)	23.6	77.2 (1.31)	25.9	76.5 (1.07)	15.6	75.9 (1.45)
Pause Token	44.5	76.8 (0.96)	77.2	76.5 (0.78)	24.6	77.1 (0.55)	24.7	76.6 (1.00)	15.6	75.1 (1.52)
Pre^2-0.5b-1-1	46.1	76.9 (0.49)	78.6	76.5 (0.85)	24.6	76.3 (1.61)	24.4	76.3 (1.57)	15.6	75.4 (2.36)
Pre^2-0.5b-3-1	45.1	75.0 (1.55)	71.3	75.8 (0.81)	24.6	75.3 (1.99)	23.3	75.7 (0.90)	15.6	77.0 (0.92)
Pre^2-0.5b-5-1	44.4	74.5 (0.40)	74.9	74.4 (0.43)	24.6	74.6 (0.99)	28.5	74.3 (1.93)	15.6	75.3 (0.87)
Pre^2-0.5b-7-1	46.2	74.1 (1.59)	72.3	73.6 (1.37)	24.6	74.5 (1.29)	28.5	73.8 (2.19)	15.6	73.1 (0.88)
Pre^2-0.5b-1-2	45.0	75.8 (1.31)	77.8	76.1 (1.24)	24.6	75.7 (1.16)	26.3	76.0 (1.04)	15.6	74.2 (1.68)
Pre^2-0.5b-1-3	45.3	75.3 (1.46)	75.5	76.5 (0.88)	24.6	75.6 (1.38)	25.8	75.6 (1.23)	16.4	75.1 (0.79)
Pre^2-0.5b-1-4	45.3	75.1 (1.63)	71.0	75.2 (0.76)	24.6	75.3 (0.41)	26.4	75.4 (1.38)	15.6	75.3 (2.04)
Pre^2-0.5b-1-5	49.0	74.6 (1.04)	73.8	74.5 (0.71)	24.6	75.1 (1.31)	25.7	75.6 (0.95)	15.6	73.8 (1.69)

Table 5: Inference efficiency analysis comparing **Pre**^{2} variants against the baseline and Pause Token.

ers increases, performance first improves and then declines or converges. We find that the optimal depth is 3, since modeling the latent space does not require a large number of parameters. Excessive computation and parameterization may lead to overfitting.

5.4 Width Scaling of Pre-thinking Scope

Figure 3 examines the impact of scaling the pre-thinking scope (here we fix the depth at 1 transformer layer) (width dimension) from 1 to 5 tokens, which means that we will expand the width of pre-thinking scope during training and inference time. Note that we fix the pre-answering scope at 1, as all benchmark answers are sufficiently short to be compressed into a single token representation. Generally, expanding the pre-thinking scope demonstrates progressive performance improvements. This trend suggests that allocating wider latent space for reasoning compression enhances the model's capacity to capture complex thought processes. These findings indicate that width-wise scaling of the pre-thinking module provides complementary benefits to depth scaling, with wider scopes enabling richer compression of reasoning chains.

5.5 Ablation on Params-matching

As shown in Table 4, we demonstrate that performance gains stem from architectural and inference paradigm innovations rather than increased parameter count, verified by a size-matched baseline constructed by scaling the original LLM's layer depth.

5.6 Model Efficiency

Table 5 presents a comprehensive evaluation of inference throughput (tokens/second) across all model variants and benchmarks, demonstrating that our architectural do not significantly degrade inference performance compared to the baseline.

6 Conclusion

We presented a phase-aware reasoning framework that decouples thinking and answering in large language models by combining latent representations with explicit chain-of-thought supervision. By independently modeling pre-thinking and pre-answering phases, our approach mitigates the limitations of autoregressive reasoning while preserving pretrained reasoning capabilities. Experiments across in-domain and out-of-domain benchmarks demonstrate consistent improvements in both performance and inference efficiency. This work highlights the importance of structured reasoning phases as a promising direction for building more efficient and robust reasoning models.

Limitations

Despite its effectiveness, our approach has several limitations. First, due to resource constraints, we did not conduct experiments on very large-scale models, such as those with more than 13B parameters. Second, while our method improves inference efficiency relative to explicit chain-of-thought decoding, it still relies on explicit reasoning supervision during training, limiting its applicability to domains where high-quality reasoning annotations are available.

Ethical Considerations

Our use of publicly available datasets and developed models in this research raises no ethical concerns, and we confirm compliance with the ACL Code of Ethics.

References

Sangmin Bae, Yujin Kim, Reza Bayat, Sungnyun Kim, Jiyoun Ha, Tal Schuster, Adam Fisch, Hrayr Harutyunyan, Ziwei Ji, Aaron Courville, and 1 others. 2025. Mixture-of-recursions: Learning dynamic recursive depths for adaptive token-level computation. *arXiv preprint arXiv:2507.10524*.

Jeffrey Cheng and Benjamin Van Durme. 2024. Compressed chain of thought: Efficient reasoning through dense representations. *arXiv preprint arXiv:2412.13171*.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *Preprint*, arXiv:1803.05457.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Yuntian Deng, Yejin Choi, and Stuart Shieber. 2024. From explicit cot to implicit cot: Learning to internalize cot step by step. *arXiv preprint arXiv:2405.14838*.

Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. 2022. Pal: Program-aided language models. *arXiv preprint arXiv:2211.10435*.

Sachin Goyal, Ziwei Ji, Ankit Singh Rawat, Aditya Krishna Menon, Sanjiv Kumar, and Vaishnavh Nagarajan. 2023. Think before you speak: Training language models with pause tokens. *arXiv preprint arXiv:2310.02226*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Shibo Hao, Sainbayar Sukhbaatar, DiJia Su, Xian Li, Zhiting Hu, Jason Weston, and Yuandong Tian. 2024. Training large language models to reason in a continuous latent space. *arXiv preprint arXiv:2412.06769*.

Yinhan He, Wendy Zheng, Yaochen Zhu, Zaiyi Zheng, Lin Su, Sriram Vasudevan, Qi Guo, Liangjie Hong, and Jundong Li. 2025. Semcot: Accelerating chain-of-thought reasoning through semantically-aligned implicit tokens. *arXiv preprint arXiv:2510.24940*.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. *Preprint*, arXiv:2009.03300.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Andrew Lampinen, Ishita Dasgupta, Stephanie Chan, Kory Mathewson, Mh Tessler, Antonia Creswell, James McClelland, Jane Wang, and Felix Hill. 2022. Can language models learn from explanations in context? In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 537–563.

Yiwei Li, Peiwen Yuan, Shaoxiong Feng, Boyuan Pan, Xinglin Wang, Bin Sun, Heda Wang, and Kan Li. 2024. Escape sky-high cost: Early-stopping self-consistency for multi-step reasoning. *arXiv preprint arXiv:2401.10480*.

Jingyu Liu and Ce Zhang. 2025. Hamburger: Accelerating llm inference via token smashing. *arXiv preprint arXiv:2505.20438*.

Yue Liu, Jiaying Wu, Yufei He, Ruihan Gong, Jun Xia, Liang Li, Hongcheng Gao, Hongyu Chen, Baolong Bi, Jiaheng Zhang, and 1 others. 2025. Efficient inference for large reasoning models: A survey. *arXiv preprint arXiv:2503.23077*.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori B Hashimoto. 2025. s1: Simple test-time scaling. In *Proceedings of the 2025 Conference on*

Empirical Methods in Natural Language Processing, pages 20286–20332.

Maxwell Nye, Anders Johan Andreassen, Guy Gur-Ari, Henryk Michalewski, Jacob Austin, David Bieber, David Dohan, Aitor Lewkowycz, Maarten Bosma, David Luan, and 1 others. 2021. Show your work: Scratchpads for intermediate computation with language models.

OpenAI. 2024. Gpt-4o. Large language model.

Arkil Patel, Satwik Bhattamishra, and Navin Goyal. 2021. Are NLP models really able to solve simple math word problems? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2080–2094, Online. Association for Computational Linguistics.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Subhro Roy and Dan Roth. 2015. Solving general arithmetic word problems. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 1743–1752, Lisbon, Portugal. Association for Computational Linguistics.

Zhenyi Shen, Hanqi Yan, Linhai Zhang, Zhanghao Hu, Yali Du, and Yulan He. 2025. Codi: Compressing chain-of-thought into continuous space via self-distillation. *arXiv preprint arXiv:2502.21074*.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel Bowman. 2023. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. *Advances in Neural Information Processing Systems*, 36:74952–74965.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Yiming Wang, Pei Zhang, Siyuan Huang, Baosong Yang, Zhuosheng Zhang, Fei Huang, and Rui Wang. 2025. Sampling-efficient test-time scaling: Self-estimating the best-of-n sampling in early decoding. *arXiv preprint arXiv:2503.01422*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Xilin Wei, Xiaoran Liu, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Jiaqi Wang, Xipeng Qiu, and Dahua Lin. 2025. Sim-cot: Supervised implicit chain-of-thought. *arXiv preprint arXiv:2509.20317*.

Heming Xia, Chak Tou Leong, Wenjie Wang, Yongqi Li, and Wenjie Li. 2025. Tokenskip: Controllable chain-of-thought compression in llms. *arXiv preprint arXiv:2502.12067*.

Yige Xu, Xu Guo, Zhiwei Zeng, and Chunyan Miao. 2025. SoftCoT: Soft chain-of-thought for efficient reasoning with LLMs. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 23336–23351, Vienna, Austria. Association for Computational Linguistics.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822.

Eric Zelikman, Georges Harik, Yijia Shao, Varuna Jayasiri, Nick Haber, and Noah D Goodman. 2024. Quiet-star: Language models can teach themselves to think before speaking. *arXiv preprint arXiv:2403.09629*.

Zhuosheng Zhang, Aston Zhang, Mu Li, and Alex Smola. 2022. Automatic chain of thought prompting in large language models. In *The eleventh international conference on learning representations*.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, and 1 others. 2022. Least-to-most prompting enables complex reasoning in large language models. *arXiv preprint arXiv:2205.10625*.

Rui-Jie Zhu, Zixuan Wang, Kai Hua, Tianyu Zhang, Ziniu Li, Haoran Que, Boyi Wei, Zixin Wen, Fan Yin, He Xing, Lu Li, Jiajun Shi, Kaijing Ma, Shanda Li, Taylor Kergan, Andrew Smith, Xingwei Qu, Mude Hui, Bohong Wu, and 14 others. 2025. Scaling latent reasoning via looped language models. *Preprint*, arXiv:2510.25741.

A Experiment Details

We provide the full hyperparameter settings, training procedures, and additional analysis used in our experiments.

A.1 Implementation Details

Our framework, **Pre**^{2}, was implemented using PyTorch and the Litgpt framework. We selected the **Qwen2.5** series (Qwen et al., 2025) (0.5B and 1.5B) as our backbone models due to their strong mathematical reasoning capabilities.

Module Initialization   As described in Section 3, we freeze the original embedding layer of the backbone model to maintain a stable semantic space. The pre-thinking (f_{think}) and pre-answering (f_{ans}) modules are initialized as lightweight Transformer decoder blocks. Specifically, their hidden size and number of attention heads align with the backbone model to ensure compatibility with the frozen embeddings. For the latent vectors $\mathbf{z}_{think}^{(0)}$ and $\mathbf{z}_{ans}^{(0)}$, we use a Gaussian initialization with mean 0 and standard deviation 0.02.

Training Setup   All models were trained on a cluster of 8 NVIDIA A100 (80GB) GPUs using the Distributed Data Parallel (DDP) strategy. The training process utilized the AdamW optimizer. To stabilize the learning of the newly introduced latent modules alongside the backbone, we applied a linear warmup strategy followed by a cosine decay scheduler. For the baselines (Freeze-Baseline and Pause Token), we strictly followed the same training configurations (batch size, learning rate, and scheduler) to ensure a fair comparison. All evaluations are under multi-sampling evaluation (temperature = 0.1).

A.2   Hyperparameters

Table 6 lists the detailed hyperparameters used for the main experiments. We determined the loss weights λ_{think} and λ_{ans} through a preliminary grid search on a hold-out validation set from GSM8K-Aug. We found that setting the weights to 1.0 provided a balanced gradient flow between the alignment objectives ($\mathcal{L}_{think}, \mathcal{L}_{ans}$) and the autoregressive prediction objective ($\mathcal{L}_{LM}$).

B   Dataset Details

In this section, we provide detailed specifications of the datasets used in our experiments. We first present the statistical overview and then detail the specific characteristics and examples for each benchmark.

B.1   Dataset Overview and Metadata

Table 7 summarizes the general metadata for each dataset. All selected datasets focus on the *Math* domain and require *Arithmetic* reasoning capabilities. The answer types are consistently numerical values.

B.2   Dataset Statistics

Table 8 presents the statistical details regarding the length of inputs and reasoning paths. We report the average length of questions (tokens), the average length of the Chain-of-Thought (CoT) rationale, and the average number of reasoning steps.

B.3   Benchmark Detail

In this section, we describe the specific characteristics of each evaluation benchmark and the training data.

GSM8K-Aug (Deng et al., 2024)   GSM8K-Aug is an augmented dataset derived from GSM8K (Cobbe et al., 2021). It expands the original 8.5k training problems to roughly 385k examples through paraphrasing, numerical resampling, and synthetic generation using GPT-4. The dataset exhibits a distribution of reasoning steps where the majority of problems require two to four steps, accompanied by a long tail of instances requiring six or more steps. This balance of common and complex instances makes the dataset suitable for training models to generalize across various reasoning difficulty levels.

GSM-Hard (Gao et al., 2022)   GSM-Hard is a challenging variant of the GSM8K dataset constructed to test the ability of models to cope with harder numerical values. It retains the same problem statements as the original GSM8K but replaces many of the numbers with larger and less common numerical values, thereby increasing the difficulty of superficial arithmetic computation and reasoning. The dataset consists of approximately 1,319 examples.

MultiArith (Roy and Roth, 2015)   MultiArith is a dataset of multi-step arithmetic word problems designed to challenge systems in correctly sequencing multiple operations. It contains 600 problems collected from educational sources, each solvable by a single equation involving two or more of the four basic operations (addition, subtraction, multiplication, division). The problems require reasoning over multiple sentences to extract and combine numeric quantities, understand implied operations, and compute the result. It is widely used as a benchmark for evaluating arithmetic reasoning generalization, particularly for handling compositional and sequential numerical reasoning.

Hyperparameter	0.5b										1.5b		
	1-1	1-2	1-3	1-4	1-5	3-1	5-1	7-1	pt	sft	1-1	pt	sft
Pre-thinking Scope	1	2	3	4	5	5	5	5	1	-	1	1	-
Thinking Layers	1	1	1	1	1	3	5	7	-	-	1	-	-
Answering Layers	1	1	1	1	1	3	5	7	-	-	1	-	-
Epochs	50										11	-	-
Micro Batch Size	32										16	-	-
Max Gradient Norm	1.0												
Optimizer	AdamW												
Learning Rate	2.0e-4												
Min LR	6.0e-5												
LR Warmup Steps	2000												
Precision	bf16-mixed												
Weight Decay	0.01												
Global Batch Size	256												
β_1	0.9												
β_2	0.999												
λ_{think}	0.15												
λ_{ans}	0.15												

Table 6: Hyperparameters for all model variants. (For the format 1-1, the first 1 means we use 1-layer for Pre-thinking module and Pre-answering module and the latter 1 means Pre-thinking scope.)

Dataset	Properties			Size		License
	Domain	Reasoning	Ans. Type	Train	Test	
GSM8K-AUG	Math	Arithmetic	Number	385,620	1,319	MIT
GSM-Hard	Math	Arithmetic	Number	1,319	-	MIT
MultiArith	Math	Arithmetic	Number	420	180	CC BY 4.0
SVAMP	Math	Arithmetic	Number	700	300	MIT
ASDiv-AUG	Math	Arithmetic	Number	4,183	1,038	CC BY 4.0

Table 7: Overview of the datasets. We categorize the datasets by their domain properties and sample sizes.

Dataset	Avg. Q Len.	Avg. CoT Len.	Avg. Steps
GSM8K-AUG	61.3	36.2	3.26
GSM-Hard	65.8	154.2	-
MultiArith	41.3	-	-
SVAMP	41.5	15.0	1.28
ASDiv-AUG	36.6	12.3	1.23

Table 8: Detailed statistics of the **test split** used in our experiments. Lengths are calculated based on token count, and steps represent the reasoning depth of the gold solutions.

SVAMP (Patel et al., 2021) SVAMP (Simple Variations on Arithmetic Math Word Problems) is a benchmark dataset designed to test the robustness of math word problem solvers to superficial changes. It contains 1,000 elementary-level arithmetic word problems (grade 4 and below), each involving a single unknown and solvable by an arithmetic expression with no more than two operators. The problems are generated through controlled variations in wording, structure, and number values applied to existing datasets (such as MAWPS and ASDiv-A) to reduce artifacts and superficial cues.

ASDiv-AUG (Xu et al., 2025) ASDiv (Academia Sinica Diverse MWP Dataset) is a diverse corpus designed to evaluate the capability of solvers across a wide range of language patterns and problem types. The original dataset contains approximately 2,305 math word problems, each annotated with its problem type and grade level to indicate difficulty. ASDiv-AUG serves as an augmented or hardened version of this benchmark, typically constructed by filtering for higher-complexity problems or generating challenging variations to demand stronger mathematical reasoning capabilities from the models.

C Comparison with Latent COT Methods

Dataset	Example Question	Rationale / Steps	Answer
GSM8K-Aug	Out of 600 employees in a company, 30% got promoted while 10% received bonus. How many employees did not get either a promotion or a bonus?	["«600*30/100=180»", "«600*10/100=60»", "«180+60=240»", "«600-240=360»"]	360
GSM-Hard	Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with 4933828. She sells the remainder at the farmers' market daily for $2 per fresh duck egg. How much in dollars does she make every day at the farmers' market?	def solution():
"""Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder at the farmers' market daily for $2 per fresh duck egg. How much in dollars does she make every day at the farmers' market?"""
eggs_per_day = 16
eggs_eaten = 3
eggs_baked = 4933828
eggs_sold = eggs_per_day - eggs_eaten - eggs_baked
price_per_egg = 2
money_made = eggs_sold * price_per_egg
result = money_made
return result	-9,867,630
MultiArith	There are 64 students trying out for the school's trivia teams. If 36 of them didn't get picked for the team and the rest were put into 4 groups, how many students would be in each group?	-	7
SVAMP	There are 87 oranges and 290 bananas in Philip's collection. If the bananas are organized into 2 groups and oranges are organized into 93 groups How big is each group of bananas?	(290.0 / 2.0)	145
ASDiv-AUG	gino has 64 popsicle sticks . i have 100 popsicle sticks . what is the sum of our popsicle sticks ?	«64+100=164»	164

Table 9: Examples from the evaluation and training datasets. Each entry shows a representative question, the reasoning steps (Rationale) required to solve it, and the final numerical answer.

Model	GSM8K	GSM-Hard	MultiArith	ASDiv	SVAMP
llama-3.2-1b-baseline	52.91	12.05	95.00	79.19	52.66
llama-3.2-1b-freeze-baseline	52.53	11.75	94.17	79.09	51.00
llama-3.2-1b-pause token	53.14	12.43	94.83	79.28	53.33
llama-3.2-1b-1	54.43	12.66	95.17	79.67	54.33
llama-3.2-1b-coconut	45.30	9.90	90.10	–	48.80
llama-3.2-1b-icot	19.00	4.40	39.00	–	40.90

Table 10: Performance comparison of LLaMA-3.2-1B variants on five benchmarks.