A Distributional Perspective on Actor-Critic Framework

Abstract

Recent distributional reinforcement learning methods, despite their successes, still contain fundamental problems that can lead to inaccurate representations of value distributions, such as distributional instability, action type restriction, and biased approximation. In this paper, we present a novel distributional actor-critic framework, GMAC, to address such problems. Adopting a stochastic policy removes the first two problems, and the bias in the approximation is alleviated by minimizing the Cramér distance between the value distribution and its Bellman target distribution. In addition, GMAC improves data efficiency by generating the Bellman target distribution through the Sample-Replacement algorithm, denoted by SR(λ), which provides a distributional generalization of multi-step policy evaluation algorithms. We empirically show that our method captures the multimodality of value distributions and improves the performance of conventional actor-critic methods with low computational cost in both discrete and continuous action spaces, using Arcade Learning Environment (ALE) and PyBullet environment.

1 Introduction

The ability to learn complex representations via neural networks has enjoyed success in various applications of reinforcement learning (RL), such as pixel-based video gameplays (Mnih et al., 2015), the game of Go (Silver et al., 2016), robotics (Levine et al., 2016), and high dimensional controls like humanoid robots (Lillicrap et al., 2016; Schulman et al., 2015). Starting from the seminal work of Deep Q-Network (DQN) (Mnih et al., 2015), the advance in value prediction network, in particular, has been one of the main driving forces for the breakthrough.

Among the milestones of the advances in value function approximation, distributional reinforcement learning (DRL) further develops the scalar value function to a distributional representation. The distributional perspective offers various benefits by providing more information on the characteristics and the behavior of the value. One such benefit is the preservation of multimodality in value distributions, which leads to more stable learning of the value function (Bellemare et al., 2017a).

Despite the development, several issues remain, hindering DRL from becoming a robust framework. First, a theoretical instability exists in the control setting of value-based DRL methods (Bellemare et al., 2017a). Second, previous DRL algorithms are limited to a single type of action space, either discrete (Bellemare et al., 2017a; Dabney et al., 2018b;a) or continuous (Barth-Maron et al., 2018; Singh et al., 2020). Third, the Wasserstein distance that is commonly used in DRL does not guarantee unbiasedness in sample gradients, which may induce biased approximations (Bellemare et al., 2017b).

The instability issue is not present under the stochastic policy as shown by the convergence of distributional Bellman operator (Bellemare et al., 2017a). In addition, the general form of the stochastic policy gradient method does not assume a specific type of action space, e.g. discrete or continuous (Williams, 1988; 1992; Sutton et al., 1999). By replacing the Wasserstein distance with the Cramér distance, the sample gradient becomes unbiased. Combining these solutions, we arrive at a distributional actor-critic with Cramér distance as the value distribution loss.

However, many actor-critic methods suffer from data inefficiency and often include multi-step algorithms like the λ-return algorithm (Watkins, 1989) and off-policy updates, e.g. importance sampling. Here we address this problem by adapting multi-step off-policy updates to the distributional perspec-

(a) State of interest

(b) The evaluated value distributions

Figure 1: Modality of value distribution during the learning process of Breakout-v4. (a) An arrow is added in the inset to indicate the ball's direction of travel. The episode reaches a terminal state if the paddle misses the ball. (b) Probability density functions of the value distributions learned by each actor-critic when $\{0.2, 0.4, 1.2\}$M frames are collected. As the policy improves, the probability of losing a turn ($V = 0$) decreases, and the probability of earning scores ($V > 0$) increases. Note that the modality transition from $V = 0$ is clearly captured by the GMM + Cramér method.

tive, by defining a generalized form of the multi-step distributional Bellman targets. Furthermore, we introduce a novel value-distribution learning method which we call Sample-Replacement, denoted by SR(λ). We show that the expectation of the target distribution from SR(λ) is equivalent to the scalar λ-return. Additionally, we propose to parameterize the value distribution as a Gaussian mixture model (GMM). When combining GMM with the Cramér distance, we can derive an analytic solution and obtain unbiased sample gradients at a much lower computational cost compared to the method using Wasserstein distance. Altogether, we call our framework GMAC (Gaussian mixture actor-critic).

We present experimental results to demonstrate that this framework can successfully handle both discrete and continuous action spaces and learn a more accurate representation of value distributions, with a less computational cost.

2 RELATED WORKS

Bellemare et al. (2017a) has shown that the distributional Bellman operator derived from the distributional Bellman equation is a contractor in a maximal form of the Wasserstein distance. Based on this point, Bellemare et al. (2017a) proposed a categorical distributional model, C51, which is later discussed to be minimizing the Cramér distance in the projected distributional space (Rowland et al., 2018; Bellemare et al., 2019). Dabney et al. (2018b) proposed quantile regression-based models, QR-DQN, which parameterizes the distribution with a uniform mixture of Diracs and uses sample-based Huber quantile loss (Huber, 1964). Dabney et al. (2018a) later expand it further so that a full continuous quantile function can be learned through the implicit quantile network (IQN). Yang et al. (2019) then further improved the approximation of the distribution by adjusting the set of quantiles. Rowland et al. (2019) proposed expectile regression in place of quantile regression for learning categorical distribution to address the error in the Bellman target approximation. Outside of RL, Bellemare et al. (2017b) proposed to use Cramér distance in place of Wasserstein distance used in WGAN due to its unbiasedness in sample gradients (Arjovsky et al., 2017).

There have been many applications of the distributional perspective, which exploit the additional information from value distribution. Dearden et al. (1998) modeled parametric uncertainty and Morimura et al. (2010a;b) designed a risk-sensitive algorithm using a distributional perspective. Mavrin et al. (2019) utilized the idea of the uncertainty captured from the variance of value distribution with a decay factor to add an intrinsic reward to the objective of conventional greedy policy. Nikolov et al. (2019) has also utilized the distributional representation of the value function by using information-directed-sampling for better exploration of the value-based method. The sample-efficiency was addressed by combining multi-step off-policy algorithms like Retrace(λ) (Gruslys et al., 2017).

Just as C51 has been expanded to QR-DQN through quantile regression, Barth-Maron et al. (2018) expanded DDPG by training a distributional critic through quantile regression. Singh et al. (2020) has further expanded the work by using an implicit quantile network for the critic. Several works (Duan et al., 2020; Kuznetsov et al., 2020; Ma et al., 2020) have proposed a distributional version of the soft-actor-critic (SAC) framework to address the error from over-estimating the value. However, previous works concentrated on extending a specific actor-critic framework to the distributional setting. To the best of our knowledge, our work is the first to connect stochastic policy as a solution to the problems in value-based DRL. We believe that the findings from this paper can easily generalize to other actor-critic frameworks as well.

3 Distributional Reinforcement Learning

We consider a conventional RL setting, where an agent's interaction with its environment is described by a Markov Decision Process (MDP) $(\mathcal{X}, \mathcal{A}, R, P, \gamma)$, where $\mathcal{X}$ and $\mathcal{A}$ are state and action spaces, $R(x, a)$ is the stochastic reward function for a pair of state x and action a, $P(x'|x, a)$ is the transition probability of observing x' given the pair (x, a), and $\gamma \in (0,1)$ is a time discount factor. A policy $\pi(\cdot|x)$ maps a state $x \in \mathcal{X}$ to a probability distribution over actions $a \in \mathcal{A}$.

The objective of RL is to maximize the expected return, $\mathbb{E}[G_t]$ where $G_t = \sum_{t=0}^{\infty} \gamma^t R(x_t, a_t)$ is the sum of discounted rewards from state x_t given a policy π at time t. Then for any state x_t, the value V and state-action value Q under the given policy π can be defined as

$$V(x_t) = \mathbb{E}[G_t \mid X = x_t], \quad Q(x_t, a_t) = \mathbb{E}[G_t \mid X = x_t, A = a_t]. \tag{1}$$

A recursive relationship in the value in terms of the reward and the random transition is described by the Bellman equation (Bellman, 1957) given by

$$Q(x, a) = \mathbb{E}[R(x, a)] + \gamma \mathbb{E}_{a' \sim \pi, x' \sim P}[Q(x', a')], \tag{2}$$

where the first expectation is calculated over a given state-action pair (x, a) and the second expectation is taken over the next possible states $x' \sim P(\cdot|x, a)$ and actions $a' \sim \pi(\cdot|x)$.

DRL extends the Bellman equation to an analogous recursive equation, termed the distributional Bellman equation (Morimura et al., 2010a;b; Bellemare et al., 2017a), using a distribution of the possible sum of discounted rewards $Z(x, a)$:

$$Z(x, a) \overset{D}{=} R(x, a) + \gamma Z(x', a'), \tag{3}$$

where $\overset{D}{=}$ denotes having equal distributions and $Q(x, a) = \mathbb{E}[Z(x, a)]$. Then Z is learned through distributional Bellman operator $\mathcal{T}^\pi$ defined as

$$\mathcal{T}^\pi Z(x, a) :\overset{D}{=} R(x, a) + \gamma P^\pi Z(x, a) \tag{4}$$

where $P^\pi : \mathcal{Z} \to \mathcal{Z}$ is a state transition operator under policy π, $P^\pi Z(x, a) :\overset{D}{=} Z(x', a')$. Analogously, the distributional Bellman optimality operator $\mathcal{T}$ can be defined as

$$\mathcal{T} Z(x, a) :\overset{D}{=} R(x, a) + \gamma Z(x', \arg\max_{a'} \mathbb{E}_{x' \sim P}[Z(x', a')]). \tag{5}$$

The distributional Bellman operator has been proven to be a γ-contraction in a maximal form of Wasserstein distance (Bellemare et al., 2017a), which has a practical definition given by

$$d_p(U, V) = \left(\int_0^1 |F_U^{-1}(\omega) - F_V^{-1}(\omega)|^p d\omega \right)^{1/p}, \tag{6}$$

where U, V are random variables and F_U, F_V are their cumulative distribution functions (cdf).

However, unlike the distributional Bellman operator, the distributional Bellman optimality operator is not a contractor in any metric (Bellemare et al., 2017a). Thus, the distance $d_p(\mathcal{T} Z_1, \mathcal{T} Z_2)$ between some random variables Z_1, Z_2 may not converge to a unique solution. This issue has been discussed in Bellemare et al. (2017a), with an example of oscillating value distribution caused by a specific tie-breaker design of the *argmax* operator. One way to overcome this issue is learning value distributions under the stochastic policy and finding an optimal policy under principles of conservative policy iteration by Kakade & Langford (2002). See Appendix A for more discussion.

Algorithm 1: SR(λ)

Input: Trajectory of states and values $\{(x_1, Z_1), \ldots, (x_T, Z_T)\}$ for a given length T, discount factor γ, weight parameter λ

Output: Set of λ-returns $\{Z_1^{(\lambda)}, \ldots, Z_{T-1}^{(\lambda)}\}$

$\boldsymbol{X} \leftarrow$ Collect m samples $\{X_1, \ldots, X_m\}$ from Z_T

for $t = T - 1$ **to** 1 **do**

    $\boldsymbol{X} \leftarrow r_t + \gamma \boldsymbol{X}$ // `Bellman operator`

    $Z_t^{(\lambda)} \leftarrow \sum_{i=1}^{m} \delta_{X_i}$ // `empirical distribution using` m `Diracs`

    $\boldsymbol{X}' \leftarrow$ Collect m samples $\{X_1', \ldots, X_m'\}$ from Z_t

    for $i = 1$ **to** m **do**

        $X_i \leftarrow X_i'$ with probability $1 - \lambda$

    end

end

---

4 ALGORITHM

In this section, we incrementally develop the building blocks of our proposed method. First, we present an efficient distributional version of λ-return algorithm called Sample-Replacement, denoted by SR(λ). Then, we show that minimizing the energy distance, which is equivalent to a specific form of the Cramér distance, between Gaussian mixtures can be a better solution than using quantile regressions when working with distributional actor-critic and SR(λ).

4.1 SR(λ): SAMPLE-REPLACEMENT FOR λ-RETURN DISTRIBUTION

The actor-critic method is a specific case of temporal-difference (TD) learning method in which the value function, the critic, is learned through the TD error defined by the difference between the TD target given by n-step return, $G_t^{(n)} = \sum_{i=1}^{n} \gamma^{i-1} r_{t+i} + \gamma^n V(x_{t+n})$, and the current value estimate $V(x_t)$. A special case of TD method, called TD(λ) (Sutton, 1988), generates a weighted average of n-step returns for the TD target, also known as the λ-return,

$$G_t^{(\lambda)} = (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} G_t^{(n)}, \quad \lambda \in [0, 1], \tag{7}$$

to mitigate the variance and bias trade-off between Monte Carlo and the TD(0) return to enhance data efficiency. From an alternative perspective, equation 7 can be thought of as finding a TD target via taking the expectation of a random variable $\tilde{G}$ whose sample space is the set of all n-step returns, $\{G_t^{(0)}, \ldots, G_t^{(\infty)}\}$. Then the probability distribution of $\tilde{G}$ is given by

$$\Pr[\tilde{G} = G_t^{(n)}] = (1 - \lambda)\lambda^{n-1}. \tag{8}$$

Similar to $G_t^{(n)}$, we define n-step approximation of the value distribution as

$$Z_t^{(n)} \stackrel{D}{:=} \sum_{i=0}^{n-1} \gamma^i R(x_{t+i}, a_{t+i}) + \gamma^n \mathbb{E}_{a' \sim \pi}[Z(x_{t+n}, a')], \tag{9}$$

where $\mathbb{E}[Z_t^{(n)}] = G_t^{(n)}$. Then, a distributional analogy of equation 8 can be written as

$$\Pr[\tilde{Z} = Z_t^{(n)}] = (1 - \lambda)\lambda^{n-1} \tag{10}$$

where $\tilde{Z}$ is a random variable whose sample space is a set of all n-step approximations, $\{Z_t^{(0)}, \ldots, Z_t^{(\infty)}\}$. Unlike $\tilde{G}$, we cannot directly calculate the expectation over the possible realizations of $\tilde{Z}$. Instead, we redefine equation 10 in terms of cdfs:

$$\Pr[\tilde{F}_Z = F_{Z_t^{(n)}}] = (1 - \lambda)\lambda^{n-1}. \tag{11}$$

$F_{Z_t^{(n)}}$ denotes the cdf of the n-step return $Z_t^{(n)}$, and $\tilde{F}_Z$ is a random variable over possible cdfs of the Bellman target distribution. Note that the cdf of $\tilde{Z}$ has a different domain from $\tilde{F}_Z$.

Then, for any z, we can successfully rewrite equation 11 as a linear combination of $F_{Z_t^{(n)}}$

$$\mathbb{E}_n[\tilde{F}_Z] = (1-\lambda)\sum_{n=1}^{\infty}\lambda^{n-1}F_{Z_t^{(n)}}. \tag{12}$$

Let us define a random variable that has $\mathbb{E}[\tilde{F}_Z]$ as its cdf as $Z_t^{(\lambda)}$. Then we can show that the pdf of $Z_t^{(\lambda)}$ is a mixture of the pdfs of $Z_t^{(n)}$ and their expectations are identical to equation 7 (see Appendix B), meaning that its behavior in expectation is equal to that of the λ-return.

Both the cdf $F_{Z_t^{(\lambda)}}$ and the pdf $f_{Z_t^{(\lambda)}}$ of the λ-returns have simple forms, yet in practice evaluating each of them requires $O(n^2)$ for both space and time complexity for each sampled n-step trajectory, while the original TD(λ) only requires $O(n)$ for both space and time complexity. We address this issue by using an empirical approximation of the distribution of λ-return with fixed-size samples

$$f_{Z_t^{(\lambda)}} := \sum_{n=1}^{\infty}(1-\lambda)\lambda^{n-1}f_{Z_t^{(n)}} \approx \frac{1}{m}\sum_{i=1}^{m}\delta_{z_t^{(n)}}, \tag{13}$$

where for the last term n is sampled from the geometric distribution with $(1-\lambda)\lambda^{n-1}$ as its probability mass function, i.e. $\text{Geo}(1-\lambda)$. We note that, in practice, collecting infinite horizon trajectory is infeasible, and thus the general form of the distribution in equation 13 becomes a truncated sum (Cichosz, 1995; van Seijen et al., 2011):

$$\hat{f}_{Z_t^{(\lambda)}} = (1-\lambda)\sum_{n=1}^{N}\lambda^{n-1}f_{Z_t^{(n)}} + \lambda^N f_{Z_t^{(N)}}. \tag{14}$$

To obtain such samples, we start with m samples of the last value distribution in the sampled trajectory. Traversing through the sampled trajectory in a reversed order, we replace each sample with a new sample from the next state with a probability of $1-\lambda$. Then the obtained set $\boldsymbol{X}_m$ is equivalent to a set of samples from the empirical distribution of the λ-returns, $\hat{f}_{Z_t^{(\lambda)}}$. A more detailed description of the algorithm can be found in Algorithm 1.

For sample-based methods like the implicit quantile network, one can directly use this set $\boldsymbol{X}_m$ as the target samples. However, the Wasserstein distance minimized in the implicit quantile network cannot guarantee the unbiasedness of the sample gradient, meaning it may not be suitable for empirical distributions like equation 13. Thus, we propose to minimize the Cramér distance instead.

4.2 Cramér Distance

Let P and Q be probability distributions over $\mathbb{R}$. If we define the cdf of P, Q as F_P, F_Q respectively, the l_p family of divergence between P and Q is

$$l_p(P, Q) := \left(\int_{-\infty}^{\infty}|F_P(x) - F_Q(x)|^p dx\right)^{1/p}. \tag{15}$$

When $p = 2$, it is termed the Cramér distance. The distributional Bellman operator is a $|\gamma|^{1/p}$-contraction mapping in the Cramér metric space, whose proof can be found in Appendix C.

A notable characteristic of the Cramér distance is the unbiasedness of the sample gradient,

$$\mathbb{E}_{X\sim Q}\nabla_{\theta}l_2^2(\hat{P}_m, Q_{\theta}) = \nabla_{\theta}l_2^2(P, Q_{\theta}) \tag{16}$$

where $\boldsymbol{X}_m := \{X_1, ..., X_m\}$ are samples drawn from P, $\hat{P}_m := \frac{1}{m}\sum_{i=1}^{m}\delta_{X_i}$ is the empirical distribution, and Q_{θ} is a parametric approximation of a distribution. The unbiased sample gradient makes it suitable to use Cramér distance with stochastic gradient descent method and empirical distributions for updating the value distribution.

Székely (2002) showed that, in the univariate case, the squared Cramér distance is equivalent to one half of *energy distance* ($l_2^2(P, Q) = \frac{1}{2}\mathcal{E}(P, Q)$) defined as

$$\mathcal{E}(P, Q) := \mathcal{E}(U, V) = 2\mathbb{E}\|U - V\|_2 - \mathbb{E}\|U - U'\|_2 - \mathbb{E}\|V - V'\|_2, \tag{17}$$

where U, U' and V, V' are random variables that follow P, Q, respectively.

4.3 ENERGY DISTANCE BETWEEN GAUSSIAN MIXTURE MODELS

So far, we have described the components required to formulate a general setting of the suggested distributional extension to actor-critic methods. Here, we take one step further to enhance the approximation accuracy and computational efficiency by parameterizing the value distribution as a Gaussian mixture model. First, we start with few assumptions about the environment and setting: 1) the reward given a state-action pair $R(x, a)$ follows a single distribution with finite variance, 2) the transition probability P given the state-action pair also follows a fixed distribution with finite variance, and 3) the policy follows a distribution which can be approximated by Dirac mixtures, e.g. a multinomial or a Gaussian. Combining these assumptions, $f_Z(z|x)$, the marginal probability density of $Z(x, a)$ given the state x, can be approximated by a Gaussian mixture distribution:

$$f_Z(z|x) = \int_{\mathcal{A}} f_Z(z|x, a)\pi(a|x)da \approx \int_{\mathcal{A}} \sum_{i=1}^{K} f_Z(z|x, a)w_i\delta_{a_i}da$$

$$= \sum_{i=1}^{K} w_i f_Z(z|x, a_i) \approx \sum_{i=1}^{K} w_i\mathcal{N}(z; \mu_i, \sigma_i^2), \text{ where } \sum_{i=1}^{K} w_i = 1. \tag{18}$$

Since most environments satisfy the above conditions, it is natural to consider the Gaussian mixture model as a candidate for the family of value distributions.

If random variables X, Y follow the distributions P, Q parameterized as GMM, the energy distance has the following closed-form

$$\mathcal{E}(X, Y) = \delta(X, Y) - \delta(X, X') - \delta(Y, Y'),$$

$$\text{where } \delta(U, V) = 2\sum_{i,j} w_{ui}w_{vj}\mathbb{E}\left[|\mathcal{N}(z; \mu_{ui} - \mu_{vj}, \sigma_{ui}^2 + \sigma_{vj}^2)|\right]. \tag{19}$$

With Gaussian mixtures, the closed-form solution of the energy distance defined in equation 19 has a computational advantage over sample-based approximations like the Huber quantile loss. When using GMM, the analytic approximation of equation 13 can be derived as

$$\hat{f}_{Z_t^{(\lambda)}} \approx \sum_{n=1}^{\infty}(1 - \lambda)\lambda^{n-1}\sum_{k=1}^{K} w_{nk}\mathcal{N}(z; \mu_{nk}, \sigma_{nk}^2) \approx \frac{1}{m}\sum_{i=1}^{m}\mathcal{N}(z; \mu_{nk}, \sigma_{nk}^2), \tag{20}$$

where n is sampled from $\text{Geo}(1 - \lambda)$ and the index $k \in \{1, \dots, K\}$ is sampled proportional to the mixture weights $\{w_1, \dots, w_K\}$. This is equivalent to having a mixture of m Gaussians, thus we can simply perform sample replacement on the parameters (μ, σ^2), instead of realizations of the random variables as in equation 13. Then, the loss function described in equation 19 can easily be applied.

When bringing all the components together, we have a distributional actor-critic framework with SR(λ) that minimizes the Cramér distance between Gaussian mixture value distributions. We call this method GMAC.

5 EXPERIMENTS

In this section, we present experimental results for three different distributional versions of Proximal Policy Optimization (PPO) with SR(λ): IQAC (IQN + Huber quantile), IQAC-E (IQN + energy distance), and GMAC (GMM + energy distance), in the order of the progression of our suggested approach. The performance of the scalar version of PPO with value clipping (Schulman et al., 2016) is used as the baseline for comparison. Details about the loss function of each method can be found in Appendix D. For a fair comparison, we keep all common hyperparameters consistent across the algorithms except for the value heads and their respective hyperparameters (see Appendix E).

Figure 2: (a) An environment with two states and stochastic rewards with expected value of zero. (b) The probability density function (above) and the Cramér distance between the ground truth and the estimated distributions for IQ, IQE, and GM (below). (c) Learning curve of Montezuma's Revenge using modality information as intrinsic reward.

The results demonstrate three contributions of our proposed DRL framework: 1) the ability to correctly capture the multimodality of value distributions, 2) generalization to both discrete and continuous action spaces, and 3) significantly reduced computational cost.

Representing Multimodality As discussed throughout Section 4, we expect minimizing the Cramér distance to produce a more appropriate depiction of a distribution compared to minimizing the Wasserstein distance using Huber quantile regression. First, we demonstrate this with a simple value regression problem for an MDP of two sequential states, as shown in Figure 2 (a). The reward function r_i of each state S_i is stochastic, with r_1 from a uniform discrete distribution and r_2 from a normal distribution. Then the value distribution of S_1 should be a mixture of Gaussian, with symmetrical modes and expectation of zero (Figure 2 (b)). In this example, minimizing the Wasserstein distance (labeled as IQ) converges to a local minimum which does not correctly capture the locations of the modes. On the other hand, minimizing the Cramér distance converges to correct mode locations using both implicit quantile network and Gaussian mixture model, labeled as IQE and GM respectively in the figure. The comparison can be extended to more complex tasks such as the Atari games, of which a sample result is shown in Figure 1, and additional visualizations of the value distribution during the learning process from different games can be found in Appendix F.

So what can be achieved with correct modality? By capturing the correct modes of the distribution, an additional degree of freedom on top of the expected value can be accurately obtained, from which richer information can be derived to distinguish states by their value distributions. In particular, the extra information may be utilized as an intrinsic motivation in sparse-reward exploration tasks. To demonstrate, we compare using Cramér distance between value distributions as intrinsic reward to using TD error between scalar value estimates in a sparse reward environment of Montezuma's Revenge in Figure 2 (c), which shows a clear improvement in the performance.

Discrete and Continuous Action Spaces Experimental results from the ALE (Bellemare et al., 2013) and the PyBullet environments (Coumans & Bai, 2016–2020) show that our algorithm can be applied to both discrete and continuous action spaces. While GMAC shows overall improvement in 61 Atari games (Appendix F), we present the full learning curves of 3 Atari games in Figure 3 in which previous distributional methods have shown improvements over the scalar version. One can observe that the results from GMAC show the most significant improvement from the baseline.

All experiments are run over 5 random seeds with consistent hyperparameters. In Figure 3, a solid line represents an average of mean scores over 100 recent episodes and the shaded area represents the standard deviation over the seeds. For visual clarity, the plots are smoothed over 5M frames and 1.25M frames in Atari and PyBullet, respectively. Non-smoothed learning curves on more tasks and the final scores over the 61 ALE tasks can be found in Appendix F.

(a) Breakout   (b) Enduro   (c) Gopher

(d) Ant   (e) HalfCheetah   (f) Humanoid

Figure 3: Learning curves for 3 Atari games from ALE and 3 continuous control tasks from PyBullet.

Computational Cost Table 1 shows the number of parameters and the number of floating-point operations (FLOPs) required for a single inference and update step of each agent. We emphasize three points here. First, the implicit quantile network requires more parameters due to the intermediate embeddings of random quantiles. Second, the difference between the FLOPs for a single update in IQAC and IQAC-E indicates that the proposed energy distance requires less computation than the Huber quantile regression. Last, the results for GMAC show that using Gaussian Mixtures can greatly reduce the cost even to match the numbers of PPO while having improved performance.

Table 1: FLOP measurement results for a single process in Breakout-v4

Algorithm	Params (M)	FLOPs (G)	
		Inference	Update
PPO	0.44	1.73	5.19
IQAC	0.52	2.98	12.98
IQAC-E	0.52	2.98	8.98
GMAC	**0.44**	**1.73**	**5.27**

6 CONCLUSION

In this paper, we have developed the distributional perspective of the actor-critic framework which integrates the SR(λ) method, Cramér distance, and Gaussian mixture models for improved performance in both discrete and continuous action spaces at a lower computational cost. Furthermore, we show that our proposed method can capture the correct modality in the value distribution, while the extension of the conventional method with the stochastic policy fails to do so.

Capturing the correct modality of value distributions can improve the performance of various policy-based RL applications that exploit statistics from the value distribution. Such applications may include training risk-sensitive policies and learning control tasks with sparse rewards that require heavy exploration, where transient information from the value distribution can give benefit to the learning process. We leave further development of these ideas as future works.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. arXiv preprint arXiv:1701.07875, 2017.

Gabriel Barth-Maron, Matthew W. Hoffman, David Budden, Will Dabney, Dan Horgan, Dhruva TB, Alistair Muldal, Nicolas Heess, and Timothy Lillicrap. Distributed distributional deterministic policy gradients. In International Conference on Learning Representations (ICLR), 2018.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. Journal of Artificial Intelligence Research, 47:253–279, 2013.

Marc G. Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In Proceedings of the 34th International Conference on Machine Learning (ICML), 2017a.

Marc G. Bellemare, Ivo Danihelka, Will Dabney, Shakir Mohamed, Balaji Lakshminarayanan, Stephan Hoyer, and Rémi Munos. The cramer distance as a solution to biased wasserstein gradients, 2017b.

Marc G. Bellemare, Nicolas Le Roux, Pablo Samuel Castro, and Subhodeep Moitra. Distributional reinforcement learning with linear function approximation. In Artificial Intelligence and Statistics, volume 89 of Proceedings of Machine Learning Research, pp. 2203–2211, 2019.

Richard Bellman. Dynamic Programming. Dover Publications, 1957.

Dimitri P. Bertsekas and John N. Tsitsiklis. Neuro-Dynamic Programming. Athena Scientific, 1st edition, 1996.

P. Cichosz. Truncating temporal differences: On the efficient implementation of TD(λ) for reinforcement learning. Journal on Artificial Intelligence, 2:287–318, 1995.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. http://pybullet.org, 2016–2020.

Will Dabney, Georg Ostrovski, David Silver, and Rémi Munos. Implicit quantile networks for distributional reinforcement learning. In Proceedings of the 35th International Conference on Machine Learning (ICML), 2018a.

Will Dabney, Mark Rowland, Marc G. Bellemare, and Rémi Munos. Distributional reinforcement learning with quantile regression. In AAAI, pp. 2892–2901, 2018b.

Richard Dearden, Nir Friedman, and Stuart Russell. Bayesian q-learning. Proceedings of the fifteenth national/tenth conference on Artificial intelligence/Innovative applications of artificial intelligence, pp. 761 – 768, 1998.

Jingliang Duan, Yang Guan, Shengbo Eben Li, Yangang Ren, and Bo Cheng. Distributional soft actor-critic: Off-policy reinforcement learning for addressing value estimation errors. arXiv preprint arXiv:2001.02811, 2020.

Audrunas Gruslys, Will Dabney, Mohammad Gheshlaghi Azar, Bilal Piot, Marc Bellemare, and Remi Munos. The reactor: A fast and sample-efficient actor-critic agent for reinforcement learning. In International Conference on Learning Representation (ICLR), 2017.

Peter J. Huber. Robust estimation of a location parameter. The Annals of Mathematical Statistics, 35(1):73–101, 1964.

Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In Proceedings of the 19th International Conference on Machine Learning (ICML), 2002.

Arsenii Kuznetsov, Pavel Shvechikov, Alexander Grishin, and Dmitry P. Vetrov. Controlling overestimation bias with truncated mixture of continuous distributional quantile critics. arXiv preprint arXiv:2005.04269, 2020.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuo-motor policies. Journal of Machine Learning Research, 17:39:1–39:40, 2016.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In Proceedings of the 33rd International Conference on Learning Representations (ICML), 2016.

Xiaoteng Ma, Qiyuan Zhang, Li Xia, Zhengyuan Zhou, Jun Yang, and Qianchuan Zhao. Distributional soft actor critic for risk sensitive learning. arXiv preprint arXiv:2004.14547, 2020.

Borislav Mavrin, Hengshuai Yao, Linglong Kong, Kaiwen Wu, and Yaoliang Yu. Distributional reinforcement learning for efficient exploration. In Proceedings of the 36th International Conference on Machine Learning (ICML), 2019.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. Nature, 518(7540):529–533, 2015.

Tetsuro Morimura, Masashi Sugiyama, Hisashi Kashima, Hirotaka Hachiya, and Toshiyuki Tanaka. Parametric return density estimation for reinforcement learning. In UAI, pp. 368–375. AUAI Press, 2010a.

Tetsuro Morimura, Masashi Sugiyama, Hisashi Kashima, Hirotaka Hachiya, and Toshiyuki Tanaka. Nonparametric return distribution approximation for reinforcement learning. In Proceedings of the 27th International Conference on Machine Learning (ICML), 2010b.

Nikolay Nikolov, Johannes Kirschner, Felix Berkenkamp, and Andreas Krause. Information-directed exploration for deep reinforcement learning. In International Conference on Learning Representations (ICLR), 2019.

Martin L. Puterman. Markov Decision Processes: Discrete Stochastic Dynamic Programming. John Wiley & Sons, Inc., 1st edition, 1994.

Mark Rowland, Marc G. Bellemare, Will Dabney, Rémi Munos, and Yee Whye Teh. An analysis of categorical distributional reinforcement learning. In Amos J. Storkey and Fernando Pérez-Cruz (eds.), Artificial Intelligence and Statistics (AISTATS), volume 84 of Proceedings of Machine Learning Research, pp. 29–37. PMLR, 2018.

Mark Rowland, Robert Dadashi, Saurabh Kumar, Rémi Munos, Marc G. Bellemare, and Will Dabney. Statistics and samples in distributional reinforcement learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), Proceedings of the 36th International Conference on Machine Learning (ICML), 2019.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In Proceedings of the 32nd International Conference on Machine Learning (ICML), 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael I. Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In International Conference on Learning Representations (ICLR), 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. arXiv preprint arXiv:1707.06347, 2017.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. Nature, 529(7587):484–489, 2016.

Rahul Singh, Keuntaek Lee, and Yongxin Chen. Sample-based distributional policy gradient. arXiv preprint arXiv:2001.02652, 2020.

Richard S. Sutton. Learning to predict by the methods of temporal differences. Machine Learning, 3(1):9–44, aug 1988. ISSN 0885-6125. doi: 10.1023/A:1022633531479.

Richard S. Sutton and Andrew G. Barto. Introduction to Reinforcement Learning. MIT Press, Cambridge, MA, USA, 1st edition, 1998. ISBN 0262193981.

Richard S. Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In Proceedings of the 12th International Conference on Neural Information Processing Systems (NeurIPS), Cambridge, MA, USA, 1999.

Gabor Székely. E-statistics: The energy of statistical samples. 10 2002. doi: 10.13140/RG.2.1. 5063.9761.

Harm van Seijen, Shimon Whiteson, Hado van Hasselt, and Marco Wiering. Exploiting best-match equations for efficient reinforcement learning. Journal of Machine Learning Research, 12:2045–2094, 2011.

C. J. C. H. Watkins. Learning from Delayed Rewards. PhD thesis, King's College, Oxford, 1989.

R. J. Williams. Toward a theory of reinforcement-learning connectionist systems. Technical Report NU-CCS-88-3, College of Comp. Sci., Northeastern University, Boston, MA, 1988.

R. J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. Machine Learning, 8:229–256, 1992.

Derek Yang, Li Zhao, Zichuan Lin, Tao Qin, Jiang Bian, and Tie-Yan Liu. Fully parameterized quantile function for distributional reinforcement learning. In 33rd Annual Conference on Neural Information Processing Systems (NeurIPS), pp. 6190–6199, 2019.

Appendices

A   DISCUSSION ON THE CHOICE OF PROXIMAL POLICY OPTIMIZATION AS A BASELINE

A general learning process of RL can be described using policy iteration, which consists of two iterative phases: policy evaluation and policy improvement (Sutton & Barto, 1998). In policy iteration, the value function is assumed to be exact, meaning that given policy, the value function is learned until convergence for the entire state space, which results in a strong bound on the rate of convergence to the optimal value and policy (Puterman, 1994).

But the exact value method is often infeasible from resource limitation since it requires multiple sweeps over the entire state space. Therefore, in practice, the value function is approximated, i.e. it is not trained until convergence nor across the entire state space on each iteration. The approximate version of the exact value function method, also known as *asynchronous value iteration*, still converges to the unique optimal solution of the Bellman optimality operator. However, the Bellman optimality only describes the limit convergence, and thus the best we can practically consider is to measure the improvement on each update step.

Bertsekas & Tsitsiklis (1996) have shown that, when we approximate the value function V_π of some policy π with $\tilde{V}$, the lower bound of a greedy policy π' is given by

$$V_{\pi'}(x) \geq V_\pi(x) - \frac{2\gamma\varepsilon}{1-\gamma}, \tag{21}$$

where $\varepsilon = \max_x |\tilde{V}(x) - V_\pi(x)|$ is the L_∞ error of value approximation $\tilde{V}$. This means a greedy policy from an approximate value function guarantees that its exact value function will not degrade more than $\frac{2\gamma\varepsilon}{1-\gamma}$. However, there is no guarantee on the improvement, i.e. $V_{\pi'}(x) > V_\pi(x)$ (Kakade & Langford, 2002).

As a solution to this issue, Kakade & Langford (2002) have proposed a policy updating scheme named *conservative policy iteration*,

$$\pi_{new}(a|x) = (1 - \alpha)\pi_{old}(a|x) + \alpha\pi'(a|x), \tag{22}$$

which has an explicit lower bound on the improvement

$$\eta(\pi_{new}) \geq L_{\pi_{old}}(\pi_{new}) - \frac{2\epsilon\gamma}{(1-\gamma)^2}\alpha^2, \tag{23}$$

where $\epsilon = \max_x |\mathbb{E}_{\pi'}[A_\pi(x,a)]|$, $A_\pi(x,a) = Q(x,a) - V(x)$ is the advantage function, $\eta(\pi)$ denotes the expected sum of reward under the policy π,

$$\eta(\pi) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t R(x_t, a_t)\right], \tag{24}$$

and $L_{\pi_{old}}$ is the local approximation of η with the state visitation frequency under the old policy.

From the definition of distributional Bellman optimality operator in equation 5, one can see that the lower bound in equation 23 also holds when π' is greedy with respect to the expectation of the value distribution, i.e., $\mathbb{E}_{x'\sim P}[Z(x', a')]$. Thus the improvement of the distributional Bellman update is guaranteed in expectation under conservative policy iteration, and the value functions are guaranteed to converge in distribution to a fixed point by γ-contraction.

Schulman et al. (2015) takes this further, suggesting an algorithm called trust region policy optimization (TRPO), which extends conservative policy iteration to a general stochastic policy by replacing α with Kullback-Leibler (KL) divergence between two policies,

$$D_{KL}^{max}(\pi, \tilde{\pi}) = \max_x D_{KL}\left(\pi(\cdot|x)\|\tilde{\pi}(\cdot|x)\right). \tag{25}$$

Then, the newly formed objective is to maximize the following, which is a form of constraint optimization with penalty:

$$\hat{\mathbb{E}}_t\left[\frac{\pi(a_t|x_t)}{\tilde{\pi}(a_t|x_t)}\hat{A}_t - \beta D_{KL}(\pi(\cdot|x_t), \tilde{\pi}(\cdot|x_t))\right] = \hat{\mathbb{E}}_t\left[r_t(\pi)\hat{A}_t - \beta D_{KL}(\pi(\cdot|x_t), \tilde{\pi}(\cdot|x_t))\right]. \tag{26}$$

where $r(\pi)$ refers to the ratio $r(\pi) = \frac{\pi(a_t|x_t)}{\tilde{\pi}(a_t|x_t)}$. However, in practice, choosing a fixed penalty coefficient β is difficult and thus Schulman et al. (2015) uses hard constraint instead of the penalty.

$$\max_{\theta} \hat{\mathbb{E}}_t \left[r_t(\pi)\hat{A}_t \right] \tag{27}$$

$$\text{s.t. } D_{KL}(\pi(\cdot|x_t), \tilde{\pi}(\cdot|x_t)) \leq \delta \tag{28}$$

Schulman et al. (2017) simplifies the loss function even further in proximal policy optimization (PPO) by replacing KL divergence with ratio clipping between the old and the new policy with the following:

$$L^{CLIP} = \hat{\mathbb{E}}_t \left[\min\left(r_t(\pi)\hat{A}_t, \text{clip}(r_t(\pi), 1 - \epsilon, 1 + \epsilon)\hat{A}_t \right) \right]. \tag{29}$$

Thus, by using PPO as the baseline, we aim to optimize the value function via unique point convergence of distributional Bellman operator for a policy being approximately updated under the principle of conservative policy.

B   EXPECTATION VALUE OF $Z_t^{(\lambda)}$

Continuing from equation 12, let us define a random variable that has a cumulative distribution function of $\mathbb{E}[\tilde{F}_Z]$ as $Z_t^{(\lambda)}$. Then, its cumulative distribution function is given by

$$F_{Z_t^{(\lambda)}} = (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} F_{Z_t^{(n)}}. \tag{30}$$

Taking the derivative with respect to z on both sides, we get

$$f_{Z_t^{(\lambda)}} = (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} f_{Z_t^{(n)}}, \tag{31}$$

which describes the relationship between the probability density functions. Finding the expected value of both sides,

$$\begin{aligned}
\int_{\mathcal{Z}} f_{Z_t^{(\lambda)}} z dz &= \int_{\mathcal{Z}} (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} f_{Z_t^{(n)}} z dz \\
&= (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} \int_{\mathcal{Z}} f_{Z_t^{(n)}} z dz \\
&= (1 - \lambda) \sum_{n=1}^{\infty} \lambda^{n-1} G_t^{(n)} = G_t^{(\lambda)},
\end{aligned} \tag{32}$$

we show that $\mathbb{E}[Z_t^{(\lambda)}] = G_t^{(\lambda)}$.

C   DISTRIBUTIONAL BELLMAN OPERATOR AS A CONTRACTION IN CRAMÉR METRIC SPACE

The Cramér distance possesses the following characteristics (detailed derivation of each can be found in (Bellemare et al., 2017b)):

$$l_p(A + X, A + Y) \leq l_p(X, Y), \qquad\qquad l_p(cX, cY) \leq |c|^{1/p} l_p(X, Y). \tag{33}$$

Using the above characteristics, the Bellman operator in l_p divergence is

$$\begin{aligned}
l_p\left(\mathcal{T}^{\pi} Z_1(x, a), \mathcal{T}^{\pi} Z_2(x, a)\right) &= l_p(R(x, a) + \gamma P^{\pi} Z_1(x, a), R(x, a) + \gamma P^{\pi} Z_2(x, a)) \\
&\leq |\gamma|^{1/p} l_p(P^{\pi} Z_1(x, a), P^{\pi} Z_2(x, a)) \\
&\leq |\gamma|^{1/p} \sup_{x', a'} l_p(Z_1(x', a'), Z_2(x', a')).
\end{aligned} \tag{34}$$

Substituting the result into the definition of the maximal form of the Cramér distance yields

$$
\begin{aligned}
\bar{l}_p(\mathcal{T}^\pi Z_1, \mathcal{T}^\pi Z_2) &= \sup_{x,a} l_p(\mathcal{T} Z_1(x,a), \mathcal{T} Z_2(x,a)) \\
&\leq |\gamma|^{1/p} \sup_{x',a'} l_p(Z_1(x',a'), Z_2(x',a')) \\
&= |\gamma|^{1/p} \bar{l}_p(Z_1, Z_2).
\end{aligned} \tag{35}
$$

Thus the distributional Bellman operator is a $|\gamma|^{1/p}$-contraction mapping in the Cramér metric space. Similar characteristics as in equation 33 can be derived for the energy distance

$$
\mathcal{E}(A+X, A+Y) \leq \mathcal{E}(X,Y), \qquad\qquad \mathcal{E}(cX, cY) = c\mathcal{E}(X,Y), \tag{36}
$$

showing that the distributional Bellman operator is a γ-contractor in energy distance

$$
\mathcal{E}(\mathcal{T}^\pi Z_1, \mathcal{T}^\pi Z_2) \leq \gamma \mathcal{E}(Z_1, Z_2). \tag{37}
$$

D   LOSS FUNCTIONS

As in other policy gradient methods, our value distribution approximator models the distribution of the value, $V(x_t)$, not the state-action value $Q(x_t, a_t)$, and denote it as $Z_\theta(x_t)$ parametrized with θ, whose cumulative distribution function is defined as

$$
F_{Z_\theta(x_t)} = \sum_{a \in \mathcal{A}} \pi(a, x_t) F_{Z(x_t, a)}. \tag{38}
$$

Below, we provide the complete loss function of value distribution approximation for each of the cases used in experiments (Section 5).

D.1   IMPLICIT QUANTILE + WASSERSTEIN (IQAC)

For the value loss of IQAC, we follow the general flow of Huber quantile loss described in Dabney et al. (2018b). For two random samples $\tau, \tau' \sim U([0,1])$,

$$
\delta_t^{\tau, \tau'} = Z_t^{(\lambda)}(x_t, a_t; \tau') - Z_\theta(x_t; \tau) \tag{39}
$$

where $Z_t^{(\lambda)}$ is generated via SR(λ) and $Z(x; \tau) = F_Z^{-1}(\tau)$ is realization of $Z(X)$ given $X = x$ and τ. Then, the full loss function of value distribution is given by

$$
L_{Z_\theta} = \frac{1}{N'} \sum_{i=1}^{N} \sum_{j=1}^{N'} \rho_{\tau_i}^\kappa \left(\delta_t^{\tau_i, \tau'_j} \right) \tag{40}
$$

where N and N' are number of samples of τ, τ', respectively, and ρ is the Huber quantile loss

$$
\rho_\tau^\kappa(\delta_{ij}) = |\tau - \mathbb{I}\{\delta_{ij} < 0\}| \frac{L_\kappa(\delta_{ij})}{\kappa}, \quad \text{with} \tag{41}
$$

$$
L_\kappa(\delta_{ij}) = \begin{cases} \frac{1}{2}\delta_{ij}^2, & \text{if}|\delta_{ij}| \leq \kappa \\ \kappa(|\delta_{ij}| - \frac{1}{2}\kappa), & \text{otherwise.} \end{cases} \tag{42}
$$

D.2   IMPLICIT QUANTILE + ENERGY DISTANCE (IQAC-E)

Here, we replace the Huber quantile loss in equation 40 with sample-based approximation of energy distance defined in equation 19.

$$
L_{Z_\theta} = \frac{2}{NN'} \sum_{i=1}^{N} \sum_{j=1}^{N'} \left| \delta_t^{\tau_i, \tau'_j} \right| - \frac{1}{N^2} \sum_{i=1}^{N} \sum_{i'=1}^{N} \left| \delta_t^{\tau_i, \tau_{i'}} \right| - \frac{1}{N'^2} \sum_{j=1}^{N'} \sum_{j'=1}^{N'} \left| \delta_t^{\tau'_{j'}, \tau'_j} \right| \tag{43}
$$

D.3 GAUSSIAN MIXTURE + ENERGY DISTANCE (GMAC)

Unlike the two previous losses, which use samples at τ generated by the implicit quantile network $Z_\theta(x_t; \tau)$, here we discuss a case in which the distribution is k-component Gaussian mixture parameterized with (μ_k, σ_k^2, w_k).

Using the expectation of a folded normal distribution, we define δ between two Gaussian distributions as

$$\delta(\mu_i, \sigma_i^2, \mu_j, \sigma_j^2) = \sqrt{\frac{2}{\pi}} \sqrt{\sigma_i^2 + \sigma_j^2} \exp\left(-\frac{(\mu_i - \mu_j)^2}{2(\sigma_i^2 + \sigma_j^2)}\right) + (\mu_i - \mu_j)\left[1 - 2\Phi\left(\frac{(\mu_i - \mu_j)}{\sqrt{2}}\right)\right].$$

$$(44)$$

Let $Z_\theta(x)$ and $Z_t^{(\lambda)}$ be Gaussian mixtures parameterized with $(\mu_{\theta i}, \sigma_{\theta i}^2, w_{\theta i}), (\mu_{\lambda j}, \sigma_{\lambda j}^2, w_{\lambda j})$, respectively. Then, the loss function for the value head is given by

$$
\begin{aligned}
L_{Z_\theta} = {} & \frac{2}{NN'} \sum_{i=1}^{N} \sum_{j=1}^{N'} w_{\theta i} w_{\lambda j} \delta(\mu_{\theta i}, \sigma_{\theta i}^2, \mu_{\lambda j}, \sigma_{\lambda j}^2) \\
& - \frac{1}{N^2} \sum_{i=1}^{N} \sum_{i'=1}^{N} w_{\theta i} w_{\theta i'} \delta(\mu_{\theta i}, \sigma_{\theta i}^2, \mu_{\theta i'}, \sigma_{\theta i'}^2) \\
& - \frac{1}{N'^2} \sum_{j=1}^{N'} \sum_{j'=1}^{N'} w_{\lambda j} w_{\lambda j'} \delta(\mu_{\lambda j}, \sigma_{\lambda j}^2, \mu_{\lambda j'}, \sigma_{\lambda j'}^2).
\end{aligned}
$$

$$(45)$$

E   IMPLEMENTATION DETAILS

Table 2: Network architecture for GMAC on atari

Layer Type	Specifications		Filter size, stride
Input	84 x 84 x 4		
Conv1	20 x 20 x 32		8 x 8 x 32, 4
Conv2	9 x 9 x 64		4 x 4 x 64, 2
Conv3	7 x 7 x 32		3 x 3 x 32, 1
FC1	512		
Heads	Policy	Value	
(FC)	action dim	# of modes ($= 5$)	

Table 3: Parameter settings for training atari games

Parameter	PPO	IQAC	IQAC-E	GMAC
Learning rate			2.5e-4	
Optimizer			Adam	
Total frames			2e8	
Rollout steps			128	
Skip frame			4	
Environments			64	
Minibatch size			512	
Epoch			4	
γ			0.99	
λ			0.95	
Dirac samples	-		64	-
Mixtures	-	-	-	5

Table 4: Parameter settings for training PyBullet games

Parameter	PPO	IQAC	IQAC-E	GMAC
Learning rate			1e-4	
Optimizer			Adam	
Total env steps			5e-7	
Rollout steps			512	
Skip fram			1	
Environments			64	
Minibatch size			2048	
Epoch			10	
γ			0.99	
λ			0.95	
Dirac samples	-		64	-
Mixtures	-	-	-	5

F   MORE EXPERIMENTAL RESULTS

F.1   TWO STATE MDP

Recall the two-state MDP problem presented in Figure 2. This specific setup was designed to compare the regression performance of a network under bootstrap via Bellman operation, to test different reward types and multimodal value distribution regression. The test is performed across various optimizers, as different loss functions behave differently under specific components of the optimizer e.g. momentum. We show that the Cramér based loss function indeed converges to a much accurate value, almost zero energy distance, regardless of the network structure (implicit quantile or Gaussian mixture), while Huber quantile regression fails to capture clear locations of the modes. This phenomenon is more apparent when the modes are nearby, around a distance of 1. This is also applicable to most ALE tasks under the widely used setting, where the rewards are clipped to 1 and thus the possible modes are usually distanced in the same order as the two-state MDP example. The value distribution regression results across few Atari games, shown in the following subsection, also present similar intuition.

(a) SGD   (b) SGD+momentum   (c) SGD+nesterov

(d) RMSprop   (e) ADAM

Figure 4: All optimizers show Cramér based methods consistently achieving the best approximation of the true mode location.

F.2 VALUE DISTRIBUTION LEARNING IN ATARI GAMES

Figure 5: More value distributions of different tasks. All states are chosen such that the agent is in place of near-death or near positive score. Thus, when the policy is not fully trained, such as in a very early stage, the value distribution should include a notion of death indicated by a mode positioned at zero. In all games, IQN + Huber quantile (IQAC) fails to correctly capture a mode positioned at zero while the other two methods, IQN + energy distance (IQAC-E) and GMM + energy distance (GMAC) captures the mode in the early stage of policy improvement. Again, the visual representation is *maxpool* of the 4 frame stacks in the given state.

F.3 LEARNING CURVES

(a) BeamRider   (b) Breakout   (c) Enduro

(d) Gopher   (e) Gravitar   (f) Montezuma's Revenge

(g) Seaquest   (h) Venture

Figure 6: Raw learning curves for 8 selected atari games.

Figure 7: Raw learning curves for 5 selected PyBullet continuous control tasks.

Table 5: Average score over last 100 episodes in 200M frame collected for training 61 atari games. PPO and GMAC are trained using same single seed and hyperparameters. Random and Human scores are taken from Wang et al.

GAMES	RANDOM	HUMAN	PPO	GMAC
Adventure	NA	NA	**0.00**	**0.00**
AirRaid	NA	NA	10,205.75	**62,328.75**
Alien	227.80	**7,127.70**	2,918.60	3,687.10
Amidar	5.80	**1,719.50**	1,244.12	1,363.72
Assault	222.40	742.00	7,508.03	**10,281.73**
Asterix	210.00	8,503.30	13,367.00	**22,650.00**
Asteroids	719.10	**47,388.70**	2,088.10	2,597.50
Atlantis	12,850.00	29,028.10	3,073,796.00	**3,141,534.00**
BankHeist	14.20	753.10	1,263.80	**1,274.30**
BattleZone	2,360.00	**37,187.50**	18,540.00	32,490.00
BeamRider	363.90	**16,926.50**	5,913.84	8,718.72
Berzerk	123.70	2,630.40	1,748.10	**3,081.20**
Bowling	23.10	**160.70**	33.54	19.39
Boxing	0.10	12.10	96.79	**99.89**
Breakout	1.70	30.50	384.29	**462.68**
Carnival	NA	NA	5,079.20	**6,344.20**
Centipede	2,090.90	**12,017.00**	5,205.25	4,303.10
ChopperCommand	811.00	**7,387.90**	872.00	1,795.00
CrazyClimber	10,780.50	35,829.40	112,640.00	**125,143.00**
DemonAttack	152.10	1,971.00	50,590.65	**411,118.85**
DoubleDunk	-18.60	-16.40	-3.26	**-2.72**
ElevatorAction	NA	NA	10,449.00	**14,254.00**
Enduro	0.00	860.50	1,588.68	**2,092.65**
FishingDerby	-91.70	-38.70	37.01	**37.52**
Freeway	0.00	29.60	32.53	**32.84**
Frostbite	62.50	**4,334.70**	3,571.50	3,392.40
Gopher	257.60	2,412.50	8,199.80	**252,668.00**
Gravitar	173.00	**3,351.40**	1,151.50	2,401.00
Hero	1,027.00	30,826.40	37,725.55	**41,509.05**
IceHockey	-11.20	**0.90**	-1.90	0.34
Jamesbond	29.00	302.80	642.50	**1,512.00**
JourneyEscape	NA	NA	**-607.00**	-680.00
Kangaroo	52.00	3,035.00	1,742.00	**12,909.00**
Krull	1,598.00	2,665.50	**9,605.51**	9,127.63
KungFuMaster	258.50	22,736.50	26,846.00	**31,025.00**
MontezumaRevenge	0.00	**4,753.30**	0.00	0.00
MsPacman	307.30	**6,951.60**	3,674.20	3,884.40
NameThisGame	2,292.30	8,049.00	13,229.10	**14,031.30**
Phoenix	761.40	7,242.60	37,263.70	**42,664.00**
Pitfall	-229.40	**6,463.70**	0.00	-3.36
Pong	-20.70	14.60	20.87	**20.97**
Pooyan	NA	NA	4,018.95	**4,178.65**
PrivateEye	24.90	**69,571.30**	100.00	100.00
Qbert	163.90	13,455.00	**25,519.25**	23,176.25
Riverraid	1,338.50	17,118.00	15,983.00	**19,761.30**
RoadRunner	11.50	7,845.00	56,321.00	**68,272.00**
Robotank	2.20	11.90	23.45	**45.82**
Seaquest	68.40	**42,054.70**	1,832.00	1,838.40
Skiing	-17,098.10	**-4,336.90**	-7,958.81	-29,975.52
Solaris	1,236.30	**12,326.70**	2,452.80	2,579.20
SpaceInvaders	148.00	1,668.70	**2,544.10**	2,228.30
StarGunner	664.00	10,250.00	74,848.00	**104,188.00**
Tennis	-23.80	-8.30	-8.16	**-5.90**
TimePilot	3,568.00	5,229.20	12,157.00	**13,227.00**
Tutankham	11,40	167.60	206.32	**209.82**
UpNDown	533.40	11,693.20	**158,629.50**	129,243.70
Venture	0.00	1,187.50	0.00	**1,181.00**
VideoPinball	16,256.90	17,667.90	**279,504.81**	55,272.82
WizardOfWar	563.50	4,756.50	8,749.00	**11,388.00**
YarsRevenge	3,092.90	54,576.90	92,709.94	**103,895.05**
Zaxxon	32.50	9,173.00	13,336.00	**18,436.00**