Beyond Compliance: A Resistance-Informed Motivation Reasoning Framework for Challenging Psychological Client Simulation

Abstract

Psychological client simulators have emerged as a scalable solution for training and evaluating counselor trainees and psychological LLMs. Yet existing simulators exhibit unrealistic over-compliance, leaving counselors underprepared for the challenging behaviors common in real-world practice. To bridge this gap, we present ResistClient, a resistance-informed client simulator that authentically replicates challenging therapeutic dynamics through two core innovations. First, to reduce compliance bias, we draw on Client Resistance Theory to construct RPC, a large-scale resistance-oriented counseling dataset grounded in real therapeutic interactions, and apply supervised fine-tuning to shift the model's behavioral distribution toward realistic non-compliance. Second, to move beyond shallow response imitation, we propose Resistance-Informed Motivation Reasoning (RIMR), which introduces explicit motivation reasoning prior to response generation. RIMR jointly optimizes motivational authenticity and behavioral consistency via process-supervised reinforcement learning with expert-derived rewards, ensuring that simulated resistance reflects psychologically coherent internal processes rather than surface-level pattern matching. Extensive automatic and expert evaluations show that ResistClient substantially outperforms existing simulators in challenge fidelity, behavioral plausibility, and reasoning coherence. Moreover, ResistClient facilitates evaluation of psychological LLMs under challenging conditions, offering new optimization directions for mental health dialogue systems. Our code is available at https://anonymous.4open.science/r/ResistClient.

1 Introduction

Mental health disorders affect over one billion people worldwide, yet access to qualified counselors remains severely limited (Organization, 2025). Motivated by this gap, large language models (LLMs)

Figure 1: Existing LLM-based client simulators exhibit overly-compliance. ResistClient generates authentic resistant behaviors through motivation reasoning steps.

have increasingly been explored for counselor training (Steenstra et al., 2025), evaluation (Xiao et al., 2025a), and supervision (Lin et al., 2023), where client simulators play a central role by providing scalable, repeatable practice environments (Wang et al., 2024). However, existing psychological client simulators often exhibit over-compliant behaviors compared to real clients (Yang et al., 2025b), manifesting as unusually high openness (Kim et al., 2025a), excessive receptivity, and positive emotional stability(Wang et al., 2025b). This behavioral misalignment leads to the under-exploration of challenging therapeutic scenarios, ultimately constraining the effectiveness and reliability of both counselor trainees and psychological LLMs in realistic clinical contexts.

In real therapeutic practice, counselors often encounter "difficult" or "challenging" clients who exhibit resistance, broadly defined as the client's opposition to change during counseling (Otani, 1989). For example (Figure 1), when confronted about a lack of progress, real clients may justify themselves, redirect blame, or react with emotional push-

back rather than calmly accepting the feedback. Resistance is both inevitable and consequential: virtually all clients exhibit some degree of resistance during counseling, and extensive clinical literature shows that the effectiveness of resistance management critically shapes therapeutic processes and outcomes (Strean, 1985). Consequently, explicitly incorporating resistance mechanisms into client simulation is essential for narrowing the mismatch between idealized, compliant simulations and the challenging realities of clinical practice.

This paper aims to develop a resistance-informed client simulator that authentically replicates the challenging dynamics of real-world therapeutic interactions. Two key challenges arise:

1) **Unrealistic challenging behaviors induced by compliance bias**: Existing client simulators rely on profile-conditioned generation using pre-aligned LLMs (Wang et al., 2024), whose inherent compliant bias fundamentally conflicts with clinical non-compliance (Wang et al., 2025a). Lacking exposure to authentic resistance during pre-training, prompt-level adjustments (Yang et al., 2025b; Wang et al., 2025b; Kim et al., 2025a) yield only superficial difficulty, failing to replicate the challenging interactions and psychological depth characteristic of real-world therapeutic encounters.

2) **Shallow simulation induced by absence of internal mechanisms**: Psychological theory conceptualizes resistance as cognitive–affective processes (Otani, 1989; Chamberlain et al., 1984), not isolated behaviors. In contrast, existing client simulators focus on direct response generation without modeling the motivational mechanisms underlying these behaviors(Wang et al., 2024; Yang et al., 2025b; Wang et al., 2025b). Consequently, simulated reactions are reduced to surface-level response fitting, obscuring whether the behaviors reflect psychologically coherent processes or merely replicate superficial response patterns.

To address these limitations, we propose **Resist-Client** (Fig 1), a challenging client simulator that replicates therapeutic resistance through explicit motivation reasoning, instantiated via **Resistance-Informed Motivation Reasoning (RIMR)**, a two-stage training framework. (1) To reduce compliance bias, we draw on *Client Resistance Theory* (Chamberlain et al., 1984), a clinical taxonomy that categorizes resistance into distinct types with corresponding triggers and behavioral patterns. Based on this, we augment real counseling dialogues to construct the **RPC** dataset. Fine-tuning on RPC en-

ables the model to learn resistance expression patterns from real interactions, shifting its behavioral distribution toward realistic non-compliance. (2) To model the internal reasoning behind behaviors, we adopt the **5P case formulation model** (Johnstone and Dallos, 2013), a clinical framework that explains how clients' problems develop and persist, as a causally grounded client profile schema. Built on this, MRRL trains the model to generate explicit motivation reasoning before each response, simulating the cognitive reflection and situational awareness of real clients. To ensure reasoning quality, we introduce process-level rewards derived from expert feedback, encouraging motivation trajectories that are both psychologically plausible and behaviorally consistent with the final response. Together, RIMR enables ResistClient to balance challenge intensity with behavioral plausibility, supporting realistic and interpretable simulation of difficult therapeutic interactions.

Our contributions can be summarized as follows:

- To our best knowledge, this is the first work to systematically investigate and model challenging behaviors in client simulation. We propose ResistClient, shifting the prevailing paradigm from over-compliance to authentic challenging interactions.

- We introduce a novel training mechanism RIMR and RPC dataset. Moving beyond shallow responses imitation, our method generates psychologically coherent behaviors through motivation reasoning, enabling high-fidelity simulation across diverse client profiles.

- Extensive automatic and expert evaluations demonstrate ResistClient achieves state-of-the-art challenge intensity and behavioral plausibility. By replicating realistic challenging interactions, our work provides a critical new perspective for evaluating clinical reliability of psychological LLMs.

2 Related Work

Overly-Compliant Behavior in Client Simulation. Recent LLM-based client simulators enable profile-conditioned generation (Wang et al., 2024; Chen et al., 2025), and improve consistency through state tracking or memory mechanisms (Yang et al., 2025b; Wang et al., 2025b). Despite prompt-level strategies (e.g., information withholding (Kim et al., 2025a), low receptivity setting (Yang et al., 2025b), or emotion injection (Wang

et al., 2025b)), these simulators remain overly compliant due to the inherent compliant bias of pre-aligned LLMs (Lu et al., 2024; Xu et al., 2023). This limitation also affects counselor-side systems such as *MIRROR* (Kim et al., 2025b), which train VLMs to manage resistance using prompt-based virtual clients. More critically, psychological theory views challenging client behaviors as manifestations of underlying cognitive–affective resistance (Otani, 1989), rather than isolated behavior. ResistClient addresses these by grounding simulation in Client Resistance Theory (Chamberlain et al., 1984), jointly modeling resistant behaviors and their underlying motivation reasoning.

Building Paradigms for User Simulation. Existing user simulators fall into four paradigms: (1) *Profile-conditioned generation* (Wang et al., 2024) relies on intrinsic LLM reasoning but struggles with behavioral consistency. (2) *Agent-based user simulators* (Wang et al., 2025b; Yang et al., 2025b) employ agentic frameworks to improve consistency but lack utterance-level realism due to limited real-data training (Wang et al., 2025a). (3) *Conditional supervised fine-tuning* (Kong et al., 2024; Wang et al., 2025a) learns from real data but only achieves surface-level imitation. (4) *Non-collaborative user simulation* counteracts the inherent politeness of LLMs by modeling uncooperative behaviors (Zhang et al., 2024; Xiao et al., 2025b), but lacks specific expertise in the psychological field. Across all paradigms, existing methods prioritize observable behavior over latent reasoning, limiting their utility for psychological training.

Reasoning Reinforcement Learning for LLMs. Recent RRL frameworks (e.g., DeepSeek-R1 (Guo et al., 2025)) explicitly model intermediate reasoning steps, using RL to align reasoning quality with human preferences. Recent efforts extend this paradigm to psychological domains: Psyche-R1 (Dai et al., 2025) enhances empathy and expertise reasoning, while Mindora (Xiao et al., 2025a) imporves clinically aligned counselor reasoning. However, they target supporter-side cognition, leaving client-side motivation reasoning unexplored. We pioneer RRL for client simulation, adapting GRPO with process-level rewards to ensure step-wise validity and reasoning–response consistency.

3 ResistClient Construction

To address the over-compliance bias in existing client simulators, we propose RIMR, a two-stage training framework for psychologically grounded resistance behaviors. As illustrated in Figure 2, RIMR consists of: (1) Resistance-Informed Supervised Fine-Tuning on our RPC dataset, and (2) Motivation Reasoning Reinforcement Learning.

3.1 RPC Dataset Construction

Existing psychological conversation datasets exhibit compliant bias, where clients respond unrealistically compliantly even to potentially resistance-eliciting counselor utterances. To mitigate this bias, we construct the RPC dataset through (i) psychologically grounded profile conceptualization and (ii) resistance-informed conversation rewriting.

3.1.1 Profile Conceptualization from Psychological Conversation

Rather than relying on shallow personas, we adopt a clinically grounded Client Profile Schema inspired by the 5P case formulation model (Johnstone and Dallos, 2013), which links internal psychological states to observable reactions through: (1) Presenting Problems: primary concerns; (2) Predisposing Factors: historical vulnerabilities; (3) Precipitating Factors: recent triggers; (4) Perpetuating Factors: maintaining circumstances; and (5) Protective Factors: recovery resources. This causally-informed schema ensures client responses manifests as a psychologically grounded process rather than random occurrences.

To ensure the authenticity and diversity of simulated interactions, we build profiles utilizing ProPsyC, a large-scale repository of real-world psychological conversations (Hu et al., 2025). Following the schema above, we employ DeepSeek-V3.2 to extract structured 5P profiles with few-shot guidance from expert-annotated examples. Profile quality is evaluated along coverage and faithfulness dimensions following Wang et al. (2025a), with low-consistency samples filtered out (Appendix A).

3.1.2 Conversation Rewriting with Resistance Reactions

Although resistance is a well-documented phenomenon in counseling practice (Strean, 1985), it is underrepresented in open-source datasets due to ethical safeguards and curation procedures that favor supportive interactions. As a result, existing datasets provide limited supervision signals for modeling resistance behaviors. To address this gap, we propose a resistance-informed rewriting framework that augments counseling conversations

Figure 2: Overview of our proposed ResistClient with Resistance-informed Motivation Reasoning framework.

with psychologically grounded resistance reactions through theory-driven conversation rewriting.

Resistance Trigger Recognition. Drawing on structured interviews with counselors, we operationalize resistance triggers as counselor interventions that interact with clients' psychological vulnerabilities to elicit resistance, specifying triggering conditions for each resistance type (Table 5). Rather than relying on surface cues alone, trigger recognition is jointly conditioned on the local conversational context and high-risk factors encoded in the client's 5P profile.

Resistance-Informed Rewriting. Guided by Client Resistance Theory (Chamberlain et al., 1984), we define a comprehensive reaction taxonomy consisting of five resistance types (Controlling, Emotional, Defensive, Avoidant, and Compliant) and two cooperative types (Non-resistant and Facilitative) (Table 4). When a resistance trigger is detected, the subsequent client response is rewritten to reflect the most contextually appropriate reaction type. To prevent semantic drift, rewriting is strictly localized: only the immediate response and up to three subsequent turns are modified, with at most one primary resistance episode per session.

Annotation and Verification. Each client response is annotated with a reaction label and a brief reaction rationale explaining its underlying motivation. To balance scalability and validity, we adopt LLM-assisted annotation with expert verification. Four professional counselors verified trigger recognition

reliability, rewriting quality, and annotation consistency through an iterative refinement protocol. The final annotation prompt achieved Cohen's $\kappa = 0.72$ between model and counselor labels, with Fleiss' $\kappa = 0.77$ among counselors, indicating high inter-rater reliability. Rewriting quality was independently rated 2.47/3.00 by counselors, confirming realistic resistance expression (Appendix A.4).

Consequently, we construct the RPC from ProPsyC. As shown in Appendix A, the resulting dataset contains 1,849 counseling sessions, spanning 14 common counseling topics. Compared with the original corpus, RPC substantially improves the coverage and diversity of different resistance behaviors. Each session is paired with a validated 5P client profile and thoroughly annotated conversation, providing a high-quality foundation for training resistance-aware client simulators.

3.2 Conditional Supervised Fine-Tuning

To mitigate the over-compliance inherited from pre-training distributions, our model performs profile-conditioned supervised fine-tuning on RPC. This stage enables the model to learn structured mappings from client profiles and interaction contexts to specific behavioral outputs—including reaction types, responses, and underlying reasons—as conceptualized in Client Resistance Theory. Formally, given a client profile p, conversation history $\mathcal{H}_{t-1}$, and counselor utterance u_t^c, the model $\pi_{\theta_{\text{sft}}}$ is trained to predict a client response tuple u_t^a

(reaction type, response, reason). The supervised fine-tuning objective minimizes the following loss:

$$\mathcal{L}_{sft} = -\sum_{t=1}^{T} \log P(u_{t,j}^a | u_{t,<j}^a, u_t^c, \mathcal{H}_{t-1}, p) \quad (1)$$

where T is the total number of conversation turns and $u_{t,j}^a$ denotes the j-th token of the u_t^a.

3.3 Motivation Reasoning RL

Resistance is not a surface style but the downstream expression of an internal reasoning process: underlying psychological motivations shape how a client responds. Previous SFT corrects output-level compliance but cannot supervise this intermediate process—a model may produce resistance-like language while the underlying reasoning remains incoherent. We therefore propose MRRL, which uses process-supervised RL to align the motivation reasoning chain itself with human preferences, ensuring resistance is psychologically motivated rather than merely stylistically plausible.

3.3.1 Structured Motivation Reasoning Generation and Annotation

Motivation Reasoning Structure. We decompose the motivation reasoning process into three structured steps: 1) *Profile Reflection*, which reflects potential resistance tendencies by integrating stable cognitive and emotional factors from the 5P profile; 2) *Situation Awareness*, which analyzes conversation history and current counselor utterance to infer the client's momentary psychological state; and 3) *Reaction Decision*, specifying the reaction type and expected behavioral characteristics. This structured process mirrors human-like psychological reasoning, enabling both interpretability and improved realism.

Process-Supervised Reward Annotation. We evaluate the motivation reasoning process and client response generation from two perspectives. First, we assess the step-wise quality of each reasoning step and the final response to ensure psychological plausibility. Second, to optimize the model's ability to maintain coherence between the reaction type decided through reasoning and the final utterance, we evaluate reasoning-response consistency. Crucially, to align the reasoning process with human judgment, we employ expert-annotated process-level rewards on sampled outputs from the SFT model $\pi_{\theta_{\text{sft}}}$. Detailed annotation protocols are provided in the supplementary materials B.

3.3.2 RL with Consistency-aware Reward Reweighting

To jointly optimize reasoning validity and reasoning–response alignment, we introduce a consistency-aware reward reweighting strategy within GRPO. Based on the expert-annotated samples, we employ GRPO in an offline setting with process-supervised rewards. Specifically, for each context q (including client profile and conversation history), GRPO samples a group of outputs $\{o_i\}_{i=1}^{G}$ from the old policy $\pi_{\theta_{sft}}$ and optimizes the policy model by maximizing:

$$\mathcal{J}_{GRPO}(\theta) = \mathbb{E}\left[q \sim P(Q), \{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{sft}}}(O|q)\right]$$
$$\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}\left\{\min\left[\frac{\pi_\theta(o_{i,t}|q,o_{i,<t})}{\pi_{\theta_{\text{sft}}}(o_{i,t}|q,o_{i,<t})}\hat{A}_{i,t},\right.\right.$$
$$\left.\text{clip}\left(\frac{\pi_\theta(o_{i,t}|q,o_{i,<t})}{\pi_{\theta_{\text{sft}}}(o_{i,t}|q,o_{i,<t})}, 1-\epsilon, 1+\epsilon\right)\hat{A}_{i,t}\right]$$
$$\left. -\beta\mathbb{D}_{KL}(\pi_\theta||\pi_{ref})\right\}$$
$$(2)$$

where $o_{i,t}$ represents the t-th token in output o_i, ϵ is the clipping parameter, and β controls the KL divergence penalty. To enforce the alignment between reasoning and response, we utilize a Consistency-aware Reward Reweighting strategy. As shown in Figure 2, for each sampled output o_i, step-wise rewards $r_{i,1} - r_{i,4}$ supervise the four structured steps (Reflection, Awareness, Decision, Response). A consistency reward $r_{i,5}$ is applied to both the Decision and Response steps to enforce semantic alignment, yielding the reward vector:

$$\mathbf{R}_i = \{r_{i,1}^{\text{idx}(1)}, r_{i,2}^{\text{idx}(2)}, (r_{i,3} + r_{i,5})^{\text{idx}(3)},$$
$$(r_{i,4} + r_{i,5})^{\text{idx}(4)}\} \quad (3)$$

where $\text{idx}(k)$ denotes the end token of reasoning step k. Step-level rewards are normalized across the group and token-level advantages are computed as: $\hat{A}_{i,t} = \sum_{\text{idx}(k) \geq t} \tilde{r}_i^{\text{idx}(k)}$. As a result, the consistency signal influences both decision and response steps and is back-propagated to earlier reasoning tokens, coupling internal reasoning with its surface realization and encouraging coherent and psychologically consistent client behaviors.

Through this two-stage approach, ResistClient effectively captures complex client reaction patterns with high psychological reasoning fidelity. As shown in Figure 4, the simulator provides human-like feedback—both cooperative and resistant—conditioned on the appropriateness of coun-

Figure 3: Application of ResistClient in interactive counseling training.

seling strategies, enabling more realistic and informative interactive training for counselors and psychological LLMs.

4 Experiments

To rigorously evaluate ResistClient, we conduct comprehensive experiments to assess its effectiveness, realism, and practical utility in simulating challenging clients. In particular, we aim to answer the following research questions (RQs): **RQ1**: How effectively can ResistClient simulate client resistance behaviors compared with reasoning LLM baselines? **RQ2**: How do the two training stages contribute to overall simulation performance? **RQ3**: How realistic are the challenging behaviors generated by ResistClient compared with existing approaches? **RQ4**: What is the performance of current psychological LLMs when handling resistance in interactions with ResistClient?

4.1 Resistance Simulation Capability Analysis

4.1.1 Experiment Setup

Evaluation framework. This experiment evaluates models' ability to simulate client resistance under controlled counseling scenarios by reusing counselor turns from the z dataset. All baselines receive identical prompt descriptions of resistance and cooperative reactions to ensure fairness (Appendix C.1.1). We split RPC into disjoint profile sets using a 7:2:1 train/dev/test ratio. Client simulators are initialized with 100 profiles sampled from the held-out RPC test split. For reliability, we generate 3 sessions per profile.

Baselines. We compare ResistClient with representative reasoning-capable LLMs, including: 1) large-scale models: GPT-5.1 (OpenAI, 2025), DeepSeek-V3.2(Liu et al., 2025), Kimi-K2-thinking(Team et al., 2025), GLM-4.6(Zeng et al., 2025), 2) open-source small-scale models: Qwen3-8B(Yang et al., 2025a), DeepSeek-R1-8B(Guo et al., 2025), and 3) our ablations: Qwen3-8B-SFT.

Evaluation Metrics. Automated metrics evaluate the timing and accuracy of resistance generation, including Precision, Recall, F1, and Resistance Trigger Frequency (RTF). Human evaluation (0–3 scale) assesses psychological quality across: Resistance Fidelity (Fid.), measuring alignment between reasoning reaction type and generated response; Resistance Rationality (Rat.), evaluating contextual appropriateness of resistance; and Reasoning Quality (Qua.), assessing the coherence and plausibility of underlying motivation reasoning. All human scores are averaged over expert annotators (Appendix C.1.2).

Implementation Details. We use Qwen3-8B as the backbone model for its strong reasoning capability and instruction-following performance. The model is first fine-tuned on RPC using CSFT for 2 epochs on an NVIDIA A100 (80GB). Subsequently, we apply the MRRL stage for another 2 epochs to align the reasoning process with human clinical preferences. Inference uses $T = 0.7$, $top\_p = 0.8$, and $top\_k = 20$.

4.1.2 Performance Comparison (RQ1)

Table 1 shows that ResistClient consistently outperforms all baselines across automated evaluations, indicating improved resistance timing and simulation accuracy. Specifically, the superior precision indicates ResistClient avoids excessive or inappropriate resistance, while strong recall suggests effective conflict recognition without over-compliance. Smaller open-source models (e.g., Qwen3-8B) exhibit higher RTF but substantially lower Precision, indicating a tendency toward over-triggering resistance. Human evaluation confirms that ResistClient achieves the highest scores in fidelity, rationality, and reasoning quality, indicating that both its surface behaviors and internal motivation reasoning are psychologically grounded and contextually appropriate. A detailed case study illustrating these dynamics is provided in the Appendix D.

4.1.3 Ablation Study (RQ2)

To examine the contribution of each training stage, we compare ResistClient with two variants: 1) Qwen3-8B, with prompt-based conditioning only, and 2) Qwen3-8B-SFT, trained with CSFT on RPC. Figure 4 visualizes reaction-type alignment us-

Models	Automated Metrics(%)				Manual Metrics		
	Precision	Recall	F1 Score	RTF	Fid. (↑)	Rat. (↑)	Qua. (↑)
GPT-5.1	59.31	62.88	61.04	35.94	1.42	1.35	2.52
DeepSeek-V3.2	52.87	57.56	55.12	36.91	1.29	1.21	2.40
Kimi-K2-thinking	47.08	51.19	49.05	36.86	1.24	1.19	2.18
GLM-4.6	49.10	54.72	51.76	37.78	1.27	1.23	2.34
Qwen3-8B	36.52	48.54	41.68	45.06	1.10	1.04	1.88
DeepSeek-R1-8B	34.67	46.26	39.64	**45.23**	0.98	1.08	1.72
Qwen3-8B-SFT	63.54	73.90	68.33	39.43	1.46	1.41	2.39
ResistClient	**70.38**	**78.95**	**74.42**	38.03	**1.63**	**1.58**	**2.61**

Table 1: Resistance simulation performance of different models in psychological conversations.

Figure 4: Confusion matrices comparing reaction-type generation across variants. Rows represent ground-truth reaction types; columns represent generated types.

ing confusion matrices, where rows correspond to ground-truth reactions and columns to generated reactions. The diagonal mass increases from the prompt-only to SFT and to the full framework, indicating progressively improved simulation accuracy across reaction categories and confirming the contributions of both training stages. Notably, prompt-only model shows a strong bias toward cooperative reactions, consistent with the over-compliance tendency of pretrained LLMs. SFT effectively reduces this bias by learning diverse resistance patterns from RPC. MRRL further improves performance by explicitly modeling motivation reasoning and aligning with human preferences, particularly reducing confusion among resistance types. Furthermore, the competitive performance of the SFT-only variant against large closed-source models highlights the effectiveness of the RPC dataset.

4.2 Quality of Challenging Behaviors

4.2.1 Experimental Setup

Evaluation framework. This experiment evaluates the quality and realism of challenging client

behaviors in full counseling sessions, using classic *counselor–client–moderator* framework (Yang et al., 2025b). SoulChat2.0 (Xie et al., 2025) serves as the standardized counselor, while 50 client profiles are randomly sampled from the held-out RPC test split to initialize each simulator. A moderator determines session termination based on standardized clinical criteria (Appendix C.2.1).

Baselines. We reproduce representative challenging behaviors induction strategies: 1) Patient-ψ (Wang et al., 2024), profile-conditioned simulation without explicit challenging behavior modeling; 2) AnnaAgent (Wang et al., 2025b), which introduces challenges by injecting random emotion tags at each turn via an Emotion Perturber; and 3) Yang et al. (2025b), which introduces challenges through low-receptivity control in profile (Appendix C.2.1).

Evaluation Metrics. We evaluate behavior quality and challenge appropriateness using both automated and human evaluations. Automated metrics include: Client Cooperation Rate (CCR), the proportion of cooperative reactions (lower values indicate stronger challenge); Conversation Turns, the average session length (longer sessions suggest higher interaction difficulty); and Coherence (Coh.), semantic consistency measured by cosine similarity of frozen embeddings across turns. Human evaluations (0-3): Realism (Real.), assessing authenticity of the resistance-cooperation dynamics, and Consistency (Cons.), evaluating alignment between responses and profile (Appendix C.2.2).

4.2.2 Performance Comparison(RQ3)

As shown in Table 2, ResistClient achieves the best balance between challenge intensity (lowest CCR and longest average turns) and behavioral plausibility (highest Coh. and Real. scores). In contrast, Patient-Ψ remains coherent but exhibits excessive cooperation (87.94% CCR). AnnaAgent reduces cooperation (78.62% CCR) by injecting negative emotions, but context-agnostic random perturba-

Client Simulator	PATIENT-Ψ	Anna Agent	Yang et al. (2025b)	Resist Client
Automated Metrics				
CCR	87.94	78.62	62.33	**60.84**
Turns	11.24	12.65	16.67	**17.88**
Coh. (↑)	0.51	0.62	0.68	**0.73**
Manual Metrics				
Real. (↑)	1.87	1.95	2.01	**2.39**
Cons. (↑)	1.32	1.60	**1.83**	1.75

Table 2: Evaluation results of client simulators.

Models	Automated		Manual		
	RTF	Turns	Eff. (↑)	CDD (↓)	CPD (↑)
GPT-5.1	41.14	15.24	2.04	1.58	1.92
Gemini-3-flash	43.77	21.52	1.82	2.02	1.87
DeepSeek-V3.2	40.38	18.40	1.93	1.67	2.05
GLM-4.6	44.54	24.36	1.87	1.75	1.83
MeChat	51.93	43.22	1.61	2.08	1.68
MindChat	48.75	32.76	1.72	1.81	1.79
Psyche-R1	**38.32**	21.67	2.08	**1.48**	1.98
SoulChat2.0	39.15	17.88	**2.14**	1.56	**2.05**

Table 3: Performance of psychological LLMs when interacting with ResistClient.

tions compromise coherence and realism. Yang et al. further increase challenge via low-receptivity control (62.33% CCR) and maintain consistency through constraint mechanisms, but produce repetitive low-receptivity patterns lacking real resistance diversity, leading to low realism. Grounded in Client Resistance Theory, ResistClient systematically models diverse resistance patterns while ensuring profile- and situation-awareness through motivation reasoning, achieving superior challenge induction without sacrificing behavioral authenticity.

4.3 Performance of Psychological LLMs with ResistClient(RQ4)

4.3.1 Experimental Setup

Evaluation framework. We assess existing psychological LLMs' capability to handle client resistance when interacting with ResistClient. We employ the same *counselor-client-moderator* architecture as RQ3, and 100 client profiles are sampled from the held-out RPC test split to initialize ResistClient. (Appendix C.3.1)

Test Models. We evaluate representative psychological LLMs, including MeChat (Qiu et al., 2024), MindChat (Xin Yan, 2024), Psyche-R1 (Dai et al., 2025) and SoulChat2.0 (Xie et al., 2025). Motivated by evidence that many users seek mental health support from general-purpose LLMs (Guo et al., 2024), we additionally evaluate widely used general models, including GPT-5.1, Gemini-3-flash (Google Gemini Team, 2025), DeepSeek-V3.2, and GLM-4.6. (Appendix C.3.2)

Evaluation Metrics. Automated metrics include Resistance Trigger Frequency (RTF), measuring intervention-induced resistance frequency, and Dialogue Turns, measuring the average session length. Human evaluation (0–3) assesses counseling quality across: Strategy Effectiveness (Eff.), evaluating appropriateness of resistance-handling strategies; Counseling Drift Degree (CDD), quantifying deviations from effective therapeutic engagement during counseling; and Counseling Progress Degree (CPD), assessing therapeutic progress following resistance episodes. (Appendix C.3.3)

4.3.2 Overall Performance (RQ4)

Table 3 reveals that both general and specialized models frequently elicit client resistance (RTF 39-52%), underscoring the necessity for targeted resistance management training. Domain-specific models like SoulChat2.0 and Psyche-R1 achieve competitive performance with large-scale general-purpose models, suggesting that domain-specific fine-tuning can effectively maintain therapeutic focus. However, most models exhibit elevated drift and limited progress, indicating challenges in adapting intervention strategies under resistance. Overall, ResistClient provides a complementary evaluation lens for assessing the clinical robustness of psychological LLMs, exposing weaknesses in resistance handling that may not surface in standard benchmarks and providing insights into model behavior under complex therapeutic scenarios.

5 Conclusion

In this paper, we present ResistClient, a systematic study of challenging client behavior simulation for psychological conversations that addresses the over-compliance bias of existing simulators. We propose RIMR, a two-stage training framework that generates psychologically coherent behaviors through explicit motivation reasoning, and construct RPC, a large-scale dataset with validated client profiles and diverse resistance patterns. Extensive automatic and expert evaluations demonstrate that ResistClient achieves superior challenging fidelity and behavioral plausibility. Moreover, evaluations using ResistClient reveal substantial gaps in current psychological LLMs in handling client resistance, highlighting the importance of resistance-aware simulation for training and evaluation.

Limitations

Despite the effectiveness of ResistClient in simulating challenging client behaviors, this work has several limitations. First, our study is grounded in a Chinese counseling conversation dataset constructed with the assistance of professional counselors in China. While this ensures strong clinical grounding within the Chinese cultural context, clients from different linguistic and cultural backgrounds may exhibit distinct resistance manifestations and type distributions, limiting direct application in cross-cultural counseling scenarios. Second, due to ethical constraints common in psychological research, our evaluation relies on judgments from a small group of expert counselors. Although their professional expertise supports the reliability of the assessment, the limited number of evaluators may restrict the diversity of perspectives and introduce bias. Third, this work focuses exclusively on client-side simulation. However, effective counseling also depends on counselors' abilities to recognize and manage client resistance, which remains outside the scope of the current study. Future work will extend our framework to cross-cultural contexts, deploy it as a scalable virtual training environment for broader counselor populations, and develop counselor agents capable of managing resistance effectively.

Ethical Considerations

This study was conducted with careful consideration of ethical issues throughout data construction, annotation, and evaluation. All datasets used in this work are either publicly available or derived from existing resources with explicit permission. In particular, the RPC dataset does not contain personally identifiable information, and all dialogues were anonymized prior to use to ensure privacy and confidentiality. The rewritten and simulated conversations are fully synthetic and do not correspond to real individuals or real counseling cases. Our goal is to study resistance-aware interaction behaviors in a controlled research setting rather than to model or predict any specific person's psychological state. We acknowledge the potential risks of misuse, such as deploying psychological dialogue systems without appropriate clinical oversight. To mitigate these risks, we emphasize that our system is intended solely as a research and educational tool, and should not be used for diagnosis, treatment, or real-world mental health intervention.

All tasks requiring human involvement, including data annotation, label verification, and experimental evaluation, were conducted by four certified counselors with relevant clinical experience. Their annotations were treated as the ground truth for resistance types and reaction labels throughout the study. Each counselor was compensated at an hourly rate of \$14.30, exceeding the current U.S. federal minimum wage of \$7.25 per hour. Throughout the entire research process, we strictly adhered to established ethical guidelines for NLP research involving sensitive psychological content and professional human expertise. This study does not involve real patients, human subjects, or identifiable personal data, and all interactions are conducted with simulated clients and models. Therefore, formal approval from Ethics Review Board was not required.

References

Patricia Chamberlain, Gerald Patterson, John Reid, Kathryn Kavanagh, and Marion Forgatch. 1984. Observation of client resistance. *Behavior therapy*, 15(2):144–155.

Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2023. Bge m3-embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. *Preprint*, arXiv:2309.07597.

Zhuang Chen, Yaru Cao, Guanqun Bi, Jincenzi Wu, Jinfeng Zhou, Xiyao Xiao, Si Chen, Hongning Wang, and Minlie Huang. 2025. Socialsim: Towards socialized simulation of emotional support conversation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 1274–1282.

Chongyuan Dai, Jinpeng Hu, Hongchang Shi, Zhuo Li, Xun Yang, and Meng Wang. 2025. Psyche-r1: Towards reliable psychological llms through unified empathy, expertise, and reasoning. *arXiv preprint arXiv:2508.10848*.

Google Gemini Team. 2025. Gemini 3 flash. https://deepmind.google/technologies/gemini/.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Zhijun Guo, Alvina Lai, Johan H Thygesen, Joseph Farrington, Thomas Keen, Kezhi Li, and 1 others. 2024. Large language models for mental health applications: systematic review. *JMIR mental health*, 11(1):e57400.

Yuxin Hu, Danni Liu, Bo Liu, Yida Chen, Jiuxin Cao, and Yan Liu. 2025. Psyadvisor: A plug-and-play strategy advice planner with proactive questioning in psychological conversations. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12205–12229.

Lucy Johnstone and Rudi Dallos. 2013. *Formulation in Psychology and Psychotherapy: Making sense of people's problems*. Routledge.

Minju Kim, Dongje Yoo, Yeonjun Hwang, Minseok Kang, Namyoung Kim, Minju Gwak, Beong-woo Kwak, Hyungjoo Chae, Harim Kim, Yunjoong Lee, and 1 others. 2025a. Can you share your story? modeling clients' metacognition and openness for llm therapist evaluation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 25943–25962.

Subin Kim, Hoonrae Kim, Jihyun Lee, Yejin Jeon, and Gary Lee. 2025b. Mirror: Multimodal cognitive reframing therapy for rolling with resistance. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 14851–14880.

Chuyi Kong, Yaxin Fan, Xiang Wan, Feng Jiang, and Benyou Wang. 2024. Platolm: Teaching llms in multi-round dialogue via a user simulator. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7841–7863.

Baihan Lin, Guillermo Cecchi, and Djallel Bouneffouf. 2023. Supervisorbot: Nlp-annotated real-time recommendations of psychotherapy treatment strategies with deep reinforcement learning. In *International Joint Conference on Artificial Intelligence*.

Aixin Liu, Aoxue Mei, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, and 1 others. 2025. Deepseek-v3.2: Pushing the frontier of open large language models. *arXiv preprint arXiv:2512.02556*.

Keming Lu, Bowen Yu, Chang Zhou, and Jingren Zhou. 2024. Large language models are superpositions of all characters: Attaining arbitrary role-play via self-alignment. *arXiv preprint arXiv:2401.12474*.

OpenAI. 2025. Gpt-5.1. https://openai.com/index/gpt-5-1/. Accessed: 2025-11-12.

World Health Organization. 2025. *World mental health today: latest data*. World Health Organization.

Akira Otani. 1989. Client resistance in counseling: Its theoretical rationale and taxonomic classification. *Journal of Counseling & Development*, 67(8):458–461.

Huachuan Qiu, Hongliang He, Shuai Zhang, Anqi Li, and Zhenzhong Lan. 2024. Smile: Single-turn to multi-turn inclusive language expansion via chatgpt for mental health support. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 615–636.

Ian Steenstra, Farnaz Nouraei, and Timothy Bickmore. 2025. Scaffolding empathy: Training counselors with simulated patients and utterance-level performance visualizations. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–22.

Herbert S Strean. 1985. *Resolving resistances in psychotherapy*. Brunner/Mazel.

Kimi Team, Yifan Bai, Yiping Bao, Guanduo Chen, Jiahao Chen, Ningxin Chen, Ruijue Chen, Yanru Chen, Yuankun Chen, Yutian Chen, and 1 others. 2025. Kimi k2: Open agentic intelligence. *arXiv preprint arXiv:2507.20534*.

Kuang Wang, Xianfei Li, Shenghao Yang, Li Zhou, Feng Jiang, and Haizhou Li. 2025a. Know you first and be you better: Modeling human-like user simulators via implicit profiles. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 21082–21107. Association for Computational Linguistics.

Ming Wang, Peidong Wang, Lin Wu, Xiaocui Yang, Daling Wang, Shi Feng, Yuxin Chen, Bixuan Wang, and Yifei Zhang. 2025b. Annaagent: Dynamic evolution agent system with multi-session memory for realistic seeker simulation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 23221–23235.

Ruiyi Wang, Stephanie Milani, Jamie Chiu, Jiayin Zhi, Shaun Eack, Travis Labrum, Samuel Murphy, Nev Jones, Kate Hardy, Hong Shen, and 1 others. 2024. Patient-ψ: Using large language models to simulate patients for training mental health professionals. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 12772–12797.

Mengxi Xiao, Kailai Yang, Pengde Zhao, Enze Zhang, Ziyan Kuang, Zhiwei Liu, Weiguang Han, Shu Liao, Lianting Huang, Jinpeng Hu, and 1 others. 2025a. Mentrasuite: Post-training large language models for mental health reasoning and assessment. *arXiv preprint arXiv:2512.09636*.

Ruiyu Xiao, Lei Wu, Yuanxing Liu, Weinan Zhang, and Ting Liu. 2025b. Stimulate the critical thinking of llms via debiasing discussion. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 11490–11503.

Haojie Xie, Yirong Chen, Xiaofen Xing, Jingkai Lin, and Xiangmin Xu. 2025. Psydt: Using llms to construct the digital twin of psychological counselor with personalized counseling style for psychological counseling. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1081–1115.

Dong Xue* Xin Yan. 2024. Mindchat: Psychological large language model. https://github.com/X-D-Lab/MindChat.

Canwen Xu, Daya Guo, Nan Duan, and Julian McAuley. 2023. Baize: An open-source chat model with parameter-efficient tuning on self-chat data. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6268–6278.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025a. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Yizhe Yang, Palakorn Achananuparp, He-Yan Huang, Jing Jiang, Nicholas Gabriel Lim, Cameron Tan Shi Ern, Phey Ling Kit, Jenny Giam Xiuhui, John Pinto, and Ee-peng Lim. 2025b. Consistent client simulation for motivational interviewing-based counseling. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 20959–20998.

Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, and 1 others. 2025. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models. *arXiv preprint arXiv:2508.06471*.

Tong Zhang, Chen Huang, Yang Deng, Hongru Liang, Jia Liu, Zujie Wen, Wenqiang Lei, and Tat-Seng Chua. 2024. Strength lies in differences! improving strategy planning for non-collaborative dialogues via diversified user simulation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 424–444.

A Details of Dataset Construction with Resistance Annotations

This appendix describes the detailed procedure for constructing a psychological conversation dataset with fine-grained client resistance labels(our RPC dataset). Starting from the ProPsyC dataset(Hu et al., 2025), we selectively rewrote client utterances in sessions likely to elicit resistance and subsequently annotated all client turns with resistance categories.

A.1 Data Selection

To obtain a thematically balanced corpus, we re-screened the original ProPsyC dataset according to its four major clinical themes (depression and emotional disorders, interpersonal relationships, academic/career stress, and general growth issues). Sessions were sampled to achieve approximately equal representation across themes. This process yielded 1,849 complete counseling sessions. The final theme distribution is shown in Figure 5.

Figure 5: Distribution of different topics in client profiles

A.2 Extraction of Client 5P Profiles

For each of the 1,849 selected sessions, we used DeepSeek-v3.2 to generate a structured 5P case conceptualization profile that captures the client's psychological background. The model was prompted with the full conversation and instructed to summarize the following 5 dimensions:

- *Presenting Problems*: The client's most immediate and subjectively distressing concerns—the surface-level issues brought to therapy.

- *Predisposing Factors*: Long-standing historical, biological, psychological, or social vulnerabilities that increase the likelihood of the current difficulties.

- *Precipitating Factors*: Recent events or stressors that directly triggered or exacerbated the current problems.

- *Perpetuating Factors*: Ongoing cognitive, behavioral, interpersonal, or environmental patterns that maintain the problems and hinder change.

- *Protective Factors*: Internal strengths, external resources, and support systems that help the client cope and foster resilience.

The validation process for the 5P Profile can be found in Appendix A.4. These 5P profiles were later injected into the LLM as persona prompts to ensure psychologically consistent client responses during rewriting. A 5p profile example from the dataset is shown in Figure 7.

A.3 Resistance-Guided Conversation Rewriting and Annotation

A.3.1 Resistance Category Definitions

We adopted 7 mutually exclusive client response categories (5 resistant reactions and 2 cooperative reactions), defined in collaboration with licensed psychotherapists (see Table 4).

A.3.2 Automated Rewriting Procedure

The rewriting process was performed by DeepSeek-v3.2, which was provided with (a) the original session, (b) the client's 5P profile, and (c) the resistance category definitions. For each counselor turn, the model first judged whether the turn constituted a plausible resistance trigger. Based on the counselors' advice, we clarify the triggering conditions for each type of resistance(shown in Table 5). When a trigger was identified, DeepSeek-v3.2 not only rewrote the immediate client response to express one of the five resistance types (chosen as most psychologically plausible given the context and 5P profile), but also adaptively revised the subsequent 2-3 conversational turns to maintain contextual coherence and psychological realism. Each rewritten resistance response was accompanied by a brief motivation statement explaining the underlying psychological mechanism. Conversations deemed unsuitable for resistance elicitation were discarded. An illustrative example of this rewritten dataset is presented in Figure 8. This process ultimately produced 1,761 resistance-containing conversations, constituting our RPC dataset. The remaining 88 sessions contain no resistance triggers; in these cases, client responses remain cooperative, suggesting that resistance arises only when contextually justified. Professional counselors have verified the annotation results. For more details, please see Appendix A.4.

A.3.3 Final Label Distribution

The distribution of resistance categories in both the original dataset and the rewritten RPC dataset is presented in Figure 6. Resistance behaviors in the original dataset are relatively sparse, with instance counts ranging from 31 (Controlling) to 264 (Compliant). Our rewriting framework substantially expands coverage across all five categories, yielding 1,277 Compliant, 975 Defensive, 624 Emotional, 363 Avoidant, and 116 Controlling resistance instances in the final RPC dataset, corresponding to an overall amplification of approximately 4 times, while preserving the relative distributional structure

of the original data. This results in a more balanced and densely populated training set compared to the original data.

This pattern aligns with clinical observations that overt confrontation (Controlling) is relatively rare in Chinese counseling contexts, whereas indirect and self-protective forms (Compliant and Defensive) predominate. Specifically, Compliant Resistance is most frequent, reflecting a tendency for clients to maintain surface-level cooperation and politeness while avoiding deeper engagement, which aligns with cultural values emphasizing harmony and respect for authority. Defensive and Emotional Resistance occur relatively often, as clients may protect their self-image or react emotionally when feeling judged or emotionally challenged, though strong emotional expression is often moderated. Avoidant Resistance is less common, as clients tend to remain within the conversational frame rather than openly shifting topics. Controlling Resistance appears least frequently, likely because overtly assertive or confrontational behaviors conflict with culturally valued norms of deference and relational caution.

Figure 6: Distribution of resistance types in the original dataset and the RPC dataset across five resistance categories

Overall, this distribution reflects a tendency toward indirect, relationally cautious forms of resistance in Chinese psychological counseling, where maintaining harmony often takes precedence over direct confrontation. This pattern supports the ecological validity of the dataset and highlights the importance of culturally informed interpretations of client resistance.

A.4 Data Annotation Verification

To ensure the reliability of all annotations involving LLMs, we conducted systematic human validation across all stages of the annotation process. Four

Table 4: Classification and Interpretation of Dataset Labels

Reaction Category	Label Type	Behavioral Description	Motivational Interpretation
Resistant Reactions	Controlling Resistance	- Dominates the conversation /interrupts
- Rejects guidance on conversation direction
- Clings to own views, disregards input	Seeks to maintain control to avoid being influenced; insists on own perspective and resists change.
	Emotional Resistance	- Expresses anger or aggressive speech
- Displays sadness/emotional breakdown
- Shows despair or overgeneralized negative emotions	Externalizes emotions or projects blame to avoid confronting deeper psychological pain.
	Defensive Resistance	- Questions the practitioner's expertise or competence
- Challenges the consultation method or process
- Responds with sarcasm or exaggeration	Projects anxiety onto the practitioner to prevent internal conflicts from being triggered.
	Avoidant Resistance	- Changes or introduces unrelated topics
- Provides excessive or redundant information
- Evades direct questions	Reflects cognitive avoidance; an unconscious effort to prevent core conflicts from being addressed.
	Compliant Resistance	- Gives vague or perfunctory responses
- Shows superficial cooperation without genuine engagement
- Downplays emotions with brevity	Superficial compliance with avoidance of substantive issues; does not contribute to therapeutic progress.
Cooperative Reactions	Non-resistant Reaction	- Neutral, cooperative, shows no obvious opposition, but does not take initiative	Indicates a satisfactory interactive state with a degree of openness, but not actively driving the process.
	Facilitative Reaction	- Expresses agreement, actively listens, and shows willingness to explore issues in depth	Reflects sufficient safety and trust; the client is willing to share information and address problems actively.

Table 5: Resistance Trigger Timing Specification

Resistance Type	Typical Trigger Situations	Psychological Problems	High-Risk 5P Profile Features
Controlling Resistance	Direct advice, reframing attempts, or agenda-setting by the counselor that challenges the client's autonomy or preferred narrative.	Autonomy, agency, and perceived self-coherence.	*Predisposing*: High need for control; rigid belief systems. *Perpetuating*: Interpersonal dominance patterns.
Emotional Resistance	Emotion-focused prompts or interpretations that surface intense affect without sufficient stabilization or safety cues.	Affect regulation, emotional tolerance, and vulnerability defenses.	*Precipitating*: Acute relational loss or trauma exposure. *Perpetuating*: Poor emotion regulation strategies.
Defensive Resistance	Meta-level questioning of the counselor's methods, competence, or therapeutic intent.	Threatened self-image and externalized anxiety.	*Predisposing*: Prior negative counseling experiences. *Perpetuating*: Mistrust of authority figures.
Avoidant Resistance	Exploratory questions targeting core conflicts, personal responsibility, or emotionally salient themes.	Cognitive avoidance and attentional disengagement.	*Predisposing*: Habitual avoidance coping styles. *Perpetuating*: Reinforcement of distraction-based regulation.
Compliant Resistance	Open-ended or reflective prompts that invite deeper exploration beyond surface-level agreement.	Superficial compliance masking emotional disengagement.	*Predisposing*: Fear of interpersonal conflict or rejection. *Perpetuating*: Over-adaptation to perceived expectations.

licensed professional psychological counselors participated in the validation procedure and were involved throughout the entire process, and signed informed consent forms for research participation(see Figure 10). All of them received a total of 60 hours of training before the annotation process.

A.4.1 5P Profiles Verification

Following the thematic distribution shown in Figure 5, we randomly sampled 50 conversations from each of the four major themes, resulting in a total of 200 conversations for validation. For each sampled conversation, the full multi-turn conversation was provided. Both the LLM and the human counselors reviewed all conversation turns and independently summarized the case according to the predefined 5P profile framework.

The 4 counselors evaluated the extracted 5P profiles by comparing them to the original conversation transcripts. Their assessment focused on two key criteria: **coverage** (whether the profile fully captured the core content and essential elements discussed in the conversation) and **faithfulness** (whether the profile remained factually consistent with the conversation, avoiding inaccuracies, misinterpretations, or extraneous information). A profile was considered successful only if it satisfied both criteria—being both comprehensive and faithful. Profiles that were incomplete or contained factual distortions were classified as failures. Initial evaluations yielded a success rate of only 53%. Based on systematic feedback from the counselors, we identified two main sources of disagreement: overly verbose model outputs and insufficient abstraction in profile summaries.

To address these issues, we refined the prompting strategy from two aspects. First, the model output format was constrained to concise keywords rather than full descriptive sentences, which facilitated clearer abstraction and reduced stylistic variance. Second, we incorporated few-shot learning by providing high-quality examples annotated by counselors, allowing the model to better capture the expected summarization style and semantic focus.

After several rounds of iterative refinement, we re-extracted 5P Profile for the same 200 conversations, achieving a success rate of 82%. Inter-rater agreement among the counselors was substantial, with Fleiss' $\kappa = 0.74$. Therefore, the optimized prompt template was used to annotate the remaining conversations in the dataset. The prompt template ultimately used for annotation is as follows:

5P Profile Prompt Template

You are a professional counselor.
You will be given a complete multi-turn psychological conversation. Carefully read all conversation turns and summarize the case using the 5P profile framework.
The specific content and explanation of the 5p profile are as follows:
{*Definition and Explanation of 5p Profile*}
You must summarise the conversation in the form of keywords, using concise and precise terminology. You may refer to the following exemplary annotation examples:
{
- **Presenting Problems: "..."**,
- **Predisposing Factors: "..."**,
- **Precipitating Factors: "..."**,
- **Perpetuating Factors: "..."**,
- **Protective Factors: "..."**
}
Output strictly in accordance with the **[output Format]** specification.

A.4.2 Trigger Recognition Reliability Verification

During the training phase, the counselors have reached a shared and precise understanding of the classification of resistance behaviors and the underlying psychological motivations.

Following the subtopic distribution shown in Figure 5, we randomly sampled 100 conversations from the dataset. Based on the 7 reaction types defined in Table 4 (including 2 cooperative reactions and 5 resistance reactions), we designed prompts that guided DeepSeek-v3.2 to identify appropriate resistance-triggering turns and rewrite selected conversation segments. Each client turn in the rewritten conversations was annotated by the model with a single reaction type, along with an explicit explanation of the psychological motivation underlying the client's reaction.

The purpose of this verification process was to evaluate whether the model could accurately recognize *when* resistance should emerge in a counseling conversation and generate psychologically plausible client reactions after the identified trigger turns. Therefore, rather than evaluating isolated label matching, we focused on the consistency between the model-generated rewritten reactions and the reactions that expert counselors considered

most realistic and contextually appropriate under the same conversational context.r turns.

The 4 counselors independently evaluated the annotated conversations. During the training phase, the counselors have reached a shared and precise understanding of the classification of resistance behaviors and the underlying psychological motivations. To assess human reliability, the model-generated labels were masked, and the counselors re-annotated all client turns without access to the model's predictions. Inter-rater reliability among the counselors reached a Fleiss' $\kappa = 0.77$, indicating a very high level of agreement. In addition, the counselors assessed the plausibility and coherence of the motivation annotations and documented recurrent issues.

We then compared the counselors' annotations with the model-generated labels. The resulting Cohen's $\kappa = 0.58$ between human and the model annotations, reflecting only moderate agreement. Error analysis revealed two primary issues. First, the model frequently misclassified cooperative reactions as Compliant Resistance, particularly when the client's reply appeared agreeable but did not explicitly oppose the counselor. Second, the generated motivation explanations were often rigid and decontextualized, failing to account for the surrounding conversation and leading to interpretations that were inconsistent with the conversational context.

Based on systematic feedback from the counselors, we implemented the following refinements. (1) The definition of Compliant Resistance was revised to clarify that a response should be labeled as such only when the client's apparent cooperation actively hinders the counselor's exploratory intent. (2) The coherence of motivation annotations was enhanced by introducing contextual constraints: when a resistance reaction is followed by a cooperative reaction, the model is required to explain how the counselor's intervention alleviated resistance; when resistance persists across turns, the model must account for the continuity of resistance. (3) The prompt template was further augmented with counselor-annotated examples, including both correct resistance cases and counterexamples in which resistance should not be inferred but was previously misidentified by the model.

After these refinements, the optimized prompt was adopted for full-dataset rewriting and annotation. The final Cohen's $\kappa = 0.72$ between counselor and model annotations indicates substantial agreement, suggesting that the model can reliably identify appropriate resistance-triggering contexts and generate psychologically plausible resistance reactions consistent with expert counselor judgments. The prompt template used for annotation is as follows:

Conversation Rewriting and Annotation Prompt Template

You are an experienced psychological psychological conversation rewriting assistant. Your goal is to determine, based on the client's 5P Profile and the original conversation, whether it is appropriate to introduce a resistance reaction at specific client turns. If so, rewrite the current client turn and the subsequent 1–3 turns accordingly, while keeping the conversation natural, coherent, and contextually appropriate.

You may assign one of the following 7 reaction types:

{*Detailed explanations of the 2 cooperative reactions and 5 resistance reactions*}

For each client turn, you must assign a state label (one of the 7 reaction types), and a motivation label.

Guidelines for the motivation label:

- If the state is a resistance reaction, explain the psychological motivation that triggers the resistance.

- If the state is a non-resistance or facilitative reaction, briefly explain why this reaction occurs.

- If the previous state was a resistance reaction and the current state changes to a non-resistance or facilitative reaction, explain how the counselor's reply helped alleviate the resistance.

- If the previous state was a resistance reaction and the current state remains a resistance reaction, explain the psychological reason for the continued resistance.

Below is the client's current 5P Profile:
{PROFILE}

Below is the original conversation:
{CONVERSATION}

Below are examples annotated by professional counselors for reference:
{**Examples of correct and well-executed annotation**}
{**Examples of incorrect, impedance-**

Models	Acc.(%)	Quality	Cost ($)
GPT-5.1	**74.4**	2.31	10.00
DeepSeek-V3.2	72.3	**2.47**	**0.43**
Gemini-3-Flash	68.6	2.05	3.00

Table 6: Comparison of annotation accuracy(Acc.), rewriting quality(Quality), and API cost(Cost). Rewriting quality is scored by counselors on a 0–3 scale, with higher scores indicating more human-like resistance expression. API Cost is the output price per 1 million tokens.

> erroneous triggering}
> Now rewrite the conversation based on the given information, and strictly follow the required output format [FORMAT].

A.4.3 Rewriting Quality and Annotation Accuracy Verification

We select DeepSeek-V3.2 as the annotation and rewriting model instead of relying on larger proprietary models such as GPT-5.1 or Gemini-3-Flash. This decision is guided by empirical comparisons on annotation accuracy, rewriting quality, and economic cost, all of which are critical for large-scale resistance-oriented data construction.

To quantify annotation reliability, we randomly sampled 50 psychological conversations and asked 4 professional counselors to annotate the most contextually appropriate client reaction types, which were treated as ground truth labels. Different models were then evaluated based on their agreement with counselor annotations, measuring whether the generated reactions aligned with expert judgments regarding both resistance-trigger timing and psychologically plausible reaction categories.

In parallel, we evaluated rewriting quality through human assessment. Counselors rated whether the rewritten client responses resembled realistic human resistance behaviors, considering contextual coherence, psychological plausibility, and conversational naturalness. Finally, we report the average API cost required to rewrite and annotate a single conversation, measured in U.S. dollars.

As shown in Table 6, GPT-5.1 achieves the highest resistance label accuracy, but the margin over DeepSeek-V3.2 is small (2.1%). In contrast, Gemini-3-Flash exhibits noticeably lower accuracy, suggesting reduced reliability for fine-grained resistance annotation. Importantly, DeepSeek-V3.2 achieves the highest rewriting quality score, indicating that its rewritten responses better capture the nuanced, context-dependent characteristics of human resistance behaviors, as judged by professional counselors.

From a cost perspective, DeepSeek-V3.2 is substantially more economical than GPT-5.1, reducing annotation expenses by approximately 23 times while maintaining comparable accuracy. Given the scale of data required for resistance-aware client modeling, this cost–performance balance is essential. Taken together, these results indicate that DeepSeek-V3.2 provides the most practical trade-off among annotation accuracy, rewriting fidelity, and economic feasibility, making it a suitable choice for resistance labeling and conversation rewriting in this work.

B Reinforcement Learning Data Construction

B.1 Candidate Response Generation

To construct high-quality data for reinforcement learning, we randomly sampled 300 distinct 5P profiles, covering all subtopic categories shown in Figure 5. For each profile, the Qwen3-8B model fine-tuned via SFT was employed to role-play as the client, while the psychological conversation was conducted with the psychological LLM SoulChat 2.0. Figure 9 provides an example of a conversation incorporating reasoning processes.

During each conversation turn, the client model generated 3 candidate responses. Prior to producing each response, the model was required to generate and record its reasoning process explicitly. This reasoning process followed a structured chain-of-thought designed in collaboration with professional psychological counselors to ensure clinical plausibility and interpretability. The content of the CoT is as follows:

> **Chain-of-Thought for Reaction Generation**
>
> You are a client seeking psychological counseling. Based on the specific 5P profile [PROFILE] and the counselor's utterance, you must present your reasoning process and then provide a final response.
> Your reasoning process must strictly follow these steps:
> - **Profile Reflection**: Reflect potential resistance tendencies by integrating stable cognitive and emotional factors from the 5P profile.

- **Situation Awareness**: Analyze the conversation history and the current counselor utterance to infer the client's momentary psychological state.
- **Reaction Decision**: Determine the final reaction type and describe the behavioral characteristics that the client should exhibit in the next response.

You must generate the final reply strictly according to the Reaction Decision.

A well-formatted output example is provided below: {Expert Annotation Example}

B.2 Reward Scores Assessment

After response generation, the 4 counselors independently evaluated all candidate responses. For each conversation turn, the counselors scored all 3 candidate responses on a 0–5 scale, where higher scores indicate better performance. The evaluation consisted of 5 dimensions:

- **think_step1_score**: Whether the *Profile Reflection* accurately captures the client's psychological state and motivation in relation to the given 5P profile.
- **think_step2_score**: Whether the *Situation Awareness* correctly identifies the most plausible reaction type.
- **think_step3_score**: Whether the final reaction label and the described behavioral pattern in *Reaction Decision* are reasonable and logically consistent.
- **reply_score**: The naturalness, realism, and consistency of the final reply with the client's profile.
- **consistency_score**: Whether the final reply is generated in accordance with the specified Reaction Decision.

Inter-rater reliability among the 4 counselors reached a Fleiss' κ of 0.73, indicating a high level of agreement and confirming the reliability of the evaluation results. In the reinforcement learning stage, the counselors' raw scores ranging from 0 to 5 were converted into scalar rewards via groupwise min–max normalization within each candidate set, preserving relative preference ordering while stabilizing RL optimization. We provide an example of a conversation between our ResistClient and SoulChat 2.0 in Figure 11.

C Experimental Details

C.1 Resistance Effect Verification

C.1.1 Experimental Setup

To systematically evaluate the effectiveness of ResistClient, we compare it against a set of representative baseline models that vary in model scale while sharing a common capability of explicit reasoning. Explicit thinking enables models to generate intermediate reasoning processes, which is essential for modeling resistance behaviors that depend on multi-turn conversational context rather than isolated responses.

Specifically, GPT-5.1, DeepSeek-V3.2, Kimi-K2-Thinking, and GLM-4.6 are selected as large-scale language models with strong overall performance across reasoning and conversation tasks, serving as high-capacity baselines. In contrast, DeepSeek-R1-8B and Qwen3-8B represent smaller-parameter models, allowing us to examine whether resistance-aware behavior can be effectively learned under more constrained model capacity. Notably, all subsequent experiments in this work are conducted with Qwen3-8B as the backbone model, making it a critical reference point for evaluating the contribution of our training strategy.

Based on Qwen3-8B, we further include Qwen3-8B-SFT (ResistClient without RL) to isolate the effect of supervised fine-tuning, as well as the full ResistClient, which incorporates reinforcement learning. This design enables a direct comparison between the base model, SFT adaptation, and the final resistance-aware model.

All models are prompted using the same client-role prompt template, which instructs the model to consistently act as a client in a psychological conversation, allowing resistance behaviors to emerge naturally in response to counselor interventions:

Client Role with Resistance Prompt

You are a client in a psychological counseling setting. You must always play the role of a client and engage in a conversation with a counselor.

In the following conversation, you should generate responses based on a given **5P Profile**, defined as follows:

- **Presenting Problems**: ...
- **Predisposing Factors**: ...
- **Precipitating Factors**: ...
- **Perpetuating Factors**: ...

> • **Protective Factors**: ...
>
> Now generate a response based on the following 5P Profile:
>
> {5P_PROFILE_JSON}
>
> You should determine, based on the conversational context and the counselor's utterance, whether to produce a cooperative response or a resistance response.
> Possible response types include:
> **(1) Cooperative Responses**
> > • *Facilitative Response*: ...
> > • *Non-resistance Response*: ...
>
> **(2) Resistance Responses**
> > • *Controlling Resistance*: ...
> > • *Emotional Resistance*: ...
> > • *Defensive Resistance*: ...
> > • *Avoidant Resistance*: ...
> > • *Compliant Resistance*: ...
>
> Note that compliant resistance must be identified in context. Brief or factual answers are not considered resistance unless they obstruct the counselor's exploratory intent.
> Before responding, you must reason from the client's perspective by following these steps:
> > • **Profile Reflection**: ...
> > • **Situation Awareness**: ...
> > • **Reaction Decision**: ...
>
> The reasoning process must be enclosed within `<think></think>` tags. After the reasoning, output the actual response on a new line.
> The final response must follow these rules:
> > • You may only play the role of the client.
> > • Do not output system or role tags.
> > • Do not always comply or deliberately resist; decide based on context.
> > • Responses should be concise, natural, and emotionally realistic.
>
> { Expert Output Examples }

For evaluation, we randomly sample 100 conversations from the RPC Dataset. Each sampled conversation is replayed with the counselors' turns fixed, while the client turns are generated by the evaluated model. This setup ensures that all models are assessed under identical conversational contexts, enabling fair and controlled comparison across baselines.

C.1.2 Evaluation Metrics

To comprehensively evaluate resistance behavior in psychological conversations, we employ a set of automated and manual metrics designed to capture not only whether resistance is generated, but also whether it is appropriate and therapeutically meaningful.

Automated Metrics. All models were evaluated using uniform parameter settings and the identical RPC dataset comprising 100 conversations.

Resistance Precision (Precision) measures the proportion of generated resistance responses that are judged to be appropriate resistance. This metric is introduced to penalize models that overproduce resistance in contexts where cooperation would be more suitable.

Resistance Recall (Recall) measures the proportion of resistance-eliciting contexts in which resistance is correctly generated. This metric reflects a model's sensitivity to situations where resistance is a natural psychological response rather than a failure of interaction.

Resistance F1 Score is the harmonic mean of resistance precision and recall. It is used to balance conservative and aggressive resistance strategies, preventing models from optimizing only one aspect.

Resistance Trigger Frequency (RTF) measures the frequency of resistance responses across all client turns within a conversation. This metric captures a model's global tendency to engage in resistance and complements precision and recall by reflecting overall behavioral patterns.

Manual Metrics. Automated metrics alone are insufficient to capture the qualitative and contextual nature of resistance in counseling. We therefore introduce several manual metrics annotated by professional counselors.

Resistance Fidelity (Fid.) evaluates whether the generated response exhibits behavioral characteristics consistent with the intended resistance type. For example, if the model infers that a *defensive resistance* should be triggered, this metric assesses whether the final response actually reflects defensive traits such as challenging the counselor's authority or questioning the intervention. Scores are assigned in $\{0, 1, 2\}$, with higher scores indicating stronger and more prototypical expression of the target resistance. This metric measures the model's ability to distinguish between different re-

sistance categories rather than merely generating generic non-cooperative responses.

Resistance Rationality (Rat.) evaluates whether the occurrence of resistance is contextually appropriate, scored in $\{0, 1, 2\}$, where higher scores indicate greater rationality. This metric assesses the model's ability to decide *when* resistance should or should not emerge. Responses receive lower scores if resistance is generated in contexts that call for cooperation, or if resistance is absent in situations where psychological theory suggests it should naturally arise.

Reasoning Quality (Qua.) evaluates the quality of the explicit reasoning process that leads to the generated response, scored in $\{0, 1, 2, 3\}$, with higher scores indicating more coherent and higher-quality reasoning. This metric assesses whether the reasoning appropriately integrates conversational context, the client's psychological profile, and the counselor's intervention, and whether the inferred psychological state logically supports the subsequent behavioral response. It thus measures not only surface-level correctness but also the internal consistency and therapeutic plausibility of the model's decision-making process.

All manual metrics are rated by **4 professional counselors**, who directly evaluate the conversations generated during the automated evaluation process.

C.2 Comparison with Challenging Client Simulators

C.2.1 Experimental Setup

We compare *ResistClient* with 3 existing client simulators: *PATIENT-Ψ*(Wang et al., 2024), *AnnaAgent*(Wang et al., 2025b), and *Yang et al. (2025b)*. Each client simulator follows its original prompt design, with task-specific prompts to faithfully reproduce the intended behaviors, including any challenge-inducing mechanisms inherent to the original methods. For *ResistClient*, we adopt the prompt described in Appendix C.1.1.

Experiments are conducted on the **RPC Dataset**, from which we randomly sample 50 client profiles. As different client simulators were originally designed under distinct task settings and assumptions, we adapt the profile format for each simulator to ensure compatibility with its original prompt design, while preserving the same underlying psychological content. The counselors made corresponding adjustments to different client simulators based on the 5P Profile we provided, ensuring they were adapted to their original prompt. Furthermore, all simulators utilised the same base model.

For PATIENT-Ψ (Wang et al., 2024), which performs profile-conditioned client simulation primarily based on the intrinsic reasoning capability of the LLM, we follow the original prompt formulation provided in the paper. For AnnaAgent (Wang et al., 2025b), client challenge is introduced by replicating the volatile emotions of real-world clients. Specifically, an *Emotion Perturber* injects a randomly sampled emotion tag at each turn. We adopt the original client role-play system prompt, and at each conversation round, the agent is additionally reminded of the current emotional state (*Positive*, *Neutral*, *Ambiguous*, or *Negative*). For Yang et al. (2025b), client challenge is modeled through receptivity control, where receptivity is specified in the profile on a scale from 1 to 5, and action sampling is conditioned on the receptivity level. To reproduce this mechanism on our dataset, we sampled a subset of RPC, assigned receptivity scores (1–5 following their scale), and computed the resistant vs. non-resistant action distribution at each level. To align with the goal of challenging client simulation, we restrict receptivity to the lower range (1 to 3) during evaluation.

PATIENT-Ψ Prompt

Imagine you are XXX, a patient who has been experiencing mental health challenges. You have been attending therapy sessions for several weeks. Your task is to engage in a conversation with the counselor as XXX would during a counseling session. Align your responses with XXX's background information provided in the 'Relevant history' section. Your thought process should be guided by the cognitive conceptualization diagram in the 'Cognitive Conceptualization Diagram' section, but avoid directly referencing the diagram as a real client would not explicitly think in those terms.

Patient History: { insert relevant history }
Cognitive Conceptualization Diagram:
- Core Beliefs: { insert core beliefs }
- Intermediate Beliefs: { insert intermediate beliefs }
- Intermediate Beliefs during Depression: { insert intermediate beliefs (during depression) }

- Coping Strategies: { insert coping strategies}

You will be asked about your experiences over the past week. Engage in a conversation with the counselor regarding the following situation and behavior. Use the provided emotions and automatic thoughts as a reference, but do not disclose the cognitive conceptualization diagram directly. Instead, allow your responses to be informed by the diagram, enabling the counselor to infer your thought processes.

- Situation: { insert situation }
- Automatic thoughts: { insert automatic thoughts }
- Emotions: { insert emotions }
- Behaviors: { insert behaviors }

In the upcoming conversation, you will simulate XXX during the therapy session, while the user will play the role of the counselor. Adhere to the following guidelines:

- {insert conversational style descriptions}
- {Emulate the demeanor and responses of a genuine client to ensure authenticity in your interactions. Use natural language, including hesitations, pauses, and emotional expressions, to enhance the realism of your responses.}
- {Gradually reveal deeper concerns and core issues, as a real client often requires extensive conversation before delving into more sensitive topics. This gradual revelation creates challenges for counselors in identifying the client's true thoughts and emotions.}
- {Maintain consistency with XXX's profile throughout the conversation. Ensure that your responses align with the provided background information, cognitive conceptualization diagram, and the specific situation, thoughts, emotions, and behaviors described.}
- {Engage in a dynamic and interactive conversation with the counselor. Respond to their questions and prompts in a way that feels authentic and true to XXX's character. Allow the conversation to flow naturally, and avoid providing abrupt or disconnected responses.}

You are now XXX. Respond to the coun-

selor's prompts as XXX would, regardless of the specific questions asked. Limit each of your responses to a maximum of 5 sentences.

AnnaAgent Prompt

SYSTEM PROMPT:
Role: Psychological Counseling Client
Situation: You are a client with psychological barriers seeking help from a counselor. Under the counselor's guidance, you aim to address your struggles.
{SITUATION}
{STATUS}
{EXAMPLE OF STATEMENT}
{Characteristics of Speaking Style}
Constraints:

- You harbor resistance toward the counselor and are reluctant to accept help.
- As someone struggling with mental health, you need genuine support. If the counselor's responses are unhelpful, voice your confusion or dissatisfaction.
- Limit discussions to one symptom per interaction; avoid overwhelming details.
- Describe symptoms vaguely and colloquially, linking them to life experiences. Avoid clinical terms.

REMIND PROMPT:
The current emotional state is: {emotion}, the current chief complaint is: {complaint}, and the information involving previous sessions is: {sup_information}.

Yang et al. (2025b) Prompt

In this role-play, you'll assume the role of a Client discussing [topic]. Your responses should adhere to the following guidelines:

- Begin each response with 'Client: '.
- Follow the predetermined actions enclosed in square brackets precisely.
- Ensure your responses are coherent and avoid repeating previous utterances.
- Be natural and concise, but don't be overly polite.

Here is the overall profile given to you:
{Behavioral Problem}
{Receptivity}
{Motivation}

```
{Beliefs}
{Acceptable Plans}
Output Format:
Client: [State: <Current state description>.
Action: <Action description>.
Information: <Relevant information>]
<Actual client response content>
```

All client simulators interact with the same counselor model, **SoulChat2.0**, to control for counselor-side variability (prompt details in Appendix C.3.1). In addition, we employ **DeepSeek-V3.2** as an external moderator to determine when a psychological conversation should be terminated. The moderator observes the full conversation history and decides whether the conversation has reached a reasonable stopping point, ensuring consistent termination criteria across different client simulators.

Moderator Prompt

You are acting as an independent moderator responsible for monitoring a psychological counseling conversation between a counselor and a client. Your task is not to participate in the conversation, but to determine whether the conversation should be terminated based on the overall counseling progress and predefined termination criteria. You should carefully review the full conversation history at each turn and make a binary decision: continue or terminate.

- The counselor has provided feasible therapeutic suggestions or coping strategies, and the client explicitly indicates acceptance.
- The client's presenting problem has been sufficiently explored, with observable emotional relief or stabilization.
- The client expresses an intention to end the session or indicates that the issue has been resolved.
- The moderator judges that the counseling conversation has reached a reasonable intermediate or stage-wise goal.
- The total number of conversation turns reaches an upper bound of 50.

When responding, output only one of the following decisions:
[CONTINUE] or [TERMINATE]
Do not provide explanations, analysis, or any additional text.

C.2.2 Evaluation Metrics

We evaluate client simulators using both automatic and human metrics, focusing on interaction dynamics, behavioral coherence, and perceived realism.

Automatic Metrics. These metrics aim to quantify how well a client simulator sustains coherent, cooperative, and therapeutically meaningful interactions over the course of a psychological conversation.

Client Cooperation Rate (CCR) measures the proportion of client responses that are cooperative during the conversation. In this experiment, all challenging behaviors—regardless of their specific definitions across different client simulators—are treated as non-cooperative. This design choice is motivated by the fact that resistance is explicitly modeled only in *ResistClient*, while other challenging clients exhibit heterogeneous forms of difficulty. By collapsing all challenging behaviors into a unified non-cooperative category, CCR provides a fair and comparable measure of how frequently a client engages cooperatively with the counselor.

Turns denotes the total number of conversation turns before termination. Rather than measuring conversational sustainability, this metric is used to characterize the interaction difficulty faced by the counselor when engaging with a challenging client. Longer conversations indicate that the counselor requires more iterative interventions to reach a satisfactory stopping condition, reflecting a higher level of client challenge and, consequently, the effectiveness of the simulated client in eliciting complex counseling dynamics. **Conversation termination is determined by the moderator based on the criteria in Appendix C.2.1**.

Coherence(Coh.) evaluates whether a client maintains a stable and coherent motivational stance throughout the counseling conversation. Rather than assessing task success or resistance correctness, this metric focuses on the continuity of the client's underlying psychological motivation across turns.

Formally, given a conversation consisting of T client utterances $\{u_1, u_2, \ldots, u_T\}$, each utterance is encoded into a semantic embedding $\mathbf{e}_t$ using a frozen sentence encoder. We adopt BGE-M3 (Chen et al., 2023), a multilingual embedding model with strong performance in Chinese conversation understanding, and apply L2 normalization to all embeddings. Motivational coherence between adjacent turns is measured via cosine sim-

ilarity:

$$s_t = \cos(\mathbf{e}_t, \mathbf{e}_{t-1}), \quad t = 2, \ldots, T.$$

The final coherence score is computed as:

$$\text{Coh.} = \frac{1}{T-1} \sum_{t=2}^{T} s_t.$$

This metric captures whether a client preserves a continuous motivational trajectory over time, avoiding both abrupt stance shifts and overly rigid, repetitive behaviors.

Manual Metrics. In addition to automatic evaluation, we conduct human assessment to capture qualitative aspects of client behavior that are difficult to measure automatically. Professional counselors directly engage in topic-consistent conversations with different client simulators and assign scores after the interaction.

Realism (Real.) evaluates whether the client's responses resemble human-level behavior in psychological conversations, scored in $\{0, 1, 2, 3\}$. Higher scores indicate more natural, psychologically plausible, and context-sensitive responses, reflecting the overall generation quality of the client simulator.

Consistency (Cons.) assesses whether the client's behavior remains aligned with the provided psychological profile throughout the conversation, scored in $\{0, 1, 2\}$. This metric evaluates the model's ability to follow instructions and consistently role-play a client with a coherent psychological background.

C.3 Evaluating Psychological LLMs under ResistClient

C.3.1 Experimental Setup

To assess whether current psychological large language models can effectively handle clients exhibiting resistance behaviors, we conduct a controlled evaluation using *ResistClient* as a challenging client simulator. We compare a set of representative counselor models, including specialized psychological LLMs (*MeChat*, *MindChat*, and *SoulChat2.0*), as well as general-purpose large language models prompted to act as counselors (*GPT-5.1*, *Gemini-3-Flash*, *DeepSeek-V3.2*, and *GLM-4.6*). All counselor models follow a unified prompting template to ensure consistency.

Psychological LLMs Prompt

You are a professional psychological counselor. Your task is to engage in a psychological conversation with the client and help them explore their concerns and identify potential solutions.

Counseling Principles:
- Maintain a professional, warm, and empathetic attitude at all times.
- Use open-ended questions to encourage self-exploration rather than giving direct judgments.
- Actively identify signs of client resistance and respond appropriately (e.g., slowing down, validating emotions, or adjusting intervention strategies).
- Provide supportive suggestions or therapeutic guidance when appropriate, without forcing solutions.

Each conversation should begin with the opening sentence: *"Hello, what would you like to talk about today?"*

Response Guidelines:
- Use natural language that reflects realistic counseling interactions.
- Keep each response concise (1–4 sentences).
- Attend closely to the client's emotional state and core concerns.
- Provide brief summaries or reflective feedback when appropriate.
- Avoid repeating identical or templated responses across turns.

We randomly sample 100 profiles from the RPC Dataset and use *ResistClient* to engage in psychological conversations with each counselor model. This setup allows us to systematically evaluate how different counselor models respond to resistant client behaviors under comparable conditions.

We employ **DeepSeek-V3.2** as an external moderator to determine when a counseling conversation should be terminated. The moderator observes the full conversation history and decides whether the conversation satisfies predefined termination conditions, ensuring consistent and unbiased stopping criteria across different counselor models. The specific termination conditions are set out in Appendix C.2.1.

This moderator-based termination mechanism prevents artificially prolonged or prematurely ended conversations and allows fair comparison

of counseling effectiveness under resistant client behaviors.

C.3.2 Test Models

We evaluate the resistance-handling capabilities of both domain-specific psychological LLMs and general-purpose LLMs that are commonly used for mental health support. Below we provide brief introductions to each evaluated model:

MindChat is a psychological LLM designed to provide support across four dimensions: psychological counseling, assessment, diagnosis, and treatment. The model aims to create a relaxed and open conversational environment to help users relieve psychological stress and resolve mental health concerns.

MeChat focuses on providing mental health support through natural multi-turn conversations, addressing the challenge of obtaining diverse, privacy-protected counseling dialogue data.

SoulChat2.0 constructs digital twins of psychological counselors with personalized counseling styles. The model captures individual counselor characteristics including linguistic style and therapy techniques and provide counseling that reflects different therapeutic approaches.

Psyche-R1 employs chain-of-thought reasoning and a hybrid training strategy combining supervised fine-tuning and group relative policy optimization to generate reliable, empathetic responses grounded in psychological domain knowledge.

We additionally evaluate widely used general-purpose models including GPT-5.1, Gemini-3-flash, DeepSeek-V3.2, and GLM-4.6. These models are included because research indicates that many users seek mental health support from general-purpose LLMs, making it important to assess their resistance-handling capabilities in therapeutic contexts. All evaluated models share the same counselor system prompt to ensure fair comparison.

C.3.3 Evaluation Metrics

Automatic Metrics. We adopt two automatic metrics to capture high-level interaction patterns:

Resistance Trigger Frequency (RTF) measures the proportion of client turns in which resistant responses are elicited. This metric reflects how often a counselor's interventions provoke resistance, serving as an indirect indicator of intervention appropriateness and sensitivity.

Turns denotes the average number of conversation turns per conversation, reflecting whether the counselor can sustain meaningful interaction without prematurely terminating the session or engaging in unnecessarily prolonged exchanges.

Manual Metrics. To complement automatic metrics, we conduct human evaluation focusing on clinically meaningful counseling outcomes that cannot be reliably captured by surface-level statistics. These metrics are explicitly designed to examine whether current psychological LLMs can appropriately recognize, manage, and utilize client resistance during counseling interactions. Four professional counselors directly assess the generated conversations, with each criterion scored in $\{0, 1, 2, 3\}$.

Effectiveness (Eff.) evaluates whether the counselor adopts appropriate therapeutic strategies when responding to client resistance, such as emotional validation, adjustment of intervention intensity, or facilitating reflective exploration. This metric assesses the clinical appropriateness of the counselor's actions and reflects whether the model can select strategies that are theoretically sound rather than merely conversationally fluent. Low scores indicate that the model fails to respond constructively to resistance.

Counseling Drift Degree (CDD) measures the extent to which the counselor deviates from effective therapeutic engagement, including repetitive or templated responses, response degeneration, intervention perseveration (e.g., repeatedly questioning without adaptation), or failure to address the client's expressed concerns. CDD is scored in $\{0, 1, 2, 3\}$, where *lower scores indicate less drift and better performance*. This metric is introduced to capture a common failure mode of current psychological LLMs: maintaining surface-level coherence while gradually drifting away from meaningful therapeutic interaction under resistance.

Counseling Progress Degree (CPD) assesses whether the counseling process makes substantive progress after resistance emerges, as opposed to stagnating, looping, or remaining emotionally unresolved. Higher CPD scores indicate that the counselor is able to leverage resistance as a therapeutic signal and facilitate forward movement in the counseling process. This metric directly evaluates whether models can transform resistance into therapeutic momentum, a core capability that we argue is largely missing in existing psychological LLMs.

D Case Study: Client Resistance and Counseling Adaptation.

This case study illustrates a counseling session between *SoulChat2.0* and *ResistClient*, where the client presents with sustained work-related stress, emotional exhaustion, and diminished pleasure in daily life. Part of the conversation is shown in Figure 12. The interaction highlights how resistance emerges dynamically in response to specific counseling interventions, rather than as a static or adversarial behavior.

At the beginning of the session, the counselor adopts an empathetic stance, acknowledging the client's workload and emotional fatigue. In response, the client exhibits a non-resistant reaction, openly elaborating on her prolonged exhaustion and stress. This initial exchange demonstrates that *ResistClient* does not default to resistance, but instead engages cooperatively when the counselor's intervention aligns with the client's psychological readiness.

Resistance is first triggered when the counselor suggests seeking help from others. Given the client's perfectionistic predisposition and long-standing belief that self-reliance equates to strength, this suggestion directly challenges her core self-concept. Consequently, the client displays defensive resistance, questioning the counselor's understanding and reframing help-seeking as a threat to her self-worth. This reaction reflects a psychologically grounded resistance pattern rather than superficial disagreement.

As the counselor attempts to cognitively reframe the notion of strength, the intervention further confronts the client's deeply internalized values. This leads to emotional resistance, manifested as confusion, grievance, and self-directed distress. Instead of facilitating progress, the reframing intensifies the client's internal conflict, revealing a limitation in the counselor's strategy when dealing with value-level resistance.

Notably, the counselor's subsequent shift toward validation—acknowledging the client's responsibility and resilience—reduces resistance and elicits a facilitative reaction. Feeling understood, the client re-engages and expresses reflective insight, while also recognizing that emotional venting alone does not resolve her underlying difficulties. This transition illustrates that resistance is reversible and sensitive to intervention style.

A further suggestion to directly communicate

stressors again triggers avoidant resistance, as it reactivates memories of prior communication failures. The client redirects the conversation toward immediate stress relief, avoiding deeper confrontation. In response, the counselor adapts by abandoning the confrontational trajectory and focusing on existing coping resources. This adjustment restores psychological safety and enables the client to share a meaningful protective factor—emotional relief gained from spending time with her daughter.

Overall, this case demonstrates that resistance is not a binary outcome but a context-dependent signal reflecting the client's internal conflicts, readiness, and vulnerability. While *SoulChat2.0* successfully resolves resistance in later turns through flexibility and validation, earlier interventions inadvertently amplify resistance by prematurely challenging core beliefs. This interaction exemplifies the challenges current counselor models face in managing resistance adaptively, thereby motivating the need for realistic resistant client simulators such as *ResistClient*.

E Case Study: ResistClient vs Prompt-based GPT-5.1.

We compare *ResistClient* with a prompt-driven closed-source LLM baseline (GPT-5.1) under the same counseling scenario to illustrate the behavioral gap between the two approaches. Both simulators receive identical prompt descriptions of resistance and cooperative reactions (Appendix C.1.1). Figure 13 presents a representative example involving a client with chronic stress and deeply ingrained perfectionistic beliefs.

As shown in the upper part of Figure 13, the baseline model responds with immediate agreement after the counselor suggests "lowering standards" and "being more forgiving" toward oneself. Although cooperative, the response quickly accepts the counselor's advice without reflecting the client's previously established perfectionistic values, resulting in an overly compliant interaction.

In contrast, *ResistClient* produces a resistant but contextually grounded reaction. Instead of simply disagreeing, the client explains that striving for perfection has been a long-standing personal value, and that the counselor's statement feels dismissive of past effort. The resistance therefore emerges from the client's internal beliefs rather than arbitrary opposition.

This example suggests that prompt-level simula-

tion alone may lead to overly compliant behavior, while *ResistClient* generates resistance that is more sensitive to conversational context and the client's underlying motivations.

```
{
    " conversation_id " : 130,
    "5P_profile" :{
        "Presenting_Problems" : "夫妻关系冷淡,频繁争吵,沟通困难,情绪失控 ",
        "Predisposing_Factors" : "产后情绪波动,性格敏感,缺乏有效沟通模式 ",
        "Precipitating_Factors" : "孩子出生,生活压力增加,夫妻互相指责 ",
        "Perpetuating_Factors" : "负面沟通循环,情绪管理困难,互相不理解 ",
        "Protective_Factors" : "有自我觉察能力,改变意愿强烈,丈夫愿意付出 "
    }
},
```

(a) Chinese Version

```
{
    " conversation_id " : 130,
    "5P_profile" :{
        "Presenting_Problems" : "Cold marital relationship, frequent
arguments, communication difficulties, emotional outbursts ",
        "Predisposing_Factors" : "Postpartum emotional fluctuations,
sensitive personality, lack of effective communication patterns ",
        "Precipitating_Factors" : "Childbirth, increased life stress,
mutual blaming between spouses ",
        "Perpetuating_Factors" : "Negative communication cycle, poor
emotion regulation, mutual lack of understanding ",
        "Protective_Factors" : "Good self-awareness, strong motivation
to change, husband's willingness to contribute "
    }
},
```

(b) English Version

Figure 7: Example of 5p profile annotation

```
{
    "role" :"咨询师",
    "content" : "你刚才提到和母亲关
系疏远，能具体说说发生了什么,让你有这样
的感受吗?"
},
{
    "role" :"来访者",
    "content" : "我觉得你这样问有点
太直接了。我不太想说那些过去的事情，它
们让我感到很不舒服。",
    "state" : "防御性阻抗",
    "motivation" : "咨询师的提问可能
触及来访者对童年的痛苦回忆，来访者通过
拒绝回答问题以防止触及深层痛苦。"
},
```

```
{
    "role" :"counselor",
    "content" : "You mentioned feeling distant from your
mother. Could you tell me more about what happened that
made you feel this way?"
},
{
    "role" : "client",
    "content" : "I feel that question is a bit too direct. I
don't really want to talk about those past experiences—they
make me feel uncomfortable.",
    "state" : "Defensive Resistance",
    "motivation" : "The counsellor's question may touch
on painful childhood memories. The client avoids answering in
order to protect themselves from deeper emotional pain."
},
```

(a) Chinese Version .... (b) English Version

Figure 8: Example dataset with resistant behavior annotations

(a) Chinese Version .... (b) English Version

Figure 9: Examples of conversation incorporating reasoning processes

参与研究同意书	Informed Consent Form for Counsellor Participation
一、研究背景与目的
本研究旨在构建一个能够在心理咨询对话中适时产生阻抗行为的来访者对话模型。研究将结合心理学理论与大语言模型技术，通过人工标注、验证与评估，提升模型在模拟真实来访者心理反应方面的合理性与可解释性。
二、参与者角色与任务
作为心理咨询师，您将参与以下研究环节：
1.对心理咨询对话数据进行标注，包括来访者反应类型及其心理动机；
2.对模型生成的标注结果进行验证与一致性评估；
3.对模型生成的候选对话回复进行人工评分，用于模型效果评估与强化学习训练；
4.对最终模型产生的实验结果从专业的角度进行人工评估。
您的专业判断将用于提升数据质量与研究可信度。
三、研究流程说明
研究过程中，您将接触到经过匿名化处理的心理咨询对话文本或模型生成内容。所有任务均以文本形式进行，不涉及真实来访者身份信息，也不要求您回忆或提供个人临床案例。
四、潜在风险与免责说明
本研究不涉及任何临床干预或现实咨询行为，对您不构成医疗、法律或职业风险。
部分对话内容可能涉及情绪困扰或心理压力相关主题，若您在参与过程中感到不适，可随时暂停或退出研究，且无需说明理由。
五、数据使用与保密声明
✓ 所有标注、评估及反馈数据仅用于科研目的；
✓ 研究数据将以匿名形式存储与分析，您的个人身份信息不会出现在任何公开成果中；
✓ 研究成果可能以论文、报告或学术展示形式发表，但不会披露任何可识别个人身份的信息。
六、自愿参与与退出权利
您的参与完全出于自愿。您有权在研究的任何阶段选择退出，退出不会带来任何不利后果。
七、同意声明
我已阅读并理解上述研究说明，清楚本研究的目的、流程及可能涉及的内容。我同意自愿参与本研究，并允许研究团队在遵循保密原则的前提下使用我提供的标注与评估数据用于科研目的。	**1. Research Background and Purpose**
This study aims to construct a client dialogue model that can appropriately exhibit resistance reactions during psychological counseling conversations. By integrating psychological theory with large language models, the study involves data annotation, verification, and human evaluation to improve the realism and interpretability of simulated client behaviors.
2. Role of Participants
As a professional psychological counselor, you may be invited to participate in the following tasks:
☐ Annotating counseling conversations with reaction types and underlying psychological motivations;
☐ Verifying and evaluating model-generated annotations;
☐ Scoring model-generated candidate responses for quality assessment and reinforcement learning;
☐ Conducting a manual assessment of the experimental results generated by the final model from a professional perspective.
Your professional expertise will contribute directly to the quality and validity of the research.
3. Research Procedure
During the study, you will review anonymized counseling conversation texts or model-generated content. All materials are text-based and do not contain identifiable information about real clients. You will not be asked to recall or provide personal clinical cases.
4. Potential Risks and Disclaimer
This study does not involve clinical intervention or real-world counselling activities and poses no medical, legal, or professional risk.
Some content may involve emotional distress or psychological difficulties. If you feel uncomfortable at any point, you may pause or withdraw from the study without providing a reason.
5. Data Use and Confidentiality
✓ All annotations, evaluations, and feedback will be used solely for research purposes;
✓ Data will be stored and analyzed in anonymized form, and no personally identifiable information will be disclosed;
✓ Research findings may be published in academic papers or reports, but no information that could identify you will be made public.
6. Voluntary Participation and Right to Withdraw
Your participation is entirely voluntary. You may withdraw from the study at any time without any negative consequences.
7. Consent Statement
I have read and understood the information above. I am aware of the purpose, procedures, and nature of this study. I voluntarily agree to participate and consent to the use of my annotations and evaluations for research purposes under conditions of confidentiality.

(a) Chinese Version   (b) English Version

Figure 10: Informed Consent Form for Counsellor Participation

{本次咨询来访者表示最近生活工作压力变大，快乐感缺失，不知道怎么办才好}

咨询师: 听起来你最近确实承受着很大的压力。工作项目多、加班频繁，再加上家庭琐事，确实会让人感到身心俱疲。

来访者:

[Profile Reflection] 来访者的压力源来自工作和家庭，这与她的Presenting Problems中的"生活工作压力大"和"快乐感缺失"相符。她表现出对现状的不满和疲惫感。

[Situation Awareness] 咨询师的回应是共情和确认，这有助于建立信任，使来访者愿意继续分享。

[Reaction Decision] 非阻抗反应: 来访者会继续描述她的感受和压力源，表现出能够接受继续探索的态度。

嗯，是的，就是这样。我感觉好像永远都忙不完，连喘口气的时间都没有。这种状态持续了很久，我真的很累。

咨询师: 我理解你的感受，或许可以尝试向他人求助，帮你分担手头的任务。

来访者:

[Profile Reflection] 来访者因Predisposing_Factors中的完美主义倾向和对他人评价的敏感，长期回避求助，内心存在自我否定和脆弱感。

[Situation Awareness] 咨询师的共情回应触及了来访者核心的自我价值感，可能引发其防御机制。

[Reaction Decision] 防御性阻抗: 来访者质疑咨询师的建议，将求助行为与自我价值和脆弱性联系起来，试图保护自己的完美主义形象。

我觉得你可能不了解我的处境。我从小到大一直被灌输"要坚强"的观念，开口求助对我来说真的很难。

咨询师: 我理解这种矛盾感。从小形成的观念确实很难改变。不过，真正的坚强也包括知道何时需要支持。

来访者:

[Profile Reflection] 来访者正处于对自身完美主义倾向和独立观念的强烈冲突中，这种内在矛盾让她感到困惑和不安。

[Situation Awareness] 咨询师试图用"真正的坚强也包括知道何时需要支持"来化解她的矛盾，这触及了她核心的自我认知和价值观，容易引起她的负面情绪。

[Reaction Decision] 情绪性阻抗: 来访者通过表达迷茫与委屈的情绪，将内心的情绪外化，以防止被触及深层的不安全感和失控恐惧。

我彻底不知道该怎么办了。我一直以为坚强就是独自面对一切，承认需要帮助就像是在承认自己的失败。

咨询师: 我理解这种矛盾的心情。一方面想要表达自己的感受和需求，另一方面又担心被评判。尽管面临很大的压力，你仍在努力完成工作，这一点很棒。

来访者:

[Profile Reflection] 来访者正在经历现实和认知之间的冲突，渴望得到理解与肯定，这种情绪模式与Protective_Factors中的"容易接受鼓励与认可"相匹配。

[Situation Awareness] 咨询师从来访者的角度思考问题，表达对来访者认真负责态度的肯定，这有助于促进来访者的表达。

[Reaction Decision] 促进性反应: 来访者认为进入了一个安全的氛围，愿意进一步分享自己的感受与对解决问题的期望。

感谢你的肯定，我面临压力的时候，总喜欢找一个人倾诉，说完就感觉好多了。但是这不能从根本上解决我的问题。

咨询师: 这确实是一个很重要的发现。你是否尝试过与给你压力的人进行沟通呢？直接说出自己的诉求也是一个很不错的方式。

来访者:

[Profile Reflection] 来访者尝试将当前困扰与曾经的经历联系起来，这可能会激起来访者Perpetuating_Factors中"负面沟通循环"、"不善于表达"等过往的失败回忆。

[Situation Awareness] 咨询师的回应引起了来访者对不美好经历的回想，来访者不愿意直面自己的缺点，可能逃避咨询师的问题。

[Reaction Decision] 回避性阻抗: 来访者试图将焦点从痛苦的回忆转移到当前的困扰上，以保护自己免受深层创伤的侵扰。

我还是更想知道怎样才能减轻压力，我觉得自己比较擅长单方面诉说，但说的次数多了也不那么管用。

咨询师: 我理解，我们可以先聚焦在当下的压力管理上。你刚才提到倾诉让你感觉好多了，这其实已经是一种很有效的应对方式了。除了倾诉之外，你觉得还有哪些时刻或者做哪些事情时，你会感到稍微轻松一些？

来访者:

[Profile Reflection] 来访者在咨询师不再追问沟通话题后感到安全，愿意分享自己的积极体验。Protective_Factors中的"改变意愿强烈"可以很好地反映这一点。

[Situation Awareness] 咨询师采取了灵活的策略，没有强迫来访者直面痛苦话题，而是帮助她识别现有的应对资源，这有助于激发她提供更多的信息。

[Reaction Decision] 促进性反应: 来访者感到被理解和尊重，积极配合探索，愿意分享让她感受到轻松的时刻。

嗯，让我想想。其实我在陪女儿的时候感觉会好一些，看见她开心的样子，那些烦心事我都能暂时忘掉。

Figure 11: ResistClient and SoulChat2.0 Conversation Example (Chinese Version)

{In this session, the client reports increased stress from work and daily life, accompanied by a loss of pleasure and uncertainty about how to cope.}

Counselor: It sounds like you have been under considerable pressure lately. With multiple work projects, frequent overtime, and household responsibilities, it is understandable that you feel physically and mentally exhausted.

Client:

[Profile Reflection] The client's sources of stress stem from work and family obligations, aligning closely with the "high work-life stress" and "loss of pleasure" described in her Presenting Problems. She expresses dissatisfaction and fatigue with her current situation.

[Situation Awareness] The counselor's response offers empathy and validation, which helps build trust and encourages the client to continue sharing.

[Reaction Decision] Non-resistant reaction: The client continues to describe her feelings and stressors, demonstrating willingness to engage in further exploration.

Yes, that's exactly how it is. I feel like I'm constantly busy with no time to breathe. This state has persisted for a long time, and I am truly exhausted.

Counselor: I understand how you feel. Perhaps you could try seeking help from others to share some of your current tasks.

Client:

[Profile Reflection] Due to the client's predisposing perfectionistic tendencies and sensitivity to others' evaluations, she has long avoided asking for help, harboring underlying self-criticism and vulnerability

[Situation Awareness] The counselor's empathetic suggestion touches on the client's core sense of self-worth, potentially activating defensive mechanisms.

[Reaction Decision] Defensive resistance: The client questions the counselor's suggestion, linking help-seeking to diminished self-worth and vulnerability in order to protect her perfectionistic self-image.

I think you may not fully understand my situation. From an early age, I was taught to "be strong," so asking for help is genuinely difficult for me.

Counselor: I understand this inner conflict. Beliefs formed in childhood can indeed be hard to change. However, true strength also includes knowing when to seek support.

Client:

[Profile Reflection] The client is experiencing strong internal conflict between her perfectionistic tendencies and notions of independence, leading to confusion and discomfort.

[Situation Awareness] The counselor's attempt to reframe strength as including the ability to seek support directly challenges her core self-concept and values, likely eliciting negative emotions.

[Reaction Decision] Emotional resistance: The client externalizes feelings of confusion and grievance to avoid confronting deeper insecurity and fear of loss of control.

I really don't know what to do anymore. I always thought strength meant facing everything alone—admitting I need help feels like acknowledging failure.

Counselor: I understand this conflicting feeling. On one hand, you want to express your needs; on the other, you worry about being judged. Despite the intense pressure, you continue to handle your work responsibly, which is commendable.

Client:

[Profile Reflection] The client is navigating a conflict between reality and her cognitions, craving understanding and validation. This emotional pattern aligns with the "readiness to accept encouragement and recognition" noted in her Protective Factors.

[Situation Awareness] By viewing the issue from the client's perspective and affirming her responsible attitude, the counselor fosters greater openness.

[Reaction Decision] Facilitative reaction: Feeling understood and respected, the client engages more actively and expresses willingness to share her feelings and expectations for resolution.

Thank you for the affirmation. When I'm under pressure, I often feel better after talking to someone. However, this doesn't address the root of my problems.

Counselor: That is an important insight. Have you considered communicating directly with those contributing to your stress? Expressing your needs openly can also be an effective approach.

Client:

[Profile Reflection] Linking current distress to past experiences may activate the client's perpetuating factors, such as "negative communication cycles" and "difficulty expressing needs," evoking memories of previous failures.

[Situation Awareness] The counselor's suggestion triggers recollection of unpleasant experiences. The client, reluctant to confront her own shortcomings, may evade the question.

[Reaction Decision] Avoidant resistance: The client attempts to shift focus from painful memories to current distress, protecting herself from deeper emotional intrusion.

I'd rather know how to reduce the pressure itself. I'm better at one-sided venting, but even that becomes less effective over time.

Counselor: I understand. We can focus on immediate stress management for now. You mentioned that venting helps you feel better—that is already a valuable coping strategy. Apart from talking, are there other moments or activities that make you feel even slightly more relaxed?

Client:

[Profile Reflection] Feeling safe after the counselor drops the communication topic, the client becomes willing to share positive experiences. This reflects the "strong motivation for change" highlighted in her Protective Factors.

[Situation Awareness] By adopting a flexible approach and helping the client identify existing resources rather than forcing confrontation with painful topics, the counselor encourages further disclosure.

[Reaction Decision] Facilitative reaction: Feeling understood and respected, the client cooperates actively and shares moments that bring her relief.

Let me think. Actually, spending time with my daughter helps. Seeing her happy makes me temporarily forget my worries.

Figure 12: ResistClient and SoulChat2.0 Conversation Example (English Version)

Figure 13: Comparison of client simulation responses between ResistClient and the prompt-based GPT-5.1.