HYBRID-REGRESSIVE NEURAL MACHINE TRANSLATION

ABSTRACT

Although the non-autoregressive translation model based on iterative refinement has achieved comparable performance to the autoregressive counterparts with faster decoding, we empirically found that such aggressive iterations make the acceleration rely heavily on small batch size (e.g., 1) and computing device (e.g., GPU). By designing synthetic experiments, we highlight that iteration times can be significantly reduced when providing a good (partial) target context. Inspired by this, we propose a two-stage translation prototype – Hybrid-Regressive Translation (HRT). HRT first jumpily generates a discontinuous sequence by autoregression (e.g., make a prediction every k tokens, $k > 1$). Then, with the help of the partially deterministic target context, HRT fills all the previously skipped tokens with one iteration in a non-autoregressive way. The experimental results on WMT'16 En↔Ro and WMT'14 En↔De show that our model outperforms the state-of-the-art non-autoregressive models with multiple iterations, even autoregressive models. Moreover, compared with autoregressive models, HRT can be steadily accelerated 1.5 times regardless of batch size and device.

1 INTRODUCTION

Although autoregressive translation (AT) has become the *de facto* standard for Neural Machine Translation Bahdanau et al. (2015), its nature of generating target sentences sequentially (e.g., from left to right) makes it challenging to respond quickly in a production environment. One straightforward solution is the non-autoregressive translation (NAT) Gu et al. (2017), which predicts the entire target sequence in one shot. However, such one-pass NAT models lack dependencies between target words and still struggles to produce smooth translations, despite many efforts developed Ma et al. (2019); Guo et al. (2019a); Wang et al. (2019b); Shao et al. (2019); Sun et al. (2019).

Recent studies show that extending one-pass NAT to multi-pass NAT, so-called iterative refinement (IR-NAT), is expected to break the performance bottleneck Lee et al. (2018); Ghazvininejad et al. (2019); Gu et al. (2019); Guo et al. (2020); Kasai et al. (2020). Unlike one-pass NAT, which outputs the prediction immediately, IR-NAT takes the translation hypothesis from the previous iteration as a reference and regularly polishes the new translation until achieving the predefined iteration count I or no changes appear in the translation. Compared with AT, IR-NAT with I=10 runs 2-5 times faster with a considerable translation accuracy, as reported by Guo et al. (2020).

Figure 1: Relative speedup ratio (α) compared MP with AT on GPU (solid) and CPU (dashed). The value of α denotes running faster (positive) or slower (negative) $|\alpha|$ times than AT.

However, we highlight that the fast decoding of IR-NAT heavily relies on *small batch size* and *GPU*, which is rarely mentioned in prior studies [1]. Without loss of generality, we take Mask-Predict (MP)

---

[1]Unfortunately, such a decoding setting is not common in practice. NMT systems deployed on GPUs tend to use larger batches to increase translation throughput, while the batch size of 1 is used more frequently in offline systems running on CPUs. e.g., smartphones.

Ghazvininejad et al. (2019) as an example, a typical IR-NAT paradigm based on the conditional masked language model. Figure 1 illustrates that when the batch exceeds 8, MP(I=10) is already running slower than AT, and the situation is even worse on CPU.

To tackle this problem, we first design a synthetic experiment to understand the relationship between target context and iteration times. We mask some proportion tokens on the translation generated by a pretrained AT and take it as the decoder input of the pretrained MP. Then we surprisingly found that even masking 70% AT hypothesis, the remaining target context can help MP(I=1) to compete with the standard MP(I=10) (Figure 2). This result confirms that decoding with multiple iterations in NAT is unnecessary when providing a good (partial) reference hypothesis.

Inspired by this, we propose a two-stage translation prototype——Hybrid-Regressive Translation (HRT). After encoding, HRT first uses an autoregressive decoder (called Skip-AT) to produce a discontinuous translation hypothesis. Concretely, at decoding step i, the SKip-AT decoder immediately predicts the $(i + k)$-th token y_{i+k} without generating $y_{i+1}, \ldots, y_{i+k-1}$, where k is a hyperparameter and $k > 1$. Then, a non-autoregressive decoder like MP (called Skip-MP) predicts previously skipped tokens with one iteration according to the deterministic context provided by Skip-AT. Since both Skip-AT and Skip-MP share the same model parameters, HRT does not increase parameters significantly. To train HRT effectively and efficiently, we further propose *joint training guided by curriculum learning* and *mixed distillation*. Experimental results on WMT En↔Ro and En↔De show that HRT is far superior to existing IR-NATs and achieves comparable or even better accuracy than AT with a consistent 50% decoding speedup on varying batch sizes and devices (GPU, CPU).

2 BACKGROUND

Given a source sentence $\boldsymbol{x} = \{x_1, x_2, \ldots, x_M\}$ and a target sentence $\boldsymbol{y} = \{y_1, y_2, \ldots, y_N\}$, there are several ways to model $P(\boldsymbol{y}|\boldsymbol{x})$:

Autoregressive translation (AT) is the dominant approach in NMT, which decomposes $P(\boldsymbol{y}|\boldsymbol{x})$ by chain rules:

$$P(\boldsymbol{y}|\boldsymbol{x}) = \prod_{t=1}^{N} P(y_t|\boldsymbol{x}, y_{<t}) \tag{1}$$

where $y_{<t}$ denotes the generated prefix translation before time step t. However, the existence of $y_{<t}$ requires the model must wait for y_{t-1} to be produced before predicting y_t, which hinders the possibility of parallel computation along with time step.

Non-autoregressive translation (NAT) is first proposed by Gu et al. (2017), allowing the model to generate all target tokens simultaneously. NAT replaces $y_{<t}$ with target-independent input $\boldsymbol{z}$ and rewrites Eq. 1 as:

$$P(\boldsymbol{y}|\boldsymbol{x}) = P(N|x) \prod_{t=1}^{N} P(y_t|\boldsymbol{x}, \boldsymbol{z}) \tag{2}$$

In Gu et al. (2017), they monotonically copy the source embedding as $\boldsymbol{z}$ according to a fertility model. Subsequently, the researchers developed more advanced methods to enhance $\boldsymbol{z}$, such as adversarial source embedding Guo et al. (2019a), reordered source sentence Ran et al. (2019), latent variables Ma et al. (2019); Shu et al. (2019) etc, but there still is a huge performance gap between AT and NAT.

Iterative refinement based non-autoregressive translation (IR-NAT) extends the traditional one-pass NAT by introducing the multi-pass decoding mechanism Lee et al. (2018); Ghazvininejad et al. (2019); Gu et al. (2019); Guo et al. (2020); Kasai et al. (2020). IR-NAT applies a conversion function $\mathcal{F}$ on the deterministic hypothesis of previous iteration $\boldsymbol{y}\prime$ as the alternative to $\boldsymbol{z}$. Common implementations of $\mathcal{F}$ include identity Lee et al. (2018), random masking Ghazvininejad et al. (2019) or random deletion Gu et al. (2019) etc. Thus, we can predict $\boldsymbol{y}$ by:

$$P(\boldsymbol{y}|\boldsymbol{x}) = \prod_{t=1}^{N'} P(y'_{m(t)}|\boldsymbol{x}, \mathcal{F}(\boldsymbol{y}\prime)) \tag{3}$$

where N' is the number of refined tokens in $\mathcal{F}(\boldsymbol{y}\prime)$, m(t) is the real position of t-th refined token in $\boldsymbol{y}\prime$. In this way, the generation process of IR-NAT is simple: first, the NAT model produces

Figure 2: Comparison of four masking strategies {Head, Tail, Random, Chunk} in synthetic experiments on WMT En→Ro (Left) and En→De (Right) test sets. For Chunk, we test the chunk size from {2, 3, 4}. Dashed lines represent Mask-Predict's scores reported by Ghazvininejad et al. (2019). b stands for "beam size" while I stands for "the number of iterations".

an inaccurate translation as the initial hypothesis, and then iteratively refines it until converge or reaching the maximum number of iterations.

Mask-Predict (MP) is a typical instance of IR-NAT, trained by a conditional masked language model objective like BERT Devlin et al. (2019). In this work, we use MP as the representation of IR-NAT due to its excellent performance and simplification. In MP, $\mathcal{F}$ randomly masks some tokens over the sequence in training but selects those predicted tokens with low confidences at inference.

3 IS ITERATIVE REFINEMENT ALL YOU NEED?

As mentioned earlier, IR-NAT with multiple iterations slows down severely in some cases. It is natural to think of reducing iterations to alleviate it. This section starts from synthetic experiments on WMT'16 En→Ro and WMT'14 En→De to verify the assumption that a sufficiently good decoder input can help reduce iterations. Here we construct the "good" decoder input from the translation hypothesis produced by an AT model.

Models We use the official MP models released by Ghazvininejad et al. (2019) [2]. Since the authors did not publish their AT baselines, we use the same data to retrain AT models with the standard Transformer-Base configuration Vaswani et al. (2017) and obtain comparable performance with theirs (see Appendix A for more details).

Decoding AT models decode with beam sizes of 5 on both tasks. Then, we replace a certain percentage of AT translation tokens with $<mask>$ and use it as input to the MP model (see below for replacement strategy). Unlike the standard MP model that uses a large beam size (e.g., 5) and iterates several times (e.g., 10), the MP model used here only iterates once with beam size 1. We substitute all input $<mask>$ with MP's predictions to obtain the final translation. We report case-sensitive tokenized BLEU score by *multi-bleu.perl*.

Mask Strategy We tested 4 strategies to mask AT translations: Head, Tail, Random and Chunk. Given the masking rate p_{mask} and the translation length N, the number of masked tokens is $N_{mask}=\max(1, \lfloor N \times p_{mask} \rfloor)$. Then Head/Tail always masks the first/last N_{mask} tokens, while Random masks the translation randomly. Chunk is slightly different from the above strategies. It first divides the target sentence into C chunks, where $C = \text{Ceil}(N/k)$ and k is the chunk size. Then in each chunk, we retain the first token, but mask other k-1 tokens. Thus, the actual masking rate in Chunk is 1-1/k instead of p_{mask}. To exclude randomness, we ran Random three times with different seeds and report the average results.

3.1 RESULTS

The experimental results are illustrated in Figure 2, where we can see that:

---

[2]https://github.com/facebookresearch/Mask-Predict

Table 1: Examples of training samples. $<s2>$ is a special $$ for k=2. $<m>$ is short for $<mask>$.

Mode	Input	Target
AT	$, y_1, y_2, y_3, y_4$	$y_1, y_2, y_3, y_4, $
MP	$y_1, <m>, <m>, y_4, <m>$	$\text{PAD}, y_2, y_3, \text{PAD}, $
Skip-AT (k=2)	$<s2>, y_2, y_4$	$y_2, y_4, $
Skip-MP (k=2)	$<m>, y_2, <m>, y_4, <m>, $	$y_1, \text{PAD}, y_3, \text{PAD}, , \text{PAD}$

A balanced bidirectional context is critical. Compared with `Tail` and `Head`, it is obvious that `Rand` and `Chunk` both have better performance. We attribute it to the benefit of the bidirectional context in `Rand` and `Chunk` Devlin et al. (2019), because `Tail` and `Head` can only provide unidirectional context (i.e., prefix or suffix). In addition, `Chunk` is superior to `Rand`, which indicates that the balanced distribution of deterministic tokens is necessary [3].

Small beams and one iteration are sufficient. Compared with the standard MP with the beam size of 5 and 10 iterations, it is interesting to find that even if only 30%-40% of the AT translations are exposed, our MP using greedy search and one iteration can achieve quite comparable performance.

4 HYBRID-REGRESSIVE TRANSLATION

A limitation in the above synthetic experiment is that the MP decoder input comes from an AT hypothesis, which is impossible in practice [4]. To solve this problem as well as inspired by the `Chunk` strategy's success, we propose a two-stage translation paradigm called Hybrid-Regressive Translation (HRT). Briefly speaking, HRT can autoregressively generate a discontinuous sequence with chunk size k (stage I), and non-autoregressively fill the skipped tokens (stage II) in one model. Thus, the standard AT can be regarded as the special case of HRT when k=1 without stage II.

4.1 ARCHITECTURE

Overview. Our HRT consists of three parts: encoder, Skip-AT decoder (for stage I), and Skip-MP decoder (for stage II). All components adopt the Transformer architecture Vaswani et al. (2017): the encoder contains self-attention sublayers and feedforward sublayers, and additional cross-attention sublayers are added to the decoder. The two decoders have the same network structure and share model parameters, leading to the same parameter size compared to the standard MP. The only difference between the two decoders lies in the masking mode in the self-attention sublayer. The Skip-AT decoder masks future tokens to guarantee strict left-to-right generation, while the Skip-MP decoder eliminates this limitation to leverage the bi-directional context.

Simplified relative position representation. Another difference from the standard MP architecture is that our decoder self-attention equips with relative position representation (RPR) Shaw et al. (2018) to enable the model to capture the positional relationship between words easily. Precisely, the decoder self-attention with RPR is calculated by:

$$O_i = \text{Softmax}\left(\frac{Q_i(K^T + R_i)}{\sqrt{d_k}}\right)V \tag{4}$$

where R_i is the relative position embedding [5]. Note that Eq. 4 only injects the relative positional representation in `Key` ($K^T + R_i$) without involving `Value` V. We found that this simplification has no negative impact on performance but significantly saves memory footprint.

No target length predictor. Most previous NAT methods need to jointly train the translation model with an independent translation length predictor. However, such a length predictor is unnecessary for us because the translation length is a by-product of Skip-AT, e.g., $N_{nat} = k \times N_{at}$, where N_{at} is the sequence length produced by Skip-AT [6]. Another bonus is that we can avoid carefully tuning the weighting coefficient between the length loss and the token prediction loss.

---

[3] `Chunk` guarantees that each unmasked token can meet at least one deterministic token within the window size of k (left or right).

[4] We can directly return AT predictions as translation results without going through MP.

[5] $R_i = \text{Embed}(\text{clip}(i, 1), \ldots, \text{clip}(i, N))$, where $\text{clip}(i, j) = \max(w, \min(w, j - i))$, w is the window size.

[6] More precisely, N_{nat} here is the maximum target length rather than the realistic length because multiple $$ may be predicted in the last k tokens.

4.2 TRAINING

Training HRT models is not trivial because a single HRT model needs to learn to generate sequences by both autoregression and non-autoregression. This section will introduce three details of training HRT models, including chunk-aware training samples, curriculum learning, and mixed distillation. We describe the entire training algorithm in Appendix B.

Chunk-aware training samples. As listed in Table 1, the training samples for Skip-AT and Skip-MP are different from the standard AT and MP. Compared with AT, Skip-AT shrinks the sequence length from N to N/k. Moreover, MP has the opportunity to mask any token over the target sequence without considering the position. However, the masking pattern in Skip-MP is deterministic, i.e., masking all non-first tokens in each chunk. Therefore, we can say that the training sample for Skip-AT and Skip-MP is in a chunk-aware manner.

Curriculum learning. Unfortunately, direct joint training of Skip-AT and Skip-MP is problematic because the chunk-aware training samples cannot make full use of all the tokens in the sequence. For example, in Table 1, the target tokens y_1 and y_3 have no chance to be learned as the decoder input of either Skip-AT or Skip-MP. However, there is no such problem in AT and MP. Therefore, we propose to gradually transition from joint training {AT, MP} to {Skip-AT, Skip-MP} through curriculum learning Bengio et al. (2009). In other words, the model is trained from chunk size 1 to chunk size k (k>1). More concretely, given a batch of original sentence pairs $B = (\mathbf{x}_i, \mathbf{y}_i)|_{i=1}^n$ and let the proportion of chunk size k in B be p_k, we start with $p_k = 0$ and construct the training samples of AT and MP for all pairs. And then we gradually increase p_k to introduce more learning signals for Skip-AT and Skip-MP until p_k=1. In implement, we schedule p_k by:

$$p_k = \left(\frac{t}{T}\right)^{\lambda} \tag{5}$$

where t and T are the current and total training steps, respectively. λ is a hyperparameter and we use λ=1 to increase p_k in a linear manner for all experiments.

Mixed Distillation. NAT models generally use the distillation data generated by AT models due to more smoothing data distribution Zhou et al. (2020). However, making full use of distillation data may miss the diversity in raw data. To combine the best of both worlds, we propose a simple and effective approach – *Mixed Distillation* (MixDistill). During training, MixDistill randomly samples a target sentence from the raw version $\boldsymbol{y}$ with probability p_{raw} or its distillation version $\boldsymbol{y}^*$ with probability 1-p_{raw}, where p_{raw} is a hyperparameter [7]. By learning from raw target sentences, we empirically found that HRT is less prone to over-fit in some simple tasks (e.g., WMT'16 En→Ro).

4.3 INFERENCE

After encoding, the Skip-AT decoder starts from $<sk>$ to autoregressively generate a discontinuous target sequence $\boldsymbol{y}_{at} = (z_1, z_2, \ldots, z_m)$ with chunk size k until meeting $$. Then we construct the input of Skip-MP decoder $\boldsymbol{x}_{mp}$ by appending $k - 1$ $<mask>$ before every z_i. The final translation is generated by replacing all $<mask>$ with the predicted tokens by Skip-MP decoder with one iteration. If there are multiple $$ existing, we truncate to the first $$. Note that the beam size b_{at} in Skip-AT can be different from the beam size b_{mp} in Skip-MP as long as st. $b_{at} \geq b_{mp}$. If $b_{at} > b_{mp}$, then we only feed the Skip-MP with the top b_{mp} Skip-AT hypothesis. Finally, we choose the hypothesis with the highest score:

$$score(\hat{\boldsymbol{y}}) = \underbrace{\sum_{i=1}^{m}(z_i|\boldsymbol{x}, z_{<i})}_{\text{Skip-AT score}} + \underbrace{\sum_{i=0}^{m-1}\sum_{j=1}^{k-1}(\hat{y}_{i\times k+j}|\boldsymbol{x}, \boldsymbol{x}_{mp})}_{\text{Skip-MP score}} \tag{6}$$

where z_i=$\hat{y}_{i\times k}$. In Appendix C, we summarized the comparison with the existing three methods from the aspects of decoding step and calculation cost, including AT, MP, and semi-autoregressive translation (SAT) Wang et al. (2018). Besides, thanks to the joint training of chunk size 1 and k simultaneously, the HRT model can also behave like a standard AT model by forcing decoding by

---

[7]Training with full raw data or full distillation data can be regarded as the special case of MixDistill when p_{raw}=1 or p_{raw}=0.

Table 2: The BLEU scores of our proposed HRT and the baseline methods on four tasks. Unless otherwise stated, the used beam size is 5. "?" denotes dynamic iterations. "20L" stands for using a 20-layer encoder. "NPD" is short for Noisy Parallel Decoding. All HRT models only iterate once by non-autoregression.

| | System | Iterations | WMT'16 | | WMT'14 | |
			En-Ro	Ro-En	En-De	De-En
ATs	Transformer	-	34.25	34.40	27.45	31.86
	Transformer-20L	-	-	-	28.79	33.02
Existing NATs	Iterative Refinement Lee et al. (2018)	?	29.66	30.30	21.54	25.43
	Mask-Predict Ghazvininejad et al. (2019)	1	27.32	28.20	18.05	21.83
	Mask-Predict Ghazvininejad et al. (2019)	10	33.08	33.31	27.03	30.53
	LevTransformer Gu et al. (2019)	?	-	-	27.27	-
	JM-NAT Guo et al. (2020)	10	33.52	33.72	27.69	32.24
	SAT (k=2) Wang et al. (2018)	-	-	-	26.90	-
	FCL-NAT (NPD 9) Guo et al. (2019b)	1	-	-	25.75	29.50
Our models	HRT (b_{at}=1, b_{mp}=1)	1	34.11	34.28	27.85	31.80
	HRT (b_{at}=5, b_{mp}=1)	1	34.36	34.55	27.98	31.93
	HRT (b_{at}=5, b_{mp}=5)	1	**34.53**	**34.80**	28.10	32.07
	HRT-20L (b_{at}=1, b_{mp}=1)	1	-	-	28.79	32.86
	HRT-20L (b_{at}=5, b_{mp}=1)	1	-	-	28.90	33.06
	HRT-20L (b_{at}=5, b_{mp}=5)	1	-	-	**28.99**	**33.08**

chunk size one (denoted as C_d=1). In this way, we can only use the Skip-AT decoder to generate the entire sequence without the help of Skip-MP. Thus, C_d=1 can be regarded as the performance upper bound when the decoding chunk size is k (denoted as C_d=k).

5 EXPERIMENTS

Datasets. We conducted experiments on four widely used tasks: WMT'16 English↔Romanian (En↔Ro, 610k) and WMT'14 English↔German (En↔De, 4.5M). We replicated the same data processing as Ghazvininejad et al. (2019) for fair comparisons.

AT teachers for distillation. Since Ghazvininejad et al. (2019) only release the distillation data of En↔Ro, not En↔De, we retrained the AT teacher models of En↔De to produce the distillation data. Specifically, Ghazvininejad et al. (2019) use Transformer-Large as the teacher, but we use the deep PreNorm Transformer-Base with a 20-layer encoder, which is faster to train and infer with comparable performance Wang et al. (2019a).

Models and hyperparameters. We ran all experiments on 8 TITAN X (Pascal) GPUs. Unless noted otherwise, we use the chunk size k=2 and λ=1. p_{raw}=0.5 for En↔Ro and p_{raw}=0.8 for En↔Ro according to validation sets. The windows size of RPR is 16 [8]. HRT models are finetuned on pretrained AT models for the same training steps. Other training hyperparameters are the same as Vaswani et al. (2017) or Wang et al. (2019a) (using deep-encoder). Please refer to them for more details.

Translation quality. Table 2 reports the BLEU scores on four tasks. First of all, we can see that IR-NAT models significantly outperform those one-pass NAT models (e.g., SAT, FCL-NAT, FlowSeq). However, our small beam model (b_{at}=b_{mp}=1) can defeat the existing multiple-iteration models. Furthermore, when the beam sizes increase to 5, HRT equipped with a standard 6-layer encoder achieves +1.0 BLEU point improvement in En↔Ro compared to the previous best results Guo et al. (2020). Even on harder En↔De tasks, we also outperform them with a 0.4 BLEU score. We can easily trade-off between performance and speed by using b_{at}=5 but b_{mp}=1. Not only NAT models, but also we are surprised to find that HRT can even surpass the AT models trained from scratch. We attribute it to two reasons: (1) HRT is fine-tuned on a well-trained AT model, making training easier; (2) Mixing up AT and NAT has a better regularization effect than training alone. Besides, in line with Guo et al. (2020), which demonstrate that the encoder is critical for NAT, we can obtain a further improvement of about +0.8 BLEU when using a deeper encoder.

Translation speed. Unlike the previous works that only run the model on GPU with batch size of 1, we systematically test the decoding speed using varying batch sizes and devices on WMT'14

---

[8]For autoregressive baselines, adding RPR in the Transformer decoder did not bring obvious improvement over the vanilla Transformer. For example, on WMT'14 En→De, Transformer=27.45 and Transformer+RPR=27.34.

Figure 3: Comparison of decoding speed w.r.t. batch size and computing device on WMT'14 En→De task. The x-axis is the relative speed compared to the corresponding autoregressive models (dashed lines at x=1). GPU:TITAN X (Pascal), CPU:Intel(R) Xeon(R) E5-2680 v3 @ 2.50GHz. MP10 denotes the MP model with 10 iterations. HRT{#1}−{#2} denotes HRT with b_{at}=#1 and b_{mp}=#2.

Table 3: Performance against different data strategies. C_d=1 represents decoding the HRT model in an autoregressive manner.

Lang.	C_d	Raw	Dist.	Mix Dist.
En→Ro	k	33.85	33.39	**34.08**
	1	34.31	33.54	**34.55**
En→De	k	26.37	28.00	**28.10**
	1	27.60	28.42	**28.51**

Table 4: The effect of training by different chunk sizes. Latency is tested in batch size of 16 using C_d=k and b_{at}=b_{mp}=1.

Chunk	BLEU		Latency (sec.)	
(k)	C_d= k	C_d= 1	GPU	CPU
2	**34.11**	33.86	20.0	70.5
3	31.15	33.78	13.0	54.6
4	28.22	**34.12**	**12.2**	**53.9**

En→De test set (see Figure 3). By default, the beam size is 5. It can be seen that although HRT is slower than MP10 when running on GPU with a batch size of 1, MP10 dramatically slows down as the batch size increases. In contrast, HRT5-1 is consistently more than 50% faster than AT without changing with the environment. These results show that our HRT can be an effective and efficient substitute for AT and IR-NAT.

6 ANALYSIS

Effect of Mixed Distillation. In Table 3, we compared different data strategies, including raw data (Raw), sequence-level knowledge distillation (Dist.), and mixed distillation (Mix Dist.). Overall, Mix Dist. is superior to other methods across the board, which indicates that training with raw data and distillation data is complementary. In addition, we also find that the performance of the distillation data is lower than the raw data on En→Ro task, which is against the previous results. As interpreted by Zhou et al. (2020), we suspect that when the translation model is strong enough, training by distillation data completely may make the learning too easy and lead to over-fitting.

Effect of chunk size. We tested the chunk size k from {2, 3, 4}, and the results are listed in Table 4. Obviously, we can see that: (1) A large k has more significant acceleration on GPU because fewer autoregressive steps are required; (2) As k increases, the performance of hybrid-regressive decoding drops sharply (e.g., k=4 is 6 BLEU points lower than k=2.), but k has little effect on autoregressive modes. It indicates that the training difficulty of Skip-AT increases as k gets bigger.

Effect of decoding mode. We tested the well-trained HRT model with two decoding modes: autoregressive (C_d=1) and hybrid-regressive (C_d=k). Concretely, We divided the test set of WMT'14 En→De into several groups according to the source sentence's length and then compared the two decoding modes in terms of translation speed and accuracy in each group (see Figure 4). First of all, we can see that regardless of the source sentence length, the running speed of C_d=k is consistently faster than C_d=1 on both GPU and CPU, thanks to the shorter autoregressive length. This advantage

Figure 4: Translation speed (Left: GPU, Middle: CPU) and BLEU score (Right) against source sentence's length for different decoding modes in HRT (k=2): C_d=1 denotes decoding by autoregression, while C_d=k denotes hybrid-regressive decoding. Speed is measured at batch size=32, b_{at}=5, b_{mp}=1.

is more evident on CPU: When the source length is less than 10, C_d=k runs 1.6 times faster than C_d=1, while the speedup ratio increases to 2.0 when the source length > 50. As for accuracy, C_d=k has closed performance to C_d=1 when the length is between 10 and 30, but shorter or longer sentences will hurt the performance. This result indicates that if we dynamically adjust the decoding chunk size C_d according to the source sentence's length, the HRT model can be expected to improve the performance further at the expense of a certain speed.

Ablation study. We also did an ablation study on WMT'16 En→Ro test set. As shown in Table 5, we can see that all introduced techniques help to improve performance. In particular, using mixed distillation prevents the HRT model from over-fitting and leads to +1.1 BLEU points improvement compared to the standard distillation (-MixDistill). In addition, the other three methods, including training the HRT model from a pretrained AT model (FT), using a relative positional representation on decoder (RPR), and using curriculum learning (CL), can bring about 0.3-0.4 BLEU improvements each. It should be noted that removing curriculum learning makes the trained HRT model fail to decode by C_d=1, whose BLEU score is only 5.18.

Table 5: Ablation study on WMT'16 En→Ro test set.

System	AT	HRT	−FT	−RPR	−MixDistill	−CL(q_k=1.0)
BLEU	34.25	34.53	34.14	34.22	33.41	34.22

7 RELATED WORK

Iterative refinement. Lee et al. (2018) first extend NAT from the conventional one-pass manner to the multi-pass manner. They add an additional decoder to learn to recover from a collapsed target sequence to gold one. Mask-Predict Ghazvininejad et al. (2019) simplifies the two-decoder structure by introducing the conditional masked language model objective. During each iteration, Mask-Predict retains partial inputted target tokens according to the prediction confidence, while Lev-Transformer Gu et al. (2019) uses multiple discriminators to judge which tokens should be edited.

Combination of AT and NAT. The idea of incorporating AT in the NAT model is not new Kaiser et al. (2018); Ran et al. (2019); Akoury et al. (2019). The main difference from existing methods lies in the content of AT output, such as latent variables Kaiser et al. (2018), reordered source tokens Ran et al. (2019), syntactic labels Akoury et al. (2019) etc. In contrast, our approach uses the deterministic target tokens, which has been proven effective in Ghazvininejad et al. (2019).

8 CONCLUSION

We have pointed out that NAT, especially IR-NAT, cannot efficiently accelerate decoding when using a large batch or running on CPUs. Through a well-designed synthetic experiment, we highlighted that given a good decoder input, the number of iterations in IR-NAT could be dramatically reduced. Inspired by this, we proposed a two-stage translation paradigm HRT to combine AT and NAT's advantages. The experimental results show that HRT owning equivalent or even higher accuracy and 50% acceleration ratio on varying batches and computing devices is a good substitute for AT.

REFERENCES

Nader Akoury, Kalpesh Krishna, and Mohit Iyyer. Syntactically supervised transformers for faster neural machine translation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1269–1281, 2019.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *3rd International Conference on Learning Representations, ICLR 2015*, 2015.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 41–48, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585161. doi: 10.1145/1553374.1553380. URL https://doi.org/10.1145/1553374.1553380.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Marjan Ghazvininejad, Omer Levy, Yinhan Liu, and Luke Zettlemoyer. Mask-predict: Parallel decoding of conditional masked language models. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 6111–6120, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1633. URL https://www.aclweb.org/anthology/D19-1633.

Jiatao Gu, James Bradbury, Caiming Xiong, Victor OK Li, and Richard Socher. Non-autoregressive neural machine translation. *arXiv preprint arXiv:1711.02281*, 2017.

Jiatao Gu, Changhan Wang, and Junbo Zhao. Levenshtein transformer. In *Advances in Neural Information Processing Systems*, pp. 11179–11189, 2019.

Junliang Guo, Xu Tan, Di He, Tao Qin, Linli Xu, and Tie-Yan Liu. Non-autoregressive neural machine translation with enhanced decoder input. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 3723–3730, 2019a.

Junliang Guo, Xu Tan, Linli Xu, Tao Qin, Enhong Chen, and Tie-Yan Liu. Fine-tuning by curriculum learning for non-autoregressive neural machine translation. *arXiv preprint arXiv:1911.08717*, 2019b.

Junliang Guo, Linli Xu, and Enhong Chen. Jointly masked sequence-to-sequence model for non-autoregressive neural machine translation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 376–385, 2020.

Lukasz Kaiser, Samy Bengio, Aurko Roy, Ashish Vaswani, Niki Parmar, Jakob Uszkoreit, and Noam Shazeer. Fast decoding in sequence models using discrete latent variables. In *International Conference on Machine Learning*, pp. 2390–2399, 2018.

Jungo Kasai, James Cross, Marjan Ghazvininejad, and Jiatao Gu. Parallel machine translation with disentangled context transformer. In *ICML 2020: 37th International Conference on Machine Learning*, 2020.

Jason Lee, Elman Mansimov, and Kyunghyun Cho. Deterministic non-autoregressive neural sequence modeling by iterative refinement. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 1173–1182, Brussels, Belgium, October-November 2018. doi: 10.18653/v1/D18-1149. URL https://www.aclweb.org/anthology/D18-1149.

Xuezhe Ma, Chunting Zhou, Xian Li, Graham Neubig, and Eduard Hovy. Flowseq: Non-autoregressive conditional sequence generation with generative flow. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4273–4283, 2019.

Qiu Ran, Yankai Lin, Peng Li, and Jie Zhou. Guiding non-autoregressive neural machine translation decoding with reordering information. *arXiv preprint arXiv:1911.02215*, 2019.

Chenze Shao, Yang Feng, Jinchao Zhang, Fandong Meng, Xilin Chen, and Jie Zhou. Retrieving sequential information for non-autoregressive neural machine translation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3013–3024, 2019.

Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self-attention with relative position representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, pp. 464–468, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-2074. URL https://www.aclweb.org/anthology/N18-2074.

Raphael Shu, Jason Lee, Hideki Nakayama, and Kyunghyun Cho. Latent-variable non-autoregressive neural machine translation with deterministic inference using a delta posterior. *arXiv preprint arXiv:1908.07181*, 2019.

Zhiqing Sun, Zhuohan Li, Haoqing Wang, Di He, Zi Lin, and Zhihong Deng. Fast structured decoding for sequence models. In *Advances in Neural Information Processing Systems*, pp. 3011–3020, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pp. 6000–6010, 2017.

Chunqi Wang, Ji Zhang, and Haiqing Chen. Semi-autoregressive neural machine translation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 479–488, 2018.

Qiang Wang, Bei Li, Tong Xiao, Jingbo Zhu, Changliang Li, Derek F. Wong, and Lidia S. Chao. Learning deep transformer models for machine translation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1810–1822, Florence, Italy, July 2019a. URL https://www.aclweb.org/anthology/P19-1176.

Yiren Wang, Fei Tian, Di He, Tao Qin, ChengXiang Zhai, and Tie-Yan Liu. Non-autoregressive machine translation with auxiliary regularization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 5377–5384, 2019b.

Chunting Zhou, Jiatao Gu, and Graham Neubig. Understanding knowledge distillation in non-autoregressive machine translation. In *ICLR 2020 : Eighth International Conference on Learning Representations*, 2020.

A   AT Transformer in synthetic experiments

Table 6: Performance of autoregressive models in the synthetic experiment.

AT Transformer	En-Ro	En-De
Vaswani et al. (2017)	-	27.3
Ghazvininejad et al. (2019)	34.28	27.74
Our implementation	34.25	27.45

In the synthetic experiment, we trained all AT models with the standard Transformer-Base configuration: layer=6, dim=512, ffn=2048, head=8. The difference from Ghazvininejad et al. (2019) is that they trained the AT models for 300k steps, but we updated 50k/100k steps on En→Ro and En→De, respectively. Although fewer updates, as shown in Table 6, our AT models have comparable performance with theirs.

B   Training algorithm

Algorithm 1 Training Algorithm for Hybrid-Regressive Translation

---

Input: Training data D including distillation targets, pretrained AT model M_{at}, chunk size k, mixed distillation rate p_{raw}

Output: Hybrid-Regressive Translation model M_{hrt}

1: $M_{hrt} \leftarrow M_{at}$ ▷ finetune on pre-trained AT
2: **for** t in $1, 2, \ldots, T$ **do**
3:      $X = \{x_1, \ldots, x_n\}, Y = \{y_1, \ldots, y_n\}, Y' = \{y'_1, \ldots, y'_n\} \leftarrow$ fetch a batch from D
4:      **for** i in $1, 2, \ldots, n$ **do**
5:          $B_i = (X_i, Y_i^*) \leftarrow$ sampling $Y_i^* \sim \{Y_i, Y'_i\}$ with $P(Y_i) = p_{raw}$ ▷ mixed distillation
6:      **end for**
7:      $p_k \leftarrow$ get the chunk-aware proportion by Eq. 5   ▷ curriculum learning
8:      $B_{c=k}, B_{c=1} \leftarrow B_{:\lfloor n \times p_k \rfloor}, B_{\lfloor n \times p_k \rfloor:}$ ▷ split batch
9:      $B_{c=k}^{at}, B_{c=k}^{mp} \leftarrow$ construct {Skip-AT, Skip-MP} training samples based on $B_{c=k}$
10:     $B_{c=1}^{at}, B_{c=1}^{mp} \leftarrow$ construct {AT, MP} training samples based on $B_{c=1}$
11:     Optimize M_{hrt} using $B_{c=k}^{at} \cup B_{c=1}^{at} \cup B_{c=k}^{mp} \cup B_{c=1}^{mp}$ ▷ joint training
12: **end for**

Algorithm 1 describes the process of training the HRT model. The HRT model is pre-initialized by a pre-trained AT model (Line 1). During training, the training batch B_i randomly select a raw target sentence Y_i or its distilled version Y' (Line 4-6). Then according to Eq. 5, we can divide B into two parts: $B_{c=1}$ and $B_{c=k}$, where $|B_{c=k}|/|B| = p_k$ (Line 7-8). Next, we construct four kinds of training samples based on corresponding batches: $B_{c=k}^{at}$, $B_{c=1}^{at}$, $B_{c=k}^{mp}$ and $B_{c=1}^{mp}$. Finally, we collect all training samples together and accumulate their gradients to update the model parameters, which results in the batch size being twice that of standard training.

C   Computation complexity

In Table 7, we summarized the comparison with autoregressive translation (AT), iterative refinement based non-autoregressive translation (IR-NAT) and semi-autoregressive translation (SAT) Wang et al. (2018).

AT. Although both HRT and AT contain a slow autoregressive generation process, HRT's length is k times shorter than AT. Considering that the computational complexity of self-attention is quadratic with its length, HRT can save more time in autoregressive decoding.

IR-NAT. Since Skip-AT provides a high-quality target context, HRT does not need to use large beam size and multiple iterations like IR-NAT. The experimental results also show that our light NAT can make up for the increased cost in Skip-AT and can achieve stable acceleration regardless of the decoding batch size and running device.

Table 7: Compare hybrid-regressive translation (HRT) to autoregressive translation (AT), iterative refinement based non-autoregressive translation (IR-NAT), and semi-autoregressive translation (SAT). $Q(i)$ denotes the computation cost in autoregressive mode when producing the i-th token (e.g., the prefix length is $i - 1$). $\hat{Q}_b(i)$ denotes the computation cost in non-autoregressive mode when producing i tokens by one shot with a beam size of b. $I = 4 \sim 10$, k is generally 2.

Method	Steps	Computing Cost
AT	L	$\sum_{i=1}^{L} Q(i)$
IR-NAT	I	$I \times \hat{Q}_{b=5}(L)$
SAT	L/k	$L/k \times (\hat{Q}_{b=5}(k) + \epsilon)$
HRT	L/k + 1	$\sum_{i=1}^{L/k} Q(i \times k) + \hat{Q}_{b=1}(L)$

SAT. SAT generates segments locally by non-autoregression, but it is still autoregressive between segments. We claim that the SAT reduces the decoding steps by k, but each token's calculation remains unchanged. In other words, in the time step i, there are $i - 1$ tokens used for self-attention. By contrast, only i/k tokens are involved in our Skip-AT.