Revisiting Score Propagation in Graph Out-of-Distribution Detection

Longfei Ma[1*], **Yiyou Sun**[2*], **Kaize Ding**[3], **Zemin Liu**[1†], **Fei Wu**[1†]

[1]Zhejiang University, [2]University of Wisconsin-Madison, [3]Northwestern University
{longfeima, liu.zemin, wufei}@zju.edu.cn,
sunyiyou@cs.wisc.edu, kaize.ding@northwestern.edu

Abstract

The field of graph learning has been substantially advanced by the development of deep learning models, in particular graph neural networks. However, one salient yet largely under-explored challenge is detecting Out-of-Distribution (OOD) nodes on graphs. Prevailing OOD detection techniques developed in other domains like computer vision, do not cater to the interconnected nature of graphs. This work aims to fill this gap by exploring the potential of a simple yet effective method – OOD score propagation, which propagates OOD scores among neighboring nodes along the graph structure. This post hoc solution can be easily integrated with existing OOD scoring functions, showcasing its excellent flexibility and effectiveness in most scenarios. However, the conditions under which score propagation proves beneficial remain not fully elucidated. Our study meticulously derives these conditions and, inspired by this discovery, introduces an innovative edge augmentation strategy with theoretical guarantee. Empirical evaluations affirm the superiority of our proposed method, outperforming strong OOD detection baselines in various scenarios and settings. To ensure reproducibility, we have made our code and relevant data publicly available at https://github.com/longfei-ma/GRASP.

1 Introduction

Graph-like data structures are ubiquitous in many domains, such as social networks [87, 40], molecular chemistry [19, 82], and recommendation systems [84, 45]. As graph neural networks increasingly serve as powerful tools for navigating this complex data landscape, a compelling yet under-explored issue emerges: Out-of-Distribution (OOD) node detection. Imagine a recommender system suggesting irrelevant or even harmful products to users, or a bioinformatics algorithm misusing an unknown protein. This gives rise to the importance of OOD detection in graph data, which determines whether an input is in-distribution (ID) or OOD and enables the model to take precautions.

While existing OOD detection methods have shown promising results in computer vision [66, 27, 18, 15, 95], natural language procession [11, 57] and tabular data analytics [68], their effectiveness diminishes when applied to graph data [77]. These conventional techniques operate under the assumption that data points are independently sampled, which misaligns with the interconnected nature of graphs. To better leverage the structural knowledge from the graph, OOD score propagation [77] has been employed to enhance graph OOD detection performance by directly propagating the computed OOD scores along the graph structure (as shown in Figure 1). Although this strategy has shown promising results on some datasets,

Figure 1: Illustration of OOD scores propagation.

---

[*]Co-first author.

[†]Corresponding author.

38th Conference on Neural Information Processing Systems (NeurIPS 2024).

Figure 2: Two illustrative examples when scoring propagation is harmful/helpful. We consider ID nodes in green and OOD nodes in red. Inter-edges are defined to be `ID-to-OOD` edges and Intra-edges are `ID-to-ID` or `OOD-to-OOD` edges. The value represents the respective OOD scores. Consequently, the propagated scores in these cases will be the mean of the scores of adjacent nodes as shown in Figure 1.

the reasons behind its effectiveness and the conditions under which it works are not clear. To dive deep into it, our research embarks on addressing two research questions related to OOD score propagation:

Question 1: "Will naive OOD score propagation always help graph OOD Detection?" The short answer is no. This method can be ineffective on graphs where inter-edges (`ID-to-OOD`) are predominant. Using the examplse in Figure 2(a), where only inter-edges exist, prior to conducting score propagation, all ID and OOD nodes can be fully distinguished. However, after performing score propagation along these edges, the ID and OOD nodes are completely misclassified. Conversely, after adding intra-edges and making them donimate, as shown in Figure 2(b), score propagation would be beneficial to distinguish ID and OOD nodes. These two examples intuitively illustrate how the ratio of intra-edges and inter-edges can impact the effectiveness of OOD score propagation. We substantiate this intuition in Section 3. This finding naturally paves the way for subsequent questions.

Question 2: "How to derive a better score propagation strategy for graph OOD detection?" Building on our prior findings, we propose a graph augmentation strategy as presented in Section 4. Specifically, our strategy selects a subset G of the training set and puts additional edges to the nodes within G. Beyond its practical implications, our solution is theoretically supported: When G predominantly connects to ID data over OOD data, our strategy can provably enhance the post-propagation OOD detection outcomes.

We summarize our contributions as below:

- **Theoretical understanding:** We delve deeply into the mechanism of score propagation to understand its potential for graph OOD detection and elucidate the conditions under which it thrives, providing an understanding that extends beyond existing knowledge.

- **Practical solution:** To counter the identified challenge of inter-edges' domination, we propose **GR**aph-**A**ugmented **S**core **P**ropagation (GRASP), an innovative edge augmentation strategy with theoretical guarantee. By strategically adding edges to a chosen subset G of the training set, as detailed in Section 4, our method aims to enhance the intra-edge ratio, thereby boosting OOD detection outcomes post-propagation.

- **Empirical studies**: We demonstrate the superior performance of the proposed method on extensive graph OOD detection benchmarks, different pre-trained methodologies [34, 69, 7, 94], and different OOD scoring functions. Under the same condition, our proposed strategy substantially reduces the FPR95 by **17.87**% and **32.21**% compared to the strongest graph OOD detection baselines on common and large-scale benchmarks respectively. Comprehensive analyses are also provided to validate the effectiveness of the proposed approach and the correctness of the theoretical findings.

2 Preliminaries

Problem setup. We consider a traditional semi-supervised node classification setting with the additional unlabeled nodes from the out-of-distribution class. Let $\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}$ denote the graph with nodes $\mathcal{V}$ and edges $\mathcal{E}$, where the node set $\mathcal{V}$ with size N are attributed with data matrix $X \in \mathbb{R}^{N \times d}$. The structure of graph $\mathcal{G}$ is described by the adjacency matrix $A \in \{0, 1\}^{N \times N}$. We let the corresponding row-stochastic matrices as $\bar{A} = \mathrm{D}^{-1}A$, where D is the diagonal matrix with

$D_{ii} = \sum_j A_{ij}$. The N nodes are partially labeled, so we let $\mathcal{V}_l$ and $\mathcal{V}_u$ represent the labeled and unlabeled node sets respectively, i.e, $\mathcal{V} = \mathcal{V}_l \cup \mathcal{V}_u$. Given a training set $\mathcal{D}^{tr} = \left\{ (\mathbf{x}_i, y_i) \right\}_{i \in \mathcal{V}_l}$ with $\mathbf{x}_i$ as the i-th row of X and $y_i \in \mathcal{Y} \triangleq \{1, \cdots, C\}$, the goal of node classification is to learn a mapping $f : \mathcal{V} \to \mathbb{R}^C$ from the nodes to the probability of each class.

Out-of-distribution detection. When deploying a model in the real world, a reliable classifier should not only accurately classify known in-distribution (ID) nodes, but also identify "unknown" nodes or OOD nodes. Formally, we can represent the unlabeled node set by $\mathcal{V}_u = \mathcal{V}_{uid} \cup \mathcal{V}_{uood}$ where $\mathcal{V}_{uid}$ and $\mathcal{V}_{uood}$ represent the in-distribution (ID) node and OOD node respectively. **The goal of the graph OOD detection** is to derive an algorithm to decide if a node $i \in \mathcal{V}_u$ is from $\mathcal{V}_{uood}$ or $\mathcal{V}_{uid}$.

This can be achieved by having an OOD detector, in tandem with the node classification model f. OOD detection can be formulated as a binary classification problem. At test time, the goal of OOD detection is to decide whether an unlabeled node $i \in \mathcal{V}_u$ is from ID or OOD. The decision can be made via a level set estimation:

$$F_{OODD}(i, \mathcal{G}; \lambda) = \begin{cases} \text{ID} & g(\mathbf{x}_i) \geq \lambda \\ \text{OOD} & g(\mathbf{x}_i) < \lambda \end{cases},$$

where nodes with higher scores $g(\mathbf{x}_i)$ are classified as ID and vice versa, and λ is the threshold commonly chosen so that a high fraction (e.g., 95%) of ID data is correctly classified.

In this paper, we consider **post hoc** OOD detection methods to produce $g(\mathbf{x}_i)$ which does not require expensive re-training. As an example, a classical way to compute $g(\mathbf{x}_i)$ is Maximum Softmax Probability (MSP) [23] which is given by the maximum softmax value. We include details of the considered OOD detection methods in Appendix B.

3 Will propagation always help Graph OOD Detection?

In the introduction, we delineate the limitations of OOD score propagation using a concrete example and elucidate the intuition that it may fail when inter-edges dominate. In this section, we formally delineate the conditions under which OOD score propagation works. We start by showing the formal definition of propagation.

Define OOD scoring propagation. Given a raw OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$ with $\hat{\mathbf{g}}_i = g(\mathbf{x}_i)$, the propagated scoring vector is given by:

$$\textit{Propagated OOD Scoring Vector}: \mathbf{g} = \bar{A}^k \hat{\mathbf{g}}, \tag{1}$$

where $k \in \mathbb{N}^+$ are hyperparameters.

Is it necessarily the case that $\mathbf{g}$ *outperforms* $\hat{\mathbf{g}}$? The answer is **NO**. We elucidate with the theoretical insight below.

Theoretical Insight. As discussed in the Introduction from Figure 2, when the number of `ID-to-ID` and `OOD-to-OOD` edges surpasses that of `ID-to-OOD` edges, the propagation mechanism tends to "aggregate" the scores associated with the ID and OOD nodes respectively, which further amplify the separability between them. Conversely, when the number of `ID-to-OOD` edges are more than the other types of edges, the scores for both ID and OOD nodes become undistinguishable post-propagation.

The example above offers the insight that the relative performance of $\mathbf{g}$ compared to $\hat{\mathbf{g}}$ is contingent upon the structural dynamics of the network, specifically the distribution of edges. To formally articulate this relationship, we adopt a probabilistic framework for modeling edges. Specifically, we assume that the edge follows a Bernoulli distribution characterized by parameters η_{intra} and η_{inter} for intra-edges (`ID-to-ID` and `OOD-to-OOD`) and inter-edges (`ID-to-OOD`), respectively:

$$A_{ij} \sim \begin{cases} Ber(\eta_{intra}), & \text{if } i, j \in \mathcal{V}_{uid} \text{ or } i, j \in \mathcal{V}_{uood} \\ Ber(\eta_{inter}), & \text{if } i \in \mathcal{V}_{uid}, j \in \mathcal{V}_{uood} \text{ or } j \in \mathcal{V}_{uid}, i \in \mathcal{V}_{uood} \end{cases}$$

In the context of probabilistic modeling, the subsequent Theorem 3.1 can be established to formalize the inherent understanding.

Theorem 3.1. *(Informal) (a) When $\eta_{intra} \gg \eta_{inter}$, it is highly likely that the propagation algorithm will yield enhanced performance in OOD detection. (b) When $\eta_{intra} \approx \eta_{inter}$ or even $\eta_{intra} < \eta_{inter}$, the score propagation is likely to be either ineffective or detrimental to the performance.*

We also provide the formal version below (Theorem 3.2) which provides a mathematical foundation for understanding how varying the Bernoulli parameters influence the efficacy of the propagation in the context of OOD detection. We provide the detailed proof in Appendix A.

Theorem 3.2. *(Formal) For any two test ID/OOD node set $S_{id} \subset \mathcal{V}_{uid}, S_{ood} \subset \mathcal{V}_{uood}$ with equal size N_s, let the ID-vs-OOD separability $\mathcal{M}_{sep}$ defined on an OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$ as*

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) \triangleq \mathbb{E}_{i \in S_{id}}\hat{\mathbf{g}}_i - \mathbb{E}_{j \in S_{ood}}\hat{\mathbf{g}}_j.$$

If $\mathcal{M}_{sep}(\hat{\mathbf{g}}) > 0$ and $\eta_{intra} - \eta_{inter} > 1/N_s$, for some $\epsilon > 0$ and constant c, we have $\mathbb{P}\left(\mathcal{M}_{sep}(A\hat{\mathbf{g}}) \geq \mathcal{M}_{sep}(\hat{\mathbf{g}}) - \epsilon\right) \geq 1 - exp\left(-\frac{c\epsilon^2}{\|\hat{\mathbf{g}}\|_2^2}\right).$

Summary. This section has presented a comprehensive theoretical evidence to substantiate the claim that propagation through the adjacency matrix A does not necessarily enhance out-of-distribution (OOD) detection in graphs. Moreover, Theorem 3.2 reveals that the critical factor in enhancing post-propagation performance lies in **improving the ratio of intra-edges** within the graph structure. These insights serve as a direct motivation for the augmentation strategy in the next section.

4   An Augmented Score Propagation Strategy

The findings from the preceding section give rise to a subsequent thought: "*Can we improve the propagation strategy for graph OOD detection performance?*" In an ideal scenario, if an oracle were to indicate that a particular subset in the test set belongs exclusively to the ID or OOD, one could augment the graph by adding intra-edges or removing inter-edges. This would consequently improve the ratio of intra-edges η_{intra}, leading to enhanced OOD detection performance post-propagation.

However, such an oracle does not exist in practical settings, and even approximating such a subset proves to be a difficult task. Existing literature has suggested the use of pseudo-labels assigned to nodes [36, 79, 2, 73, 55]. Nonetheless, these studies also caution that this approach is susceptible to "confirmation bias", whereby errors in estimation are inadvertently amplified.

To circumvent it, this paper proposes the solution for adding edges to a subset of the training set $\mathcal{V}_l$, which is assured to be in-distribution data. We start by showing the theoretical underpinnings that adding such a subset can, under specified conditions, contribute to improved OOD detection performance after propagation.

4.1   Theoretical Insight

Our approach involves adding the edges to a subset G of training data and then propagating the out-of-distribution (OOD) scoring vector using the enhanced adjacency matrix. Specifically, when edges are added to G, this action can be mathematically represented as incorporating a perturbation matrix $E = \mathbf{e}_G\mathbf{e}_G^\top$ into A, as demonstrated in Figure 3. Here, $\mathbf{e}_S \in \mathbb{R}^N$ denotes an indicator vector for a set $S \subset \mathcal{V}$, where the vector takes the value of 1 if the index $i \in S$ and value 0 otherwise. A sufficient condition for the efficacy of this augmentation strategy in enhancing post-propagation OOD detection performance is outlined in Theorem 4.1.

Theorem 4.1. *(Informal) For a subset G in the training set, augmenting G by adding edges to all its nodes can lead to improved post-propagation OOD detection performance, provided that the following condition is met: G has more edges to ID data than OOD data.*

We also provide the formal version below (Theorem 4.2) that incorporates a perturbation analysis. This analysis elucidates how edge augmentation in the training set can positively influence the

Figure 3: The augmentation procedure.

propagation algorithm's ability to enhance OOD detection. For the sake of the main intuition, we provide the analysis on A instead of $\bar{A}$ for simplicity. We provide the detailed proof in Appendix A.

Theorem 4.2. *(Formal) For any two test ID/OOD node set $S_{id} \subset \mathcal{V}_{uid}, S_{ood} \subset \mathcal{V}_{uood}$ with size N_s, let the ID-vs-OOD separability $\mathcal{M}_{sep}$ defined on a non-negative OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$ as*

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) \triangleq \mathbb{E}_{i \in S_{id}} \hat{\mathbf{g}}_i - \mathbb{E}_{j \in S_{ood}} \hat{\mathbf{g}}_j.$$

Let $\mathcal{E}_{S \leftrightarrow S'} \subset \mathcal{E}$ to denote the edge set of edges between two node sets S and S', where $S, S' \subset \mathcal{V}$. If we can find a node set $G \subset \mathcal{V}_l$ such that $|\mathcal{E}_{G \leftrightarrow S_{id}}| > |\mathcal{E}_{G \leftrightarrow S_{ood}}|$, we have

$$\mathcal{M}_{sep}((A + \delta E)^2 \hat{\mathbf{g}}) > \mathcal{M}_{sep}(A^2 \hat{\mathbf{g}}),$$

where $E = \mathbf{e}_G \mathbf{e}_G^\top$ and $\delta > 0$.

The Theorem 4.2 shows a critical principle for enhancing propagation: the optimal strategy entails the addition of edges to the subset G such that there are more edges to ID data than OOD data. For some S_{id}, S_{ood} in the test set, the goal is to find the set

$$G_* = \underset{S \subset \mathcal{V}_l, |S| = N_g}{\arg\max} \frac{|\mathcal{E}_{S \leftrightarrow S_{id}}|}{|\mathcal{E}_{S \leftrightarrow S_{ood}}|}, \tag{2}$$

where N_g is a hyperparameter to control the size of G_*. Inspired by the optimization target, we proceed to present our pragmatic algorithmic approach.

4.2 Graph-Augmented Score Propagation (GRASP)

Our augmentation approach hinges on the selection of a subset, G, from the training set, as exemplified in Equation 2. Two principal challenges arise in implementing this: (1) We cannot directly determine the number of edges linked to ID/OOD data because these reside in the test set and their labels remain unknown. (2) An exhaustive search to find a subset is computationally expensive, as the number of combinatorial possibilities increases in a factorial manner. In this paper, we tackle these challenges by providing the practical approximation method.

Selection of $\mathbf{S_{id}}/\mathbf{S_{ood}}$. Our discussion begins by detailing the methodology to select the subset from the test ID/OOD dataset, symbolized by S_{id} and S_{ood} in Equation 2. A straightforward approach to obtain the most likely ID is by selecting nodes with the largest confidence and the least for OOD in class predictions. Following [23], we employ the max softmax probability (MSP) as a representation of confidence. The selected sets can be defined as:

$$S_{id} = \{i \in \mathcal{V}_u | \max_{c \in [C]} f_c(i) > \lambda_\alpha\}, S_{ood} = \{j \in \mathcal{V}_u | \max_{c \in [C]} f_c(j) < \lambda_{100-\alpha}, \tag{3}$$

where λ_α denotes the α-th percentile of the MSP scores corresponding to nodes in $\mathcal{V}_u$. To offer a clear view, Figure 4 portrays S_{id} and S_{ood} in the marginal regions highlighted in orange. Selecting a subset in the leftmost and rightmost regions reduces the error when identifying the ID/OOD subsets, given that overlapping between ID and OOD predominantly occurs around the central region of the distribution.

Selection of G. Upon establishing S_{id} and S_{ood}, the next step is to determine G using Equation 2. Directly enumerating every possible G is impractical. Instead, we adopt a greedy approach, prioritizing the node with the highest "likelihood" score. To elucidate, for each node $i \in \mathcal{V}_l$, the score can be

Figure 4: Illustration of the rationale in selecting S_{id} and S_{ood}. MSP score is reported on Dataset `Coauther-CS` with the division of ID and OOD classes introduced in Appendix C.

computed as the ratio of the edge count to S_{id} over S_{ood}:

$$h(i) = |\mathcal{E}_{\{i\}\leftrightarrow S_{id}}|/(|\mathcal{E}_{\{i\}\leftrightarrow S_{ood}}| + 1), \tag{4}$$

where we incorporate an addition of 1 in the denominator to circumvent division by zero. Subsequently, G can be expressed as:

$$G = \{i \in \mathcal{V}_l | h(i) > \tau_\beta\}, \tag{5}$$

where τ_β stands for the β-th percentile of $h(i)$ scores for nodes in $\mathcal{V}_l$. Once G is defined, edge augmentation can be executed as demonstrated in Section 4.1. The OOD score is then propagated with the new adjacency matrix $A_+ = A + \mathbf{e}_G\mathbf{e}_G^\top$ in place:

$$\mathbf{g}_{GRASP} = (\bar{A}_+)^k\hat{\mathbf{g}}, \tag{6}$$

where $k \in \mathbb{N}^+$ are hyperparameters.

Complexity analysis. While our algorithm introduces the fully connected matrix E, our method can be effciently implemented by matrix-vector multiplication, leading to computational footprint in terms of runtime and memory usage with $\mathcal{O}(N + 2k|\mathcal{E}| + n)$ and $\mathcal{O}(N + |\mathcal{E}| + n)$ respectively after propagation for k times, where n is node count of subset G. We provide the comprehensive complexity analysis in Appendix D.6.

5 Experiments

Datasets. We conduct extensive experiments using 10 real-world datasets that span diverse domains, scales, and structures (homophily or heterophily). A high-level summary of the dataset statistics is provided in Table 1, with a detailed information of the datasets and the comprehensive description of ID/OOD split in Appendix C. Specifically, `Cora` [61] serves as a widely recognized citation network. `Amazon-Photo` [52] represents a co-purchasing network on Amazon. `Coauthor-CS` [62] portrays a coauthor network within the realm of computer science. Moreover, `Chameleon` and `Squirrel` [59] are two notable Wikipedia networks, predominantly utilized as

Table 1: Summary statistics of the datasets: size of the training set $|\mathcal{V}_l|$, test ID set $|\mathcal{V}_{uid}|$, test OOD set $|\mathcal{V}_{uood}|$; number of ID classes C, scale of the dataset, and whether the graph is homophily.

Dataset	$|\mathcal{V}_l|$	$|\mathcal{V}_{uid}|$	$|\mathcal{V}_{uood}|$	C	Scale	Homph
Cora	180	724	18K	3	SM	✓
Amazon-Photo	618	2K	4K	3	SM	✓
Coauthor-CS	2K	10K	5K	11	SM	✓
Chameleon	272	1K	916	3	SM	✗
Squirrel	622	2K	2K	3	SM	✗
Reddit2	33K	133K	65K	11	LG	✓
ogbn-products	130K	522K	1M	11	LG	✓
ArXiv-year	23K	92K	53K	3	LG	✗
Snap-patents	351K	1M	1M	3	LG	✗
Wiki	212K	850K	862K	3	LG	✗

heterophilic graph benchmarks. We additionally incorporate 5 **large-scale** graphs to evaluate our proposed methods: `Reddit2` [88] and `ogbn-products` [24] are large homophily datasets; `ArXiv-year`, `Snap-patents`, and `Wiki` [44] are recently proposed large-scale heterophily benchmarks.

Remark on homophily/heterophily. In Table 1, datasets are also categorized based on the attribute of homophily, denoting the tendency of nodes with the same class to connect. Conversely, the heterophily graph demonstrates a tendency for nodes of disparate classes to connect. This characteristic not only presents a challenge for node classification but also for graph OOD detection. The underlying reason is that the OOD data is from different classes with ID, and heterophily exacerbates the ratio of

Table 2: **Main results on common benchmarks.** Comparison with competitive out-of-distribution detection methods on pre-trained GCN. We take the average values that are percentages over 5 independently trained backbones. ↑ (↓) indicates larger (smaller) values are better.

Method	Cora		Amazon		Datasets Coauthor		Chameleon		Squirrel		Average	
	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑
MSP	70.86	84.56	49.26	89.34	28.82	94.34	85.70	57.96	94.68	48.51	65.86	74.94
Energy	67.54	85.47	42.13	90.28	20.29	95.67	88.06	59.20	93.98	45.07	62.40	75.14
KNN	90.20	70.94	65.19	84.71	51.24	90.13	93.38	57.90	94.72	54.68	78.95	71.67
ODIN	68.41	84.98	44.06	89.90	22.59	95.27	85.31	57.94	94.17	44.08	62.91	74.43
Mahalanobis	69.68	85.48	96.49	75.58	85.71	84.98	95.55	53.19	94.90	54.99	88.47	70.84
GKDE	63.71	86.27	81.29	77.26	25.48	95.13	92.93	50.14	96.71	49.38	72.02	71.64
GPN	58.45	82.93	72.95	82.63	34.11	93.82	82.25	68.20	95.58	48.38	68.67	75.19
OODGAT	94.59	53.63	71.34	66.95	96.53	52.18	94.43	59.67	95.27	46.13	90.43	55.71
GNNSafe	54.71	87.52	22.39	96.27	16.64	95.82	100.00	50.42	100.00	35.88	58.75	73.18
GRASP (Ours)	**29.70**	**93.50**	**14.38**	**96.68**	**7.84**	**97.75**	**66.88**	**76.93**	**85.59**	**61.09**	**40.88**	**85.19**

inter-edge connections between ID and OOD, which is deemed undesirable for graph OOD detection according to Theorem 3.2.

Implementation Details. Our graph OOD detection technique operates in a *post hoc* fashion utilizing a pre-trained network and so can be used in various pre-trained network seamlessly. We present results evaluated on Graph Convolutional Network (GCN) [34] in the main paper to save space and put detailed results of other architectures in Appendix D.3. All pre-trained models possess a layer depth of 2. With the pre-trained network, we proceed to execute the graph OOD detection. By default, we report the performance of the augmented propagation (GRASP) on the MSP score [23]. The compatibility with other OOD scoring functions is also shown in Table 6. We set the propagation number k as 8, with percentile values $\alpha = 5$ and $\beta = 50$. The sensitivity analysis of the hyper-parameters is included in Appendix D.4.

Metrics. Following the convention in literature [23, 47, 65], we use AUROC and FPR95 as evaluation metrics for OOD detection.

5.1 Main Results

GRASP consistently achieves superior performance. We provide results of 5 common small-scale benchmarks and 5 **large-scale** datasets in Table 2 and Table 3 respectively, wherein only the averaged results over 5 runs are presented to save space and the detailed results with standard errors of these two scale datasets are shown in Table 12 and Table 13 respectively. From the results we can see that our proposed methodology (GRASP) consistently demonstrates promising performance. The comparative analysis encompasses a broad spectrum of *post hoc* competitive Out-of-Distribution (OOD) detection techniques in existing literature and training-based methods tailored for graph OOD detection. We categorize the baseline methods into two groups: (a) Traditional OOD detection methods including MSP [23], Energy [47], ODIN [43], Mahalanobis [37], and KNN [67]; (b) Graph OOD detection methods including GKDE [92], GPN [64], OODGAT [63], and GNNSafe [77]. In these tables, we present GRASP results based on the MSP score. Noteworthy findings include: (a) The traditional OOD detection methods exhibit suboptimal performance in the realm of graph OOD detection. For instance, GRASP reduced the average FPR95 by **17.87**% and **32.21**% compared to the strongest traditional OOD detection method GNNSafe and Mahalanobis on common and large-scale benchmarks, respectively. This outcome is anticipated given their lack of specificity in design towards graph data. (b) GRASP outperforms existing baselines by a large margin, surpassing the best baseline GNNSafe by **17.87**% and **40**% concerning average FPR95 on two scale benchmarks respectively. These results further corroborate that the theoretically motivated solution GRASP is also appealing to use in practice.

GRASP is also competitive on large-scale graph datasets. Contrasted with the small-scale benchmarks in Table 2, the large-scale scenario in Table 3 presents more challenges due to a large number of nodes and edges. From Table 3 we can see that all baseline OOD detection methodologies exhibit suboptimal performance on large-scale benchmarks, while our method GRASP robustly performs the best.

GRASP exhibits significant advantages over training-based baselines. In addition to contrasting with *post hoc* methods, we extend our comparison to a parallel line of graph Out-Of-Distribution (OOD) detection research, which focuses on refining the training strategy to improve graph OOD detection performance. The compared methods include GKDE [92], GPN [64] and OODGAT [63]. While

Table 3: **Main results on large-scale benchmarks.** Comparison with competitive out-of-distribution detection methods on pre-trained method GCN. We take the average values that are percentages over 5 independently trained backbones. OOM means Out-Of-Memory and OOT denotes that no results have been got after running over 48 hours for each run. ↑ (↓) indicates larger (smaller) values are better.

Method	reddit2		ogbn-products		Datasets arxiv-year		snap-patents		wiki		Average	
	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑
MSP	96.59	46.61	86.87	70.19	95.03	47.24	94.31	46.99	95.46	54.70	93.65	53.15
Energy	96.77	44.13	85.09	68.13	94.10	51.35	96.82	46.03	97.31	29.02	94.02	47.73
KNN	90.78	66.74	84.22	73.58	95.35	57.96	90.54	53.45	93.43	43.69	90.86	59.08
ODIN	96.74	44.69	85.65	68.95	95.06	47.36	94.27	45.20	97.88	29.91	93.92	47.22
Mahalanobis	71.73	74.89	OOM	OOM	88.60	59.57	96.03	58.50	72.33	67.95	82.17	65.23
GKDE	OOT	OOT	OOM	OOM	OOM	OOM	OOM	OOM	OOM	OOM	-	-
GPN	OOM	OOM	OOM	OOM	95.62	50.97	OOM	OOM	OOM	OOM	95.62	50.97
OODGAT	OOM	OOM	OOM	OOM	92.90	59.38	OOM	OOM	OOM	OOM	92.90	59.38
GNNSafe	99.49	31.99	77.86	85.66	100.00	35.30	99.92	27.35	72.63	60.32	89.98	48.12
GRASP (Ours)	**2.41**	**98.50**	**39.77**	**93.79**	**73.93**	**81.24**	**75.22**	**72.13**	**58.49**	**77.97**	**49.96**	**84.73**

these approaches necessitate a costly re-training procedure, they perform mediocrely across all small-scale datasets and even run out-of-memory on almost all large-scale benchmarks, rendering them impractical for real-world deployment.

GRASP is performant on challenging heterophily datasets. As indicated in Table 2 and 3, GNNSafe, which performs well on homophily datasets, experiences significant degradation on the difficult heterophily benchmarks due to its naïve propagation mechanism. In contrast, GRASP maintains optimal performance on these hard scenarios.

5.2 A Comprehensive Analysis of GRASP

Ablation study on augmentation policy. Recall that the key part of our method GRASP is the augmentation policy that consists in adding edges to the training nodes with top 50% scores of $h(i)$, which corresponds to the nodes on the right side of Figure 5. We ablate the contributions of $h(i)$ by comparision with alternative augmentation approaches that utilize $h(i)$ differently in Table 4, specifically, (1) selecting 50% of training nodes with the lowest $h(i)$ values (left side of Figure 5), (2) randomly selecting 50% of training nodes, corresponding to randomly picking node indices from the x-axis of Figure 5, (3) directly adding edges to S_{id} and S_{ood} within the test set (*i.e.*, `TestAug`), and (4) a classic graph augmentation method named GAug [91],

Figure 5: Illustration of the number of edges from each training node i to S_{id} and S_{ood} on Chameleon dataset. The x-axis denotes the training node indices, ordered by $h(i)$ from low to high.

which adds or removes edges based on an edge predictor that disregards $h(i)$ completely. We have the following key observations:

(*a*) *Selection by $h(i)$ is effective.* For example, our strategy using the top 50% scores of $h(i)$ outperforms that uses random 50%, which, in turn, outperforms the low 50% way. This is because a higher score of $h(i)$ implies higher edge count towards ID data than to OOD data, which can increase the ratios of intra-edges and improve OOD detection performance after propagation. In contrast, the alternative augmentation method `GAug`, which does not consider the score $h(i)$ at all, performs even worse than the Low 50% policy.

Table 4: Ablation study on OOD detection performance by different augmentation policy. We report averaged AUROC over 5 independently pre-trained GCN models.

Strategy	Cora	Amaz	Coau	Cham	Squi	Avg
GAug	64.94	74.38	91.41	63.79	47.96	68.50
TestAug	59.24	75.78	95.00	50.58	48.64	65.85
Low 50%	88.84	95.02	97.21	54.60	53.52	77.84
Random 50%	90.23	95.37	97.45	65.32	57.59	81.19
Top 50% (**Ours**)	**93.50**	**96.68**	**97.75**	**76.93**	**61.09**	**85.19**

(*b*) *Directly adding edges to S_{id} and S_{ood} within the test set is sub-optimal.* Specifically, employing this method leads to nearly **20**% lower than that achieved with GRASP, which substantiates the notion that "confirmation bias" can adversely affect the graph OOD detection.

Table 5: GRASP consistently enhances the OOD detection performance of nodes connected by both inter-edges and intra-edges on datasets characterized by a strong degree of heterophily (datasets highlighted in bold in the table). However, naive propagation tends to compromise the performance of these nodes.

Datasets	MSP		MSP+prop		MSP+**GRASP**	
	intra	inter	intra	inter	intra	inter
cora	48.06	46.90	60.91	48.31	78.42	50.48
amazon	66.70	57.82	81.80	68.58	89.56	78.66
coauthor	87.72	73.30	93.88	81.37	94.85	83.21
chameleon	57.48	51.22	55.63	51.02	70.79	55.19
squirrel	44.76	38.45	43.74	37.04	49.89	41.69
reddit2	64.85	54.85	65.70	54.99	96.56	93.63
ogbn-product	31.72	37.73	37.10	43.63	67.95	64.30
arxiv-year	60.18	8.34	62.93	4.27	70.42	16.21
snap-patents	61.49	5.76	64.12	0.37	67.24	9.89
wiki	56.58	48.39	60.62	52.06	69.13	61.19

Overall, the ablation study suggests that our proposed augmentation policy is crucial to OOD detection performance.

GRASP can effectively boost performance of challenging nodes connected by inter-edges. As stated in the introduction 1, the reason OOD score propagation does not always work is the confusion between ID and OOD nodes resulting from propagation along the inter-edges. For example in heterophily datasets, where connected nodes tend to possess different labels, OOD nodes are more likely to appear on the inter-edges. To assess the capability of our proposed augmentation propagation method to address this challenge, we present in Table 5 the accuracy of detecting OOD nodes connected by intra-edges (`intra`) and inter-edges (`inter`) respectively, using the original MSP without any propagation, naive propagation based on MSP (`MSP+prop`), and our proposed augmentation propagation (`MSP+GRASP`) respectively. From the results we can see that naive propagation performs well only on strong homophily datasets, while on strong heterophily datasets (datasets highlighted in bold in the table), its performance is even worse than without propagation, as expected. In contrast, employing our augmentation method still results in substantial performance gain after propagation on these challenging datasets.

GRASP is compatible with a wide range of OOD scoring methods. In Table 6, we demonstrate the compatibility of GRASP with various alternative scoring functions. Each method generates OOD scores to form a scoring vector; GRASP is then applied to facilitate score propagation. The use of GRASP markedly surpasses the performance of its non-augmented counterpart across all datasets.

Table 6: GRASP is compatible with different OOD scoring functions. We compare OOD detection methods and the performance after the simple propagation in Equation 1 (denoted by "+ prop") and with GRASP respectively. We report AUROC results that are averaged over 5 independent pre-trained GCN models.

Method	Cora	Amazon	Coauth	Chamel	Squirr
MSP	84.56	89.34	94.34	57.96	48.51
MSP+prop	88.02	95.32	97.15	50.35	36.21
MSP+**GRASP**	**93.50**	**96.68**	**97.75**	**76.93**	**61.09**
Energy	85.47	90.28	95.67	59.20	45.07
Energy+prop	87.52	96.27	95.82	50.42	36.49
Energy+**GRASP**	**88.34**	**96.35**	**96.64**	**62.04**	**60.66**
KNN	70.94	84.71	90.13	57.90	54.68
KNN+prop	73.70	92.36	95.47	49.76	53.99
KNN+**GRASP**	**91.48**	**97.43**	**96.52**	**76.32**	**60.24**

Remark on other empirical findings. We include other empirical findings in Appendix. Specifically, in Table 14, we prove that GRASP also achieves superior performance on the other GNN architectures in the literature. In Figure 7, we demonstrate a strong positive correlation between ratios of intra-edges and the corresponding OOD detection performance, validating the correctness of Theorem 3.2. We also show in Table 15 that GRASP can increase the ratio of intra-edges after augmentation, consequently boosting OOD performance. This substantiates the correctness of Theorem 4.2. What's more, we conduct a thorough accounting of computation/memory demands compared to baselines on all scale datasets in Table 16 and Table 17 respectively, which underscore the strong practicality

of our approach. Lastly, in Appendix D.7, we investigate the other propagation mechanisms in the literature and their impact on graph OOD detection performance emperically.

6   Related Work

Out-of-distribution Detection. The primary focus within this realm has been on the development of scoring functions for OOD detection. These works can be broadly categorized into two main streams: (1) output-based methods [23, 43, 47, 71, 25, 72, 95, 26, 15, 90, 16, 21], and (2) feature-based methods including the Mahalanobis distance [37, 60, 56] and KNN distance [67]. These methodologies are predominantly applied in domains such as computer vision, where samples are inherently independent of each other. However, these techniques are not designed to adeptly handle data structures like graphs, where samples are inter-connected.

Out-of-distribution detection for graph data. Graph anomaly detection has a rich history [12, 74, 89, 75, 48, 14, 50, 32, 46, 51]. In recent years, the OOD detection in graph data introduced fresh challenges, particularly with multi-class classification for in-distribution data, escalating the difficulty in discerning outlier data. Some of the works focus on graph-level OOD detection [42, 49, 4, 76]. For node-level OOD detection, GKDE [92] and GPN [64] apply Bayesian Network models to estimate uncertainties to detect OOD nodes. However, Bayesian-based approaches can encounter impediments such as inaccurate predictions and high computational demands, which limit their broader applicability [83]. GNNSafe [77] emerges as the work employing post hoc energy-based score to perform OOD detection. Given the merits of post hoc methods, our study first provides a comprehensive understanding of the OOD score propagation in Graphs, extending beyond existing knowledge.

Graph Data Augmentation. Graph Data Augmentation is a common technique in graph machine learning [20, 6, 58, 29, 93, 91, 33, 53, 13, 3] to improve the node classification performance. Existing methods operate exclusively on in-distribution (ID) data. Furthermore, their test set data also originates from the in-distribution and shares the same classes as the training set. In contrast, our data augmentation is purposefully crafted for OOD detection, supported by the theoretical explanation.

7   Conclusions

In this research, we delve into an important yet under-explored challenge in the realm of graph data: Out-of-Distribution (OOD) detection. Recognizing the inadequacies of traditional OOD detection techniques in the context of graph data, our exploration centered on the potential of score propagation as a viable and efficient solution. Our findings reveal the specific conditions under which score propagation will be helpful—in situations where the ratio of intra-edges surpasses that of inter-edges. Motivated by this finding, our edge augmentation strategy selectively adds edges to a specific subset G of the training set, which provably improves post-propagation OOD detection outcomes under certain conditions. Extensive empirical evaluations reinforced the merit of our approach.

8   Acknowledgements

This work was supported by the National Natural Science Foundation of China (62441605), and the Starry Night Science Fund of Zhejiang University Shanghai Institute for Advanced Study (SN-ZJUSIAS-0010).

References

[1] Sami Abu-El-Haija, Bryan Perozzi, Amol Kapoor, Nazanin Alipourfard, Kristina Lerman, Hrayr Harutyunyan, Greg Ver Steeg, and Aram Galstyan. Mixhop: Higher-order graph convolutional architectures via sparsified neighborhood mixing. In *international conference on machine learning*, pages 21–29. PMLR, 2019.

[2] Eric Arazo, Diego Ortego, Paul Albert, Noel E O'Connor, and Kevin McGuinness. Pseudo-labeling and confirmation bias in deep semi-supervised learning. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE, 2020.

[3] Mehdi Azabou, Venkataramana Ganesh, Shantanu Thakoor, Chi-Heng Lin, Lakshmi Sathidevi, Ran Liu, Michal Valko, Petar Veličković, and Eva L Dyer. Half-hop: A graph upsampling approach for slowing down message passing. 2023.

[4] Gleb Bazhenov, Sergei Ivanov, Maxim Panov, Alexey Zaytsev, and Evgeny Burnaev. Towards ood detection in graph classification from uncertainty estimation perspective. *arXiv preprint arXiv:2206.10691*, 2022.

[5] Gleb Bazhenov, Denis Kuznedelev, Andrey Malinin, Artem Babenko, and Liudmila Prokhorenkova. Evaluating robustness and uncertainty of graph models under structural distributional shifts. *Advances in Neural Information Processing Systems*, 36, 2024.

[6] Deli Chen, Yankai Lin, Wei Li, Peng Li, Jie Zhou, and Xu Sun. Measuring and relieving the over-smoothing problem for graph neural networks from the topological view. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 3438–3445, 2020.

[7] Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. Simple and deep graph convolutional networks. In *International conference on machine learning*, pages 1725–1735. PMLR, 2020.

[8] Yongqiang Chen, Yatao Bian, Kaiwen Zhou, Binghui Xie, Bo Han, and James Cheng. Does invariant graph learning via environment augmentation learn invariance? *Advances in Neural Information Processing Systems*, 36, 2024.

[9] Zhengyu Chen, Teng Xiao, Kun Kuang, Zheqi Lv, Min Zhang, Jinluan Yang, Chengqiang Lu, Hongxia Yang, and Fei Wu. Learning to reweight for generalizable graph neural network. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 8320–8328, 2024.

[10] Eli Chien, Jianhao Peng, Pan Li, and Olgica Milenkovic. Adaptive universal generalized pagerank graph neural network. *International Conference on Learning Representations*, 2021.

[11] Pierre Colombo, Eduardo Dadalto, Guillaume Staerman, Nathan Noiry, and Pablo Piantanida. Beyond mahalanobis distance for textual ood detection. *Advances in Neural Information Processing Systems*, 35:17744–17759, 2022.

[12] Kaize Ding, Kai Shu, Xuan Shan, Jundong Li, and Huan Liu. Cross-domain graph anomaly detection. *IEEE Transactions on Neural Networks and Learning Systems*, 33(6):2406–2415, 2021.

[13] Kaize Ding, Zhe Xu, Hanghang Tong, and Huan Liu. Data augmentation for deep graph learning: A survey. *ACM SIGKDD Explorations Newsletter*, 24(2):61–77, 2022.

[14] Kaize Ding, Qinghai Zhou, Hanghang Tong, and Huan Liu. Few-shot network anomaly detection via cross-network meta-learning. In *Proceedings of the Web Conference 2021*, pages 2448–2456, 2021.

[15] Andrija Djurisic, Nebojsa Bozanic, Arjun Ashok, and Rosanne Liu. Extremely simple activation shaping for out-of-distribution detection. In *The Eleventh International Conference on Learning Representations*, 2022.

[16] Xuefeng Du, Yiyou Sun, and Yixuan Li. When and how does in-distribution label help out-of-distribution detection? In *Forty-first International Conference on Machine Learning*, 2024.

[17] Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.

[18] Ido Galil, Mohammed Dabbah, and Ran El-Yaniv. A framework for benchmarking class-out-of-distribution detection and its application to imagenet. In *The Eleventh International Conference on Learning Representations*, 2022.

[19] Johannes Gasteiger, Janek Groß, and Stephan Günnemann. Directional message passing for molecular graphs. In *International Conference on Learning Representations*, 2019.

[20] Johannes Gasteiger, Stefan Weißenberger, and Stephan Günnemann. Diffusion improves graph learning. *Advances in neural information processing systems*, 32, 2019.

[21] Soumya Suvra Ghosal, Yiyou Sun, and Yixuan Li. How to overcome curse-of-dimensionality for out-of-distribution detection? In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19849–19857, 2024.

[22] Shurui Gui, Meng Liu, Xiner Li, Youzhi Luo, and Shuiwang Ji. Joint learning of label and environment causal independence for graph out-of-distribution generalization. *Advances in Neural Information Processing Systems*, 36, 2024.

[23] Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2016.

[24] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *Advances in neural information processing systems*, 33:22118–22133, 2020.

[25] Rui Huang, Andrew Geng, and Yixuan Li. On the importance of gradients for detecting distributional shifts in the wild. *Advances in Neural Information Processing Systems*, 34:677–689, 2021.

[26] Wenjian Huang, Hao Wang, Jiahao Xia, Chengyan Wang, and Jianguo Zhang. Density-driven regularization for out-of-distribution detection. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho, editors, *Advances in Neural Information Processing Systems*, 2022.

[27] Paul F Jaeger, Carsten Tim Lüth, Lukas Klein, and Till J Bungert. A call to reflect on evaluation practices for failure detection in image classification. In *The Eleventh International Conference on Learning Representations*, 2022.

[28] Tianrui Jia, Haoyang Li, Cheng Yang, Tao Tao, and Chuan Shi. Graph invariant learning with subgraph co-mixup for out-of-distribution generalization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 8562–8570, 2024.

[29] Wei Jin, Yao Ma, Xiaorui Liu, Xianfeng Tang, Suhang Wang, and Jiliang Tang. Graph structure learning for robust graph neural networks. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 66–74, 2020.

[30] Wei Jin, Tong Zhao, Jiayuan Ding, Yozen Liu, Jiliang Tang, and Neil Shah. Empowering graph representation learning with test-time graph transformation. In *The Eleventh International Conference on Learning Representations*, 2022.

[31] Mingxuan Ju, Tong Zhao, Wenhao Yu, Neil Shah, and Yanfang Ye. Graphpatcher: Mitigating degree bias for graph neural networks via test-time augmentation. *Advances in Neural Information Processing Systems*, 36, 2024.

[32] Hwan Kim, Byung Suk Lee, Won-Yong Shin, and Sungsu Lim. Graph anomaly detection with graph neural networks: Current status and challenges. *IEEE Access*, 2022.

[33] Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.

[34] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *International Conference on Learning Representations*, 2017.

[35] Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. *International Conference on Learning Representations*, 2019.

[36] Dong-Hyun Lee et al. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *Workshop on challenges in representation learning, ICML*, volume 3, page 896. Atlanta, 2013.

[37] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *Advances in neural information processing systems*, 31, 2018.

[38] Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graphs over time: densification laws, shrinking diameters and possible explanations. In *Proceedings of the eleventh ACM SIGKDD international conference on Knowledge discovery in data mining*, pages 177–187, 2005.

[39] Jure Leskovec and Andrej Krevl. Snap datasets: Stanford large network dataset collection, 2014.

[40] Chang Li and Dan Goldwasser. Encoding social information with graph convolutional networks forpolitical perspective detection in news media. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2594–2604, 2019.

[41] Xiner Li, Shurui Gui, Youzhi Luo, and Shuiwang Ji. Graph structure and feature extrapolation for out-of-distribution generalization. *arXiv preprint arXiv:2306.08076*, 2023.

[42] Zenan Li, Qitian Wu, Fan Nie, and Junchi Yan. Graphde: A generative framework for debiased learning and out-of-distribution detection on graphs. *Advances in Neural Information Processing Systems*, 35:30277–30290, 2022.

[43] Shiyu Liang, Yixuan Li, and R Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018.

[44] Derek Lim, Felix Hohne, Xiuyu Li, Sijia Linda Huang, Vaishnavi Gupta, Omkar Bhalerao, and Ser Nam Lim. Large scale learning on non-homophilous graphs: New benchmarks and strong simple methods. *Advances in Neural Information Processing Systems*, 34:20887–20902, 2021.

[45] Changshu Liu, Liangjian Wen, Zhao Kang, Guangchun Luo, and Ling Tian. Self-supervised consensus representation learning for attributed graph. In *Proceedings of the 29th ACM international conference on multimedia*, pages 2654–2662, 2021.

[46] Kay Liu, Yingtong Dou, Yue Zhao, Xueying Ding, Xiyang Hu, Ruitong Zhang, Kaize Ding, Canyu Chen, Hao Peng, Kai Shu, et al. Bond: Benchmarking unsupervised outlier node detection on static attributed graphs. *Advances in Neural Information Processing Systems*, 35:27021–27035, 2022.

[47] Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in neural information processing systems*, 33:21464–21475, 2020.

[48] Yang Liu, Xiang Ao, Zidi Qin, Jianfeng Chi, Jinghua Feng, Hao Yang, and Qing He. Pick and choose: a gnn-based imbalanced learning approach for fraud detection. In *Proceedings of the web conference 2021*, pages 3168–3177, 2021.

[49] Yixin Liu, Kaize Ding, Huan Liu, and Shirui Pan. Good-d: On unsupervised graph out-of-distribution detection. In *Proceedings of the Sixteenth ACM International Conference on Web Search and Data Mining*, pages 339–347, 2023.

[50] Yixin Liu, Zhao Li, Shirui Pan, Chen Gong, Chuan Zhou, and George Karypis. Anomaly detection on attributed networks via contrastive self-supervised learning. *IEEE transactions on neural networks and learning systems*, 33(6):2378–2392, 2021.

[51] Xiaoxiao Ma, Ruikun Li, Fanzhen Liu, Kaize Ding, Jian Yang, and Jia Wu. Graph anomaly detection with few labels: A data-centric approach. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 2153–2164, 2024.

[52] Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. Image-based recommendations on styles and substitutes. In *Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval*, pages 43–52, 2015.

[53] Hyeonjin Park, Seunghun Lee, Sihyeon Kim, Jinyoung Park, Jisu Jeong, Kyung-Min Kim, Jung-Woo Ha, and Hyunwoo J Kim. Metropolis-hastings data augmentation for graph neural networks. *Advances in Neural Information Processing Systems*, 34:19010–19020, 2021.

[54] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[55] Hieu Pham, Zihang Dai, Qizhe Xie, and Quoc V Le. Meta pseudo labels. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11557–11568, 2021.

[56] Jie Ren, Stanislav Fort, Jeremiah Liu, Abhijit Guha Roy, Shreyas Padhy, and Balaji Lakshminarayanan. A simple fix to mahalanobis distance for improving near-ood detection. *arXiv preprint arXiv:2106.09022*, 2021.

[57] Jie Ren, Jiaming Luo, Yao Zhao, Kundan Krishna, Mohammad Saleh, Balaji Lakshminarayanan, and Peter J Liu. Out-of-distribution detection and selective generation for conditional language models. In *The Eleventh International Conference on Learning Representations*, 2022.

[58] Yu Rong, Wenbing Huang, Tingyang Xu, and Junzhou Huang. Dropedge: Towards deep graph convolutional networks on node classification. 2020.

[59] Benedek Rozemberczki, Carl Allen, and Rik Sarkar. Multi-scale attributed node embedding. *Journal of Complex Networks*, 9(2):cnab014, 2021.

[60] Vikash Sehwag, Mung Chiang, and Prateek Mittal. Ssd: A unified framework for self-supervised outlier detection. In *Proceedings of the International Conference on Learning Representations*, 2021.

[61] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

[62] Arnab Sinha, Zhihong Shen, Yang Song, Hao Ma, Darrin Eide, Bo-June Hsu, and Kuansan Wang. An overview of microsoft academic service (mas) and applications. In *Proceedings of the 24th international conference on world wide web*, pages 243–246, 2015.

[63] Yu Song and Donglin Wang. Learning on graphs with out-of-distribution nodes. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 1635–1645, 2022.

[64] Maximilian Stadler, Bertrand Charpentier, Simon Geisler, Daniel Zügner, and Stephan Günnemann. Graph posterior network: Bayesian predictive uncertainty for node classification. *Advances in Neural Information Processing Systems*, 34:18033–18048, 2021.

[65] Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. *Advances in Neural Information Processing Systems*, 34:144–157, 2021.

[66] Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*, pages 20827–20840. PMLR, 2022.

[67] Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning (ICML)*. PMLR, 2022.

[68] Dennis Ulmer, Lotta Meijerink, and Giovanni Cinà. Trust issues: Uncertainty estimation does not enable reliable ood detection on medical tabular data. In *Machine Learning for Health*, pages 341–354. PMLR, 2020.

[69] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *International Conference on Learning Representations*, 2017.

[70] Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge university press, 2018.

[71] Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. Vim: Out-of-distribution with virtual-logit matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4921–4930, 2022.

[72] Qizhou Wang, Feng Liu, Yonggang Zhang, Jing Zhang, Chen Gong, Tongliang Liu, and Bo Han. Watermarking for out-of-distribution detection. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho, editors, *Advances in Neural Information Processing Systems*, 2022.

[73] Xiao Wang, Hongrui Liu, Chuan Shi, and Cheng Yang. Be confident! towards trustworthy graph neural networks via confidence calibration. *Advances in Neural Information Processing Systems*, 34:23768–23779, 2021.

[74] Xuhong Wang, Baihong Jin, Ying Du, Ping Cui, Yingshui Tan, and Yupu Yang. One-class graph neural networks for anomaly detection in attributed networks. *Neural computing and applications*, 33:12073–12085, 2021.

[75] Yanling Wang, Jing Zhang, Shasha Guo, Hongzhi Yin, Cuiping Li, and Hong Chen. Decoupling representation learning and classification for gnn-based anomaly detection. In *Proceedings of the 44th international ACM SIGIR conference on research and development in information retrieval*, pages 1239–1248, 2021.

[76] Yili Wang, Yixin Liu, Xu Shen, Chenyu Li, Kaize Ding, Rui Miao, Ying Wang, Shirui Pan, and Xin Wang. Unifying unsupervised graph-level anomaly detection and out-of-distribution detection: a benchmark. *arXiv preprint arXiv:2406.15523*, 2024.

[77] Qitian Wu, Yiting Chen, Chenxiao Yang, and Junchi Yan. Energy-based out-of-distribution detection for graph neural networks. In *The Eleventh International Conference on Learning Representations*, 2022.

[78] Qitian Wu, Fan Nie, Chenxiao Yang, Tianyi Bao, and Junchi Yan. Graph out-of-distribution generalization via causal intervention. *arXiv preprint arXiv:2402.11494*, 2024.

[79] Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and Quoc V. Le. Self-training with noisy student improves imagenet classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[80] Bingbing Xu, Huawei Shen, Qi Cao, Keting Cen, and Xueqi Cheng. Graph convolutional networks using heat kernel for semi-supervised learning.

[81] Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken-ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In *International conference on machine learning*, pages 5453–5462. PMLR, 2018.

[82] Yujun Yan, Jiong Zhu, Marlena Duda, Eric Solarz, Chandra Sripada, and Danai Koutra. Groupinn: Grouping-based interpretable neural network for classification of limited, noisy brain data. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 772–782, 2019.

[83] Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *arXiv preprint arXiv:2110.11334*, 2021.

[84] Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. Graph convolutional neural networks for web-scale recommender systems. In *Proceedings of the 24th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 974–983, 2018.

[85] Junchi Yu, Jian Liang, and Ran He. Mind the label shift of augmentation-based graph ood generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11620–11630, 2023.

[86] Haonan Yuan, Qingyun Sun, Xingcheng Fu, Ziwei Zhang, Cheng Ji, Hao Peng, and Jianxin Li. Environment-aware dynamic graph learning for out-of-distribution generalization. *Advances in Neural Information Processing Systems*, 36, 2024.

[87] Reza Zafarani, Mohammad Ali Abbasi, and Huan Liu. *Social media mining: an introduction*. Cambridge University Press, 2014.

[88] Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor Prasanna. Graphsaint: Graph sampling based inductive learning method. In *International Conference on Learning Representations*, 2019.

[89] Ge Zhang, Jia Wu, Jian Yang, Amin Beheshti, Shan Xue, Chuan Zhou, and Quan Z Sheng. Fraudre: Fraud detection dual-resistant to graph inconsistency and imbalance. In *2021 IEEE International Conference on Data Mining (ICDM)*, pages 867–876. IEEE, 2021.

[90] Jinsong Zhang, Qiang Fu, Xu Chen, Lun Du, Zelin Li, Gang Wang, xiaoguang Liu, Shi Han, and Dongmei Zhang. Out-of-distribution detection based on in-distribution data patterns memorization with modern hopfield energy. In *The Eleventh International Conference on Learning Representations*, 2023.

[91] Tong Zhao, Yozen Liu, Leonardo Neves, Oliver Woodford, Meng Jiang, and Neil Shah. Data augmentation for graph neural networks. In *Proceedings of the aaai conference on artificial intelligence*, volume 35, pages 11015–11023, 2021.

[92] Xujiang Zhao, Feng Chen, Shu Hu, and Jin-Hee Cho. Uncertainty aware semi-supervised learning on graph data. *Advances in Neural Information Processing Systems*, 33:12827–12836, 2020.

[93] Cheng Zheng, Bo Zong, Wei Cheng, Dongjin Song, Jingchao Ni, Wenchao Yu, Haifeng Chen, and Wei Wang. Robust graph representation learning via neural sparsification. In *International Conference on Machine Learning*, pages 11458–11468. PMLR, 2020.

[94] Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *Advances in neural information processing systems*, 33:7793–7804, 2020.

[95] Yao Zhu, YueFeng Chen, Chuanlong Xie, Xiaodan Li, Rong Zhang, Hui Xue', Xiang Tian, bolun zheng, and Yaowu Chen. Boosting out-of-distribution detection with typical features. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho, editors, *Advances in Neural Information Processing Systems*, 2022.

A   Proofs

Theorem A.1. *(Recap of Theorem 3.2) For any two test ID/OOD node set $S_{id} \subset \mathcal{V}_{uid}, S_{ood} \subset \mathcal{V}_{uood}$ with equal size N_s, let the ID-vs-OOD separability $\mathcal{M}_{sep}$ defined on a OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$ as*

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) \triangleq \mathbb{E}_{i \in \mathcal{S}_{id}} \hat{\mathbf{g}}_i - \mathbb{E}_{j \in \mathcal{S}_{ood}} \hat{\mathbf{g}}_j.$$

If $\mathcal{M}_{sep}(\hat{\mathbf{g}}) > 0$ and $\eta_{intra} - \eta_{inter} > 1/N_s$, for some $\epsilon > 0$ and constant c, we have

$$\mathbb{P}\left(\mathcal{M}_{sep}(A\hat{\mathbf{g}}) \geq \mathcal{M}_{sep}(\hat{\mathbf{g}}) - \epsilon\right) \geq 1 - exp(-\frac{c\epsilon^2}{\|\hat{\mathbf{g}}\|_2^2}).$$

Proof. Without losing the generality, we set the $\hat{\mathbf{g}}_i = 0$, if $i \in S_{ood} \cup S_{id}$, since we only care about the detection results in the given test node set S_{ood} and S_{id}.

The $\mathcal{M}_{sep}(\hat{\mathbf{g}})$ can be re-written as

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) = \hat{\mathbf{g}}^\top (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}).$$

Then we have

$$\mathcal{M}_{sep}(A\hat{\mathbf{g}}) = \hat{\mathbf{g}}^\top A(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})$$

According to General Hoeffding's inequality (Theorem 2.6.3) in [70], we know that

$$\mathbb{P}\left(\mathbb{E}[\hat{\mathbf{g}}^\top A(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})] - \hat{\mathbf{g}}^\top A(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}) \leq \epsilon\right) \geq 1 - \exp(-\frac{c\epsilon^2}{\|\hat{\mathbf{g}}\|_2^2}),$$

where c is some constant value.

Since $\hat{\mathbf{g}}_i = 0$, if $i \in \mathcal{V}_l$,

$$\begin{aligned}
\mathbb{E}[\hat{\mathbf{g}}^\top A(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})] &= \hat{\mathbf{g}}^\top \mathbb{E}[A](\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}) \\
&= \hat{\mathbf{g}}^\top N_s(\eta_{intra} - \eta_{inter})(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}) \\
&> \hat{\mathbf{g}}^\top (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})
\end{aligned}$$

Combining together, we have

$$\mathbb{P}\left(\hat{\mathbf{g}}^\top A(\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}) \geq \hat{\mathbf{g}}^\top (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}) - \epsilon\right) \geq 1 - \exp(-\frac{c\epsilon^2}{\|\hat{\mathbf{g}}\|_2^2})$$

$\square$

Theorem A.2. *(Recap of Theorem 4.2) For any two test ID/OOD node set $S_{id} \subset \mathcal{V}_{uid}, S_{ood} \subset \mathcal{V}_{uood}$ with equal size N_s, let the ID-vs-OOD separability $\mathcal{M}_{sep}$ defined on a non-negative OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$ as*

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) \triangleq \mathbb{E}_{i \in \mathcal{S}_{id}} \hat{\mathbf{g}}_i - \mathbb{E}_{j \in \mathcal{S}_{ood}} \hat{\mathbf{g}}_j.$$

Let $\mathcal{E}_{S \leftrightarrow S'} \subset \mathcal{E}$ to denote the edge set of edges between two node sets S and S', where $S, S' \subset \mathcal{V}$. If we can find a node set $G \subset \mathcal{V}_l$ such that $|\mathcal{E}_{G \leftrightarrow S_{id}}| > |\mathcal{E}_{G \leftrightarrow S_{ood}}|$, we have

$$\mathcal{M}_{sep}((A + \delta E)^2 \hat{\mathbf{g}}) > \mathcal{M}_{sep}(A^2 \hat{\mathbf{g}}),$$

where $E = \mathbf{e}_G \mathbf{e}_G^\top$ and $\delta > 0$.

Proof. The $\mathcal{M}_{sep}(\hat{\mathbf{g}})$ can be re-written as

$$\mathcal{M}_{sep}(\hat{\mathbf{g}}) = \frac{1}{N_s} \hat{\mathbf{g}}^\top (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}}).$$

We can then directly derive the proof by expanding

$$
\begin{aligned}
\mathcal{M}_{sep}((A + \delta E)^2 \hat{\mathbf{g}}) - \mathcal{M}_{sep}(A^2 \hat{\mathbf{g}}) &= \frac{1}{N_s} (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})^\top \left((A + \delta E)^2 \hat{\mathbf{g}} - A^2 \hat{\mathbf{g}} \right) \\
&= \frac{1}{N_s} (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})^\top \left(\delta(AE + EA)\hat{\mathbf{g}} + \delta^2 \mathbf{e}_G \mathbf{e}_G^\top \mathbf{e}_G \mathbf{e}_G^\top \hat{\mathbf{g}} \right) \\
&= \frac{\delta}{N_s} (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})^\top \left(A \mathbf{e}_G \mathbf{e}_G^\top \hat{\mathbf{g}} + \mathbf{e}_G \mathbf{e}_G^\top A \hat{\mathbf{g}} \right) \\
&= \frac{\delta}{N_s} (\mathbf{e}_{S_{id}} - \mathbf{e}_{S_{ood}})^\top A \mathbf{e}_G \mathbf{e}_G^\top \hat{\mathbf{g}} \\
&= \frac{\delta}{N_s} (\mathbf{e}_G^\top \hat{\mathbf{g}})(\mathbf{e}_{S_{id}}^\top A \mathbf{e}_G - \mathbf{e}_{S_{ood}}^\top A \mathbf{e}_G) \\
&= \frac{\delta(\mathbf{e}_G^\top \hat{\mathbf{g}})}{|G| N_s} (|\mathcal{E}_{G \leftrightarrow S_{id}}| - |\mathcal{E}_{G \leftrightarrow S_{ood}}|) \\
&> 0,
\end{aligned}
$$

where the second and the third equation are derived by the fact that $G \subset \mathcal{V}_l$ and then we have $\mathbf{e}_{S_{id}}^\top \mathbf{e}_G = 0$ and $\mathbf{e}_{S_{ood}}^\top \mathbf{e}_G = 0$.

$\square$

B Details of Baselines

For the reader's convenience, we summarize in detail a few common techniques for defining OOD scores that measure the degree of ID-ness on a given input. By convention, a higher (lower) score is indicative of being in-distribution (out-of-distribution).

MSP [23] This method proposes to use the maximum softmax score as the OOD score. For each node i, we use $F_{OODD}(i) = \max_{c \in [C]} f_c(i)$ as the OOD score.

ODIN [43] This method improves OOD detection with temperature scaling and input perturbation. In all experiments, we set the temperature scaling parameter $T = 1000$. For graph neural network, we found the input perturbation does not further improve the OOD detection performance and hence we set $\epsilon = 0$.

Mahalanobis [37] This method uses multivariate Gaussian distributions to model class-conditional distributions of softmax neural classifiers and uses Mahalanobis distance-based scores for OOD detection. The mean μ_c of each multivariate Gaussian distribution with class c and a tied covariance $\boldsymbol{\Sigma}$ are estimated based on training samples. We define the confidence score $M(\mathbf{x})$ using the Mahalanobis distance between test sample $\mathbf{x}$ and the closest class-conditional Gaussian distribution.

Energy [47] This method proposes using energy score for OOD detection. The energy function maps the logit outputs to a scalar $E(\mathbf{x}_i; f) \in \mathbb{R}$, which is relatively lower for ID data. Note that [47] used the *negative energy score* for OOD detection, in order to align with the convention that $S(\mathbf{x})$ is higher (lower) for ID (OOD) data.

KNN [67] This method uses the k-th nearest neighbor distance between a test graph node and the training set as the OOD score. We use $k = 10$ for all experiments in this paper.

C Dataset Details

We adopt ten publicly available benchmarks used for graph learning, covering diverse domains, scales, and structures (homophily or heterophily). For five homophily datasets `Cora`, `Amazon-Photo`, `Coauthor-CS`, `Reddit2` and `ogbn-products`, we use the data loader provided by the Pytorch Geometric package [3]. For the remaining five heterophily datasets, we directly use the pickle file or download from the given hyperlinks proposed by [44].

`Cora` [61] is a 7-class citation network comprising 2,708 nodes, 5,429 edges and 1,433 features. In this network, each node represents a published paper, each edge signifies a citation relationship, and the label class is each paper's topic, which is the goal to predict.

---

[3]https://pytorch-geometric.readthedocs.io/en/latest/modules/datasets.html

`Amazon-Photo` [52] is an 8-class item co-purchasing network on Amazon, which contains 7,650 nodes, 238,162 edges and 745 features. In this network, each node denotes a product, each edge indicates that two linked products are frequently purchased together, and the node label denotes the category of the product.

`Coauthor-CS` [62] is a 15-class coauthor network of computer science, which contains 18,333 nodes, 163,788 edges and 6,805 features. In this network, nodes denote authors and there is an edge between two authors if co-authored a paper. And the label represents the study field for the authors.

`Reddit2` [88] is a large homophily post network with 41 classes, where nodes are posts based on user comments and the task is to predict communities of online posts based on user comments.

`ogbn-products` [24] is a super large homophily undirected and unweighted graph with 47 classes, representing an Amazon product co-purchasing network. Nodes represent products sold in Amazon, and edges between two products indicate that the products are purchased together. The task is to predict the category of a product in a multi-class classification setup, where the 47 top-level categories are used for target labels.

`Chameleon` and `Squirrel` [59] are two Wikipedia networks with 5 classes, where nodes represent web pages and edges represent hyperlinks between them. Node features represent several informative nouns in the Wikipedia pages and the task is to predict the average daily traffic of the web page [17].

`arXiv-year` [24] is the ogbn-arXiv network with different labels and is altered to be heterophily, in which the class labels are set to be the year that the paper is posted, instead of subject area in the original paper. The nodes are arXiv papers, and directed edges connect a paper to other papers that it cites. The node features are averaged word2vec token features of both the title and abstract of the paper. The five classes are chosen by partitioning the posting dates so that class ratios are approximately balanced [44].

`snap-patents` [39, 38] is a big dataset of utility patents in the US. Each node represents a patent and edges connect patents that cite each other. Node features are derived from patent metadata [44]. Like `arXiv-year`, this dataset is changed to set the task to predict the time at which a patent was granted, which is also five classes.

`wiki` [44] is a super big dataset of Wikipedia articles, which are crawled and cleaned from the internet. Nodes represent pages and edges represent links between them. Node features are derived from the average GloVe embeddings [54] of the titles and abstracts and labels indicate total page views over a 60-day period, categorized into five classes based on quintiles.

The complete information and statistics of all these datasets aforementioned are summarized in Table 7.

Table 7: Statistics of all the graph datasets. # C is the total number of distinct node classes.

Dataset	# Nodes	# Edges	# Features	# C	Domain	Homoph	OOD Class	ID Class
Cora	2,708	5,429	1,433	7	citation	✓	$\{0, \cdots, 3\}$	$\{4, 5, 6\}$
Amazon-Photo	7,650	238,162	745	8	product	✓	$\{0, \cdots, 4\}$	$\{5, 6, 7\}$
Coauthor-CS	18,333	163,788	6,805	15	citation	✓	$\{0, \cdots, 3\}$	$\{4, \cdots, 14\}$
Reddit2	232,965	23,213,838	602	41	post	✓	$\{0, \cdots, 10\}$	$\{11, \cdots, 40\}$
ogbn-products	2,449,029	61,859,140	100	47	product	✓	$\{0, \cdots, 11\}$	$\{12, \cdots, 46\}$
Chameleon	2,277	31,421	2,325	5	Wikipedia	✗	$\{0, 1\}$	$\{2, 3, 4\}$
Squirrel	5,201	198,493	2,089	5	Wikipedia	✗	$\{0, 1\}$	$\{2, 3, 4\}$
arXiv-year	169,343	1,166,243	128	5	citation	✗	$\{0, 1\}$	$\{2, 3, 4\}$
snap-patents	2,923,922	13,975,788	269	5	patent	✗	$\{0, 1\}$	$\{2, 3, 4\}$
wiki	1,925,342	303,434,860	600	5	Wikipedia	✗	$\{0, 1\}$	$\{2, 3, 4\}$

D Additional Experiments

D.1 Graph ID Classification Details

In this section, we provide a detailed report on the ID ACC results of nine popular GNN pretrained backbones used in our paper, including GCN [34], GAT [69], GCNJK [81], GATJK [81], APPNP [35], MixHop [1], GPR-GNN [10], GCNII [7], and H_2GCN [94]. The results of all the nine architectures on five common benchmarks and architecture GCN on five large-scale benchmarks are presented in Table 8 and Table 9 respectively. In addition, we present the ID ACC results of three training-based methods on the ten benchmarks. It is important to note that these training-based methods only yield results on five small-scale datasets and the moderately sized arxiv-year dataset. They fail to produce results on the remaining four large datasets, as shown in Tables 10 and Table 11.

Table 8: ID ACCs of six pre-trained methods on common benchmarks. For each pre-trained method, we take the average values that are percentages over 5 independently trained backbones.

Backbone	Cora	Amazon	Coauthor	Chameleon	Squirrel
GCN	93.89 ± 1.31	96.72 ± 0.76	96.21 ± 0.61	71.20 ± 2.07	72.32 ± 2.02
GAT	93.89 ± 1.64	96.44 ± 0.92	95.67 ± 0.35	73.43 ± 3.42	75.88 ± 1.73
GCNJK	92.92 ± 2.03	96.88 ± 0.56	95.93 ± 0.32	71.03 ± 2.41	72.22 ± 0.71
GATJK	93.27 ± 1.91	96.31 ± 0.38	95.78 ± 0.26	74.55 ± 1.95	76.47 ± 1.45
GCNII	94.07 ± 1.28	96.62 ± 0.57	96.97 ± 0.37	73.08 ± 1.78	72.57 ± 1.92
H_2GCN	94.07 ± 1.84	96.26 ± 0.74	94.57 ± 0.43	71.85 ± 2.21	74.73 ± 1.11
APPNP	91.44 ± 1.48	95.63 ± 0.19	95.79 ± 0.28	54.77 ± 1.66	42.87 ± 2.07
MixHop	86.05 ± 4.01	93.47 ± 1.31	93.80 ± 0.28	59.48 ± 3.15	53.18 ± 0.69
GPR-GNN	91.02 ± 1.76	95.35 ± 0.14	96.04 ± 0.16	46.24 ± 10.26	45.73 ± 0.95

Table 9: ID ACCs of pre-trained GCN models on five large-scale datasets. We report the average values that are percentages over 5 independently trained backbones.

Backbone	reddit2	ogbn-products	arxiv-year	snap-patents	wiki
GCN	51.36 ± 0.35	74.39 ± 0.09	56.67 ± 0.33	62.48 ± 0.10	54.89 ± 0.16

Table 10: ID ACCs of three training-based ood detection methods on five small-scale datasets. For each method, we take the average values that are percentages over 5 independently runs.

Method	Cora	Amazon	Coauthor	Chameleon	Squirrel
GKDE	91.40 ± 1.39	91.30 ± 2.30	96.14 ± 0.50	65.22 ± 1.67	53.29 ± 2.97
GPN	91.49 ± 1.51	93.96 ± 2.39	89.83 ± 4.25	62.40 ± 1.40	46.27 ± 5.37
OODGAT	76.02 ± 7.77	61.88 ± 1.19	31.71 ± 1.06	61.00 ± 2.84	50.88 ± 2.35

Table 11: ID ACCs of three training-based methods on five large-scale datasets, where OOM means Out-Of-Memory and OOT denotes that no results have been got after running over 48 hours for each run. All the training-based methods only have results on the moderately sized arXiv-year dataset. For each method, we take the average values that are percentages over 5 independently runs.

Method	reddit2	ogbn-products	arxiv-year	snap-patents	wiki
GKDE	OOM	OOM	OOT	OOM	OOM
GPN	OOM	OOM	43.07 ± 2.02	OOM	OOM
OODGAT	OOM	OOM	43.43 ± 0.36	OOM	OOM

D.2 Detailed Main Graph OOD Detection Results

Table 12: **Detailed main results on common benchmarks.** Comparison with competitive out-of-distribution detection methods on pre-trained GCN. We take the average values with standard errors that are percentages over 5 independently trained backbones. ↑ (↓) indicates larger (smaller) values are better.

Method	Cora		Amazon		Coauthor		Chameleon		Squirrel	
	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑
MSP	70.86 ± 15.88	84.56 ± 5.39	49.26 ± 10.51	89.34 ± 3.49	28.82 ± 1.94	94.34 ± 0.41	85.70 ± 7.09	57.96 ± 3.31	94.68 ± 1.01	48.51 ± 0.46
Energy	67.54 ± 22.98	85.47 ± 4.98	42.13 ± 9.96	90.28 ± 3.42	20.29 ± 1.49	95.67 ± 0.25	88.06 ± 7.50	59.20 ± 4.31	93.98 ± 1.42	45.07 ± 1.68
KNN	90.20 ± 4.35	70.94 ± 5.62	65.19 ± 7.26	84.71 ± 3.28	51.24 ± 1.83	90.13 ± 0.50	93.38 ± 5.48	57.90 ± 6.48	94.72 ± 2.84	54.68 ± 2.25
ODIN	68.41 ± 18.48	84.98 ± 5.59	44.06 ± 10.69	89.90 ± 3.65	22.59 ± 1.76	95.27 ± 0.33	85.31 ± 7.64	57.94 ± 3.75	94.17 ± 0.44	44.08 ± 0.35
Mahalanobis	69.68 ± 14.60	85.48 ± 1.69	96.49 ± 5.96	75.58 ± 7.97	85.71 ± 1.82	84.98 ± 0.58	95.55 ± 2.36	53.19 ± 4.30	94.90 ± 0.51	54.99 ± 0.70
GKDE	63.71 ± 14.36	86.27 ± 2.69	81.29 ± 3.36	77.26 ± 5.54	25.48 ± 1.48	95.13 ± 0.29	92.93 ± 4.89	50.14 ± 5.50	96.71 ± 0.67	49.38 ± 3.58
GPN	58.45 ± 31.98	82.93 ± 11.20	72.95 ± 19.77	82.63 ± 5.87	34.11 ± 22.46	93.82 ± 2.63	82.25 ± 6.55	68.20 ± 6.70	95.58 ± 1.65	48.38 ± 4.43
OODGAT	94.59 ± 6.38	53.63 ± 5.13	71.34 ± 15.34	66.95 ± 16.02	96.53 ± 3.39	52.18 ± 8.26	94.43 ± 3.43	59.67 ± 6.37	95.27 ± 1.00	46.13 ± 3.10
GNNSafe	54.71 ± 31.41	87.52 ± 6.16	22.39 ± 4.90	96.27 ± 0.31	16.64 ± 1.90	95.82 ± 0.28	100.00 ± 0.00	50.42 ± 0.65	100.00 ± 0.00	35.88 ± 0.24
NODESafe	45.73 ± 21.86	89.70 ± 4.60	63.25 ± 23.15	79.03 ± 13.00	39.06 ± 25.23	87.45 ± 13.31	100.00 ± 0.00	50.34 ± 0.58	100.00 ± 0.00	36.18 ± 0.23
fDBD	81.56 ± 10.45	56.77 ± 12.97	51.87 ± 13.89	73.31 ± 7.86	59.68 ± 3.50	63.10 ± 1.01	89.85 ± 11.80	50.85 ± 14.89	94.78 ± 1.30	53.17 ± 3.24
GRASP	29.70 ± 12.25	93.50 ± 1.65	14.38 ± 6.63	96.68 ± 0.28	7.84 ± 0.58	97.75 ± 0.18	66.88 ± 6.48	76.93 ± 4.18	85.59 ± 3.61	61.09 ± 1.49

Table 13: **Detailed main results on large-scale benchmarks.** Comparison with competitive out-of-distribution detection methods on pre-trained method GCN. We take the average values with standard errors that are percentages over 5 independently trained backbones. OOM means Out-Of-Memory and OOT denotes that no results have been got after running over 48 hours for each run. ↑ (↓) indicates larger (smaller) values are better.

Method	reddit2		ogbn-products		arxiv-year		snap-patents		wiki	
	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑
MSP	96.59 ± 0.14	46.61 ± 0.66	86.87 ± 0.35	70.19 ± 0.92	95.03 ± 1.46	47.24 ± 3.70	94.31 ± 0.30	46.99 ± 0.83	95.46 ± 0.32	54.70 ± 0.68
Energy	96.77 ± 0.03	44.13 ± 0.14	85.09 ± 0.45	68.13 ± 0.38	94.10 ± 2.76	51.35 ± 5.91	96.82 ± 1.07	46.03 ± 4.59	97.31 ± 1.54	29.02 ± 2.78
KNN	90.78 ± 0.75	66.74 ± 0.55	84.22 ± 2.00	73.58 ± 1.21	95.35 ± 0.92	57.96 ± 2.19	90.54 ± 1.09	53.45 ± 0.93	93.43 ± 2.57	43.69 ± 4.83
ODIN	96.74 ± 0.07	44.69 ± 0.24	85.65 ± 0.31	68.95 ± 0.52	95.06 ± 1.47	47.36 ± 3.46	94.27 ± 0.30	45.20 ± 0.87	97.88 ± 0.18	29.91 ± 0.47
Mahalanobis	71.73 ± 1.55	74.89 ± 1.01	OOM	-	88.60 ± 1.27	59.57 ± 1.27	96.03 ± 0.22	58.50 ± 0.81	72.33 ± 2.15	67.95 ± 1.56
GKDE	OOT	-	OOM	-	OOM	-	OOM	-	OOM	-
GPN	OOM	-	OOM	-	95.62 ± 3.29	50.97 ± 14.98	OOM	-	OOM	-
OODGAT	OOM	-	OOM	-	92.90 ± 0.94	59.38 ± 3.44	OOM	-	OOM	-
GNNSafe	99.49 ± 0.07	31.99 ± 0.26	77.86 ± 1.09	85.66 ± 1.16	100.00 ± 0.00	35.30 ± 0.06	99.92 ± 0.18	27.35 ± 0.18	72.63 ± 2.05	60.32 ± 4.51
NODESafe	86.47 ± 10.45	47.00 ± 9.33	OOT	-	100.00 ± 0.00	35.32 ± 0.04	100.00 ± 0.00	27.27 ± 0.01	OOT	-
fDBD	89.78 ± 0.73	55.72 ± 0.88	83.41 ± 0.53	66.67 ± 1.15	95.82 ± 2.23	48.87 ± 9.73	94.99 ± 0.20	43.27 ± 2.50	96.53 ± 0.55	59.32 ± 1.23
GRASP	2.41 ± 0.09	98.50 ± 0.02	39.77 ± 1.25	93.79 ± 0.24	73.93 ± 0.60	81.24 ± 0.39	75.22 ± 0.09	72.13 ± 0.06	58.49 ± 1.07	77.97 ± 1.38

D.3 Graph OOD Detection Results on Various Backbones

GRASP can seamlessly be applied to various GNN backbones. In this section, we report the OOD detection performance of all baselines on various popular architectures in Table 14

Table 14: Results of various GNN pretrained backbones on common benchmarks.

Pre-trained Backbone	OOD Detection Method	Cora FPR↓	Cora AUROC↑	Amazon FPR↓	Amazon AUROC↑	Coauthor FPR↓	Coauthor AUROC↑	Chameleon FPR↓	Chameleon AUROC↑	Squirrel FPR↓	Squirrel AUROC↑
GCN	MSP	70.86	84.56	49.26	89.34	28.82	94.34	85.70	57.96	94.68	48.51
	Energy	67.54	85.47	42.13	90.28	20.29	95.67	88.06	59.20	93.98	45.07
	KNN	90.20	70.94	65.19	84.71	51.24	90.13	93.38	57.90	94.72	54.68
	ODIN	68.41	84.98	44.06	89.90	22.59	95.27	85.31	57.94	94.17	44.08
	Mahalanobis	69.68	85.48	96.49	75.58	85.71	84.98	95.55	53.19	94.90	54.99
	GNNSafe	54.71	87.52	22.39	96.27	16.64	95.82	100.00	50.42	100.00	35.88
	GRASP (ours)	**29.70**	**93.50**	**14.38**	**96.68**	**7.84**	**97.75**	**66.88**	**76.93**	**85.59**	**61.09**
GAT	MSP	55.33	88.82	29.88	94.39	28.15	94.26	91.27	61.94	95.21	47.50
	Energy	80.71	79.16	26.48	95.24	20.96	95.65	92.71	61.11	96.47	45.69
	KNN	71.14	81.28	46.42	90.74	42.51	91.51	89.02	61.13	95.37	53.16
	ODIN	55.27	89.06	26.92	94.89	24.61	94.95	90.83	62.89	96.11	45.68
	Mahalanobis	67.92	86.37	14.28	95.80	26.27	94.46	95.35	50.65	91.36	57.67
	GNNSafe	58.97	85.64	29.12	93.16	25.41	93.91	100.00	50.39	100.00	36.21
	GRASP (ours)	**22.76**	**94.28**	**14.21**	**96.79**	**8.59**	**97.51**	**70.15**	**73.40**	**85.84**	**61.18**
GCNJK	MSP	81.33	80.40	32.45	94.64	26.43	94.44	86.42	68.19	94.93	51.83
	Energy	96.56	70.16	40.90	93.80	18.75	95.75	91.92	65.16	95.36	49.68
	KNN	90.98	73.81	64.47	85.18	50.95	89.98	94.45	59.04	94.64	53.49
	ODIN	81.04	80.68	28.35	95.13	21.12	95.41	86.03	68.58	95.04	50.64
	Mahalanobis	60.84	86.20	61.61	87.11	83.04	87.34	87.23	66.61	91.52	57.24
	GNNSafe	65.01	83.11	22.41	96.28	13.27	96.47	100.00	50.40	100.00	36.21
	GRASP (ours)	**29.69**	**92.98**	**12.66**	**96.86**	**8.03**	**97.74**	**59.61**	**75.78**	**86.02**	**60.70**
GATJK	MSP	69.56	84.51	47.21	91.32	24.66	95.37	94.39	55.43	94.67	50.98
	Energy	62.27	85.75	34.75	92.89	17.23	96.38	91.11	59.01	95.61	48.76
	KNN	82.54	74.32	70.98	83.48	38.95	92.56	92.21	61.14	95.20	54.32
	ODIN	64.25	85.21	39.29	92.19	18.16	96.30	93.56	56.10	95.24	48.62
	Mahalanobis	79.60	79.33	52.79	88.53	34.60	93.68	91.59	52.38	91.52	56.19
	GNNSafe	44.43	90.01	22.46	95.45	17.54	95.32	100.00	50.39	100.00	36.15
	GRASP (ours)	**29.04**	**92.57**	**14.78**	**96.70**	**8.32**	**97.70**	**78.65**	**71.09**	**85.88**	**61.17**
APPNP	MSP	59.37	89.01	64.64	86.51	18.38	96.45	94.24	48.87	94.41	50.91
	Energy	81.82	81.21	62.87	84.36	14.57	97.01	90.55	55.75	90.91	53.04
	KNN	75.33	81.21	49.55	89.76	38.44	91.71	92.14	54.19	94.12	53.14
	ODIN	56.72	89.47	60.67	86.76	15.02	96.98	94.63	50.71	94.41	50.60
	Mahalanobis	73.64	86.02	98.75	62.13	30.20	93.91	92.38	58.15	93.29	56.65
	GNNSafe	59.70	85.45	19.26	95.08	12.10	96.60	100.00	50.45	100.00	36.24
	GRASP (ours)	**26.45**	**94.16**	**5.69**	**97.11**	**8.69**	**97.59**	**83.41**	**63.02**	**86.42**	**60.76**
H$_2$GCN	MSP	67.00	86.50	59.23	86.88	99.37	40.35	91.00	62.79	94.34	57.21
	Energy	68.06	86.84	57.05	86.21	97.85	51.65	92.66	63.24	96.75	53.18
	KNN	80.00	79.68	63.85	80.54	60.66	77.25	95.13	56.89	95.62	57.45
	ODIN	65.21	87.10	56.25	86.97	99.43	41.58	91.07	63.52	95.08	55.69
	Mahalanobis	81.67	80.55	86.26	77.33	97.92	61.02	97.62	58.29	96.36	53.54
	GNNSafe	43.97	88.83	33.40	90.87	93.00	43.23	100.00	50.35	100.00	36.26
	GRASP (ours)	**33.54**	**92.63**	**16.57**	**96.48**	**14.23**	**96.08**	**66.38**	**74.72**	**86.04**	**60.83**
MixHop	MSP	83.94	78.60	53.56	90.97	48.66	90.91	92.95	56.77	95.60	49.07
	Energy	83.67	77.15	57.04	89.28	28.49	94.67	94.10	57.21	95.61	48.87
	KNN	93.36	69.93	65.41	86.45	62.40	85.91	89.52	57.64	93.44	54.00
	ODIN	83.14	79.10	50.00	91.25	41.39	92.65	93.45	56.48	95.68	47.58
	Mahalanobis	82.35	80.04	90.05	81.85	47.41	91.67	93.93	56.30	91.33	56.56
	GNNSafe	66.86	83.77	39.72	93.54	33.83	92.46	100.00	50.35	100.00	36.42
	GRASP (ours)	**32.11**	**92.77**	**10.07**	**96.99**	**9.41**	**97.31**	**76.92**	**66.12**	**85.92**	**60.69**
GPR-GNN	MSP	64.90	87.44	62.84	87.66	23.96	95.64	96.09	47.65	95.78	44.62
	Energy	72.85	83.86	64.23	85.28	16.42	96.50	93.78	49.09	95.16	42.63
	KNN	74.24	81.46	48.47	90.48	38.83	92.31	94.39	55.31	94.18	51.74
	ODIN	62.58	88.13	55.49	88.41	17.24	96.51	96.16	47.50	95.51	42.32
	Mahalanobis	79.56	84.53	97.25	69.75	49.93	91.56	87.01	55.95	87.24	61.10
	GNNSafe	51.65	85.91	13.63	96.46	14.73	95.96	100.00	50.32	100.00	36.25
	GRASP (ours)	**26.71**	**94.02**	**5.30**	**97.14**	**8.28**	**97.70**	**76.53**	**72.43**	**85.40**	**61.33**
GCNII	MSP	72.85	83.02	51.72	88.13	23.18	95.21	96.03	55.46	94.13	49.46
	Energy	83.15	75.24	48.28	88.78	17.72	96.03	95.87	56.75	94.61	48.63
	KNN	83.99	76.02	59.25	86.74	36.05	93.43	94.72	52.86	94.65	53.47
	ODIN	71.49	83.31	49.44	88.35	19.44	95.75	95.61	56.63	94.73	48.34
	Mahalanobis	73.90	82.01	77.63	80.87	44.01	92.63	96.68	46.57	91.66	53.62
	GNNSafe	66.70	83.12	27.08	93.13	17.87	94.47	100.00	50.35	100.00	36.32
	GRASP (ours)	**27.92**	**93.51**	**23.53**	**93.72**	**8.82**	**97.61**	**76.79**	**66.44**	**86.27**	**60.62**

D.4 Analysis of Hyper-parameters Sensitivity

We show the sensitivity of hyper-parameters α, β and k in Figure 6. The vertical axis in the figure represents the average AUROC values across common datasets. The performance comparison in the bar plot for each hyper-parameter is reported by fixing other hyper-parameters. We see that within the range of chosen hyperparameter values, our proposed method's performance does not vary significantly, which constantly outperforms baselines by a large margin.

Figure 6: Sensitivity analysis of all the hyper-parameters and the averaged AUROC values of common benchmarks on model GCN with MSP are displayed. The middle bar in each plot corresponds to the hyperparameter value used in our main experiments.

D.5 Relationship between Ratio of Intra-Edges and OOD Detection performance

Figure 7: Ratio of intra-edges and OOD detection performance have strong positive correlation.

As shown in Figure 7, the ratio of intra-edges and OOD detection performance have strong positive correlation. This validates the correctness of Theorem 4.2. The detailed the number in Figure 7 are listed in Table 15. From the table we can see that after using our proposed augmentation, the ratio of intra-edges increases and in turn boosts the OOD detection performance.

Table 15: Ratios of intra-edges η_{intra} and respective OOD detection performance on all benchmarks before and after employing graph augmentation.

Datasets	Before Aug		After Aug	
	η_{intra}	AUROC	η_{intra}	AUROC
cora	82.31	87.52	92.23	93.50
amazon	93.44	96.27	96.56	96.68
coauthor	92.68	95.82	97.18	97.75
chameleon	57.03	50.42	78.81	76.93
squirrel	39.45	35.88	62.54	61.09
reddit2	40.30	31.99	97.90	98.50
ogbn-products	81.98	85.66	93.56	93.79
arxiv-year	41.93	35.30	82.15	81.24
snap-patents	34.74	27.35	71.74	72.13
wiki	60.31	60.32	79.64	77.97

D.6 Computational Complexity Analysis

Our method's computational footprint in terms of runtime and memory usage after propagation for k times is:

- Time Complexity: $\mathcal{O}(N + 2k|\mathcal{E}| + n)$

- Memory Complexity: $\mathcal{O}(N + |\mathcal{E}| + n)$

While our algorithm introduces the fully connected matrix E, which brings about explosive growth of connections after each propagation and results in challenges in performing related computations, we adeptly transform the complex and time-consuming structural computations into simple matrix-vector multiplication operations, making original expensive operation tractable and leading to efficient linear complexity. Below, we provide the support from both mathmatical and empirical points.

Complexity analysis. Our method consists of two major computational modules, specifically, (a) calculating connections between training nodes and testing nodes; (b) augmentation propagation.

(a) *Calculating connections between training nodes and testing nodes.* We utilize two indicator vectors, I_{id} and I_{ood}, both with a length of nodes number N, to represent the number of connections each node has with S_{id} and S_{ood}, respectively. The initial values of I_{id} are set to 1 at the indices corresponding to S_{id} and 0 at the remaining indices (corresponding to S_{ood}). The initial value of I_{id} is denoted as $I_{id}^{(0)}$. Similarly, I_{ood} has a initial value of 1 at all indices corresponding to S_{ood} and 0 at the indices corresponding to S_{id}. We also represent the initial value of I_{ood} as $I_{ood}^{(0)}$. After propagation for k times, the connections between each node with S_{id} are:

$$
\begin{aligned}
I_{id}^{(k)} &= A^k I_{id}^{(0)} \\
&= A^{k-1} \cdot A I_{id}^{(0)} \\
&= A^{k-1} \cdot I_{id}^{(1)} \\
&= (\text{run } k - 1 \text{ times ...})
\end{aligned}
$$

In the above equation, $AI_{id}^{(i)}$ can be computed in $\mathcal{O}(|\mathcal{E}_{id}|)$ with sparse matrix multiplication for each propagation, where $|\mathcal{E}_{id}|$ represents number of edges connected to S_{id} nodes.

The above abalysis and conclusion also applys to computing $I_{ood}^{(k)}$, resulting computational complexity $\mathcal{O}(|\mathcal{E}_{ood}|)$, where $|\mathcal{E}_{ood}|$ is number of edges connected to S_{ood} nodes. This leads to time and memory costs $\mathcal{O}(|\mathcal{E}_{id}| + |\mathcal{E}_{ood}|) = \mathcal{O}(|\mathcal{E}|)$ for calculating needed number of connections in each propagation and $\mathcal{O}(k|\mathcal{E}|)$ and $\mathcal{O}(|\mathcal{E}|)$ for time and memory costs after propagation for k times, respectively.

(b) *Augmentation propagation.* As described by Equation 6 in the main paper, given a raw OOD scoring vector $\hat{\mathbf{g}} \in \mathbb{R}^N$, the propagated scoring vector using augmented adjacency matrix after

propagation for k times is given by:

$$\begin{aligned}
\mathbf{g}_{GRASP} &= (\bar{A}_+)^k \hat{\mathbf{g}} \\
&= (D_+^{-1} A_+)^k \hat{\mathbf{g}} \\
&= (D_+^{-1} A_+)^{k-1} \cdot (D_+^{-1}(A + E)) \hat{\mathbf{g}} \\
&= (D_+^{-1} A_+)^{k-1} \cdot (D_+^{-1} \boxed{A\hat{\mathbf{g}}} + D_+^{-1} \boxed{E\hat{\mathbf{g}}}) \\
&= (\text{run } k - 1 \text{ times ...})
\end{aligned}$$

In the above equation,

- $E\hat{\mathbf{g}}$ can be computed with time/space complexity $\mathcal{O}(n)$ by a simple summation operation ($\mathbf{g}_i$ in G will be replaced by $\sum_{i \in G} \mathbf{g}_i$) to get rid of the matrix multiplication.
- $A\hat{\mathbf{g}}$ can be computed in $\mathcal{O}(|\mathcal{E}|)$ with sparse matrix multiplication.
- D_+^{-1} is an $\mathcal{O}(N)$ operation since it is scaling over all elements in the vector.

Above all, the time/memory complexity of augmented propagation is $\mathcal{O}(N + |\mathcal{E}| + n)$ for each propagation and the time and memory costs are $\mathcal{O}(N + k|\mathcal{E}| + n)$ and $\mathcal{O}(N + |\mathcal{E}| + n)$ for k times respectively with memory reutilization.

Integrating the above two considerations, the time complexity of our algorithm after propagation for k times is $\mathcal{O}(N + 2k|\mathcal{E}| + n)$, while the space complexity is $\mathcal{O}(N + |\mathcal{E}| + n)$. Notably, the utilization of space reuse results in a linear space complexity.

Empirical results. Then we conduct comprehensive experiments comparing the time and space costs of our algorithm with various baselines (both post-hoc and training-based approaches) in Table 16 and Table 17. From the experimental results, it is evident that our algorithm is highly efficient across all datasets.

Based on the experimental results in Table 16 and Table 17, we have:

- In comparison to training-based methods, post-hoc methods exhibit significantly lower runtime and memory consumption.
- Considering that the minimum time and space complexity required to run a graph algorithm is $\mathcal{O}(N + |\mathcal{E}|)$, as outlined in our algorithm complexity analysis, our algorithm incurs limited additional time and space costs, specifically $\mathcal{O}(|\mathcal{E}|)$ and $\mathcal{O}(n)$ on time and memory costs respectively in each propagation. This can be validated by the small extra overhead incurred by our algorithm compared to MSP or Energy from the table.
- Compared with training-based methods, our algorithm demonstrates substantially lower time and space demands on five large-scale datasets. And when compared to post-hoc baselines on these datasets, the overhead of our method is also reasonable. The performance of our method on these large-scale datasets underscores the strong practicality of our approach.

Table 16: Time (s) and Memory (M) costs of all algorithms with backbone GCN on common benchmarks.

| Method | Cora | | Amazon | | Coauthor | | Chameleon | | Squirrel | |
	time	memory	time	memory	time	memory	time	memory	time	memory
GKDE	26.72038	3366.0078	160.00094	3388.5859	1004.73209	4199.8438	37.24027	3310.9219	170.25729	3234.3828
GPN	28.63986	3702.5703	58.71772	3719.0977	77.55155	3634.6562	50.64548	3620.9688	50.69732	3650.5781
OODGAT	77.98510	3369.0039	395.87711	3390.8789	411.43511	3851.3672	182.10900	3291.6289	454.62221	3319.9883
MSP	0.02508	622.7852	0.03915	635.4102	0.13018	1092.0469	0.04835	634.0508	0.05129	657.9961
Energy	0.04687	624.1016	0.09624	636.5156	0.11084	1094.7227	0.10995	634.7500	0.11732	660.5039
KNN	0.24068	630.9219	0.12629	658.2109	0.29778	1101.2969	0.17183	636.4375	0.14258	660.1758
ODIN	0.01500	621.8164	0.04800	636.4023	0.07353	1093.6406	0.16158	635.4062	0.06357	659.5781
Mahalanobis	0.14636	627.3945	0.22022	641.2070	0.28823	1099.3750	0.20611	637.1797	0.18573	661.4375
GNNSafe	0.05700	626.2344	0.14713	652.7969	0.34739	1106.1875	0.12293	637.9531	0.10340	662.4766
GRASP(ours)	0.05305	628.7930	0.14779	677.2617	0.25272	1118.0156	0.14554	644.0938	0.12774	668.0742

Table 17: Time (s) and Memory (M) costs of all algorithms with backbone GCN on large-scale benchmarks.

Method	reddit2		ogbn-products		Datasets arxiv-year		snap-patents		wiki	
	time	memory	time	memory	time	memory	time	memory	time	memory
GKDE	-	OOM	-	OOM	OOT	-	-	OOM	-	OOM
GPN	-	OOM	-	OOM	444.83901	3808.7227	-	OOM	-	OOM
OODGAT	-	OOM	-	OOM	1214.97670	3491.1055	-	OOM	-	OOM
MSP	0.26172	2588.9844	0.4599	4571.1289	0.35540	726.5898	8.91248	4014.2188	431.68647	9765.8008
Energy	0.26987	2590.5273	0.49488	4567.3398	0.51500	726.1719	14.84026	4039.9102	296.09063	9788.4453
KNN	3.48512	2697.3789	4247.99327	4699.3047	3.77242	732.8984	6241.00550	3933.3164	3180.91959	9812.8906
ODIN	0.28509	2587.1289	0.49385	4562.1719	0.61390	727.6797	3.60580	4005.2305	244.30793	9760.2422
Mahalanobis	1.95486	2703.2734	-	OOM	1.27940	730.4141	5.92890	4056.0820	243.92857	9829.1562
GNNSafe	0.85545	2621.5547	4.19187	4589.9609	0.97220	790.1992	17.00348	4187.6680	365.39017	9655.1055
GRASP(ours)	1.86865	2628.3633	9.62959	4647.5273	0.67847	768.2070	20.97008	4279.9219	649.71668	9724.7852

D.7 Explore How Different Propagation Mechanisms Impact the Findings.

In this section, we investigate the effect of different propagation mechanisms on graph OOD detection performance, like higher-order diffusion and the other various classical propagation mechanisms in the literature, including Personalized PageRank (PPR) [35], Heat Kernel Diffusion (GraphHeat) [80], Graph Diffusion Convolution (GDC) [20], Mixing Higher-Order Propagation (MixHop) [1], and Generalized PageRank (GPR) [10]. The emperical observations are as follows:

- From the analysis of the hyper-parameter (order of propagation) and its impact on the AUROC in Figure 6, we find that OOD detection performance benefits from propagation orders within a reasonable range. However, excessive propagation (greater than 16) may be detrimental.

- The AUROC results of the other various classical propagation mechanisms on graph OOD detection are shown in Table 18 and Table 19. We can see that these propagation mechanisms perform inconsistently among various datasets. In contrast, our propagation mechanism GRASP constantly demonstrates superior performance among all datasets.

Table 18: Various classical propagation mechanisms on each dataset.

Method	Cora	Amazon	Coauthor	Chameleon
PPR	91.98	95.45	97.29	49.22
GraphHeat	63.72	63.39	67.52	50.67
GDC	89.33	90.47	95.29	59.91
MixHop	91.49	94.42	97.09	49.33
GPR	91.87	94.81	97.23	48.62
GRASP	**93.50**	**96.68**	**97.75**	**76.93**

Table 19: Various classical propagation mechanisms on each dataset.

Method	Squirrel	arXiv-year	snap-patents	wiki
PPR	52.31	56.87	46.70	34.83
GraphHeat	53.92	38.40	41.00	OOM
GDC	48.17	OOM	OOM	OOM
MixHop	51.29	34.41	28.93	39.22
GPR	52.49	34.30	29.66	36.98
GRASP	**61.09**	**81.24**	**72.13**	**77.97**

E Limitations

While the proposed method of OOD score propagation shows promise in improving OOD detection in graph learning, there are limitations worth noting. The effectiveness of the method heavily relies on the connectivity and structure of the graph. In scenarios where the graph exhibits random connectivity patterns, the propagation of OOD scores with the proposed solution may no longer be effective. Addressing these limitations will be crucial for ensuring the robustness and generalizability of the proposed OOD detection approach in graph learning.

F Broader Impact

This paper on detecting Out-of-Distribution (OOD) nodes in graph learning holds significant potential for various fields and applications. By addressing a salient yet under-explored challenge in graph neural networks, the proposed method of OOD score propagation offers a promising avenue for enhancing the robustness and reliability of graph-based machine learning systems. The implications extend beyond the realm of graph learning, as OOD detection is a critical component in many real-world applications, including anomaly detection, fraud detection, and network security. Improving OOD detection in graph structures can lead to more accurate and reliable decision-making in domains such as social network analysis, recommendation systems, and biological network analysis. Overall, this research has the potential to drive advancements in graph-based machine learning and contribute to the development of more robust and reliable AI systems with broader societal impact.

G Other Related Works

Graph OOD Generalization. Unlike graph OOD detection, which aims to increase the gap between ID and OOD for effective OOD detection, graph OOD generalization aims to learn the invariant aspects behind ID and OOD. By enhancing these invariant points, the gap between ID and OOD data is reduced to improve the robustness of graph models on OOD data. The distinction among different proposed methods lies in identifying different invariant factors. GTRANS [30] leverages contrastive learning to learn the optimal perturbations of features and structures to enhance the GNN model's robustness against OOD. GRAPHPATCHER [31] improves GNN's robustness against low-degree scenarios during testing by corrupting a portion of nodes and reconstructing the original structure. LiSA [85] employs variational subgraph generators to generate label-invariant subgraphs for data augmentation, thereby enhancing the robustness of GNN models. [9] leverages the stability of correlation and employs a graph decorrelation method to learn stable associations, raising the graph OOD generalization capability. [78] boosts generalization by eliminating confounding bias. [41] extrapolates structure and feature spaces to generate OOD graph data, which is then used for data augmentation to improve OOD generalization. [28] strengthens graph OOD generalization by extracting invariant subgraphs and learning invariant patterns behind graphs based on these subgraphs. [8] introduces a set of minimal assumptions for feasible invariant graph learning. [5] investigates OOD generalization under different structural shifts. [22] incorporates label and environment causal independence to discover causal subgraphs for intensifying OOD generalization. [86] improves the OOD generalization of dynamic graphs by learning spatio-temporal invariant patterns from an environment learning perspective.