Generalization Error Bounds on Deep Learning with Markov Datasets

Abstract

In this paper, we derive upper bounds on generalization errors for deep neural networks with Markov datasets. These bounds are developed based on Koltchinskii and Panchenko's approach for bounding the generalization error of combined classifiers with i.i.d. datasets. The development of new symmetrization inequalities in high-dimensional probability for Markov chains is a key element in our extension, where the spectral gap of the infinitesimal generator of the Markov chain plays a key parameter in these inequalities. We also propose a simple method to convert these bounds and other similar ones in traditional deep learning and machine learning to Bayesian counterparts for both i.i.d. and Markov datasets. Extensions to m-order homogeneous Markov chains such as AR and ARMA models and mixtures of several Markov data services are given.

1 Introduction

In statistical learning theory, understanding generalization for neural networks is among the most challenging tasks. The standard approach to this problem was developed in seminar papers by Vapnik [27], and it is based on bounding the difference between the generalization error and the training error. These bounds are expressed in terms of the so called VC-dimension of the class. However, these bounds are very loose when the VC-dimension of the class can be very large, or even infinite. In 1998, several authors [2, 3] suggested another class of upper bounds on generalization error that are expressed in terms of the empirical distribution of the margin of the predictor (the classifier). Later, Koltchinskii and Panchenko [13] proposed new probabilistic upper bounds on generalization error of the combination of many complex classifiers such as deep neural networks. These bounds were developed based on the general results of the theory of Gaussian, Rademacher, and empirical processes in terms of general functions of the margins, satisfying a Lipschitz condition. They improved previously known bounds on generalization error of convex combination of classifiers.

In the context of supervised classification, PAC-Bayesian bounds have proved to be the tightest [1, 15, 19]. Several recent works have focused on gradient descent based PAC-Bayesian algorithms, aiming to minimise a generalisation bound for stochastic classifiers [4, 9, 28]. Most of these studies use a surrogate loss to avoid dealing with the zero-gradient of the misclassification loss. Several authors used other methods to estimate of the misclassification error with a non-zero gradient by proposing new training algorithms to evaluate the optimal output distribution in PAC-Bayesian bounds analytically [6, 7, 18]. Recently, there have been some interesting works which use information-theoretic approach to find PAC-bounds on generalization errors for machine learning [10, 31] and deep learning [12].

All of the above-mentioned bounds are derived based on the assumption that the dataset is generated by an i.i.d. process with unknown distribution. However, in many applications in machine learning such as speech, handwriting, gesture recognition, and bio-informatics, the samples of data are usually

correlated. In this work, we develop some upper bounds on generalization errors for deep neural networks with Markov or hidden Markov datasets. Our bounds are derived based on the same approach as Koltchinskii and Panchenko [13]. To deal with the Markov structure of the datasets, we need to develop some new techniques in this work. The development of new symmetrization inequalities in high-dimensional probability for Markov chains is a key element in our extension, where the pseudo spectral gap of the infinitesimal generator of the Markov chain plays as a key parameter in these inequalities. Furthermore, we also apply our results to m-order Markov chains such as AR and ARMA models and mixtures of Markov chains.

Finally, a simple method to convert all our bounds for traditional deep learning to counterparts for Bayesian deep learning is given. Our method can be applied to convert other similar bounds for i.i.d. datasets in the research literature as well. Bayesian deep learning has been recently introduced by Wilson and Izmailov [29]. The key distinguishable property of a Bayesian approach is marginalization, rather than using a single setting of weights in (traditional) deep learning. Bayesian marginalization can particularly improve the accuracy and calibration of modern deep neural networks, which are typically underspecified by the data, and can represent many compelling but different solutions.

2 Preliminaries

2.1 Mathematical Backgrounds

Let a Markov chain $\{X_n\}_{n=1}^{\infty}$ on a state space $\mathcal{S}$ with transition kernel $Q(x, dy)$ and the initial state $X_1 \sim \nu$, where $\mathcal{S}$ is a Polish space in $\mathbb{R}$. In this paper, we consider the Markov chains which are irreducible and recurrent, so the existence of a stationary distribution π is guaranteed. An irreducible and recurrent Markov chain on an infinite state-space is called Harris chain [24]. A Markov chain is called *reversible* if the following detailed balance condition is satisfied:

$$\pi(dx)Q(x, dy) = \pi(dy)Q(y, dx), \qquad \forall x, y \in \mathcal{S}. \tag{1}$$

Let $L_2(\pi)$ be the Hilbert space of complex valued measurable functions on $\mathcal{S}$ that are square integrable w.r.t. π. We endow $L_2(\pi)$ with inner product $\langle f, g \rangle := \int fg^* d\pi$, and norm $\|f\|_{2,\pi} := \langle f, f \rangle_\pi^{1/2}$. Let E_π be the associated averaging operator defined by $(E_\pi)(x, y) = \pi(y), \forall x, y \in \mathcal{S}$, and

$$\lambda = \|Q - E_\pi\|_{L_2(\pi) \to L_2(\pi)}, \tag{2}$$

where $\|B\|_{L_2(\pi) \to L_2(\pi)} = \max_{v:\|v\|_{2,\pi}=1} \|Bv\|_{2,\pi}$. Q can be viewed as a linear operator (infinitesimal generator) on $L_2(\pi)$, denoted by $\mathbf{Q}$, defined as $(\mathbf{Q}f)(x) := \mathbb{E}_{Q(x,\cdot)}(f)$, and the reversibility is equivalent to the self-adjointness of $\mathbf{Q}$. The operator $\mathbf{Q}$ acts on measures on the left, creating a measure $\mu\mathbf{Q}$, that is, for every measurable subset A of $\mathcal{S}$, $\mu\mathbf{Q}(A) := \int_{x \in \mathcal{S}} Q(x, A)\mu(dx)$. For a Markov chain with stationary distribution π, we define the *spectrum* of the chain as

$$S_2 := \left\{ \xi \in \mathbb{C} : (\xi\mathbf{I} - \mathbf{Q}) \text{ is not invertible on } L_2(\pi) \right\}. \tag{3}$$

It is known that $\lambda = 1 - \gamma^*$ [20], where

$$\gamma^* := \begin{cases} 1 - \sup\{|\xi| : \xi \in \mathcal{S}_2, \xi \neq 1\}, \\ \qquad \text{if eigenvalue 1 has multiplicity 1}, \\ 0, \qquad \text{otherwise} \end{cases}$$

is the *the absolute spectral gap* of the Markov chain. The absolute spectral gap can be bounded by the mixing time t_{mix} of the Markov chain by the following expression:

$$\left(\frac{1}{\gamma^*} - 1 \right) \log 2 \leq t_{\mathrm{mix}} \leq \frac{\log(4/\pi_*)}{\gamma_*}, \tag{4}$$

where $\pi_* = \min_{x \in \mathcal{S}} \pi_x$ is the *minimum stationary probability*, which is positive if $Q^k > 0$ (entry-wise positive) for some $k \geq 1$. See [30] for more detailed discussions. In [8, 30], the authors provided algorithms to estimate t_{mix} and γ_{ps} from a single trajectory.

By $\mathcal{M}(\mathcal{S})$ denote the set of real-valued signed measures on $(\mathcal{S}, \mathcal{B}(\mathcal{S}))$ where $\mathcal{B}(\mathcal{S})$ is the set of all Borel subsets in $\mathcal{S}$[1]. Assume that $\nu << \pi$. Define

$$\mathcal{M}_2 := \left\{ \nu \in \mathcal{M}(\mathcal{S}) : \left\| \frac{d\nu}{d\pi} \right\|_2 < \infty \right\}, \tag{5}$$

---

[1]The set function $\mu : \mathcal{B}(\mathcal{S}) \to \mathbb{R}$ is a real-valued signed measure if $\mu(\emptyset) = 0$ and for pairwise disjoint $A_1, A_2, \cdots$ with $A_k \in \mathcal{B}(\mathcal{S})$ for all $k \in \mathbb{Z}_+$, one has $\mu(\bigcup_{k=1}^{\infty} A_k) = \sum_{k=1}^{\infty} \mu(A_k)$.

where $\|\cdot\|_2$ is the standard L_2 norm in the Hilbert space of complex valued measurable functions on $\mathcal{S}$. We also assume that

$$c := \left\|\frac{dv}{d\pi}\right\|_\infty < \infty. \tag{6}$$

For $\{X_n\}_{n=1}^\infty$ being an i.i.d. sequence, which is a special case of Markov chain, or an arbitrary homogeneousness Markov chain with $X_1 \sim \pi$, it holds that $c = 1$.

2.2 Problem settings

In this paper, we consider a uniformly bounded class of functions:

$$\mathcal{F} := \big\{f : \mathcal{S} \to \mathbb{R}\big\} \tag{7}$$

such that

$$\sup_{f \in \mathcal{F}} \|f\|_\infty \leq M \tag{8}$$

for some finite constant M. Define the following probability measure

$$P(A) := \int_A \pi(x)dx, \tag{9}$$

for any measurable set $A \in \mathcal{S}$. In addition, let P_n be the empirical measure based on the sample $(X_1, X_2, \cdots, X_n)$, i.e.,

$$P_n := \frac{1}{n}\sum_{i=1}^n \delta_{X_i}, \tag{10}$$

We also denote $Pf := \int_S f dP$ and $P_n f := \int_S f dP_n$. Then, we have

$$Pf = \int_{\mathcal{S}} f(x)\pi(x)dx, \tag{11}$$

and

$$P_n f = \frac{1}{n}\sum_{i=1}^n f(X_i). \tag{12}$$

On the Banach space of uniformly bounded functions $\mathcal{F}$, define an infinity norm: $\|Y\|_{\mathcal{F}} = \sup_{f \in \mathcal{F}} |Y(f)|$. Let

$$G_n(\mathcal{F}) := \mathbb{E}\left[\left\|n^{-1}\sum_{i=1}^n g_i \delta_{X_i}\right\|_{\mathcal{F}}\right], \tag{13}$$

where $\{g_i\}$ is a sequence of i.i.d. standard normal variables, independent of $\{X_i\}$. We will call $n \mapsto G_n(\mathcal{F})$ *the Gaussian complexity function* of the class $\mathcal{F}$.

Similarly, we define

$$R_n(\mathcal{F}) := \mathbb{E}\left[\left\|n^{-1}\sum_{i=1}^n \varepsilon_i \delta_{X_i}\right\|_{\mathcal{F}}\right], \tag{14}$$

where $\{\varepsilon_i\}$ is a sequence of i.i.d. Rademacher (taking values $+1$ and -1 with probability $1/2$ each) random variables, independent of $\{X_i\}$. We will call $n \mapsto R_n(\mathcal{F})$ *the Rademacher complexity function* of the class $\mathcal{F}$.

For real applications in machine learning, we can assume that feature vectors are generated by a Markov chain $\{X_n\}_{n=1}^\infty$ with stochastic matrix Q, and $\{Y_n\}_{n=1}^\infty$ is the corresponding sequence of labels such as in text and speech services. Furthermore, Q is irreducible and recurrent on some finite set $\mathcal{S}$. An i.i.d. sequence of feature vectors can be considered as a special Markov chain where $Q(x, x')$ only depends on x'. In the supervised learning, the sequence of labels $\{Y_n\}_{n=1}^\infty$ can be

considered as being generated by a Hidden Markov Model (HMM), where the emission probability $P_{Y_n|X_n}(y|x) = g(x, y)$ for all $n \geq 1$ and $g : \mathcal{S} \times \mathcal{Y} \to \mathbb{R}_+$. It is easy to see that $\{(X_n, Y_n)\}_{n=1}^\infty$ is a Markov chain with the transition probability

$$
\begin{aligned}
& P_{X_{n+1}Y_{n+1}|X_nY_n}(x_{n+1}, y_{n+1}|x_n, y_n) \\
& \quad = Q(x_n, x_{n+1})g(x_{n+1}, y_{n+1}).
\end{aligned}
\tag{15}
$$

Let $\tilde{Q}(x_1, y_1, x_2, y_2) := Q(x_1, x_2)g(x_2, y_2)$ for all $x_1, x_2 \in \mathcal{S}$ and $y_1, y_2 \in \mathcal{Y}$, which is the transition probability of the Markov chain $\{(X_n, Y_n)\}_{n=1}^\infty$ on $\tilde{S} := \mathcal{S} \times \mathcal{Y}$. Then, it is not hard to see that $\{(X_n, Y_n)\}_{n=1}^\infty$ is irreducible and recurrent on $\tilde{S}$, so it has a stationary distribution, say $\tilde{\pi}$. The associated following probability measure is defined as

$$
P(A) := \int_{\mathcal{S} \times \mathcal{Y}} \tilde{\pi}(x, y) dx dy,
\tag{16}
$$

and the empirical distribution P_n based on the observations $\{(X_k, Y_k)\}_{k=1}^n$ is

$$
P_n := \frac{1}{n} \sum_{k=1}^n \delta_{X_k, Y_k}.
\tag{17}
$$

2.3 Contributions

In this paper, we aim to develop a set of novel upper bounds on *the generalization errors* for deep neural networks with Markov dataset. More specially, our target is to find a relationship between Pf and $P_n f$ which holds for all $f \in \mathcal{F}$ in terms of Gaussian and Rademacher complexities. Our main contributions include:

- We develop general bounds on generalization errors for machine learning (and deep learning) on Markov datasets.

- Since the dataset is non-i.i.d., the standard symmetrization inequalities in high-dimensional probability can not be applied. In this work, we extend some symmetrization inequalities for i.i.d. random processes to Markov ones.

- We propose a new method to convert all the bounds for machine learning (and deep learning) models to Bayesian settings.

- Extensions to m-order homogeneous Markov chains such as AR and ARMA models and mixtures of several Markov services are given.

3 Main Results

3.1 Probabilistic Bounds for General Function Classes

In this section, we develop probabilistic bounds for general function classes in terms of Gaussian and Rademacher complexities.

First, we prove the following key lemma, which is an extension of the symmetrization inequality for i.i.d. sequences (for example, [25]) to a new version for Markov sequences $\{X_n\}_{n=1}^\infty$ with the stationary distribution π and the initial distribution $\nu \in \mathcal{M}_2$:

Lemma 1. *For all $n \in \mathbb{Z}^+$, define*

$$
A_n := \sqrt{\frac{2M}{n(1-\lambda)} + \frac{64M^2}{n^2(1-\lambda)^2} \left\| \frac{dv}{d\pi} - 1 \right\|_2}.
\tag{18}
$$

Then, the following holds:

$$
\mathbb{E}\big[\|P_n^0\|_{\mathcal{F}}\big] - A_n - \frac{2M}{\sqrt{n}} \leq \mathbb{E}\big[\big\|P_n - P\big\|_{\mathcal{F}}\big] \leq 2\mathbb{E}\big[\|P_n^0\|_{\mathcal{F}}\big] + A_n, \quad \forall t > 0.
\tag{19}
$$

The proof of this lemma can be found in Appendix A of the supplementary material. Compared with the i.i.d. case, the symmetrization inequality for Markov chain in Lemma 1 are different in two perspectives: (1) The expectation $\mathbb{E}\left[\|P_n^0\|_{\mathcal{F}}\right]$ is now is under the joint distributions of Markov chain and Rademacher random variables and (2) The term A_n appears in both lower and upper bounds to compensate for the difference between the initial distribution ν and the stationary distribution π of the Markov chain[2]. If $X_1 \sim \pi$ (or $\nu = \pi$), the term A_n is unnecessary in (19). See our detailed proof for this fact.

By applying Lemma 1, the following theorem can be proved (cf. Appendix B).

Theorem 2. *Let φ is a non-increasing function such that $\varphi(x) \geq \mathbf{1}_{(-\infty,0]}(x)$ for all $x \in \mathbb{R}$. For any $t > 0$,*

$$\mathbb{P}\left(\exists f \in \mathcal{F} : P\{f \leq 0\} > \inf_{\delta \in (0,1]}\left[P_n\varphi\left(\frac{f}{\delta}\right) + \frac{8L(\varphi)}{\delta}R_n(\mathcal{F})\right.\right.$$
$$\left.\left. + \frac{2M}{\sqrt{n}}\left(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\right) + A_n\right]\right) \leq \frac{\pi^2 c}{3}\exp\left(-\frac{1-\lambda}{64e}t^2\right) \qquad (20)$$

and

$$\mathbb{P}\left(\exists f \in \mathcal{F} : P\{f \leq 0\} > \inf_{\delta \in (0,1]}\left[P_n\varphi\left(\frac{f}{\delta}\right) + \frac{2L(\varphi)\sqrt{2\pi}}{\delta}G_n(\mathcal{F})\right.\right.$$
$$\left.\left. + \frac{2M}{\sqrt{n}}\left(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\right) + \frac{2}{\sqrt{n}} + A_n\right]\right) \leq \frac{\pi^2 c}{3}\exp\left(-\frac{1-\lambda}{64e}t^2\right), \qquad (21)$$

where A_n is defined in (18) and c is defined in (6).

Since $A_n = O(1/\sqrt{n})$, Theorem 2 shows that with high probability, the generalization error can be bounded by Rademacher or Gaussian complexity functions plus an $O(1/\sqrt{n})$ term, where n is the training set length. This fact also happens in i.i.d. case [13]. However, because the dependency among samples in Markov chain, the constant in $O(1/\sqrt{n})$ term is larger than the i.i.d. case.

3.2 Bounding the generalization error in deep neural networks

In this section, we consider the same example as [13, Section 6]. However, we assume that feature vectors in the dataset are generated by a Markov chain instead of an i.i.d. process. Let $\mathcal{H}$ be a the class of all uniformly bounded functions $f : \mathcal{S} \to \mathbb{R}$. $\mathcal{H}$ is called the class of *base functions*. Denote by $\tilde{\mathcal{H}}$ the class of measurable functions $\tilde{f} : \mathcal{S} \times \mathcal{Y} \to \mathbb{R}$, where $\mathcal{Y}$ is the alphabet of labels. $\tilde{\mathcal{H}}$ is introduced for real machine learning applications where we need to work with a new Markov chain generated from both feature vectors and their labels $\{(X_n, Y_n)\}_{n=1}^{\infty}$ instead of the feature-based Markov chain $\{X_n\}_{n=1}^{\infty}$. See Subsection 2.2 for detailed discussions. For binary classification, $\tilde{\mathcal{H}} := \{\tilde{f} : f \in \mathcal{H}\}$, where $\tilde{f}(x, y) = yf(x)$.

Consider a feed-forward neural network with V layers of neurons

$$V = \{v_i\} \cup \bigcup_{j=0}^{l} V_j \qquad (22)$$

where $V_l = \{v_o\}$. The neurons v_i and v_o are called the input and the output neurons, respectively. To define the network, we will assign the labels to the neurons in the following way. Each of the base neurons is labelled by a function from the base class $\mathcal{H}$. Each neuron of the j-th layer V_j, where $j \geq 1$, is labelled by a vector $w := (w_1, w_2, \cdots, w_n) \in \mathbb{R}^n$, where n is the number of inputs of the neuron. Here, w will be called the vector of weights of the neuron.

Given a Borel function σ from $\mathbb{R}$ into $[-1, 1]$ (for example, sigmoid function) and a vector $w := (w_1, w_2, \cdots, w_n) \in \mathbb{R}^n$ where $n = |\mathcal{S}| + 1$, let

$$N_{\sigma,w} : \mathbb{R}^n \to \mathbb{R}, N_{\sigma,w}(u_1, u_2, \cdots, u_n) := \sigma\left(\sum_{j=1}^{n} w_j u_j\right). \qquad (23)$$

---

[2]This difference causes a burn-in time [23] which is the time between the initial and first time that the Markov chain is stationary.

164 Let $\sigma_j : j \geq 1$ be functions from $\mathbb{R}$ into $[-1, 1]$, satisfying the Lipschitz conditions

$$\left|\sigma_j(u) - \sigma_j(v)\right| \leq L_j|u - v|, \qquad u, v \in \mathbb{R}. \tag{24}$$

165 The neural network works can be formed as the following. The input neuron inputs an instance $x \in \mathcal{S}$.
166 A base neuron computes the value of the base function on this instance and outputs the value through
167 its output edges. A neuron in the j-th layer ($j \geq 1$) computes and outputs through its output edges
168 the value $N_{\sigma_j, w}(u_1, u_2, \cdots, u_n)$ (where $u_1, u_2, \cdots, u_n$ are the values of the inputs of the neuron).
169 The network outputs the value $f(x)$ (of a function f it computes) through the output edge.

170 We denote by $\mathcal{N}_l$ the set of such networks. We call $\mathcal{N}_l$ the class of feed-forward neural networks with
171 base $\mathcal{H}$ and l layers of neurons (and with sigmoid σ_j). Let $\mathcal{N}_\infty := \bigcup_{j=1}^{\infty} \mathcal{N}_j$. Define $\mathcal{H}_0 := \mathcal{H}$, and
172 then recursively

$$\mathcal{H}_j := \left\{ N_{\sigma_j, w}(h_1, h_2, \cdots, h_n) : n \geq 0, h_i \in \mathcal{H}_{j-1}, w \in \mathbb{R}^n \right\} \cup \mathcal{H}_{j-1}. \tag{25}$$

173 Denote $\mathcal{H}_\infty := \bigcup_{j=1}^{\infty} \mathcal{H}_j$. Clearly, $\mathcal{H}_\infty$ includes all the functions computable by feed-forward neural
174 networks with base $\mathcal{H}$.

175 Let $\{b_j\}$ be a sequence of positive numbers. We also define recursively classes of functions com-
176 putable by feed-forward neural networks with restrictions on the weights of neurons:

$$\mathcal{H}_j(b_1, b_2, \cdots, b_j) := \left\{ N_{\sigma_j, w}(h_1, h_2, \cdots, h_n) : n \geq 0, \right.$$

$$\left. h_i \in \mathcal{H}_{j-1}(b_1, b_2, \cdots, b_{j-1}), w \in \mathbb{R}^n, \|w\|_1 \leq b_j \right\} \bigcup \mathcal{H}_{j-1}(b_1, b_2, \cdots, b_{j-1}), \tag{26}$$

177 where $\|w\|_1$ denotes the 1-norm of the vector w.

178 Clearly,

$$\mathcal{H}_\infty = \bigcup \left\{ \mathcal{H}_j(b_1, \cdots, b_j) : b_1, \cdots, b_j < +\infty \right\}. \tag{27}$$

179 Let φ be a function such that $\varphi(x) \geq I_{(-\infty, 0]}(x)$ for all $x \in \mathbb{R}$ and φ satisfies the Lipschitz condition
180 with constant $L(\varphi)$. Then, the following is a direct application of Theorem 2.

181 **Theorem 3.** *For any $t \geq 0$ and for all $l \geq 1$,*

$$\mathbb{P}\left(\exists f \in \mathcal{H}(b_1, b_2, \cdots, b_l) : P\{\tilde{f} \leq 0\} > \inf_{\delta \in (0,1]} \left[P_n \varphi\left(\frac{\tilde{f}}{\delta} \right) + \frac{2\sqrt{2\pi} L(\varphi)}{\delta} \prod_{j=1}^{l} (2L_j b_j + 1) G_n(\mathcal{H}) \right.\right.$$

$$\left.\left. + \frac{2M}{\sqrt{n}} \left(t + \sqrt{\frac{128e}{1-\lambda} \log \log_2 2\delta^{-1}} \right) + A_n \right] \right) \leq \frac{\pi^2 c}{3} \exp\left(-\frac{1-\lambda}{64e} t^2 \right), \tag{28}$$

182 *where A_n is defined in* (18) *and c is defined in* (6).

183 **Remark 4.** $P\{\tilde{f} \leq 0\}$ *represents the probability of mis-classification in the deep neural network.*

184 *Proof.* Let

$$\mathcal{H}'_l := \mathcal{H}(b_1, b_2, \cdots, b_l). \tag{29}$$

185 As the proof of [13, Theorem 13], it holds that

$$G_n(\mathcal{H}'_l) \leq \prod_{j=1}^{l} (2L_j b_j + 1) G_n(\mathcal{H}). \tag{30}$$

186 Hence, (28) is a direct application of Theorem 2 and (30). $\qquad \square$

187 Now, given a neural network $f \in \mathcal{N}_\infty$, let

$$l(f) := \min\{j \geq 1 : f \in \mathcal{N}_j\}. \tag{31}$$

For any number k such that $1 \leq k \leq l(f)$, let $V_k(f)$ be the set of all neurons of layer k in the neural network which is represented by f. Denote

$$W_k(f) := \max_{m \in V_k(f)} \|w^{(m)}\|_1 \vee b_k, \qquad k = 1, 2, \cdots, l(f), \tag{32}$$

and let

$$\Lambda(f) := \prod_{k=1}^{l(f)} (4L_k W_k(f) + 1), \tag{33}$$

$$\Gamma_\alpha(f) := \sum_{k=1}^{l(f)} \sqrt{\frac{\alpha}{2} \log(2 + \log_2 W_k(f))}, \tag{34}$$

where $\alpha > 0$ is the number such that $\zeta(\alpha) < 3/2$, ζ being the Riemann zeta-function:

$$\zeta(\alpha) := \sum_{k=1}^{\infty} k^{-\alpha}. \tag{35}$$

Then, by using Theorem 3 with $b_k \to \infty$ and the same arguments as [13, Proof of Theorem 14], we obtain the following result.

Theorem 5. *For any $t \geq 0$ and for all $l \geq 1$,*

$$\mathbb{P}\left(\exists f \in \mathcal{H}_\infty : P\{\tilde{f} \leq 0\} > \inf_{\delta \in (0,1]} \left[P_n \varphi\left(\frac{\tilde{f}}{\delta}\right) + \frac{2\sqrt{2\pi}L(\varphi)}{\delta} \Lambda(f) G_n(\mathcal{H}) + \frac{2}{\sqrt{n}} \right. \right.$$
$$\left. \left. + \frac{2M}{\sqrt{n}}\left(t + \Gamma_\alpha(f) + \sqrt{\frac{128e}{1-\lambda} \log \log_2 2\delta^{-1}} \right) + A_n \right] \right)$$
$$\leq \frac{\pi^2 c}{3}\left[3 - 2\zeta\left(\frac{\alpha(1-\lambda)}{128e}\right) \right]^{-1} \exp\left(-\frac{1-\lambda}{64e} t^2 \right), \tag{36}$$

where A_n is defined in (18) *and c is defined in* (6).

It follows, in particular, in the example of the voting methods of combining classifiers [3], from Theorem 3, we achieve the following PAC-bound:

$$P\{\tilde{f} \leq 0\} \leq \inf_{\delta \in (0,1]} \left[P_n\{\tilde{f} \leq \delta\} + \frac{8C}{\delta}\sqrt{\frac{V(\mathcal{H})}{n}} \right.$$
$$\left. + A_n + \frac{2M}{\sqrt{n}}\left(t_\alpha + \sqrt{\frac{128e}{1-\lambda} \log \log_2 2\delta^{-1}} \right) \right] \tag{37}$$

with probability at least $1 - \alpha$ (PAC- Bayes bound), where $V(\mathcal{H})$ is the VC-dimension of the class $\mathcal{H}$ and C is some positive constant and t_α is chosen such that $\frac{\pi^2 c}{3} \exp(-\frac{1-\lambda}{64e} t_\alpha^2) = \alpha$.

3.3 Generalization Error Bounds on Bayesian Deep Learning

For Bayesian machine learning and deep learning, $\mathcal{F} := \{f : \mathcal{S} \times \mathcal{W} \to \mathbb{R}\}$, where $\mathcal{S}$ is the state space of the Markov chain and $\mathcal{W}$ is the domain of (random) coefficients. We assume that $\mathcal{S}$ and $\mathcal{W}$ are Polish spaces on $\mathbb{R}$, which include both discrete sets and $\mathbb{R}$. For example, in binary classification, $f(X, W) = \text{sgn}(W^T X + b)$ where the feature X and the coefficient W are random vectors with specific prior distributions. In practice, the distribution of W is known which depends on our design method, and the distribution of X is unknown. For example, W is assumed to be Gaussian in Bayesian deep neural networks [29].

Since all the bounds on Subsections 3.1 and 3.2 hold for any function f in $\mathcal{F}$ at each fixed vector $W = w$, hence, they can be directly applied to Bayesian settings where W is random. However, these bounds are not expected to be tight enough since we don't use the prior distribution of W when deriving them.

In the following, we use another approach to derive new (and tighter) bounds for Bayesian deep learning and machine learning from all the bounds in Subsections 3.1 and 3.2. For illustration

purposes, we only derive a new bound. Other bounds can be derived in a similar fashion. We assume that $W_1, W_2, \cdots, W_n$ are i.i.d. random variables as in [29].

Let

$$\tilde{P}_n := \frac{1}{n} \sum_{i=1}^{n} \delta_{X_i, W_i}, \tag{38}$$

and define a new probability measure $\tilde{P}$ on $\mathcal{S} \times \mathcal{W}$ such that

$$\tilde{P}(A) := \int_A \tilde{\pi}(x, w) dx dw, \tag{39}$$

for all (Borel) set A on $\mathcal{S} \times \mathcal{W}$. Here, $\tilde{\pi}$ is the stationary distribution of the irreducible Markov process $\{(X_n, W_n)\}_{n=1}^{\infty}$ with stochastic matrix

$$\tilde{Q} := \{Q(x, w)P_W(w)\}_{x \in \mathcal{S}, w \in \mathcal{W}}. \tag{40}$$

In addition, define two new (averaging) linear functionals:

$$\hat{P}_n := \frac{1}{n} \sum_{i=1}^{n} \int_{\mathcal{W}} \delta_{X_i, w} dP_W(w), \tag{41}$$

and

$$\hat{P} := \int_{\mathcal{S}} \int_{\mathcal{W}} \delta_{x, w} \tilde{\pi}(x, w) dP_W(w) dP(x), \tag{42}$$

such that

$$\hat{P}_n(f) = \frac{1}{n} \sum_{i=1}^{n} \int_{\mathcal{W}} f(X_i, w) dP_W(w), \tag{43}$$

and

$$\hat{P}(f) := \int_{x \in \mathcal{S}} \int_{\mathcal{W}} f(x, w) \tilde{\pi}(x, w) dP_W(w) dP(x). \tag{44}$$

In practice, the prior distribution of W is known, so we can estimate $\hat{P}_n(f)$ based on the training set $\{(X_1, Y_1), (X_2, Y_2), \cdots, (X_n, Y_n)\}$, which is a Markov chain on $\mathcal{X} \times \mathcal{Y}$ (cf. Section 2.2). The following result can be proved.

Theorem 6. *Let $\tilde{E}_\pi$ be the associated averaging operator associated with the Markov chain $\tilde{Q}$ defined in Subsection 2.1 and φ_k be a sequence of function such that $\varphi_k(x) \geq I_{(-\infty, 0]}(x)$. For any $t > 0$,*

$$\mathbb{P}\Bigg(\exists f \in \mathcal{F} : \hat{P}\{f \leq 0\} > \inf_{k > 0} \Bigg[\hat{P}_n \varphi_k(f) + 4L(\varphi_k)R_n(\mathcal{F})$$
$$+ \frac{2M}{\sqrt{n}}\Bigg(t + \sqrt{\frac{128e}{1 - \lambda} \log \log_2 2\delta^{-1}}\Bigg) + A_n\Bigg]\Bigg) \leq \frac{\pi^2 c}{3} \exp\Bigg(-\frac{1 - \lambda}{64e}t^2\Bigg) \tag{45}$$

and

$$\mathbb{P}\Bigg(\exists f \in \mathcal{F} : \hat{P}\{f \leq 0\} > \inf_{k > 0} \Bigg[\hat{P}_n \varphi_k(f) + \sqrt{2\pi}L(\varphi_k)G_n(\mathcal{F}) + \frac{2}{\sqrt{n}}$$
$$+ \frac{2M}{\sqrt{n}}\Bigg(t + \sqrt{\frac{128e}{1 - \lambda} \log \log_2 2\delta^{-1}}\Bigg) + A_n\Bigg]\Bigg) \leq \frac{\pi^2 c}{3} \exp\Bigg(-\frac{1 - \lambda}{64e}t^2\Bigg), \tag{46}$$

where $\lambda := \|\tilde{Q} - \tilde{E}_\pi\|_{L_2(\pi) \to L_2(\pi)}$ and A_n is defined in (18) and c is defined in (6).

Proof. Let $W_1, W_2, \cdots, W_n$ be an n samples of $W \sim P_W$ on $\mathcal{W}$ (or samples of some set of random coefficients). For simplicity, we assume that $\{W_n\}_{n=1}^{\infty}$ is an i.i.d. sequence. Then, it is obvious that $\{(X_n, W_n)\}_{n=1}^{\infty}$ forms a Markov chain with probability transition probability

$$\tilde{Q}(x_n, w_n; x_{n+1}, w_{n+1})$$
$$= \mathbb{P}(X_{n+1} = x_{n+1}, W_{n+1} = w_{n+1} | X_n = x_n, W_n = w_n) \tag{47}$$
$$= Q(x_n, x_{n+1})P_W(w_{n+1}). \tag{48}$$

From Theorem 6, it holds that

$$\mathbb{P}\bigg(\exists f \in \mathcal{F} : \tilde{P}\{f \leq 0\} > \inf_{k>0}\bigg[\tilde{P}_n\varphi_k(f) + 4L(\varphi_k)R_n(\mathcal{F})$$
$$+ \frac{2M}{\sqrt{n}}\bigg(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\bigg) + A_n\bigg]\bigg) \leq \frac{\pi^2}{3}\exp\bigg(-\frac{1-\lambda}{64e}t^2\bigg). \qquad (49)$$

This means that with probability at least $1 - \frac{\pi^2 c}{3}\exp\big(-\frac{1-\lambda}{64e}t^2\big)$, it holds that

$$\tilde{P}\{f \leq 0\} \leq \inf_{k>0}\bigg[\tilde{P}_n\varphi_k(f) + 4L(\varphi_k)R_n(\mathcal{F}) + \frac{2M}{\sqrt{n}}\bigg(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\bigg) + A_n\bigg]. \tag{50}$$

From (50), it holds that with probability at least $1 - \frac{\pi^2 c}{3}\exp\big(-\frac{1-\lambda}{64e}t^2\big)$,

$$\tilde{P}\{f \leq 0\} \leq \inf_{k>0}\bigg[\frac{1}{n}\sum_{i=1}^{n}\varphi_k(f(X_i, W_i)) + 4L(\varphi_k)R_n(\mathcal{F}) + A_n\bigg]. \tag{51}$$

From (51), with probability at least $1 - \frac{\pi^2 c}{3}\exp\big(-\frac{1-\lambda}{64e}t^2\big)$, it holds that

$$\mathbb{E}_W\big[\tilde{P}\{f \leq 0\}\big] \leq \mathbb{E}_W\bigg[\inf_{k>0}\bigg[\frac{1}{n}\sum_{i=1}^{n}\varphi_k(f(X_i, W_i)) + 4L(\varphi_k)R_n(\mathcal{F}) + A_n\bigg]$$
$$+ \frac{2M}{\sqrt{n}}\bigg(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\bigg)\bigg] \tag{52}$$

$$\leq \inf_{k>0}\mathbb{E}_W\bigg[\frac{1}{n}\sum_{i=1}^{n}\varphi_k(f(X_i, W_i)) + 4L(\varphi_k)R_n(\mathcal{F}) + A_n + \frac{2M}{\sqrt{n}}\bigg(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\bigg)\bigg] \tag{53}$$

$$= \inf_{k>0}\frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_W[\varphi_k(f(X_i, W_i))] + 4L(\varphi_k)R_n(\mathcal{F}) + A_n + \frac{2M}{\sqrt{n}}\bigg(t + \sqrt{\frac{128e}{1-\lambda}\log\log_2 2\delta^{-1}}\bigg). \tag{54}$$

From (54), we obtain (45). Similarly, we can achieve (46). □

4   Extension to High-order Markov Chains

In this section, we show that all the results in the previous sections can be extended to any homogeneous Markov sequence of arbitrary order. The main idea in deriving bounds for m-order homogeneous Markov chains such as Autoregressive (AR) and Autoregressive Moving-Average (ARMA) models is to convert these Markov chains to equivalent 1-order homogeneous Markov chains and use our previous bounds for the new Markov chains. See Section 4 in the supplementary material for more detailed discussions. We also present a method to extend our results to a mixture of m independent Markov services in this section.

5   Conclusions

In this paper, we derive upper bounds on generalization errors for machine learning and deep neural networks based on a new assumption that the dataset has Markov or hidden Markov structure. We also propose a new method to convert all these bounds to Bayesian deep learning and machine learning. Extension to m-order Markov chains and a mixture of Markov chains are also given. An interesting future research topic is to develop some new algorithms to evaluate performance of these bounds on real Markov datasets.

References

[1] A. Ambroladze, E. P.-H. and ShaweTaylor, J. Tighter PAC-Bayes bounds. In *NIPS*, 2007.

[2] Bartlett, P. and Shawe-Taylor, J. *Generalization Performance of Support Vector Machines and Other Pattern Classifiers*, pp. 43–54. MIT Press, 1999.

[3] Bartlett, P., Freund, Y., Lee, W. S., and Schapire, R. E. Boosting the margin: a new explanation for the effectiveness of voting methods. *The Annals of Statistics*, 26(5):1651 – 1686, 1998.

[4] Biggs, F. and Guedj, B. Differentiable PAC-Bayes objectives with partially aggregated neural networks. *Entropy*, 23, 2021.

[5] Billingsley, P. *Probability and Measure*. Wiley-Interscience, 3rd edition, 1995.

[6] Clerico, E., Deligiannidis, G., and Doucet, A. Conditional Gaussian PAC-Bayes. *Arxiv: 2110.1188*, 2021.

[7] Clerico, E., Deligiannidis, G., and Doucet, A. Wide stochastic networks: Gaussian limit and PACBayesian training. *Arxiv: 2106.09798*, 2021.

[8] Combes, R. and Touati, M. Computationally efficient estimation of the spectral gap of a markov chain. *Proceedings of the ACM on Measurement and Analysis of Computing Systems*, 3:1 – 21, 2019.

[9] Dziugaite, G. K. and Roy., D. M. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In *Uncertainty in Artificial Intelligence (UAI)*, 2017.

[10] Esposito, A. R., Gastpar, M., and Issa, I. Generalization error bounds via Rényi-f-divergences and maximal leakage. *IEEE Transactions on Information Theory*, 67(8):4986–5004, 2021.

[11] Fan, J., Jiang, B., and Sun, Q. Hoeffding's Inequality for General Markov Chains and Its Applications to Statistical Learning. *J. Mach. Learn. Research*, 22:1–35, May 2021.

[12] Jakubovitz, D., Giryes, R., and Rodrigues, M. R. D. Generalization Error in Deep Learning. *Arxiv: 1808.01174*, 30, 2018.

[13] Koltchinskii, V. and Panchenko, D. Empirical Margin Distributions and Bounding the Generalization Error of Combined Classifiers. *The Annals of Statistics*, 30(1):1 – 50, 2002.

[14] Kontoyiannis, I., Lastras-Montaño, L. A., and Meyn, S. P. Relative entropy and exponential deviation bounds for general Markov chains. In *Proc. of Intl. Symp. on Inform. Th.*, 2005.

[15] Langford, J. and Shawe-Taylor, J. PAC-Bayes and Margins. In *Advances of Neural Information Processing Systems (NIPS)*, 2003.

[16] Ledoux, M. and Talagrand, M. *Probability in Banach Spaces*. Springer, New York., 1991.

[17] Lezaud, P. Chernoff and Berry-Esséen inequalities for Markov processes. *ESAIM: Probability and Statistics, EDP Sciences*, 5:183–201, 2001.

[18] McAllester, A. Some PAC-Bayesian theorems. In *Conference on Learning Theory (COLT)*, 1998.

[19] McAllester, D. A. Pac-bayesian stochastic model selection. *Machine Learning*, 51, 2004.

[20] Paulin, D. Concentration inequalities for Markov chains by Marton couplings and spectral methods. *Electronic Journal of Probability*, 20(79):1 – 32, 2015.

[21] Rao, S. A Hoeffding inequality for Markov chains. *Electronic Communications in Probability*, 24(none):1 – 11, 2019.

[22] Royden, H. and Fitzpatrick, P. *Real Analysis*. Pearson, 4th edition, 2010.

[23] Rudolf, D. Explicit error bounds for Markov chain Monte Carlo. *Arxiv: 1108.3201*, 2011.

[24] Tuominen, P. and Tweedie, R. L. Markov Chains with Continuous Components. *Proceedings of the London Mathematical Society*, s3-38(1):89–114, 01 1979.

[25] Van Der Vaart, A. W. and Wellner. *Weak convergence and Empirical Processes.* Springer, New York, 1996.

[26] Van Der Vaart, A. W. and Wellner, J. A. *Weak convergence and Empirical Processes.* Springer, New York., 1996.

[27] Vapnik, V. N. *Statistical Learning Theory*. Wiley, New York, 1998.

[28] W. Zhou, V. Veitch, M. A. R. P. A. and Orbanz., P. Non-vacuous generalization bounds at the imagenet scale: a PAC-Bayesian compression approach. In *The International Conference on Learning Representations (ICLR)*, 2019.

[29] Wilson, A. G. and Izmailov, P. Bayesian deep learning and a probabilistic perspective of model construction. In *Proc. 37th ICML*. Morgan Kaufmann, 2020.

[30] Wolfer, G. and Kontorovich, A. Estimating the mixing time of ergodic markov chains. In *32nd Annual Conference on Learning Theory*, 2019.

[31] Xu, A. and Raginsky, M. Information-theoretic analysis of generalization capability of learning algorithms. In *Advances of Neural Information Processing Systems (NIPS)*, 2017.