Accelerated Linearized Laplace Approximation for Bayesian Deep Learning

Abstract

Laplace approximation (LA) and its linearized variant (LLA) enable effortless adaptation of pretrained deep neural networks to Bayesian neural networks. The generalized Gauss-Newton (GGN) approximation is typically introduced to improve their tractability. However, LA and LLA are still confronted with non-trivial inefficiency issues and should rely on Kronecker-factored, diagonal, or even last-layer approximate GGN matrices in practical use. These approximations are likely to harm the fidelity of learning outcomes. To tackle this issue, inspired by the connections between LLA and neural target kernels (NTKs), we develop a Nyström approximation to NTKs to accelerate LLA. Our method benefits from the capability of popular deep learning libraries for forward mode automatic differentiation, and enjoys reassuring theoretical guarantees. Extensive studies reflect the merits of the proposed method in aspects of both scalability and performance. Our method can even scale up to architectures like vision transformers. We also offer valuable ablation studies to diagnose our method.

1   Introduction

Deep neural networks (DNNs) excel at modeling deterministic relationships and have become *de facto* solutions for diverse pattern recognition problems [18, 54]. However, DNNs fall short in reasoning about model uncertainty [1] and suffer from poor calibration [17]. These issues are intolerable in risk-sensitive scenarios like self-driving [27], healthcare [34], finance [25], etc.

Bayesian Neural Networks (BNNs) have emerged as effective prescriptions to these pathologies [37, 21, 44, 16]. They usually proceed by estimating the posteriors over high-dimensional NN parameters. Due to some intractable integrals, diverse approximate inference methods have been applied to learning BNNs, spanning variational inference (VI) [1, 36], Markov chain Monte Carlo (MCMC) [55, 4], Laplace approximation (LA) [38, 50, 30], etc.

LA has recently gained unprecedented attention because its *post-hoc* nature nicely suits with the *pretraining-finetuning* fashion in deep learning (DL). LA approximates the posterior with a Gaussian around its maximum, whose mean and covariance are the *maximum a posteriori* (MAP) and the inversion of the Hessian respectively. It is a common practice to approximate the Hessian with the generalized Gauss-Newton (GGN) matrix [40] to make the whole workflow more tractable.

Linearized LA (LLA) [14, 22] applies LA to the first-order approximation of the NN of concern. LLA shares with LA the same predictive mean yet possesses a more benign covariance, which mitigates the underfitting issue of LA [33]. Immer et al. [22] argue that LLA is more sensible than LA in the presence of GGN approximation; LLA can perform on par with or better than popular alternatives on various uncertainty quantification (UQ) tasks [14, 6, 7]. The `Laplace` library [6] further substantially advances LLA's applicability, making it a simple and competing baseline for Bayesian DL.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

ELLA   LLA   LLA-KFAC   LLA-Diag   LLA*

Figure 1: 1-D regression on $y = \sin 2x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$. Red dots, central blue curves, and shaded regions refer to the training data, mean predictions, and uncertainty respectively. The model is a pretrained multilayer perceptron (MLP) with 3 hidden layers. Compared to LLA with KFAC approximation (LLA-KFAC), LLA with diagonal approximation (LLA-Diag), and last-layer LLA (LLA*), ELLA delivers a more reliable approximation to LLA, while being cost-effective. Surprisingly, ELLA offers better 'in-between' uncertainty than LLA here.

The practical adoption of LA and LLA actually entails further approximations on top of GGN. E.g., when using `Laplace` to process a pretrained ResNet [18], practitioners are recommended to resort to a Kronecker-factored (KFAC) [40] or diagonal approximation of the full GGN matrix for tractability. An orthogonal tactic is to apply LA/LLA to only NNs' last layer [30]. Yet, the approximation errors in these cases can hardly be identified, significantly undermining the fidelity of the learning outcomes.

This paper aims at scaling LLA up in a more assurable way. We first revisit the inherent connections between Neural Tangent Kernels (NTKs) [24] and LLA [28, 22], and find that, if we can approximate the NTKs with the inner product of some low-dimensional vector representations of the data, LLA can be considerably accelerated. Given this finding, we propose to adapt the Nyström method to approximate the NTKs of multi-output NNs, and advocate leveraging forward mode automatic differentiation (*fwAD*) to efficiently compute the involved Jacobian-vector products (JVPs). The resultant *accElerated LLA (ELLA)* preserves the principal structures of vanilla LLA yet without explicitly computing/storing the costly GGN/Jacobian matrices for the training data. What's more, we theoretically analyze the approximation error between the predictive of ELLA and that of vanilla LLA, and find that it deceases rapidly as the Nyström approximation becomes accurate.

We perform extensive studies to show that ELLA can be a low-cost and effective baseline for Bayesian DL. We first describe how to specify the hyperparameters of ELLA, and use an illustrative regression task to demonstrate the effectiveness of ELLA (see Figure 1). We then experiment on standard image classification benchmarks to exhibit the superiority of ELLA over competing baselines in aspects of both performance and scalability. We further show that ELLA can even scale up to modern architectures like vision transformers (ViTs) [11].

2 Background

Consider a learning problem on $\mathcal{D} = (\mathbf{X}, \mathbf{Y}) = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}_{i=1}^N$, where $\boldsymbol{x}_i \in \mathcal{X}$ and $\boldsymbol{y}_i \in \mathbb{R}^C$ (e.g., regression) or $\{0, 1\}^C$ (e.g., classification) refer to observations and targets respectively. The advance in machine learning suggests using a NN $g_{\boldsymbol{\theta}}(\cdot) : \mathcal{X} \rightarrow \mathbb{R}^C$ with parameters $\boldsymbol{\theta} \in \mathbb{R}^P$ for data fitting. Despite well-performing, regularly trained NNs only capture the most likely interpretation for the data, thus miss the ability to reason about uncertainty and are prone to overfitting and overconfidence.

BNNs [37, 21, 44] characterize model uncertainty by probabilistic principle and can holistically represent all likely interpretations. Typically, BNNs impose a prior $p(\boldsymbol{\theta})$ on NN parameters and chase the Bayesian posterior $p(\boldsymbol{\theta}|\mathcal{D}) = p(\mathcal{D}|\boldsymbol{\theta})p(\boldsymbol{\theta})/p(\mathcal{D})$ where $p(\mathcal{D}|\boldsymbol{\theta}) = \prod_i p(\boldsymbol{y}_i|\boldsymbol{x}_i, \boldsymbol{\theta}) = \prod_i p(\boldsymbol{y}_i|g_{\boldsymbol{\theta}}(\boldsymbol{x}_i))$. Analytical estimation is usually intractable due to NNs' high nonlinearity. Thereby, BNN methods usually find a surrogate of the true posterior $q(\boldsymbol{\theta}) \approx p(\boldsymbol{\theta}|\mathcal{D})$ via approximate inference methods like variational inference (VI) [1, 20, 36, 62, 29], Laplace approximation (LA) [38, 50], Markov chain Monte Carlo (MCMC) [55, 4, 63], particle-optimization based variational inference (POVI) [35], etc.

BNNs predict for new data $\boldsymbol{x}_*$ by posterior predictive $p(\boldsymbol{y}|\boldsymbol{x}_*, \mathcal{D}) = \mathbb{E}_{p(\boldsymbol{\theta}|\mathcal{D})} p(\boldsymbol{y}|\boldsymbol{x}_*, \boldsymbol{\theta}) \approx \mathbb{E}_{q(\boldsymbol{\theta})} p(\boldsymbol{y}|\boldsymbol{x}_*, \boldsymbol{\theta}) \approx \frac{1}{S} \sum_{s=1}^S p(\boldsymbol{y}|g_{\boldsymbol{\theta}_s}(\boldsymbol{x}_*))$ where $\boldsymbol{\theta}_s \sim q(\boldsymbol{\theta})$ are i.i.d. Monte Carlo (MC) samples.

2.1 Laplace Approximation and Its Linearized Variant

Typically, LA builds a Gaussian approximate posterior in the form of $q(\boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{\theta}; \hat{\boldsymbol{\theta}}, \boldsymbol{\Sigma})$, where $\hat{\boldsymbol{\theta}}$ denotes the MAP solution, i.e., $\hat{\boldsymbol{\theta}} = \arg\max_{\boldsymbol{\theta}} \log p(\mathcal{D}|\boldsymbol{\theta}) + \log p(\boldsymbol{\theta})$. $\boldsymbol{\Sigma}$ is the inversion of the Hessian

of the negative log posterior w.r.t. the parameters, i.e., $\boldsymbol{\Sigma}^{-1} = -\nabla_{\boldsymbol{\theta}\boldsymbol{\theta}}^2 (\log p(\mathcal{D}|\boldsymbol{\theta}) + \log p(\boldsymbol{\theta}))|_{\boldsymbol{\theta}=\hat{\boldsymbol{\theta}}}$. Without loss of generality, we base the following discussion on the isotropic Gaussian prior $p(\boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{\theta}; \mathbf{0}, \sigma_0^2 \mathbf{I}_P)^1$, so $-\nabla_{\boldsymbol{\theta}\boldsymbol{\theta}}^2 \log p(\boldsymbol{\theta})|_{\boldsymbol{\theta}=\hat{\boldsymbol{\theta}}}$ amounts to $\mathbf{I}_P/\sigma_0^2$.

Due to the intractability of the Hessian for NNs with massive parameters, it is a common practice to use the symmetric positive and semi-definite (SPSD) GGN matrix as a workaround, i.e.,

$$\boldsymbol{\Sigma}^{-1} = \sum_i J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}_i)^\top \Lambda(\boldsymbol{x}_i, \boldsymbol{y}_i) J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}_i) + \mathbf{I}_P/\sigma_0^2, \tag{1}$$

where $J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \triangleq \nabla_{\boldsymbol{\theta}} g_{\boldsymbol{\theta}}(\boldsymbol{x})|_{\boldsymbol{\theta}=\hat{\boldsymbol{\theta}}}$ and $\Lambda(\boldsymbol{x}, \boldsymbol{y}) \triangleq -\nabla_{\boldsymbol{gg}}^2 \log p(\boldsymbol{y}|\boldsymbol{g})|_{\boldsymbol{g}=g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})}$.

When concatenating $\{J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}_i) \in \mathbb{R}^{C \times P}\}_{i=1}^N$ as a big matrix $\mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}} \in \mathbb{R}^{NC \times P}$ and organizing $\{\Lambda(\boldsymbol{x}_i, \boldsymbol{y}_i) \in \mathbb{R}^{C \times C}\}_{i=1}^N$ as a block-diagonal matrix $\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \in \mathbb{R}^{NC \times NC}$, we have:

$$\boldsymbol{\Sigma} = \left[\mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}} + \mathbf{I}_P/\sigma_0^2 \right]^{-1}. \tag{2}$$

Yet, LA suffers from underfitting [33]. This is probably because GGN approximation implicitly turns the original model $g_{\boldsymbol{\theta}}(\boldsymbol{x})$ into a linear one $g_{\boldsymbol{\theta}}^{\text{lin}}(\boldsymbol{x}) = g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) + J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})(\boldsymbol{\theta} - \hat{\boldsymbol{\theta}})$ but $g_{\boldsymbol{\theta}}(\boldsymbol{x})$ is still leveraged to make prediction. I.e., there exists a *shift* between posterior inference and prediction [22]. To mitigate this issue, a proposal is to predict with $g_{\boldsymbol{\theta}}^{\text{lin}}(\boldsymbol{x})$, giving rise to linearized LA (LLA) [14, 28, 22].

LA and LLA nicely fit the *pretraining-finetuning* fashion in DL – they can be *post-hoc* applied to pretrained models where only the GGN matrices require to be estimated and further inverted. By LA and LLA, practitioners can adapt off-the-shelf high performing DNNs to BNNs easily.

LLA has revealed strong results on diverse UQ problems [14, 6, 7]. The `Laplace` library [6] further advances LLA's applicability, and evidences LLA is competitive to popular alternatives [63, 32, 39].

Scalability issue The GGN matrix of size $P \times P$ is still unamenable in modern DL scenarios, so further approximations sparsifying it are always introduced. The diagonal and KFAC [40] approximations are commonly adopted ones [50, 62], where only a diagonal or block-diagonal structure of the original GNN matrix is preserved. An orthogonal tactic is to concern only a subspace of the high-dimensional parameter space (e.g., the parameter space of the last layer [30]) to reduce the scale of the GGN matrix. However, these strategies sacrifice the fidelity of the learning outcomes as the approximation errors in these cases can hardly be theoretically measured. To this end, we develop *accElerated Linearized Laplace Approximation (ELLA)* to push the limit of LLA in a more assurable way.

3 Methodology

In this section, we first revisit the relation of LLA to Gaussian processes (GPs) and Neural Tangent Kernels (NTKs) [24]. After that, we reveal how to accelerate LLA by kernel approximation. Based on these findings, we develop an efficient implementation of ELLA using the Nyström method [58].

3.1 The Gaussian Process View of LLA

Integrating $q(\boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{\theta}; \hat{\boldsymbol{\theta}}, \boldsymbol{\Sigma})$ with the linear model $g_{\boldsymbol{\theta}}^{\text{lin}}(\boldsymbol{x})$ actually gives rise to a function-space approximate posterior [14, 28, 22] in the form of $q(f) = \mathcal{GP}(f|g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}), \kappa_{\text{LLA}}(\boldsymbol{x}, \boldsymbol{x}'))$ with

$$\kappa_{\text{LLA}}(\boldsymbol{x}, \boldsymbol{x}') \triangleq J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \boldsymbol{\Sigma} J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^\top. \tag{3}$$

By Woodbury matrix identity [60], we have:

$$\boldsymbol{\Sigma} = \left[\mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}} + \mathbf{I}_P/\sigma_0^2 \right]^{-1} = \sigma_0^2 \left(\mathbf{I}_P - \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}}^\top [\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}}^\top]^{-1} \mathbf{J}_{\hat{\boldsymbol{\theta}}, \mathbf{X}} \right). \tag{4}$$

It follows that

$$\kappa_{\text{LLA}}(\boldsymbol{x}, \boldsymbol{x}') = \sigma_0^2 \left(\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}') - \kappa_{\text{NTK}}(\boldsymbol{x}, \mathbf{X}) [\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \kappa_{\text{NTK}}(\mathbf{X}, \mathbf{X})]^{-1} \kappa_{\text{NTK}}(\mathbf{X}, \boldsymbol{x}') \right), \tag{5}$$

where $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}') \triangleq J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^\top$ denotes the neural tangent kernel (NTK) [24] corresponding to $g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})$. Note that $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}')$ is a *matrix-valued* kernel, with values in the space of $C \times C$ matrices.

---

[1]$\mathbf{I}_P$ refers to the identity matrix of size $P \times P$.

The main challenge then turns into the computation and inversion of the gram matrix $\kappa_{\text{NTK}}(\mathbf{X}, \mathbf{X})$ of size $NC \times NC$. When either N or C is large, the estimation of κ_{LLA} still suffers from inefficiency issue. To address this, existing work [22] assumes independence among the C output dimensions to cast $q(f)$ into C independent GPs following [51], and randomly subsample $M \ll N$ data points to form a cheap substitute for the original gram matrix. Despite effective in some cases, these approximations are heuristic, lacking a clear theoretical foundation.

3.2 Scale Up LLA by Kernel Approximation

We show that if we can approximate $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}')$ with the inner product of some explicit $C \times K$-dimensional representations of the data, i.e., $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}') \approx \varphi(\boldsymbol{x})\varphi(\boldsymbol{x}')^\top$ with $\varphi : \mathcal{X} \to \mathbb{R}^{C \times K}$, the scalability of the whole workflow can be unleashed.

Concretely, letting $\boldsymbol{\varphi}_\mathbf{X} \in \mathbb{R}^{NC \times K}$ be the concatenation of $\{\varphi(\boldsymbol{x}_i) \in \mathbb{R}^{C \times K}\}_{i=1}^N$, we have

$$\kappa_{\text{LLA}}(\boldsymbol{x}, \boldsymbol{x}') \approx \sigma_0^2 \Big(\varphi(\boldsymbol{x})\varphi(\boldsymbol{x}')^\top - \varphi(\boldsymbol{x})\boldsymbol{\varphi}_\mathbf{X}^\top \left[\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \boldsymbol{\varphi}_\mathbf{X}\boldsymbol{\varphi}_\mathbf{X}^\top \right]^{-1} \boldsymbol{\varphi}_\mathbf{X}\varphi(\boldsymbol{x}')^\top \Big)$$

$$= \varphi(\boldsymbol{x}) \underbrace{\left[\sum_i \varphi(\boldsymbol{x}_i)^\top \Lambda(\boldsymbol{x}_i, \boldsymbol{y}_i)\varphi(\boldsymbol{x}_i) + \mathbf{I}_K/\sigma_0^2 \right]^{-1}}_{\mathbf{G}} \varphi(\boldsymbol{x}')^\top \triangleq \kappa_{\text{ELLA}}(\boldsymbol{x}, \boldsymbol{x}'). \tag{6}$$

The matrix $\mathbf{G} \in \mathbb{R}^{K \times K}$ possesses a similar formula to the $\boldsymbol{\Sigma}$ in the original κ_{LLA} in Equation (3), yet much smaller. Once having φ, it is only required to perform one forward pass of g and φ for each training data to estimate $\mathbf{G}$. When K is reasonably small, e.g., < 100, it is cheap to invert $\mathbf{G}$.

3.3 Approximate NTKs via the Nyström Method

Typical kernel approximation means include Nyström method [45, 58] and random features-based methods [48, 49, 61, 43, 15, 9]. Given that the latter routinely rely on a relatively large number of random features to gain a faithful approximation (which means a large K), we suggest leveraging the Nyström method, which captures only several principal components of the kernel, to build φ.

To comfortably apply the Nyström method, we first rewrite $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}')$ as a *scalar-valued* kernel $\kappa_{\text{NTK}}((\boldsymbol{x}, i), (\boldsymbol{x}', i')) = J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}, i)J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}', i')^\top$ where $J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}, i) \triangleq \nabla_{\boldsymbol{\theta}} [g_{\boldsymbol{\theta}}(\boldsymbol{x})]^{(i)}|_{\boldsymbol{\theta}=\hat{\boldsymbol{\theta}}} : \mathcal{X} \times [C] \to \mathbb{R}^{1 \times P2}$ computes the gradient of i-th output w.r.t. parameters.

By Mercer's theorem [42],

$$\kappa_{\text{NTK}}((\boldsymbol{x}, i), (\boldsymbol{x}', i')) = \sum_{k \geq 1} \mu_k \psi_k(\boldsymbol{x}, i)\psi_k(\boldsymbol{x}', i'), \tag{7}$$

where $\psi_k \in L^2(\mathcal{X} \times [C], q)^3$ refer to the eigenfunctions of the NTK w.r.t. some probability measure q with $\mu_k \geq 0$ as the associated eigenvalues. Based on this, the Nyström method discovers the top-K eigenvalues as well as the corresponding eigenfunctions for kernel approximation.

By definition, the eigenfunctions can represent the spectral information of the kernel:

$$\int \kappa_{\text{NTK}}((\boldsymbol{x}, i), (\boldsymbol{x}', i')) \psi_k(\boldsymbol{x}', i')q(\boldsymbol{x}', i') = \mu_k\psi_k(\boldsymbol{x}, i), \forall k \geq 1, \tag{8}$$

while being orthonormal under q:

$$\int \psi_k(\boldsymbol{x}, i)\psi_{k'}(\boldsymbol{x}, i)q(\boldsymbol{x}, i) = \mathbb{1}[k = k'], \forall k, k' \geq 1. \tag{9}$$

In our case, $q(\boldsymbol{x}, i)$ can be factorized as the product of the data distribution and a uniform distribution over $\{1, ..., C\}$, which can be trivially sampled from. The Nyström method draws M ($M \geq K$) i.i.d. samples $\tilde{\mathbf{X}} = \{(\boldsymbol{x}_1, i_1), ..., (\boldsymbol{x}_M, i_M)\}$ from q to approximate the integration in Equation (8):

$$\frac{1}{M}\sum_{m=1}^M \kappa_{\text{NTK}}((\boldsymbol{x}, i), (\boldsymbol{x}_m, i_m)) \psi_k(\boldsymbol{x}_m, i_m) = \mu_k\psi_k(\boldsymbol{x}, i), \forall k \in [K]. \tag{10}$$

---

[2] We use superscript to index a multi-dimensional tensor and $[C]$ represents set of integers from 1 to C.

[3] $L^2(, q)$ denotes the space of square-integrable functions w.r.t. q.

Applying this equation to these samples gives rise to:

$$\frac{1}{M} \sum_{m=1}^{M} \kappa_{\text{NTK}} \left((\boldsymbol{x}_{m'}, i_{m'}), (\boldsymbol{x}_m, i_m)\right) \psi_k(\boldsymbol{x}_m, i_m) = \mu_k \psi_k(\boldsymbol{x}_{m'}, i_{m'}), \forall k \in [K], m' \in [M], \tag{11}$$

then we arrive at

$$\frac{1}{M} \mathbf{K} \boldsymbol{\psi}_k \approx \mu_k \boldsymbol{\psi}_k, k \in [K], \tag{12}$$

where $\mathbf{K} = \mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}}^{\top}$, with $\mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}} \in \mathbb{R}^{M \times P}$ as the concatenation of $\{J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}_m, i_m) \in \mathbb{R}^{1 \times P}\}_{m=1}^{M}$, and $\boldsymbol{\psi}_k = [\psi_k(\boldsymbol{x}_1, i_1), ..., \psi_k(\boldsymbol{x}_M, i_M)]^{\top}$. This implies a scaled eigendecomposition problem of $\mathbf{K}$.

We compute the top-K eigenvalues $\lambda_1, ..., \lambda_K$ of matrix $\mathbf{K}$ and record the corresponding *orthonormal* eigenvectors $\boldsymbol{u}_1, ..., \boldsymbol{u}_K$. Given the constraint in Equation (9), it is easy to see that:

$$\mu_k \approx \frac{\lambda_k}{M}, \text{ and } \psi_k(\boldsymbol{x}_m, i_m) \approx \sqrt{M} \boldsymbol{u}_k^{(m)}, m \in [M]. \tag{13}$$

Combining Equation (13) and (10) yields the Nyström approximation of the top-K eigenfunctions:

$$\hat{\psi}_k(\boldsymbol{x}, i) = \frac{\sqrt{M}}{\lambda_k} \sum_{m=1}^{M} \boldsymbol{u}_k^{(m)} \kappa_{\text{NTK}} \left((\boldsymbol{x}, i), (\boldsymbol{x}_m, i_m)\right) = \frac{\sqrt{M}}{\lambda_k} J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}, i) \mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}}^{\top} \boldsymbol{u}_k. \tag{14}$$

Then, the mapping φ which satisfied $\kappa_{\text{NTK}}(\boldsymbol{x}, \boldsymbol{x}') \approx \varphi(\boldsymbol{x}) \varphi(\boldsymbol{x}')^{\top}$ can be realized as:

$$[\varphi(\boldsymbol{x})]^{(i,k)} = \hat{\psi}_k(\boldsymbol{x}, i) \sqrt{\mu_k} = J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}, i) \mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}}^{\top} \boldsymbol{u}_k / \sqrt{\lambda_k}, \tag{15}$$

$$\Rightarrow \varphi(\boldsymbol{x}) = [J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \boldsymbol{v}_1, ..., J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \boldsymbol{v}_K] \text{ with } \boldsymbol{v}_k = \mathbf{J}_{\hat{\boldsymbol{\theta}}, \tilde{\mathbf{X}}}^{\top} \boldsymbol{u}_k / \sqrt{\lambda_k}. \tag{16}$$

Connection to sparse approximations of GPs A recent work [57] has shown that sparse variational Gaussian processes (SVGP) [53, 3] is algebraically equivalent to the Nyström approximation because the Evidence Lower BOund (ELBO) of the former encompasses the learning objective of the latter. That's to say, ELLA implicitly deploys a sparse approximation to the original GP predictive of LLA.

3.4 Implementation

As shown, the estimation of φ on a data point $\boldsymbol{x}$ degenerates as K JVPs, which can be accomplished by invoking *fwAD* for K times:

$$\begin{pmatrix} \boldsymbol{x}, \hat{\boldsymbol{\theta}} \\ \boldsymbol{v}_k \end{pmatrix} \xrightarrow{\text{forward}} \begin{matrix} g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \\ J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \boldsymbol{v}_k \end{matrix}, k \in [K], \tag{17}$$

where the model output $g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})$ and the JVP $J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}) \boldsymbol{v}_k$ are simultaneously computed in *one single forward pass*. Prevalent DL libraries like PyTorch [47] and Jax [2] have already been armed with the capability for *fwAD*. Algorithm 2 details the procedure of building φ in a PyTorch-like style.

With that, we can trivially compute the posterior $q(f)$ according to Equation (6), as detailed in Algorithm 1. The procedures for estimating $\mathbf{G}$ and the posterior can both be batched for acceleration.

Computation overhead The estimation of φ involves M forward and backward passes of $g_{\hat{\boldsymbol{\theta}}}$ and the eigendecomposition of a matrix of size $M \times M$. After that, we only need to make $\{\boldsymbol{v}_k\}_{k=1}^{K}$ persistent, which amounts to *storing K more NN copies*. Estimating $\mathbf{G}^{-1}$ requires scanning the training set once and inverting a matrix of $K \times K$, which is cheap. The evaluation of $q(f)$ embodies that of φ, i.e., performing K *forward passes under the scope of fwAD*. This is similar to other BNNs that perform S forward passes with different MC parameter samples to estimate the posterior predictive.

4 Theoretical Analysis

In this section, we theoretically analyze the approximation error of $\kappa_{\text{ELLA}}(\boldsymbol{x}, \boldsymbol{x}')$ to $\kappa_{\text{LLA}}(\boldsymbol{x}, \boldsymbol{x}')$.

To reduce unnecessary complexity, this section assumes using $M = K$ i.i.d. MC samples when performing the Nyström method. Then, κ_{ELLA} can be reformulated as (details deferred to Appendix A.3)

Algorithm 1: Build the LLA posterior.

```
# g_θ̂: NN pre-trained by MAP; (X,Y):
# training set; C: number of classes
# M,K,σ₀²: hyper-parameters
def estimate_G(φ,X,Y,K,σ₀²):
    G = zeros(K,K)
    for (x,y) in (X,Y):
        g_x,φ_x = φ(x)
        Λ_x,y = hessian(nll(g_x,y),g_x)
        G += φ_xᵀΛ_x,yφ_x
    return G + eye(K)/σ₀²
def _q_f(φ,G⁻¹,x)
    g_x,φ_x = φ(x)
    κ_x,x = φ_xG⁻¹φ_xᵀ
    return 𝒩(g_x,κ_x,x)
φ = build_φ(g_θ̂,X,C,M,K)
G⁻¹ = inv(estimate_G(φ,X,Y,K,σ₀²))
q_f = partial(_q_f,φ,G⁻¹)
```

Algorithm 2: Build φ.

```
def build_φ(g_θ̂,X,C,M,K):
    def _φ(g_θ̂,C,{v_k}ᵏₖ₌₁,x):
        φ_x = zeros(C,K)
        for k in range(K):
            with fwAD.enable():
                g_x,jvp = g_(θ̂,v_k)(x)
            φ_x[:,k] = jvp
        return g_x,φ_x
    J_θ̂,X̃ = zeros(M,dim(θ̂))
    for m in range(M):
        x_m = uniform_sample(X)
        i_m = uniform_sample([C])
        J_θ̂,X̃[m] = grad(g_θ̂(x_m)[i_m],θ̂)
    {λ_k,u_k}ᵏₖ₌₁ = eig(J_θ̂,X̃J_θ̂,X̃ᵀ,top=K)
    for k in range(K):
        v_k = J_θ̂,X̃ᵀu_k/√λ_k
    return partial(_φ,g_θ̂,C,{v_k}ᵏₖ₌₁)
```

$$\kappa_{\text{ELLA}}(\boldsymbol{x},\boldsymbol{x}') = J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\,\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\underbrace{\left[\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}/\sigma_0^2\right]^{-1}}_{\boldsymbol{\Sigma}'}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\,J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})^{\top}. \quad (18)$$

Thereby, the gap between $\kappa_{\text{ELLA}}(\boldsymbol{x},\boldsymbol{x}')$ and $\kappa_{\text{LLA}}(\boldsymbol{x},\boldsymbol{x}')$ can be upper bounded by $\mathcal{E} = \|\boldsymbol{\Sigma}' - \boldsymbol{\Sigma}\|$, where $\|\cdot\|$ represents the matrix 2-norm (i.e., the spectral norm). In typical cases, $P \gg M$, thus with high probability $\mathbf{K} = \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} \succ 0$. We present an upper bound of $\mathcal{E}$ as follows.

Theorem 1 (Proof in Appendix A.4). *Let c_Λ be a finite constant associated with Λ, and $\mathcal{E}'$ the error of Nyström approximation* $\|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}(\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top})^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\|$. *It holds that*

$$\mathcal{E} \leq \sigma_0^4 c_\Lambda \mathcal{E}' + \sigma_0^2.$$

$\mathcal{E}'$ has been extensively analyzed by pioneering work [12, 5, 26], and we simply adapt the results developed by Drineas and Mahoney [12] to our case. We denote the maximum diagonal entry and the $M + 1$-th largest eigenvalue of $\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}$ by c_κ and $\tilde{\lambda}_{M+1}$ respectively.

Theorem 2 (Error bound of Nyström approximation). *With probability at least $1 - \delta$, it holds that:*

$$\mathcal{E}' \leq \tilde{\lambda}_{M+1} + \frac{NC}{\sqrt{M}}c_\kappa(2 + \log\frac{1}{\delta}).$$

Plugging this back to $\mathcal{E}$, we arrive at the corollary below.

Corollary 1. *With probability at least $1 - \delta$, the following bound exists:*

$$\mathcal{E} \leq \sigma_0^4 c_\Lambda(\tilde{\lambda}_{M+1} + \frac{NC}{\sqrt{M}}c_\kappa(2 + \log\frac{1}{\delta})) + \sigma_0^2.$$

As desired, the upper bound of $\mathcal{E}$ decreases along with the growing of the number of MC samples M.

5 Experiments

We first discuss how to specify the hyperparameters of ELLA, then expose an interesting finding. After that, we compare ELLA to competing baselines to evidence its merits in efficacy and scalability.

5.1 Specification of Hyperparameters

Given an NN $g_{\hat{\boldsymbol{\theta}}}$ pretrained by MAP, we need to specify the prior variance σ_0^2, the number of MC samples in Nyström method M, and the number of remaining eigenpairs K before applying ELLA. We simply set σ_0^2 to $\frac{1}{N\gamma}$ with γ as the weight decay coefficient used for pretraining according to [10].

| | (a) | (b) | (c) |

Figure 2: (a)-(b): The approximation errors $\epsilon_{\text{Nyström}}$ and ϵ_{ELLA} vary w.r.t. M and K ($M \geq K$). (c): The test NLL of ELLA on CIFAR-10 varies w.r.t. the number of training data N.

Table 1: Comparison on test accuracy (%) ↑, NLL ↓, and ECE ↓ on CIFAR-10.

Method	ResNet-20			ResNet-32			ResNet-44			ResNet-56		
	Acc.	NLL	ECE	Acc.	NLL	ECE	Acc.	NLL	ECE	Acc.	NLL	ECE
ELLA	92.6	**0.233**	**0.009**	93.5	**0.216**	**0.008**	94.0	**0.202**	**0.007**	94.4	**0.187**	**0.007**
MAP	92.6	0.282	0.039	93.5	0.292	0.041	94.0	0.275	0.039	94.4	0.252	0.037
MFVI-BF	92.7	**0.233**	0.017	93.6	0.222	0.020	94.0	**0.202**	0.017	94.5	**0.187**	0.016
*LLA**	92.6	0.269	0.034	93.5	0.259	0.033	94.0	0.236	0.028	94.3	0.213	0.022
LLA-KFAC*	92.6	0.270	0.034	93.5	0.260	0.033	94.0	0.232	0.028	94.3	0.201	0.025
LLA-Diag	92.3	0.729	0.406	92.8	0.755	0.432	92.7	0.780	0.446	93.0	0.841	0.481
LLA-KFAC	92.1	0.853	0.469	91.9	1.027	0.548	91.3	1.094	0.566	89.7	1.173	0.578

We perform an empirical study to inspect how M and K affect the quality of the Nyström approximation and the ELLA GP covariance. We take 2000 MNIST images as training set $\mathbf{X}$, and 256 others as validation set $\mathbf{X}_{\text{val}}$. The architecture contains 2 convolutions and a linear head. Batch normalization [23] and ReLU activation are used. The number of parameters P is $29,034$. Larger architectures or larger $\mathbf{X}$ will render the exact evaluation of κ_{LLA} unapproachable. We quantify the approximation error of the Nyström method by $\epsilon_{\text{Nyström}} \triangleq \|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} (\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top})^{-1} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\| / \|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\|$, and that from κ_{ELLA} to κ_{LLA} by $\epsilon_{\text{ELLA}} \triangleq \frac{1}{|\mathbf{X}_{\text{val}}|} \sum_{\boldsymbol{x} \in \mathbf{X}_{\text{val}}} \|\kappa_{\text{ELLA}}(\boldsymbol{x},\boldsymbol{x}) - \kappa_{\text{LLA}}(\boldsymbol{x},\boldsymbol{x})\| / \|\kappa_{\text{LLA}}(\boldsymbol{x},\boldsymbol{x})\|$. We vary M from 4 to 2000 and K from 4 to M, and report the approximation errors in Figure 2 (a)-(b). We notice that 1) the larger K the better; 2) when fixing K, $\epsilon_{\text{Nyström}}$ and ϵ_{ELLA} decay as M grows; 3) $\epsilon_{\text{Nyström}}$ decays more rapidly than ϵ_{ELLA}, echoing Theorem 1. Given that ELLA needs to store K vectors of size P, small K is desired for efficiency. $K \in [16, 32]$ seems to be a reasonable choice given Figure 2. Unless otherwise stated, we set $M = 2000$ and $K = 20$ in the following experiments.

ELLA (or LLA) finds a GP posterior, so predicts with a variant of the aforementioned posterior predictive: $p(\boldsymbol{y}|\boldsymbol{x}_*, \mathcal{D}) = \mathbb{E}_{p(f|\mathcal{D})} p(\boldsymbol{y}|f(\boldsymbol{x}_*)) \approx \mathbb{E}_{q(f)} p(\boldsymbol{y}|f(\boldsymbol{x}_*)) = \mathbb{E}_{\boldsymbol{f} \sim \mathcal{N}(g_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}_*), \kappa_{\text{ELLA}}(\boldsymbol{x}_*, \boldsymbol{x}_*))} p(\boldsymbol{y}|\boldsymbol{f})$. In classification tasks, we use 512 MC samples to approximate the last expectation and it is cheap.

5.2 The Overfitting Issue of ELLA

Reinspecting Equation (1) and (6), we see, with more training data involved, the covariance in LA, LLA, and ELLA shrinks and the uncertainty dissipates. However, under ubiquitous model misspecification [41], *should the uncertainty vanish that fast?* We perform a study with ResNets [18] on CIFAR-10 [31] to find an answer. Concretely, we randomly subsample N data from the training set of CIFAR-10, and fit ELLA on them. We depict the test negative log-likelihood (NLL), accuracy, and expected calibration error (ECE) [17] of the ELLA in Figure 2 (c) and Appendix B.1. The *V-shape* curves of NLL and ECE across settings reflect an *overfitting* issue of ELLA (or more generally, LLA).

To address this issue, we advocate *performing early stop when applying ELLA to big data*. Specifically, when iterating over the training data to estimate $\mathbf{G}$ (see Equation (6)), we continuously record the NLL of the current ELLA posterior on some validation data, and stop when there is a trend of overfitting. If we cannot access a validation set easily, we can apply strong data augmentation to some training data to form a substitute of the validation set. Cross validation is also required by [7], but in the sake of finding a proper Gaussian prior variance σ_0^2. An additional benefit of early stopping is that it significantly reduces ELLA's time cost for handling large data (e.g., ImageNet [8]).

Figure 3: NLL (Left) and ECE (Right) on CIFAR-10 corruptions for models trained with ResNet-56 architecture. Each box corresponds to a summary of the results across 19 types of skew.

(a) (b) (c)

Figure 4: (a) Error versus confidence plots for methods trained on CIFAR-10 and tested on CIFAR-10+SVHN. (b) Test NLL of ELLA varies w.r.t. K on CIFAR-10. (c) Comparison on the wall-clock time used for predicting all CIFAR-10 test data (measured on an NVIDIA A40 GPU). The results are obtained with ResNet-20 architecture.

5.3 Illustrative Regression

We build a regression problem with $N = 16$ samples from $y = \sin 2x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$ as shown in Figure 1. The model is a MLP with 3 hidden layers and `tanh` activations, and we pretrain it by MAP for 1000 iterations. For ELLA, we set $M = 16$ and $K = 5$ for efficiency. Unless stated otherwise, we use the interfaces of `Laplace` [6] to implement LLA, LLA-KFAC, LLA-Diag, and LLA*. Compared to LLA-KFAC, LLA-Diag, and LLA*, ELLA delivers a closer approximation to LLA.

5.4 CIFAR-10 Classification

Then, we assess ELLA on CIFAR-10 [31] with ResNet architectures [18]. We obtain pretrained models from the open source community. Apart from MAP, LLA*, LLA-Diag, LLA-KFAC, we further introduce last-layer LLA with KFAC approximation (LLA*-KFAC) and mean-field VI via Bayesian finetuning [10] (MFVI-BF)[4] as baselines. LLA cannot be directly applied as the GGN matrices are huge. These methods all locate in the family of Gaussian approximate posteriors and are all *post-hoc* applied to the pretrained models to establish fair comparison. Regarding the setups, we use $M = 2000$ and $K = 20$ for ELLA;[5] we use 20 MC samples to estimate the posterior predictive of MFVI-BF (as it incurs 20 NN forward passes), and use 512 ones for the other methods as stated.

We present the comparison on test accuracy, NLL, and ECE in Table 1. As shown, ELLA exhibits superior NLL and ECE across settings. MFVI-BF also gives good NLL. LLA* and LLA*-KFAC can improve the uncertainty and calibration of MAP, yet underperforming ELLA. LLA-Diag and LLA-KFAC fail for unclear reasons (also reported by [9]), so are excluded from the following studies.

We then examine the models on the widely used out-of-distribution (OOD) generalization/robustness benchmark CIFAR-10 corruptions [19] and report the results in Figure 3 and Appendix B.1. It is prominent that ELLA surpasses the baselines in aspects of NLL and ECE at various levels of skew, implying its ability to make conservative predictions for OOD inputs.

We further evaluate the models on the combination of the CIFAR-10 test data and the OOD SVHN test data. The predictions on SVHN are all regarded as wrong due to label shift. We plot the average error rate of the samples with $\leq \tau$ ($\tau \in [0, 1]$) confidence in Figure 4 (a). As shown, ELLA makes less mistakes than the baselines under various confidence thresholds. Figure 4 (b) displays how K impacts the test NLL. We see that $K \in [20, 30]$ can already lead to good performance, reflecting the efficiency of ELLA. Figure 4 (c) shows the comparison on the time used for predicting all CIFAR-10 test data. ELLA is slightly slower than MFVI and substantially faster than non-last-layer LLA.

---

[4]Flipout [56] trick is deployed for variance-reduced gradient estimation.

[5]Storing 2000 vectors of size P is costly, so we trade time for memory and compute them whenever needed.

Table 2: Comparison on test accuracy (%) ↑, NLL ↓, and ECE ↓ on ImageNet.

Method	ResNet-18			ResNet-34			ResNet-50		
	Acc.	NLL	ECE	Acc.	NLL	ECE	Acc.	NLL	ECE
ELLA	69.8	1.243	**0.016**	73.4	1.071	**0.014**	76.2	0.948	**0.018**
MAP	69.8	1.247	0.026	73.3	1.081	0.035	76.2	0.962	0.037
MFVI-BF	**70.3**	**1.216**	0.044	**73.7**	**1.045**	0.033	76.2	**0.945**	0.032

Figure 5: NLL (Left) and ECE (Right) on ImageNet corruptions for models trained with ViT-B architecture. Each box corresponds to a summary of the results across 19 types of skew.

5.5 ImageNet Classification

We apply ELLA to ImageNet classification [8] to demonstrate its scalability. The experiment settings are identical with those for CIFAR-10. We observe that all LLA methods implemented with `Laplace` would cause out-of-memory (OOM) errors, thus take only MAP and MFVI-BF as baselines. Table 2 presents the comparison on test accuracy, NLL, and ECE with ResNet architectures. We see that ELLA maintains its superiority in ECE while MFVI-BF can induce higher accuracy and lower NLL. This may be attributed to that the pretrained MAP model lies at a sharp maxima of the true posterior so it is necessary to properly adjust the mean of the Gaussian approximate posterior.

We lastly apply ELLA to ViT-B [11]. We compare ELLA to MAP in Table 3 as all other baselines incur OOM errors or crushingly long running time. As shown, ELLA beats MAP in multiple aspects. Figure 5 shows the results of ELLA and MAP on ImageNet corruptions [19]. They are consistent with those for CIFAR-10 corruptions. We reveal by this experiment that ELLA can be a more applicable and scalable method than most of existing BNNs.

Table 3: Comparison on test accuracy (%) ↑, NLL ↓, and ECE ↓ on ImageNet with ViT-B architecture.

Method	Acc.	NLL	ECE
ELLA	81.6	0.695	0.022
MAP	81.5	0.700	0.039

6 Related Work

LA [38, 50, 14, 30, 22, 6, 7] locally approximates the true posterior with a Gaussian, analogous to VI with Gaussian variationals [16, 1, 36, 52, 46] and SWAG [39]. LA can be applied to pretrained models effortlessly while the acquired posteriors are potentially restrictive (see Section 5.5). VI enjoys higher flexibility yet relies on costly training; BayesAdapter [10] seems to be a remedy to the issue but its accessibility is still lower than LA. SWAG stores a series of SGD iterates to heuristically construct an approximate posterior and is empirically weaker than LA/LLA [6].

Though more expressive approaches like deep ensembles [32] and MCMC [55, 4, 63] can explicitly explore diverse posterior modes, they face limitations in efficiency and scalability. What's more, it has been shown that LA/LLA can perform on par with or better than deep ensembles and cyclical MCMC on multiple benchmarks [6]. This may be attributed to the un-identified, complicated relationships between the parameters space and the function space of DNNs [59]. Also of note that LA can embrace deep ensembles to capture multiple posterior modes [13].

7 Conclustion

This paper proposes ELLA, a simple, effective, and reliable approach for Bayesian deep learning. ELLA addresses the unreliability issues of existing approximations to LLA and is implemented based on Nyström approximation. We offer theoretical guarantees for ELLA and perform extensive studies to testify its efficacy and scalability. ELLA currently accounts for only the predictive, and extending it to estimate model evidence for model selection [38] deserves future investigation.

References

[1] Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *International Conference on Machine Learning*, pages 1613–1622, 2015.

[2] James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018.

[3] David Burt, Carl Edward Rasmussen, and Mark Van Der Wilk. Rates of convergence for sparse variational gaussian process regression. In *International Conference on Machine Learning*, pages 862–871. PMLR, 2019.

[4] Tianqi Chen, Emily Fox, and Carlos Guestrin. Stochastic gradient hamiltonian monte carlo. In *International Conference on Machine Learning*, pages 1683–1691. PMLR, 2014.

[5] Corinna Cortes, Mehryar Mohri, and Ameet Talwalkar. On the impact of kernel approximation on learning accuracy. In *International Conference on Artificial Intelligence and Statistics*, pages 113–120. JMLR Workshop and Conference Proceedings, 2010.

[6] Erik Daxberger, Agustinus Kristiadi, Alexander Immer, Runa Eschenhagen, Matthias Bauer, and Philipp Hennig. Laplace redux-effortless bayesian deep learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[7] Erik Daxberger, Eric Nalisnick, James U Allingham, Javier Antorán, and José Miguel Hernández-Lobato. Bayesian deep learning via subnetwork inference. In *International Conference on Machine Learning*, pages 2510–2521. PMLR, 2021.

[8] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2009.

[9] Zhijie Deng, Jiaxin Shi, and Jun Zhu. Neuralef: Deconstructing kernels by deep neural networks. *arXiv preprint arXiv:2205.00165*, 2022.

[10] Zhijie Deng, Hao Zhang, Xiao Yang, Yinpeng Dong, and Jun Zhu. Bayesadapter: Being bayesian, inexpensively and reliably, via bayesian fine-tuning. *arXiv preprint arXiv:2010.01979*, 2020.

[11] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

[12] Petros Drineas, Michael W Mahoney, and Nello Cristianini. On the nyström method for approximating a gram matrix for improved kernel-based learning. *Journal of Machine Learning Research*, 6(12), 2005.

[13] Runa Eschenhagen, Erik Daxberger, Philipp Hennig, and Agustinus Kristiadi. Mixtures of laplace approximations for improved post-hoc uncertainty in deep learning. *arXiv preprint arXiv:2111.03577*, 2021.

[14] Andrew YK Foong, Yingzhen Li, José Miguel Hernández-Lobato, and Richard E Turner. 'in-between'uncertainty in bayesian neural networks. *arXiv preprint arXiv:1906.11537*, 2019.

[15] Deena P Francis and Kumudha Raimond. Major advancements in kernel function approximation. *Artificial Intelligence Review*, 54(2):843–876, 2021.

[16] Alex Graves. Practical variational inference for neural networks. In *Advances in Neural Information Processing Systems*, pages 2348–2356, 2011.

[17] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. *arXiv preprint arXiv:1706.04599*, 2017.

[18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[19] Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

[20] José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of Bayesian neural networks. In *International Conference on Machine Learning*, pages 1861–1869, 2015.

[21] Geoffrey Hinton and Drew Van Camp. Keeping neural networks simple by minimizing the description length of the weights. In *ACM Conference on Computational Learning Theory*, 1993.

[22] Alexander Immer, Maciej Korzepa, and Matthias Bauer. Improving predictions of bayesian neural nets via local linearization. In *International Conference on Artificial Intelligence and Statistics*, pages 703–711. PMLR, 2021.

[23] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pages 448–456. PMLR, 2015.

[24] Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *arXiv preprint arXiv:1806.07572*, 2018.

[25] Huisu Jang and Jaewook Lee. An empirical study on modeling and prediction of bitcoin prices with bayesian neural networks based on blockchain information. *Ieee Access*, 6:5427–5437, 2017.

[26] Rong Jin, Tianbao Yang, Mehrdad Mahdavi, Yu-Feng Li, and Zhi-Hua Zhou. Improved bounds for the nyström method with application to kernel classification. *IEEE Transactions on Information Theory*, 59(10):6939–6949, 2013.

[27] Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems*, pages 5574–5584, 2017.

[28] Mohammad Emtiyaz Khan, Alexander Immer, Ehsan Abedi, and Maciej Korzepa. Approximate inference turns deep networks into gaussian processes. *arXiv preprint arXiv:1906.01930*, 2019.

[29] Mohammad Emtiyaz Khan, Didrik Nielsen, Voot Tangkaratt, Wu Lin, Yarin Gal, and Akash Srivastava. Fast and scalable Bayesian deep learning by weight-perturbation in adam. In *International Conference on Machine Learning*, pages 2616–2625, 2018.

[30] Agustinus Kristiadi, Matthias Hein, and Philipp Hennig. Being bayesian, even just a bit, fixes overconfidence in relu networks. *arXiv preprint arXiv:2002.10118*, 2020.

[31] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[32] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, pages 6402–6413, 2017.

[33] Neil David Lawrence. *Variational inference in probabilistic models*. PhD thesis, Citeseer, 2001.

[34] Christian Leibig, Vaneeda Allken, Murat Seçkin Ayhan, Philipp Berens, and Siegfried Wahl. Leveraging uncertainty information from deep neural networks for disease detection. *Scientific Reports*, 7(1):1–14, 2017.

[35] Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose Bayesian inference algorithm. In *Advances in Neural Information Processing Systems*, pages 2378–2386, 2016.

[36] Christos Louizos and Max Welling. Structured and efficient variational deep learning with matrix gaussian posteriors. In *International Conference on Machine Learning*, pages 1708–1716, 2016.

[37] David JC MacKay. A practical Bayesian framework for backpropagation networks. *Neural Computation*, 4(3):448–472, 1992.

[38] David John Cameron Mackay. *Bayesian methods for adaptive models*. PhD thesis, California Institute of Technology, 1992.

[39] Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. In *Advances in Neural Information Processing Systems*, pages 13153–13164, 2019.

[40] James Martens and Roger Grosse. Optimizing neural networks with kronecker-factored approximate curvature. In *International Conference on Machine Learning*, pages 2408–2417. PMLR, 2015.

[41] Andres Masegosa. Learning under model misspecification: Applications to variational and ensemble methods. *Advances in Neural Information Processing Systems*, 33:5479–5491, 2020.

[42] J Mercer. Functions ofpositive and negativetypeand theircommection with the theory ofintegral equations. *Philosophicol Trinsdictions of the Rogyal Society*, pages 4–415, 1909.

[43] Marina Munkhoeva, Yermek Kapushev, Evgeny Burnaev, and Ivan Oseledets. Quadrature-based features for kernel approximation. *Advances in Neural Information Processing Systems*, 31, 2018.

[44] Radford M Neal. *Bayesian Learning for Neural Networks*. PhD thesis, University of Toronto, 1995.

[45] Evert J Nyström. Über die praktische auflösung von integralgleichungen mit anwendungen auf randwertaufgaben. *Acta Mathematica*, 54:185–204, 1930.

[46] Kazuki Osawa, Siddharth Swaroop, Anirudh Jain, Runa Eschenhagen, Richard E Turner, Rio Yokota, and Mohammad Emtiyaz Khan. Practical deep learning with Bayesian principles. *arXiv preprint arXiv:1906.02506*, 2019.

[47] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pages 8026–8037, 2019.

[48] Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. *Advances in Neural Information Processing Systems*, 20, 2007.

[49] Ali Rahimi and Benjamin Recht. Weighted sums of random kitchen sinks: Replacing minimization with randomization in learning. *Advances in Neural Information Processing Systems*, 21, 2008.

[50] Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *6th International Conference on Learning Representations*, volume 6. International Conference on Representation Learning, 2018.

[51] Matthias Seeger. Gaussian processes for machine learning. *International journal of neural systems*, 14(02):69–106, 2004.

[52] Shengyang Sun, Changyou Chen, and Lawrence Carin. Learning structured weight uncertainty in Bayesian neural networks. In *International Conference on Artificial Intelligence and Statistics*, pages 1283–1292, 2017.

[53] Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *International Conference on Artificial Intelligence and Statistics*, pages 567–574. PMLR, 2009.

[54] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pages 5998–6008, 2017.

[55] Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *International Conference on Machine Learning*, pages 681–688, 2011.

[56] Yeming Wen, Paul Vicol, Jimmy Ba, Dustin Tran, and Roger Grosse. Flipout: Efficient pseudo-independent weight perturbations on mini-batches. *arXiv preprint arXiv:1803.04386*, 2018.

[57] Veit Wild, Motonobu Kanagawa, and Dino Sejdinovic. Connections and equivalences between the nystr\" om method and sparse variational gaussian processes. *arXiv preprint arXiv:2106.01121*, 2021.

[58] Christopher Williams and Matthias Seeger. Using the nyström method to speed up kernel machines. *Advances in Neural Information Processing Systems*, 13, 2000.

[59] Andrew Gordon Wilson and Pavel Izmailov. Bayesian deep learning and a probabilistic perspective of generalization. *arXiv preprint arXiv:2002.08791*, 2020.

[60] Max A Woodbury. *Inverting modified matrices*. Statistical Research Group, 1950.

[61] Felix Xinnan X Yu, Ananda Theertha Suresh, Krzysztof M Choromanski, Daniel N Holtmann-Rice, and Sanjiv Kumar. Orthogonal random features. *Advances in Neural Information Processing Systems*, 29, 2016.

[62] Guodong Zhang, Shengyang Sun, David Duvenaud, and Roger Grosse. Noisy natural gradient as variational inference. In *International Conference on Machine Learning*, pages 5847–5856, 2018.

[63] Ruqi Zhang, Chunyuan Li, Jianyi Zhang, Changyou Chen, and Andrew Gordon Wilson. Cyclical stochastic gradient mcmc for bayesian deep learning. *arXiv preprint arXiv:1902.03932*, 2019.

A Proof

A.1 Derivation of Equation (5)

Given

$$\mathbf{\Sigma} = \sigma_0^2\Big(\mathbf{I}_P - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\Big),$$

we have

$$\begin{aligned}
\kappa_{\mathrm{LLA}}(\boldsymbol{x},\boldsymbol{x}') =& J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{\Sigma} J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^{\top}\\
=& \sigma_0^2 J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\left(\mathbf{I}_P - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\left[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\right]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\right)J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^{\top}\\
=& \sigma_0^2 \left(J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^{\top} - J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\left[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\right]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x}')^{\top}\right)\\
=& \sigma_0^2\Big(\kappa_{\mathrm{NTK}}(\boldsymbol{x},\boldsymbol{x}') - \kappa_{\mathrm{NTK}}(\boldsymbol{x},\mathbf{X})[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \kappa_{\mathrm{NTK}}(\mathbf{X},\mathbf{X})]^{-1}\kappa_{\mathrm{NTK}}(\mathbf{X},\boldsymbol{x}')\Big).
\end{aligned}$$

A.2 Derivation of Equation (6)

$$\begin{aligned}
\kappa_{\mathrm{ELLA}}(\boldsymbol{x},\boldsymbol{x}') =& \sigma_0^2\left(\varphi(\boldsymbol{x})\varphi(\boldsymbol{x}')^{\top} - \varphi(\boldsymbol{x})\boldsymbol{\varphi}_{\mathbf{X}}^{\top}\left[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \boldsymbol{\varphi}_{\mathbf{X}}\boldsymbol{\varphi}_{\mathbf{X}}^{\top}\right]^{-1}\boldsymbol{\varphi}_{\mathbf{X}}\varphi(\boldsymbol{x}')^{\top}\right)\\
=& \varphi(\boldsymbol{x})\sigma_0^2\left(\mathbf{I}_K - \boldsymbol{\varphi}_{\mathbf{X}}^{\top}\left[\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \boldsymbol{\varphi}_{\mathbf{X}}\boldsymbol{\varphi}_{\mathbf{X}}^{\top}\right]^{-1}\boldsymbol{\varphi}_{\mathbf{X}}\right)\varphi(\boldsymbol{x}')^{\top}\\
=& \varphi(\boldsymbol{x})\left[\boldsymbol{\varphi}_{\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\boldsymbol{\varphi}_{\mathbf{X}} + \mathbf{I}_K/\sigma_0^2\right]^{-1}\varphi(\boldsymbol{x}')^{\top} \qquad \text{(Woodbury matrix identity)}\\
=& \varphi(\boldsymbol{x})\Big[\sum_i \varphi(\boldsymbol{x}_i)^{\top}\Lambda(\boldsymbol{x}_i,\boldsymbol{y}_i)\varphi(\boldsymbol{x}_i) + \mathbf{I}_K/\sigma_0^2\Big]^{-1}\varphi(\boldsymbol{x}')^{\top}.
\end{aligned}$$

A.3 Derivation of Equation (18)

When $M = K$, the eigenvalues and eigenvectors of $\mathbf{K} = \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}$ can be organized as

square matrices $\mathrm{diag}(\boldsymbol{\lambda}) = \mathrm{diag}(\lambda_1,...,\lambda_K)$ and $\boldsymbol{U} = [\boldsymbol{u}_1,...,\boldsymbol{u}_K]$ respectively. And $\varphi(\boldsymbol{x}) =$

$[J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\boldsymbol{v}_1,...,J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\boldsymbol{v}_K] = J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U}\,\mathrm{diag}(\boldsymbol{\lambda})^{-\frac{1}{2}}$. Of note that $\boldsymbol{U}$ is a orthogonal matrix where

$\boldsymbol{U}\boldsymbol{U}^{\top} = \boldsymbol{U}^{\top}\boldsymbol{U} = \mathbf{I}_K \Rightarrow \boldsymbol{U}^{-1} = \boldsymbol{U}^{\top}$, and by definition, $\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} = \boldsymbol{U}\,\mathrm{diag}(\boldsymbol{\lambda})\boldsymbol{U}^{\top}$. Then

$$\begin{aligned}
\kappa_{\mathrm{ELLA}}(\boldsymbol{x},\boldsymbol{x}') =& \varphi(\boldsymbol{x})\Big[\sum_i \varphi(\boldsymbol{x}_i)^{\top}\Lambda(\boldsymbol{x}_i,\boldsymbol{y}_i)\varphi(\boldsymbol{x}_i) + \mathbf{I}_K/\sigma_0^2\Big]^{-1}\varphi(\boldsymbol{x}')^{\top}\\
=& \varphi(\boldsymbol{x})\left[\boldsymbol{\varphi}_{\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\boldsymbol{\varphi}_{\mathbf{X}} + \mathbf{I}_K/\sigma_0^2\right]^{-1}\varphi(\boldsymbol{x}')^{\top}\\
=& J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U}\,\mathrm{diag}(\boldsymbol{\lambda})^{-\frac{1}{2}}\Big[\mathrm{diag}(\boldsymbol{\lambda})^{-\frac{1}{2}}\boldsymbol{U}^{\top}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U}\,\mathrm{diag}(\boldsymbol{\lambda})^{-\frac{1}{2}}\\
& \hspace{10em} + \mathbf{I}_K/\sigma_0^2\Big]^{-1}\mathrm{diag}(\boldsymbol{\lambda})^{-\frac{1}{2}}\boldsymbol{U}^{\top}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})^{\top}\\
=& J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U}\Big[\boldsymbol{U}^{\top}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U} + \mathrm{diag}(\boldsymbol{\lambda})/\sigma_0^2\Big]^{-1}\boldsymbol{U}^{\top}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})^{\top}\\
=& J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\Big[\boldsymbol{U}\boldsymbol{U}^{\top}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\boldsymbol{U}\boldsymbol{U}^{\top} + \boldsymbol{U}\,\mathrm{diag}(\boldsymbol{\lambda})\boldsymbol{U}^{\top}/\sigma_0^2\Big]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})^{\top}\\
=& J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\Big[\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\mathbf{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}/\sigma_0^2\Big]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}J_{\hat{\boldsymbol{\theta}}}(\boldsymbol{x})^{\top}.
\end{aligned}$$

A.4 Proof of Theorem 1

Theorem 1. *Let c_{Λ} be a finite constant associated with Λ, and $\mathcal{E}'$ the error of Nyström approximation*

$\|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}(\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top})^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\|$. *It holds that*

$$\mathcal{E} \leq \sigma_0^4 c_{\Lambda}\mathcal{E}' + \sigma_0^2.$$

Proof. With $\mathbf{K} = \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} \succ 0$, let $\mathbf{P} = \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\mathbf{K}^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}$. By Woodbury matrix identity,

$$
\begin{aligned}
\boldsymbol{\Sigma}' &= \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\Big[\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}/\sigma_0^2\Big]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \\
&= \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\Big[\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} + \mathbf{K}/\sigma_0^2\Big]^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \\
&= \sigma_0^2\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\Big[\mathbf{K}^{-1} - \mathbf{K}^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\mathbf{K}^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top})^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}\mathbf{K}^{-1}\Big]\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \\
&= \sigma_0^2\Big[\mathbf{P} - \mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top})^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\Big].
\end{aligned}
$$

It is interesting to see that $\mathbf{P}$ is a projector: $\mathbf{P}^2 = \mathbf{P}$ and $\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top} = \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^{\top}$. Then

$$
\boldsymbol{\Sigma}' = \sigma_0^2\big[\mathbf{P} - \mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{-1}/\sigma_0^2 + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top})^{-1}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\big].
$$

By Woodbury matrix identity again,

$$
\begin{aligned}
\boldsymbol{\Sigma}' &= \sigma_0^2\Bigg[\mathbf{P} - \sigma_0^2\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\Big(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} - \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}(\mathbf{I}_P/\sigma_0^2 \\
&\qquad\qquad\qquad\qquad\qquad + \mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P})^{-1}\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\Big)\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\Bigg] \\
&= \sigma_0^2\Bigg[\mathbf{P} - \sigma_0^2\Big(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} - \mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}(\mathbf{I}_P/\sigma_0^2 \\
&\qquad\qquad\qquad\qquad\qquad + \mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P})^{-1}\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}\Big)\Bigg].
\end{aligned}
$$

Let $\mathbf{T} = (\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} + \mathbf{I}_P/\sigma_0^2)^{-1}$, so $\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} = \mathbf{T}^{-1} - \mathbf{I}_P/\sigma_0^2$. It follows that

$$
\boldsymbol{\Sigma}' = \sigma_0^2\Big[\mathbf{P} - \sigma_0^2\Big(\mathbf{T}^{-1} - \mathbf{I}_P/\sigma_0^2 - (\mathbf{T}^{-1} - \mathbf{I}_P/\sigma_0^2)\mathbf{T}(\mathbf{T}^{-1} - \mathbf{I}_P/\sigma_0^2)\Big)\Big] = \mathbf{T} + \sigma_0^2(\mathbf{P} - \mathbf{I}_P).
$$

As a result,

$$
\begin{aligned}
\mathcal{E} &= \|\boldsymbol{\Sigma}' - \boldsymbol{\Sigma}\| \\
&= \|\mathbf{T} + \sigma_0^2(\mathbf{P} - \mathbf{I}_P) - \boldsymbol{\Sigma}\| \\
&\leq \|\mathbf{T} - \boldsymbol{\Sigma}\| + \sigma_0^2\|\mathbf{P} - \mathbf{I}_P\| \\
&= \|\mathbf{T} - \boldsymbol{\Sigma}\| + \sigma_0^2,
\end{aligned}
$$

where we leverage the fact that the eigenvalue of the projector $\mathbf{P}$ is either 1 or 0. And

$$
\begin{aligned}
\|\mathbf{T} - \boldsymbol{\Sigma}\| &= \|-\mathbf{T}(\mathbf{T}^{-1} - \boldsymbol{\Sigma}^{-1})\boldsymbol{\Sigma}\| \\
&= \|-\mathbf{T}(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}})\boldsymbol{\Sigma}\| \\
&\leq \|\mathbf{T}\|\|\boldsymbol{\Sigma}\|\|\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\| \\
&\leq \frac{\|\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\|}{\lambda_{\min}(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} + \mathbf{I}_P/\sigma_0^2)\lambda_{\min}(\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} + \mathbf{I}_P/\sigma_0^2)} \\
&\leq \sigma_0^4\|\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\|,
\end{aligned}
$$

where $\lambda_{\min}(\cdot)$ denotes the smallest eigenvalue of a matrix. The last inequality holds due to that the eigenvalues of $\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P} + \mathbf{I}_P/\sigma_0^2$ and $\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} + \mathbf{I}_P/\sigma_0^2$ are larger than or equal to $1/\sigma_0^2$ as $\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\mathbf{P}$ and $\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^{\top}\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}$ are SPSD.

To estimate the upper bound of $\|\mathbf{T} - \boldsymbol{\Sigma}\|$, we lay out the following Lemma.

Lemma 1 (Proposition of Weinstein–Aronszajn identity). *If $\mathcal{A}$ and $\mathcal{B}$ are matrices of size $m \times n$ and $n \times m$ respectively, the non-zero eigenvalues of $\mathcal{A}\mathcal{B}$ and $\mathcal{B}\mathcal{A}$ are the same.*

It follows that

$$
\begin{aligned}
\|\mathbf{T} - \boldsymbol{\Sigma}\| \leq & \sigma_0^4 \|\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}\| \\
= & \frac{\sigma_0^4}{2} \|(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}})(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} - \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}) \\
& \qquad + (\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}})(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} + \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}})\| \\
\leq & \frac{\sigma_0^4}{2} \|(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}})(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} - \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}})\| \\
& \qquad + \frac{\sigma_0^4}{2} \|((\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}})(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} - \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}))^\top\| \\
= & \sigma_0^4 \|(\mathbf{P}\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} + \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}})(\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{P} - \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}^{\frac{1}{2}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}})\| \quad (\|\mathbf{A}^\top\| = \|\mathbf{A}\|) \\
= & \sigma_0^4 \|(\mathbf{P} + \mathbf{I}_P)\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top \boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}(\mathbf{P} - \mathbf{I}_P)\| \\
= & \sigma_0^4 \|\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}(\mathbf{P} - \mathbf{I}_P)(\mathbf{P} + \mathbf{I}_P)\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top\| \qquad\qquad \text{(Lemma 1)} \\
= & \sigma_0^4 \|\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}(\mathbf{P} - \mathbf{I}_P)\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top\| \qquad\qquad (\mathbf{P}^2 = \mathbf{P}) \\
= & \sigma_0^4 \|\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}(\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top (\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top)^{-1} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top)\| \\
\leq & \sigma_0^4 \|\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\| \|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top (\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top)^{-1} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top\|.
\end{aligned}
$$

It is easy to show that $\|\boldsymbol{\Lambda}_{\mathbf{X},\mathbf{Y}}\| \leq c_\Lambda$ with c_Λ as a finite constant. For example, when handling regression tasks, $-\log p(\boldsymbol{y}|\boldsymbol{g})$ typically boils down to $\frac{1}{2\sigma_{\text{noise}}^2}(\boldsymbol{g} - \boldsymbol{y})^\top (\boldsymbol{g} - \boldsymbol{y})$ where σ_{noise}^2 refers to the variance of data noise, so $-\nabla_{\boldsymbol{gg}}^2 \log p(\boldsymbol{y}|\boldsymbol{g}) = \frac{1}{\sigma_{\text{noise}}^2} \mathbf{I}_C$ and $c_\Lambda = \frac{1}{\sigma_{\text{noise}}^2}$.

When facing classification cases, $-\log p(\boldsymbol{y}|\boldsymbol{g})$ becomes the softmax cross-entropy loss. It is guaranteed that $c_\Lambda \leq 2$ because

$$
\begin{aligned}
\| - \nabla_{\boldsymbol{gg}}^2 \log p(\boldsymbol{y}|\boldsymbol{g})\| = & \|\operatorname{diag}(\operatorname{softmax}(\boldsymbol{g})) - \operatorname{softmax}(\boldsymbol{g})\operatorname{softmax}(\boldsymbol{g})^\top\| \\
\leq & \|\operatorname{diag}(\operatorname{softmax}(\boldsymbol{g}))\| + \|\operatorname{softmax}(\boldsymbol{g})\operatorname{softmax}(\boldsymbol{g})^\top\| \\
\leq & 1 + \|\operatorname{softmax}(\boldsymbol{g})^\top \operatorname{softmax}(\boldsymbol{g})\| \leq 1 + 1 = 2.
\end{aligned}
$$

To summarize, we have the following bound for the approximation error $\mathcal{E}$:

$$
\mathcal{E} \leq \|\mathbf{T} - \boldsymbol{\Sigma}\| + \sigma_0^2 = \sigma_0^4 c_\Lambda \|\mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top (\mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}}^\top)^{-1} \mathbf{J}_{\hat{\boldsymbol{\theta}},\tilde{\mathbf{X}}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top - \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}} \mathbf{J}_{\hat{\boldsymbol{\theta}},\mathbf{X}}^\top\| + \sigma_0^2.
$$

$\square$

B More experiments

B.1 More Results on CIFAR-10

Figure 6 present how the test accuracy and ECE of ELLA on CIFAR-10 vary w.r.t. the number of training data N.

Figure 7, Figure 8, and Figure 9 show the results of the considered methods on CIFAR-10 corruptions using ResNet-20, ResNet-32, and ResNet-44 architectures respectively. We can see that ELLA surpasses the baselines in aspects of NLL and ECE at various levels of skew. These results signify ELLA's ability to make conservative predictions for OOD inputs.

Figure 6: The test accuracy and ECE of ELLA on CIFAR-10 vary w.r.t. the number of training data N.

Figure 7: NLL (Left) and ECE (Right) on CIFAR-10 corruptions for models trained with ResNet-20 architecture. Each box corresponds to a summary of the results across 19 types of skew.

Figure 8: NLL (Left) and ECE (Right) on CIFAR-10 corruptions for models trained with ResNet-32 architecture. Each box corresponds to a summary of the results across 19 types of skew.

Figure 9: NLL (Left) and ECE (Right) on CIFAR-10 corruptions for models trained with ResNet-44 architecture. Each box corresponds to a summary of the results across 19 types of skew.