# Invariance Principle Meets Information Bottleneck for Out-of-Distribution Generalization

## Abstract

The invariance principle from causality is at the heart of notable approaches such as invariant risk minimization (IRM) that seek to address out-of-distribution (OOD) generalization failures. Despite the promising theory, invariance principle-based approaches fail in common classification tasks, where invariant (causal) features capture all the information about the label. Are these failures due to the methods failing to capture the invariance? Or is the invariance principle itself insufficient? To answer these questions, we revisit the fundamental assumptions in linear regression tasks, where invariance-based approaches were shown to provably generalize OOD. In contrast to the linear regression tasks, we show that for linear classification tasks we need much stronger restrictions on the distribution shifts, or otherwise OOD generalization is impossible. Furthermore, even with appropriate restrictions on distribution shifts in place, we show that the invariance principle alone is insufficient. We prove that a form of the *information bottleneck* constraint along with invariance helps address key failures when invariant features capture all the information about the label and also retains the existing success when they do not. We propose an approach that incorporates both of these principles and demonstrate its effectiveness in several experiments.

## 1 Introduction

Recent years have witnessed an explosion of examples showing deep learning models are prone to exploiting shortcuts (spurious features) (Geirhos et al., 2020; Pezeshki et al., 2020) which make them fail to generalize out-of-distribution (OOD). In Beery et al. (2018), a convolutional neural network was trained to classify camels from cows; however, it was found that the model relied on the background color (e.g., green pastures for cows) and not on the properties of the animals (e.g., shape). These examples become very concerning when they occur in real-life applications (e.g., COVID-19 detection (DeGrave et al., 2020)).

To address these out-of-distribution generalization failures, invariant risk minimization (Arjovsky et al., 2019) and several other works were proposed (Krueger et al., 2020; Koyama and Yamaguchi, 2020; Parascandolo et al., 2021; Pezeshki et al., 2020; Robey et al., 2021). The invariance principle from causality (Peters et al., 2015; Pearl, 1995) is at the heart of these works. The principle distinguishes predictors that only rely on the causes of the label from those that do not. The optimal predictor that only focuses on the causes is invariant and min-max optimal (Rojas-Carulla et al., 2018; Koyama and Yamaguchi, 2020; Ahuja et al., 2021) under a large class of distribution shifts but the same is not true for other predictors.

**Our contributions.** Despite the promising theory, invariance principle-based approaches fail in settings (Aubin et al., 2021) where invariant features capture all information about the label contained in the input. A particular example is image classification (e.g., cow vs. camel) (Beery et al., 2018)

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

where the label is a deterministic function of the invariant features (e.g, shape of the animal), and does not depend on the spurious features (e.g., background). To understand such failures, we revisit the fundamental assumptions in linear regression tasks, where invariance-based approaches were shown to provably generalize OOD. We show that, in contrast to the linear regression tasks, OOD generalization is significantly harder for linear classification tasks; we need much stronger restrictions in the form of support overlap assumptions on the distribution shifts, or otherwise it is not possible to guarantee OOD generalization under interventions on variables other than the target class. We then proceed to show that, even under the right assumptions on distribution shifts, the invariance principle is insufficient. However, we establish that *information bottleneck* (IB) constraints (Tishby et al., 2000), together with the invariance principle, provably works in both settings – when invariant features completely capture the information about the label and also when they do not. (Table 1 summarizes our theoretical results presented later). We propose an approach that combines both these principles and demonstrate its effectiveness on linear unit tests (Aubin et al., 2021) and on different colored MNIST datasets (Arjovsky et al., 2019; Ahuja et al., 2021).

| Task | Invariant features capture label info | Support overlap invariant features | Support overlap spurious features | **OOD generalization guarantee** $(\mathcal{E}_{tr} \to \mathcal{E}_{all})$ | | | |
|---|---|---|---|---|---|---|---|
| | | | | ERM | IRM | IB-ERM | IB-IRM |
| Linear Classification | Full/Partial | No | Yes/No | Impossible for any algorithm to generalize OOD [Thm2] | | | |
| | Full | Yes | No | ✗ | ✗ | ✓ | ✓ [Thm3,4] |
| | Partial | Yes | No | ✗ | ✗ | ✗ | ✓ [Appendix] |
| | Full | Yes | Yes | ✓ | ✓ | ✓ | ✓ [Thm3,4] |
| | Partial | Yes | Yes | ✗ | ✓ | ✗ | ✓ |
| Linear Regression | Full | No | No | ✓ | ✓ | ✓ | ✓ |
| | Partial | No | No | ✗ | ✓ | ✗ | ✓ [Thm4] |

Table 1: Summary of the new and existing results (Arjovsky et al., 2019; Rosenfeld et al., 2021). IB-ERM (IRM): information bottleneck - empirical (invariant) risk minimization ERM (IRM).

## 2   OOD generalization and invariance: background & failures

**Background.** We consider a supervised training data $D$ gathered from a set of training environments $\mathcal{E}_{tr}$: $D = \{D^e\}_{e \in \mathcal{E}_{tr}}$, where $D^e = \{x_i^e, y_i^e\}_{i=1}^{n^e}$ is the dataset from environment $e \in \mathcal{E}_{tr}$ and $n^e$ is the number of instances in environment $e$. $x_i^e \in \mathbb{R}^d$ and $y_i^e \in \mathcal{Y} \subseteq \mathbb{R}^k$ correspond to the input feature value and the label for $i^{th}$ instance respectively. Each $(x_i^e, y_i^e)$ is an i.i.d. draw from $\mathbb{P}^e$, where $\mathbb{P}^e$ is the joint distribution of the input feature and the label in environment $e$. Let $\mathcal{X}^e$ be the support of the input feature values in the environment $e$. The goal of OOD generalization is to use training data $D$ to construct a predictor $f : \mathbb{R}^d \to \mathbb{R}^k$ that performs well across many unseen environments in $\mathcal{E}_{all}$, where $\mathcal{E}_{all} \supset \mathcal{E}_{tr}$. Define the risk of $f$ in environment $e$ as $R^e(f) = \mathbb{E}\big[\ell(f(X^e), Y^e)\big]$, where for example $\ell$ can be 0-1 loss, logistic loss, square loss, $(X^e, Y^e) \sim \mathbb{P}^e$, and the expectation $\mathbb{E}$ is w.r.t. $\mathbb{P}^e$. Formally stated, our goal is to use the data from training environments $\mathcal{E}_{tr}$ to find $f : \mathbb{R}^d \to \mathcal{Y}$ to minimize

$$\min_f \max_{e \in \mathcal{E}_{all}} R^e(f). \tag{1}$$

So far we did not state any restrictions on $\mathcal{E}_{all}$. Consider binary classification: without any restrictions on $\mathcal{E}_{all}$, no method can reduce the above objective ($\ell$ is 0-1 loss) to below one. Suppose a method outputs $f^*$; if $\exists\, e \in \mathcal{E}_{all} \setminus \mathcal{E}_{tr}$ with labels based on $1 - f^*$, then it achieves an error of one. Some assumptions on $\mathcal{E}_{all}$ are thus necessary. Consider how $\mathcal{E}_{all}$ is restricted using invariance for linear regressions (Arjovsky et al., 2019).

**Assumption 1.** *Linear regression structural equation model (SEM). In each $e \in \mathcal{E}_{all}$*

$$Y^e \leftarrow w_{\mathsf{inv}}^* \cdot Z_{\mathsf{inv}}^e + \epsilon^e, \quad Z_{\mathsf{inv}}^e \perp \epsilon^e, \quad \mathbb{E}[\epsilon^e] = 0, \mathbb{E}\big[|\epsilon^e|^2\big] \leq \sigma_{\mathsf{sup}}^2$$
$$X^e \leftarrow S(Z_{\mathsf{inv}}^e, Z_{\mathsf{spu}}^e) \tag{2}$$

*where $w_{\mathsf{inv}}^* \in \mathbb{R}^m$, $Z_{\mathsf{inv}}^e \in \mathbb{R}^m$, $Z_{\mathsf{spu}} \in \mathbb{R}^o$, $S \in \mathbb{R}^{d \times (m+o)}$, $S$ is invertible $(m + o = d)$. We focus on invertible $S$ but several results extend to non-invertible $S$ as well (see Appendix).*

Assumption 1 states how $Y^e$ and $X^e$ are generated from latent invariant features $Z_{\mathsf{inv}}^e$,[1] latent spurious features $Z_{\mathsf{spu}}^e$ and noise $\epsilon^e$. The *relationship between label and invariant features is invariant, i.e.,* $w_{\mathsf{inv}}^*$ *is fixed* across all environments. However, the distributions of $Z_{\mathsf{inv}}^e$, $Z_{\mathsf{spu}}^e$, and $\epsilon^e$ are allowed to change arbitrarily across all the environments. Suppose $S$ is identity. If we regress only on the

---

[1]In many examples in the literature, invariant features are causal, but not always (Rosenfeld et al., 2021).

75 invariant features $Z_{\text{inv}}^e$, then the optimal solution is $w_{\text{inv}}^*$, which is independent of the environment,
76 and the error it achieves is bounded above by the variance of $\epsilon^e$ ($\sigma_{\text{sup}}^2$). If we regress on the entire
77 $Z^e$ and the optimal predictor places a non-zero weight on $Z_{\text{spu}}^e$ (e.g., $Z_{\text{spu}}^e \leftarrow Y^e + \zeta^e$), then this
78 predictor fails to solve equation (1) ($\exists\, e \in \mathcal{E}_{all}$, $Z_{\text{spu}}^e \to \infty$, error $\to \infty$, see Appendix for details).
79 Also, not only regressing on $Z_{\text{inv}}^e$ is better than on $Z^e$, it can be shown that it is optimal, i.e., it solves
80 equation (1) under Assumption 1 and achieves a value of $\sigma_{\text{sup}}^2$ for the objective in equation (1).

81 **Invariant predictor.** Define a linear representation map $\Phi : \mathbb{R}^{r \times d}$ (that transforms $X^e$ as $\Phi(X^e)$)
82 and define a linear classifier $w : \mathbb{R}^{k \times r}$ (that operates on the representation $w \cdot \Phi(X^e)$). We want to
83 search for representations $\Phi$ such that $\mathbb{E}[Y^e|\Phi(X^e)]$ is invariant (in Assumption 1 if $\Phi(X^e) = Z_{\text{inv}}^e$,
84 then $\mathbb{E}[Y^e|\Phi(X^e)]$ is invariant). We say that a data representation $\Phi$ elicits an invariant predictor
85 $w \cdot \Phi$ across the set of training environments $\mathcal{E}_{tr}$ if there is a predictor $w$ that simultaneously achieves
86 the minimum risk, i.e., $w \in \arg\min_{\tilde{w}} R^e(\tilde{w} \cdot \Phi)$, $\forall e \in \mathcal{E}_{tr}$. The main objective of IRM is stated as

$$\min_{w \in \mathbb{R}^{k \times r}, \Phi \in \mathbb{R}^{r \times d}} \frac{1}{|\mathcal{E}_{tr}|} \sum_{e \in \mathcal{E}_{tr}} R^e(w \cdot \Phi) \quad \text{s.t.} \ w \in \arg\min_{\tilde{w} \in \mathbb{R}^{k \times r}} R^e(\tilde{w} \cdot \Phi), \ \forall e \in \mathcal{E}_{tr}. \quad (3)$$

87 Observe that if we drop the constraints in the above which search only over invariant predictors then
88 we get standard empirical risk minimization (ERM) (Vapnik, 1992) (assuming all the training envi-
89 ronments occur with equal probability). In all our theorems, we use 0-1 loss for binary classification
90 $\mathcal{Y} = \{0, 1\}$ and square loss for regression $\mathcal{Y} = \mathbb{R}$. For binary classification, the output of the predictor
91 is given as $\mathsf{I}(w \cdot \Phi(X^e))$, where $\mathsf{I}(\cdot)$ is the indicator function that takes a value 1 if the input is $\geq 0$
92 and 0 otherwise, and the risk is $R^e(w \cdot \Phi) = \mathbb{E}\big[|\mathsf{I}(w \cdot \Phi(X^e)) - Y^e|\big]$. For regression, the output of
93 the predictor is $w \cdot \Phi(X^e)$ and the corresponding risk is $R^e(w \cdot \Phi) = \mathbb{E}\big[(w \cdot \Phi(X^e) - Y^e)^2\big]$. We
94 now present the main OOD generalization result from Arjovsky et al. (2019) for linear regressions.

95 **Theorem 1.** *(Informal) If Assumption 1 is satisfied,* $\mathsf{Rank}[\Phi] > 0$, *$|\mathcal{E}_{tr}| > 2d$, and $\mathcal{E}_{tr}$ lie in a linear*
96 *general position (a mild condition on the data in $\mathcal{E}_{tr}$, defined in the Appendix), then each solution to*
97 *equation* (3) *achieves OOD generalization (solves equation* (1), $\nexists\, e \in \mathcal{E}_{all}$ *with risk* $> \sigma_{\text{sup}}^2$).

98 Despite the above guarantees, IRM has been shown to fail in several cases including linear SEMs in
99 (Aubin et al., 2021). We take a closer look at these failures next.

100 **Understanding the failures: fully informative invariant features vs. partially informative in-**
101 **variant features (FIIF vs. PIIF).** We define properties salient to the datasets/SEMs used in the OOD
102 generalization literature. Each $e \in \mathcal{E}_{all}$, the distribution $(X^e, Y^e) \sim \mathbb{P}^e$ satisfies the following proper-
103 ties. a) $\exists$ a map $\Phi^*$ (linear or not), which we call an *invariant feature map*, such that $\mathbb{E}\big[Y^e|\Phi^*(X^e)\big]$
104 is the same for all $e \in \mathcal{E}_{all}$ and $Y^e \not\perp \Phi^*(X^e)$. These conditions ensure $\Phi^*$ maps to features that
105 have a finite predictive power and have the same optimal predictor across $\mathcal{E}_{all}$. For the SEM in
106 Assumption 1, $\Phi^*$ maps to $Z_{\text{inv}}^e$. b) $\exists$ a map $\Psi^*$ (linear or not), which we call *spurious feature map*,
107 such that $\mathbb{E}\big[Y^e|\Psi^*(X^e)\big]$ is not the same for all $e \in \mathcal{E}_{all}$ and $Y^e \not\perp \Psi^*(X^e)$ for some environments.
108 $\Psi^*$ often creates a hindrance in learning predictors that only rely on $\Phi^*$. Note that $\Psi^*$ should not be a
109 transformation of some $\Phi^*$. For the SEM in Assumption 1, suppose $Z_{\text{spu}}^e$ is anti-causally related to
110 $Y^e$, then $\Psi^*$ maps to $Z_{\text{spu}}^e$ (See Appendix for an example).

111 In the colored MNIST (CMNIST) dataset (Arjovsky et al., 2019), the digits are colored in such a
112 way that in the training domain, color is highly predictive of the digit label but this correlation being
113 spurious breaks down at test time. Suppose the invariant feature map $\Phi^*$ extracts the uncolored digit
114 and the spurious feature map $\Psi^*$ extracts the background color. Ahuja et al. (2021) studied two
115 variations of the colored MNIST dataset, which differed in the way final labels are generated from
116 original MNIST labels (corrupted with noise or not). They showed that the IRM exhibits good OOD
117 generalization (50% improvement over ERM) in anti-causal-CMNIST (AC-CMNIST, original data
118 from Arjovsky et al. (2019)) but is no different from ERM and fails in covariate shift-CMNIST (CS-
119 CMNIST). In AC-CMNIST, the invariant features $\Phi^*(X^e)$ (uncolored digit) are *partially informative*
120 about the label, i.e., $Y \not\perp X^e|\Phi^*(X^e)$, and color contains information about label not contained in the
121 uncolored digit. On the other hand in CS-CMNIST, invariant features are *fully informative* about the
122 label, i.e., $Y \perp X^e|\Phi^*(X^e)$, i.e., they contains all the information about the label that is contained in
123 input $X^e$. Many real image datasets have fully informative invariant features; the labels (digit value)
124 are a deterministic function of the invariant features (uncolored digit) and spurious features (color of
125 the digit) do not affect the label. [2] In Table 2, we divide the different datasets used in the literature

---

[2]The deterministic labelling case was referred as realizable problems in (Arjovsky et al., 2019).

| Fully informative invariant features (FIIF) | Partially informative invariant features (PIIF) |
|---|---|
| $\forall e \in \mathcal{E}_{all}, Y^e \perp X^e | \Phi^*(X^e)$ | $\exists\, e \in \mathcal{E}_{all}\ Y^e \not\perp X^e | \Phi^*(X^e)$ |
| Task: classification | Task: classification or regression |
| Example 2/2S, CS-CMNIST | Example 1/1S, Example 3/3S, AC-CMNIST |
| SEM in Assumption 2 | SEM in Rosenfeld et al. (2021) |
| **ERM and IRM fail** | **ERM fails, IRM succeeds sometimes** |
| Theorem 3,4 (This paper) | Theorem 9, 5.1 (Arjovsky et al., 2019; Rosenfeld et al., 2021) |

Table 2: Categorization of OOD evaluation datasets and SEMs. Example 1/1S, 2/2S, 3/3S from (Aubin et al., 2021), AC-CMNIST(Arjovsky et al., 2019), CS-CMNIST(Ahuja et al., 2021).

based on informativeness of the invariant features. We observe that when the invariant features are fully informative, both IRM and ERM fail but only in classification tasks and not in regression tasks (Ahuja et al., 2021); this is consistent with the linear regression result in Theorem 1, where IRM succeeds regardless of whether $Y^e \perp X^e | Z^e_{\text{inv}}$ holds or not. Motivated by this observation, we take a closer look at the classification tasks where invariant features are fully informative.

## 3 OOD generalization theory for linear classification tasks

**A two-dimensional example with fully informative invariant features.** We start with a 2D classification example (based on Nagarajan et al. (2021)), which can be understood as a simplified version of the CS-CMNIST dataset (Ahuja et al., 2021), Example 2/2S of Aubin et al. (2021), where both IRM and ERM fail. The example goes as follows. In each training environment $e \in \mathcal{E}_{tr}$

$$Y^e \leftarrow \mathsf{I}\left(X^e_{\text{inv}} - \frac{1}{2}\right),\ \text{where } X^e_{\text{inv}} \in \{0,1\} \text{ is Bernoulli}\left(\frac{1}{2}\right),$$

$$X^e_{\text{spu}} \leftarrow X^e_{\text{inv}} \oplus W^e,\ \text{where } W^e \in \{0,1\} \text{ is Bernoulli}\left(1 - p^e\right) \text{ with selection bias } p^e > \frac{1}{2}, \tag{4}$$

where Bernoulli($a$) takes value 1 with probability $a$ and 0 otherwise. Each training environment is characterized by the probability $p^e$. Following Assumption 1, we assume that the labelling function does not change from $\mathcal{E}_{tr}$ to $\mathcal{E}_{all}$, thus the relation between the label and the invariant features does not change. Assume that the distribution of $X^e_{\text{inv}}$ and $X^e_{\text{spu}}$ can change arbitrarily. See Figure 1a) for a pictorial representation of this example illustrating the gist of the problem: there are many classifiers with the same error on $\mathcal{E}_{tr}$ while only the one identical to the labelling function $\mathsf{I}(X^e_{\text{inv}} - \frac{1}{2})$ generalizes correctly OOD. Define a classifier $\mathsf{I}(w_{\text{inv}}x_{\text{inv}} + w_{\text{spu}}x_{\text{spu}} - \frac{1}{2}(w_{\text{inv}} + w_{\text{spu}}))$. Define a set of classifiers $\mathcal{S} = \{(w_{\text{inv}}, w_{\text{spu}}) \text{ s.t. } w_{\text{inv}} > |w_{\text{spu}}|\}$. Observe that all the classifiers in $\mathcal{S}$ achieve a zero classification error on the training environments. However, only classifiers for which $w_{\text{spu}} = 0$ solve the OOD generalization (eq. (1)). With $\Phi$ as the identity, it can be shown that all the classifiers $\mathcal{S}$ form an invariant predictor (satisfy the constraint in equation (3) over all the training environments when $\ell$ is the 0-1 loss). Observe that increasing the number of training environments to infinity does not address the problem, unlike with the linear regression result discussed in Theorem 1 (Arjovsky et al., 2019), where it was shown that if the number of environments increases linearly in the dimension of the data, then the solution to IRM also solves the OOD generalization (eq. (1)). [3] We use the above example to construct general SEMs for linear classification when the invariant features are fully informative. We follow the structure of the SEM from Assumption 1 in our construction.

**Assumption 2.** *Linear classification structural equation model (FIIF). In each $e \in \mathcal{E}_{all}$*

$$Y^e \leftarrow \mathsf{I}\left(w^*_{\text{inv}} \cdot Z^e_{\text{inv}}\right) \oplus N^e, \quad N^e \sim \text{Bernoulli}(q), q < \frac{1}{2}, \quad N^e \perp (Z^e_{\text{inv}}, Z^e_{\text{spu}}),$$

$$X^e \leftarrow S\left(Z^e_{\text{inv}}, Z^e_{\text{spu}}\right), \tag{5}$$

*where $w^*_{\text{inv}} \in \mathbb{R}^m$ with $\|w^*_{\text{inv}}\| = 1$ is the labelling hyperplane, $Z^e_{\text{inv}} \in \mathbb{R}^m$, $Z^e_{\text{spu}} \in \mathbb{R}^o$, $N^e$ is binary noise with identical distribution across environments, $\oplus$ is the XOR operator, $S$ is invertible.*

If noise level $q$ is zero, then the above SEM covers linearly separable problems. See Figure 2a) for the directed acyclic graph (DAG) corresponding to this SEM. From the DAG observe that $Y^e \perp X^e | Z^e_{\text{inv}}$,

---

[3]Please note that this example illustrates certain important facets in a very simple fashion; only in this example a max-margin classifier can solve the problem but not in general. (Further explanation in the Appendix).

Figure 1:   a) 2D classification example illustrating multiple invariant predictors: Most of these predictors rely on spurious features and each of them achieve zero error across all $\mathcal{E}_{tr}$, b) illustration of the impossibility result. If latent invariant features in the training environments are separable, then there are multiple equally good candidates that could have generated the data, and the algorithm cannot distinguish between these.

which implies that the invariant features are fully informative. Contrast this with a DAG that follows Assumption 1 shown in Figure 2b), where $Y^e \not\perp X^e | Z^e_{\text{inv}}$ and thus the invariant features are not fully informative. If $\mathcal{E}_{all}$ follows the SEM in Assumption 2 and suppose the distribution of $Z^e_{\text{inv}}$, $Z^e_{\text{spu}}$ can change arbitrarily, then it can be shown that only a classifier identical to the labelling function $I(w^*_{\text{inv}} \cdot Z^e_{\text{inv}})$ can solve the OOD generalization (eq. (1)); such a classifier achieves an error of $q$ (noise level) in all the environments. As a result, if for a classifier we can find $e \in \mathcal{E}_{all}$ that follows Assumption 2 where the error is greater than $q$, then such a classifier does not solve equation (1). Now we ask – what are the minimal conditions on training environments $\mathcal{E}_{tr}$ to achieve OOD generalization when $\mathcal{E}_{all}$ follow Assumption 2? To achieve OOD generalization for linear regressions, in Theorem 1, it was required that the number of training environments grows linearly in the dimension of the data. However, there was no restriction on the support of the latent invariant and latent spurious features, and they were allowed to change arbitrarily from train to test (for further discussion on this, see the Appendix). Can we continue to work with similar assumptions for the SEM in Assumption 2 and solve the OOD generalization (eq. (1))? We state some assumptions and notations to answer that. Define the support of the invariant (spurious) features $Z^e_{\text{inv}}$ ($Z^e_{\text{spu}}$) in environment $e$ as $\mathcal{Z}^e_{\text{inv}}$ ($\mathcal{Z}^e_{\text{spu}}$).

**Assumption 3.** *Bounded invariant features.* $\cup_{e \in \mathcal{E}_{tr}} \mathcal{Z}^e_{\text{inv}}$ *is a bounded set.*[4]

**Assumption 4.** *Bounded spurious features.* $\cup_{e \in \mathcal{E}_{tr}} \mathcal{Z}^e_{\text{spu}}$ *is a bounded set.*

**Assumption 5.** *Invariant feature support overlap.* $\forall e \in \mathcal{E}_{all}, \mathcal{Z}^e_{\text{inv}} \subseteq \cup_{e' \in \mathcal{E}_{tr}} \mathcal{Z}^{e'}_{\text{inv}}$

**Assumption 6.** *Spurious feature support overlap.* $\forall e \in \mathcal{E}_{all}, \mathcal{Z}^e_{\text{spu}} \subseteq \cup_{e' \in \mathcal{E}_{tr}} \mathcal{Z}^{e'}_{\text{spu}}$

Assumption 5 (6) states that the support of the invariant (spurious) features for unseen environments is the same as the union of the support over the training environments. It is important to note that support overlap does not imply that the distribution over the invariant features does not change. We now define a margin that measures how much the is training support of invariant features $Z^e_{\text{inv}}$ separated by the labelling hyperplane $w^*_{\text{inv}}$. Define $\text{Inv-Margin} = \min_{z \in \cup_{e \in \mathcal{E}_{tr}} \mathcal{Z}^e_{\text{inv}}} \text{sgn}(w^*_{\text{inv}} \cdot z)(w^*_{\text{inv}} \cdot z)$. This margin only coincides with the standard margin in support vector machines when the noise level $q$ is 0 (linearly separable) and $S$ is identity. If $\text{Inv-Margin} > 0$, then the labelling hyperplane $w^*_{\text{inv}}$ separates the support into two halves (see Figure 1b)).

**Assumption 7.** *Strictly separable invariant features.* $\text{Inv-Margin} > 0$.

Next, we show the importance of support overlap for invariant features.

**Theorem 2.** *Impossibility of guaranteed OOD generalization for linear classification. Suppose each $e \in \mathcal{E}_{all}$ follows Assumption 2. If for all the training environments $\mathcal{E}_{tr}$, the latent invariant features are bounded and strictly separable, i.e., Assumption 3 and 7 hold, then every deterministic algorithm fails to solve the OOD generalization (eq. (1)), i.e., for the output of every algorithm $\exists \, e \in \mathcal{E}_{all}$ in which the error exceeds the minimum required value $q$ (noise level).*

The proofs to all the theorems are in the Appendix. We provide a high-level intuiton as to why invariant feature support overlap is crucial to the impossibility result. In Figure 1b), we show that if

---

[4]A set $\mathcal{Z}$ is bounded if $\exists M < \infty$ such that $\forall z \in \mathcal{Z}, \|z\| \leq M$.

the support of latent invariant features are strictly separated by the labelling hyperplane $w_{\mathsf{inv}}^*$, then we can find another valid hyperplane $w_{\mathsf{inv}}^+$ that is equally likely to have generated the same data. There is no algorithm that can distinguish between $w_{\mathsf{inv}}^*$ and $w_{\mathsf{inv}}^+$. As a result, if we use data from the region where the hyperplanes disagree (yellow region Figure 1b)), then the algorithm fails.

**Significance of Theorem 2.** We showed that without the support overlap assumption on the invariant features, OOD generalization is impossible for linear classification tasks. This is in contrast to linear regression in Theorem 1 (Arjovsky et al., 2019), where even in the absence of the support overlap assumption, guaranteed OOD generalization was possible. Applying the above Theorem 2 to the 2D case (eq. (4)) implies that we cannot assume that the support of invariant latent features can change, or else that case is also impossible to solve.

Next, we ask what further assumptions are minimally needed to be able to solve the OOD generalization (eq. (1)). Each classifier can be written as $\bar{w} \cdot X^e = \bar{w} \cdot S(Z_{\mathsf{inv}}^e, Z_{\mathsf{spu}}^e) = \tilde{w}_{\mathsf{inv}} \cdot Z_{\mathsf{inv}}^e + \tilde{w}_{\mathsf{spu}} Z_{\mathsf{spu}}^e$. If $\tilde{w}_{\mathsf{spu}} \neq 0$, then the classifier $\bar{w}$ is said to rely on spurious features.

**Theorem 3.** *Sufficiency and Insufficiency of ERM and IRM. Suppose each $e \in \mathcal{E}_{all}$ follows Assumption 2. Assume that a) the invariant features are strictly separable, bounded, and satisfy support overlap, b) the spurious features are bounded (Assumptions 3-5, 7 hold).*

- *Sufficiency: If the spurious features satisfy support overlap (Assumption 6 holds), then both ERM and IRM solve the OOD generalization problem (eq. (1)). Also, some of the ERM and IRM solutions rely on the spurious features and still achieve OOD generalization.*

- *Insufficiency: If spurious features do not satisfy support overlap, then both ERM and IRM fail at solving the OOD generalization problem (eq. (1)). Also, the classifiers that solve the OOD generalization problem do not rely on spurious features at all.*

**Significance of Theorem 3.** From the first part, we learn that if the support overlap is satisfied for both the invariant features and the spurious features, then either ERM or IRM can solve the OOD generalization (eq. (1)). Interestingly, in this case we can have classifiers that rely on the spurious features and yet solve the OOD generalization (eq. (1)). For the 2D case (eq. (4)) this case implies that the entire set $\mathcal{S}$ solves the OOD generalization (eq. (1)). From the second part, we learn that if support overlap holds for invariant features but not for spurious features, then the ideal OOD optimal predictors rely only on the invariant features. In this case, methods like ERM and IRM continue to rely on spurious features and fail at OOD generalization. For the above 2D case (eq. (4)) this implies that only the predictors that rely only on $X_{\mathsf{inv}}^e$ in the set $\mathcal{S}$ solve the OOD generalization (eq. (1)).

To summarize, we looked at SEMs for classification tasks when invariant features are fully informative, and find that the support overlap assumption over invariant features is necessary. Even in the presence of support overlap for invariant features, we showed that ERM and IRM can easily fail if the support overlap is violated for spurious features. This raises a natural question – Can we even solve the case with the support overlap assumption only on the invariant features? We will now show that the information bottleneck principle can help tackle these cases.

# 4 Information bottleneck principle meets invariance principle

**Why the information bottleneck?** The information bottleneck principle prescribes to learn a representation that compresses the input $X$ as much as possible while preserving all the relevant information about the target label $Y$ (Tishby et al., 2000). Mutual information $I(X; \Phi(X))$ is used to measure information compression. If representation $\Phi(X)$ is a deterministic transformation of $X$, then in principle we can use the entropy of $\Phi(X)$ to measure compression (Kirsch et al., 2020). Let us revisit the 2D case (eq. (4)) and apply this principle to it. Following the second part of Theorem 3, where ERM and IRM failed, assume that invariant features satisfy the support overlap assumption, but make no such assumption for the spurious features. Consider three choices for $\Phi$: identity (selects both features), selects invariant feature only, selects spurious feature only. The entropy of $H(\Phi(X^e))$ when $\Phi$ is the identity is $H(p^e) + \log(2)$, where $H(p^e)$ is the Shannon entropy in Bernoulli$(p^e)$. If $\Phi$ selects the invariant/spurious features only, then $H(\Phi(X^e)) = \log(2)$. Among all three choices, the one that has least entropy and also achieves zero error is the representation that focuses on invariant feature. We could find the OOD optimal predictor in this example just by using information bottleneck. Does it mean the invariance principle isn't needed? We answer this next.

**Why invariance?** Consider a simple classification SEM. In each $e \in \mathcal{E}_{tr}$, $Y^e \leftarrow X_{\mathsf{inv}}^{1,e} \oplus X_{\mathsf{inv}}^{2,e} \oplus N^e$ and $X_{\mathsf{spu}}^e \leftarrow Y^e \oplus V^e$, where all the random variables involved are binary valued, noise $N^e, V^e$

(a) FIIF (this work)   (b) PIIF (Arjovsky et al., 2019)   (c) PIIF (Rosenfeld et al., 2021)

Figure 2: Comparison of the DAG from Assumption 2 (fully informative invariant features) vs. DAGs from Rosenfeld et al. (2021); Arjovsky et al. (2019) (partially informative invariant features).

are Bernoulli with parameters $q$ (identical across $\mathcal{E}_{tr}$), $c^e$ (varies across $\mathcal{E}_{tr}$) respectively. If $c^e < q$, then in $\mathcal{E}_{tr}$ predictions based on $X_{\mathsf{spu}}^e$ are better than predictions based on $X_{\mathsf{inv}}^{1,e}, X_{\mathsf{inv}}^{2,e}$. If both $X_{\mathsf{inv}}^{1,e}, X_{\mathsf{inv}}^{2,e}$ are uniform Bernoulli, then these features have a higher entropy than $X_{\mathsf{spu}}^e$. In this case, the information bottleneck would bar using $X_{\mathsf{inv}}^{1,e}, X_{\mathsf{inv}}^{2,e}$. Instead, we want the model to focus on $X_{\mathsf{inv}}^{1,e}$, $X_{\mathsf{inv}}^{2,e}$ and not on $X_{\mathsf{spu}}^e$. Invariance constraints encourage the model to focus on $X_{\mathsf{inv}}^{1,e}, X_{\mathsf{inv}}^{2,e}$. In this example, observe that invariant features are partially informative unlike the 2D case (eq. (4)).

**Why invariance and information bottleneck?** We have illustrated through simple examples when the information bottleneck is needed but not invariance and vice-versa. We now provide a simple example where both these constraints are needed at the same time. This example combines the 2D case (eq. (4)) and the example we highlighted in the paragraph above: $Y^e \leftarrow X_{\mathsf{inv}}^e \oplus N^e$, $X_{\mathsf{spu}}^{1,e} \leftarrow X_{\mathsf{inv}}^e \oplus W^e$, and $X_{\mathsf{spu}}^{2,e} \leftarrow Y^e \oplus V^e$. In this case, the invariance constraint does not allow representations that use $X_{\mathsf{spu}}^{2,e}$ but does not prohibit representations that rely on $X_{\mathsf{spu}}^{1,e}$. However, information bottleneck constraints on top ensure that representations that only use $X_{\mathsf{inv}}^e$ are used. We now describe an objective that combines both these principles:

$$\min_{w,\Phi} \sum_{e \in \mathcal{E}_{tr}} h^e\big(w \cdot \Phi\big) \quad \text{s.t.} \ \frac{1}{|\mathcal{E}_{tr}|} \sum_{e \in \mathcal{E}_{tr}} R^e\big(w \cdot \Phi\big) \le r^{\mathsf{th}}, \ w \in \arg\min_{\tilde{w} \in \mathbb{R}^{k \times r}} R^e(\tilde{w} \cdot \Phi), \forall e \in \mathcal{E}_{tr}, \ (6)$$

where $h^e$ in the above is a lower bounded differential entropy defined below and $r^{\mathsf{th}}$ is the threshold on the average risk. Typical information bottleneck based optimization in neural networks involves minimization of the entropy of the representation output from a certain hidden layer. For both analytical convenience and also because the above setup is a linear model, we work with the simplest form of bottleneck which directly minimizes the entropy of the output layer. Recall the definition of differential entropy of a random variable $X$, $h(X) = -\mathbb{E}_X[\log d\mathbb{P}_X]$ and $d\mathbb{P}_X$ is the Radon-Nikodym derivative of $\mathbb{P}_X$ with respect to Lebesgue measure. Because in general differential entropy has no lower bound, we add a small independent noise term $\zeta$ (Kirsch et al., 2020) to the classifier to ensure that the entropy is bounded below. We call the above optimization information bottleneck based invariant risk minimization (IB-IRM). In summary, *among all the highly predictive invariant predictors we pick the ones that have the least entropy*. If we drop the invariance constraint from the above optimization, we get information bottleneck based empirical risk minimization (IB-ERM). In the above formulation and following result, we assume that $X^e$ are continuous random variables; the results continue to hold for discrete $X^e$ as well (See Appendix for details).

**Theorem 4.** *IB-IRM and IB-ERM vs IRM and ERM*

● *Fully informative invariant features (FIIF). Suppose each $e \in \mathcal{E}_{all}$ follows Assumption 2. Assume that the invariant features are separable, bounded, and satisfy support overlap (Assumptions 3,5 and 7 hold). Also, for each $e \in \mathcal{E}_{tr}$ $Z_{\mathsf{spu}}^e \leftarrow AZ_{\mathsf{inv}}^e + W^e$, where $A \in \mathbb{R}^{o \times m}$, $W^e \in \mathbb{R}^o$ is continuous, bounded, and zero mean noise. Each solution to IB-IRM (eq. (6), with $\ell$ as 0-1 loss, and $r^{\mathsf{th}} = q$), and IB-ERM solves the OOD generalization (eq. (1)) but ERM and IRM (eq.(3)) fail.*

● *Partially informative invariant features (PIIF). Suppose each $e \in \mathcal{E}_{all}$ follows Assumption 1 and $\exists\, e \in \mathcal{E}_{tr}$ such that $\mathbb{E}[\epsilon^e Z_{\mathsf{spu}}^e] \ne 0$. If $|\mathcal{E}_{tr}| > 2d$ and the set $\mathcal{E}_{tr}$ lies in a linear general position (a mild condition defined in the Appendix), then each solution to IB-IRM (eq. (6), with $\ell$ as square loss, $\sigma_\epsilon^2 < r^{\mathsf{th}} \le \sigma_Y^2$, where $\sigma_Y^2$ and $\sigma_\epsilon^2$ are the variance in the label and noise across $\mathcal{E}_{tr}$) and IRM (eq.(3)) solves OOD generalization (eq. (1)) but IB-ERM and ERM fail.*

**Significance of Theorem 4 and remarks.** In the first part (FIIF), IB-ERM and IB-IRM succeed without assuming support overlap for the spurious features, which was crucial for success of ERM

289 and IRM in Theorem 3. Observe that when invariant features are fully informative, IB-ERM and
290 IB-IRM succeed, but when invariant features are partially informative IB-IRM and IRM succeed. In
291 real data settings, we do not know if the invariant features are fully or partially informative. Since
292 IB-IRM is the only common winner in both the settings, it would be pragmatic to use it in the absence
293 of domain knowledge about the informativeness of the invariant features. In the paragraph preceding
294 the objective in equation (6), we discussed examples where both the IB and IRM constraints were
295 needed at the same time. In the Appendix, we generalize that example and show that if we change the
296 assumptions in linear classification SEM in Assumption 2 such that the invariant features are partially
297 informative, then we see the joint benefit of IB and IRM constraints. At this point, it is also worth
298 pointing to a result in Rosenfeld et al. (2021), which focused on linear classification SEMs (DAG
299 shown in Figure 2c) with partially informative invariant features. Under the assumption of complete
300 support overlap for spurious and invariant features, authors showed IRM succeeds.

## 4.1 Proposed approach

We take the three terms from the optimization in equation (6) and create a weighted combination as

$$\sum_e \Big( R^e(\Phi) + \lambda \|\nabla_{w,w=1.0} R^e(w \cdot \Phi)\|^2 + \nu h^e(\Phi) \Big) \leq \sum_e \Big( R^e(\Phi) + \lambda \|\nabla_{w,w=1.0} R^e(w \cdot \Phi)\|^2 + \nu h(\Phi) \Big).$$

303 In the LHS above, the first term corresponds to the risks across environments, the
304 second term approximates invariance constraint (follows the IRMv1 objective (Arjovsky
305 et al., 2019)), and the third term is the entropy of the classifier in each environment.

306 In the RHS, $h(\Phi)$ is the entropy of $\Phi$ unconditional on the environ-
307 ment (the entropy on the left-hand side is entropy conditional on
308 the environment assuming all the environments are equally likely).
309 Optimizing over differential entropy is not easy, and thus we re-
310 sort to minimizing an upper bound of it (Kirsch et al., 2020). We
311 use the standard result that among all continuous random variables
312 with same variance, Gaussian has the maximum differential entropy.
313 Since the entropy of a Gaussian increases with its variance, we use
314 the variance of $\Phi$ instead of the differential entropy (For further
315 details see the Appendix). Our final objective is given as

$$\sum_e \Big( R^e(\Phi) + \lambda \|\nabla_{w,w=1.0} R^e(w \cdot \Phi)\|^2 + \gamma \mathsf{Var}(\Phi) \Big). \quad (7)$$

Figure 3: Comparing conver-
gence of $\frac{|w_{\mathsf{spu}}|}{\sqrt{w_{\mathsf{spu}}^2 + w_{\mathsf{inf}}^2}}$ (metric from
Nagarajan et al. (2021)) for aver-
age selection bias $p = 0.9$.

**On the behavior of gradient descent with and without informa-**
317 **tion bottleneck.** In the entire discussion so far, we have focused on ensuring that the set of optimal
318 solutions to the desired objective (IB-IRM, IB-ERM, etc.) correspond to the solutions of the OOD
319 generalization problem (eq. (1)). In some simple cases, such as the 2D case (eq. (4)), it can be shown
320 that gradient descent is biased towards selecting the ideal classifier (Soudry et al., 2018; Nagarajan
321 et al., 2021). Even though gradient descent can eventually learn the ideal classifier that only relies on
322 the invariant features, training is frustratingly slow as was shown by Nagarajan et al. (2021). In the
323 next theorem, we characterize the impact of using IB penalty ($\mathsf{Var}(\Phi)$) in the 2D example (eq. (4)).
324 We compare the methods in terms of $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}|$ used in Nagarajan et al. (2021); $w_{\mathsf{spu}}(t)$ and $w_{\mathsf{inv}}(t)$ are
325 the weights for the spurious feature and the invariant feature at time $t$ of training (assuming training
326 happens with continuous time gradient descent).

327 **Theorem 5.** *Impact of IB on learning speed. Suppose each $e \in \mathcal{E}_{tr}$ follows the 2D case from*
328 *equation (4). Set $\lambda = 0$, $\gamma > 0$ in equation (7) to get the IB-ERM objective with $\ell$ as exponential loss.*
329 *Continuous-time gradient descent on this IB-ERM objective achieves $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}| \leq \epsilon$ in time less than*
330 $\frac{W_0(\frac{1}{2\gamma})}{2(1-p)\epsilon}$ *($W_0(\cdot)$ denotes the principal branch of the Lambert W function), while in the same time the*
331 *ratio for ERM $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}| \geq \ln(\frac{1+2p}{3-2p})/\ln \big(1 + \frac{W_0(\frac{1}{2\gamma})}{2(1-p)\epsilon}\big)$, where $p = \frac{1}{|\mathcal{E}_{tr}|} \sum_{e \in \mathcal{E}_{tr}} p^e$.*

332 $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}|$ converges to zero for both methods but it converges much faster for IB-ERM (for $p = 0.9, \epsilon =$
333 $0.001, \gamma = 0.58$, the ratio for IB-ERM is $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}| \leq 0.001$ and ratio for ERM is $|\frac{w_{\mathsf{spu}}(t)}{w_{\mathsf{inv}}(t)}| \geq 0.09$). In
334 the above theorem, we analyzed the impact of information bottleneck only. The convergence analysis
335 for both the penalties jointly comes with its own challenges, and we hope to explore this in future
336 work. However, we carried out experiments with gradient descent on all the objectives for the 2D
337 example (eq. (4)). See Figure 3 for the comparisons.

| | #Envs | ERM | IB-ERM | IRM | IB-IRM |
|---|---|---|---|---|---|
| Example1 | 3 | $13.36 \pm 1.49$ | $12.96 \pm 1.30$ | $11.15 \pm 0.71$ | $11.68 \pm 0.90$ |
| Example1s | 3 | $13.33 \pm 1.49$ | $12.92 \pm 1.30$ | $11.07 \pm 0.68$ | $11.74 \pm 1.03$ |
| Example2 | 3 | $0.42 \pm 0.01$ | $0.00 \pm 0.00$ | $0.45 \pm 0.00$ | $0.00 \pm 0.00$ |
| Example2s | 3 | $0.45 \pm 0.01$ | $0.00 \pm 0.01$ | $0.45 \pm 0.01$ | $0.06 \pm 0.12$ |
| Example3 | 3 | $0.48 \pm 0.07$ | $0.49 \pm 0.06$ | $0.48 \pm 0.07$ | $0.48 \pm 0.07$ |
| Example3s | 3 | $0.49 \pm 0.06$ | $0.49 \pm 0.06$ | $0.49 \pm 0.07$ | $0.49 \pm 0.07$ |
| Example1 | 6 | $33.74 \pm 60.18$ | $32.03 \pm 57.05$ | $23.04 \pm 40.64$ | $25.66 \pm 45.96$ |
| Example1s | 6 | $33.62 \pm 59.80$ | $31.92 \pm 56.70$ | $22.92 \pm 40.60$ | $25.60 \pm 45.62$ |
| Example2 | 6 | $0.37 \pm 0.06$ | $0.02 \pm 0.05$ | $0.46 \pm 0.01$ | $0.43 \pm 0.11$ |
| Example2s | 6 | $0.46 \pm 0.01$ | $0.02 \pm 0.06$ | $0.46 \pm 0.01$ | $0.45 \pm 0.10$ |
| Example3 | 6 | $0.33 \pm 0.18$ | $0.26 \pm 0.20$ | $0.14 \pm 0.18$ | $0.19 \pm 0.19$ |
| Example3s | 6 | $0.36 \pm 0.19$ | $0.27 \pm 0.20$ | $0.14 \pm 0.18$ | $0.19 \pm 0.19$ |

Table 3: Comparisons on linear unit tests in terms of mean square error (regression) and classification error (classification). "#Envs" means the number of training environments.

| | ERM | IB-ERM | IRM | IB-IRM |
|---|---|---|---|---|
| CS-CMNIST | $60.27 \pm 1.21$ | $71.80 \pm 0.69$ | $61.49 \pm 1.45$ | $71.79 \pm 0.70$ |
| AC-CMNIST | $16.84 \pm 0.82$ | $50.24 \pm 0.47$ | $66.98 \pm 1.65$ | $67.67 \pm 1.78$ |

Table 4: Classification accuracy comparisons on colored MNISTs.

## 5 Experiments

**Methods, datasets & metrics.** We compare our approaches – information bottleneck based ERM (IB-ERM) and information bottleneck based IRM (IB-IRM) with ERM and IRM. We use all the datasets in Table 2. We follow the same protocol for tuning hyperparameters from Aubin et al. (2021); Arjovsky et al. (2019) for their respective datasets (see the Appendix for more details). As is reported in literature, for Example 2/2S, Example 3/3S we use classification error and for AC-CMNIST, CS-CMNIST we use accuracy. For Example 1/1S, we use mean square error.

**Summary of results.** In Table 3, we provide a comparison of methods for different examples in linear unit tests (Aubin et al., 2021) for three and six training environments. In Table 4, we provide a comparison of the methods for different CMNIST datasets. Based on our Theorem 4, we do not expect ERM and IB-ERM to do well on Example 1/1S, Example 3/3S and AC-CMNIST as these datasets fall in the PIIF category, i.e, the invariant features are partially informative. On these examples, we find that IRM and IB-IRM do better than ERM and IB-ERM (for Example 3/3S when there are three environments all methods perform poorly). Based on our Theorem 4, we do not expect IRM and ERM to do well on Example 2/2S and CS-CMNIST as these datasets fall in the FIIF category, i.e., the invariant features are fully informative. On these examples, we find that IB-ERM always performs well (close to oracle), IB-IRM also performs well (except for the case of six environments for Example 2). In summary, IB-IRM fairs consistently in both FIIF and PIIF settings and should be preferred in the absence of knowledge of whether the invariant features are fully or partially informative.

## 6 Conclusion, limitations & future work

In this work, we revisited the fundamental assumptions for OOD generalization. We showed how linear classification tasks are different and need much stronger assumptions than linear regression tasks. We also showed that when invariant features carry all the information about the label, invariance principle is insufficient. We prove that a form of the information bottleneck constraint along with invariance goes a long way in overcoming the failures while retaining the existing provable guarantees.

**Limitations and future work.** In recent works (Rosenfeld et al., 2021; Kamath et al., 2021; Gulrajani and Lopez-Paz, 2021), there has been criticism of different aspects of IRM, e.g., failure of IRMv1 penalty in non-linear models, the tuning of IRMv1 penalty, etc.. Since we use IRMv1 penalty in our proposed loss, these criticisms apply to our objective as well. Building a better objective function to capture invariance is important and an interesting future work. Our work mainly focused on linear models; recently, Rosenfeld et al. (2021) have pointed out to the challenges that IRM faces for non-linear models. We believe this is a fruitful avenue for future work and we present our perspective on this extension and the concerned related works (Lu et al., 2021) in the Appendix.

## References

Ahuja, K., Wang, J., Dhurandhar, A., Shanmugam, K., and Varshney, K. R. (2021). Empirical or invariant risk minimization? a sample complexity perspective. In *International Conference on Learning Representations*.

Arjovsky, M., Bottou, L., Gulrajani, I., and Lopez-Paz, D. (2019). Invariant risk minimization. *arXiv preprint arXiv:1907.02893*.

Aubin, B., Słowik, A., Arjovsky, M., Bottou, L., and Lopez-Paz, D. (2021). Linear unit-tests for invariance discovery. *arXiv preprint arXiv:2102.10867*.

Beery, S., Van Horn, G., and Perona, P. (2018). Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision*, pages 456–473.

DeGrave, A. J., Janizek, J. D., and Lee, S.-I. (2020). AI for radiographic COVID-19 detection selects shortcuts over signal. *medRxiv*.

Geirhos, R., Jacobsen, J.-H., Michaelis, C., Zemel, R., Brendel, W., Bethge, M., and Wichmann, F. A. (2020). Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673.

Gulrajani, I. and Lopez-Paz, D. (2021). In search of lost domain generalization. In *International Conference on Learning Representations*.

Kamath, P., Tangella, A., Sutherland, D. J., and Srebro, N. (2021). Does invariant risk minimization capture invariance? *arXiv preprint arXiv:2101.01134*.

Kirsch, A., Lyle, C., and Gal, Y. (2020). Unpacking information bottlenecks: Unifying information-theoretic objectives in deep learning. *arXiv preprint arXiv:2003.12537*.

Koyama, M. and Yamaguchi, S. (2020). Out-of-distribution generalization with maximal invariant predictor. *arXiv preprint arXiv:2008.01883*.

Krueger, D., Caballero, E., Jacobsen, J.-H., Zhang, A., Binas, J., Zhang, D., Priol, R. L., and Courville, A. (2020). Out-of-distribution generalization via risk extrapolation (rex). *arXiv preprint arXiv:2003.00688*.

Lu, C., Wu, Y., Hernández-Lobato, J. M., and Schölkopf, B. (2021). Nonlinear invariant risk minimization: A causal approach. *arXiv preprint arXiv:2102.12353*.

Nagarajan, V., Andreassen, A., and Neyshabur, B. (2021). Understanding the failure modes of out-of-distribution generalization. In *International Conference on Learning Representations*.

Parascandolo, G., Neitz, A., ORVIETO, A., Gresele, L., and Schölkopf, B. (2021). Learning explanations that are hard to vary. In *International Conference on Learning Representations*.

Pearl, J. (1995). Causal diagrams for empirical research. *Biometrika*, 82(4):669–688.

Peters, J., Bühlmann, P., and Meinshausen, N. (2015). Causal inference using invariant prediction: identification and confidence intervals. *arXiv preprint arXiv:1501.01332*.

Pezeshki, M., Kaba, S.-O., Bengio, Y., Courville, A., Precup, D., and Lajoie, G. (2020). Gradient starvation: A learning proclivity in neural networks. *arXiv preprint arXiv:2011.09468*.

Robey, A., Pappas, G. J., and Hassani, H. (2021). Model-based domain generalization. *arXiv preprint arXiv:2102.11436*.

Rojas-Carulla, M., Schölkopf, B., Turner, R., and Peters, J. (2018). Invariant models for causal transfer learning. *The Journal of Machine Learning Research*, 19(1):1309–1342.

Rosenfeld, E., Ravikumar, P. K., and Risteski, A. (2021). The risks of invariant risk minimization. In *International Conference on Learning Representations*.

Soudry, D., Hoffer, E., Nacson, M. S., Gunasekar, S., and Srebro, N. (2018). The implicit bias of gradient descent on separable data. *The Journal of Machine Learning Research*, 19(1):2822–2878.

Tishby, N., Pereira, F. C., and Bialek, W. (2000). The information bottleneck method. *arXiv preprint physics/0004057*.

Vapnik, V. (1992). Principles of risk minimization for learning theory. In *Advances in neural information processing systems*, pages 831–838.