Exploring Biases in Facial Expression Analysis

Abstract

Automated facial expression recognition is useful for many applications, but models are often subject to racial biases. These racial biases may be hard to reveal due to the complexity and opacity of the complex networks needed for state-of-the-art performance. Racial biases are also hard to demonstrate due to the inability to fully match facial expressions across real people. In this paper we use artificially created faces where facial expression can be carefully manipulated and matched across artificial faces with different skin colors and different facial shapes. We show that several public facial expression models appear to have a racial bias. In future work, we will work towards using the artificial data to help understand the basis of these biases and remove them from facial expression models.

1   Introduction

Automated facial expression recognition (FER) is useful for many applications including monitoring: student engagement and boredom, consumer interest and happiness, customer distress, and pain levels in patients who are unable to communicate either due to age, motor disabilities, or cognitive state.

It is important that recognition of facial expressions be fair and consistent in recognizing expressions in people of different races and skin colors. One challenge in achieving model fairness in deep learning FER models is the complexity of deep learning processes. Due to the black-box nature of deep learning models, it is difficult to understand how the FER models digest and interpret facial features to score emotion. Therefore, researchers often struggle to identify the weaknesses of FER models that prompt disparate performance due to racial biases. Such biases may arise due to the under-representation of specific populations or due to difficulties in detecting relevant features like different skin color or facial features.

Another challenge in achieving model fairness is the difficulty of obtaining facial expression datasets with sufficient quality, quantity, and diversity. The traditional means of obtaining data for facial expression datasets is expensive and cumbersome. Also, when using pictures or videos of real people making either natural or posed facial expressions, it is not possible to exactly control all aspects to ensure, for example, that a White face is making exactly the same expression (and thus should be scored in the same way) as a Black face.

Recently, Fabi et al. [5] used artificially generated faces to explore racial bias in pain-related facial expressions in a specific computer vision pain-estimation model. They revealed that, while the network was able to recognize largely monotonic increases in activation of facial muscles, they were subject to different offset biases, and gains for different skin colors and races.

In this work, we generate and use new artificially generated faces made by the FaceGen Modeller as a means to explore racial biases in several publicly available computer vision facial expression models. The advantages of synthetic face images are that we can control facial parameters (such as race, action unit activation, gender, skin color, texture), holding all others constant to isolate how different manipulations affect the different models. This work will serve as a careful elucidation of

the problem and some of the dependencies which will enable future work towards removing these biases from these and other facial expression models. This work may also help inform any sensory components to human bias in FER when observing people of color.

2 Methods

In this section, we describe our synthetic face dataset and explore what results facial expression models produce with controlled manipulations to race, facial action units, and skin texture.

2.1 FaceGen Synthetic Image Dataset

Our work uses artificially generated facial images made through the FaceGen Modeller software. FaceGen Modeller is a programming tool that can generate synthetic faces based on different manipulations you provide such as race, action unit activation level, gender, texture, etc. Our dataset consists of four sets of "races": "European", "European features with dark skin color" or "European Black", "African", and "African features with light skin color" or "African White". We used the FaceGen Modeller to generate random male faces with random skin textures from arbitrary racial backgrounds. For the original "African" and "European" faces, we did not change any parameters under the category "modify". For the other two sets, the skin shade of the faces were set between 2.5 (lighten) to -3.0 (darken). For the set of "European Black", we take each European face and set the skin shade parameter towards -3 and made it as natural as possible. Similarly, for the set of "African White", we take each African face and set the skin shade parameter toward 2.5 and made it as natural as possible. "African White" and "European Black" are thus two artificial categories we created to observe how coloring alone (with no change in face shape) affected the models. For the remainder of the paper, we refer to the four categories as "races".

The expressions of the synthetic faces were constructed via manipulating the facial action unit (AU) activation levels. The Facial Action Coding System (FACS) [4] codified the facial action units (AU) as facial muscles that would be anatomically representative for expressing emotion; hereon referred as AUs. After modifying the races and colors, we manipulated the facial expression with ten AUs (4: Brow Lowerer, 6: Cheek Raiser, 7: Lid Tightener, 9: Nose Wrinkler, 10: Upper Lip Raiser, 12: Lip Corner Puller, 20: Lip stretcher, 25: Lips part, 26: Jaw Drop, 43: Eyes Closed), and the AUs being activated to six levels (0%, 20%, 40%, 60%, 80%, 100%) separately (except for AU43: Eyes Closed which could only be set to 0% and 100%). This step was applied to the four racial sets as we mentioned earlier, leading to 224 images in total. Fig.1 shows rows of synthetic faces set with the same expressions, except having differing facial morphologies and skin color.

Figure 1: Synthetic face images used for experimental evaluations. Each row shows the same expression for each of African, African White, European, and European Black. (First row) The row displays African, African White, European, and European Black face settings respectively. This row involves the activation of AU7: Lid Tightener (100% activation) with rest of the AU activations to be set at 0%. (Second row) In this row AU10: Upper Lip Raiser is activated to 100% for all face settings. (Third row) In this row AU25: Lips part is activated to 100% for all face settings. (Fourth row) In this row AU26: Jaw Drop is activated to 100% for all face settings.

2.2 Extended MTL Model for Pain-Estimation

This model, followed on the work of [5], is the extended multi-task machine learning pain estimation neural network of Xu et al. [12], referred as the Pain-Estimation model from here onward . This model was trained and evaluated on the UNBC-McMaster Shoulder Pain dataset [7]. The UNBC-McMaster dataset is publicly available and comprises of 200 face videos from 25 patients with shoulder pain as they performed movements of their shoulder resulting in differing levels of pain. From these videos, each frame was labelled with 11 facial action unit (AU) intensities, and a corresponding PSPI value, and 66 AAM landmarks. The PSPI score [10] is a pain metric computed from a distinct set of AU intensities that are pain-related. The first of this three-staged model is a VGGFace network [9] pre-trained on classifying 2622 faces of celebrity icons, most of which are racially white. This network was then additionally trained on the UNBC-McMaster Shoulder Pain dataset to detect pain-related AUs (4, 6, 7, 10, 12, 20, 25, 26, 43) and the PSPI intensity of a facial image. The second stage was a fully connected neural network to predict sequence-level/video pain scores from the PSPI predictions of the first stage. The third stage combined these pain scores to output a final Visual Analog Scale value (VAS). This model is publicly available. Our experiments only utilize the first stage of this model.

2.3 Multi-task EfficientNet-B2 Emotion Classification

The second model evaluated, Multi-task EfficientNet-B2, follows the work of [11] on the emotion and engagement classification in an online learning setting. This state-of-the-art model follows a two-stage training structure of pre-training on face detection and fine-tuning on emotion classification. The face detection stage of this model is a pre-trained VGGFace network and uses tracking & clustering techniques to extract facial sequences. Then, the model is fine-tuned on the largest publicly available facial emotion dataset, AffectNet [8] - a collection of 287,651 images annotated with eight basic emotions (anger, contempt, disgust, fear, happiness, neutral, sadness, and surprise). We included this model in our evaluation because it achieved the greatest performance for facial emotion recognition on AffectNet, obtaining the highest known accuracy on both 8-emotion and 7-emotion classification. This model is publicly available.

2.4 Intel OpenVINO Emotion Recognition

Intel's Open Visual Inference and Neural Network Optimization (OpenVINO) library is a series of toolkits that provides effective deep learning neural networks on various tasks such as object, detection, segmentation, and estimation [1]. Their emotion recognition model performs on top of their underlying face detection model which produces coordinates over the bounding box surrounding the detected face. The underlying network features a MobileNet backbone [6] that utilizes depthwise separable convolutions as a measure for running neural networks efficiently on mobile devices. The emotion recognition has been trained and evaluated with only five emotions ('Neutral', 'Happy', 'Sad', 'Surprise', 'Anger') from the AffectNet dataset. The architecture of the emotion recognition model is that of a fully connected neural network that outputs a softmax probability across the five emotions detected. This model was able to achieve a 70.2% on the AffectNet valuation set. This model is publicly available.

3 Experiments

3.1 Experiment 1: Racial biases in facial action unit estimation.

Synthetic image transformations for AU estimation evaluation. In this experiment, we explored the task of facial action unit estimation on the synthetic face dataset we generated. For evaluating on the Pain-Estimation model [12], we utilize the MTCNN (multitask CNN) [13] face detector to detect the faces off the synthetic images. This aspect was troublesome for the dark-skinned faces as it would sometimes not detect them at all, or mistake the facial bounding box coordinates; unlike the correct detections made on the light-skinned faces. In order to mitigate this issue, we cropped the dark-skinned faces with the complementing light-skinned face bounding box coordinates. The bounding box surrounding the detected face is extended by a factor of 0.3 before cropping. The input images are reshaped to 256×256, center-cropped to 224×224 and their color channels were adjusted to that of the VGGFace network.

A bias in dark-skinned vs light-skinned face AU activation estimation is prevalent. For the nine AU estimations that are considered in the Pain-Estimation model, we sampled facial images with those specific AUs being manipulated, across the four sets of races mentioned earlier. We ran model inference on those images and explored performance disparities between these racially diverse faces on AU estimation. We then analyzed the results by running paired t-tests based on skin color and/or racial background. Table 1 provides results on the test-statistics and p-values returned for faces with the same facial textures, but differing skin colors. These statistics are used to test for AU estimation inequalities in faces that only differ by color. For AU20, AU25, and AU43, we observe $p>0.05$, indicating that the Pain-Estimation model did not produce different activation estimations in African vs. African-White faces (AU20: ($t=1.59$, $p=0.1728$), AU25: ($t=-0.71$, $p=0.5075$), AU43: ($t=1.853e-3$, $p=0.9988$)). Similarly, AU4 and AU43 showed no significant differences in AU activations for European vs European-Black faces (AU4: ($t=-0.71$, $p=0.5117$, AU43: ($t=-0.71$, $p=0.6062$)). However, the other AUs demonstrated disparate predictions between dark-skinned and light-skinned versions of the same faces. For example, in Fig.2, the model produced higher AU6 and AU10 activations for African faces than the African-White faces. Despite the fact that the facial morphologies in the African/African-White faces were the same, the sole manipulation of skin color resulted in disparate performance, revealing a color bias during AU activation estimation within the model.

Paired t-test on AU activation estimations				
	African vs. African-White		European vs. European-Black	
Action Unit	test stat.	p-value	test stat.	p-value
4	-6.94	9.5077e-4	-0.71	0.511713
6	99.48	1.9460e-9	-4.52	0.0062
7	-9.73	1.9441e-4	12.13	0.000067
10	7.21	7.9851e-4	-5.62	0.0024
12	13.83	3.5373e-5	2.94	0.0322
20	1.59	0.1728	17.86	0.000010
25	-0.71	0.5075	18.15	0.000009
26	-5.18	3.5034e-3	-2.73	0.0413
43	1.853e-3	0.9988	-0.71	0.6062

Table 1: Paired t-tests on AU activation estimations made by the Pain-Estimation model. Each test was based on the model's evaluations on the individual AU manipulations (on the right column) with respect to the four racial sets.

Figure 2: Histograms comparing the percentages of predicted AU estimation distribution in the Pain-Estimation model. Each predicted AU plot distribution pertains to the model's AU activation predictions for the synthetic images that had that AU manipulated. Each plot confides the AU estimation predictions being made to the 4 sets of racially diverse images - African (Blue)/African-White (Red)/European (Orange)/European-Black (Green).

3.2 Experiment 2: Racial biases in facial emotion classification.

Synthetic image transformations for emotion classification evaluation.

In this experiment, we explored the bias of several facial emotion recognition models using the same synthetic dataset as Experiment 1. During model inference on the Multi-task EfficientNet-B2 model, the input images are represented in RGB format, cropped to 224×224, and normalized with ImageNet [2] mean and standard deviation values. For evaluation on the Intel OpenVINO emotion recognition model, the synthetic images were resized to 64×64 and their color channel orders are ordered in BGR format.

Classification intensities showed polarizing biases between negative and positive emotions. The Multi-task EfficientNet-B2 emotion classification model was evaluated on the entire synthetic face dataset and showed a greater bias surrounding negative emotion classification, than positive. Fig.3 (Top) shows that the predicted emotion intensities vary with the skin colors. We also see that the face morphologies of the synthetic faces impact the emotion intensities as well. The "disgust" emotions rated higher intensities for African-White faces than European faces. Although both subsets had similar skin colors, their differing facial morphologies prompted differences in emotion intensity predictions. On the other hand, European and African-White faces exhibited higher "fear" intensities than the African and European-black counterparts.

To delve deeper into the bias with negative emotion classification, we evaluated the model on faces that had 0% activations across all AUs for "disgust", "contempt", "fear", "sadness", and "anger" emotions. As shown in Fig.3 (Bottom), the African-White faces conveyed higher "disgust" intensities as compared to the African faces showing a clear color bias; however, the European and European-Black faces were seen to be having similar intensities on "disgust" and "sadness". Another case of color bias is also seen in "fear" where European and African-White faces yield higher intensity.

Figure 3: (Top) State-of-the-art AffectNet model (Multi-task EfficientNet-B2) performance on emotion intensity classification on the synthetic face dataset across all racial sets and AU activation manipulations. The emotions received are "anger", "contempt", "disgust", "fear", "happiness", "sadness", "neutral", and "surprise". The intensities range from (0%-100%). (Bottom) Histograms reflecting the Multi-task EfficientNet-B2's predictions on synthetic faces that had 0% activations on all AUs. These histograms are to show the effect over the four sets of racial backgrounds, across the negative emotions of "disgust", "contempt", "fear", "sadness", and "anger".

Similar color biases can be seen in the OpenVINO emotion recognition model - in which disparities amongst negative and positive emotion intensities are exhibited. Fig.4 shows the probability distribution across the "happy" (positive) and "sad" (negative) emotions being represented from the synthetic faces which had 0% activations over all its AUs. After running a paired t-test on this experiment (Table 2), we discovered that the p-values for the "happy" emotion was varied between African vs. African-White and European vs. European-Black faces. For "happy", the African-White faces had higher intensity than African (t=-5.90, p=0.0002), while there was lesser of a disparity between European and European-Black faces (t=-2.06, p=0.0696). Additionally, African-White faces had high intensity values in comparison to the African faces on the "sad" emotion. Further analysis of the OpenVINO model can be seen in the Supplementary Material section.

Figure 4: Histogram plots showing OpenVINO's performance on emotion intensity classification on the synthetic faces that had 0% activations over all AUs.

Paired t-test on emotion intensity prediction				
	African vs. African-White		European vs. European-Black	
Emotion	test stat.	p-value	test stat.	p-value
Neutral	8.74	0.000011	-2.92	0.0169
Happy	-5.90	0.0002	-2.06	0.0696
Sad	-3.27	0.0096	1.28	0.2299
Surprise	0.76	0.4625	1.03	0.3305
Anger	4.94	0.0008	-0.42	0.6851

Table 2: Paired t-tests on emotion classification made by OpenVINO. The tests are based on the synthetic faces with 0% activation across all AUs.

4   Discussion

We developed a synthetic face image dataset rich with diversity using manipulations of skin-color, action unit activation, and facial morphology by race. In our investigation of racial biases in public facial expression analysis models, synthetic images were a necessary tool for exposing bias in FER models due to color and facial morpohology. Using the FaceGen Modeller, we manipulated each facial parameter to create faces that differed across skin colors and facial morphologies. Next, we controlled facial expressions by manipulating activation intensities across ten AUs. We performed two experiments on analyzing predictions being made by (1) an AU estimation model and (2) two emotion recognition models. We observed color biases being instantiated by the Pain-Estimation model, where certain AU estimations had higher predictions for certain skin colors. In synthetic faces where all facial parameters were equal except color, there is an apparent gap in intensity between several AUs. However, we did not observe that one skin color necessarily performed better or worse than the other in terms of performance or intensity. This suggests that, despite the racial imbalances of the datasets (eg: 64.4% of training data in AffectNet is made up white race (of 7 total races) [3]), model bias is not representative of dataset representation. Additionally, we observed biases due to differing facial morphologies in the public FER models. Specifically, we discovered gaps in intensity level during emotion classification between faces that were similar in skin color, but differed in facial features. The investigations presented in this paper expose the racial bias present in several public facial emotion analysis models. Exploring such biases using artificially generated faces demonstrates the value of using synthetic data to carefully manipulate facial features in order to deliberately examine underlying biases that exist in FER models. In future work, we will leverage synthetic images to help identify and mitigate the root of racial biases in FER models.

References

[1] Ine Shinta Dewi Albert Yakobus Chandra. "Analysis Result Emotion Recognition Using Facial Expression Using OpenVINO". In: *Seminar Multimedia Artificial Intelligence* (2020). URL: https://www.ijser.org/researchpaper/Analysis-Of-Emotion-Recognition-Using-Facial-Expression-With-OpenVINO.pdf.

[2] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. "ImageNet: A large-scale hierarchical image database". In: *2009 IEEE Conference on Computer Vision and Pattern Recognition*. 2009, pp. 248–255. DOI: 10.1109/CVPR.2009.5206848.

[3] Iris Dominguez-Catena, Daniel Paternain, and Mikel Galar. *Assessing Demographic Bias Transfer from Dataset to Model: A Case Study in Facial Expression Recognition*. 2022. DOI: 10.48550/ARXIV.2205.10049. URL: https://arxiv.org/abs/2205.10049.

[4] Paul Ekman and Wallace V Friesen. "Measuring facial movement". In: *Environmental psychology and nonverbal behavior* 1.1 (1976), pp. 56–75.

[5] Sarah Fabi, Xiaojing Xu, and Virginia R. de Sa. "Exploring the Racial Bias in Pain Detection with a Computer Vision Model". In: *Proceedings of the 44th Annual Meeting of the Cognitive Science Society*. Ed. by J. Culbertson, A. Perfors, H. Rabagliati, and V Ramenzoni. 2022, pp. 358–365.

[6] Andrew G. Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. *MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications*. cite arxiv:1704.04861. 2017. URL: http://arxiv.org/abs/1704.04861.

[7] Patrick Lucey, Jeffrey F Cohn, Kenneth M Prkachin, Patricia E Solomon, and Iain Matthews. "Painful data: The UNBC-McMaster shoulder pain expression archive database". In: *Face and Gesture 2011*. IEEE. 2011, pp. 57–64.

[8] Ali Mollahosseini, Behzad Hassani, and Mohammad H. Mahoor. "AffectNet: A Database for Facial Expression, Valence, and Arousal Computing in the Wild". In: *CoRR* abs/1708.03985 (2017). arXiv: 1708.03985. URL: http://arxiv.org/abs/1708.03985.

[9] Omkar M. Parkhi, Andrea Vedaldi, and Andrew Zisserman. "Deep Face Recognition". In: *Proceedings of the British Machine Vision Conference (BMVC)*. Ed. by Xianghua Xie, Mark W. Jones, and Gary K. L. Tam. BMVA Press, 2015, pp. 41.1–41.12. ISBN: 1-901725-53-7. DOI: 10.5244/C.29.41. URL: https://dx.doi.org/10.5244/C.29.41.

[10] Kenneth M Prkachin and Patricia E Solomon. "The structure, reliability and validity of pain expression: Evidence from patients with shoulder pain". In: *Pain* 139.2 (2008), pp. 267–274.

[11] Andrey V. Savchenko, Lyudmila V. Savchenko, and Ilya Makarov. "Classifying emotions and engagement in online learning based on a single facial expression recognition neural network". In: *IEEE Transactions on Affective Computing* (2022), pp. 1–12. DOI: 10.1109/TAFFC.2022.3188390.

[12] Xiaojing Xu, Jeannie S Huang, and Virginia R De Sa. "Pain Evaluation in Video using Extended Multitask Learning from Multidimensional Measurements". In: *Proceedings of the Machine Learning for Health NeurIPS Workshop*. Ed. by Adrian V. Dalca, Matthew B.A. McDermott, Emily Alsentzer, Samuel G. Finlayson, Michael Oberst, Fabian Falck, and Brett Beaulieu-Jones. Vol. 116. Proceedings of Machine Learning Research. PMLR, 2020, pp. 141–154. URL: https://proceedings.mlr.press/v116/xu20a.html.

[13] K. Zhang, Z. Zhang, Z. Li, and Y. Qiao. "Joint Face Detection and Alignment Using Multitask Cascaded Convolutional Networks". In: *IEEE Signal Processing Letters* 23.10 (2016), pp. 1499–1503. ISSN: 1070-9908. DOI: 10.1109/LSP.2016.2603342.