MEDIMP: Medical Images and Prompts for renal transplant representation learning

Abstract

End-stage renal disease is characterized by an irremediable reduction in kidney function. Renal transplantation emerges as the most effective solution. Occurring from heterogeneous causes and complex phenomena, a substantial risk of transplant chronic dysfunction or rejection persists and may lead to graft loss. Medical imaging plays a substantial role in renal transplant monitoring in clinical practice. However, graft supervision is multi-disciplinary, notably joining nephrology, urology, and radiology, while identifying robust biomarkers from such high-dimensional and complex data for diagnosis and prognosis is challenging. In this work, taking inspiration from the recent success of Large Language Models (LLMs), we propose MEDIMP – Medical Images and Prompts – a model to learn meaningful multi-modal representations of renal transplant Dynamic Contrast-Enhanced Magnetic Resonance Imaging (DCE MRI) by incorporating structural clinical and biological data after translating them into text prompts. MEDIMP is based on contrastive learning from joint text-image paired embeddings to perform this challenging task. Moreover, a framework to generate medical prompts is proposed, using automatic textual data augmentations from LLMs. Our goal is to learn meaningful manifolds of renal transplant DCE MRI, interesting for the prognosis of the transplant or patient status (2, 3, and 4 years after the transplant), fully exploiting the available multi-modal data in the most efficient way. Extensive experiments and comparisons with other representation learning methods prove the effectiveness of MEDIMP, giving new directions toward medical prompts.

Keywords: Contrastive Learning, Natural Language Processing, LLM, MRI, Renal transplantation, Medical Prompts.

1. Introduction

End-stage renal disease is characterized by an irremediable reduction in kidney function, and renal replacement therapy is required to save the patient's life. Being more cost-effective than long-term dialysis and highly improving patients' quality of life, renal transplantation emerges as the most effective solution (Suthanthiran and Strom, 1994). However, a substantial risk of transplant chronic dysfunction or rejection persists and may lead to graft loss or, ultimately, patient death (Hariharan et al., 2021). In clinical practice, the graft health status is primarily indicated by calculating the glomerular filtration rate (GFR) from the creatinine level, resulting from blood tests. For further examinations, medical imaging plays a substantial role in renal transplant monitoring, and diverse imaging modalities have been investigated to assess renal transplant functions (Sharfuddin, 2013).

Recent advances in self-supervised learning (Taleb et al., 2020) enabled training powerful deep learning representations with limited data and supervision. Milecki et al. (2022) proposed weakly-supervised proxy tasks from clinical information to learn rich representations

of DCE MRI of renal transplant using a single continuous attribute. These features were further used to predict kidney function 2 years post-transplantation from follow-up medical imaging exams, indicating promising results and confirming that combining imaging and clinical attributes could lead to powerful biomarkers for predicting renal transplant failure.

Recent advances in Natural Language Processing (NLP) make textual data a potent candidate for designing weakly-supervised tasks to train computer vision models. Zhang et al. (2020) proposed a contrastive learning approach to pair text-image data in medical imaging using CT scans and pathology descriptions from radiology experts-diagnosis. However, such data curation is arduous, being highly time-consuming for medical experts, while such reports contain mainly information about the corresponding medical imaging exam, and they do not focus on other comorbidities. Extending this work, Radford et al. (2021) used this approach to train models producing robust representations of natural images as well as between textual and imaging data, reporting competitive results on several downstream tasks on unseen datasets in comparison to fully supervised baselines.

Learning powerful representations of medical imaging is of utmost importance, given the usual small size and the limited amount of annotations available. In such a setting, learning is performed in two stages. In the first stage, different self-supervised or weakly-supervised learning methods are used on the available imaging datasets, applying different types of learning, such as contrastive or adversarial learning (Milecki et al., 2022; Sowrirajan et al., 2020; Azizi et al., 2021; Boyd et al., 2021). Such representations are then frozen or fine-tuned on different downstream tasks, on which the amount of information is not enough for fully supervised learning. Such pretrainings could provide better representations and usually outperform ImageNet pretrained networks applied to medical imaging. However, they may produce suboptimal representations for the downstream tasks that merely capture spurious correlations (Arjovsky et al., 2019). This is also discussed in (Gamper and Rajpoot, 2021) for histopathology data, where the authors proposed a new dataset coupling images and captions of textbooks for better pretraining of deep neural network architectures. Therefore, in this work, we propose to go one more step forward by generating representations using imaging and paired clinicobiological attributes while exploring recent NLP advances in Large Language Models (LLMs). In particular, ChatGPT (OpenAI, 2022), a 175B parameters model, offers a powerful tool to work on textual data.

Specifically, we introduce MEDIMP (**MED**ical **IM**ages and **P**rompts), a method that learns relevant DCE MRI representations of renal transplants using contrastive learning from images and medical prompts pairs. The medical prompts are generated from paired clinical and biological data to produce supplementary information to imaging modalities to pretrain robust image encoders. The learned manifold enabled us to outperform state-of-the-art methods in the challenging task of kidney function prediction post-transplantation (2, 3, and 4 years) from 4 DCE MRI follow-up exams. Our contributions are as follows:

1. proposing a semi-automatic medical prompt generation from clinical and biological data for renal transplantation. To the best of our knowledge, we are the first to propose such an approach to augment medical textual data automatically;

2. learning multi-modal representations of renal transplant DCE MRI by training with contrastive learning an image and text encoder from clinical and biological attributes.

Figure 1: **Overview of our proposed method MEDIMP – Medical Images and Prompts.**
1. Medical prompts are generated from clinicobiological data using predefined templates of sentences, given as inputs to Large Language Models to produce augmented text data. 2. The medical prompts are used to learn multi-modal representations of renal transplants DCE MRI using contrastive learning from image-text pairs.

2. Method

Our multi-modal representations are based on contrastive learning, coupling imaging, and text embeddings. Our text is based on attributes easily accessible, widely used in clinical practice, and supplementary to imaging data. Our goal is to use the learned manifold of renal transplant DCE MRI for the prognosis of the transplant or patient status after $2, 3$, and 4 years post-transplantation. An overview of the method is presented in Figure 1.

2.1. Contrastive learning from joint text-image pairs

The first component of MEDIMP is pretraining an image encoder E_I, and a text encoder E_T, following a contrastive learning scheme using image-text pairs. Let us denote $(x_i, x_t) \in \mathbb{R}^{B \times N_x \times N_y \times N_z} \times \mathbb{R}^{B \times T}$ a batch of B corresponding pairs of an 3D MRI volume x_{ib} and a tokenized text x_{tb} for $b \in [\![1, B]\!]$. Both encoders transform x_i and x_t, in $f_i = E_\mathrm{I}(x_i)$ and $f_t = E_\mathrm{T}(x_t)$ respectively, to a batch of D dimensional embeddings. Both encoders are jointly trained to maximize the cosine similarity between the B pairs of image and text embeddings by optimizing the two following losses:

$$\mathcal{L}_{i \to t} = \sum_{b=1}^{B} - \log \frac{e^{\cos(f_{ib}, f_{tb})/\tau}}{\sum_{k=1}^{B} e^{\cos(f_{ib}, f_{tk})/\tau}} \tag{1}$$

where $\cos(\cdot, \cdot)$ is the cosine similarity function and $\tau \in \mathbb{R}^+$ a learned temperature parameter. Such loss was first proposed as the InfoNCE loss (van den Oord et al., 2018) to maximize a lower bound on mutual information and is widely used in recent uni-modal contrastive learning frameworks (Chen et al., 2020). $\mathcal{L}_{i \to t}$ enforces the image embeddings to align to the text embeddings and is, therefore, asymmetric. We define similarly $\mathcal{L}_{t \to i}$:

$$\mathcal{L}_{t \to i} = \sum_{b=1}^{B} - \log \frac{e^{\cos(f_{tb}, f_{ib})/\tau}}{\sum_{k=1}^{B} e^{\cos(f_{tb}, f_{ik})/\tau}} \tag{2}$$

The total loss is obtained by averaging Equation (1) and Equation (2), denoted as $\mathcal{L}_{contrastive}$. $\mathcal{L}_{contrastive}$ learns a multi-modal feature space by jointly optimizing E_I and E_T to maximize the cosine similarity of the embeddings f_i and f_t between the B true pairs per batch and minimizing the cosine similarity of the $B^2 - B$ false pairs.

2.2. Medical prompts from structural clinical and biological data

To exploit image-text pairing with contrastive learning, as well as the expression and encoding capability of recent NLP model advances, such as Large Language Models (LLMs) (Brown et al., 2020; OpenAI, 2022; Radford et al., 2021), we propose a framework to generate textual data from structural clinicobiological data that describe variables used in clinical practice and linked to the graft survival. The process is displayed on the left side of Figure 1. First, medical experts guided us to set thresholds to categorize continuous variables into text labels such as "low", "high", "stable", and "unstable" and to produce one *template sentence* per variable of interest, e.g., "the glomerular filtration rate (GFR) of the patient is very low at the first-year follow-up exam". Templates offer only one way of expressing the information of the variables. Indeed, the richness of language vocabulary can provide a variety of descriptions for the same information, such as "During the first-year follow-up visit, the transplant patient's GFR is found to be very low.", "The transplant patient's GFR is assessed as very low at the date follow-up examination.", generating descriptive text to train the proposed contrastive scheme. This richness was leveraged by recent advances in LLMs at training; hence, they offer robust NLP tools. Specifically, we use the dialogue LLM ChatGPT (OpenAI, 2022) to produce $N = 10$ textual data augmentations for each template sentence. All generated prompts are reported in Appendix A.

2.3. Implementation details

The image encoder followed the ResNet50 architecture initialized with CLIP (Radford et al., 2021) weights, a model pretrained on a dataset of 400 million (image, text) pairs collected from the internet and duplicated to 3D in the depth to match our data dimension. For the text encoder, we used the BERT (Devlin et al., 2018) architecture initialized with the Bio+Clinical BERT (Alsentzer et al., 2019) model pretrained on the MIMIC clinical notes (Johnson et al., 2016). The first 11 layers of Bio+Clinical BERT were frozen, fine-tuning only the last layer of the transformer with our contrastive task. Appendix C discusses the ablation of fine-tuning more layers for our task. The temperature parameter τ was initialized to 0.07, incorporated into the model as a learnable parameter, and clipped to prevent scaling the logits by more than 100, following the recommendations of CLIP trainings.

For the image data, we used data augmentation with the sequential application with a 0.5 probability of horizontal flipping, random affine transformation, random Gaussian blur ($\sigma \in [0, 0.5]$), random Gaussian noise ($\sigma \in [0, 0.05]$), and random contrast perturbation ($\log \gamma \in [-0.3, 0.3]$), using TorchIO python library (Pérez-García et al., 2021).

Figure 2: **t-SNE visualizations of the features of the last layer of MEDIMP image encoder using the DCE MRI follow-ups.** Colormaps are set by the 4 variables of interest value used for the medical prompts: (1) Exam (exam date), (2) GFR ($\mathrm{mL.min}^{-1}$, (3) Creat ($\mu mol.L^{-1}$), and (4) donor's age (year).

| (1) Exam | (2) GFR (mL.min⁻¹) | (3) Creat (μmol.L⁻¹) | (4) Donor's Age (year) |

The Adam (Kingma and Ba, 2014) optimizer with decoupled weight decay regularization (Loshchilov and Hutter, 2017) of 0.02 was used with a starting learning rate of $5e^{-5}$ following a cosine schedule and preceded by a linear warm-up of 40 epochs. The batch size was set to 88 and the model trained for 200 epochs with mixed-precision on 4 NVIDIA Tesla V100 GPU using Pytorch (Paszke et al., 2019).

3. Data

Our study was approved by the Institutional Review Board, which waived the need for patients' consent. The data cohort corresponds to study reference Anonymous01. All the data used in this study are anonymized. Our imaging data are based on DCE MRI series collected from 105 subjects (split as 72/5 training/validation, and 28 test). Each subject underwent up to 4 follow-up exams, taking place approximately 15 days, 30 days, 3 months, and 1 year post-transplantation. The DCE MRI volumes sized $512 \times 512 \times [64 - 88]$ voxels included spacing ranging in $[0.78 - 0.94] \times [0.78 - 0.94] \times [1.9 - 2.5]$ mm. All volumes were cropped around the transplant using an automatic and unsupervised method for selecting the region of interest and reducing dimensionality (Milecki et al., 2021). Intensity normalization was executed to each volume independently by applying standard normalization, clipping values to $[-5, 5]$, and rescaling linearly to $[0, 1]$.

To provide the clinical and biological data used to generate text annotations, all the 77 patients in the train set were regularly subjected to blood tests a few days before the transplantation and several years after to measure the serum creatinine (Creat) level in $\mu mol.L^{-1}$. The donor's age variable and the glomerular filtration rate (GFR) value at each follow-up exam were also collected. Only the target labels were available for the 28 test subjects, defined in the next section.

4. Experiments & Results

First, we visualize the obtained representations of DCE MRI from the trained image encoder using t-SNE decomposition (van der Maaten and Hinton, 2008). Figure 2 shows the different obtained reduced feature spaces by the model trained on all available clinical and biological

variables ($n_{cl} = 4$), adding colormaps related to the different clinical and biological variables of interest. While the continuous variables were categorized and transformed to medical prompts, MEDIMP image encoder demonstrates relevant representations towards (B) the GFR and (C) the Creat. The t-SNE decomposition does not reveal favorable representations regarding (D) Donor's Age. On the contrary, the obtained feature space serves well the (A) Exam date information, where we retrieve better clustered very early exams (D15, blue) and late exams (M12, red), due to their respective distance to the transplantation surgery.

Downstream task and metrics. We evaluate MEDIMP on the downstream task of serum creatinine (Creat) prediction from the imaging features of 4 follow-up exams using a light transformer architecture and tailored for missing follow-up exams as proposed by Milecki et al. (2022). In clinical practice, Creat level results from blood tests and is a primary indicator of kidney function. The binary classification downstream task is obtained when binarizing the Creat value using a threshold of $110\mu mol.L^{-1}$ at different prediction dates. The Creat target prediction value is calculated as the mean over an interval of three months before and after the prediction dates. To make the task more challenging, we evaluate the performance of the representations at 2, 3, and 4 years post-transplantation and also report the mean over the three predictions, for the 28 test subjects.
Metrics: The two evaluation metrics used were the F1 score and the area under the receiver operating characteristic curve (ROC AUC).

Ablation. First, we ablate all information used in our method by adding different combinations of the clinical and biological measurements in the medical prompts, i.e., the glomerular filtration rate (GFR) at the exam date, the number of the patient's exam (Exam), the creatinine levels variation from the previous exam (Creat), and the age of the donor (D.A.). For this, we report the results in the bottom part of Table 1 (MEDIMP). We observe that the best mean scores over the three predictions are obtained using all the available medical prompts (last row). Moreover, the AUC decreases over the prediction date, showing the increasing prognosis difficulty with time. Using only the GFR prompts (row 6), AUC scores are just above random, indicating the need for more descriptive text.

Comparison to the state of the art. Table 1 reports the results when comparing the proposed MEDIMP with the previous state-of-the-art (Milecki et al., 2022), denoted as CosEmbLoss (row 1 & 2). Note that the main model of CosEmbLoss uses only GFR information. Hence, it is directly comparable to MEDIMP when using only GFR (6th row)[1]. These experiments reveal that smaller and more compact models such as the CosEmbLoss perform better than big models when the text information is not very rich. However, when more variables are integrated, our proposed methods outperform the CosEmbLoss. For a fair comparison, we also compare MEDIMP to several baselines with the same level of information. In particular, we evaluate against three baselines, denoted as the CosEmbLoss++, where we gradually add the same level of information as in MEDIMP. In practice, we optimize the same two-stream approach by averaging several cosine embedding losses based on the number of variables of interest incorporated. We report these results in rows 3-5 of Table 1. We observe that CosEmbLoss++ achieve their best performance using a combina-

---

1. CosEmbLoss uses the continuous value on their loss directly. In contrast, we categorize the variable to generate the prompts, hence using less information than CosEmbLoss

Table 1: **Comparison of MEDIMP vs the state of the art.** We evaluate the performance of the representations at 2,3,4 years post-transplantation and report the mean. Ablations in weak annotations added from either the variable values for the comparison CosEmbLoss pertaining or our proposed generated textual data are denoted as GFR (GFR value at the follow-up exam), Exam (which follow-up exam), Creat (creatinine levels variations from the previous exam), and D.A. (the donor's age). We report F1 score (F1), and ROC AUC (AUC). **Bold**, Underlined indicates the top **1**, 2 performing combinations, respectively.

Method	Weak annotations				2 years		3 years		4 years		Mean	
	GFR	Exam	Creat	D.A.	AUC	F1	AUC	F1	AUC	F1	AUC	F1
CosEmbLoss	✓				76.2	86.4	77.8	70.6	67.0	77.3	73.6	78.1
CosEmbLoss				✓	75.5	81.1	75.6	68.8	66.1	78.1	72.4	76.0
CosEmbLoss++	✓			✓	84.4	88.9	82.5	**86.4**	73.9	85.7	80.3	87.0
CosEmbLoss++	✓		✓		81.6	87.8	71.3	85.1	71.3	90.2	74.7	87.7
CosEmbLoss++	✓		✓	✓	78.2	87.0	75.0	83.3	74.8	87.0	76.0	85.8
MEDIMP	✓				56.5	83.3	51.9	79.1	49.6	**90.2**	52.6	84.2
MEDIMP	✓	✓			81.0	**89.4**	81.9	80.0	74.8	84.4	79.2	84.6
MEDIMP	✓	✓		✓	76.9	73.2	**86.3**	85.7	74.8	**90.2**	79.3	83.0
MEDIMP	✓	✓	✓		72.8	86.4	71.9	81.0	71.3	71.8	72.0	79.7
MEDIMP	✓	✓	✓	✓	**85.0**	**89.4**	84.4	83.7	**75.7**	**90.2**	**81.7**	**87.8**

tion of 2 variables. The best mean AUC is 80.3% with GFR and D.A., and the best F1 is 87.7% with GFR and Creat, which are lower than the best MEDIMP performances. Note, the Exam information was not added to CosEmbLoss++ as this variable is less adapted to CosEmbLoss. Nevertheless, combining the 3 variables of interest with CosEmbLoss++ lowers the performance to 76.0% AUC and 85.8% F1 in Mean. Overall, MEDIMP with all medical prompts results in the best predictions at 2 and 4 years post-transplantation.

Medical Prompt generation. To demonstrate the relevance of the proposed approach for medical prompt generation, we compare our main model with two other approaches that produce text information. The first one is noted as "Manual" and comprises all the templates indicated by the medical experts, corresponding to only one sentence per variable of interest. Note that this is the base of our proposed medical prompting without using the prompt expansion method described in Section 2.2. The second one uses an existing NLP model (T5 (Raffel et al., 2019)) to produce sentences from structural data. For a fair comparison, we train the T5 model on the WebNLG 2020 data (Gardent et al., 2017) and infer it on our data to generate text, denoted as "T5 WebNLG". Results are summarised in Table 2, indicating the superiority of our method. The "T5 WebNLG" approach offers a competitive F1 for all the predictions, although the AUC is the lowest except for the 2 years prediction. We show in Appendix B examples of generated text from the three approaches. "Manual" approach lacks diversity in the text data, and therefore the training process of our proposed approach without text augmentations is more challenging.

5. Discussion

Our experiments have shown improvements in the representation learning capabilities of deep image encoders for renal transplantation MRI compared to the previous state-of-the-

Table 2: **Quantitative evaluation of the proposed method against other text generation methods.** All medical prompts were used. We report F1 score (F1), and ROC AUC (AUC). **Bold**,Underlined indicates the top **1**,2 performing combinations, respectively.

Method	2 years		3 years		4 years		Mean	
	AUC	F1	AUC	F1	AUC	F1	AUC	F1
MEDIMP	**85.0**	**89.4**	**84.4**	**83.7**	75.7	**90.2**	**81.7**	**87.8**
Manual	74.2	76.2	80.6	62.1	**80.0**	76.9	78.3	71.7
T5 WebNLG	74.8	85.7	78.8	83.3	74.8	85.7	76.1	84.9

art approach for the specific application of renal transplant function forecasting. MEDIMP aimed at enhancing representation learning approaches using external data, by leveraging the power of deep NLP models such as LLMs and introducing a novel process to incorporate relevant clinical and biological medical information. We deem that such an approach crossing modalities in medical research would highly improve the capacity to learn and understand complex medical or biological phenomena. However, some limitations of the proposed framework remain to be analyzed. (1) First, although limited data is part of the challenges this study aims to tackle, supplementary test data would indubitably support validating our method. To our knowledge, no public medical imaging dataset offers simultaneously longitudinal imaging, biological, as well as clinical data for each patient for prognosis at different times. Nevertheless, our proposed framework could be easily translated to similar datasets having imaging data and any type of tabular data. To ensure this, the code of our paper will be publicly available after the anonymous review. (2) Second, this work constitutes a first attempt to generate medical prompts as text information from a few clinical and biological variables of interest which are very important to apprehend complex medical concepts. Thus, we would seek to extend this work to be able to exploit more variables to guide the training of the image encoders. Using our proposed framework this can be easily implemented since only a few templates will need to be defined to automatically generate the text augmentations. (3) Finally, the study of the development and comprehension of LLMs is recent. We expect such NLP models to increase the emphasis on using textual data. In this work, we use ChatGPT to enable relevant and robust text augmentations to be able to train our joint text-image framework correctly. One could think of several ways to further use such models as powerful tools, for instance, through prompt engineering tuned for medical cases. However, the main drawback of these models is their reliability, in the sense that inaccurate generation might be challenging to detect.

6. Conclusion

We have introduced MEDIMP, an approach to learn powerful manifolds of renal transplant DCE MRI data toward transplant function forecasting in the context of renal transplantation monitoring. This approach provides an elegant way to incorporate clinical or biological information into the learning process of feature extraction of medical imaging data. The presented representation learning strategy enabled us to outperform the state of the art in the challenging task of creatinine prediction. These promising results advocate using textual data from emerging LLMs to assist in training robust medical imaging models.

Acknowledgments

Acknowledgments withheld.

References

Emily Alsentzer, John R. Murphy, Willie Boag, Wei-Hung Weng, Di Jin, Tristan Naumann, and Matthew B. A. McDermott. Publicly available clinical BERT embeddings. Eprint arXiv:1904.03323, 2019.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Shekoofeh Azizi, Basil Mustafa, Fiona Ryan, Zachary Beaver, Jan Freyberg, Jonathan Deaton, Aaron Loh, Alan Karthikesalingam, Simon Kornblith, Ting Chen, Vivek Natarajan, and Mohammad Norouzi. Big self-supervised models advance medical image classification. Eprint arXiv:2101.05224, 2021.

Joseph Boyd, Mykola Liashuha, Eric Deutsch, Nikos Paragios, Stergios Christodoulidis, and Maria Vakalopoulou. Self-supervised representation learning using visual field expansion on digital pathology. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 639–647, 2021.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. Eprint arXiv:2005.14165, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. Eprint arXiv:2002.05709, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. Eprint arXiv:1810.04805, 2018.

Jevgenij Gamper and Nasir Rajpoot. Multiple instance captioning: Learning representations from histopathology textbooks and articles. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16549–16559, 2021.

Claire Gardent, Anastasia Shimorina, Shashi Narayan, and Laura Perez-Beltrachini. The WebNLG challenge: Generating text from RDF data. In *Proceedings of the 10th International Conference on Natural Language Generation*, pages 124–133, Santiago de Compostela, Spain, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-3518.

Sundaram Hariharan, Ajay K. Israni, and Gabriel Danovitch. Long-term survival after kidney transplantation. *N. Engl. J. Med.*, 385(8):729–743, 2021.

A. E. Johnson, T. J. Pollard, L. Shen, L. W. Lehman, M. Feng, M. Ghassemi, B. Moody, P. Szolovits, L. A. Celi, and R. G. Mark. MIMIC-III, a freely accessible critical care database. *Sci Data*, 3:160035, May 2016.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. Eprint arXiv:1412.6980, 2014.

Ilya Loshchilov and Frank Hutter. Fixing weight decay regularization in adam. Eprint arXiv:1711.05101, 2017.

Kevin Lu, Aditya Grover, Pieter Abbeel, and Igor Mordatch. Pretrained transformers as universal computation engines. Eprint arXiv:2103.05247, 2021.

Leo Milecki, Sylvain Bodard, Jean-Michel Correas, Marc-Olivier Timsit, and Maria Vakalopoulou. 3D unsupervised kidney graft segmentation based on deep learning and multi-sequence MRI. In *2021 IEEE 18th International Symposium on Biomedical Imaging (ISBI)*, pages 1781–1785, 2021. doi: 10.1109/ISBI48211.2021.9433854.

Leo Milecki, Vicky Kalogeiton, Sylvain Bodard, Dany Anglicheau, Jean-Michel Correas, Marc-Olivier Timsit, and Maria Vakalopoulou. Contrastive masked transformers for forecasting renal transplant function. In *Medical Image Computing and Computer Assisted Intervention – MICCAI 2022*, pages 244–254, Cham, 2022. Springer Nature Switzerland. ISBN 978-3-031-16449-1.

OpenAI. Chatgpt: Optimizing language models for dialogue, 2022. URL https://openai.com/blog/chatgpt/.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Fernando Pérez-García, Rachel Sparks, and Sébastien Ourselin. Torchio: A python library for efficient loading, preprocessing, augmentation and patch-based sampling of medical images in deep learning. *Comput. Methods Programs Biomed.*, 208:106236, 2021. ISSN 0169-2607.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. Eprint arXiv:2103.00020, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. Eprint arXiv:1910.10683, 2019.

Asif Sharfuddin. Renal relevant radiology: Imaging in kidney transplantation. *Clinical journal of the American Society of Nephrology*, 9, 11 2013. doi: 10.2215/CJN.02960313.

Hari Sowrirajan, Jingbo Yang, Andrew Y. Ng, and Pranav Rajpurkar. MoCo-CXR: MoCo pretraining improves representation and transferability of chest X-ray models. Eprint arXiv:2010.05352, 2020.

Manikkam Suthanthiran and Terry B. Strom. Renal transplantation. *N. Engl. J. Med.*, 331 (6):365–376, 1994.

Aiham Taleb, Winfried Loetzsch, Noel Danz, Julius Severin, Thomas Gaertner, Benjamin Bergner, and Christoph Lippert. 3D self-supervised methods for medical imaging. In *Advances in Neural Information Processing Systems*, volume 33, pages 18158–18172. Curran Associates, Inc., 2020.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. Eprint arXiv:1807.03748, 2018.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9(86):2579–2605, 2008.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Yuhao Zhang, Hang Jiang, Yasuhide Miura, Christopher D. Manning, and Curtis P. Langlotz. Contrastive learning of medical visual representations from paired images and text. Eprint arXiv:2010.00747, 2020.

Appendix A. ChatGPT prompts

The main conversation with the dialogue LLM ChatGPT (OpenAI, 2022) to generate our medical prompts is the following:

- Input 1: "I want to find synonyms or text augmentations of full sentences in the context renal transplantation. Are you familiar with these concepts ?"

  Output 1: "Yes, I am familiar with the concept of finding synonyms or text augmentations of full sentences, also known as text augmentation or data augmentation. This is a technique used to artificially increase the size and diversity of a dataset by applying various natural language processing (NLP) techniques such as synonym replacement, random insertion, deletion, and substitution of words. In the context of renal transplantation, it could be used to expand the number of examples of medical reports or other texts related to renal transplantation by generating similar but slightly different versions of the original text."

- Input 2: "The full sentence template is "The age of the donor is {age}. The glomerular filtration rate (GFR) of the patient is {gfr} at {date} follow-up exam. And the creatinine levels variation were {adj}" where {age}, {gfr}, {date}, {adj} can be changed by me but not by you, do you understand ?"

  Output 2: "Yes, I understand. You have provided a sentence template with placeholders for age, glomerular filtration rate (GFR), date, and an adjective that can be changed by you. And you are looking for text augmentation to generate similar but slightly different versions of the original text with the help of natural language processing(NLP) techniques such as synonym replacement, random insertion, deletion, and substitution of words."

- Input 3: "Provide full sentence synonyms of the sentences I provided, you are allowed to give more context information and not especially respect the exact number of sentences."

  Output 3: "Here are some examples of synonyms or text augmentations of the sentence template you provided:

  1. "The age of the kidney donor is {age}. The patient's glomerular filtration rate was measured to be {gfr} at the {date} follow-up appointment. The creatinine levels showed {adj} variation."

  2. "The individual who provided the kidney for transplant was {age} years old. The recipient's GFR was determined to be {gfr} during the {date} check-up. Creatinine levels fluctuated {adj}."

  3. "At the time of transplant, the donor was {age} years of age. The patient's GFR was evaluated as {gfr} at the {date} follow-up examination. Creatinine levels demonstrated {adj} changes."

  4. "The age of the individual who donated the kidney was {age}. The GFR of the transplant recipient was {gfr} at the {date} examination. There were {adj} variations in creatinine levels."

5. "The kidney donor was {age} years old. The GFR of the transplant patient was measured as {gfr} at the {date} follow-up visit. The creatinine levels showed {adj} fluctuations."

6. "The donor's age was {age} at the time of transplant. The patient's glomerular filtration rate was found to be {gfr} during the {date} appointment. Creatinine levels were {adj}."

Please note that the sentences are not exact synonyms, but variations that convey similar information, and that it's possible to generate a lot more variations by changing the words, phrases or structures of the sentences."

- Input 4: "Give ten more synonym examples of the provided sentence and you can generate more variations as you proposed."

Output 4: "Sure, here are ten more examples of text augmentations of the sentence template you provided:

1. "The kidney donor was {age} years of age. The patient's GFR was found to be {gfr} at the {date} check-up. Creatinine levels displayed {adj} fluctuations."

2. "At the time of transplant, the age of the kidney donor was {age}. The patient's glomerular filtration rate was {gfr} at the {date} follow-up. Creatinine levels varied {adj}."

3. "The individual who provided the kidney for transplant was {age} years old. The GFR of the recipient was determined to be {gfr} during the {date} examination. There were {adj} changes in creatinine levels."

4. "The age of the kidney donor was {age}. The GFR of the transplant recipient was {gfr} at the {date} follow-up visit. Creatinine levels fluctuated {adj}."

5. "The individual who donated the kidney was {age} years of age. The patient's glomerular filtration rate was measured as {gfr} at the {date} check-up. The creatinine levels demonstrated {adj} variations."

6. "At the time of transplant, the donor's age was {age}. The GFR of the patient was evaluated as {gfr} during the {date} follow-up. The creatinine levels showed {adj} fluctuations."

7. "The kidney donor was {age} years old at the time of transplant. The patient's glomerular filtration rate was {gfr} at the {date} examination. Creatinine levels varied {adj}."

8. "The individual who provided the kidney for transplant was {age} years of age. The recipient's GFR was determined to be {gfr} at the {date} follow-up appointment. The creatinine levels displayed {adj} changes."

9. "At the time of transplant, the age of the kidney donor was {age}. The GFR of the transplant patient was {gfr} during the {date} check-up. Creatinine levels fluctuated {adj}."

10. "The individual who donated the kidney was {age} years old. The glomerular filtration rate of the transplant recipient was {gfr} at the {date} examination. The creatinine levels showed {adj} variation."

Please note that the above sentences are not exact synonyms, but variations that convey similar information, and that there are many more variations that can be generated by changing the words, phrases or structures of the sentences."

Appendix B. Textual data generation

We compare the proposed approach for medical prompt generation with two other approaches that produce text annotations. The first one is noted as "Manual" and comprises all the templates indicated by the medical experts, corresponding to only one sentence per variable of interest. Note that this is the base of our proposed medical prompting without using the LLM augmentation method. The second one uses an existing NLP model (T5 (Raffel et al., 2019)) to produce sentences from structural data. We train the T5 model on the WebNLG 2020 data (Gardent et al., 2017) and infer it on our data to generate text, denoted as "T5 WebNLG". We observe that the "Manual" approach lacks diversity in the textual data, as no text augmentations are performed for this straightforward process. "T5 WebNLG" offers some more variability in words used, but the structure of the sentences remains similar and straightforward. Moreover, some incorrect generations occur, e.g., "The age of the donor" is replaced by "The age of the patient". Such errors introduce anomalies in the data, a highly sensitive issue in such a medical context.

- "Manual" – from one sentence template:
  "The age of the donor is low. The glomerular filtration rate (GFR) of the patient is high at one month follow-up exam. And the creatinine levels variation were stable.";

- "T5 WebNLG" – pretraining a model to generate textual data from structural data:

  - correct generation example: "The age of the donor is high. The glomerular filtration rate is medium. The creatinine levels of a patient are unstable.";

  - incorrect generation example: "The age of the patient was low. The glomerular filtration rate of GFR is an extrem low rate. The creatinine levels of a patient are unstable."

- MEDIMP: see Appendix A.

Appendix C. Freezing the text encoder

For the text encoder, we used the BERT (Devlin et al., 2018) architecture initialized with the Bio+Clinical BERT (Alsentzer et al., 2019) model pretrained on the MIMIC clinical notes. BERT is based on the transformer (Vaswani et al., 2017) architecture and composed of 12 transformer blocks. Our main models were obtained by freezing the first 11 layers of the Bio+Clinical BERT model, fine-tuning only the last layer of the transformer with our contrastive task.

Benefiting from a dataset of 400 million (image, text) pairs collected from the internet, Radford et al. (2021) trained both their image and text encoder from scratch. While we used the same initialization as Zhang et al. (2020), they froze their text encoder's first half (6 layers). In recent NLP work, Lu et al. (2021) suggested to only finetune normalization layers

(LN) in the transformer blocks, without finetuning of the self-attention and feedforward layers of the residual blocks. Table 3 reports the ablation results using this latest strategy, denoted as not LN, and gradually freezing the 6, 9, and 11 first layers of the text encoder. The ablation was evaluated using two sets of weak annotations from our proposed method, first the GFR and date, denoted as MEDIMP A and second the GFR, Exam and Donor's Age, denoted as MEDIMP B. We observe that freezing the first 11 layers gives us the best performances, and this is the strategy we used for our paper.

Table 3: **Ablation results on the way of freezing the text encoder.** We report F1 score (F1), and ROC AUC (AUC). **Bold**, Underlined indicates the top **1**, 2 performing combinations, respectively.

Method	Freezing $E_\mathbf{T}$	2 years		3 years		4 years		Mean	
		AUC	F1	AUC	F1	AUC	F1	AUC	F1
MEDIMP A	First 11	81.1	**89.4**	81.9	80.0	74.8	84.4	79.2	**84.6**
MEDIMP A	First 9	74.8	75.7	81.9	81.0	76.5	68.6	77.7	75.1
MEDIMP A	First 6	74.2	74.4	70.0	82.1	83.5	68.6	75.9	75.0
MEDIMP A	not LN	73.5	70.6	77.5	80.0	73.0	71.8	74.7	74.1
MEDIMP B	First 11	76.9	73.2	**86.3**	**85.7**	74.8	**90.2**	79.3	83.0
MEDIMP B	First 9	**83.7**	64.5	78.1	82.9	75.7	64.7	79.2	70.7
MEDIMP B	First 6	75.5	70.6	84.4	80.0	**84.4**	82.9	**81.4**	77.8
MEDIMP B	not LN	66.7	81.0	79.4	80.9	60.9	85.7	69.0	82.5