Redundancy-Free Message Passing for Graph Neural Networks

Rongqin Chen [1,2]
chen.rongqin@connect.um.edu.mo

Shenghui Zhang [1]
zhang.shenghui@connect.um.edu.mo

Leong Hou U, Ryan [1]
ryanlhu@um.edu.mo

Ye Li [2]
ye.li@siat.ac.cn

[1] State Key Laboratory of Internet of Things for Smart City, University of Macau, China
[2] Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences, China

Abstract

Graph Neural Networks (GNNs) resemble Weisfeiler-Lehman (1-WL) test, which iteratively update the representation of each node by aggregating information from WL-subtrees. However, despite the computational superiority of the iterative aggregation scheme, it introduces redundant message flows to encode nodes. We found that the redundancy in message passing prevented conventional GNNs from propagating the information of long-length paths and learning graph similarities. In order to address this issue, we proposed Redundancy-Free Graph Neural Network (RFGNN), in which the information of each path (of limited length) in the original graph is propagated along a message flow devoid of duplicate edges. Our rigorous theoretical analysis demonstrates the following advantages of RFGNN: (1) RFGNN has the most expressive power if it is sufficiently high, and height-k RFGNN is strictly more powerful than k-layer WL-test based GNNs; (2) RFGNN efficiently propagate structural information in original graphs, avoiding the over-squashing issue; and (3) RFGNN is more likely to encode graphs with closer graph edit distances into more similar representations. The experimental evaluation of graph property prediction tasks validated our theoretical statements, and the performance of RFGNN can reach the best results in most challenges.

1 Introduction

Graph Neural Networks (GNNs) generally imitate Weisfeiler-Lehman (1-WL) test [1] in the sense that they iteratively update the representation of each node of a graph by aggregating information from its neighbors [2], which are referred to as WL-test based GNNs in this study. The iterative neighborhood aggregation scheme encodes trees (called WL-subtrees [3]), where a node's child nodes in a WL-subtree are neighbor nodes of the node in the original graph; any WL-subtree is therefore a height-balanced tree. Despite the fact that research on GNNs has made great strides and achieved remarkable success in recent years, the vast majority of studies do not break the paradigm of repetitive neighborhood aggregation, which provides computational superiority but generates negative consequences due to message flow redundancy in tree-like encoding. Figure 1 illustrates an example of message flow redundancy in a computational graph. Message flow redundancy is prevalent, especially when the number of messaging passing iterations (a.k.a. neural network layers) increases. Although there have been studies on the computation of redundancy in GNNs, e.g. [4], it should be noted that computational redundancy is orthogonal to messaging redundancy.

| (a) Input Graph | (b) 2-Layer GNN Computational Graph | (c) A message flow that transmits redundant information (i.e., the orange node) |

Figure 1: Redundancy exists in message flows, which are propagation chains in a GNN computational graph that deliver the information from input nodes to output nodes.

The redundancy phenomenon is accompanied by the problem of *over-squashing*, which refers to the phenomenon in which the information originating from distant nodes can be distorted, thus limiting the efficiency of message passing for tasks that rely on long-distance interactions [5]. This issue is attributable to the bottleneck of compressing a rapidly growing number of neighboring nodes into a vector of finite length [6] and the failure of certain input features to influence the output representation [5]. However, in previous studies, the understanding of over-squashing and the explanation for why it occurs are still deficient. In this study, we carefully analyze the influence of an input feature on an output representation along a *trail* (extracted from the original graph), and we observe that longer trails typically have a smaller impact than shorter trails in the neighborhood aggregation process. One key reason behind this is that short trails usually result in a great number of redundant message flows in the computational graph.

According to previous research [7, 8, 9, 10], a fundamental problem of graph learning is to quantify the similarities between graphs. In the real world, many graphs, such as molecules, have structures at both coarse levels (such as chains, rings, and trees) and fine levels (like chemical bonds and functional groups). Some scholars [11] believe that an ideal method of graph similarity measurement should be able to capture subgraphs at different levels of granularity. However, WL-subtree [3] can only capture the graph similarity at coarse levels because WL-subtrees are height-balanced trees. Besides, WL-test based GNNs tend to encode two graphs that yield similar WL subtrees as similar representations. However, even if only one edge in the two original graphs is different, this can lead to two very different WL subtrees due to the message flow redundancy. Thus, WL-test based GNNs may have insufficient expressive power to measure graph similarity.

We propose Redundancy-Free Graph Neural Network (RFGNN) to address the aforementioned issues. We first eliminate the message flow redundancy with a concept called *path search tree* (a.k.a. breadth-first tree), which is constructed by running a breadth-first search (BFS) from a node [12]. Since there are no repeated nodes in each path in the path search tree, by using the tree as the message passing graph, the resulting model would not suffer from message flow redundancy. However, this simple path search tree model cannot capture some graph structures, e.g., ring. To enhance the expressiveness of the model, we define a new concept called *extended path (epath)*, which can represent a ring structure when its starting and finishing nodes are the same. Based on epath, we propose a concept called *Truncated ePaths Tree (TPT)*, an epath search tree obtained by running a BFS, where all epaths of limited length starting from the node are accessed. Given a TPT (of a graph node), RFGNN is a neural network to perform bottom-up message passing. Finally, we collect the representations of all TPTs in order to update the representation of the entire graph.

In comparison to prior research in the field of GNNs, the leading technologies and theories of this paper were summarized as follows: 1) To the best of our knowledge, this is the first theoretical examination of message flow redundancy in GNNs and its practical implications; 2) We proved that RFGNN with sufficiently high has the most expressive power, and height-k RFGNN is strictly more expressive than k-layer WL-test based GNNs; 3) De-redundancy balances the influence of epaths starting at the same node during message passing, propagates structural information in original graphs efficiently, and reduces over-squashing; 4) RFGNN always generates similar message passing graphs

for similar graphs compared to WL-test based GNNs; hence, RFGNN can learn better representations of similar graphs than WL-test based GNNs.

The rest of this paper is structured as follows. Section 2 outlines the basic theories of GNNs. In Section 3, we demonstrate that redundancy is prevalent in GNNs and analyze why it contributes to the issue of over-squashing in GNNs. The framework of RFGNN is presented in Section 4, which not only eliminates the redundancy in computational graphs but also provides several additional advantages. Some related works are given in Section 5. Section 6 empirically validates RFGNN on a variety of graph property prediction challenges and demonstrates that RFGNN achieves state-of-the-art performance on the vast majority of tasks. The conclusion is given in Section 7.

2 Preliminaries

We begin by reviewing the most commonly used message passing paradigm and its derivative GNNs, as well as introducing our notations. Let $G(V, E) \in \mathcal{G}$ be a graph, where $V = \mathcal{V}(G) = \{1, 2, \ldots\}$, $E = \mathcal{E}(G) \subseteq V \times V$, and $\mathcal{G}$ is the graph set consisting of all possible graphs. The nodes and edges in G can have feature vectors associated with them, denoted by $\mathbf{x}_u$ for $u \in V$ and $\mathbf{e}_{u,v}$ for $(u, v) \in E$. We consider graph property prediction problems, where, given a set of graphs $\{G_1, \ldots, G_N\} \subseteq \mathcal{G}$ and their labels $\{y_1, \ldots, y_N\} \subseteq \mathcal{Y}$, we aim to learn a representation vector $\mathbf{h}_G$ that helps to predict the label of an entire graph by a predictor, $y_G = \rho(\mathbf{h}_G)$.

Message passing and graph neural networks. GNNs iteratively update the representation of the nodes by aggregating neighbor information. The l-th layer of GNN can be described as

$$\mathbf{h}_u^{(l)} = \psi^{(l)} \left(\mathbf{h}_u^{(l-1)}, \cup_{v \in \mathcal{N}(u)} \phi^{(l)} \left(\mathbf{e}_{(u,v)}^{(l-1)}, \mathbf{h}_v^{(l-1)} \right) \right), \tag{1}$$

where $\psi^{(l)}$ and $\phi^{(l)}$ denote differentiable functions such as MLPs (Multi Layer Perceptrons), $\cup$ denotes a differentiable, permutation invariant aggregator, (e.g., *sum* and *mean*), $\mathbf{h}_u^{(l)}$ is the node u representation, and $\mathbf{e}_{(u,v)}^{(l-1)}$ is the edge (u, v) representation transformed from $\mathbf{e}_{(u,v)}$ by a differentiable function such as a linear function. We initialize $\mathbf{h}_u^{(0)} = \mathbf{x}_u$. The readout χ function aggregates node representations from the final layer to obtain the entire graph representation $\mathbf{h}_G$:

$$\mathbf{h}_G = \chi \left(\left\{ \mathbf{h}_u^{(k)} \mid u \in G \right\} \right). \tag{2}$$

The readout χ can be a simple permutation invariant function such as *sum*.

Weisfeiler-Lehman test and WL-subtree. The graph isomorphism problem is to identify whether two graphs are topologically equivalent, i.e., isomorphic. Weisfeiler-Lehman (1-WL) test [1] iteratively updates the label of a node by hashing the set of its own and neighbors' labels. Graphs are deemed non-isomorphic by 1-WL if their node labels differ at one iteration. Based on 1-WL, Shervashidze et al. [3] propose WL-subtree kernel, which measures the similarity of graphs based on the number of distinct node labels. A node label represents a tree (WL-subtree) rooted at the node and constructed from its neighborhood. That means WL-subtree kernel compares graph similarity by the number of distinct WL-subtrees.

Computational graph. Computational graphs represent neural networks as graphs on which gradients can be conveniently computed using chaining laws [13]. In message passing GNNs, the computational graph for a node is the message passing graph that aggregates neighborhood information into the node. The computational graph is jointly determined by the adopted message passing paradigm and the structure of the input graph.

3 Message Flow Redundancy and Practical Implications

In this section, we first explain redundancy in computational graphs and then discuss the over-squashing issue. Without loss of generality, we discuss the computational graph of a k-layer WL-test based GNN for (the representation of) a node. All proofs can be found in Appendix A.

3.1 Message Flow Redundancy in Computational Graph

Definition 1 (Message flow). *A message flow p in a computational graph depicts the propagation chain of an input feature from an input node to an output node, where $p(i)$ denotes the i-th node of p (zero based index).*

Message flow redundancy. A WL-based test GNN iteratively updates the node representation by aggregating the neighbor information, where the message passing process (of the neighbor information) is analogous to traverse the graph by walks, defined as follows.

Definition 2 (Walk). *A walk is a sequence of nodes and edges in a graph that can be formed by a traverse that permits backtracking and access to node self-loops.*

Corollary 1. *A message flow of output node u in the computational graph is a walk of the same length that ends at u in the original graph.*

Definition 3 (Trail). *A trail is a succession of graph nodes and edges with no repeating edges, where $tr(i)$ refers to the i-th node of tr (zero based index).*

For instance, $u_1 \rightarrow u_2 \rightarrow u_3 \rightarrow u_1 \rightarrow u_4$ is a valid trail, which has no repeating edges.

Lemma 1. *The message flows that propagate a trail's information are walks of the trail.*

A trail can not be compressed since there is no repeated edges in the trail. As illustrated in Figure 2, we can transform a trail into message flows via unordered sampling with replacement, a sampling fashion in which repetition is allowed and ordering does not matter [14, Section 2.1.4]. Message flows derived from the same trail carry identical trail-related information. And the presence of backtracking edges and self-loop edges in message flows is redundant.

(a) Trail

(b) Sampling Backtracking Edges

(c) Sampling Self-Loop Edges

(d) Derived Message Flow

Figure 2: The process of deriving a message flow from a trail: Firstly, backtracking edges are sampled and placed in the trail. Then, self-loop edges are sampled and inserted into the trail.

Message flow redundancy is prevalent. Without loss of generality, suppose a trail of length r and a message flow of length k derived from the trail. The backtracking edge of a self-loop edge is also a self-loop edge. Thus, we begin by sampling s backtracking edges from the r backtracking edges. After the backtracking edges are placed, we sample $k - r - 2s$ self-loop edges from the $r + 1 + 2s$ self-loop edges.

Lemma 2. *Given a length-r trail, the number of length-k message flows derived from the trail is*

$$\sum_{s=0}^{\lfloor \frac{k-r}{2} \rfloor} r^s (r + 1 + 2s)^{(k-r-2s)}$$

where $1 \leq r \leq k$.

Lemma 2 demonstrates that message flow redundancy is widespread because a shorter trail than the number of GNN layers would result in numerous message flows with backtracking and self-loop edges.

3.2 Redundancy Causes Message Over-squashing

The message flow redundancy in computational graphs comes with a phenomenon named *over-squashing*, which occurs when GNNs are unable to propagate information effectively across a graph

[6]. Recently, Topping et al. [5] have proposed the *Jacobian* of a GNN-output to quantify the effect of over-squashing.

The influence of a change   Given a graph with nodes u and v, as well as a k-layer WL-test based GNN to update node representations. The *Jacobian* measures how a change of the input feature $\mathbf{x}_v$ affects the node output $\mathbf{h}_u^{(k)}$.

$$\partial \mathbf{h}_u^{(k)} / \partial \mathbf{x}_v \tag{3}$$

Similar to [5], to avoid heavy notations, the node attributes and representations are assumed to be scalar; this assumption simplifies the analysis, whereas the vector case yields equivalent results.

Lemma 3. *Given a graph with node set V, nodes $u, v \in V$, and the computational graph of a k-layer WL-test based GNN for u. If all length-k paths in the computational graph of u are activated with the same probability, we can measure the **relative influence of the input feature $\mathbf{x}_v$ on the node output** $\mathbf{h}_u^{(k)}$, on average, as*

$$\mathbb{E}\left(\frac{\partial \mathbf{h}_u^{(k)} / \partial \mathbf{x}_v}{\sum_{v' \in V} \partial \mathbf{h}_u^{(k)} / \partial \mathbf{x}_{v'}} \right) = \frac{\left[\prod_{l=k}^{1} \widetilde{A} \right]_{u,v}}{\sum_{v' \in V} \left[\prod_{l=k}^{1} \widetilde{A} \right]_{u,v'}}, \tag{4}$$

where $\widetilde{A} = A + I$ is the adjacency matrix of the graph with self-loop.

The influence of a change along a message flow   Given a graph, the computational graph of a k-layer WL-test based GNN and its message flow p. The effect of a change in $\mathbf{x}_{p(0)}$ to the output node $\mathbf{h}_{p(k)}^{(k)}$ along the message flow p (a.k.a **the influence of $\mathbf{x}_{p(0)}$ on $\mathbf{h}_{p(k)}^{(k)}$ along p**) can be computed as

$$\frac{\partial \mathbf{h}_{p(k)}^{(k)}}{\partial p} = \prod_{l=k}^{1} \frac{\partial \mathbf{h}_{p(l)}^{(l)}}{\partial \mathbf{h}_{p(l-1)}^{(l-1)}}. \tag{5}$$

Lemma 4. *Given a graph with node set V, the computational graph of a k-layer WL-test based GNN for a node, and its message flow p. We compute **the relative influence of $\mathbf{x}_{p(0)}$ on $\mathbf{h}_{p(k)}^{(k)}$ along p**, on average, as*

$$\mathbb{E}\left(\frac{\partial \mathbf{h}_{p(k)}^{(k)} / \partial p}{\sum_{p' \in P} \partial \mathbf{h}_{p(k)}^{(k)} / \partial p'} \right) = \frac{\prod_{l=k}^{1} \widetilde{A}_{p(l),p(l-1)}}{\sum_{v' \in V} \left[\prod_{l=k}^{1} \widetilde{A} \right]_{p(k),v'}},$$

where $\widetilde{A} = A + I$ is the adjacency matrix of the graph with self-loop and P is the set of message flows that end at $tr(k)$.

The influence of a change along a trail   Given a graph with a trail tr and the computational graph of a k-layer WL-test based GNN for tr's head node. Let P^* be the set of message flows derived from tr within the computational graph for the node $tr(k)$. How a change in $\mathbf{x}_{tr(0)}$ will be propagated along tr and affect $\mathbf{h}_{tr(r)}^{(k)}$ (a.k.a **the influence of $\mathbf{x}_{tr(0)}$ on $\mathbf{h}_{tr(r)}^{(k)}$ along tr**), denoted as $\partial \mathbf{h}_{tr(r)}^{(k)} / \partial tr$, is computed as the summation of the influence of $\mathbf{x}_{tr(0)}$ on $\mathbf{h}_{tr(r)}^{(k)}$ along all message flows belonging to P^*, i.e.,

$$\frac{\partial \mathbf{h}_{tr(r)}^{(k)}}{\partial tr} = \sum_{p' \in P^*} \frac{\partial \mathbf{h}_{tr(r)}^{(k)}}{\partial p'} \tag{6}$$

Corollary 2. *Given a graph with a trail tr and the computational graph of a k-layer WL-test based GNN for tr's head node. We compute **the relative influence along** tr, on average, as*

$$\mathbb{E}\left(\frac{\partial \mathbf{h}_{tr(r)}^{(k)} / \partial tr}{\sum_{p' \in P} \partial \mathbf{h}_{p(k)}^{(k)} / \partial p'} \right) = \frac{\sum_{p' \in P^*} \prod_{r=k}^{1} \widetilde{A}_{p'(r),p'(r-1)}}{\sum_{v' \in V} \left[\prod_{r=k}^{1} \widetilde{A} \right]_{p(k),v'}},$$

where $\widetilde{A} = A + I$ is the adjacency matrix of the graph with self-loop and P^* is the set of message flows derived from tr.

The relative influence along a trail is proportional (in terms of probability) to the number of message flows derived from the trail, according to Corollary 2. According to Lemma 2, a trail typically produces fewer messaging paths than its child trail. Therefore, the effect along a lengthy path is always less than that of its sub-paths. Therefore, **redundancy in the message passing paradigm is a significant element in the occurrence of over-squashing**. Topping et al. [5] stated the phenomenon of over-squashing occurs when the absolute value of the *Jacobian* $\partial \mathbf{h}_u^{(k)} / \partial \mathbf{x}_v$ is small. Supplementally, we find the phenomenon of over-squashing would occur even if the absolute value of the *Jacobian* $\partial \mathbf{h}_u^{(k)} / \partial \mathbf{x}_v$ is large: keeping the influence along tr constant, the relative influence along tr decrease as the absolute value of the *Jacobian* $\partial \mathbf{h}_{tr(k)}^{(k)} / \partial \mathbf{x}_{tr(0)}$ increases.

4 Redundancy-Free Graph Neural Network

In the last section, we have discussed message flow redundancy and its practical implications. To overcome this issue, we propose Redundancy-Free GNN (RFGNN), a kind of message passing GNN which is not only message flow redundancy-free but also improves the overall expressive power, message passing capability, and thus generates better performance. All proofs for RFGNN can be found in Appendix B, and the space and time complexity analysis can be found in Appendix C.

4.1 The RFGNN Framework

We first discuss the redundancy-free message passing paradigm based on a concept called extended path, $epath$, formally defined as

Definition 4 (Extended Path, $epath$). *An epath is a path that has no repeated node along the path except that the starting node is allowed to be the ending node when the length of the path is larger than 2.*

For instance, $u_1 \rightarrow u_2 \rightarrow u_3 \rightarrow u_1$ is an epath but not a path, since u_1 is repeated at the ending node. Note that $u_1 \rightarrow u_2 \rightarrow u_1$ is not an epath since the length is not larger than 2.

A *component* of a graph is a connected subgraph that is not part of any larger connected subgraph [15]. BFS [12] allows us to traverse all epaths of a component from a node. On the basis of epath and BFS [12], we define the term Truncated ePath Tree (TPT) as follows:

(a) Input Graph   (b) Process of ePaths Search

Figure 3: The height-4 Truncated ePath Tree of G from u (hexagon).

Definition 5 (Truncated ePath Tree (TPT)). *Given a graph $G = (V, E)$ and a node $u \in V$, the height-k TPT $\text{TPT}_{(G,u)}^k$ is an epath search tree obtained by running a BFS from u, where all epaths of length up to k are accessed.*

As shown in Figure 3, the original graph can form a height-4 truncated epath tree (TPT) as a tree structure of 8 nodes, where every tree path (from the root to the leaf) is an epath of length smaller than or equal to 4. For ease of discussion, given a node v on level k, we define $\mathcal{C}^k(v)$ as the child node set of the node v.

Definition 6 (Truncated ePaths Forest (TPF)). *Given a graph $G = (V, E)$, the height-k TPF of G is a multiset for all nodes $u \in V$ as*

$$\text{TPF}_G^k := \left\{ \left\{ \text{TPT}_{(G,u)}^k \mid \forall u \in V \right\} \right\}.$$

Redundancy-Free Graph Neural Network (RFGNN). Given $\text{TPT} \in \text{TPF}_G$ and $u \in \mathcal{V}(\text{TPT})$ at level $(l-1)$. We denote $\mathbf{x}_u^{(l-1)}$ as a hidden feature transformed from the node features of u, $\mathbf{h}_v^{(l)}$ as a hidden feature of the subtree rooted at node $v \in \mathcal{C}^{(l-1)}(u)$, and $\mathbf{e}_{u,v}^{(l)}$ as a hidden feature transformed from the edge features of (u, v). We can describe the RFGNN representation update process of a node u at level $(l-1)$ as follows.

$$\mathbf{h}_u^{(l-1)} = \psi^{(l)}\left(\mathbf{x}_u^{(l-1)}, \cup_{v \in \mathcal{C}^{(l-1)}(u)} \phi^{(l)}\left(\mathbf{e}_{u,v}^{(l)}, \mathbf{h}_v^{(l)}\right)\right), \tag{7}$$

where $\cup$ denotes a differentiable and permutation invariant function, e.g., *sum* and *mean*, and ϕ and ψ denote differentiable functions such as MLPs (Multi Layer Perceptrons).

To obtain the entire graph representation $\mathbf{h}_G$, we adopt a readout function χ as in Equation 8 that aggregates the root node representations of the TPTs.

$$\mathbf{h}_G = \chi\left(\left\{\mathbf{h}_{root(\text{TPT})}^{(0)} \mid \text{TPT} \in \text{TPF}_G\right\}\right), \tag{8}$$

where the readout function χ can be a simple permutation invariant function such as *sum*.

Symmetries. Given a graph G with adjacency matrix A and feature matrix $\mathbf{x}$, a function f is (node) permutation equivalent if $f(A, \mathbf{x}) = f\left(MAM^T, M\mathbf{x}\right)$, for any permutation matrix M. GNN layers respect this equation, which ensures they compute the same functions up to a permutation (i.e., relabeling) of the nodes. Similarly, RFGNN is equivalent with respect to permutations of nodes, since the resulted TPTs and TPF is independent on any node permutation.

Corollary 3. *Redundancy-Free GNNs are permutation equivalent.*

Memory consumption Even RFGNN can provide better expressive power than WL-test based GNNs. However, its memory consumption may also be higher since it requires constructing a Truncated ePath Forest (TPF). In the future work, we will carefully study potential techniques, e.g., common paths consolidation, to overcome this issue.

4.2 The Expressive Power of RFGNN

1-WL is recognized as an indicator for the expressive power of GNNs [16, 17, 18]. In line with these work, we measure the expressive power of our model using a hashing procedure of TPFs. We first define the hashing procedure of TPFs (TPFH), Then, we prove that TPFH has the most expressive power if it is sufficiently high, and the height-k TPFH is strictly more expressive than the 1-WL test of k rounds.

TPF Hashing (TPFH). The height-k TPFH is a hashing scheme for height-k TPFs, which is a generalization of 1-WL [1]. In short, the hashing scheme is to assign labels to all nodes. For ease of discussion, we first denote $u^{(l)} \in \text{TPT}$ as a node u at level l of a TPT TPT. Let $c_u^{(l)}$ be the label assigned to $u^{(l)}$ and let $t_u^{(l)}$ be the label assigned to the tree rooted at $u^{(l)}$. We initialize the tree labels of nodes at level k by their labels in the original graph. The hashing procedure is conducted recursively from the level $(k-1)$ to the root. Specifically, we collect the tree labels of the child nodes of u, denoted as $\{\{t_v^{(l+1)} \mid \forall v \in \mathcal{C}^{(l)}(u)\}\}$ (note it would be a null multiset if node u has no child nodes). Then, we compute the tree label of u by an injective mapping, $t_u^{(l)} = \text{HASH}(c_u^{(l)}, \{\{t_v^{(l+1)} \mid \forall v \in \mathcal{C}^{(l)}(u)\}\})$, where HASH is a perfect hash function. Finally, we collect labels of all TPTs of a TPF as a multiset and injectively map it into a label by a perfect

hash function. Two graphs are considered non-isomorphic if the labels of their TPFs are not equal. Otherwise, the test is inconclusive.

Lemma 5. *Non-isomorphic graphs will generate non-isomorphic TPFs if the TPFs are sufficiently high.*

According to Lemma 5, the hashing of TPFs with enough height can assign different labels to non-isomorphic graphs. In other words, TPFH has the most expressive power to separate non-isomorphic graphs.

Lemma 6. *For two graphs G_1 and G_2, and two nodes $u \in \mathcal{V}(G_1)$ and $v \in \mathcal{V}(G_2)$, if the height-k WL-subtree of u is non-isomorphic to that of v, the height-k TPTs of them are non-isomorphic too.*

Lemma 7. *There exist two graphs G_1 and G_2 and two nodes, $u \in \mathcal{V}(G_1)$ and $v \in \mathcal{V}(G_2)$, where the height-k WL-subtree of u is isomorphic to that of v, but the height-k TPTs of them are non-isomorphic.*

According to Lemma 6 and Lemma 7, the expressive power of height-k TPFH is better than that of 1-WL with k iterations. Similar to the proof in WL-test based GNNs [16], RFGNN can be shown to provide the same expressive power of TPFH when each layer of RFGNN are equipped with a sufficient number of layers and the parametric local aggregators they use can learn to be injective.

4.3   Advantages of RFGNN

We attempt to investigate what a RFGNN has learned by measuring how the output of a height-k RFGNN, as in Equation 7 , is influenced by input values and hidden representations.

Lemma 8. *Assume a height-k RFGNN as in Equation 7, a graph G, and an epath ep in G of length $l \leq k$. We can measure the **influence of the node feature** $\mathbf{x}_{ep[i]}^{(i)}$ **on the tree representation** $\mathbf{h}_{ep[0]}^{(0)}$, where $0 \leq i \leq l$, as*

$$\frac{\partial \mathbf{h}_{ep[0]}^{(0)}}{\partial \mathbf{x}_{ep[i]}} = \left(\prod_{j=0}^{i-1} \left(\partial_2 \psi^{(j)} \partial_2 \phi^{(j)} \right) \right) \left(\partial_{\mathbf{x}_{ep[i]}} \psi^{(i)} + \partial_2 \psi^{(i)} \partial_{\mathbf{x}_{ep[i]}} \phi^{(i)} \right)$$

*Similarly, we can measure the **influence of the tree representation** $\mathbf{h}_{ep[i]}^{(i)}$ **on the tree representation** $\mathbf{h}_{ep[0]}^{(0)}$, where $0 \leq i \leq l$, as*

$$\frac{\partial \mathbf{h}_{ep[0]}^{(0)}}{\partial \mathbf{h}_{ep[i]}^{(i)}} = \left(\prod_{j=0}^{i-1} \left(\partial_2 \psi^{(j)} \partial_2 \phi^{(j)} \right) \right) \partial_2 \psi^{(i)} \partial_{\mathbf{h}_{ep[i]}^{(i)}} \phi^{(i)}$$

Avoid over-quashing.   Lemma 8 points out that if all edges in the computational graph of a RFGNN is activated with the same probability, on average, epaths starting with the same node and having the same length would have the same influence on their shared starting node. This is similar to the finding of [19, 5]. Thus, the problem of over-squashing induced by message flow redundancy in the computational graph is avoided.

Capture subgraphs at multiple levels of granularity.   An ideal method of graph similarity measurement should be able to capture subgraphs at different levels of granularity [11]. GIN [16] achieve this by an architecture similar to Jumping Knowledge Networks [20], which concatenates node representations across all layers. In contrast, RFGNN can directly detect the presence of subtrees of arbitrary heights of TPTs by deactivating information about trees (rooted nodes in TPTs) that do not belong to subtrees.

Graph similarity comparison and graph overlap detection.   Intuitively, GNNs should be able to encode graphs with near graph edit distance (GED) [21] into similar representations. As stated in the introduction, WL-test based GNNs would generate vastly different message passing graphs for similar graphs. According to Lemma 9, RFGNN always generate similar message passing graphs for similar graphs, which could learn better representations of similar graphs than WL-test based GNNs. Besides, RFGNN could handle the graph overlapping structure better than WL-test based GNNs since overlapping subgraphs always generate a large number of the same epaths in the computational graphs (and thus overlapping subgraphs can be captured). Note that RFGNN could generate fewer message flows than other WL-test based GNNs due to the redundancy-free property.

Lemma 9. *Given a graph $G = (V, E)$, a node $u \in V$, and an edge $e \in E$ within the k-hop neighborhood of u. Let n be the number of rings in the k-hop neighborhood of u. We have that the number of repeations of e within the height-k TPT of u is no more than $1 + n$.*

5 Related Work

Higher order GNNs. Recently, higher expressive GNNs have been developed, which based on enhanced WL algorithms. such as PPGN (based on k-WL) [17], 1-2-3-GNN (based on k-WL) [22], CWNs (based on Cellular WL) [23], and Nested GNNs (based on Nested 1-WL) [24]. Nonetheless, none of them breaks the iterative aggregation-update scheme.

Over-squashing issue. The *Jacobian* of a GNN-output is limited by a term given as the power of the graph normalised adjacency matrix [5]. And, [6, 5] both argued that small absolute values of the *Jacobian* are indicative of poor information propagation or over-squashing. Furthermore, [5] investigated graphs from a Ricci curvature perspective and demonstrated how negative curved edges contribute to the problem of over-squashing. In this work, we prove that the redundancy in the computational graph is one key factor for the over-squashing issue, indicating that the over-squashing phenomenon will occur regardless of the absolute value of the *Jacobian*.

Graph kernels. Graph kernels are frequently employed to measure the similarities between graphs by decomposing graphs into substructures and comparing these substructures [25]. The measurement of graph similarity could be utilized for subsequent tasks such as classifications [25]. In comparison to earlier graph kernels, Tree++ [7] has the highest classification accuracy on numerous benchmark datasets. The main reason for its success is that this method allows comparing graphs at multiple levels of granularity.

6 Experiments

We examine the performance of RFGNN and compare it with that of baseline approaches.

First, we evaluate RFGNN by conducting a series of supervised graph classification tasks on 5 bioinformatics datasets (NCI1 [26], PTC [27], MUTAG [28], PROTEINS [29], ENZYMES [29]) and 3 small molecules datasets (BZR [30], COX2 [30], DHFR [30]). We adopted two different sorts of baselines: graph kernels (such as WL-subtree [3] and Tree++ [7]) and GNNs (such as GIN [16], PPGN [18], 1-2-3-GNN [22], and CIN [23]). We applied RFGNN with a height of 3. ϕ and ψ functions in Equation 7 are an identify mapping (because because all these datasets have no edge attributes) and a 2-layer MLP, respectively. The experiment configurations follows that of GIN [16], such as the number of hidden units (32), batch size (128), 10-fold cross validation, the number of epochs (350), and learning rate (initialized as 0.01 decayed by 0.5 every 50 epochs). Configurations of baselines are follow their original papers. These experiments were run on a Linux server with 64GB memory, one GeForce GTX 1070 (8G) GPU and an Intel 16-core i9-9900K CPU. Due to the lack of executable codes, some Tree++ results are missing. In addition, a 1-2-3-GNN result is missing, because of out-of-memory error.

The data set statistics and the test set classification accuracy of RFGNN and baselines are shown in Table 1. We see that RFGNN outperforms GIN and even high order GNNs on most datasets, supporting our argument that RFGNN is a theoretically sound method for improving GNN performance.

To further evaluate the ability to model long-range interactions and the capacity to quantify graph similarity of RFGNN, we computed and compared the performance of RFGNNs with heights ranging from 6 to 8 and baseline approaches on QM9 [31, 32], a graph dataset with 12 regression tasks. QM9 [31, 32] contains 130K small molecules. The task here is to separately perform regressions on 12 targets representing energetic, electronic, geometric, and thermodynamic properties, based on the graph structure and node/edge features. All evaluation metrics are mean absolute error (MAE). We use a *sum* aggregator to obtain graph representations. $\phi^{(l)}$ and $\psi^{(l)}$ in Equation 7 both are 2-layer MLPs. All other settings follow [24]. These experiments were run on a Linux server with 376.6GB memory, 6 NVIDIA RTX A6000 (47.5 GiB) GPUs and four Intel(R) Xeon(R) Gold 18-core 6240 CPUs.

Table 1: Statistics of the datasets and performance comparison.

Datasets	MUTAG	PROTEINS	PTC	NCI1	ENZYMES	BZR	COX2	DHFR
#graphs	188	1113	344	4110	600	405	467	756
#classes	2	2	2	2	6	2	2	2
Avg. #nodes	17.93	39.06	25.56	29.87	32.63	35.75	41.22	42.43
Avg. #edges	19.79	72.82	25.96	32.30	62.14	38.36	43.44	44.54
TPF Avg. # nodes	232.84	2165.3	336.56	376.48	1908.11	503.12	564.87	563.00
TPF Avg. # edges	216.77	2160.0	311.41	349.05	1904.98	469.98	525.87	522.69
WL subtree	90.4 ± 5.7	75.0 ± 3.1	59.9 ± 4.3	$\mathbf{86.0 \pm 1.8}$	62.6 ± 1.2	87.3 ± 0.8	81.2 ± 1.1	82.4 ± 0.9
Tree++	–	75.5 ± 0.5	–	85.8 ± 0.1	–	87.9 ± 1.0	84.3 ± 0.9	83.7 ± 0.6
GIN	90.0 ± 8.8	76.2 ± 2.8	64.6 ± 7.0	82.7 ± 1.7	$72.5 \pm 6.1,$	89.9 ± 3.8	$\mathbf{87.6 \pm 4.0}$	82.9 ± 3.9
1-2-3-GNN	92.2 ± 4.4	77.3 ± 4.2	67.6 ± 5.5	61.0 ± 5.3	–	82.0 ± 3.3	78.7 ± 1.3	63.4 ± 4.9
PPGN	90.6 ± 8.7	77.2 ± 4.7	66.2 ± 6.5	83.2 ± 1.1	63.3 ± 11.8	89.4 ± 4.0	86.7 ± 4.1	79.6 ± 4.5
CIN	92.7 ± 6.1	77.0 ± 4.3	68.2 ± 5.6	83.6 ± 1.4	62.6 ± 8.1	78.8 ± 1.0	78.4 ± 1.1	68.1 ± 3.1
RFGNN	$\mathbf{93.3 \pm 6.0}$	$\mathbf{77.5 \pm 3.4}$	$\mathbf{71.5 \pm 3.2}$	83.6 ± 1.6	$\mathbf{75.3 \pm 5.0}$	$\mathbf{90.9 \pm 3.2}$	87.4 ± 4.6	$\mathbf{84.5 \pm 4.6}$

We report the average test MAE across 10 folds. We show the QM9 results in Table 2. The results of baseline methods are extracted from [24]. We highlight the results of RFGNNs if they are better than those of baselines. Several positive conclusions can be drawn from the experimental results: (1) RFGNNs achieved the best results on 7 out of 12 prediction targets, which means RFGNNs have better performance on measuring graph similarity. (2) The performance of RFGNN increases with increasing height on several targets, which underlines the need for modeling long-range interactions in these targets. (3) Ne. 1-GNN has the potential to model longer-range interactions better than RFGNN-8 due to its deeper layers; however, Ne. 1-GNN does not perform better than RFGNN-8. We believe that redundancy-free message passing allows RFGNN to model long-range interactions more competently than Ne. 1-GNN, as Ne. 1-GNN's message passing is redundant.

Table 2: MAE results on QM9 (smaller the better)

Target	μ	α	$\varepsilon_{\text{HOMO}}$	$\varepsilon_{\text{LUMO}}$	$\Delta\varepsilon$	$\langle R^2 \rangle$	ZPVE	U_0	U	H	G	C_v
DTNN [33]	$\mathbf{0.244}$	0.95	0.00388	0.00512	0.0112	17.0	0.00172	2.43	2.43	2.43	2.43	0.27
MPNN [2]	0.358	0.89	0.00541	0.00623	0.0066	28.5	0.00216	2.05	2.00	2.02	2.02	0.42
Deep LRP [34]	0.364	0.298	0.00254	0.00277	0.00353	19.3	0.00055	0.413	0.413	0.413	0.413	0.129
1-GNN [22]	0.493	0.78	0.00321	0.00355	0.0049	34.1	0.00124	2.32	2.08	2.23	1.94	0.27
1-2-GNN [22]	0.493	0.27	0.00331	0.00350	0.0047	21.5	0.00018	$\mathbf{0.0357}$	0.107	0.070	0.140	0.0989
1-3-GNN [22]	0.473	0.46	0.00328	0.00354	0.0046	25.8	0.00064	0.6855	0.686	0.794	0.587	0.158
1-2-3-GNN [22]	0.476	0.27	0.00337	0.00351	0.0048	22.9	0.00019	0.0427	0.111	$\mathbf{0.0419}$	$\mathbf{0.0469}$	0.0944
Ne. 1-GNN [24]	0.428	0.29	0.00265	0.00297	0.0038	20.5	0.00020	0.295	0.361	0.305	0.489	0.174
Ne. 1-2-GNN [24]	0.437	0.278	0.00275	0.00271	0.0039	20.4	0.00017	0.252	0.265	0.241	0.272	0.0891
Ne. 1-3-GNN [24]	0.436	0.261	0.00265	0.00269	0.0039	20.2	0.00017	0.291	0.278	0.267	0.287	0.0879
Ne. 1-2-3-GNN [24]	0.433	0.265	0.00279	0.00276	0.0039	20.1	$\mathbf{0.00015}$	0.205	0.200	0.249	0.253	0.0811
RFGNN-6	0.323	0.216	$\mathbf{0.00204}$	0.00206	$\mathbf{0.00311}$	$\mathbf{14.277}$	0.000156	0.0997	0.1257	0.1153	0.1103	$\mathbf{0.07720}$
RFGNN-7	0.318	$\mathbf{0.209}$	$\mathbf{0.00200}$	0.00205	$\mathbf{0.00310}$	14.316	0.000162	0.1082	0.1149	0.1101	0.1099	$\mathbf{0.07420}$
RFGNN-8	0.322	$\mathbf{0.208}$	$\mathbf{0.00200}$	0.00205	0.00314	14.057	0.000159	0.0775	$\mathbf{0.0741}$	0.0744	0.1015	$\mathbf{0.07485}$

We implement RFGNN based on the Deep Graph Library (DGL) [35]. Our code is available at **TODO**.

7 Conclusions

In this work, we carefully investigated the message flow redundancy issue in recent GNNs and its implications. In particular, we have proved that message flow redundancy is one key factor in the over-squashing phenomenon. To address the message flow redundancy issue, we have proposed Redundancy-Free Graph Neural Networks (RFGNN), which conducts redundancy-free message passing. Theoretically, we demonstrate the benefits of our method, and experimentally, we show that our RFGNN outperforms existing WL-test based GNNs on a large number of graph property prediction challenges.

References

[1] Boris J Weisfeiler and Andrei A Lehman. A reduction of a graph to a canonical form and an algebra arising during this reduction. nauchno-technicheskaya informatsiya, 2 (9): 12–16, 1968.

[2] Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. *ArXiv*, abs/1704.01212, 2017.

[3] Nino Shervashidze, Pascal Schweitzer, Erik Jan van Leeuwen, Kurt Mehlhorn, and Karsten M. Borgwardt. Weisfeiler-Lehman Graph Kernels. *Journal of Machine Learning Research*, 12(77):2539–2561, 2011.

[4] Zhihao Jia, Sina Lin, Rex Ying, Jiaxuan You, Jure Leskovec, and Alexander Aiken. Redundancy-free computation for graph neural networks. *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2020.

[5] Jake Topping, Francesco Di Giovanni, Benjamin Paul Chamberlain, Xiaowen Dong, and Michael M. Bronstein. Understanding over-squashing and bottlenecks on graphs via curvature. In *International Conference on Learning Representations*, 2022.

[6] Uri Alon and Eran Yahav. On the bottleneck of graph neural networks and its practical implications. In *9th International Conference on Learning Representations, ICLR 2021*, 2021.

[7] Wei Ye, Zhen Wang, Rachel Redberg, and Ambuj K. Singh. Tree++: Truncated tree based graph kernels. *IEEE Transactions on Knowledge and Data Engineering*, 33:1778–1789, 2021.

[8] Yu Su, Fangqiu Han, Richard E Harang, and Xifeng Yan. A fast kernel for attributed graphs. In *Proceedings of the 2016 SIAM international conference on data mining*, pages 486–494. SIAM, 2016.

[9] Giannis Nikolentzos, Polykarpos Meladianos, and Michalis Vazirgiannis. Matching node embeddings for graph similarity. In *Thirty-first AAAI conference on artificial intelligence*, 2017.

[10] Nino Shervashidze, Pascal Schweitzer, Erik Jan Van Leeuwen, Kurt Mehlhorn, and Karsten M Borgwardt. Weisfeiler-lehman graph kernels. *Journal of Machine Learning Research*, 12(9), 2011.

[11] Anton Tsitsulin, Davide Mottin, Panagiotis Karras, Alexander M. Bronstein, and Emmanuel Müller. Netlsd: Hearing the shape of a graph. *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2018.

[12] Wikipedia contributors. Breadth-first search — Wikipedia, the free encyclopedia. https://en.wikipedia.org/w/index.php?title=Breadth-first_search&oldid=1091199031, 2022.

[13] Michael Collins. Computational graphs, and backpropagation. *Lecture Notes, Columbia University.*, pages 11–23, 2018.

[14] Hossein Pishro-Nik. *Introduction to probability, statistics, and random processes*. Amazon, 2016.

[15] Wikipedia contributors. Component (graph theory) — Wikipedia, the free encyclopedia, 2022. [Online; accessed 9-October-2022].

[16] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019.

[17] Haggai Maron, Heli Ben-Hamu, Nadav Shamir, and Yaron Lipman. Invariant and equivariant graph networks. *ArXiv*, abs/1812.09902, 2019.

[18] Haggai Maron, Heli Ben-Hamu, Hadar Serviansky, and Yaron Lipman. Provably powerful graph networks. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 2153–2164, 2019.

[19] Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In *ICML*, pages 5449–5458, 2018.

[20] Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In *ICML*, 2018.

[21] Xinbo Gao, Bing Xiao, Dacheng Tao, and Xuelong Li. A survey of graph edit distance. *Pattern Analysis and applications*, 13(1):113–129, 2010.

[22] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. *ArXiv*, abs/1810.02244, 2019.

[23] Cristian Bodnar, Fabrizio Frasca, Nina Otter, Yu Guang Wang, Pietro Lio', Guido Montúfar, and Michael M. Bronstein. Weisfeiler and lehman go cellular: Cw networks. In *NeurIPS*, 2021.

[24] Muhan Zhang and Pan Li. Nested graph neural networks. *Advances in Neural Information Processing Systems*, 34, 2021.

[25] Nils M. Kriege, Fredrik D. Johansson, and Christopher Morris. A survey on graph kernels. *Applied Network Science*, 5:1–42, 2020.

[26] John Boaz Lee, Ryan Rossi, and Xiangnan Kong. Graph classification using structural attention. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1666–1674, 2018.

[27] Hannu Toivonen, Ashwin Srinivasan, Ross D King, Stefan Kramer, and Christoph Helma. Statistical evaluation of the predictive toxicology challenge 2000–2001. *Bioinformatics*, 19(10):1183–1193, 2003.

[28] Asim Kumar Debnath, Rosa L Lopez de Compadre, Gargi Debnath, Alan J Shusterman, and Corwin Hansch. Structure-activity relationship of mutagenic aromatic and heteroaromatic nitro compounds. correlation with molecular orbital energies and hydrophobicity. *Journal of medicinal chemistry*, 34(2):786–797, 1991.

[29] Karsten M Borgwardt, Cheng Soon Ong, Stefan Schönauer, SVN Vishwanathan, Alex J Smola, and Hans-Peter Kriegel. Protein function prediction via graph kernels. *Bioinformatics*, 21(suppl_1):i47–i56, 2005.

[30] Jeffrey J. Sutherland, Lee A. O'Brien, and Donald F. Weaver. Spline-fitting with a genetic algorithm: A method for developing classification structure-activity relationships. *Journal of chemical information and computer sciences*, 43 6:1906–15, 2003.

[31] Raghunathan Ramakrishnan, Pavlo O. Dral, Matthias Rupp, and O. Anatole von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific Data*, 1, 2014.

[32] Zhenqin Wu, Bharath Ramsundar, Evan N. Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S. Pappu, Karl Leswing, and Vijay S. Pande. Moleculenet: A benchmark for molecular machine learning. *arXiv: Learning*, 2017.

[33] Kristof T. Schütt, Farhad Arbabzadah, Stefan Chmiela, Klaus-Robert Müller, and Alexandre Tkatchenko. Quantum-chemical insights from deep tensor neural networks. *Nature Communications*, 8, 2017.

[34] Zhengdao Chen, Lei Chen, Soledad Villar, and Joan Bruna. Can graph neural networks count substructures? *ArXiv*, abs/2002.04025, 2020.

[35] Minjie Wang, Da Zheng, Zihao Ye, Quan Gan, Mufei Li, Xiang Song, Jinjing Zhou, Chao Ma, Lingfan Yu, Yujie Gai, Tianjun Xiao, Tong He, George Karypis, Jinyang Li, and Zheng Zhang. Deep graph library: A graph-centric, highly-performant package for graph neural networks. *arXiv: Learning*, 2019.