Assistive Teaching of Motor Control Tasks to Humans

Abstract

Recent works on shared autonomy and assistive-AI technologies, such as assistive robotic teleoperation, seek to model and help human users with limited ability in a fixed task. However, these approaches often fail to account for humans' ability to adapt and eventually learn how to execute a control task themselves. Furthermore, in applications where it may be desirable for a human to intervene, these methods may have inhibited their ability to learn how to succeed with full self-control. In this paper, we focus on the problem of *assistive teaching* of motor control tasks such as parking a car or landing an aircraft. Despite their ubiquitous role in humans' daily activities and occupations, motor tasks are rarely taught in a uniform way due to their high complexity and variance. We propose an AI-assisted teaching algorithm that leverages skill discovery methods from reinforcement learning (RL) literature to (i) break down any motor control task into teachable skills, (ii) construct novel drill sequences, and (iii) individualize curricula to students with different capabilities. Through an extensive mix of synthetic and user studies on two motor control tasks—parking a car with a joystick and writing characters from the Balinese alphabet—we show that assisted teaching with skills improve student performance by around 40% compared to practicing full trajectories without skills, and practicing with individualized drills can result in up to 25% further improvement.

1 Introduction

Imagine a novice human is tasked with operating a machine with challenging or unfamiliar controls, such as landing an aircraft or parking an oversized vehicle with novel transmission. A fully autonomous form of assistance, such as a self-driving car, would aid this user by entirely replacing their control, seeking interventions only when necessary. Shared autonomous systems, such as those used in robot assistive teleoperation [1, 2, 3], would seek to model the human's goals and capabilities, and provide assistance in the form of corrections [4] or simplified control spaces [3]. However, neither form of assistance would actually help the user *learn* how to successfully operate the machine, and may even serve as a crutch that prevents their ability to ever perform the task independently.

Although humans can learn a variety of complex motor control tasks (e.g., driving a car, or operating surgical robots), they often rely on the assistance of specialized teachers. Receiving fine-grained instruction from these specialized teachers can often be non-uniform, costly, and limited by their availability. Here, we are interested in a more accessible and efficient approach: we wish to develop an AI-assisted teaching algorithm capable of teaching motor control tasks in an individualized manner. While several works leveraged AI techniques to aid instruction in traditional education tasks such as arithmetic [5, 6, 7] and foreign language learning [8, 9], motor control tasks introduce several unique challenges, such as the high complexity of the input and output space for motor control tasks (e.g., controlling a high degree freedom robotic arm with a 6 degrees of freedom joystick or the continuous output space of trajectories in driving), as well as the need for generalization across seemingly different scenarios in these high-dimensional and complex spaces.

To address these challenges, our insight is to utilize compositional motor skills for teaching: skills are more manageable to teach, and can be used to construct novel compositional drills for an individual. We take inspiration from how specialized human teachers teach motor control tasks. For example, a piano teacher may assign a student structured exercises (e.g., musical scales or arpeggios) to build up their general technique. Further, they may guide the student to break down complex musical phrases into more manageable chunks, repeatedly practice those, and then compose them together [10].

However, such fine-grained teaching often requires access to a specialized teacher capable of identifying skills and creating individualized drills based on a students' unique expertise. This is not only expensive, but can be highly suboptimal for many motor control tasks where a teacher may not have full visibility into the student's various inputs for a task (e.g. how much the student pushed the brake pedal), but only observability of the final behavior of the system (e.g. how close the vehicle is to the curbside), leading to less meaningful feedback. Can we leverage the rich action data provided by students learning motor control tasks to develop more efficient and reliable individualized instruction?

Our key insight is to leverage automated skill discovery methods from the RL literature to break down motor control tasks performed by an expert into *teachable skills*. We then identify which of the expert's skills are skills that the student is struggling with, and construct *novel drills* that focus on those particular skills to *individualize* their curriculum. Our contributions include: 1) Developing an algorithm to identify which skills of a motor control task a student struggles with, 2) Automatically creating individualized drills based on students' expertise in various skills, and 3) Empirically validating the helpfulness of our AI-assisted teaching framework in two different motor control tasks: controlling a simulated vehicle to park with an unintuitive joystick, and writing Balinese words using a computer mouse or trackpad. Our results show that assisted teaching with skills improve student performance by around 40% compared to practicing full trajectories without skills, and practicing with individualized drills can result in up to 25% further improvement.

2   Related work

Skill discovery in Reinforcement Learning. A large body of work has studied how to leverage behavioral primitives, or skills in RL. Hierarchical RL approaches [11, 12] use skills as temporal abstractions to accelerate learning [13, 14, 15]. However, hand-designing skills can be difficult, especially in continuous spaces. Several works proposed methods to automatically discover skills [16, 17, 18, 19, 20]. Works in unsupervised skill discovery derive task-agnostic skills directly from an environment, without a reward function [21, 22, 23, 24, 25, 26]. Skills can also be learned from a set of tasks [27] or demonstrations [28, 29]; e.g., CompILE [28] learns to segment and reconstruct given trajectories, using learned segment encodings to represent skills. Rather than using discovered skills to aid the learning of automated agents (e.g., via RL or planning [23, 24, 25]), we investigate the novel application of discovered skills to teaching *humans*.

Assistive human-AI systems. Human-AI collaborative systems have the potential to augment a human's individual capabilities. In the paradigm of *shared autonomy* [30], an AI assistant modulates a user's input on tasks such as robot teleoperation [1, 2, 3]. Unlike our work, these works generally assume the human's policy is fixed, and do not directly aim for a human to learn from the AI agent [4]. Bragg et al. [31] improve both collaborative performance and user learning in a shared autonomy framework, but they rely on simulated users in their evaluation. We present a technique to support human learning to improve individual proficiency, and rigorously evaluate it on real users.

AI-assisted teaching. A distinct line of work has focused on developing algorithms for helping humans learn. *Knowledge tracing* attempts to model a student's knowledge state in terms of skills relevant to a set of tasks, yet have generally required manual skill annotations [32] or large-scale student data [33]. *Instructional sequencing* uses a model of student learning to select a sequence of instructional activities to maximize learning, but approaches have generally focused on domains like language learning, arithmetic, and logic [34]. Relatedly, *machine teaching* [35] explores the problem of selecting optimal training data for a student with a known model of learning, and has been effective in discrete domains with structured knowledge such as mathematics and visual classification [36].

We build on the idea that a student's proficiency can be represented in terms of different skills, and an AI assistant can adapt a curriculum accordingly. However, to the best of our knowledge, we are the first to explore how to teach motor control tasks informed by student actions. This setup has unique challenges: it is less obvious how to delineate skills, how to handle student feedback (in the form of

continuous trajectories), and how to measure a student's proficiency at a skill. We leverage advances from skill discovery in RL, and do not require expert annotation of skills nor large-scale student data.

Motor learning in humans. *Motor skill learning* in psychology refers to the acquisition of skilled actions as a result of practice or experience [37, 38]. Our approach is informed by several theories in motor learning and specifically the common insights that human motor control operates hierarchically, and that direct practice of individual skills generally aids skill learning [37, 39].

3 Formulation

In this section, we formalize the problem of *Student-Aware AI-Assisted Teaching*. We go over preliminaries and formalize skill discovery, and then define the problem statement leading to our 3-step approach of teaching complex motor control tasks: (i) distilling tasks into underlying skills, (ii) identifying the student's proficiency, and (iii) creating novel and individualized curricula.

3.1 Preliminaries

We formalize the target motor control task as a standard Markov decision process (MDP) $\langle \mathcal{S}, \mathcal{A}, \rho, f, R, T \rangle$ with finite horizon T, where ρ is the initial state distribution and f is a deterministic transition function. In our formulation, R is a random variable for reward functions such that each $r \sim R$ is a function $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$. Given an initial state $s_0 \sim \rho$ and a reward function $r \sim R$ (both of which are revealed at the beginning of the task), the goal is to maximize the cumulative reward over the horizon. We call any (s_0, r) pair a scenario ξ drawn from a set of all possible scenarios Ξ. We assume access to a set of expert demonstrations, e.g., demonstrations drawn from a pre-trained RL agent that optimizes the cumulative reward for any given scenario.

An inexperienced human would lack the expertise to perform optimally in a given scenario ξ. Our goal is to develop teaching algorithms that leverage expert demonstrations to improve student performance. For example, we want a human unfamiliar with Balinese to learn to write any Balinese word, which would correspond to one r. For this, we develop an algorithm that uses skill discovery methods to automatically create individualized drills based on the discovered skills and the student performance.

Skill discovery. Humans often break down complex tasks into relevant skills (i.e., compositional action sequences that lead to high performance)—when learning how to write, we first master how to write letters, and then compose them to write words and sentences. We define a skill as a latent variable m that lies in some finite discrete latent space $\mathcal{M}$. Each skill is an embedding that corresponds to an action sequence $\Lambda = (a_1, a_2, \ldots, a_{|\Lambda|})$ optimal at some state $s \in \mathcal{S}$ under some reward $r \sim R$:

$$\exists s \in \mathcal{S}, \exists r : \quad P(R = r) > 0, \quad \Lambda = \underset{a_1, a_2, \ldots, a_{|\Lambda|}}{\arg\max} \; (r(s, a_1) + r(f(s, a_1), a_2) + \ldots) \,, \quad (1)$$

and $|\Lambda| \in [H_{\min}, H_{\max}]$, where $H_{\min}$ and $H_{\max} \ll T$ are hyperparameters.

In many tasks, it is difficult to enumerate all possible skills, and it is often not clear when a skill starts and ends in a trajectory. In this work, we use skill discovery algorithms to automatically extract skills relevant to a task, and then teach the student those generated skills. While our teaching method is agnostic to the skill discovery algorithm, we use CompILE [28] as it learns skills directly from expert trajectories. Our formulation assumes access to expert trajectories, so it would be unnecessary to learn an expert policy in parallel with the skill discovery process, as several other methods do.

We use the trained CompILE as a function: SKILLEXTRACTOR(τ) where τ is a trajectory. It outputs a sequence of skills $M^\tau = (m_1^\tau, m_2^\tau, \ldots)$ and intervals $B^\tau = \big((b_{1,1}^\tau, b_{1,2}^\tau), (b_{2,1}^\tau, b_{2,2}^\tau), \ldots\big)$ such that $0 = b_0^\tau \leq b_1^\tau \leq \cdots \leq b_{N_{\text{seg}}}^\tau = T$. The intervals divide τ into N_{seg} *segments*. Actions in τ between time steps $[b_{j,1}^\tau, b_{j,2}^\tau)$ correspond to skill $m_j^\tau \in \mathcal{M}$. Effectively, CompILE learns to divide trajectories into segments, and cluster segments with similar actions into skills. We refer to [28] for more details.

3.2 Problem statement

Having formalized SKILLEXTRACTOR, which, given a trajectory τ, outputs M^τ and B^τ, we now present our problem statement for AI-assisted teaching of motor control tasks.

What should the student do? Given a set of expert demonstrations in scenarios $\Xi^e \subseteq \Xi$, where each $\xi \in \Xi^e$ is sampled from (ρ, R), we would ideally teach the student to eventually have a policy $\pi^* : \mathcal{S} \to \mathcal{A}$ that minimizes the difference between their behavior and the expert demonstrations:

$$\pi^* = \underset{\pi}{\arg\min} \sum\nolimits_{\xi \in \Xi} P(\xi) \mathcal{L}(\tau_\xi^e, \tau_\xi^\pi) \approx \underset{\pi}{\arg\min} \sum\nolimits_{\xi \in \Xi^e} \mathcal{L}(\tau_\xi^e, \tau_\xi^\pi) \,, \quad (2)$$

where τ_ξ^π denotes the student trajectory performed by policy π in scenario ξ. Similarly, τ_ξ^e denotes the expert trajectory in ξ.[1] $\mathcal{L}$ is a task-dependent loss function. While it is a straightforward goal, it is not clear how to teach a human to optimize this objective to achieve expert-like trajectories for any ξ.

What should the teacher do? We could formulate the teaching problem as a partially observable MDP (POMDP), where the teacher takes actions to guide the student to the policy π^*. The state of this POMDP would be the student's policy, initially some π_0. The teacher's observations would be the behavior of the student expressed by their trajectories, or $\tau_\xi^{\pi_k}$ for some ξ for state π_k at teaching round k. The teacher would take teaching actions in this POMDP, e.g., select scenarios to have the student practice,

Figure 1: The optimal teacher would provide a teaching action based on the students' individual policies.

for a fixed number of rounds. A teaching action at round k would move the student from π_k to π_{k+1}, which would give the teacher a reward of $\sum_{\xi \in \Xi} P(\xi) \left(\mathcal{L}(\tau_\xi^e, \tau_\xi^{\pi_k}) - \mathcal{L}(\tau_\xi^e, \tau_\xi^{\pi_{k+1}}) \right)$, i.e., the decrease in the loss value according to Eq. (2). State transitions would occur based on how a student learns: upon receiving instruction, the student updates its policy from π_k to π_{k+1} at teaching round k. The teacher should then take the optimal teaching actions that maximize its cumulative reward over teaching rounds, whose global optimum would move the student to π^* (see Fig. 1).

This approach would be useful if we had a computational model for the POMDP's transition function, i.e., how a student updates its policy from π_k to π_{k+1} for any teaching action the teacher could take. Unfortunately, we lack such computational models of human learning, especially for motor control tasks. Recent works exploring data-driven frameworks for knowledge tracing [33] and reinforcement learning based education [6] usually require large amounts of data for simpler problems. Given their large trajectory spaces, such approaches are not scalable to most motor control tasks.

Approach overview. Our insight is that once we identify important skills of a motor control task, an AI assisted teaching framework can efficiently leverage the skills to teach the task. The SKILLEXTRACTOR function allows us to identify the skills used in a given trajectory. Applying it to all expert demonstrations in scenarios $\Xi^e \subseteq \Xi$ gives us a set of skills relevant in the task. Say we label the expert demonstration τ_ξ^e for each scenario $\xi \in \Xi^e$ with skills and their intervals: $(M_\xi^e, B_\xi^e) = \text{SKILLEXTRACTOR}(\tau_\xi^e)$. We would then want the student to perform each relevant skill as close as possible to the expert to solve the following optimization:

$$\pi^* = \arg\min_\pi \sum_{\xi \in \Xi} P(\xi) \sum_{m \in M_\xi^e} \mathcal{L}_m(\tau_\xi^e, \tau_\xi^\pi) \approx \arg\min_\pi \sum_{\xi \in \Xi^e} \sum_{m \in M_\xi^e} \mathcal{L}_m(\tau_\xi^e, \tau_\xi^\pi), \quad (3)$$

where $\mathcal{L}_m$ is some loss function that compares expert and student trajectories in terms of the skill m. The intuition behind this objective is two-fold: (i) we want the student to perform the same set of skills as the expert for any $\xi \in \Xi$ (this is why we sum over $m \in M_\xi^e$), and (ii) we want them to perform each skill as close as possible to how the expert performs it. The underlying assumption is that student will gain expertise if they perform the same skills in the most similar way to the expert.

Overall, (3) is a simpler objective as the space of action sequences for each skill is much smaller than the space of trajectories or scenarios. We can now try to teach a small number of skills to the student instead of unrealistically trying to match them with the expert in the large trajectory space.

Only teaching popular skills of a task may suffer from the problem that the student does not learn how to compose different skills to achieve the target task. We thus propose to create novel *drills*, which consist of repetitions of multiple skills in a single trajectory. Drills help the students (i) learn how to connect action sequences for different skills, and (ii) develop muscle memory, which is crucial in motor control tasks, for the action sequences of each skill. The generated drills can also be personalized based on what skills each student is struggling with. For instance, as in Fig. 1, two different students (in green and blue) might have different policies with different skill sets. Therefore, a teacher should generate *individualized drills* informed by the student's initial level of expertise.

To efficiently solve (3), we propose our student-aware teaching approach that follows three steps:
1) Diverse scenario selection: Identify scenarios that yield a high diversity of popular skills when an expert controls the system, **2) Expertise estimation:** Have the student control the system under these scenarios to estimate their expertise in different skills, and **3) Individualized drill generation:**

---

[1] For concision, we assume a single expert demonstration τ_ξ^e and at most a single student trajectory τ_ξ^π for any $\xi \in \Xi^e$. Without this assumption, we would take expectations over expert and student trajectories for each ξ.

| Extract Skills from Expert Demonstrations Ξ^e | Select Scenarios with Diverse Skills Ξ^s | Identify Individual Student Skill Expertise $\tau_{\xi_1}^s$ | Automatically Create Individual Practice Drills D_{m^*} |

Figure 2: **Overview of our approach.** We train a CompILE model over expert demonstrations (e.g., handwritten Balinese text) for our SKILLEXTRACTOR function, which we use to select a diverse set of scenarios (e.g. words) covering many skills. After a student provides trajectories for these scenarios, we use SKILLEXTRACTOR again to identify their individual expertise for each skill, which informs the set of drills we provide them to practice.

Based on the estimates, create individualized drills to have the student practice the skills that they are struggling with. In the subsequent section, we describe our procedure for each of these steps.

4 Student-aware assisted teaching

1) Diverse scenario selection. We select diverse scenarios that cover many different skills in order to provide flexibility in estimating students' expertise and individualizing our teaching strategy. For example, in English, we may have expert demonstrations of writing the words (scenarios) "expert", "person", "skills", from which we would select "person" to cover more diverse letter strokes (skills). Formally, we treat the problem of choosing scenarios with diverse skills as a maximum set coverage problem, which we solve using a simple greedy algorithm (see Appendix), outputting a set of scenarios that led the expert to demonstrate a wide range of skills.

Algorithm 1 Individual Expertise Identification

Input: Selected scenarios $\Xi^s \subseteq \Xi^e$
Input: Skill labels M_ξ^e for each $\xi \in \Xi^e$
Input: Student demonstration τ_ξ^s for each $\xi \in \Xi^s$
1: $E_m \leftarrow 0$ for $\forall m \in \mathcal{M}$
2: **for** $\xi \in \Xi^s$ **do**
3: $\quad M_\xi^s, B_\xi^s \leftarrow$ SKILLEXTRACTOR(τ_ξ^s)
4: $\quad j \leftarrow 0$
5: $\quad$ **for** $m \in M_\xi^e$ **do**
6: $\quad\quad$ **if** $m \notin M_\xi^s$ **then**
7: $\quad\quad\quad E_m \leftarrow E_m + r_\xi(\tau_\xi^s)/j$
8: $\quad\quad j \leftarrow j + 1$
9: **return** E

---

2) Identifying individual expertise in skills. To efficiently teach complex tasks, we seek to estimate student's expertise in different skills, such as identifying which strokes they struggle with when writing Balinese words. Requiring a diverse set of skills, the scenarios Ξ^s we select enable us to infer student's expertise efficiently: we ask the student to perform the task in those scenarios, and based on their data, construct a labels vector E that quantifies the student's expertise E_m for each skill $m \in \mathcal{M}$.

The discrepancy between skills used by the student and the expert provides a useful signal to estimate the student's expertise. Intuitively, we expect the student to demonstrate similar skills to the expert if they are proficient in those skills, while, otherwise, they might rely on a simpler or incorrect set of skills. For example, a student driver who lacks the expertise of reverse driving might attempt to park a vehicle by only driving forward. We therefore utilize the expert demonstrations in the same scenarios the student performed the task by extracting the skills the student used via SKILLEXTRACTOR and comparing them with the expert skills in those scenarios. The student's expertise in a skill m is then: $E_m = -\sum_{\xi \in \Xi^s} \Delta_m(\tau_\xi^e, \tau_\xi^s)$, where τ_ξ^s is the student trajectory in ξ, and Δ_m is a function that computes the discrepancy between the two trajectories in terms of m.

In our implementation, if a skill is used only by the expert, we assume the student did not attempt or failed that skill. We increase the discrepancy based on how far in the trajectory they failed. We assign higher penalty to failures in the beginning of the scenario for two reasons: 1) Skills relevant early in the task are often more important: other skills would not even be needed without first achieving these skills. 2) Failing at early skills might mean the student never had a chance or a need to perform the later skills due to compounding errors, so our uncertainty about the later skills is higher. Thus, we decide to be more conservative about the later skills. Specifically, we use:

$$\Delta_m(\tau_\xi^e, \tau_\xi^s) = \begin{cases} -r_\xi(\tau_\xi^s)/j & \text{if } m \notin M_\xi^s \text{ and } m_j^{\tau_\xi^e} = m, \\ 0 & \text{otherwise.} \end{cases} \quad (4)$$

Here r_ξ is the reward function under scenario ξ, which we assume to be non-positive.[2] We increase the discrepancy if a skill is only performed by the expert, and we discount this value over time (j in

---

[2]This is a mild assumption, since we can always subtract a constant offset from any finite reward function.

Eq. (4)). We also scale discrepancy with $r_\xi(\tau_\xi^s)$ so that student trajectories with lower reward will be penalized more in terms of expertise. Alg. 1 presents the pseudocode for this step. In applications where the reward function is not readily available, one could design the skill-discrepancy function Δ_m independent of the rewards by using a divergence metric between expert and student trajectories.

3) Creating individualized drills. Referring to Eq. (3), a student should master the skills they struggle with to get better at the overall task. Therefore, the teacher should first identify those skills, and then have the student practice them. For example, if a teacher thinks a student who attempted to write the word "person" struggled with writing the letter "p", they could provide the word "puppet" as a *drill* for the student. Using the expertise vector E for a student, which is the output of Alg. 1, we can select the skills m^* with low E_{m^*} as the skills that the student needs to practice.

Given a skill m^*, the student should ideally practice it in the context of skills that frequently go together with m^*, rather than in isolation or in conjunction with arbitrary skills. For example, while learning how to park a car, it does not make sense to practice turning right immediately after stopping even though both are relevant skills. Our approach uses the expert demonstrations to identify frequent skill sequences containing skill m^*. We create *drills* consisting of these sequences that enable us to have the student practice (i) the target skill m^*, and (ii) how skill m^* connects with other skills that co-exist in various scenarios. Each drill repeats such a sequence N_{rep} times. A natural approach is to iterate over all n-grams, borrowing terminology from natural language processing, of skills from the expert demonstrations. Within each n-gram, we check if m^* exists to identify the skills that often co-occur with m^*. Mathematically, *frequency* of an n-gram of skills x is:

Algorithm 2 Individualized Drill Creation

Input: Individual expertise vector E
Input: Number of skills to create drills for N_{target}
Input: Hyperparameters $n, N_{\text{drills}}, N_{\text{rep}}$
Input: Expert demonstration τ_ξ^e for each $\xi \in \Xi^e$
Input: Skill labels M_ξ^e for each $\xi \in \Xi^e$
1: Compute $f(x)$ for all n-grams x ▷ Eq. (5)
2: **for** $m^* \leftarrow \arg\text{set}_{N_{\text{target}}} \min_m E_m$ **do**   ▷ see †
3:      $X \leftarrow \arg\text{set}_{N_{\text{drills}}} \max_{x \ni m^*} f(x)$ ▷ see †
4:      $D_{m^*} \leftarrow \bigcup_{x \in X} \bigoplus_{i=1}^{N_{\text{rep}}} \bigoplus_{m \in x} \tau_m^e$ ▷ see ‡
5: **return** D

---

† $\arg\text{set}_n \min_m E_m$ returns the set of n distinct indices that individually minimize E_m.
‡ τ_m^e is the segment of an expert demonstration from interval $[b_{j,1}^{\tau^e}, b_{j,2}^{\tau^e})$ such that $m_j^{\tau^e} = m$. The operator $\oplus$ concatenates the actions of trajectory segments.

$$f(x) = \sum_{\xi \in \Xi^e} \sum_{i=1}^{|M_\xi^e| - n + 1} \mathbb{I}\left(x = (m_i^{\tau_\xi^e}, m_{i+1}^{\tau_\xi^e}, \ldots, m_{i+n-1}^{\tau_\xi^e}) \right), \tag{5}$$

which provides an approach to decide which skill sequences the student should practice. We will have the student practice the N_{drills} n-grams involving the target skill m^* with the highest frequency.

Next, we formalize a drill as a repetition of the skills in the n-grams. This ensures the student gets enough practice of skill m^* with the most common skill sequence containing m^*. We then project this constructed skill sequence back to the trajectory space by again using the expert demonstrations. While different segments of the expert demonstrations may correspond to the same skill, we randomly select one of those segments to project back to the trajectory space.[3] Alg. 2 presents the pseudocode. It returns a set of drills D_{m^*} for every target skill m^*. Though these drills can be used in several ways, e.g., explaining them to a student, here we let the student observe and then imitate each drill trajectory.

5 Experiments

Environments. We consider two motor control tasks: parking a car in simulation with a joystick controller (PARKING), and writing Balinese characters (WRITING).

WRITING: We introduce a novel task of writing Balinese character sequences[4] from the Omniglot dataset [40], which contains action sequences for 1623 characters spanning 50 alphabets provided by crowdworkers from Amazon Mechanical Turk. We sample 5 Balinese characters, introduce a connector character "-", and create goal sequences of up to 8 characters. An agent in this environment operates in 2D (x,y) continuous state and action space, and receives reward corresponding to the

---

[3]We set the initial state of each drill as the initial state of the first trajectory segment in the drill. Since the transition function f is deterministic, the initial state and action sequence specify a full trajectory.

[4]We select the Balinese alphabet because, in comparison to other alphabet systems available in the Omniglot dataset, the writing trajectories were consistent across multiple users. We view AI-assisted teaching when there may exist multiple "expert" ways of performing a task based on user preferences as an important future direction.

degree of overlap between the agent's and the gold trajectory. We train CompILE with 1000 random sequences based on trajectories provided by human contributors to the Omniglot dataset.

PARKING: We use the Parking environment from HighwayEnv [41], a goal-based continuous control task where an agent must park a car in a specified parking spot by controlling its heading and acceleration (2D action space). The 6D state space corresponds to the car's position, velocity, and heading and at each time step, and the agent receives a reward representing how close the current state is to the goal state. Scenarios differ across initial heading angles and goal parking spots, resulting in a diverse set of skills needed. We train CompILE with rollouts across random scenarios from an optimal RL agent trained for 10^6 epochs using the StableBaselines [42] implementation of Soft Actor-Critic.

In the Appendix, we provide further details of necessary pre-processing steps for both environments, as well as all hyperparameters used for training CompILE models as part of SKILLEXTRACTOR.

Drill Creation. We create one drill for each latent skill identified by SKILLEXTRACTOR for both PARKING ($n = 3, N_{\text{rep}} = 1, N_{\text{target}} = 7, N_{\text{drills}} = 1$) and WRITING ($n = 2, N_{\text{rep}} = 3, N_{\text{target}} = 8, N_{\text{drills}} = 1$) tasks. Fig. 6 shows examples of these drills.

User Study. We design web applications for our user study for both enviornments. For PARKING, students see the environment rendered on the interface, and control the car's steering and acceleration with a 2D joystick. For WRITING, students use their computer mouse or trackpad to write on an HTML5 canvas, with the goal sequence of Balinese characters displayed underneath. Students in both environments follow a sequence of pre-test scenarios, practice sessions (including skills or drill-based practice), and evaluation scenarios. We recruit students through the Prolific platform, and include further information about pay rate, average experiment times, and task interfaces in the Appendix.

5.1 Results

Does individualization help synthetic students? To demonstrate our full approach, we first show results for synthetic "students" in the PARKING environment. We train two different synthetic students using standard behavior cloning on goal-conditioned (s, a) tuples from expert demonstrations:

1. *Half-trained:* We train a 4-layer feed-forward neural network for only 50 epochs, resulting in around 50% decrease in Mean Squared Error than a student trained for 400 epochs.
2. *Reversing Difficulty:* We train a 4-layer feed-forward neural network for 400 epochs, but with only 20% of the data containing reverse acceleration actions, to simulate difficulty with reversing.

Next, following the approach described in Sec. 3, we create a pool of 25 scenarios covering a diverse set of skills returned by our trained SKILLEXTRACTOR. We then collect rollouts from each synthetic student across all scenarios, use Alg. 1 to identify which 3 skills each synthetic student has least expertise in, and select drills from our offline drill dataset that target these skills. Using an equal dataset size, we compare and report average student reward across 15 different evaluation sets, where the student is fine-tuned on (s, a) sampled from these individualized drills (**Ind. Drills**) vs. random drills (**Drills**) vs. entire (s, a) trajectories from the original expert demonstrations (**Full Trajectory**).

Our results in Fig. 3 show that for the synthetic Half-trained IL Student, fine-tuning on data from both **Ind. Drills** and randomly selected **Drills** significantly outperforms the **Full Trajectory** setting ($p < .05$, Wilcoxon signed-rank test), while the difference between **Ind. Drills** and **Drills** is not significant. This may be due to a half-trained IL agent not having low "expertise" in any particular region, but more generally benefiting from training further on good quality data. Interestingly, for the Student with Reverse Action Difficulty, **Ind. Drills** significantly outperforms *both* randomly selected **Drills** and **Full Trajectory** settings, but randomly selecting **Drills** slightly un-

Figure 3: The effect of **Ind. Drills** and random **Drills** for synthetic students.

derperforms **Full Trajectory**, perhaps due to several drills not containing as many reverse actions as in the full-trajectory data. These results suggest that while drills can benefit both types of synthetic students in general, due to being composed of very common skill sequences, the synthetic student designed to lack a certain kind of "skill" is more likely to strongly benefit from individualization. This presents a promising signal that our CompILE-based SKILLEXTRACTOR learns skills that align with our intuitions for what skills are necessary for the PARKING task. However, our eventual goal is to teach *humans* motor control tasks, so we next test the usefulness of our approach with human students.

Does assisted skill-based practice improve human learning outcomes? Before constructing and individualizing drills, it is important to verify whether the skills returned by SKILLEXTRACTOR—the building blocks of our approach—do indeed benefit student performance, as well as in comparison to simpler heuristics. For example, CompILE, as well as other skill discovery methods, take as input the expected number of skills K per expert demonstration. A simpler **Time Heuristic** approach could instead be to assume that skills are temporally ordered and have equal length, and just split each expert demonstration into K equally-sized segments. If such a heuristic sufficed, then it may not be necessary to leverage more complex skill discovery algorithms.We therefore run user studies for both PARKING and WRITING environments comparing three different settings:

1. **Skills:** Each user practices trajectories corresponding to the 3 most common skills returned by SKILLEXTRACTOR based on CompILE parameterized with K, for 3 sessions each.
2. **Time Heuristic:** We temporally split each trajectory into K intervals of equal length, and each user practices 3 different intervals for 3 sessions each.
3. **Full Trajectory:** Each user practices 3 different full trajectories of an expert demonstration (e.g. parking a car from the start state in PARKING, an entire character sequence in WRITING).

We set $K = 3$ for PARKING and $K = 8$ for WRITING. For fair comparison, the number of time-steps users are able to practice in the full trajectory and time-heuristic modes is roughly equivalent. Because our users may differ widely in prior experience (e.g. a video game player may be more familiar with the joystick in PARKING), we measure and report *Reward Improvement*, or the difference in average reward across 5 random evaluation scenarios and 2 random pre-test scenarios.

Our results in Fig. 4 show significantly ($p < .05$) higher reward improvement for students in both WRITING ($N = 25$) and PARKING ($N = 20$) in the **Skills** setting vs. **Full Trajectory** setting. This suggests that teaching students the necessary skills for a motor control task is extremely beneficial to improve learning. However, comparison between the **Skills** and **Time Heuristic** is interestingly inconsistent between environments, where **Time Heuristic** significantly

Figure 4: Students receive significantly higher reward improvement when practicing with the **Skills** setting than **Full Trajectory**. A simple **Time Heuristic** results in inconsistent performance across environments, demonstrating the necessity for a more reliable way to identifying skills for teaching.

leads to worse student learning outcomes in PARKING, but not for WRITING. One possible explanation might be that individual skills in WRITING, such as characters or certain curves, might be semantically intuitive on their own, and therefore even if **Time Heuristic** presents different characters as the same overall "skill", there is less confusion for users. On the other hand, because of the challenging dynamics in PARKING, a user may rely more on practicing skill trajectories that have clearly similar actions. Because heuristics are often environment-specific and complex, we view these results as an encouraging sign of the suitability of intelligent skill-discovery methods for teaching humans.

Finally, we ask all participants in a post-study survey *"What else would have been helpful for you to learn how to write the characters or how to park a car?"*. One user for the WRITING task who was assigned practice *without* skills responded *"Separating the characters"*. Responses from users who were assigned skill-based practice included *"Practicing a string of 2 characters"* and *"More time and more repetition"*. These responses motivate our next set of experiments on the effect of drills.

Does practice with novel drill sequences outperform skill-based practice? Though our previous results demonstrate skill-focused practice leads to stronger learning outcomes in both environments, we hypothesize it is equally important to learn how to combine skills that often co-occur via *drills*. For example, a qualitative look at the skills in Fig. 6 suggests some of the discovered skills consist of few actions, such as a short dot in WRITING or only a few time steps in PARKING. On their own these may not be useful skills to practice, but may be important to teach in the context of other skills.

To compare with our individualization method, we create a fixed set of 5 pre-test scenarios covering a diverse set of skills returned by SKILLEXTRACTOR for both environments. We select 2 random drills, and compare the change in student reward when practicing with drills (**Drills**) vs. practicing the same underlying skill sequences used to composed the drills as separate practice sessions (**Skills**). Overall, as shown in Fig. 5, we find no statistically significant difference in reward improvement when students practice repetitive drill sequences composed of multiple skills (Blue bar) vs. skills in separation (Pink bar). Possible explanations include the increased number of practice sessions in the

Skills setting (because we keep the number of total time-steps equivalent across settings) mitigating benefits of repetition or practicing skill transitions in **Drills**. However, we next ask whether we may observe benefit from drills if we were to individualize them to students.

Does individualizing drills improve student learning outcomes? For each student, we run a CompILE-based SKILLEXTRACTOR immediately after receiving all pre-test student trajectories. Fig. 6 demonstrates the top 2 skills identified as "low expertise" across all students for both PARKING ($N = 20$) and WRITING ($N = 25$) environments. SKILLEXTRACTOR combined with Alg. 1 is indeed able to identify a wide set of low-expertise skills in student trajectories, ranging from more popular skills (e.g. "horn" shape in WRITING) to rarely difficult skills (e.g. steering the car forward in a straight line in PARKING).

Figure 5: Students marginally improve reward more when practicing with **Ind. Drills** than **Skills** for both tasks. In WRITING, students significantly prefer **Ind. Drills** over both random **Drills** and **Skills**, yet this does not hold in PARKING, where targeted practice of reversing may frustrate students.

Importantly, this is despite the likely strong differences between human student and expert trajectories, emphasizing the viability of our approach to teaching humans.

Next, we select 2 unique drills targeting each identified skill, and provide them to students for practice before measuring reward improvement on an evaluation set. Fig. 5 shows individualized drills (**Ind. Drills**) lead to stronger reward improvements for students than **Skills** with marginal significance ($p \approx .06$ WRITING, $p \approx .09$ PARKING), supporting our hypothesis that individualizing drills leads to better learning outcomes. We visualize all student trajectories before and after practicing **Ind. Drills** in the Appendix.

Finally, we ask students to rate the helpfulness of practice sessions from 1-7 (1 = least helpful), and show in Fig. 5 for WRITING, students strongly preferred practice sessions from **Ind. Drills** over **Drills** and **Skills**. However, despite the higher average reward improvement for **Ind. Drills** in PARKING, students who participated in **Skills** practice rated the helpfulness of their sessions significantly higher. Though there may exist many explanations for this, including preference for shorter sequences, we observe in evaluation rounds that users who received **Ind. Drills** were

Figure 6: Alg. 1 identifies a wide range of skills as low expertise across students for both environments. Reverse actions are identified as the most common skills for students to improve on in PARKING, while common curved-shapes are identified for WRITING.

around twice as likely to try **reversing** into a parking spot than other students (**53% vs. 27%**). This is likely due to our individualization method providing drills with reversing skills, which were more common targeted skills (see Fig. 6). Crucially, in these scenarios *the expert action is also to reverse*, suggesting while individualization may initially result in a more frustrating learning experience, it may still help students achieve stronger learning outcomes by teaching more challenging skills.

6 Discussion

Our work is a first step towards building AI-assisted systems to more efficiently teach humans motor control tasks. One benefit of our approach is its agnosticism to the type of the expert, provided we can collect demonstrations, allowing us to also consider artificial agents in situations where there exists a high burden on specialized instructors. However, an important limitation is understanding how differences between how experts and students approach tasks may negatively impact learning, as well as accounting for different human control preferences (e.g. left-handed vs. right-handed). We believe this necessitates further insights from several areas within the broader NeurIPS research community, including cognitive science, reinforcement learning, and social aspects of machine learning.

References

[1] Shervin Javdani, Henny Admoni, Stefania Pellegrinelli, Siddhartha S Srinivasa, and J Andrew Bagnell. Shared autonomy via hindsight optimization for teleoperation and teaming. *The International Journal of Robotics Research (IJRR)*, 37(7):717–742, 2018.

[2] Hong Jun Jeon, Dylan P Losey, and Dorsa Sadigh. Shared autonomy with learned latent actions. *Robotics: Science and Systems (RSS)*, 2020.

[3] Dylan Losey, Hong Jun Jeon, Mengxi Li, Krishnan Srinivasan, Ajay Mandlekar, Animesh Garg, Jeannette Bohg, and Dorsa Sadigh. Learning latent actions to control assistive robots. In *Journal of Autonomous Robots (AURO)*, 2021.

[4] Siddharth Reddy, Anca D Dragan, and Sergey Levine. Shared autonomy via deep reinforcement learning. *Robotics: Science and Systems (RSS)*, 2018.

[5] Anna N. Rafferty, Emma Brunskill, Thomas L. Griffiths, and Patrick Shafto. Faster teaching via pomdp planning. *Cognitive Science*, 40 6:1290–332, 2016.

[6] Jonathan Bassen, Bharathan Balaji, Michael Schaarschmidt, Candace Thille, Jay Painter, Dawn Zimmaro, Alex Games, Ethan Fast, and John C Mitchell. Reinforcement learning for the adaptive scheduling of educational activities. *Conference on Human Factors in Computing Systems (CHI)*, 2020.

[7] Gabriel Poesia, WenXin Dong, and Noah Goodman. Contrastive reinforcement learning of symbolic reasoning domains. *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[8] Megha Srivastava and Noah Goodman. Question generation for adaptive education. *Association for Computational Linguistics (ACL)*, 2021.

[9] Tong Mu, Shuhan Wang, Erik Andersen, and Emma Brunskill. Automatic adaptive sequencing in a webgame. *International Conference on Intelligent Tutoring Systems*, 2021.

[10] Denes Agay. *Teaching Piano: A Comprehensive Guide and Reference Book for the Instructor*. Music Sales Amer, 1982.

[11] Richard S Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1-2):181–211, 1999.

[12] Andrew G Barto and Sridhar Mahadevan. Recent advances in hierarchical reinforcement learning. *Discrete Event Dynamic Systems*, 13(1):41–77, 2003.

[13] Amy McGovern and Richard S Sutton. Macro-actions in reinforcement learning: An empirical analysis. *Computer Science Department Faculty Publication Series*, page 15, 1998.

[14] Ronald Parr and Stuart Russell. Reinforcement learning with hierarchies of machines. *Advances in Neural Information Processing Systems (NIPS)*, 1997.

[15] Thomas G Dietterich. Hierarchical reinforcement learning with the MAXQ value function decomposition. *Journal of Artificial Intelligence Research*, 13:227–303, 2000.

[16] Stefan Schaal, Jan Peters, Jun Nakanishi, and Auke Ijspeert. Learning movement primitives. *Robotics Research. The Eleventh International Symposium*, pages 561–572, 2005.

[17] Christian Daniel, Gerhard Neumann, and Jan Peters. Autonomous reinforcement learning with hierarchical reps. *IEEE International Joint Conference on Neural Networks (IJCNN)*, 2013.

[18] Pravesh Ranchod, Benjamin Rosman, and George Konidaris. Nonparametric bayesian reward segmentation for skill discovery using inverse reinforcement learning. *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2015.

[19] Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. *AAAI Conference on Artificial Intelligence*, 2017.

[20] Akhil Bagaria and George Konidaris. Option discovery using deep skill chaining. *International Conference on Learning Representations (ICLR)*, 2019.

[21] Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

[22] Carlos Florensa, Yan Duan, and Pieter Abbeel. Stochastic neural networks for hierarchical reinforcement learning. *International Conference on Learning Representations (ICLR)*, 2017.

[23] Joshua Achiam, Harrison Edwards, Dario Amodei, and Pieter Abbeel. Variational option discovery algorithms. *arXiv preprint arXiv:1807.10299*, 2018.

[24] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *International Conference on Learning Representations (ICLR)*, 2019.

[25] Archit Sharma, Shixiang Gu, Sergey Levine, Vikash Kumar, and Karol Hausman. Dynamics-aware unsupervised discovery of skills. *International Conference on Learning Representations*, 2020.

[26] Víctor Campos, Alexander Trott, Caiming Xiong, Richard Socher, Xavier Giró-i Nieto, and Jordi Torres. Explore, discover and learn: Unsupervised discovery of state-covering skills. *International Conference on Machine Learning (ICML)*, 2020.

[27] Kevin Frans, Jonathan Ho, Xi Chen, Pieter Abbeel, and John Schulman. Meta learning shared hierarchies. *International Conference on Learning Representations (ICLR)*, 2018.

[28] Thomas Kipf, Yujia Li, Hanjun Dai, Vinicius Zambaldi, Alvaro Sanchez-Gonzalez, Edward Grefenstette, Pushmeet Kohli, and Peter Battaglia. CompILE: Compositional imitation learning and execution. *International Conference on Machine Learning (ICML)*, 2019.

[29] Tanmay Shankar, Shubham Tulsiani, Lerrel Pinto, and Abhinav Gupta. Discovering motor programs by recomposing demonstrations. *International Conference on Learning Representations (ICLR)*, 2019.

[30] Anca D Dragan and Siddhartha S Srinivasa. A policy-blending formalism for shared control. *The International Journal of Robotics Research (IJRR)*, 32(7):790–805, 2013.

[31] Jonathan Bragg and Emma Brunskill. Fake it till you make it: Learning-compatible performance support. *Conference on Uncertainty in Artificial Intelligence (UAI)*, 2019.

[32] Albert T Corbett and John R Anderson. Knowledge tracing: Modeling the acquisition of procedural knowledge. *User modeling and user-adapted interaction*, 4(4):253–278, 1994.

[33] Chris Piech, Jonathan Bassen, Jonathan Huang, Surya Ganguli, Mehran Sahami, Leonidas J Guibas, and Jascha Sohl-Dickstein. Deep knowledge tracing. *Advances in Neural Information Processing Systems (NIPS)*, 2015.

[34] Shayan Doroudi, Vincent Aleven, and Emma Brunskill. Where's the reward? a review of reinforcement learning for instructional sequencing. *International Journal of Artifical Intelligence in Education*, 29:568–620, 2019.

[35] Xiaojin Zhu. Machine teaching: An inverse problem to machine learning and an approach toward optimal education. *AAAI Conference on Artificial Intelligence*, 2015.

[36] Oisin Mac Aodha, Shihan Su, Yuxin Chen, Pietro Perona, and Yisong Yue. Teaching categories to human learners with visual explanations. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3820–3828, 2018.

[37] Natalie Krahe. *Motor Skill Learning: A Review of Trends and Theories.* Caroll College, 1999.

[38] Anne Shumway-Cook and Marjorie H Woollacott. *Motor control: Theory and practical applications*. Lippincqtt Williams & Wilkins, 1995.

[39] David A Rosenbaum. *Human motor control*. Elsevier, 2010.

[40] Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

[41] Edouard Leurent. An environment for autonomous driving decision-making. `https://github.com/eleurent/highway-env`, 2018.

[42] Ashley Hill, Antonin Raffin, Maximilian Ernestus, Adam Gleave, Anssi Kanervisto, Rene Traore, Prafulla Dhariwal, Christopher Hesse, Oleg Klimov, Alex Nichol, Matthias Plappert, Alec Radford, John Schulman, Szymon Sidor, and Yuhuai Wu. Stable baselines. `https://github.com/hill-a/stable-baselines`, 2018.