Consistent Inconsistency: The Negative Binomial Pattern of LLM-as-a-Judge

Abstract

Large language models (LLMs) are increasingly deployed as evaluators, yet their logical consistency remains underexplored. We conduct a large-scale, systematic study that reframes non-transitive preferences (Condorcet cycles) from observed phenomena into quantifiable, predictable diagnostic signals. Through exhaustive permutation testing across 688 debate motions and five frontier models (including the judge model GPT-4o as a contestant), we construct 165,120 tournament graphs and establish that: (i) cycle frequencies are not random but follow a tightly fitted negative binomial distribution ($R^2 = 0.9973$)—a pattern specific to LLM judgments, as confirmed by control experiments that rule out experimental artifacts; (ii) inconsistency is predictable from linguistic features, with syntactic complexity increasing ($\beta = 0.130$) and readability decreasing ($\beta = -0.085$) cycle formation; and (iii) evaluation reliability is multi-scale, demonstrated by quantifiable inconsistency rates (stance-level: 7.19%; motion-level: 14.10%) that complement traditional performance rankings. We introduce a graph-theoretic framework and standardized metrics that enable consistency-aware evaluation, providing actionable diagnostics for when and why LLM judgments become unreliable. Our work provides a principled approach to measuring and reporting evaluation consistency, moving beyond merely noting its existence.

1 Introduction

Large language models (LLMs) are increasingly positioned as *evaluators* of language, not just producers of it. In this "LLM-as-a-Judge" paradigm, a powerful LLM assesses and compares text quality, aiming to mirror human assessment. This shift makes the reliability of LLM-as-a-judge a critical bottleneck for research and deployment.

Most work emphasizes agreement with human preferences, but underexplores a more fundamental property: the **logical consistency** of judgments. In social choice theory, non-transitive preferences (Condorcet cycles) are theoretically unavoidable under mild conditions; in practice, they destabilize rankings and obscure when to trust automated evaluation.

We argue that such cycles are not mere statistical clutter. They are *structured signals* about when and why LLM judgments become unreliable. By treating cycles as consistency checks rather than artifacts to be eliminated, we obtain a principled, multi-scale view of evaluation reliability that coexists with global ranking stability.

To address these gaps, we conduct a large-scale empirical study reframing non-transitive preferences as critical diagnostic signals. Our investigation examines three underexplored dimensions: (1) the systematic patterning of Condorcet cycles across linguistic features, (2) model scale effects on evaluation consistency, and (3) the tension between local inconsistencies and global reliability. Using GPT-4o as evaluator, we assess five contemporary LLMs (GPT-4o, DeepSeek-R1, Qwen3-14B, Qwen3-8B, MiniMax-M1) across 688 debate motions from the IBM Debater CoPA dataset (Bilu et al., 2019), spanning policy, ethical, and cultural topics.

2 Related Work

2.1 LLM-as-a-Judge and Its Challenges

Adoption of LLMs as evaluators shows promising alignment with human judgments (OpenAI et al., 2024), yet faces persistent challenges including position biases (Chen et al., 2024), limited generalization in domain-specific tasks (Huang et al., 2025), and computational costs of ensembles (Zhang et al., 2025a). Prompt engineering techniques, such as chain-of-thought (Kojima et al., 2023) and self-verification (Shinn et al., 2023), aim to mitigate these issues. Surveys highlight inconsistencies like

overconfidence and bias amplification (Gu et al., 2025; Leng et al., 2025; Ren et al., 2024).

Recent work has identified intriguing patterns in how LLMs evaluate their own generations. (Panickssery et al., 2024) demonstrated that LLMs can recognize their own outputs with non-trivial accuracy (73.5% for GPT-4), and that this self-recognition capability correlates with preference biases in summarization tasks. Our experimental framework reveals a distinct pattern: the judge model GPT-4o exhibits no absolute self-preference (ranking third overall) while participating extensively in Condorcet cycles. This contrast suggests that self-recognition effects—when present—may not necessarily translate to systematic ranking advantages in debate-style evaluations. The blind evaluation protocol (Section 3) ensures that any observed patterns reflect inherent judgment tendencies rather than explicit model identity effects.

2.2 Theoretical Foundations: Non-Transitivity and Rating Systems

Non-transitive preferences ($A \succ B \succ C \succ A$) are theoretically inevitable (Liu et al., 2025a) and empirically observed, causing ranking instabilities (Xu et al., 2025). Adapted from chess (Elo, 1967), Elo ratings power modern LLM leaderboards, with advances in bias correction (Yu et al., 2025b) and Bayesian uncertainty quantification (Gao et al., 2024). New approaches address cycles in human-aligned evaluations (Zhang et al., 2025b). Comparisons reveal LLMs assume greater rationality in human decision-making (Liu et al., 2025b).

Positioning Our Contribution. While prior work focused on elimination strategies (Yu et al., 2025a; Liu et al., 2025c; Xu et al., 2025), our study introduces a systematic framework for quantifying inconsistency through permutation-based graph construction. Unlike Liu et al. (2025c) who primarily used pairwise permutations, our key innovation lies in constructing 165,120 tournament graphs via full model ordering permutations to comprehensively measure systemic inconsistency. This methodological advance enables three core contributions: (1) establishing the negative binomial distribution of cycle counts as an empirical regularity; (2) linking cycle formation to linguistic features through multi-attribute decision theory (Tversky, 1969); and (3) introducing standardized inconsistency metrics (7.19% stance-level, 14.10% motion-level) that transform cycles from noise into

reproducible diagnostics.

3 Methods

3.1 Overview

Our study employs a graph-theoretic framework to analyze preference data derived from a large-scale, automated evaluation of large language models (LLMs) in a debate task. **A key feature of our design is that the judge model (GPT-4o) is also included as a contestant, allowing us to directly investigate its behavior as both an evaluator and a performer under blind assessment conditions.** The core of our methodology involves a rigorous experimental setup where multiple LLMs generate arguments and a judge model (GPT-4o) performs pairwise comparisons. We then model these pairwise preferences as a directed graph to identify non-transitive cycles (Condorcet cycles). Finally, we conduct a comprehensive statistical and linguistic analysis to quantify and understand the sources of evaluation inconsistency.

3.2 Experimental Setup

Models. We evaluated five contemporary LLMs: GPT-4o (2024-11-20 version), DeepSeek-R1 (0528 version), MiniMax-M1 (80k), Qwen3-14B, and Qwen3-8B. All models were accessed via their respective APIs during August 2025. This selection provides a diverse mix of model sizes, architectures, and training data, offering a robust testbed for evaluating judgment consistency.

Dataset. We utilized 688 debate motions from the IBM Debater Contextual Argument Pair (CoPA) dataset (Bilu et al., 2019). This dataset covers a wide spectrum of policy, ethical, and cultural topics (e.g., "We should ban beauty contests," "Cannabis should be legalized"), enabling us to test judgment reliability across varying levels of complexity and stakes. One motion was excluded due to GPT-4o's content policy filters during the argument generation phase, while other models generated arguments for it without restrictions. This discrepancy highlights inherent differences in safety fine-tuning across model providers.

Evaluation Protocol. Our protocol consisted of four sequential phases conducted for each motion. The first phase was argument generation: for a given motion and a specific stance (pro or con), each model generated a persuasive argument, with all generations using a temperature of 0 to ensure

determinism. The second phase was judgment: the judge model (GPT-4o, temperature=0) evaluated all possible pairwise comparisons between the five generated arguments. To control for position bias, each pair was presented twice with the argument order reversed. The third phase was recording: the judge's binary preference (e.g., Argument A $\succ$ Argument B) for each comparison was recorded. The final phase was the consistency check: the complete set of recorded preferences for a motion and stance was analyzed as a tournament graph to detect the presence of Condorcet cycles, which we define as "inconsistent judgments".

Prompt Design. All prompts were engineered to ensure clean, isolated, and position-specific responses. Key design constraints included the prohibition of meta-commentary, summaries, or references to the generating model; strict enforcement of the assigned stance; counterbalancing of argument positions to mitigate order effects; and structured output formatting to facilitate automated parsing. The exact prompts are provided in Appendix 6.

Blind Evaluation Protocol. A critical feature of our design is the implementation of a *blind* evaluation. The judge model (GPT-4o) was never provided with any information regarding the identity of the model that generated a given argument. This prevents explicit bias (e.g., self-preference or bias against a specific provider) and ensures that evaluations are based solely on the perceived quality of the argument content.

3.3 Analytical Framework

We model evaluation outcomes as tournament graphs $G = (V, E)$ where vertices represent models and directed edges indicate pairwise preferences. Condorcet cycles ($A \succ B \succ C \succ A$) signify evaluation inconsistencies (Harary, 2018). Our framework combines three methodological innovations:

First, we employ exhaustive permutation testing across all possible model orderings (120 permutations per stance) to quantify the upper bounds of cyclic preference formation. This stress-test approach generated 165,120 tournament graphs for cycle detection (see Appendix 6 for computational specifics).

Second, we introduce two-level inconsistency metrics: stance-level (7.19% cyclic rate) and motion-level (14.10%). The **stance-level inconsistency rate** measures the proportion of individual argument positions (pro or con for a given motion) for which the pairwise comparisons between models form at least one Condorcet cycle. The **motion-level inconsistency rate** provides a more conservative, topic-level measure, defined as the proportion of debate motions where *any* stance (pro or con) exhibits cyclic preferences; this higher rate reflects that a single inconsistent stance suffices to deem the entire motion's evaluation inconsistent. These metrics complement traditional ranking systems by quantifying judge reliability at different granularities.

Third, we integrate Bayesian Elo ratings (Gao et al., 2024) and Bradley-Terry models to derive robust global rankings while accounting for position biases measured via McNemar's test. The full statistical implementation, including MCMC specifications and bias correction formulas, is detailed in Appendix 6.

Robustness Validation with Alternative Judge. To assess the generalizability of our findings beyond the primary judge (GPT-4o), we conducted a supplementary experiment using DeepSeek-R1 as the evaluator. This validation study employed 20 debate motions and included four models (GPT-4o, DeepSeek-R1, MiniMax-M1, Qwen3-8B), following the same pairwise comparison protocol described in Section 3. The purpose was to test whether the performance hierarchy observed with GPT-4o as judge remains consistent across different evaluators.

3.4 Illustrative Example of Permutation Methodology

Our permutation approach systematically constructs 165,120 tournament graphs by evaluating all $5! = 120$ model orderings per stance. For each permutation, we query the pairwise comparison database to build a unique evaluation scenario. For example, permutation (A,B,C,D,E) queries comparisons A-B, A-C, A-D, A-E, B-C, B-D, B-E, C-D, C-E, D-E, while permutation (B,A,C,D,E) queries B-A, A-C, etc. This systematic variation across all permutations comprehensively probes evaluation consistency under different presentation orders.

3.5 Linguistic Feature Extraction

To investigate the correlation between motion attributes and the propensity for cyclic judgments, we extracted 12 linguistic and semantic features from each debate motion text. These features capture

various aspects of textual complexity (see full list in Table 9), including basic textual properties (character length, average word length, entropy, lexical diversity, Flesch Reading Ease), syntactic features (syntactic complexity, noun ratio, verb ratio, named entity count), and semantic/sentiment features (sentiment polarity, sentiment subjectivity, semantic dispersion). All features were standardized using z-score normalization prior to being used as predictors in a Poisson regression model, where the dependent variable was the aggregate cycle count per motion.

3.6 Model Size Correlation Analysis

We analyzed relationships between model scale—as measured by published parameter count—and evaluation metrics using Pearson and Spearman correlations. Parameter count values were compiled from published sources: DeepSeek-R1, MiniMax-M1, and Qwen3 models from SilicoFlow Team (2025), while the estimate for GPT-4o was sourced from Abacha et al. (2025).

Statistical analysis followed three steps: (1) normality verification via Shapiro-Wilk tests, (2) linear correlation analysis using Pearson coefficients, and (3) non-parametric validation with Spearman ranks. The small sample size (N=5) precluded permutation testing but ensured transparent interpretation of effect sizes.

4 Results

Our analysis reveals that non-transitive preferences are systematic phenomena challenging LLM judgment consistency. We present three findings: performance hierarchies with cyclical patterns, distributional regularities of cycles, and their linguistic drivers.

4.1 Performance Hierarchies and Systemic Non-Transitivity

Our Bayesian analysis reveals a multi-faceted perspective on evaluation dynamics through three interconnected discoveries that reshape our understanding of LLM judging behavior.

The primary revelation concerns the judge model's unexpected placement in the competitive landscape. Empirical data demonstrates GPT-4o consistently occupying the third position (1592.8 [1504.8, 1678.6]) behind DeepSeek-R1 (1682.3 [1594.3, 1768.6]), with the 89.5-point Elo differential reflecting a measurable performance gap.

Crucially, this intermediate ranking occurs *without* evidence of absolute self-preference—in contrast to the self-recognition capabilities reported in other evaluation contexts (Panickssery et al., 2024). This distinction highlights the importance of task-specific validation when deploying LLM judges, as different evaluation frameworks may activate distinct judgment patterns. The contrast with prior findings in summarization tasks (Panickssery et al., 2024) indicates potential variations in evaluation patterns across contexts, though the underlying causes warrant further investigation.

The second discovery exposes the structural consequences of this hierarchy through network analysis. GPT-4o emerges as a focal point in cyclical preference patterns, involved in 72.48% of all Condorcet cycles detected. The recurrent DeepSeek ≻ GPT-4o ≻ MiniMax ≻ DeepSeek sequence accounts for 17.8% of cyclical structures (see Table 5 for participation rates), revealing how specific model interactions generate system-wide inconsistencies. This phenomenon manifests most prominently in three-node cycles (85.93% prevalence, see Figure 2), suggesting constrained but persistent deviations from transitive logic in the evaluation space.

The final insight bridges micro-level inconsistencies with macro-level reliability. The global ranking structure shows qualitative alignment with human preference benchmarks from Chatbot Arena (Table 6), particularly in the relative ordering of DeepSeek-R1 above MiniMax-M1. This directional agreement—observed across 94% of debate motions—provides tentative external validation for our task-specific evaluation patterns, though we caution against direct performance comparisons given differences in evaluation protocols and the limited overlap between benchmarked models. The coexistence of local cyclicality with this macro-level ordering challenges conventional assumptions about evaluation consistency, suggesting the need for frameworks that simultaneously account for granular inconsistencies and aggregate reliability.

Robustness Check with Alternative Judge: To validate the stability of our performance hierarchy, we conducted a complementary experiment using DeepSeek-R1 as the judge model across 20 debate motions and four models. The resulting win rates (GPT-4o: 60.83%, MiniMax-M1: 63.33%, DeepSeek-R1: 71.93%, Qwen3-8B: 35.09%) confirm the relative ranking pattern observed with GPT-4o as judge, with DeepSeek-R1 maintaining supe-

rior performance. While the absolute win rates differ due to judge-specific evaluation tendencies, the consistent ordinal ranking (DeepSeek-R1 $\succ$ MiniMax-M1 $\succ$ GPT-4o $\succ$ Qwen3-14B) demonstrates the robustness of our core finding across different judge models. This alignment strengthens our conclusion that the observed performance hierarchy reflects genuine differences in argument quality rather than judge-specific artifacts.

4.2 Distributional Analysis of Cycle Counts

Our exhaustive permutation analysis across all $5! = 120$ model orders per stance revealed $N_{\text{total cycles}} = 3,398$ cycles aggregated over $N_{\text{graphs}} = 165,120$ graphs (Table 1). The distribution of cycle counts per motion exhibits significant overdispersion (variance = $116.815 \gg$ mean = 4.94), with a negative binomial distribution providing exceptional fit ($R^2 = 0.9973$; Figure 1). This confirms that certain debate motions systematically trigger more non-transitive preferences across evaluation scenarios.

Parameter estimates (n = 0.705 [0.633, 0.783], p = 0.076 [0.067, 0.088]) indicate strong aggregation tendencies, with 14.5% of motions exhibiting no cycles while others trigger multiple preference cycles. The negative binomial model significantly outperformed alternative distributions including zero-inflated variants (see detailed comparison in Table 7).

4.3 Control Experiment: Validating the Specificity of Negative Binomial Distribution

To confirm that the observed negative binomial distribution of cycle counts reflects a genuine property of LLM judgments rather than an artifact of our experimental construction, we conducted a control experiment. We replaced GPT-4o's pairwise comparisons with randomly generated preferences under two conditions: complete randomness ($p = 0.5$) and moderate bias ($p = 0.7$), while keeping all other experimental parameters identical.

The results demonstrate a clear distributional contrast: while LLM judgment data is best modeled by a negative binomial distribution, data generated from random preferences follows a normal distribution (see Appendix 6 for detailed statistical comparisons and Figure 3). This confirms that the negative binomial pattern is specific to structured LLM evaluation behavior, indicating *overdispersion* (variance > mean) and systematic heterogene-

ity in how different debate motions trigger non-transitive preferences. The control experiment thus provides crucial validation that our graph-theoretic framework captures inherent LLM judgment characteristics, not methodological artifacts.

4.4 Linguistic Correlates of Cycle Formation

Statistical Validation of Linguistic Effects: Our Poisson regression analysis yields a Nagelkerke's Pseudo R^2 of 0.106 (Likelihood Ratio $\chi^2 = 77.25$, $p < 0.001$), indicating that linguistic features explain a significant and meaningful portion of the variance in cycle formation. This establishes that the relationship between motion characteristics and evaluation inconsistency is statistically robust.

Detailed analysis of specific features identified several motion characteristics significantly associated with cycle count formation ($p < 0.05$), with full results in Table 2. This explains why cycles cluster around specific motions.

Syntactic complexity ($\beta = 0.130$, $p < 0.001$) shows the strongest positive association with cycle formation, indicating that motions with more complex syntactic structures increase the likelihood of non-transitive preferences. **Verb ratio** ($\beta = 0.087$, $p < 0.001$) and **noun ratio** ($\beta = 0.037$, $p = 0.028$) also demonstrate positive associations, suggesting that substantive, action-oriented content triggers more evaluation inconsistencies.

Conversely, several motion characteristics show negative associations with cycle formation. **Readability** ($\beta = -0.085$, $p < 0.001$), as measured by Flesch reading ease, shows that more readable motions reduce cycle formation. **Semantic dispersion** ($\beta = -0.057$, $p < 0.001$) reveals that debate topics with more focused semantic content are associated with fewer cycles. **Sentiment polarity** ($\beta = -0.036$, $p = 0.011$) indicates that motions with more polarized sentiments decrease cycle counts.

These findings align with multi-attribute decision theory, where complex, nuanced motion content creates more opportunities for criterion shifts across different evaluation dimensions.

4.5 Evaluation Integrity and Judgment Consistency

Position bias analysis reveals systematic ordering effects across model pairs (Table 10). The global mean order bias is 0.3356 (std=0.1317), indicating a consistent preference for first-presented arguments. These biases contribute to the observed

Table 1: Summary of Graph-Level and Motion-Level Cycle Statistics

Metric	Value	Description
Total Motions (N_m)	688	
Total Stances (N_s)	1,376	$N_m \times 2$
Total Graphs (N_g)	165,120	$N_m \times 2 \times 120$
Total Cycles (N_c)	3,398	Sum over all graphs
Cycles per Motion (N_c/N_m)	4.94	Primary unit for distributional analysis
Cycles per Graph (N_c/N_g)	0.021	
Inconsistent Motions	97	Motions with ≥ 1 cyclic graph
Motion-Level Inconsistency Rate	14.10%	97/688

(a) Empirical vs. Negative Binomial CDF

(b) Empirical vs. Negative Binomial PMF

Figure 1: Distributional analysis confirms that cycle counts are highly overdispersed and tightly follow a negative binomial distribution ($R^2 = 0.9973$). This demonstrates that inconsistency is governed by a reproducible statistical regularity rather than random noise.

cyclical patterns and highlight the need for debiasing strategies.

Our analysis reveals significant evaluation inconsistencies in GPT-4o's judgments. We quantify judge reliability through two novel metrics: a 7.19% stance-specific inconsistency rate (99 out of 1376 argument pairs forming cycles) and a 14.10% motion-level inconsistency rate (97 out of 688 motions containing cyclic preferences). These inconsistency rates provide quantifiable benchmarks for judge reliability that complement traditional accuracy metrics.

4.6 Exploratory Analysis of Model Scale and Consistency

Our analysis includes five models spanning a range of published parameter counts and architectures. While the small and non-uniform sample size (N=5) precludes definitive causal conclusions about scaling laws, we conducted an exploratory correlation analysis to identify potential relationships worthy

of future study.

The strong correlation between published parameter count and cycle participation (Pearson r=0.924, p=0.025; Table 14) suggests a potential relationship between model scale and the propensity to engage in non-transitive patterns. **However, we emphasize that this correlation is exploratory and could be influenced by confounding variables such as architectural differences (e.g., mixture-of-experts vs. dense transformers), training data composition, and optimization techniques.** The correlation should be interpreted as generating a hypothesis for future research rather than confirming a scaling law.

Furthermore, we note substantial variation in efficiency metrics. For instance, Qwen3-14B achieves a notably high win rate per billion parameters (3.69 wins per B) compared to larger models (Table 13). This observation hints that architectural innovations may be an important factor in evaluation capability, alongside scale. Rigorously disentangling

Table 2: Linguistic features significantly associated with cycle formation ($p < 0.05$). Syntactic complexity and verb/noun ratios increase cycles, while readability and semantic focus reduce them. This shows that inconsistency is predictable from measurable motion attributes.

Feature	Coefficient (β)	p-value	Direction
Syntactic Complexity	0.130	0.001	Increases cycles
Verb Ratio	0.087	0.001	Increases cycles
Flesch Reading Ease	-0.085	0.001	Decreases cycles
Semantic Dispersion	-0.057	0.001	Decreases cycles
Noun Ratio	0.037	0.028	Increases cycles
Sentiment Polarity	-0.036	0.011	Decreases cycles
Intercept (const)	2.143	0.001	-

the effects of scale, architecture, and training data represents a critical direction for future research with a more comprehensive and controlled model set.

5 Discussion

This work provides the first statistical regularity of LLM inconsistency. By reframing non-transitive preferences from a nuisance into a *consistency probe*, we show that cycles follow reproducible distributions, are shaped by linguistic factors, and scale with model size. Reliability therefore lives on two levels: locally fragile yet globally stable.

5.1 Theoretical Integration

The observed performance hierarchy (DeepSeek-R1 $\succ$ MiniMax-M1 $\succ$ GPT-4o) demonstrates that evaluation consistency varies independently of absolute performance metrics. This is visually evident in the win rate matrix (Figure 2b), where stronger models (warmer colors) nonetheless participate in cyclical preferences. The alignment with Chatbot Arena leaderboard (Table 6) provides external validation for the relative ordering of DeepSeek-R1 and MiniMax-M1, while the judge model's intermediate ranking (GPT-4o at 1592.8 Elo) reflects its position in the performance hierarchy under blind evaluation conditions.

The consistency of performance hierarchies across different judge models (GPT-4o and DeepSeek-R1) further validates that observed rankings reflect genuine capability differences rather than evaluation artifacts. Meanwhile, the statistically significant explanatory power of linguistic features (Pseudo $R^2 = 0.106$) underscores the structured nature of evaluation inconsistency.

5.2 Micro-Macro Reliability

Our study uncovers a key phenomenon: local evaluation inconsistencies (14.10% cyclic rate) coexist with globally reliable rankings (DeepSeek-R1 $\succ$ MiniMax-M1 alignment). This pattern reflects Tversky's principle of context-dependent criterion weighting (Tversky, 1969).

Three analytical dimensions explain this dissociation. Node-level analysis reveals model-specific inconsistency tendencies, with MiniMax-M1 participating in 73.8% of cycles (Figure 2d). Graph-level metrics quantify system-wide reliability through permutation testing (Table 1). Bayesian ranking models establish macro-level stability (94% HDI consistency in Table 4).

The framework's innovation lies in preserving cycles as diagnostic signals rather than noise. This enables precise measurement of how micro-level inconsistencies aggregate into macro-level reliability patterns, addressing a critical gap in LLM evaluation methodologies.

5.3 Methodological Validation through Control Experiments

Our control experiment (Section 4.3) provides crucial methodological validation by demonstrating that the negative binomial distribution is LLM-specific rather than a construction artifact. The clear distributional separation between LLM judgments (negative binomial) and random preferences (normal) confirms that our framework captures genuine properties of LLM evaluation consistency. This validation addresses the potential counterargument that any tournament construction with sufficient permutations might naturally yield negative binomial distributed cycles due to combinatorial properties.

The methodological implication extends beyond our specific findings: control experiments with random preferences should become standard practice in LLM evaluation research to distinguish construction effects from genuine model behaviors. This approach enhances the credibility of distributional

analyses and provides a rigorous baseline for interpreting consistency metrics in automated evaluation systems.

The visual contrast between Figure 1 (LLM judgments) and Figure 3 (random preferences) provides compelling evidence that the negative binomial distribution is not an artifact of tournament graph construction. The normal distribution observed under random conditions aligns with central limit theorem expectations when aggregating independent permutations, while the overdispersed negative binomial distribution reflects the structured heterogeneity inherent to LLM evaluation patterns. This methodological validation addresses potential concerns that any tournament construction with sufficient permutations might naturally yield negative binomial distributed cycles, confirming instead that the pattern captures genuine properties of LLM evaluation consistency.

5.4 Exploratory Scale-Consistency Relationships

The strong preliminary correlation between published model parameter count and cycle participation (r=0.924) points to a potential, understudied aspect of scaling that merits future investigation: larger models may exhibit different patterns of non-transitive preferences alongside their higher absolute performance.

This pattern manifests clearly in the participation rate distribution (Figure 2d), where MiniMax-M1 (456B parameter count, see Table 13) shows 73.8% cycle involvement versus Qwen3-8B's 50.7% (8B parameter count). The exceptional efficiency of Qwen3-14B (3.69 wins per B) demonstrates architectural innovations can partially decouple performance from pure scale.

Although based on a small set of heterogeneous models and thus not conclusive, this exploratory signal suggests that scaling laws of consistency deserve systematic study as a parallel line of inquiry to scaling laws of accuracy. Future work should prioritize testing this hypothesis on a larger, architecturally-uniform family of models to control for confounding variables.

5.5 Actionable Implications

Our graph-theoretic framework yields three actionable principles: (1) report inconsistency metrics alongside Elo, (2) design tasks to minimize cycle formation via readable and semantically focused motions, and (3) analyze scale–consistency inter-actions as part of model development. Together, these steps transform cycles into reproducible diagnostics rather than noise.

6 Conclusion

Non-transitive preferences are not evaluation debris; they are *diagnostic signals*. By demonstrating statistical regularities of cycles, uncovering their linguistic drivers, and highlighting a preliminary scale–consistency tradeoff, we show that inconsistency can be measured, reported, and theorized rather than ignored. Practically, this enables benchmarks to report stance- and motion-level inconsistency alongside Elo, and to design tasks that minimize cycle formation through higher readability and semantic focus. Conceptually, it opens a new research frontier: **scaling laws of consistency**, complementing the well-studied scaling laws of accuracy. Looking forward, we envision a consistency-aware paradigm where every leaderboard and benchmark reports both accuracy and inconsistency metrics, enabling a richer science of evaluation and more trustworthy deployment of LLM-as-a-judge.

Limitations

Internal Validity. The exploratory analysis of scale and inconsistency is based on five models with heterogeneous architectures and partially estimated parameter counts; it should be interpreted as hypothesis-generating rather than confirming scaling laws. Our protocol controls for order effects but does not include self-comparison tests, and we rely on the theoretical assumption that a model's argument should not systematically beat itself. Residual biases not fully accounted for by counterbalancing may remain.

External Validity. Debate evaluation may differ from other tasks like summarization or code generation, and protocol choices could interact with cycle rates. While our complementary experiment with DeepSeek-R1 as judge provides preliminary evidence of cross-judge consistency, the findings from a single primary judge model (GPT-4o) require further validation across more diverse evaluators.

Future Directions. Future work should expand the model set, standardize architecture families, and test whether consistency-aware evaluation generalizes to other modalities and tasks.

References

Asma Ben Abacha, Wen wai Yim, Yujuan Fu, Zhaoyi Sun, Meliha Yetisgen, Fei Xia, and Thomas Lin. 2025. Medec: A benchmark for medical error detection and correction in clinical notes. *Preprint*, arXiv:2412.19260.

Yonatan Bilu, Ariel Gera, Daniel Hershcovich, Benjamin Sznajder, Dan Lahav, Guy Moshkowich, Anael Malet, Assaf Gavron, and Noam Slonim. 2019. Argument invention from first principles. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 1013–1026, Florence, Italy. Association for Computational Linguistics.

Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. 2024. Humans or LLMs as the judge? a study on judgement bias. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 8301–8327, Miami, Florida, USA. Association for Computational Linguistics.

Arpad E Elo. 1967. The proposed uscf rating system, its development, theory, and applications. *Chess life*, 22(8):242–247.

Yicheng Gao, Gonghan Xu, Zhe Wang, and Arman Cohan. 2024. Bayesian calibration of win rate estimation with llm evaluators. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, page 4757–4769. Association for Computational Linguistics.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, Saizhuo Wang, Kun Zhang, Yuanzhuo Wang, Wen Gao, Lionel Ni, and Jian Guo. 2025. A survey on llm-as-a-judge. *Preprint*, arXiv:2411.15594.

Frank Harary. 2018. *Graph theory (on Demand Printing of 02787)*. CRC Press.

Hui Huang, Xingyuan Bu, Hongli Zhou, Yingqi Qu, Jing Liu, Muyun Yang, Bing Xu, and Tiejun Zhao. 2025. An empirical study of LLM-as-a-judge for LLM evaluation: Fine-tuned judge model is not a general substitute for GPT-4. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 5880–5895, Vienna, Austria. Association for Computational Linguistics.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2023. Large language models are zero-shot reasoners. *Preprint*, arXiv:2205.11916.

Jixuan Leng, Chengsong Huang, Banghua Zhu, and Jiaxin Huang. 2025. Taming overconfidence in LLMs: Reward calibration in RLHF. In *The Thirteenth International Conference on Learning Representations*.

Kaizhao Liu, Qi Long, Zhekun Shi, Weijie J. Su, and Jiancong Xiao. 2025a. Statistical impossibility and possibility of aligning llms with human preferences: From condorcet paradox to nash equilibrium. *Preprint*, arXiv:2503.10990.

Ryan Liu, Jiayi Geng, Joshua C. Peterson, Ilia Sucholutsky, and Thomas L. Griffiths. 2025b. Large language models assume people are more rational than we really are. *Preprint*, arXiv:2406.17055.

Yinhong Liu, Zhijiang Guo, Tianya Liang, Ehsan Shareghi, Ivan Vulić, and Nigel Collier. 2025c. Aligning with logic: Measuring, evaluating and improving logical preference consistency in large language models. *Preprint*, arXiv:2410.02205.

LMArena Team. 2025. Chatbot arena leaderboard (text category). Online leaderboard. Accessed: 29 August 2025.

OpenAI and 1 others. 2024. Gpt-4 technical report. *Preprint*, arXiv:2303.08774.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. 2024. LLM evaluators recognize and favor their own generations. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Yi Ren, Shangmin Guo, Linlu Qiu, Bailin Wang, and Danica J. Sutherland. 2024. Bias amplification in language model evolution: An iterated learning perspective. *Preprint*, arXiv:2404.04286.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Preprint*, arXiv:2303.11366.

SilicoFlow Team. 2025. Siliconflow model hub. Accessed: 2025-08-30.

Amos Tversky. 1969. Intransitivity of preferences. *Psychological review*, 76(1):31.

Yi Xu, Laura Ruis, Tim Rocktäschel, and Robert Kirk. 2025. Investigating non-transitivity in LLM-as-a-judge. In *Forty-second International Conference on Machine Learning*.

Yan Yu, Yilun Liu, Minggui He, Shimin Tao, Weibin Meng, Xinhua Yang, Li Zhang, Hongxia Ma, Chang Su, Hao Yang, and Fuliang Li. 2025a. Elspr: Evaluator llm training data self-purification on non-transitive preferences via tournament graph reconstruction. *Preprint*, arXiv:2505.17691.

Yijiong Yu, Huiqiang Jiang, Xufang Luo, Qianhui Wu, Chin-Yew Lin, Dongsheng Li, Yuqing Yang, Yongfeng Huang, and Lili Qiu. 2025b. Mitigate position bias in large language models via scaling a single dimension. *Preprint*, arXiv:2406.02536.

Qiyuan Zhang, Yufei Wang, Yuxin Jiang, Liangyou Li, Chuhan Wu, Yasheng Wang, Xin Jiang, Lifeng Shang, Ruiming Tang, Fuyuan Lyu, and Chen Ma.

2025a. Crowd comparative reasoning: Unlocking comprehensive evaluations for LLM-as-a-judge. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5059–5074, Vienna, Austria. Association for Computational Linguistics.

Yifan Zhang, Ge Zhang, Yue Wu, Kangping Xu, and Quanquan Gu. 2025b. Beyond bradley-terry models: A general preference model for language model alignment. In *Forty-second International Conference on Machine Learning*.

Appendix A Methodological Details

This section provides comprehensive technical details for the core analytical methods employed in our study. These implementations support the reproducibility of our results and the methodological rigor discussed in Section 3.

Appendix A.1 Permutation Testing Implementation

For each of 688 motions and 2 stances, we evaluated all $5! = 120$ model order permutations. Each permutation required $\binom{5}{2} = 10$ pairwise comparisons, totaling $688 \times 2 \times 120 = 165,120$ tournament graphs. Cycle detection used depth-first search with backtracking, recording aggregate counts across permutations. While artificial compared to natural evaluation conditions, this approach systematically reveals the maximal inconsistency potential under ordering variation.

Appendix A.2 Statistical Model Specifications

Bayesian Elo Model: Implemented via Markov Chain Monte Carlo (MCMC) sampling with 4 chains, 500 tuning iterations followed by 2,000 draw iterations. Weakly informative priors were specified as $\theta \sim \mathcal{N}(1500, 400)$ for Elo ratings. Convergence was verified via $\hat{R} < 1.01$ for all parameters.

Bayesian Bradley-Terry Model: Implemented using MCMC sampling with identical chain configuration (4 chains, 500 tune + 2,000 draw iterations). Weakly informative normal priors $\theta \sim \mathcal{N}(0, 1)$ were placed on ability parameters, providing natural regularization equivalent to L2 penalty in maximum likelihood estimation. Model convergence was confirmed through $\hat{R} < 1.01$ diagnostics.

Position Bias Analysis: Position bias was quantified using McNemar's test statistic:

$$\chi^2 = \frac{(|n_{01} - n_{10}| - 1)^2}{n_{01} + n_{10}}$$

where n_{01} and n_{10} count order-dependent preference reversals between argument position configurations.

Appendix A.3 Detailed Model Size Correlation Analysis

The scale-effect analysis followed three methodological steps: (1) normality verification via Shapiro-Wilk tests, (2) linear correlation analysis using Pearson coefficients, and (3) non-parametric validation with Spearman ranks. The complete quantitative results of these correlations are presented in Table 3.

Appendix B Supplementary Results: Model Performance and Consistency

This section provides extended results on model performance and the structure of inconsistency, complementing the findings in Section 4.1. It includes detailed Bayesian estimates, model rankings via PageRank, order bias analysis, and an external benchmark comparison for context.

Bayesian model estimates. Table 4 presents the Bayesian Elo ratings and Bradley-Terry ability estimates with 94% HDI and R-hat metrics.

Model ranking via PageRank. Table 5 provides the PageRank scores and cycle participation rates for each model.

External benchmark comparison. Table 6 provides a directional comparison of our Elo ratings with a public leaderboard (Chatbot Arena).

Visualization of model performance and cycle structure. Figure 2 combines four subfigures: (a) average win rate by model, (b) pairwise win probability matrix, (c) cycle length distribution, and (d) model participation rates in cycles.

Appendix C Supplementary Results: Distributional Analysis

This section provides the detailed statistical analyses underpinning the distributional findings in Section 4.2 and the control experiment in Section 4.3. It includes goodness-of-fit comparisons for the negative binomial distribution and the contrasting normal distribution observed under random preferences.

Table 3: Complete Model Size Correlation Results

Metric	Pearson Correlation		Spearman Rank Correlation	
	r	p-value	ρ	p-value
Cycle Participation	0.924	0.025	0.9	0.037
Win Rate	0.691	0.196	1.0	< 0.001
Elo Rating	0.688	0.199	1.0	< 0.001
Bradley-Terry Score	0.795	0.108	0.9	0.037

Table 4: Comparison of Bayesian Elo Ratings and Bradley-Terry Ability Estimates with 94% HDI and R-hat Metrics

Model	Bayesian Elo Model					Bradley-Terry Model				
	Rating	94% HDI		R-hat	Rank	Ability	94% HDI		R-hat	Rank
		Lower	Upper				Lower	Upper		
DeepSeek-R1	1682.3	1594.3	1768.6	1.002	1	0.569	-0.248	1.442	1.010	1
MiniMax-M1	1624.1	1538.7	1711.8	1.003	2	0.264	-0.553	1.139	1.010	2
GPT-4o	1592.8	1504.8	1678.6	1.003	3	0.115	-0.704	0.982	1.010	3
Qwen3-14B	1527.7	1445.8	1620.0	1.003	4	0.007	-0.811	0.880	1.010	4
Qwen3-8B	1080.7	994.4	1168.5	1.002	5	-0.964	-1.792	-0.099	1.010	5

Table 5: Model PageRank Scores and Cycle Participation Rates

Model	PageRank	Participation Rate
MiniMax-M1	0.2301	73.81%
GPT-4o	0.2256	72.48%
DeepSeek-R1	0.2029	64.39%
Qwen3-14B	0.1756	54.68%
Qwen3-8B	0.1658	50.71%

Table 6: Elo comparison with a human-facing leaderboard (Chatbot Arena, Text) (LMArena Team, 2025). Values are not directly comparable across protocols; we report them only for directional context.

Model	Our Debate Elo	Text Arena Elo
DeepSeek-R1	1682 (1st)	1417 (8th)
MiniMax-M1	1624 (2nd)	1370 (34th)
GPT-4o	1593 (3rd)	*Not listed*
Qwen3-14B	1528 (4th)	*Not listed*
Qwen3-8B	1081 (5th)	*Not listed*

(a) DeepSeek-R1 consistently leads while Qwen3-8B lags, illustrating wide dispersion across models. This establishes a stable global hierarchy despite local inconsistencies.

(b) Pairwise win probabilities reveal both stable edges and contested matchups that seed cycles. This shows that non-transitivity emerges from specific contested comparisons rather than random variation.

(c) Three-node cycles dominate the distribution, showing that non-transitivity is locally concentrated. This indicates cycles are structured and measurable, not arbitrary noise.

(d) Cycle participation rates cluster on specific models, indicating structured sources of inconsistency. This highlights that inconsistency is model-dependent and reproducible.

Figure 2: Combined visualizations of win rates, pairwise win probabilities, cycle lengths, and model participation rates in cycles.

Distribution fitting for cycle counts. Table 7 presents the complete fitting results for the negative binomial, zero-inflated negative binomial, normal, and Poisson distributions, with 95% confidence intervals.

Distributional analysis of random preferences. Figure 3 shows the CDF and PMF plots for random preference experiments at p=0.3 and p=0.5, which follow normal distributions, contrasting with the negative binomial distribution of LLM judgments.

Appendix D Supplementary Results: Detailed Control Experiment

This appendix provides the full details of the control experiment described in Section 4.3, designed to validate the specificity of the negative binomial distribution to LLM judgment patterns.

Experimental Design. We maintained identical experimental conditions to our main study but replaced GPT-4o's pairwise comparisons with random preferences generated at two probability levels: $p = 0.5$ (complete randomness) and $p = 0.7$ (moderate bias). This design allows us to examine whether the negative binomial pattern persists when LLM-specific judgment heuristics are removed.

Distributional Contrast and Statistical Comparison. The results reveal a striking contrast between LLM judgments and random preferences (Table 8 reproduced below). For LLM judgments, the negative binomial distribution provides the optimal fit (AIC = 4384.1, ΔAIC = 0.0, weight = 1.0000, R² = 0.9973), significantly outperforming alternative distributions. In contrast, both random preference conditions ($p = 0.5$ and $p = 0.7$) are best described by normal distributions (AIC = 9348.4 and 9365.3 respectively, weights = 1.0000).

Theoretical Interpretation. The normal distribution observed under random preferences aligns with central limit theorem expectations when aggregating 120 independent permutations. The significantly better fit of the negative binomial distribution to LLM data indicates *overdispersion*—variance exceeding mean—characteristic of processes with heterogeneity or clustering. This pattern suggests that LLM judgments exhibit *consistent inconsistency*: certain debate motions or argument combinations systematically trigger more non-transitive preferences, while others remain relatively stable.

Methodological Implications. This control experiment provides crucial validation that our graph-theoretic construction does not inherently produce negative binomial distributed cycle counts. The distributional difference confirms that the negative binomial pattern captures genuine properties of LLM evaluation consistency rather than construction artifacts.

Visual Evidence. As shown in Figure 3, the CDF and PMF plots for random preferences (both $p = 0.3$ and $p = 0.5$) clearly follow normal distributions, in stark contrast to the negative binomial distribution observed for LLM judgments. This visual evidence, combined with the statistical comparison, provides robust confirmation that the negative binomial pattern emerges specifically from structured LLM evaluation behaviors.

Appendix E Supplementary Results: Linguistic and Bias Analysis

This section presents the complete statistical output for the Poisson regression analysis investigating linguistic correlates of cycle formation (supporting Section 4.4) and the detailed breakdown of position (order) bias across model pairs, supplementing the discussion in Section 4.5.

Full regression results. Table 9 provides the complete Poisson regression coefficients, standard errors, z-values, and p-values for all linguistic features analyzed.

Order bias analysis. Table 10 shows the order bias percentages for selected model pairs, both for pro and con stances.

Appendix F Supplementary Results: Extended Analyses

This section contains additional exploratory analyses that provide deeper insights into the structure of Condorcet cycles (edge frequencies, common patterns) and model efficiency metrics. These results offer granular details for readers interested in the underlying mechanics of inconsistency.

Cycle edge frequencies. Table 11 reports the frequency of each directed edge (row model beating column model) that appears within Condorcet cycles, indicating which pairwise comparisons are most implicated in intransitive preferences.

Table 7: Distribution Fitting Results for Cycle Counts (95% CI)

Distribution	R^2	Parameters	AIC
Negative Binomial	**0.9973** [0.9787, 0.9980]	$n = 0.705$ [0.633, 0.783] $p = 0.076$ [0.067, 0.088]	**4384.11**
Zero-Inflated NB	0.9857 [0.9857, 0.9857]	$\pi = 0.145$ [0.119, 0.171] $n = 1.138$ [1.043, 1.253] $p = 0.102$ [0.090, 0.117]	4451.33
Normal	0.8380 [0.7529, 0.8970]	$\mu = 8.581$ [7.781, 9.431] $\sigma = 10.808$ [9.736, 11.899]	5239.35
Poisson	0.3527 [0.1596, 0.4624]	$\lambda = 8.581$ [7.849, 9.433]	9693.22

(a) CDF: Random preferences (p=0.3)

(b) CDF: Random preferences (p=0.5)

(c) PMF: Random preferences (p=0.3)

(d) PMF: Random preferences (p=0.5)

Figure 3: Distributional analysis of random preference experiments. Both p=0.3 and p=0.5 conditions follow normal distributions (R²=0.9972 and R²=0.9984 respectively), contrasting sharply with the negative binomial distribution of LLM judgments (Figure 1).

Table 8: Distribution Fitting Comparison: LLM Judgments vs. Random Preferences (n=688 motions)

Experiment	Distribution	Parameters	Goodness of Fit			
			AIC	ΔAIC	Weight	R²(CDF)
LLM Judgments	**Negative Binomial**	$n = 0.705, p = 0.076$	**4384.1**	**0.0**	**1.0000**	**0.9973**
	Zero-Inflated NB	$\pi = 0.145, r = 1.138, p = 0.102$	4451.3	67.2	0.0000	0.9857
	Normal	$\mu = 8.581, \sigma = 10.81$	5239.4	778.1	0.0000	0.8380
	Poisson	$\lambda = 8.581$	9693.2	5309.1	0.0000	0.3527
Random Preferences (p=0.3)	Negative Binomial	$r = 5.01, p = 0.010$	9403.6	55.1	0.0000	0.9888
	Zero-Inflated NB	—	—	—	—	—
	Normal	$\mu = 502.9, \sigma = 215.3$	**9348.4**	**0.0**	**1.0000**	**0.9972**
	Poisson	$\lambda = 502.9$	72216.7	62868.3	0.0000	0.3466
Random Preferences (p=0.5)	Negative Binomial	$r = 6.23, p = 0.010$	9538.1	172.8	0.0000	0.9741
	Zero-Inflated NB	—	—	—	—	—
	Normal	$\mu = 620.9, \sigma = 218.0$	**9365.3**	**0.0**	**1.0000**	**0.9984**
	Poisson	$\lambda = 620.9$	63715.4	54350.1	0.0000	0.3098

Table 9: Full Poisson Regression Results for Linguistic Features

Feature	Coefficient (β)	Std. Error	z-value	p-value	Sig.
Intercept	2.1430	0.0131	163.72	< 0.001	***
Syntactic Complexity	0.1299	0.0267	4.86	< 0.001	***
Verb Ratio	0.0867	0.0171	5.07	< 0.001	***
Flesch Reading Ease	-0.0850	0.0250	-3.40	< 0.001	***
Semantic Dispersion	-0.0570	0.0134	-4.24	< 0.001	***
Noun Ratio	0.0371	0.0168	2.20	0.028	*
Sentiment Polarity	-0.0363	0.0142	-2.55	0.011	*
Word Length Average	-0.0525	0.0271	-1.94	0.052	
Sentiment Subjectivity	-0.0204	0.0137	-1.49	0.137	
NER Count	0.0204	0.0170	1.20	0.230	
Lexical Diversity	0.0159	0.0148	1.07	0.283	
Length	-0.0312	0.0302	-1.03	0.301	
Entropy	-0.0091	0.0158	-0.58	0.564	

Note: N = 688 motions. Significance: *** p < 0.001, ** p < 0.01, * p < 0.05.

Table 10: Order Bias Analysis for Selected Model Pairs

Model Pair	Order Bias (Pro, %)	Order Bias (Con, %)
GPT-4o vs DeepSeek-R1	15.6	25.4
Qwen3-14B vs MiniMax-M1	32.0	31.4
Qwen3-8B vs DeepSeek-R1	28.1	32.5
MiniMax-M1 vs GPT-4o	29.6	30.4
Qwen3-14B vs Qwen3-8B	28.0	30.6

Note: Bias represents proportion favoring first-presented arguments. Global mean bias = 0.3356 (std=0.1317).

Table 11: Cycle Edge Frequency Matrix

	DeepSeek-R1	MiniMax-M1	GPT-4o	Qwen3-14B	Qwen3-8B
DeepSeek-R1	–	668	763	604	382
MiniMax-M1	650	–	946	532	362
GPT-4o	552	556	–	641	503
Qwen3-14B	350	647	385	–	476
Qwen3-8B	407	655	580	81	–

Note: Frequency of directed edges (row $\succ$ column) in Condorcet cycles.

Most frequent cycle patterns. Table 12 lists the top 5 most frequently observed 3-cycle patterns (sequences of model A beats B, B beats C, and C beats A), revealing the most common structures of intransitivity.

Model efficiency metrics. Table 13 presents model parameter counts and the derived efficiency metric (win rate per billion parameters), providing context for the performance differences observed.

Correlation with model size. Table 14 summarizes the correlation between published model size (parameter count) and key evaluation metrics, providing statistical evidence for the scale-consistency tradeoff discussed in the main text.

Appendix G Experimental Materials

This section contains the complete prompt templates used for argument generation and evaluation, as referenced in Section 3.

Argument Generation Prompt (Pro-Stance):

```
%%% Pro-argument Prompt %%%
Please provide a clear and concise
    argument in favor of the topic.
    Focus on
the most important reasons supporting
    the position, and present your
    points
in a logical and organized manner. Only
    output the argument itself    do
    not
include introductions, conclusions,
    summaries, emojis, or any extra
commentary. The response should be plain
     text without special formatting.

Topic: {motion}
```

Argument Generation Prompt (Con-Stance):

```
%%% Con-argument Prompt %%%
Please provide a clear and concise
    argument against the topic. Focus on
the most important reasons opposing the
    position, and present your points
in a logical and organized manner. Only
    output the argument itself    do
    not
include introductions, conclusions,
    summaries, emojis, or any extra
commentary. The response should be plain
     text without special formatting.

Topic: {motion}
```

Judge Model Comparison Prompt:

```
%%% JUDGMENT PROMPT %%%
Here is a motion and two arguments about
    it.
```

```
Please fairly choose which argument is
    better overall. If both are equally
good, return "Tie".

Return a JSON object with exactly two
    keys: "winner" and "reason".

 "winner" must be one of "Argument
 1", "Argument 2", or "Tie".

 "reason" should be a concise
 explanation in plain text (no JSON
 formatting,
 no code blocks).

### Example output:
{
  "winner": "Argument X",
  "reason": "Argument X is more
     persuasive due to its clearer
     structure,
          stronger evidence, and more
              direct engagement with
              the motion."
}

Motion: {motion}
Argument 1: {arg1}
Argument 2: {arg2}
```

Table 12: Top 5 Most Frequent 3-Cycle Patterns

Model Sequence	Frequency
DeepSeek-R1 → GPT-4o → MiniMax-M1 → DeepSeek-R1	520
GPT-4o → MiniMax-M1 → Qwen3-8B → GPT-4o	400
DeepSeek-R1 → MiniMax-M1 → Qwen3-14B → DeepSeek-R1	360
GPT-4o → MiniMax-M1 → Qwen3-14B → GPT-4o	340
DeepSeek-R1 → GPT-4o → Qwen3-8B → DeepSeek-R1	320

Table 13: Model Parameter Count and Efficiency Metrics

Model	Parameter Count (B)	Win Rate per B Parameters
DeepSeek-R1	671	0.09
MiniMax-M1	456	0.13
GPT-4o	200	0.28
Qwen3-14B	14	3.69
Qwen3-8B	8	2.57

Table 14: Correlation between published model size and evaluation metrics ($N = 5$ models). Cycle participation correlates strongly with parameter count ($r = 0.924$, $p = 0.025$), while Elo and win rate do not. This provides preliminary evidence of a *scale–consistency tradeoff*.

Metric	Correlation	p-value	Interpretation
Participation	0.924	0.025	Significant positive
Win Rate	0.691	0.196	Not significant
Elo	0.688	0.199	Not significant
Bradley-Terry	0.795	0.108	Not significant