Provably Efficient Reinforcement Learning with Linear Function Approximation under Adaptivity Constraints

Abstract

We study reinforcement learning (RL) with linear function approximation under the adaptivity constraint. We consider two popular limited adaptivity models: the batch learning model and the rare policy switch model, and propose two efficient online RL algorithms for episodic linear Markov decision processes, where the transition probability and the reward function can be represented as a linear function of some known feature mapping. In specific, for the batch learning model, our proposed LSVI-UCB-Batch algorithm achieves an $\widetilde{O}(\sqrt{d^3 H^3 T} + dHT/B)$ regret, where d is the dimension of the feature mapping, H is the episode length, T is the number of interactions and B is the number of batches. Our result suggests that it suffices to use only $\sqrt{T/dH}$ batches to obtain $\widetilde{O}(\sqrt{d^3 H^3 T})$ regret. For the rare policy switch model, our proposed LSVI-UCB-RareSwitch algorithm enjoys an $\widetilde{O}(\sqrt{d^3 H^3 T [1 + T/(dH)]^{dH/B}})$ regret, which implies that $dH \log T$ policy switches suffice to obtain the $\widetilde{O}(\sqrt{d^3 H^3 T})$ regret. Our algorithms achieve the same regret as the LSVI-UCB algorithm (Jin et al., 2020), yet with a substantially smaller amount of adaptivity. We also establish a lower bound for the batch learning model, which suggests that the dependency on B in our regret bound is tight.

1 Introduction

Real-world reinforcement learning (RL) applications often come with possibly infinite state and action space, and in such a situation classical RL algorithms developed in the tabular setting are not applicable anymore. A popular approach to overcoming this issue is by applying function approximation techniques to the underlying structures of the Markov decision processes (MDPs). For example, one can assume that the transition probability and the reward are linear functions of a known feature mapping $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$, where $\mathcal{S}$ and $\mathcal{A}$ are the state space and action space, and d is the dimension of the embedding. This gives rise to the so-called linear MDP model (Yang and Wang, 2019; Jin et al., 2020). Assuming access to a generative model, efficient algorithms under this setting have been proposed by Yang and Wang (2019) and Lattimore et al. (2020). For online finite-horizon episodic linear MDPs, Jin et al. (2020) proposed an LSVI-UCB algorithm that achieves $\widetilde{O}(\sqrt{d^3 H^3 T})$ regret, where H is the planning horizon (i.e., length of each episode) and T is the number of interactions.

However, all the aforementioned algorithms require the agent to update the policy in every episode. In practice, it is often unrealistic to frequently switch the policy in the face of big data, limited computing resources as well as inevitable switching costs. Thus one may want to batch the data stream and update the policy at the end of each period. For example, in clinical trials, each phase (batch) of the trial amounts to applying a medical treatment to a batch of patients in parallel. The outcomes

of the treatment are not observed until the end of the phase and will be subsequently used to design experiments for the next phase. Choosing the appropriate number and sizes of the batches is crucial to achieving nearly optimal efficiency for the clinical trial. This gives rise to the limited adaptivity setting, which has been extensively studied in many online learning problems including prediction-from-experts (PFE) (Kalai and Vempala, 2005; Cesa-Bianchi et al., 2013), multi-armed bandits (MAB) (Arora et al., 2012; Cesa-Bianchi et al., 2013) and online convex optimization (Jaghargh et al., 2019; Chen et al., 2020), to mention a few. Nevertheless, in the RL setting, learning with limited adaptivity is relatively less studied. Bai et al. (2019) introduced two notions of adaptivity in RL, *local switching cost* and *global switching cost*, that are defined as follows

$$N_{\text{local}} = \sum_{k=1}^{K-1} \sum_{h=1}^{H} \sum_{s \in \mathcal{S}} \mathbb{1}\{\pi_h^k(s) \neq \pi_h^{k+1}(s)\} \quad \text{and} \quad N_{\text{global}} = \sum_{k=1}^{K-1} \mathbb{1}\{\pi^k \neq \pi^{k+1}\}, \qquad (1.1)$$

where $\pi^k = \{\pi_h^k : \mathcal{S} \to \mathcal{A}\}_{h \in [H]}$ is the policy for the k-th episode of the MDP, $\pi^k \neq \pi^{k+1}$ means that there exists some $(h, s) \in [H] \times \mathcal{S}$ such that $\pi_h^k(s) \neq \pi_h^{k+1}(s)$, and K is the number of episodes. Then they proposed a Q-learning method with UCB2H exploration that achieves $\widetilde{O}(\sqrt{H^3 SAT})$ regret with $O(H^3 SA \log(T/(AH)))$ local switching cost for tabular MDPs, but they did not provide tight bounds on the global switching cost.

In this paper, based on the above motivation, we aim to develop online RL algorithms with linear function approximation under adaptivity constraints. In detail, we consider time-inhomogeneous[1] episodic linear MDPs (Jin et al., 2020) where both the transition probability and the reward function are unknown to the agent. In terms of the limited adaptivity imposed on the agent, we consider two scenarios that have been previously studied in the online learning literature (Perchet et al., 2016; Abbasi-Yadkori et al., 2011): the batch learning model and the rare policy switch model. More specifically, in the batch learning model (Perchet et al., 2016), the agent is forced to pre-determine the number of batches (or equivalently batch size). Within each batch, the same policy is used to select actions, and the policy is updated only at the end of this batch. The amount of adaptivity in the batch learning model is measured by the number of batches, which is expected to be as small as possible. In contrast, in the rare policy switch model (Abbasi-Yadkori et al., 2011), the agent can adaptively choose when to switch the policy and therefore start a new batch in the learning process as long as the total number of policy updates does not exceed the given budget on the number of policy switches. The amount of adaptivity in the rare policy switch model can be measured by the number of policy switches, which turns out to be the same as the global switching cost introduced in Bai et al. (2019). It is worth noting that for the same amount of adaptivity[2], the rare policy switch model can be seen as a relaxation of the batch learning model since the agent in the batch learning model can only change the policy at pre-defined time steps. In our work, for each of these limited adaptivity models, we propose a variant of the LSVI-UCB algorithm (Jin et al., 2020), which can be viewed as an RL algorithm with full adaptivity in the sense that it switches the policy at a per-episode scale. Our algorithms can attain the same regret as LSVI-UCB, yet with a substantially smaller number of batches/policy switches. This enables parallel learning and improves the large-scale deployment of RL algorithms with linear function approximation.

The main contributions of this paper are summarized as follows:

- For the *batch learning* model, we propose an LSVI-UCB-Batch algorithm for linear MDPs and show that it enjoys an $\widetilde{O}(\sqrt{d^3 H^3 T} + dHT/B)$ regret, where d is the dimension of the feature mapping, H is the episode length, T is the number of interactions and B is the number of batches. Our result suggests that it suffices to use only $\sqrt{T/dH}$ batches, rather than T batches, to obtain the same regret $\widetilde{O}(\sqrt{d^3 H^3 T})$ achieved by LSVI-UCB (Jin et al., 2020) in the fully sequential decision model. We also prove a lower bound of the regret for this model, which suggests that the required number of batches $\widetilde{O}(\sqrt{T})$ is sharp.

- For the *rare policy switch* model, we propose an LSVI-UCB-RareSwitch algorithm for linear MDPs and show that it enjoys an $\widetilde{O}(\sqrt{d^3 H^3 T[1 + T/(dH)]^{dH/B}})$ regret, where B is the number

---

[1]We say an episodic MDP is time-inhomogeneous if its reward and transition probability are different at different stages within each episode. See Definition 3.2 for details.

[2]The number of batches in the batch learning model is comparable to the number of policy switches in the rare policy switch model.

of policy switches. Our result implies that $dH \log T$ policy switches are sufficient to obtain the same regret $\widetilde{O}(\sqrt{d^3 H^3 T})$ achieved by LSVI-UCB. The number of policy switches is much smaller than that[3] of the batch learning model when T is large.

When we prepare this paper, we notice a concurrent work by Gao et al. (2021), where they proposed an algorithm achieving $\widetilde{O}(\sqrt{d^3 H^3 T})$ regret with a $O(dH \log K)$ global switching cost in the rare policy switch model. They also proved a $\Omega(dH / \log d)$ lower bound on the global switching cost. The focus of our paper is different from theirs: our goal is to design efficient RL algorithms under a switching cost budget B, while their goal is to achieve the optimal rate in terms of T with as little switching cost as possible. On the other hand, for the rare policy switch model, our proposed algorithm (LSVI-UCB-RareSwitch) along its regret bound can imply their results by optimizing our regret bound concerning the switching cost budget B.

The rest of the paper is organized as follows. In Section 2 we discuss previous works related to this paper, with a focus on RL with linear function approximation and online learning with limited adaptivity. In Section 3 we introduce necessary preliminaries for MDPs and adaptivity constraints. Sections 4 and 5 present our proposed algorithms and the corresponding theoretical results for the batch learning model and the rare policy switch model respectively. In Section 6 we present the numerical experiment which supports our theory. Finally, we conclude our paper and point out a future direction in Section 7.

Notation We use lower case letters to denote scalars and use lower and upper case boldface letters to denote vectors and matrices respectively. For a vector $\mathbf{x} \in \mathbb{R}^d$ and matrix $\mathbf{\Sigma} \in \mathbb{R}^{d \times d}$, we denote by $\|\mathbf{x}\|_2$ the Euclidean norm and define $\|\mathbf{x}\|_{\mathbf{\Sigma}} = \sqrt{\mathbf{x}^\top \mathbf{\Sigma} \mathbf{x}}$. For any positive integer n, we denote by $[n]$ the set $\{1, \dots, n\}$. For any finite set A, we denote by $|A|$ the cardinality of A. For two sequences $\{a_n\}$ and $\{b_n\}$, we write $a_n = O(b_n)$ if there exists an absolute constant C such that $a_n \leq C b_n$, and we write $a_n = \Omega(b_n)$ if there exists an absolute constant C such that $a_n \geq C b_n$. We use $\widetilde{O}(\cdot)$ to further hide the logarithmic factors.

2   Related Works

Reinforcement Learning with Linear Function Approximation Recently, there have been many advances in RL with function approximation, especially the linear case. Jin et al. (2020) proposed an efficient algorithm for the first time for linear MDPs of which the transition probability and the rewards are both linear functions with respect to a feature mapping $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$. Under similar assumptions, different settings (e.g., discounted MDPs) have also been studied in Yang and Wang (2019); Du et al. (2020); Zanette et al. (2020); Neu and Pike-Burke (2020) and He et al. (2021). A parallel line of work studies linear mixture MDPs (a.k.a. linear kernel MDPs) based on a ternary feature mapping $\psi : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}^d$ (see Jia et al. (2020); Zhou et al. (2021b); Cai et al. (2020); Zhou et al. (2021a)). For other function approximation settings, we refer readers to generalized linear model (Wang et al., 2021), general function approximation with Eluder dimension (Wang et al., 2020; Ayoub et al., 2020), kernel approximation (Yang et al., 2020), function approximation with disagreement coefficients (Foster et al., 2021) and bilinear classes (Du et al., 2021).

Online Learning with Limited Adaptivity As we mentioned before, online learning with limited adaptivity has been studied in two popular models of adaptivity constraints: the batch learning model and the rare policy switch model.

For the *batch learning model*, Altschuler and Talwar (2018) proved that the optimal regret bound for prediction-from-experts (PFE) is $\widetilde{O}(\sqrt{T \log n})$ when the number of batches $B = \Omega(\sqrt{T \log n})$, and $\min(\widetilde{O}(T \log n / B), T)$ when $B = O(\sqrt{T \log n})$, exhibiting a phase-transition phenomenon[4]. Here T is the number of rounds and n is the number of actions. For general online convex optimization, Chen et al. (2020) showed that the minimax regret bound is $\widetilde{O}(T / \sqrt{B})$. Perchet et al. (2016) studied batched 2-arm bandits, and Gao et al. (2019) studied the batched multi-armed bandits (MAB). Dekel et al. (2014) proved a $\Omega(T / \sqrt{B})$ lower bound for batched MAB, and Altschuler and Talwar (2018) further characterized the dependence on the number of actions n and showed that the corresponding

---

[3]The number of policy switches is identical to the number of batches in the batch learning model.
[4]They call it B-switching budget setting, which is identical to the batch learning model.

minimax regret bound is $\min(\widetilde{O}(T\sqrt{n}/\sqrt{B}), T)$. For batched linear bandits with adversarial contexts, Han et al. (2020) showed that the minimax regret bound is $\widetilde{O}(\sqrt{dT} + dT/B)$ where d is the dimension of the context vectors. Better rates can be achieved for batched linear bandits with stochastic contexts as shown in Esfandiari et al. (2021); Han et al. (2020); Ruan et al. (2020).

For the *rare policy switch model*, the minimax optimal regret bound for PFE is $O(\sqrt{T \log n})$ in terms of both the expected regret (Kalai and Vempala, 2005; Geulen et al., 2010; Cesa-Bianchi et al., 2013; Devroye et al., 2015) and high-probability guarantees (Altschuler and Talwar, 2018), where T is the number of rounds, and n is the number of possible actions. For MAB, the minimax regret bound has been shown to be $\widetilde{O}(T^{2/3}n^{1/3})$ by Arora et al. (2012); Dekel et al. (2014). For stochastic linear bandits, Abbasi-Yadkori et al. (2011) proposed a rarely switching OFUL algorithm achieving $\widetilde{O}(d\sqrt{T})$ regret with $\log(T)$ batches. Ruan et al. (2020) proposed an algorithm achieving $\widetilde{O}(\sqrt{dT})$ regret with less than $O(d \log d \log T)$ batches for stochastic linear bandits with adversarial contexts.

For episodic RL with finite state and action space, Bai et al. (2019) proposed an algorithm achieving $\widetilde{O}(\sqrt{H^3 SAT})$ regret with $O(H^3 SA \log(T/(AH)))$ local switching cost where S and A are the number of states and actions respectively. They also provided a $\Omega(HSA)$ lower bound on the local switching cost that is necessary for sublinear regret. For the global switching cost, Zhang et al. (2021) proposed an MVP algorithm with at most $O(SA \log(KH))$ global switching cost for time-homogeneous tabular MDPs.

3 Preliminaries

3.1 Markov Decision Processes

We consider the time-inhomogeneous episodic Markov decision process, which is denoted by a tuple $M(\mathcal{S}, \mathcal{A}, H, \{r_h\}_{h \in [H]}, \{\mathbb{P}_h\}_{h \in [H]})$. Here $\mathcal{S}$ is the state space (may be infinite), $\mathcal{A}$ is the action space where we allow the feasible action set to change from step to step, H is the length of each episode, and $r_h : \mathcal{S} \times \mathcal{A} \to [0, 1]$ is the reward function for each stage $h \in [H]$. At each stage $h \in [H]$, $\mathbb{P}_h(s'|s, a)$ is the transition probability function which represents the probability for state s to transit to state s' given action a. A policy π consists of H mappings, $\{\pi_h : \mathcal{S} \to \mathcal{A}\}_{h \in [H]}$. For any policy π, we define the action-value function $Q_h^\pi(s, a)$ and value function $V_h^\pi(s)$ as follows:

$$Q_h^\pi(s, a) = r_h(s, a) + \mathbb{E}_\pi \left[\sum_{i=h}^H r_i(s_i, a_i) \bigg| s_h = s, a_h = a \right], \qquad V_h^\pi(s) = Q_h^\pi(s, \pi_h(s)),$$

where $a_i \sim \pi_i(\cdot|s_i)$ and $s_{i+1} \sim \mathbb{P}_i(\cdot|s_i, a_i)$. The optimal value function V_h^* and the optimal action-value function $Q_h^*(s, a)$ are defined as $V^*(s) = \sup_\pi V_h^\pi(s)$ and $Q_h^*(s, a) = \sup_\pi Q_h^\pi(s, a)$, respectively. For simplicity, for any function $V : \mathcal{S} \to \mathbb{R}$, we denote $[\mathbb{P}V](s, a) = \mathbb{E}_{s' \sim \mathbb{P}(\cdot|s,a)} V(s')$. In the online learning setting, at the beginning of k-th episode, the agent chooses a policy π^k and the environment selects an initial state s_1^k, then the agent interacts with environment following policy π^k and receives states s_h^k and rewards $r_h(s_h^k, a_h^k)$ for $h \in [H]$. To measure the performance of the algorithm, we adopt the following notion of the total regret, which is the summation of suboptimalities between policy π^k and optimal policy π^*:

Definition 3.1. We denote $T = KH$, and the regret $\text{Regret}(T)$ is defined as

$$\text{Regret}(T) = \sum_{k=1}^K \left[V_1^*(s_1^k) - V_1^{\pi^k}(s_1^k) \right].$$

3.2 Linear Function Approximation

In this work, we consider a special class of MDPs called *linear MDPs* (Yang and Wang, 2019; Jin et al., 2020), where both the transition probability function and reward function can be represented as a linear function of a given feature mapping $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$. Formally speaking, we have the following definition for linear MDPs.

Definition 3.2. $M(\mathcal{S}, \mathcal{A}, H, \{r_h\}_{h \in [H]}, \{\mathbb{P}_h\}_{h \in [H]})$ is called a linear MDP if there exist a *known* feature mapping $\phi(s, a) : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$, *unknown* measures $\{\boldsymbol{\mu}_h = (\mu_h^{(1)}, \cdots, \mu_h^{(d)})\}_{h \in [H]}$ over

174 $\mathcal{S}$ and unknown vectors $\{\boldsymbol{\theta}_h \in \mathbb{R}^d\}_{h \in [H]}$ with $\max_{h \in [H]}\{\|\boldsymbol{\mu}_h(\mathcal{S})\|_2, \|\boldsymbol{\theta}_h\|\} \leq \sqrt{d}$, such that the
175 following holds for all $h \in [H]$:

- For any state-action-state triplet $(s, a, s') \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}$, $\mathbb{P}_h(s'|s,a) = \langle \boldsymbol{\phi}(s,a), \boldsymbol{\mu}_h(s') \rangle$.

- For any state-action pair $(s, a) \in \mathcal{S} \times \mathcal{A}$, $r_h(s,a) = \langle \boldsymbol{\phi}(s,a), \boldsymbol{\theta}_h \rangle$.

178 Without loss of generality, we also assume that $\|\boldsymbol{\phi}(s,a)\|_2 \leq 1$ for all $(s,a) \in \mathcal{S} \times \mathcal{A}$.

179 With Definition 3.2, it is shown in Jin et al. (2020) that the action-value function can be written as a
180 linear function of the features.

181 **Proposition 3.3** (Proposition 2.3, Jin et al. 2020)**.** For a linear MDP, for any policy π, there ex-
182 ist weight vectors $\{\mathbf{w}_h^\pi\}_{h \in [H]}$ such that for any $(s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]$, we have $Q_h^\pi(s,a) = $
183 $\langle \boldsymbol{\phi}(s,a), \mathbf{w}_h^\pi \rangle$. Moreover, we have $\|\mathbf{w}_h^\pi\|_2 \leq 2H\sqrt{d}$ for all $h \in [H]$.

184 Therefore, with the known feature mapping $\boldsymbol{\phi}(\cdot, \cdot)$, it suffices to estimate the weight vectors
185 $\{\mathbf{w}_h^\pi\}_{h \in [H]}$ in order to recover the action-value functions. This is the core idea behind almost
186 all the algorithms and theoretical analyses for linear MDPs.

3.3 Models for Limited Adaptivity

188 In this work, we consider RL algorithms with limited adaptivity. There are two typical models for
189 online learning with such limited adaptivity: *batch learning model* (Perchet et al., 2016) and *rare*
190 *policy switch model* (Abbasi-Yadkori et al., 2011).

191 For the batch learning model, the agent pre-determines the batch grids $1 = t_1 < t_2 < \cdots < t_B <$
192 $t_{B+1} = K + 1$ at the beginning of the algorithm, where B is the number of batches. The b-th batch
193 consists of t_b-th to $(t_{b+1} - 1)$-th episodes, and the agent follows the same policy within each batch.
194 The adaptivity is measured by the number of batches.

195 For the rare policy switch model, the agent can decide whether she wants to switch the current policy
196 or not. The adaptivity is measured by the number of policy switches, which is defined as

$$N_{\text{switch}} = \sum_{k=1}^{K-1} \mathbb{1}\{\pi^k \neq \pi^{k+1}\},$$

197 where $\pi^k \neq \pi^{k+1}$ means that there exists some $(h, s) \in [H] \times \mathcal{S}$ such that $\pi_h^k(s) \neq \pi_h^{k+1}(s)$. It is
198 worth noting that N_{switch} is identical to the *global switching cost* defined in (1.1).

199 Given a budget on the number of batches or the number of policy switches, we aim to design RL
200 algorithms with linear function approximation that can achieve the same regret as their full adaptivity
201 counterpart, e.g., LSVI-UCB (Jin et al., 2020).

4 RL in the Batch Learning Model

203 In this section, we consider RL with linear function approximation in the batch learning model, where
204 given the number of batches B, we need to pin down the batches before the agent starts to interact
205 with the environment.

4.1 Algorithm and Regret Analysis

207 We propose LSVI-UCB-Batch algorithm as displayed in Algorithm 1, which can be regarded as
208 a variant of the LSVI-UCB algorithm proposed in Jin et al. (2020) yet with limited adaptivity.
209 Algorithm 1 takes a series of batch grids $\{t_1, \ldots, t_{B+1}\}$ as input, where the i-th batch starts at t_i
210 and ends at $t_{i+1} - 1$. LSVI-UCB-Batch takes the uniform batch grids as its selection of grids, i.e.,
211 $t_i = (i - 1) \cdot \lfloor K/B \rfloor + 1, i \in [B]$. By Proposition 3.3, we know that for each $h \in [H]$, the optimal
212 value function Q_h^* has the linear form $\langle \boldsymbol{\phi}(\cdot, \cdot), \mathbf{w}_h^* \rangle$. Therefore, to estimate the Q_h^*, it suffices to
213 estimate $\mathbf{w}_h^*$. At the beginning of each batch, Algorithm 1 calculates $\mathbf{w}_h^k$ as an estimate of $\mathbf{w}_h^*$ by
214 ridge regression (Line 8). Meanwhile, in order to measure the uncertainty of $\mathbf{w}_h^k$, Algorithm 1 sets
215 the estimate $Q_h^k(\cdot, \cdot)$ as the summation of the linear function $\langle \boldsymbol{\phi}(\cdot, \cdot), \mathbf{w}_h^k \rangle$ and a Hoeffding-type

---

Algorithm 1 LSVI-UCB-Batch

Require: Number of batches B, confidence radius β, regularization parameter λ
1: Set $b \leftarrow 1, t_i \leftarrow (i-1) \cdot \lfloor K/B \rfloor + 1, i \in [B]$
2: **for** episode $k = 1, 2, \ldots, K$ **do**
3:     Receive the initial state s_1^k
4:     **if** $k = t_b$ **then**
5:         $b \leftarrow b+1, Q_{H+1}^k(\cdot, \cdot) \leftarrow 0$
6:         **for** stage $h = H, H-1, \ldots, 1$ **do**
7:             $\boldsymbol{\Lambda}_h^k \leftarrow \sum_{\tau=1}^{k-1} \boldsymbol{\phi}(s_h^\tau, a_h^\tau) \boldsymbol{\phi}(s_h^\tau, a_h^\tau)^\top + \lambda \mathbf{I}$
8:             $\mathbf{w}_h^k \leftarrow (\boldsymbol{\Lambda}_h^k)^{-1} \sum_{\tau=1}^{k-1} \boldsymbol{\phi}(s_h^\tau, a_h^\tau) \cdot [r_h(s_h^\tau, a_h^\tau) + \max_{a \in \mathcal{A}} Q_{h+1}^k(s_{h+1}^\tau, a)]$
9:             $\Gamma_h^k(\cdot, \cdot) \leftarrow \beta \cdot [\boldsymbol{\phi}(\cdot, \cdot)^\top (\boldsymbol{\Lambda}_h^k)^{-1} \boldsymbol{\phi}(\cdot, \cdot)]^{1/2}$
10:            $Q_h^k(\cdot, \cdot) \leftarrow \min\{\boldsymbol{\phi}(\cdot, \cdot)^\top \mathbf{w}_h^k + \Gamma_h^k(\cdot, \cdot), H - h + 1\}^+, \pi_h^k(\cdot) \leftarrow \operatorname{argmax}_{a \in \mathcal{A}} Q_h^k(\cdot, a)$
11:         **end for**
12:     **else**
13:         $Q_h^k \leftarrow Q_h^{k-1}, \pi_h^k \leftarrow \pi_h^{k-1}, \forall h \in [H]$
14:     **end if**
15:     **for** stage $h = 1 \ldots, H$ **do**
16:         Take the action $a_h^k \leftarrow \pi_h^k(s_h^k)$, receive the reward $r_h(s_h^k, a_h^k)$ and the next state s_{h+1}^k
17:     **end for**
18: **end for**

---

exploration bonus term $\Gamma_h^k(\cdot, \cdot)$ (Line 10), which is calculated based on the confidence radius β. Then it sets the policy π_h^k as the greedy policy with respect to Q_h^k. Within each batch, Algorithm 1 simply keeps the policy used in the previous episode without updating (Line 13). Apparently, the number of batches of Algorithm 1 is B.

Here we would like to make a comparison between our LSVI-UCB-Batch and other related algorithms. The most related algorithm is LSVI-UCB proposed in Jin et al. (2020). The main difference between LSVI-UCB-Batch and LSVI-UCB is the introduction of batches. In detail, when $B = T$, LSVI-UCB-Batch degenerates to LSVI-UCB. Another related algorithm is the SBUCB algorithm proposed by Han et al. (2020). Both LSVI-UCB-Batch and SBUCB take uniform batch grids as the selection of batches. The difference is that SBUCB is designed for linear bandits, which is a special case of episodic MDPs with $H = 1$.

The following theorem presents the regret bound of Algorithm 1.

Theorem 4.1. There exists a constant $c > 0$ such that for any $\delta \in (0, 1)$, if we set $\lambda = 1$, $\beta = cdH\sqrt{\log(2dT/\delta)}$, then under Assumption 3.2, the total regret of Algorithm 1 is bounded by

$$\mathrm{Regret}(T) \leq 2H\sqrt{T \log\left(\frac{2dT}{\delta}\right)} + \frac{dHT}{2B \log 2} \log\left(\frac{T}{dH} + 1\right)$$
$$+ 4c\sqrt{2d^3 H^3 T \log\left(\frac{2dT}{\delta}\right) \log\left(\frac{T}{dH} + 1\right)}$$

with probability at least $1 - \delta$.

Theorem 4.1 suggests that the total regret of Algorithm 1 is bounded by $\widetilde{O}(\sqrt{d^3 H^3 T} + dHT/B)$. When $B = \Omega(\sqrt{T/dH})$, the regret of Algorithm 1 is $\widetilde{O}(\sqrt{d^3 H^3 T})$, which is the same as that of LSVI-UCB in Jin et al. (2020). However, it is worth noting that LSVI-UCB needs T batches, while Algorithm 1 only requires $\sqrt{T/dH}$ batches, which can be much smaller than T.

Next, we present a lower bound to show the dependency of the total regret on the number of batches for the batch learning model.

Theorem 4.2. Suppose that $B \geq (d-1)H/2$. Then for any batch learning algorithm with B batches, there exists a linear MDP such that the regret over the first T rounds is lower bounded by

$$\mathrm{Regret}(T) = \Omega(dH\sqrt{T} + dHT/B).$$

Algorithm 2 LSVI-UCB-RareSwitch

Require: Policy switch parameter η, confidence radius β, regularization parameter λ

1: Initialize $\mathbf{\Lambda}_h = \mathbf{\Lambda}_h^0 = \lambda \mathbf{I}_d$ for all $h \in [H]$
2: **for** episode $k = 1, 2, \ldots, K$ **do**
3:   Receive the initial state s_1^k
4:   **for** stage $h = 1, 2, \cdots, H$ **do**
5:     $\mathbf{\Lambda}_h^k \leftarrow \sum_{\tau=1}^{k-1} \phi(s_h^\tau, a_h^\tau)\phi(s_h^\tau, a_h^\tau)^\top + \lambda \mathbf{I}_d$
6:   **end for**
7:   **if** $\exists h \in [H], \det(\mathbf{\Lambda}_h^k) > \eta \cdot \det(\mathbf{\Lambda}_h)$ **then**
8:     $Q_{H+1}^k(\cdot, \cdot) \leftarrow 0$
9:     **for** step $h = H, H-1, \cdots, 1$ **do**
10:       $\mathbf{\Lambda}_h \leftarrow \mathbf{\Lambda}_h^k$
11:       $\mathbf{w}_h^k \leftarrow (\mathbf{\Lambda}_h^k)^{-1} \sum_{\tau=1}^{k-1} \phi(s_h^\tau, a_h^\tau) \cdot [r_h(s_h^\tau, a_h^\tau) + \max_{a \in \mathcal{A}} Q_{h+1}^k(s_{h+1}^\tau, a)]$
12:       $\Gamma_h^k(\cdot, \cdot) \leftarrow \beta \cdot [\phi(\cdot, \cdot)^\top (\mathbf{\Lambda}_h^k)^{-1} \phi(\cdot, \cdot)]^{1/2}$
13:       $Q_h^k(\cdot, \cdot) \leftarrow \min\{\phi(\cdot, \cdot)^\top \mathbf{w}_h^k + \Gamma_h^k(\cdot, \cdot), H - h + 1\}^+, \pi_h^k(\cdot) \leftarrow \operatorname{argmax}_{a \in \mathcal{A}} Q_h^k(\cdot, a)$
14:     **end for**
15:   **else**
16:     $Q_h^k \leftarrow Q_h^{k-1}, \pi_h^k \leftarrow \pi_h^{k-1}, \forall h \in [H]$
17:   **end if**
18:   **for** stage $h = 1 \ldots, H$ **do**
19:     Take the action $a_h^k \leftarrow \pi_h^k(s_h^k)$, receive the reward $r_h(s_h^k, a_h^k)$ and the next state s_{h+1}^k
20:   **end for**
21: **end for**

Theorem 4.2 suggests that in order to obtain a standard $\sqrt{T}$-regret, the number of batches B should be at least in the order of $\Omega(\sqrt{T})$, which is similar to its counterpart for batched linear bandits (Han et al., 2020).

5   RL in the Rare Policy Switch Model

In this section, we consider the rare policy switch model, where the agent can adaptively choose the batch sizes according to the information collected during the learning process.

5.1   Algorithm and Regret Analysis

We first present our second algorithm, LSVI-UCB-RareSwitch, as illustrated in Algorithm 2. Again, due to the nature of linear MDPs, we only need to estimate $\mathbf{w}_h^*$ by ridge regression, and then calculate the optimistic action-value function using the Hoeffding-type exploration bonus $\Gamma_h^k(\cdot, \cdot)$ along with the confidence radius β. Note that the size of the bonus term in Q_h^k is determined by $\mathbf{\Lambda}_h^k$. Intuitively speaking, the matrix $\mathbf{\Lambda}_h^k$ in Algorithm 2 represents how much information has been learned about the underlying MDP, and the agent only needs to switch the policy after collecting a significant amount of additional information. This is reflected by the determinant of $\mathbf{\Lambda}_h^k$, and the upper confidence bound will become tighter (shrink) as $\det(\mathbf{\Lambda}_h^k)$ increases. The determinant based criterion is similar to the idea of doubling trick, which has been used in the rarely switching OFUL algorithm for stochastic linear bandits (Abbasi-Yadkori et al., 2011), UCRL2 algorithm for tabular MDPs (Jaksch et al., 2010), and UCLK/UCLK+ for linear mixture MDPs in the discounted setting (Zhou et al., 2021b,a).

As shown in Algorithm 2, for each stage $h \in [H]$ the algorithm maintains a matrix $\mathbf{\Lambda}_h$ which is updated at each policy switch (Line 10). For every $k \in [K]$, we denote by b_k the episode from which the policy π_k is computed. This is consistent with the one defined in Algorithm 1 in Section 4. At the start of each episode k, the algorithm computes $\{\mathbf{\Lambda}_h^k\}_{h \in [H]}$ (Line 5) and then compares them with $\{\mathbf{\Lambda}_h\}_{h \in [H]}$ using the determinant-based criterion (Line 7). The agent switches the policy if there exists some $h \in [H]$ such that $\det(\mathbf{\Lambda}_h^k)$ has increased by some pre-determined parameter $\eta > 1$, followed by policy evaluation (Lines 11-13). Otherwise, the algorithm retains the previous policy (Line 16). Here the hyperparameter η controls the frequency of policy switch, and the total number of policy switches can be bounded by a function of η.

Algorithm 2 is also a variant of LSVI-UCB proposed in Jin et al. (2020). Compared with LSVI-UCB-Batch in Algorithm 1 for the batch learning model, LSVI-UCB-RareSwitch adaptively decides when to switch the policy and can be tuned by the hyperparameter η and therefore fits into the rare policy switch model.

We present the regret bound of Algorithm 2 in the following theorem.

Theorem 5.1. There exists some constant $c > 0$ such that for any $\delta \in (0, 1)$, if we set $\lambda = 1$, $\beta = cdH\sqrt{\log(2dT/\delta)}$ and $\eta = (1 + K/d)^{dH/B}$, then the number of policy switches N_{switch} in Algorithm 2 will not exceed B. Moreover, the total regret of Algorithm 2 is bounded by

$$
\text{Regret}(T) \le 2H\sqrt{T \log\left(\frac{2dT}{\delta}\right)} + 2c\sqrt{2d^3 H^3 T} \cdot \sqrt{\left(\frac{T}{dH} + 1\right)^{\frac{dH}{B}} \log\left(\frac{T}{dH} + 1\right) \log\left(\frac{2dT}{\delta}\right)}
\tag{5.1}
$$

with probability at least $1 - \delta$.

A few remarks are in order.

Remark 5.2. Algorithm 2 needs to update the value of each $\det(\mathbf{\Lambda}_h^k)$, and thanks to the special structure of $\mathbf{\Lambda}_h^k$, this can be done efficiently by applying the matrix determinant lemma along with the Sherman Morrison formula for efficiently updating each $(\mathbf{\Lambda}_h^k)^{-1}$. For simplicity and clarity of the presentation, we do not include these details in the pseudo-code.

Remark 5.3. By ignoring the non-dominating term, Theorem 5.1 suggests that the total regret of Algorithm 2 is bounded by $\widetilde{O}(\sqrt{d^3 H^3 T[1 + T/(dH)]^{dH/B}})$. Also, if we are allowed to choose B, we can choose $B = \Omega(dH \log T)$ to achieve $\widetilde{O}(\sqrt{d^3 H^3 T})$ regret, which is the same as that of LSVI-UCB in Jin et al. (2020). This also significantly improves upon Algorithm 1 when T is sufficiently large since previously we need $B = \Omega(\sqrt{T/dH})$.

Remark 5.4. Our result exhibits a trade-off between the total regret bound and the number of policy switches. We can see that as the adaptivity budget B increases, the regret bound decreases. In particular, $B = \Omega(dH \log T)$ corresponds to choosing η to be a constant, which reduces to the case studied in a concurrent work Gao et al. (2021).

Remark 5.5. Gao et al. (2021) established a lower bound, which claims that any rare policy switch RL algorithm suffers a linear regret when $B = \widetilde{o}(dH)$. However, unlike our lower bound for the batch learning model (Theorem 4.2), their result does not provide a fine-grained regret lower bound for arbitrary adaptivity constraint B. It remains an open problem to establish such kind of lower bound.

6 Numerical Experiment

In this section, we provide numerical experiments to support our theory. We run our algorithms, LSVI-UCB-Batch and LSVI-UCB-RareSwitch, on a synthetic linear MDP given in Example 6.1, and compare them with the fully adaptive baseline, LSVI-UCB (Jin et al., 2020).

Example 6.1 (Hard-to-learn linear MDP, Zhou et al. 2021b). Let $d > 0$ be some integer and $\delta \in (0, 1)$ be a constant. The state space $\mathcal{S} = \{0, 1\}$ consists of two states, and the action space $\mathcal{A} = \{\pm 1\}^{d-3}$ contains 2^{d-3} actions where each action is represented by a $(d-3)$-dimensional vector $\mathbf{a}$. For each state-action pair $(s, \mathbf{a}) \in \mathcal{S} \times \mathcal{A}$, the feature vector is given by

$$
\boldsymbol{\phi}(s, a) = \begin{cases} (-\mathbf{a}^\top, 1 - \delta, \delta, 0)^\top & s = 0, \\ (0, \dots, 0, \delta, 1 - \delta, 1) & s = 1. \end{cases}
\tag{6.1}
$$

For each $h \in [H]$, let $\boldsymbol{\gamma}_h \in \{\pm\delta/(d-2)\}^{d-2}$ and define the corresponding vector-valued measure as

$$
\boldsymbol{\mu}_h(s) = \begin{cases} (\boldsymbol{\gamma}_h^\top, 1, 0, 0)^\top & s = 0 \\ (-\boldsymbol{\gamma}_h^\top, 0, 1, 0)^\top & s = 1 \end{cases}.
\tag{6.2}
$$

Finally, we set $\boldsymbol{\theta}_h \equiv (0, \dots, 0, 1) \in \mathbb{R}^d$ for all $h \in [H]$.

(a) LSVI-UCB-Batch

(b) LSVI-UCB-RareSwitch

Figure 1: Plot of average regret, $\text{Regret}(T)/K$, v.s. the number of episodes. The results are averaged over 50 rounds of each algorithm, and the error bars are choosen to be $[20\%, 80\%]$ empirical confidence intervals.

It is straightforward to verify that the feature vectors in (6.1) and the vector-valued measures in (6.2) constitute a valid linear MDP such that, for all $\mathbf{a} \in \mathcal{A}$ and $h \in [H]$,

$$r_h(s, \mathbf{a}) = \mathbb{1}\{s = 1\}, \qquad \mathbb{P}_h(s'|s, \mathbf{a}) = \begin{cases} 1 - \delta - \langle \mathbf{a}, \gamma_h \rangle & (s, s') = (0, 0), \\ \delta + \langle \mathbf{a}, \gamma_h \rangle & (s, s') = (1, 0), \\ \delta & (s, s') = (1, 0), \\ 1 - \delta & (s, s') = (1, 1). \end{cases}$$

In our experiment[5], we set $H = 10$, $K = 2500$, $\delta = 0.35$ and $d = 13$, thus $\mathcal{A}$ contains 1024 actions. Now we apply our algorithms, LSVI-UCB-Batch and LSVI-UCB-RareSwitch, to this linear MDP instance, and compare their performance with the fully adaptive baseline LSVI-UCB (Jin et al., 2020) under different parameter settings. In detail, for LSVI-UCB-Batch, we run the algorithm for $B = 15, 50$ respectively; for LSVI-UCB-RareSwitch, we set $\eta = 4$ and 8. We plot the average regret $(\text{Regret}(T)/K)$ against the number of episodes in Figure 1.

From Figure 1, we can see that for LSVI-UCB-Batch, when $B \approx \sqrt{K}$, it achieves the similar regret as the fully adaptive LSVI-UCB. With smaller B, the regret increases. For LSVI-UCB-RareSwitch, a constant value of η yields similar order of regret compared with LSVI-UCB as suggested by Theorem 5.1. The results indicate that our algorithms can indeed achieve comparable performance as LSVI-UCB, even under limited adaptivity. This corroborates our theory.

7 Conclusions

In this work, we study online RL with linear function approximation under the adaptivity constraints. We consider both the batch learning model and the rare policy switch models and propose two new algorithms LSVI-UCB-Batch and LSVI-UCB-RareSwitch for each setting. We show that LSVI-UCB-Batch enjoys an $\widetilde{O}(\sqrt{d^3 H^3 T} + dHT/B)$ regret and LSVI-UCB-RareSwitch enjoys an $\widetilde{O}(\sqrt{d^3 H^3 T[1 + T/(dH)]^{dH/B}})$ regret. Compared with the fully adaptive LSVI-UCB algorithm (Jin et al., 2020), our algorithms can achieve the same regret with a much fewer number of batches/policy switches. We also prove the regret lower bound for the batch learning learning model, which suggests that the dependency on B in LSVI-UCB-Batch is tight.

For the future work, we would like to prove the regret lower bound for the rare policy switching model that explicitly depends on the given adaptivity budget B.

---

[5]All experiments are performed on a PC with Intel i7-9700K CPU.

References

ABBASI-YADKORI, Y., PÁL, D. and SZEPESVÁRI, C. (2011). Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, vol. 24.

ALTSCHULER, J. and TALWAR, K. (2018). Online learning over a finite action set with limited switching. In *Conference On Learning Theory*. PMLR.

ARORA, R., DEKEL, O. and TEWARI, A. (2012). Online bandit learning against an adaptive adversary: from regret to policy regret. *arXiv preprint arXiv:1206.6400* .

AYOUB, A., JIA, Z., SZEPESVARI, C., WANG, M. and YANG, L. (2020). Model-based reinforcement learning with value-targeted regression. In *International Conference on Machine Learning*. PMLR.

BAI, Y., XIE, T., JIANG, N. and WANG, Y.-X. (2019). Provably efficient q-learning with low switching cost. In *Advances in Neural Information Processing Systems*, vol. 32.

CAI, Q., YANG, Z., JIN, C. and WANG, Z. (2020). Provably efficient exploration in policy optimization. In *International Conference on Machine Learning*. PMLR.

CESA-BIANCHI, N., DEKEL, O. and SHAMIR, O. (2013). Online learning with switching costs and other adaptive adversaries. In *Advances in Neural Information Processing Systems*, vol. 26.

CHEN, L., YU, Q., LAWRENCE, H. and KARBASI, A. (2020). Minimax regret of switching-constrained online convex optimization: No phase transition. In *Advances in Neural Information Processing Systems*, vol. 33.

DEKEL, O., DING, J., KOREN, T. and PERES, Y. (2014). Bandits with switching costs: T 2/3 regret. In *Proceedings of the forty-sixth annual ACM symposium on Theory of computing*.

DEVROYE, L., LUGOSI, G. and NEU, G. (2015). Random-walk perturbations for online combinatorial optimization. *IEEE Transactions on Information Theory* **61** 4099–4106.

DU, S. S., KAKADE, S. M., LEE, J. D., LOVETT, S., MAHAJAN, G., SUN, W. and WANG, R. (2021). Bilinear classes: A structural framework for provable generalization in rl. In *International Conference on Machine Learning*. PMLR.

DU, S. S., KAKADE, S. M., WANG, R. and YANG, L. F. (2020). Is a good representation sufficient for sample efficient reinforcement learning? In *International Conference on Learning Representations*.

ESFANDIARI, H., KARBASI, A., MEHRABIAN, A. and MIRROKNI, V. (2021). Regret bounds for batched bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

FOSTER, D. J., RAKHLIN, A., SIMCHI-LEVI, D. and XU, Y. (2021). Instance-dependent complexity of contextual bandits and reinforcement learning: A disagreement-based perspective. In *Conference on Learning Theory*.

GAO, M., XIE, T., DU, S. S. and YANG, L. F. (2021). A provably efficient algorithm for linear markov decision process with low switching cost. *arXiv preprint arXiv:2101.00494* .

GAO, Z., HAN, Y., REN, Z. and ZHOU, Z. (2019). Batched multi-armed bandits problem. In *Advances in Neural Information Processing Systems*, vol. 32.

GEULEN, S., VÖCKING, B. and WINKLER, M. (2010). Regret minimization for online buffering problems using the weighted majority algorithm. In *COLT*. Citeseer.

HAN, Y., ZHOU, Z., ZHOU, Z., BLANCHET, J., GLYNN, P. W. and YE, Y. (2020). Sequential batch learning in finite-action linear contextual bandits. *arXiv preprint arXiv:2004.06321* .

HE, J., ZHOU, D. and GU, Q. (2021). Logarithmic regret for reinforcement learning with linear function approximation. In *International Conference on Machine Learning*. PMLR.

JAGHARGH, M. R. K., KRAUSE, A., LATTANZI, S. and VASSILVTISKII, S. (2019). Consistent online optimization: Convex and submodular. In *The 22nd International Conference on Artificial Intelligence and Statistics*.

374 JAKSCH, T., ORTNER, R. and AUER, P. (2010). Near-optimal regret bounds for reinforcement
375   learning. *Journal of Machine Learning Research* **11** 1563–1600.

376 JIA, Z., YANG, L., SZEPESVARI, C. and WANG, M. (2020). Model-based reinforcement learning
377   with value-targeted regression. In *Learning for Dynamics and Control*. PMLR.

378 JIN, C., YANG, Z., WANG, Z. and JORDAN, M. I. (2020). Provably efficient reinforcement learning
379   with linear function approximation. In *Conference on Learning Theory*. PMLR.

380 KALAI, A. and VEMPALA, S. (2005). Efficient algorithms for online decision problems. *Journal of*
381   *Computer and System Sciences* **71** 291–307.

382 LATTIMORE, T., SZEPESVARI, C. and WEISZ, G. (2020). Learning with good feature representations
383   in bandits and in rl with a generative model. In *International Conference on Machine Learning*.
384   PMLR.

385 NEU, G. and PIKE-BURKE, C. (2020). A unifying view of optimism in episodic reinforcement
386   learning. In *Advances in Neural Information Processing Systems*, vol. 33.

387 PERCHET, V., RIGOLLET, P., CHASSANG, S., SNOWBERG, E. ET AL. (2016). Batched bandit
388   problems. *The Annals of Statistics* **44** 660–681.

389 RUAN, Y., YANG, J. and ZHOU, Y. (2020). Linear bandits with limited adaptivity and learning
390   distributional optimal design. *arXiv preprint arXiv:2007.01980* .

391 WANG, R., SALAKHUTDINOV, R. R. and YANG, L. (2020). Reinforcement learning with general
392   value function approximation: Provably efficient approach via bounded eluder dimension. In
393   *Advances in Neural Information Processing Systems*, vol. 33.

394 WANG, Y., WANG, R., DU, S. S. and KRISHNAMURTHY, A. (2021). Optimism in reinforcement
395   learning with generalized linear function approximation. In *International Conference on Learning*
396   *Representations*.

397 YANG, L. and WANG, M. (2019). Sample-optimal parametric q-learning using linearly additive
398   features. In *International Conference on Machine Learning*.

399 YANG, Z., JIN, C., WANG, Z., WANG, M. and JORDAN, M. I. (2020). On function approximation
400   in reinforcement learning: Optimism in the face of large state spaces. In *Advances in Neural*
401   *Information Processing Systems*, vol. 33.

402 ZANETTE, A., LAZARIC, A., KOCHENDERFER, M. and BRUNSKILL, E. (2020). Learning near
403   optimal policies with low inherent bellman error. In *International Conference on Machine Learning*.
404   PMLR.

405 ZHANG, Z., JI, X. and DU, S. S. (2021). Is reinforcement learning more difficult than bandits? a
406   near-optimal algorithm escaping the curse of horizon. In *Conference on Learning Theory*. PMLR.

407 ZHOU, D., GU, Q. and SZEPESVARI, C. (2021a). Nearly minimax optimal reinforcement learning
408   for linear mixture markov decision processes. In *Conference on Learning Theory*. PMLR.

409 ZHOU, D., HE, J. and GU, Q. (2021b). Provably efficient reinforcement learning for discounted
410   mdps with feature mapping. In *International Conference on Machine Learning*. PMLR.