Residual Pathway Priors for Soft Equivariance Constraints

Abstract

Models such as convolutional neural networks restrict the hypothesis space to a set of functions satisfying equivariance constraints, and improve generalization in problems by capturing relevant symmetries. However, symmetries are often only partially respected, preventing models with restriction biases from fitting the data. We introduce Residual Pathway Priors (RPPs) as a method for converting hard architectural constraints into soft priors, guiding models towards structured solutions while retaining the ability to capture additional complexity. RPPs are resilient to approximate or misspecified symmetries, and are as effective as fully constrained models even when symmetries are exact. We show that RPPs provide compelling performance on both model-free and model-based reinforcement learning problems, where contact forces and directional rewards violate the assumptions of equivariant networks. Finally, we demonstrate that RPPs have broad applicability, including dynamical systems, regression, and classification.

1 Introduction

Central to the expanding application of deep learning to structured data like images, text, audio, sets, graphs, point clouds, and dynamical systems, has been a search for finding the appropriate set of inductive biases to match the model to the data. These inductive biases, such as recurrence [38], local connectivity [25], equivariance [9], or differential equations [7], reduce the set of explored hypotheses and improve generalization. Equivariance in particular has had a large impact as it allows ruling out a large class of meaningless shortcut features in many distinct domains, such as the ordering of the nodes in graphs and sets or the coordinate system chosen for an image.

A disadvantage of hard coding these restrictions is that this prior knowledge may not match reality. A scene may have long range non-local interactions, rotation equivariance may be violated by a preferred camera angle, or a dynamical system may occasionally have discontinuous transitions. In particular, symmetries are delicate. A small perturbation like adding wind breaks the rotational symmetry of a pendulum (such as in Figure 1b), and bumpy or tilted terrain could break the translation symmetry for locomotion. In these cases we would like to incorporate our prior knowledge in a way that admits our own ignorance, and allows for the possibility that the world is more complex than we imagined. We aim to develop an approach that is more general, and can be applied when symmetries are exact, approximate, or non-existent.

The Bayesian framework provides a mechanism for expressing such knowledge through priors. In much of the past work on Bayesian neural networks, the relationship between the prior distribution and the functions preferred by the prior is not transparent. While it is easy to specify different variances for different channels, or to use heavy tailed distributions, it is hard know how high level properties meaningfully translate into these low level attributes. Ultimately priors should represent our

(a) Priors over Equivariant Solutions   (b) Double Pendulum with Wind

Figure 1: **Left:** RPPs encode an Occam's razor approach to modeling. Highly flexible models like MLPs lack the inductive biases to assign high evidence to key datasets, while models with strict equivariance constraints are not flexible enough to support problems with only approximate symmetry. **Right:** An example showing that symmetries are *fragile*. The rotational symmetry of a double spring pendulum is broken by any small perturbation, such as a gentle breeze to the right.

prior *beliefs*, and those beliefs we have are about high level concepts like the locality, independence, and symmetries of the data.

To address the need for more interpretable priors we introduce *Residual Pathway Priors* (RPPs), a method for converting hard architectural constraints into soft priors. Practically, RPPs allow us to tackle problems in which perfect symmetry has been violated, but approximate symmetry is still present, as is the case for most real world physical systems.

RPPs have a prior bias towards equivariant solutions, but are not constrained to equivariance. The choice of RPPs can be viewed from an Occam's razor perspective, shown in Figure 1a, in which we seek to use models that have both the correct inductive biases and level of flexibility [36]. As we find with problems in which symmetries exist, highly flexible models with weak inductive biases like MLPs fail to concentrate prior mass around solutions that exhibit any symmetry. On the other hand when symmetries are only approximate, the strong biases of constrained models like Equivariant Multi-Layer Perceptrons (EMLP) [12] fail to provide support for the observations. As a middle ground between these two extremes, RPPs combine the inductive biases of constrained models with the flexibility of MLPs to define a model class which excels when data show approximate symmetries.

In the following sections we introduce our method and show results across a variety of domains. We list our contributions and the accompanying sections below:

1. We develop a method for constructing soft equivariance priors from hard architectural constraints (Section 4)
2. We demonstrate that RPPs are robust to varying degrees of symmetry (Section 5). RPPs perform well under exact, approximate, or misspecified symmetries.
3. Using RPP on the approximate symmetries in the complex state spaces of the Mujoco locomotion tasks, we improve the performance of model free RL agents (Section 6).

2 Related Work

The challenge of equivariant models not being able to fully fit the data has been identified in a number of different contexts, and with different application specific adjustments to mitigate the problem. Liu et al. [28] observe that convolutional networks can be extremely poor at tasks that require identifying or outputting spatial locations in an image as a result of the translation symmetry. The authors solve the problem by concatenating a coordinate grid to the input of the convolution layer. Constructing translation and rotation equivariant GCNNs, Weiler and Cesa [48] find that in order to get the best performance on CIFAR-10 and STL-10 datasets which have a preferred camera orientation, they must break the symmetry which they do by using equivariance to progressively smaller subgroups in the later layers. Bogatskiy et al. [6] go to great lengths to construct Lorentz group equivariant networks for tagging collisions in particle colliders only to break it by introducing dummy inputs that identify the collision axis. van der Wilk et al. [45] use the marginal likelihood to learn approximate

invariances in Gaussian processes from data. In a similar approach, Benton et al. [5] explore a
related concept of learning the *extent* of the symmetry using the reparametrization trick and test time
augmentation. While sharing some commonalities with RPP, this method is not aimed at achieving
approximate equivariance and cannot bake equivariance into the model architecture.

Outside of equivariance, summing solutions and learning only the difference from one solution and
the ground truth has been explored in several works. The original ResNet [18, 19] drew on this
motivation, and multi-resolution numerical solvers. Since then, Johannink et al. [22], Silver et al. [40]
proposed Residual Reinforcement Learning, whereby the RL problem is split into a user designed
controller using engineering principles and a flexible neural network policy learned with RL.

There have been several works tackling symmetries and equivariance in RL, such as permutation
equivariance for multi agent RL [41, 21, 27], as well exploring reflection symmetry for continuous
control tasks [1], and discrete symmetries in the more general framework of MDP homomorphisms
[44]. However, in each of these applications the symmetries need to be exact, and the complexities
of real data often require violating those symmetries. Although not constructed with this purpose,
some methods which use regularizers to enforce equivariance [43] could be used for approximate
symmetries. Interestingly, the value of approximate symmetries of MDPs has been explored in
some theoretical work [37, 42], but without architectures that can make use of it. Additionally data
augmentation, while not able to bake in architectural equivariance, has had successful application for
encouraging equivariance on image tasks [24] and recently even on tabular state vectors [26, 31].

3 Background

In order develop our method, we first review the concept of group symmetries, how representations
formalize the way these symmetries act on different objects.

Group Symmetries   In the machine learning context, a symmetry group G can be understood as a
set of invertible transformations under which an object is the same, such as reflections or rotations.
These symmetries can act on many different kinds of objects. A rotation could act on a simple
vector, a 2d array like an image, a complex collection objects like the state space of a robot, or more
abstractly on an entire classification problem or Markov Decision Process (MDP).

Representations   The way that symmetries act on objects is described by a *representation*. Given
an object in an n-dimensional vector space V, a group representation is a mapping $\rho : G \to \mathbb{R}^{n \times n}$,
yielding a matrix which acts on V. Vectors $v \in V$ are transformed $v \mapsto \rho(g)v$. In deep learning,
each of the inputs and outputs to our models can be embedded in some vector space: an $m \times m$ sized
rgb image exists in $\mathbb{R}^{3m^2}$, and a node valued function on a graph of m elements exists within $\mathbb{R}^m$.
The representation ρ specifies how each of these objects transform under the symmetry group G.

These representations can be composed of multiple simpler subrepresentations, describing how each
object within collection transform. For example given the representation ρ_1 of rotations acting
on a vector in $\mathbb{R}^3$ and a representation ρ_2 of how rotations act on a 3×3 matrix, the two objects
concatenated together have a representation given by $\rho_1(g) \oplus \rho_2(g) = \begin{bmatrix} \rho_1(g) & 0 \\ 0 & \rho_2(g) \end{bmatrix}$ where the
two matrices are concatenated along the diagonal. Practically this means we can represent intricate
and multifaceted structures by breaking them down into their component parts and defining how each
part transforms. For example, we may know that the velocity vector, an orientation quaternion, a joint
angle, and a control torque all transform in different ways under a left-right reflection, and one can
accommodate this information into the representation.

Equivariance   Given some data X with representation ρ_{in} and Y with representation ρ_{out}, we may
wish to learn some mapping $f : X \to Y$. A model f is equivariant [9], if applying the symmetry
transformation to the input is equivalent to applying it to the output

$$f(\rho_{\text{in}}(g)x) = \rho_{\text{out}}(g)f(x).$$

In other words, it is not the symmetry of X or Y that is relevant, but the symmetry of the function
f mapping from X to Y. If the true relationship in the data has a symmetry, then constraining the
hypothesis space to functions f that also have the symmetry makes learning easier and improves

119 generalization [10]. Equivariant models have been developed for a wide variety of symmetries and
120 data types like images [9, 49, 51, 48], sets [50, 30], graphs [29], point clouds [3, 13, 39], dynamical
121 systems [11], jets [6], and other objects [46, 12].

4 Residual Pathway Priors

123 Our method for constructing equivariance priors draws inspiration from the residual connections in
124 ResNets [18, 19], whereby training stability and generalization improves by providing multiple paths
125 for gradients to flow through the network that have different properties. One way of interpreting a
126 residual block and shortcut connection $f(x) = x + h(x)$ in combination with l2 regularization, either
127 explicitly from weight decay or implicitly from the training dynamics [34], is as a prior that places
128 higher prior likelihood on the much simpler identity mapping than on the more flexible function $h(x)$.
129 In this way, $h(x)$ need only explain the the difference between what is explained in the previous layer
130 (passed through by I) and the target.

131 We can leverage a similar approach to convert the hard constraints of a restriction prior specified
132 through a given network architecture into a soft prior that merely places higher prior likelihood on
133 such models. Supposing we have an equivariant layer $A(x)$, and a more flexible non-equivariant
134 layer $B(x)$ which contains A as a special case, we can allow the model to explain part of the data
135 with A and part with B by forming the sum $A(x) + B(x)$. A given a prior likelihood on the size
136 of A and B such as $p(A) \propto \exp\left(-\|A\|^2/2\sigma_a^2\right)$ and $p(B) \propto \exp\left(-\|B\|^2/2\sigma_b^2\right)$ with $\sigma_a > \sigma_b$, a
137 MAP optimized model will favor explanations of the data using the more structured layer A and only
138 resort to using layer B to explain the *difference* between the target and what is already explained by
139 the more structured model A. Adding these non-equivariant residual pathways to each layer of an
140 equivariant model, we have a model that has the same expressivity of a network formed entirely of B
141 layers, but with the inductive bias towards a model formed entirely with the equivariant A layers. We
142 term this a *residual pathway prior* (RPP).

143 To make the approach concrete, we first consider constructing equivariance priors using the constraint
144 solving approach known as Equivariant Multi-Layer Perceptrons (EMLP) from Finzi et al. [12].

Equivariant MLPs EMLPs provide a method for automatically constructing exactly equivariant
146 layers for any given group and representation by solving a set of constraints. The way in which
147 the vectors are equivariant is given by a formal specification of the types of the input and output
148 through defining their representations. Given some input vector space V_{in} with representation ρ_{in} and
149 some output space V_{out} with representation ρ_{out} the space of all equivariant linear layers mapping
150 $V_{\text{in}} \to V_{\text{out}}$ satisfies

$$\forall g \in G: \quad \rho_{\text{out}}(g)W = W\rho_{\text{in}}(g).$$

151 These solutions to the constraint form a subspace of matrices $\mathbb{R}^{n_{\text{out}} \times n_{\text{in}}}$ which can be solved for
152 and described by a r dimensional orthonormal basis $Q \in \mathbb{R}^{n_{\text{out}} n_{\text{in}} \times r}$. Linear layers can then be
153 parametrized in this equivariant basis. The elements of W can be parametrized $\text{vec}(W) = Q\beta$ for
154 $\beta \in \mathbb{R}^r$ for the linear layer $v \mapsto Wv$, and symmetric biases can be parametrized similarly.

Equivariance Priors with EMLP In order to convert the hard equivariance constraints in EMLP
156 into a soft prior over equivariance that can accomodate approximate symmetries, we can apply the
157 RPP procedure from above to each these linear layers in the network. Instead of parametrizing
158 the weights W directly in the equivariant basis $\text{vec}(W) = Q\beta$, we can instead define W as the
159 sum $W = A + B$ of an equivariant weight matrix $\text{vec}(A) = Q\beta$ with a Gaussian prior over β
160 and an unconstrained weight matrix $B \sim \mathcal{N}(0, \sigma_b^2 I)$ with a Gaussian prior. A Gaussian prior over
161 $\beta \sim \mathcal{N}(0, \sigma_a^2 I)$ is equivalent to the Gaussian prior $A \sim \mathcal{N}(0, \sigma_a^2 QQ^\top)$. Since Q is an orthogonal
162 matrix, we can breakdown the covariance of B into the covariance in the equivariant subspace Q as
163 well as the covariance in the orthogonal complement P, $\sigma_b^2 I = \sigma_b^2 QQ^\top + \sigma_b^2 PP^\top$. Therefore the
164 sum of the weight matrices is distributed as $A + B = W \sim \mathcal{N}(0, (\sigma_a^2 + \sigma_b^2)QQ^\top + \sigma_b^2 PP^\top)$.

165 *Regardless* of the values of the prior variances σ_a^2 and σ_b^2, solutions in the equivariant subspace $QQ^\top$
166 are automatically favored by the model and assigned higher prior probability mass than those in
167 the subspace $PP^\top$ that violate the constraint. Even if $\sigma_b > \sigma_a$, the model still favors equivariance
168 because the equivariance solutions are contained in the more flexible layer A. We show in Appendix
169 E that RPPs are insensitive to the choice of σ_a and σ_b provided that σ_a is large enough to be able to fit

the data. By replacing each of the equivariant linear layers in an EMLP with a sum of an equivariant layer and an unconstrained layer and adding in the negative prior likelihood to the loss function, we arrive at RPP-EMLP that can accommodate approximate or incorrectly specified symmetries. [1]

RPPs With Other Equivariant Models   While in EMLP these equivaraint bases are solved for explicitly, the argument holds for the linear layers in other equivaraint networks in precisely the same way. A good example of this is the translationally equivariant convolutional neural network (CNN) which can be viewed as a restricted subset of a fully connected network. Though the layers are parametrized as convolutions, the convolution operation can be expressed as a Toeplitz matrix residing within the space of dense matrices. Adding the convolution to a fully connected layer and choosing a prior variance σ_a^2 and σ_b^2 over each, we have the same RPP prior

$$W \sim N(0, \sigma_a^2 Q Q^\top + \sigma_b^2 I) \tag{1}$$

where Q is the basis of (bi-)Toeplitz matrices corresponding to 3×3 filters. This RPP convnet has the biases of convolution but can readily fit non translationally equivariant data. Likewise for other equivariant models like GCNNs [9], and we can even apply the RPP principle to the breaking of a given symmetry group to a subgroup.

5   How and Why RPPs Work

In this section we explore how and why RPPs work on a variety of domains, applying RPPs in settings where constraints are known to be helpful, cannot fully describe the problem, and are misspecified.

5.1   Dynamical Systems and Levels of Equivariance

In order to better understand how and why residual pathway priors interact with the symmetries of the problem we move to settings in which we can directly control both the type of symmetry and the level to which the symmetries are violated. We examine how RPPs coupled with EMLP networks perform (RPP-EMLP) on the inertia and double pendulum datasets featured in Finzi et al. [12] in 3 experimental settings: (i) the original inertia and double pendulum datasets which preserve exact symmetries with respect to the to O(3) and O(2) groups respectively; (ii) modified versions of these datasets in which add an additional terms (such as wind on the double pendulum) that lead to approximate symmetries; and (iii) versions with misspecified symmetry groups which break the symmetries entirely (described in Appendix D).

The results for these 3 settings are given in Figure 4. Across all settings RPP-EMLP match the performance of EMLP when symmetries are exact, perform as well as an MLP when the symmetry is misspecified and better than both when the symmetry is approximate. For these experiments we use a prior variance of $\sigma_a^2 = 10^5$ on the EMLP weights and $\sigma_b^2 = 1$ on the MLP weights.

Exact Symmetries   As part of the motivation, RPPs should properly attribute prior mass to both constrained and unconstrained solutions, we test cases in which symmetries are exact, and show that RPP-EMLP is capable of performing on par with EMLP which only admits solutions with perfect symmetry. The results in Figure 4a show that although the prior over models as described RPP-EMLP is broader than that of EMLP (as we can admit non-equivariant solutions) in the presence of perfectly equivariant data RPP-EMLP do not hinder performance, and we are able to generalize nearly as well as the perfectly prescribed EMLP model.

Approximate symmetries   To better showcase the ideas of Figure 1 we compare RPP-EMLPs to EMLPs and MLPs on the modified inertia and windy pendulum (Figure 1b) datasets. In these datasets we can think about the systems as primarily equivariant but containing non-equivariant contributions. As shown in 4b these problems are best suited for RPP-EMLP as MLPs have no bias towards the approximately symmetry present in the data, and EMLPs are overly constrained in this setting.

---

[1]For the EMLP that uses gated nonlinearities which do not always reduce to a standard Swish, we likewise add a more general Swish weighted by a parameter with prior variance σ_b^2.

(a) Exact Symmetries   (b) Approximate Symmetries   (c) Mis-specified Symmetries

Figure 2: A comparison of test performance over 10 independent trials using RPP-EMLP and equivalent EMLP and MLP models on the inertia (**top**) and double pendulum (**bottom**) datasets in which we have three varying levels of symmetries. The boxes represent the interquartile range, and the whiskers the remainder of the distribution. **Left:** perfect symmetries in which EMLP and the equivariant components of RPP-EMLP exactly capture the symmetries in the data. **Center:** approximate symmetries in which the perfectly symmetric systems have been modified to include some non-equivariant components. **Right:** mis-specified symmetries in which the symmetric components of EMLP and RPP-EMLP do not reflect the symmetries present in the data.

Misspecified symmetries In contrast to working with perfect symmetries and showing that RPP-EMLPs are competitive with EMLPs, we also show that when symmetries are *mis*specified the bias towards equivariant solutions does not hinder the performance of RPP-EMLPs. For the inertia dataset we substitute the group equivariance in EMLP from $O(3)$ to the overly large group $SL(3)$ consisting of all volume and orientation preserving linear transformations, not just the orthogonal ones. For the double pendulum dataset, we substitute $O(2)$ symmetry acting on $\mathbb{R}^3$ with the larger $SO(3)$ rotation group that contains it but is not a symmetry of the dataset.

By purposefully misspecifying the symmetry in these datasets we intentionally construct EMLP and RPP-EMLP models with incorrect inductive biases. In this setting EMLP is incapable of making accurate predictions as it has a hard constraint on an incorrect symmetry. Figure 4c shows that even in cases where the model is intentionally mis-specified that RPPs can overcome a poorly aligned inductive bias and recover solutions that perform as well as standard MLPs, even where EMLPs fail.

5.2 Posterior Levels of Equivariance

RPPs describe a method for setting a prior over equivariance, and in the presence of new data we expect the posterior distribution over equivariance to change accordingly. Using samples from a deep ensemble to query points of high density in the posterior we estimate how the distribution over equivariance error progresses through training. Recalling that with an equivariant function f we have $\rho_2(g)f(x) = f(\rho_1(g)x)$, we compute equivariance error as

$$\text{EquivErr}(f, x) = \text{RelErr}(\rho_2(g)f(x), f(\rho_1(g)x)) \;\; \text{where} \;\; \text{RelErr}(a, b) = \frac{\|a - b\|}{\|a\| + \|b\|}. \quad (2)$$

We train one deep ensemble on the inertia dataset which exhibits perfect symmetry, and another on the modified inertia dataset which has only partial symmetry, with each deep ensemble being comprised of 10 individual models using the same procedure as in Section 5.1. In Figure 3 we see that throughout training the models trained on the modified inertia concentrate around solutions with substantially higher equivariance error than models trained on the dataset with the exact symmetry. This figure demonstrates one of the core desiderata of RPPs: that we are able to converge to solutions with an appropriate level of equivariance for the data.

5.3 RPPs and Convolutional Structure

Using the RPP-Conv specified by the prior in Eqn 1 we apply the model to CIFAR-10 classification and UCI regression tasks where the inputs are reshaped to zero-padded two dimensional arrays

Figure 3: Kernel density estimators of log equivariance error across training epochs for 10 independently trained networks. Here the color denotes the dataset these models were trained on. Treating these samples as a proxy for posterior density, we see that on the non-equivariant Modified Inertia dataset, the posterior is shifted upward to match the level of equivariance in the data during training.

and treated as images. Notably, the model is still an MLP and merely has larger prior variance in the convolutional subspace. As a result it can perform well on image datasets where the inductive bias is aligned, as well as on the UCI data despite not being an image dataset as shown in Table 1. While retaining the flexibility of an MLP, the RPP performs better than the locally connected MLPs trained with β-lasso in Neyshabur [33] which get 14% error on CIFAR-10. The full details for the architectures and training procedure are given in Appendix D.

	CIFAR-10	Energy	Fertility	Pendulum	Wine
MLP	37.61 ± 0.56	0.39 ± 0.48	0.049 ± 0.0044	4.65 ± 0.50	0.66 ± 0.058
RPP	12.62 ± 0.34	0.73 ± 0.44	0.060 ± 0.0097	4.25 ± 0.50	0.69 ± 0.031
Conv	12.03 ± 0.46	1.34 ± 0.38	0.076 ± 0.0157	4.63 ± 0.36	0.79 ± 0.092

Table 1: Mean test classification error on CIFAR-10 and MSE on 4 UCI regression tasks, with one standard deviation errors taken over 10 trials. Similar to Figure 4, we find that whether the constrained convolutional structure is helpful (CIFAR) or not (UCI), RPP-Conv performs similarly to the model with the correct level of complexity.

6 Approximate Symmetries in Reinforcement Learning

Both model free and model based reinforcement learning present opportunities to take advantage of structure in the data for predictive power and data efficiency. On the one hand stands the use of model predictive control in the engineering community where finely specified dynamics models are constructed by engineers and only a small number of parameters are fit with system identification to determine mass, inertia, joint stiffness, etc. On the other side of things stands the hands off approach taken in the RL community, where general and unstructured neural networks are used for both transition models [8, 47, 20] as well as policies and value functions [15]. The state and action spaces for these systems are highly complex with many diverse inputs like quaternions, joint angles, forces, torques that each transform in different ways under a symmetry transformation like a left-right reflection or a rotation. As a result, most RL methods treat these spaces a black box ignoring all of this structure, and as a result they tend to require tremendous amounts of training data, making it difficult to apply to real systems without the use of simulators.

We can make use of this information about what kinds of objects populate the state and action spaces to encode approximate symmetries of the RL environments. As shown in van der Pol et al. [44], exploiting symmetries in MDPs by using equivariant networks can yield substantial improvements in data efficiency. But symmetries are brittle, and minor effects like rewards for moving in one direction, gravity, or even perturbations like wind, a minor tilt angle in CartPole, or other environment imperfections can break otherwise perfectly good symmetries. As shown in Table 2, broadening the scope to approximate symmetries allows for leveraging a lot more structure in the data which we can exploit with RPP. While Walker2d, Swimmer, Ant, and Humanoid have exact left/right reflection symmetries, Hopper, HalfCheetah, and Swimmer have approximate front/back reflection symmetries. Ant and Humanoid have an even more diverse set, with the D_4 dihedral symmetry by reflecting and

(a) Walker2d Left-Right (b) Swimmer Front-Back (c) HalfCheetah In-Out

Figure 4: Example illustrations of symmetries and representations from the Mujoco environments. **Left:** left-right symmetry in the *Walker2d* environment, **center:** front-back symmetry in the *Swimmer* environment, and **right:** In-out similarity in the *HalfCheetah* environment

cyclicly permuting the legs of the ant, as well as continuous rotations of the Ant and Humanoid within the environment which can be broken by external forces or rewards. Identifying this structure in the data, we are able to use the generality of EMLP to construct an equivariant model for this data, and then turn it into a soft prior using RPP.

Symmetries	Walker2d	Hopper	HalfCheetah	Swimmer	Ant	Humanoid
Exact	$\mathbb{Z}_2$	✗	✗	$\mathbb{Z}_2$	$\mathbb{Z}_2$	$\mathbb{Z}_2$
Approximate	$\mathbb{Z}_2$	$\mathbb{Z}_2$	$\mathbb{Z}_2$	$\mathbb{Z}_2 \times \mathbb{Z}_2$	$D_4 \times O(2)$	$\mathbb{Z}_2 \times O(2)$
This work	$\mathbb{Z}_2$	$\mathbb{Z}_2$	$\mathbb{Z}_2$	$\mathbb{Z}_2 \times \mathbb{Z}_2$	$\mathbb{Z}_4$	$SO(2)$

Table 2: Exact and approximate symmetries of Mujoco locomotion environments of which we use the subgroups in the bottom row, see Appendix C for the detailed action and state representations.

6.1 Approximate Symmetries in Model Free Reinforcement Learning

We evaluate RPPs on the standard suite of Mujoco continuous control tasks in the context of model-free reinforcement learning. With the appropriately specified action and state representations detailed in Appendix C, we construct RPP-EMLPs which we use as a drop-in replacement for both the policy and Q-function in the Soft Actor Critic (SAC) algorithm [15], using the same number of layers and channels. In contrast with van der Pol et al. [44] where equivariance is used just for policies, we find that using RPP-EMLP for the policy function alone is not very helpful with Actor Critic (see Figure 5). With the exception of the Humanoid-v2 environment where the RPP-EMLP destabilizes SAC, we find that incorporating the exact and approximate equivariance with RPP yields consistent improvements in the data efficiency of the RL agent as shown in Figure 5.

6.2 Better Transition Models for Model Based Reinforcement Learning

We also investigate whether the equivariance prior of RPP can improve the quality of the predictions for transition models in the context of model based RL. To evaluate this in a way decoupled from the complex interactions between policy, model, and value function in MBRL, we instead construct a static dataset of $50,000$ state transitions sampled uniformly from the replay buffer of a trained SAC agent. Since the trajectories in the replay buffer come from different times, they capture the varied dynamics MBRL transition models often encounter during training.

Figure 5: Average reward curve of RPP-SAC and SAC trained on Mujoco locomotion environments (max average reward attained at each step). Mean and one standard deviation taken over 4 trials shown in the shaded region. Incorporating approximate symmetries in the environments improves the efficiency of the model free RL agents.

Rollout	Swimmer-v2		Hopper-v2		Ant-v2	
	MLP	**RPP**	MLP	**RPP**	**MLP**	RPP
10 Steps	0.51 ± 0.02	$\mathbf{0.40 \pm 0.04}$	1.1 ± 0.1	$\mathbf{0.9 \pm 0.1}$	$\mathbf{4.2 \pm 0.1}$	5.2 ± 0.3
30 Steps	1.6 ± 0.2	$\mathbf{1.26 \pm 0.14}$	3.8 ± 0.3	$\mathbf{3.1 \pm 0.5}$	$\mathbf{11.3 \pm 0.2}$	13.9 ± 0.7
100 Steps	3.9 ± 1.0	$\mathbf{2.75 \pm 0.31}$	9.8 ± 0.5	$\mathbf{7.0 \pm 0.7}$	$\mathbf{16.0 \pm 0.3}$	20.0 ± 1.1
Equiv Err	46%	19%	98%	32%	36%	31%

Table 3: Transition model rollout relative error in percent % averaged over 10, 30, and 100 step rollouts (geometric mean over trajectory). Errorbars are 1 standard deviation taken over 3 random seeds. Equivariance error is computed from as the geometric mean averaged over the 100 step rollout.

State of the art model based approaches on Mujoco tend to use an ensemble of small MLPs that predict the state transitions [8, 47, 20, 2], without exploiting any structure of the state space. We evaluate test rollout predictions via the relative error of the state over different length horizons for the RPP model against an MLP, the method of choice. As shown in Table 3, RPP transition models outperform MLPs on the Swimmer and Hopper environments, especially for long rollouts showing promise for use in MBRL. On these environments, RPP learns a smaller but non-negligible equivariance error that still enables it to fit the data.

7 Conclusion

In this work we have presented a method for converting restriction priors such as equivariance constraints into flexible models that have a bias towards structure but are not constrained by it. Given uncertainty about the nature of the data, RPPs are a safe choice. These RPP models are able to perform as well as the equivariant models when exact symmetries are present, and as well as unstructured MLPs when the specified symmetry doesn't exist, and better than both for approximate symmetries. We have shown that encoding approximate symmetries can be a powerful technique for improving performance with the messy and complex state and action spaces in reinforcement learning, as well as in a more general regression setting.

References

[1] Farzad Abdolhosseini, Hung Yu Ling, Zhaoming Xie, Xue Bin Peng, and Michiel van de Panne. On learning symmetric locomotion. In *Motion, Interaction and Games*, pages 1–10. 2019.

[2] Brandon Amos, Samuel Stanton, Denis Yarats, and Andrew Gordon Wilson. On the model-based stochastic value gradient for continuous reinforcement learning. *arXiv preprint arXiv:2008.12775*, 2020.

[3] Brandon Anderson, Truong Son Hy, and Risi Kondor. Cormorant: Covariant molecular neural networks. In *Advances in Neural Information Processing Systems*, pages 14510–14519, 2019.

[4] Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphael Marinier, Léonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, et al. What matters in on-policy reinforcement learning? a large-scale empirical study. *arXiv preprint arXiv:2006.05990*, 2020.

[5] Gregory Benton, Marc Finzi, Pavel Izmailov, and Andrew Gordon Wilson. Learning invariances in neural networks. *arXiv preprint arXiv:2010.11882*, 2020.

[6] Alexander Bogatskiy, Brandon Anderson, Jan Offermann, Marwah Roussi, David Miller, and Risi Kondor. Lorentz group equivariant neural network for particle physics. In *International Conference on Machine Learning*, pages 992–1002. PMLR, 2020.

[7] Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *Advances in neural information processing systems*, pages 6571–6583, 2018.

[8] Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *arXiv preprint arXiv:1805.12114*, 2018.

[9] Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999. PMLR, 2016.

[10] Bryn Elesedy and Sheheryar Zaidi. Provably strict generalisation benefit for equivariant models. *arXiv preprint arXiv:2102.10333*, 2021.

[11] Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data. In *International Conference on Machine Learning*, pages 3165–3176. PMLR, 2020.

[12] Marc Finzi, Max Welling, and Andrew Gordon Wilson. A practical method for constructing equivariant multilayer perceptrons for arbitrary matrix groups. *arXiv preprint arXiv:2104.09459*, 2021.

[13] Fabian B Fuchs, Daniel E Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. *arXiv preprint arXiv:2006.10503*, 2020.

[14] Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In *Advances in Neural Information Processing Systems*, pages 15379–15389, 2019.

[15] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[16] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[17] Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[19] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pages 630–645. Springer, 2016.

[20] Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. *arXiv preprint arXiv:1906.08253*, 2019.

[21] Jiechuan Jiang, Chen Dun, Tiejun Huang, and Zongqing Lu. Graph convolutional reinforcement learning. *arXiv preprint arXiv:1810.09202*, 2018.

[22] Tobias Johannink, Shikhar Bahl, Ashvin Nair, Jianlan Luo, Avinash Kumar, Matthias Loskyll, Juan Aparicio Ojea, Eugen Solowjow, and Sergey Levine. Residual reinforcement learning for robot control. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 6023–6029. IEEE, 2019.

[23] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[24] Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

[25] Yann LeCun, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel. Backpropagation applied to handwritten zip code recognition. *Neural computation*, 1(4):541–551, 1989.

[26] Yijiong Lin, Jiancong Huang, Matthieu Zimmer, Yisheng Guan, Juan Rojas, and Paul Weng. Invariant transform experience replay: Data augmentation for deep reinforcement learning. *IEEE Robotics and Automation Letters*, 5(4):6615–6622, 2020.

[27] Iou-Jen Liu, Raymond A Yeh, and Alexander G Schwing. Pic: permutation invariant critic for multi-agent deep reinforcement learning. In *Conference on Robot Learning*, pages 590–602. PMLR, 2020.

[28] Rosanne Liu, Joel Lehman, Piero Molino, Felipe Petroski Such, Eric Frank, Alex Sergeev, and Jason Yosinski. An intriguing failing of convolutional neural networks and the coordconv solution. *arXiv preprint arXiv:1807.03247*, 2018.

[29] Haggai Maron, Heli Ben-Hamu, Nadav Shamir, and Yaron Lipman. Invariant and equivariant graph networks. *arXiv preprint arXiv:1812.09902*, 2018.

[30] Haggai Maron, Or Litany, Gal Chechik, and Ethan Fetaya. On learning sets of symmetric elements. *arXiv preprint arXiv:2002.08599*, 2020.

[31] Aditi Mavalankar. Goal-conditioned batch reinforcement learning for rotation invariant locomotion. *arXiv preprint arXiv:2004.08356*, 2020.

[32] Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

[33] Behnam Neyshabur. Towards learning convolutions from scratch. *arXiv preprint arXiv:2007.13657*, 2020.

[34] Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. *arXiv preprint arXiv:1412.6614*, 2014.

[35] Prajit Ramachandran, Barret Zoph, and Quoc V Le. Searching for activation functions. *arXiv preprint arXiv:1710.05941*, 2017.

[36] Carl Edward Rasmussen and Zoubin Ghahramani. Occam's razor. *Advances in neural information processing systems*, pages 294–300, 2001.

[37] Balaraman Ravindran and Andrew G Barto. Approximate homomorphisms: A framework for non-exact minimization in markov decision processes. 2004.

[38] David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning internal representations by error propagation. Technical report, California Univ San Diego La Jolla Inst for Cognitive Science, 1985.

[39] Victor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E (n) equivariant graph neural networks. *arXiv preprint arXiv:2102.09844*, 2021.

[40] Tom Silver, Kelsey Allen, Josh Tenenbaum, and Leslie Kaelbling. Residual policy learning. *arXiv preprint arXiv:1812.06298*, 2018.

[41] Sainbayar Sukhbaatar, Arthur Szlam, and Rob Fergus. Learning multiagent communication with backpropagation. *arXiv preprint arXiv:1605.07736*, 2016.

[42] Jonathan Taylor, Doina Precup, and Prakash Panagaden. Bounding performance loss in approximate mdp homomorphisms. *Advances in Neural Information Processing Systems*, 21: 1649–1656, 2008.

[43] Elise van der Pol, Thomas Kipf, Frans A Oliehoek, and Max Welling. Plannable approximations to mdp homomorphisms: Equivariance under actions. *arXiv preprint arXiv:2002.11963*, 2020.

[44] Elise van der Pol, Daniel Worrall, Herke van Hoof, Frans Oliehoek, and Max Welling. Mdp homomorphic networks: Group symmetries in reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[45] Mark van der Wilk, Matthias Bauer, ST John, and James Hensman. Learning invariances using the marginal likelihood. *arXiv preprint arXiv:1808.05563*, 2018.

[46] Renhao Wang, Marjan Albooyeh, and Siamak Ravanbakhsh. Equivariant maps for hierarchical structures. *arXiv preprint arXiv:2006.03627*, 2020.

[47] Tingwu Wang and Jimmy Ba. Exploring model-based planning with policy networks. *arXiv preprint arXiv:1906.08649*, 2019.

[48] Maurice Weiler and Gabriele Cesa. General $e(2)$-equivariant steerable cnns. *arXiv preprint arXiv:1911.08251*, 2019.

[49] Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5028–5037, 2017.

[50] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in neural information processing systems*, pages 3391–3401, 2017.

[51] Yanzhao Zhou, Qixiang Ye, Qiang Qiu, and Jianbin Jiao. Oriented response networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 519–528, 2017.