QUANTILE-LSTM: A ROBUST LSTM FOR ANOMALY DETECTION IN TIME SERIES DATA

ABSTRACT

Anomalies refer to the departure of systems and devices from their normal behaviour in standard operating conditions. An anomaly in an industrial device can indicate an upcoming failure, often in the temporal direction. In this paper, we make two contributions: 1) we estimate conditional quantiles and consider three different ways to define anomalies based on the estimated quantiles. 2) we use a new learnable activation function in the popular Long Short Term Memory networks (LSTM) architecture to model temporal long-range dependency. In particular, we propose Parameterized Elliot Function (PEF) as an activation function (AF) inside LSTM, which saturates lately compared to *sigmoid* and *tanh*. The proposed algorithms are compared with other well-known anomaly detection algorithms, such as Isolation Forest (iForest), Elliptic Envelope, Autoencoder, and modern Deep Learning models such as Deep Autoencoding Gaussian Mixture Model (DAGMM), Generative Adversarial Networks (GAN). The algorithms are evaluated in terms of various performance metrics, such as Precision and Recall. The algorithms are experimented on multiple industrial timeseries datasets such as Yahoo, AWS, GE, and machine sensors. We have found that the LSTM-based quantile algorithms are very effective and outperformed the existing algorithms in identifying anomalies.

1 INTRODUCTION

Anomalies indicate a departure of a system from its normal behaviour. In Industrial systems, they often lead to failures. By definition, anomalies are rare events. As a result, from a Machine Learning standpoint, collecting and classifying anomalies pose significant challenges. For example, when anomaly detection is posed as a classification problem, it leads to extreme class imbalance (data paucity problem). Morales-Forero & Bassetto (2019) have applied a semi-supervised neural network, a combination of an autoencoder and LSTM, to detect anomalies in the industrial dataset to mitigate the data paucity problem. Sperl et al. (2020) also tried to address the data imbalance issue of anomaly detection and applied a semi-supervised method to inspect large amounts of data for anomalies. However, these approaches do not address the problem completely since they still require some labeled data. Our proposed approach is to train models on a normal dataset and device some post-processing techniques to detect anomalies. It implies that the model tries to capture the normal behavior of the industrial device. Hence, no expensive dataset labeling is required. Similar approaches were tried in the past. Autoencoder-based family of models uses some form of thresholds to detect anomalies. For example, Sakurada & Yairi (2014); Jinwon & Ch (2015) mostly relied on reconstruction errors. The reconstruction error can be considered as an anomaly score. If the reconstruction error of a datapoint is higher than a threshold, then the datapoint is declared as an anomaly. However, the threshold value can be specific to the domain and the model, and deciding the threshold on the reconstruction error can be cumbersome.

MOTIVATION AND CONTRIBUTION

Unlike the above, our proposed quantile-based thresholds applied in the quantile-LSTM are generic and not specific to the domain or dataset. We have introduced multiple versions of the LSTM-based anomaly detector in this paper, namely (i) quantile-LSTM (ii) iqr-LSTM and (iii) Median-LSTM. All the LSTM versions are based on estimating the quantiles instead of the mean behaviour of an

industrial device. For example, the median is 50% quantile. Our contributions are three folds:

(1) Introduction of Quantiles in design of quantile-based LSTM techniques and their application in anomaly identification.

(2) Proposal of the Parameterized Elliot as a 'flexible-form, adaptive, learnable' activation function in LSTM, where the parameter is learnt from the dataset. We have shown empirically that the modified LSTM architecture with PEF performed better than the Elliot Function (EF) and showed that such behavior might be attributed to the slower saturation rate of PEF.

(3) Evidence of superior performance of the proposed LSTM methods over state-of-the-art (SoTA) deep learning (Autoencoder (Yin et al., 2020), DAGMM (Zong et al., 2018), DevNet (Pang et al., 2019)) and non-deep learning algorithms (iForest (Liu et al., 2008), Elliptic envelope (Rousseeuw & Driessen, 1999), Multi-Generations Tree (MGTree), Uni-variate Multi-Generations Tree (UVMGTree) (Sarkar et al., 2022) etc.) across multiple Industrial and Non-industrial data sets (Appendix, Table 9).

The rest of the paper is organized as follows. The proposal and discussion of various LSTM-based algorithms are presented in section 2. Section 3 describes the LSTM structure and introduces the PEF. This section also explains the intuition behind choosing a parameterized version of the AF and better variability due to it. Experimental results are presented in section 4. Section 5 discusses relevant literature in anomaly detection. We conclude the paper in section 6.

2 ANOMALY DETECTION WITH QUANTILE LSTMs

Quantiles are used as a robust alternative to classical conditional means in Econometrics and Statistics, as they can capture the uncertainty in a prediction and model tail behaviours (Koenker, 2005). The additional benefit lies in quantiles making very few distributional assumptions. It was also shown by Tambwekar et al. (2022) that quantiles aid in explainability as they can be used to obtain several univariate summary statistics that can be directly applied to existing explanation tools. This served as the motivation behind adopting the idea of quantiles from classification to anomaly detection, as quantiles capture tail behavior succinctly. It is well known that quantiles minimize check loss (Horowitz, 1992), which is a generalized version of Mean Absolute Error (MAE) arising from medians rather than means. It is also known that medians are often preferred to means in robust settings, particularly in skewed and heavy-tailed data. Thus, in time series data, where LSTM architecture has shown to come in handy, LSTM architecture is coupled with the idea of quantiles to capture anomalies (outliers). It is to be noted that this method is applied to univariate time series data only, and the method is agnostic to data distribution (see Table 6). As the empirical results exhibit, the distributional variance does not impact the prediction quality.

Before we discuss quantile-based anomaly detection, we describe the data structure and processing setup, with some notations. Let us consider $x_i, i = 1, 2, .., n$ be the n time-series training datapoints. We consider $T_k = \{x_i : i = k, \cdots, k + t\}$ be the set of t datapoints, and let T_k be split into w disjoint windows with each window of integer size $m = \frac{t}{w}$ and $T_k = \{T_k^1, \cdots, T_k^w\}$. Here, $T_k^j = \{x_{k+m(j-1)}, ..., x_{k+m(j)-1}\}$. In Figure 1, we show the sliding characteristics of the proposed algorithm on a hypothetical dataset, with $t = 9, m = 3$. Let $Q_\tau(D)$ be the sample quantile of the datapoints in the set D. The training data consists of, for every T_k, $X_{k,\tau} \equiv \{Q_\tau(T_k^j)\}, j = 1, \cdots, w$ as predictors with $y_{k,\tau} \equiv Q_\tau(T_{k+1})$, sample quantile at a future time-step, as the label or response. Let $\hat{y}_{k,\tau}$ be the predicted value by an LSTM model.

2.1 VARIOUS QUANTILE-LSTM ALGORITHMS

A general recipe we are proposing to detect anomalies is to: (i) estimate quantile $Q_\tau(x_{k+t+1})$ with $\tau \in (0, 1)$ and (ii) define a statistic that measures the outlier-ness of the data, given the observation x_{k+t+1}. Instead of using global thresholds, thresholds are adaptive i.e. they change at every time-point depending on quantiles.

2.1.1 QUANTILE-LSTM

As the name suggests, in quantile-LSTM, we forecast two quantiles q_{low} and q_{high} to detect the anomalies present in a dataset. We assume the next quantile values of the time period after sliding the time period by one position are dependent on the quantile values of the current time period.

Figure 1: The figure demonstrates the sliding movement of a time period including all the time windows.

(a) Anomaly detection process using quantile-LSTM

(b) Anomaly detection process using median-LSTM

Figure 2: Sigmoid function has been applied as an recurrent function, which is applied on the outcome of the forget gate ($f_t = \sigma(W_f * [h_{t-1}, x_t] + b_f)$) as well as input gate ($i_t = \sigma(W_i * [h_{t-1}, x_t] + b_i)$). PEF decides the information to store in cell $\hat{c}_t = PEF(W_c * [h_{t-1}, x_t] + b_c)$.

It is further expected that, nominal range of the data can be gleaned from q_{low} and q_{high}. Using these q_{low} and q_{high} values of the current time windows, we can forecast q_{low} and q_{high} values of the next time period after sliding by one position. Here, it is required to build two LSTM models, one for q_{low} (LSTM$_{qlow}$) and another for q_{high} (LSTM$_{qhigh}$). Let's take the hypothetical dataset as a training set from Figure 2a. It has three time windows from time period $x_1 \cdots x_9$. Table 1 defines the three time windows of the time period $x_1 \cdots x_9$ and the corresponding q_{low}, q_{high} values against the time window.

The size of the inputs to the LSTM depends on the number of time windows w and one output. Since three time windows have been considered for a time period in this example, both the LSTM models will have three inputs and one output. For example, the LSTM predicting the lower quantile, would have $X_{1,low}, X_{2,low}, X_{3,low}$ as its puts and $y_{1,low}$ as its output, for one time-period. A total of $n - t + 1$ instances will be available for training the LSTM models assuming no missing values.

TW	q_{low}	q_{high}
x_1, x_2, x_3	$X_{1,low} \equiv Q_{low}(T_1^1)$	$X_{1,high} \equiv Q_{high}(T_1^1)$
x_4, x_5, x_6	$X_{2,low} \equiv Q_{low}(T_1^2)$	$X_{2,high} \equiv Q_{high}(T_1^2)$
x_7, x_8, x_9	$X_{3,low} \equiv Q_{low}(T_1^3)$	$X_{3,high} \equiv Q_{high}(T_1^3)$

Table 1: The first time period and its corresponding time windows

After building the LSTM models, for each time period it predicts the corresponding quantile value and slides one position to the next time period on the test dataset. quantile-LSTM applies a following anomaly identification approach. If the observed value x_{k+t+1} falls outside of the predicted (q_{low}, q_{high}), then the observation will be declared as an anomaly. For example, the observed value x_{10} will be detected as an anomaly if $x_{10} < \hat{y}_{1,low}$ or $x_{10} > \hat{y}_{1,high}$. Figure 2a illustrates the anomaly identification technique of the quantile-LSTM on a hypothetical test dataset.

2.1.2 IQR-LSTM

iqr-LSTM is a special case of quantile-LSTM where q_{low} is 0.25 and q_{high} is the 0.75 quantile. In addition, another LSTM model predicts median $q_{0.5}$ as well. Effectively, at every time index k, three predictions are made $\hat{y}_{k,0.25}, \hat{y}_{k,0.5}, \hat{y}_{k,0.75}$. Based on this, we define the Inter Quartile Range (IQR) $\hat{y}_{k,0.75} - \hat{y}_{k,0.25}$. Using IQR, the following rule identifies an anomaly when $x_{t+k+1} > \hat{y}_{k,0.5} + \alpha(\hat{y}_{k,0.75} - \hat{y}_{k,0.25})$ or $x_{t+k+1} < \hat{y}_{k,0.5} - \alpha(\hat{y}_{k,0.75} - \hat{y}_{k,0.25})$

2.1.3 MEDIAN-LSTM

Median-LSTM, unlike quantile-LSTM, does not identify the range of the normal datapoints; rather, based on a single LSTM, distance between the observed value and predicted median ($x_{t+k+1} - \hat{y}_{k,0.5}$) is computed, as depicted in Figure 2b, and running statistics are computed on this derived data stream. The training set preparation is similar to quantile-LSTM.

To detect the anomalies, Median-LSTM uses an implicit adaptive threshold. It is not reasonable to have a single threshold value for the entire time series dataset when dataset exhibits seasonality and trends. We introduce some notations to make description concrete. Adopting the same conventions introduced before, define $d_k \equiv x_{t+k+1} - Q_{0.5}(T_{k+1}), k = 1, 2, \ldots, n-t$ and partition the difference series into s sets of size t each, i.e., $D \equiv D_p, p = 1, \ldots, s$, where $D_p = \{d_i : i = (s-1)t + 1, \ldots, st\}$. After computing the differences on the entire dataset, for every window D_p, mean (μ_p) and standard deviation (σ_p) for the individual time period D_p. As a result, μ_p and σ_p will differ from one time period to another time period. Median-LSTM detects the anomalies using upper threshold and lower threshold parameters of a particular time period D_p and they are computed as follows:

$$T_{p,lower} = \mu_p + w\sigma_p; T_{p,higher} = \mu_p - w\sigma_p$$

An anomaly can be flagged for $d_k \in T_p$ when either $d_k > T_{p,higher}$ or $d_k < T_{p,lower}$ Now, what should be the probable value for w? If we consider $w = 2$, it means that any datapoint beyond two standard deviations away from the mean on either side will be considered as an anomaly. It is based on the intuition that differences of the normal datapoints should be close to the mean value, whereas the anomalous differences will be far from the mean value. Hence 95.45% datapoints are within two standard deviations distance from the mean value. It is imperative to consider $w = 2$ since there is a higher probability of the anomalies falling into the 4.55% datapoints. We can consider $w = 3$ too where 99.7% datapoints are within three standard deviations. However, it may miss the border anomalies, which are relatively close to the normal datapoints and only can detect the prominent anomalies. Therefore we have used $w = 2$ across the experiments.

2.2 PROBABILITY BOUND

In this subsection, we analyze different datasets by computing the probability of occurrence of anomalies using the quantile approach. We have considered 0.1, 0.25, 0.75, 0.9, and 0.95 quantiles and computed the probability of anomalies beyond these values, as shown in Table 5 of Appendix A. The multivariate datasets are not considered since every feature may follow a different quantile threshold. Hence it is not possible to derive a single quantile threshold for all the features. It is evident from Table 5 of Appendix A that the probability of a datapoint being an anomaly is high if

the datapoint's quantile value is either higher than 0.9 or lower than 0.1. However, if we increase the threshold to 0.95, the probability becomes 0 across the datasets. This emphasizes that a higher quantile threshold does not detect anomalies. It is required to identify the appropriate threshold value, and it is apparent from the table that most of the anomalies are nearby 0.9 and 0.1 quantile values. Table 5 also demonstrates the different nature of the anomalies present in the datasets. For instance, the anomalies of Yahoo Dataset$_1$ to Yahoo Dataset$_6$ are present nearby the quantile value 0.9, whereas the anomalies in Yahoo Dataset$_7$ to Yahoo Dataset$_9$ are close to both quantile values 0.9 and 0.1. Therefore, it is possible to detect anomalies by two extreme quantile values. We can consider these extreme quantile values as higher and lower quantile thresholds and derive a lemma. We provide a proof in the Appendix B.

Lemma 1: For an univariate dataset $\mathcal{D}$, the probability of an anomaly $\mathcal{P}(\mathcal{A}) = \mathcal{P}(\mathcal{E} > \alpha_{high}) + \mathcal{P}(\mathcal{F} < \alpha_{low})$, where $\alpha_{high}, \alpha_{low}$ are the higher and lower level quantile thresholds respectively.

The lemma entails the fact that anomalies are trapped outside the high and low quantile threshold values. The bound is independent of data distribution as quantiles assume nominal distributional characteristics.

3 LSTM WITH PARAMETERIZED ELLIOT ACTIVATION (PEF)

We introduce the novel parameterized Elliot activation function, which is the parameterized version of the Elliot activation function. The suitability of parameterized Elliot function, PEF, is conceived as an adaptive variant of usual activation wherein we modify the LSTM architecture by replacing the activation function of the LSTM gates with PEF. We save 'parameter tuning' efforts by learning the parameter values from backpropagation. Additionally, the cost of saturation of standard activation functions impedes training and prediction, which is an important barrier to overcome. We expect PEF to have a lower rate of saturation in LSTM compared to other activation functions such as tanh, sigmoid, etc. To the best of our knowledge, insights on 'learning' the parameters of an AF are not available in literature except for the standard smoothness or saturation properties AFs are supposed to possess. It is, therefore, worthwhile to investigate the possibilities of learning an AF within a framework or architecture that uses the inherent patterns and variances from data.

A single LSTM block is composed of four major components: an input gate, a forget gate, an output gate, and a cell state. We have applied the parameterized Elliot Function (PEF) as activation and introduced a parameter α, which controls the shape of the Elliot function, represented by

$$f(x) = \frac{\alpha x}{1 + |x|} \tag{1}$$

with the first order derivative of PEF as: $f'(x) = \frac{\alpha}{(|x|+1)^2}$. The α in equation 1 is learnt during the back-propagation like other weight parameters of the LSTM model. There are multiple reasons to implement the PEF instead of other activation functions. Some of the reasons and salient features of the PEF are 1. The function is equal to 0, and the derivatives are also equal to α at the origin. 2. The function's derivative also saturates as the $|x|$ increases. However, the saturation rate is less than other activation functions, such as tangent. 3. One of the major benefits of the PEF is that it further decreases the rate of saturation in comparison to the non-parameterized Elliot function.

Parameterized Elliot Function (PEF): One of the major benefits of the Paramterized Elliot function is that it further decreases the rate of saturation in comparison to the non-parameterize Elliot function. We have introduced a parameter α, which controls the shape of the Elliot function. After the introduction of the PEF, the hidden state equation is as follows:$h_t = O_t \alpha_c PEF(C_t)$. By chain rule, $\frac{\partial J}{\partial \alpha_c} = \frac{\partial J}{\partial \alpha_c} = \frac{\partial J}{\partial h_t} O_t * Elliot(C_t)$. After each iteration, the α_c is updated by gradient descent $\alpha_c^{(n+1)} = \alpha_c^n + \delta * \frac{\partial J}{\partial \alpha_c}$ (See Appendix C for back propagation of LSTM with PEF).

Intuition behind Our Hypothesis: Glorot & Bengio (2010) hypothesized that in neural networks, the logistic layer output softmax(b+Wh) might initially rely more on the biases b and hence push the activation value h towards 0, thus resulting in error gradients of smaller values. They referred to this as the saturation property of neural networks. This results in slower training and prevents the gradients from propagating backward until the layers close to the input learns. This saturation property is observed in the sigmoid. The sigmoid is non-symmetric around zero and obtains smaller error gradients when the sigmoid outputs a value close to 0. Similarly, tanh in all layers tends to

(a) Derivatives comparisons of various activation functions.

(b) LSTM values for 4 layers and 50 epochs using PEF as activation function using AWS2.

(c) LSTM values for 4 layers and 50 epochs using Sigmoid as activation function using AWS2.

(d) LSTM values for 4 layers and 50 epochs using Tanh as activation function using AWS2.

Dataset	α after training	α initial value
AWS Dataset$_1$	1.612	0.1
AWS Dataset$_2$	0.895	0.1
AWS Dataset$_3$	1.554	0.1
AWS DatasetSyn$_1$	1.537	0.1
AWS DatasetSyn$_2$	0.680	0.1
AWS DatasetSyn$_3$	1.516	0.1
Yahoo Dataset$_1$	1.432	0.1
Yahoo Dataset$_2$	1.470	0.1
Yahoo Dataset$_3$	1.658	0.1
Yahoo Dataset$_5$	1.686	0.1
Yahoo Dataset$_6$	1.698	0.1
Yahoo Dataset$_7$	1.725	0.1
Yahoo Dataset$_8$	1.850	0.1
Yahoo Dataset$_9$	1.640	0.1

Table 2: Different α values for each Dataset after the training.

(e) The final α values learn on each dataset. We can see the final α value is different for different datasets.

Figure 3: The Fig shows the slow saturation rate as well as behavioral comparison of the different layers of LSTM model after the introduction of PEF with other activation functions. It also shows the final value of the learned parameter α on various datasets.

saturate towards 1, which leads to layer saturation. All the layers attain a particular value, which is detrimental to the propagation of gradients. However, this issue of attaining saturation would be less pronounced in cases where two different activation functions are used. Since each activation function behaves differently in terms of gradients, i.e., sigmoid outputs are in the range [0,1], and the gradients are minimum at the maximum and minimum values of the function. Tanh, on the other hand, has minimum gradients at -1 and 1 and reaches its maximum at 0. Therefore, even if the layers begin to saturate to a common value, some of the layers would escape the saturation regime of their activations and would still be able to learn essential features. As an outcome, this might result in fewer instances of vanishing gradients. This assumption would mean that networks with two different activations would learn faster and converge faster to a minima, and the same premise is supported by a Convergence study (details in section V). As demonstrated by Glorot and Bengio, if the saturation ratio of layers is less pronounced, it leads to better results in terms of accuracy. A standard neural network with N layers is given by $h^l = \sigma(h^{l-1}W^l + b)$ and $s^l = h^{l-1}W^l + b$. Here h^l is the output of the first hidden layer, σ is a non-linear activation function, and b is the bias. We compute the gradients as $\frac{\partial Cost}{\partial s_k^l} = f'(s_k^l)W_{k,\cdot}^l \frac{\partial Cost}{\partial s^{l+1}}$; $\frac{\partial Cost}{\partial W_{m,n}^l} = z_l^i \frac{\partial Cost}{\partial s_k^l}$. Now, we find

the variances of these values. As the network propagates, we must ensure that the variances are equal to keep the information flowing. Essentially, when $\forall (l, l'), Var[h^l] = Var[h^{l'}]$, it ensures that forward propagation does not saturate, and when $\forall (l, l'), Var[\frac{\partial Cost}{\partial s^l}] = Var[\frac{\partial Cost}{\partial s^{l'}}]$, it ensures that backward propagation flows at a constant rate. Now, what remains is to calculate these variance values. An elaborate example has been given in the Appendix D.

PEF saturation: The derivative of the PEF is represented by: $= \frac{\alpha}{x^2} EF^2$. While the derivatives of the sigmoid and tanh are dependent on x, PEF is dependent on both α and x. Even if $\frac{EF^2(x)}{x^2}$ saturates, the learned parameter α will help the PEF escape saturation. The derivatives of the sigmoid, tanh saturate when $x > 5$ or $x < -5$. However, it is not true with PEF as evident from fig 3a. As empirical evidence, the layer values for every epoch of the model are captured using various activation functions like PEF, sigmoid and tanh. It is observed that, after about 10 epochs, the values of the layers becomes more or less constant for sigmoid and tanh (fig 3c and fig 3d), indicating their values have already saturated whereas for PEF, variation can be seen till it reaches 50 epochs (fig 3b). This shows that in comparison to sigmoid and tanh as activation functions, PEF escapes saturation due to its learned parameter α. *The parameter α in PEF* changes its value as the model trains over the training dataset while using PEF as the activation function. Since it is a self training parameter, it returns different values for different datasets at the end of training. These values have been documented in table 2 and plotted in fig 3e. Table 2 demonstrates the variations in α values across multiple datasets as these values get updated.

The outcome of such an approach saves the overhead of tuning the model and also opens up avenues for discovering essential features of not-so-popular AFs. The inherent idea is to consider a 'fixed-form' activation and parameterize it. The parameter is 'learned' via the backpropagation step of the LSTM network such that the shape of the activation, determined by the parameter, is learned from data. Thus, if the dataset changes, so does the final form of the activation. In our case, the fixed form activation is the Elliot Activation function.

4 EXPERIMENT

In this section, we have evaluated the performance of the quantile-LSTM techniques on multiple datasets. We have identified multiple baseline methods, such as iForest, Elliptic envelope, Autoencoder and several deep learning based approaches for comparison purposes (See section 5 for more details on baseline methods).

4.1 DATASETS

The dataset properties have been shown in table 6. A total of 29 datasets, including real industrial datasets and synthetic datasets, have been considered in the experiments. The industrial datasets include Yahoo webscope (Yahoo!, 2019), AWS cloudwatch (Lavin & Ahmad, 2015), GE, etc. There are a couple of datasets with either one or few anomalies, such as AWS_1, AWS_2. We have injected anomalies in AWS, Yahoo, and GE datasets to produce synthetic data for fair comparison purposes. The datasets are univariate, unimodal or binodal and follow mostly Weibull, Gamma and Log normal distribution. The highest anomaly percentage is 1.47 (GE Dataset$_2$), whereas AWS Dataset$_2$ has reported the lowest percentage of anomaly i.e. 0.08 (For more details see Table 6 of Appendix, section E).

4.2 RESULTS

Table 3 demonstrates the performance comparison of various LSTM techniques. Precision and Recall, two performance metrics, are shown in the table. The Median-LSTM has achieved Recall 1 in most datasets (10 out of 15 datasets). In comparison to existing benchmarks, LSTM methods are SOTA on most of the datasets in terms of Recall. For comparison purposes, we have first compared the Recall. If the Recall is the same for two different methods, then we have compared the Precision. The method which has a higher Recall and Precision will be considered as a better performer. In AWS datasets, most of the techniques have achieved the highest Recall apart from DAGMM and DevNet. DevNet needs minimum two anomalies hence it is not applicable for AWS1 and AWS2. However, as per Precision, iqr-LSTM has performed better than other methods. In the case of GE1,

DevNet has produced a better result, whereas quantile based LSTM techniques has outperformed others on GE_2. Median-LSTM has demonstrated better result in Ambient temperature. In the case of Yahoo datasets, Median-LSTM has achieved the highest Recall on four datasets; however, quantile-LSTM and iqr-LSTM have produced better results on several datasets. For example, Median-LSTM and iqr-LSTM both achieved Recall 1 on $Yahoo_1$. However, if we compare the Precision, iqr-LSTM has shown better results. It is evident from the table 3 that all these LSTM versions are performing very well on these industrial datasets.

Dataset	Anomaly	iqr-LSTM		Median-LSTM		quantile-LSTM		Autoencoder		GAN		DAGMM		DevNet		iForest		Envelope	
		Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall
AWS1	1	0.5	1	0.052	1	0.041	1	0.045	1	0.047	1	0.125	1	NA	NA	0.0087	1	0.009	1
AWS2	2	0.13	1	0.22	1	0.0042	1	0.1	0.5	0.18	1	0.11	1	NA	NA	0.0062	1	0.04	1
AWS3	1	1	1	0.37	1	0.0181	1	0.0344	1	0.055	1	0	0	NA	NA	0.005	1	0.006	1
Ambient temperature	1	0.03	1	0.0769	1	0.02	1	0.055	1	0	0	0	0	NA	NA	0.01	1	0.02	1
GE1	3	0.019	1	0.048	1	0.0357	1	0.093	1	0.041	0.33	0	0	0.12	1	0.004	1	0.2	1
GE2	8	1	1	0.66	1	1	1	1	1	0	0	0.8	1	0.8	1	0.16	1	0.034	1
Yahoo1	2	0.076	1	0.0363	1	0.0465	1	1	0.5	0.066	1	0.07	0.5	0	0	0.005	1	0.009	1
Yahoo2	8	0.75	0.375	0.8	1	1	0.375	0.19	0.25	0.10	0.25	0	0	0	0	0.04	0.875	0.055	1
Yahoo3	8	0.615	1	0.114	0.675	0.088	1	0.023	0.25	0.11	0.875	0.15	0.62	0.39	0.5	0.04	0.875	0.032	0.875
Yahoo5	9	0.048	0.33	0.1	0.33	0.022	0.66	0.05	0.33	0	0	0.23	0.33	0.67	1	0.029	0.66	0.029	0.66
Yahoo6	4	0.12	1	0.222	1	0.0275	1	0.048	1	0	0	0.041	1	1	1	0.0073	1	0.0075	1
Yahoo7	11	0.096	0.54	0.16	0.63	0.066	0.54	0.083	0.45	0.035	0.54	0.058	0.09	0.33	0.29	0.0082	0.33	0.017	0.54
Yahoo8	10	0.053	0.7	0.142	0.8	0.028	0.3	0	0	0	0	0	0	0.063	0.11	0.01	0.6	0.010	0.6
Yahoo9	8	1	0.75	0.333	1	0.0208	0.75	1	0.37	0	0	0.5	0.375	0.07	0.8	0.04	1	0.047	1

Table 3: Performance comparison of various quantile LSTM techniques with other state of the art algorithms.

Dataset	Anomaly	iqr-LSTM		Median-LSTM		quantile-LSTM		iForest		Envelope		Autoencoder		GAN		DAGMM		DevNet	
		Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall
AWS_syn1	11	0.769	0.909	0.687	1	1	0.909	0.034	1	0.10	1	1	0.63	0.84	1	0.71	0.90	0.09	0.73
AWS_syn2	22	0.7	1	0.733	1	0.6875	1	0.065	1	0.33	1	0.5	0.63	0.70	1	0.56	1	0.44	0.27
AWS_syn3	11	1	0.9	0.47	1	1	1	0.025	1	0.072	1	0.64	0.5	0.68	1	0	0	0.2	0.45
GE_syn1	13	0.0093	1	0.203	1	0.071	0.769	0.0208	1	0.135	1	0.23	0.11	0.25	0.61	0	0	0.33	1
GE_syn2	18	0.0446	1	1	1	1	1	0.3	1	0.409	1	1	0.38	0.9	1	0.9	1	0.9	1
Yahoo_syn1	12	1	1	0.217	0.833	0.375	1	0.027	1	0.056	1	1	0.83	0.31	1	0.29	0.41	0	0
Yahoo_syn2	18	0.181	0.55	0.653	0.944	1	0.611	0.233	1	0.124	1	1	0.42	1	0.61	0.55	0.61	0	0
Yahoo_syn3	18	0.89	0.94	0.3333	0.555	0.6	1	0.0410	1	0.0762	0.944	1	0.88	0.81	0.71	0.3	0.66	0.17	0.63
Yahoo_syn5	19	0.081	0.52	0.521	0.631	0.0625	0.578	0.03125	0.842	0.0784	0.842	0.15	0.47	0.42	0.53	0.52	0.52	0.73	0.92
Yahoo_syn6	14	0.065	0.85	0.65	0.928	0.764	0.928	0.01825	1	0.00761	0.285	0.05	0.28	0.8	0.29	0.041	0.28	0	0
Yahoo_syn7	21	0.61	0.59	0.375	0.714	0.411	0.66	0.032	0.952	0.052	0.85	0.18	0.42	0.14	0.38	0.058	0.047	0.11	0.64
Yahoo_syn8	20	0.32	0.65	0.482	0.823	0.197	0.7	0.0192	0.75	0.023	0.7	0.009	0.05	0.25	0.1	0	0	0.23	0.64
Yahoo_syn9	18	1	0.77	1	1	1	0.94	0.053	1	0.048	1	0.875	0.388	0.72	1	0.57	0.22	0.03	0.29

Table 4: Performance comparison of various quantile LSTM techniques on synthetic datasets with other state of the art algorithms.

Table 4 shows the comparison with other baseline algorithms on multiple synthetic datasets. As in the previous table, Recall and Precision have been shown as performance metrics. As per these metrics, quantile-based approaches have outperformed iForest and other deep learning based algorithms on 7 out of 13 datasets. If we consider the Precision alone, the quantile LSTM based techniques have demonstrated better performance on 10 synthetic datasets. Our methods outperformed tree based anomaly identifiers MGTree and UVMGTree (Sarkar et al., 2022) as well, in terms of Recall (See Table 8 of Appendix G). There are multiple reasons for the better performance demonstrated by the quantile based LSTM approaches. First is the efficacy of the LSTM, which is well documented. Median-LSTM has detected the anomalies for each time period utilizing mean and standard deviation. It also has helped to capture the trend and seasonality. quantile-LSTM do not have any predefined threshold, which has improved their performance. Additionally, the flexibility of the parameter α in determining the shape of the activation helped in isolating the anomalies. This is evident from Fig 3e which represents the variation in α values of the PEF function across the datasets. α has been initialized to 1.5 for all the datasets.

5   RELATED WORK

Well known supervised machine learning approaches such as Linear Support Vector Machines (SVM), Random Forest (RF) and Random Survival Forest (RSF) (Voronov et al., 2018; Verma et al., 2017) have been explored for fault diagnosis and the life-time prediction of industrial systems. Anton et al. (2019) have explored SVM and RF to detect intrusion based on the anomaly in industrial data. Popular unsupervised approaches, such as Anomaly Detection Forest (Sternby et al., 2020), and k-means based Isolation Forest (Karczmarek et al., 2020) try to isolate the anomalies from the normal dataset. These methods do not require labeled data. Karczmarek et al. (2020) considered K-means based anomaly isolation, but the approach is tightly coupled with a clustering algorithm. Anomaly Detection Forest like k-means based iForest requires a training phase with a subsample of the dataset under consideration. A wrong selection of the training subsample can cause too many false alarms. Recently, Deep Learning (DL) models based on auto-encoders, long-short term memory (Erfani et al., 2016; Zhou & Paffenroth, 2017) are increasingly gaining attention for anomaly detection. Yin et al. (2020) have proposed an integrated model of Convolutional Neural Network (CNN) and LSTM based auto-encoder for Yahoo Webscope time-series anomaly detection. For reasons unknown, Yin et al. (2020) have taken only one Yahoo Webscope data to demonstrate their approach's efficacy. The DeepAnT (Munir et al., 2018) approach employs DL methods and it uses unlabeled data for training. However, the approach is meant for time-series data set such as Yahoo Webscope, Real traffic, AWS cloudwatch etc. A stacked LSTM (Malhotra et al., 2015) is used for time series anomaly prediction, and the network is trained on a normal dataset. Hierarchical Temporal Memory (HTM) method has been applied recently on sequential streamed data and compared with other time series forecasting models (Osegi, 2021). The authors in Saurav et al. (2018) have performed online timeseries anomaly detection using deep RNN. The incremental retraining of the neural network allows to adopt concept drift across multiple datasets. There are various works (Morales-Forero & Bassetto, 2019; Sperl et al., 2020), which attempt to address the data imbalance issue of the anomaly datasets since anomalies are very rare and occur occasionally. Hence they propose a semi-supervised approaches. However, the semi-supervised approach cannot avoid the expensive dataset labeling. Some approaches (Zong et al., 2018) apply predefined thresholds, such as fixed percentile value to detect the anomalies. However, a fixed threshold value may not be equally effective on different domain datasets. Deep Autoencoding Gaussian Mixture Model (DAGMM) is an unsupervised DL based anomaly detection algorithm (Zong et al., 2018), where it utilizes a deep autoencoder to generate a low-dimensional representation and reconstruction error for each input datapoint and is further fed into a Gaussian Mixture Model (GMM). Deviation Network(DevNet) (Pang et al., 2019) is a novel method that harnesses anomaly scoring networks, Z-score based deviation loss and Gaussian prior together to increase efficiency for anomaly detection.

6   DISCUSSION AND CONCLUSION

In this paper, we have proposed multiple versions of the SoTA anomaly detection algorithms along with a forecasting based LSTM method. We have demonstrated that combining the quantile technique with LSTM can be successfully implemented to detect anomalies in industrial and non-industrial datasets (See Table 7 of Appendix F) without label availability for training. We have also exploited the parameterized Elliot activation function and shown anomaly distribution against quantile values, which helps in deciding the quantile anomaly threshold. The design of a flexible form activation, i.e., PEF, also helps in accommodating variance in the unseen data as the shape of the activation is learned from data. PEF, as seen in Table 9 in Appendix H captures anomalies better than vanilla Elliot. The quantile thresholds are generic and will not differ for different datasets. The proposed techniques have addressed the data imbalance issue and expensive training dataset labeling in anomaly detection. These methods are useful where data is abundant. Traditional deep learning based methods use classical conditional means and assume random normal distributions as the underlying structure of data. These assumptions make the methods vulnerable to capturing the uncertainty in prediction and make them incapable of modeling tail behaviours. Quantile in LSTM (for time series data) is a robust alternative that we leveraged in isolating anomalies successfully. This is fortified by the characteristics of quantiles making very few distributional assumptions. The distribution-agnostic behavior of Quantiles tuned out to be a useful tool in modeling tail behavior and detecting anomalies. The proposed methods have a few drawbacks 1. quantile based LSTM techniques are applicable only on univariate datasets. 2. A few of the methods such as quantile-LSTM, iqr-LSTM have dependency on multiple thresholds.

7 ETHICS STATEMENT

The present paper discusses various anomaly detection techniques and mostly performed the experiments on publicly available datasets for reproducibility purposes. The paper empirically studies various behaviors of (mostly existing) algorithms on machine/systems data. Since our experiment do not involve human or animal subjects, it is unlikely to introduce any ethical or societal concerns.

8 REPRODUCIBILITY

We have performed the experiments mostly on the publicly available datasets (except for the GE dataset). We have given the links of the datasets in the main text. Code of the quantile based LSTM techniques are available in https://anonymous.4open.science/r/Quantile-LSTM-D840/README.md..

REFERENCES

D. D. S. Anton, S. Sinha, and H. Dieter Schotten. Anomaly-based intrusion detection in industrial data with svm and random forests. In *2019 International Conference on Software, Telecommunications and Computer Networks (SoftCOM)*, 2019. doi: `10.23919/softcom.2019.8903672`.

S.M. Erfani, S. Rajasegarar, S. Karunasekera, and C. Leckie. High-dimensional and large-scale anomaly detection using a linear one-class svm with deep learning. *Pattern Recognit*, 58:121–134, 2016.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Yee Whye Teh and Mike Titterington (eds.), *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pp. 249–256, Chia Laguna Resort, Sardinia, Italy, 2010. PMLR. URL `https://proceedings.mlr.press/v9/glorot10a.html`.

J. L. Horowitz. A smoothed maximum score estimator for the binary response model. *Econometrica*, 60(3):505–531, 1992. ISSN 00129682, 14680262. URL `http://www.jstor.org/stable/2951582`.

A. Jinwon and S. Ch. Variational autoencoder based anomaly detection using reconstruction probability. In *Special Lecture on IE*, pp. 1–18, 2015.

P. Karczmarek, A. Kiersztyn, W. Pedrycz, and E. Al. K-means-based isolation forest. *Knowledge-Based Systems*, 195, 2020.

Roger Koenker. *Quantile Regression*. Cambridge University Press, 2005.

A. Lavin and S. Ahmad. [dataset] the numenta anomaly benchmark. `https://github.com/numenta/NAB/tree/master/data`, 2015. [accessed on 15/1/2019].

T. F. Liu, M. K. Ting, and Z. H. Zhou. Isolation forest. In *2008 Eighth IEEE International Conference on Data Mining*, pp. 273–280, December 2008. doi: `10.1109/ICDMW.2016.0046`.

P. Malhotra, L. Vig, G.G. Shroff, and P. Agarwal. Long short term memory networks for anomaly detection in time series. In *European Symposium on Artificial Neural Networks, Computational Intelligence and Machine Learning*, pp. 89–94, 2015.

A. Morales-Forero and S. Bassetto. Case study: A semi-supervised methodology for anomaly detection and diagnosis. In *In 2019 IEEE International Conference on Industrial Engineering and Engineering Management (IEEM)*, pp. 1031–1037, 2019.

M. Munir, A. S. Siddiqui, A. Dengel, and S. Ahmed. Deepant: A deep learning approach for unsupervised anomaly detection in time series. *IEEE Access*, 1(1):1085–1100, 2018. doi: `10.1109/access.2018.2886457`.

E. N. Osegi. Using the hierarchical temporal memory spatial pooler for short-term forecasting of electrical load time series. *Applied Computing and Informatics*, 7(2):264–278, 2021. ISSN 2634-1964. doi: https://doi.org/10.1016/j.rser.2014.01.088.

Guansong Pang, Chunhua Shen, and Anton van den Hengel. Deep anomaly detection with deviation networks. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 353–362, 2019.

P. J. Rousseeuw and K. V. Driessen. A fast algorithm for the minimum covariance determinant estimator. *Technometrics*, 41(3):212–223, 1999. doi: 10.1080/00401706.1999.10485670.

M. Sakurada and T. Yairi. Anomaly detection using autoencoders with nonlinear dimensionality reduction. In *Proceedings of the MLSDA 2014 2nd Workshop on Machine Learning for Sensory Data Analysis - MLSDA'14*, pp. 1031–1037, 2014. doi: 10.1145/2689746.2689747.

J. Sarkar, S. Saha, and S. Sarkar. Efficient anomaly identification in temporal and non-temporal industrial data using tree based approaches. *Appl Intell*, 2022. doi: https://doi.org/10.1007/s10489-022-03940-3.

S. Saurav, P. Malhotra, V. T. N. Gugulothu, L. Vig, P. Agarwal, and G. Shroff. Online anomaly detection with concept drift adaptation using recurrent neural networks. In *Proceedings of the ACM India Joint International Conference on Data Science and Management of Data, ser. CoDS-COMAD*, pp. 78–87, 2018.

P. Sperl, J. P. Schulze, and K. B. ottinger. A3: Activation anomaly analysis. 2020. doi: arXiv: 2003.01801v3. URL https://arxiv.org/pdf/2003.01801.pdf.

J. Sternby, E. Thormarker, and M. Liljenstam. Anomaly detection forest. In *ECAI*, 2020.

A. Tambwekar, A. Maiya, S. Dhavala, and S. Saha. Estimation and applications of quantiles in deep binary classification. *IEEE Transactions on Artificial Intelligence*, 3(2):275–286, 2022. doi: 10.1109/TAI.2021.3115078.

K. N. Verma, R. K. Sevakula, and R. Thirukovalluru. Pattern analysis framework with graphical indices for condition-based monitoring. *IEEE Transactions on Reliability*, 66(4):1085–1100, 2017. doi: 10.1109/TR.2017.2729465.

S. Voronov, E. Frisk, and M. Krysander. Data-driven battery lifetime prediction and confidence estimation for heavy-duty trucks. *IEEE Transactions on Reliability*, 67(2):623–639, 2018. doi: 10.1109/TR.2018.2803798.

Yahoo! [dataset] computing systems data. https://webscope.sandbox.yahoo.com/catalog.php?datatype=s&did=70, 2019. [accessed on 15/1/2019].

C. Yin, J. Wang S. Zhang, and N. N. Xiong. Anomaly detection based on convolutional recurrent autoencoder for iot time series. *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, pp. 1–11, 2020. doi: 10.1109/tsmc.2020.2968516.

C. Zhou and R. C. Paffenroth. Anomaly detection with robust deep autoencoders. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining - KDD*, 2017. doi: 10.1145/3097983.3098052.

Bo Zong, Qi Song, Martin Renqiang Min, Wei Cheng, Cristian Lumezanu, Daeki Cho, and Haifeng Chen. Deep autoencoding gaussian mixture model for unsupervised anomaly detection. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=BJJLHbb0-.

A PROBABILITY BOUND

Dataset	$\mathcal{P}(\mathcal{E} > 0.95)$	$\mathcal{P}(\mathcal{E} > 0.9)$	$\mathcal{P}(\mathcal{E} > 0.75)$	$\mathcal{P}(\mathcal{F} < 0.25)$	$\mathcal{P}(\mathcal{F} < 0.10)$
AWS Dataset$_1$	0	0.01	0.004	0	0
AWS Dataset$_2$	0	0.1	0.1	0	0
AWS Dataset$_3$	0	0.007	0.0032	0	0
Yahoo Dataset$_1$	0	0.014	0.005	0	0
Yahoo Dataset$_2$	0	0.105	0.062	0	0
Yahoo Dataset$_3$	0	0.103	0.076	0	0
Yahoo Dataset$_4$	0	0.014	0.0055	0	0
Yahoo Dataset$_5$	0	0.043	0.016	0	0
Yahoo Dataset$_6$	0	0.028	0.011	0	0
Yahoo Dataset$_7$	0	0.047	0.018	0.0069	0.017
Yahoo Dataset$_8$	0	0.011	0.004	0.016	0.041
Yahoo Dataset$_9$	0	0.017	0.0069	0.011	0.029
Sensor Dataset$_1$	0	0.0344	0.0135	0	0
Sensor Dataset$_2$	0	0	0	0.013	0.033
GE Dataset$_1$	0	0.003	0.002	0	0
GE Dataset$_2$	0	0.05	0.042	0	0
AWS Datasetsyn$_1$	0	0.08	0.035	0	0
AWS Datasetsyn$_2$	0	0.08	0.035	0	0
AWS Datasetsyn$_3$	0	0.1	0.1	0	0
Yahoo Datasetsyn$_1$	0	0.074	0.034	0	0
Yahoo Datasetsyn$_2$	0	0.21	0.15	0	0
Yahoo Datasetsyn$_3$	0	0.13	0.11	0	0
Yahoo Datasetsyn$_5$	0	0.08	0.036	0	0
Yahoo Datasetsyn$_6$	0	0	0	0.025	0.062
Yahoo Datasetsyn$_7$	0	0.047	0.018	0.03	0.076
Yahoo Datasetsyn$_8$	0	0.034	0.015	0.026	0.051
Yahoo Datasetsyn$_9$	0	0.017	0.0069	0.034	0.088
Sensor Datasetsyn$_1$	0	0	0	0.108	0.39
Sensor Datasetsyn$_2$	0	0	0	0.146	0.36
GE DatasetSyn$_1$	0	0.017	0.0104	0	0
GE DatasetSyn$_2$	0	0.11	0.096	0	0

Table 5: Various probability values on different quantile threshold parameters (See lemma 1 of the main paper).

B LEMMA

Lemma 1:
For an univariate dataset $\mathcal{D}$, the probability of an anomaly $\mathcal{P}(\mathcal{A}) = \mathcal{P}(\mathcal{E} > \alpha_{high}) + \mathcal{P}(\mathcal{F} < \alpha_{low})$, where $\alpha_{high}, \alpha_{low}$ are the higher and lower level quantile thresholds respectively.

Figure 4: The structure of LSTM cell.

Proof. A datapoint is declared an anomaly if its quantile value is higher than α_{high} or lower than α_{low}. Here α_{high}, α_{low} are the higher and lower quantile threshold value. $\mathcal{P}(\mathcal{E} > \alpha_{high})$ is the probability of an anomaly whose quantile value is higher than α_{high}. On the other side, $\mathcal{P}(\mathcal{F} < \alpha_{low})$ is the probability of quantile value of anomalous datapoint lower than α_{low}. Hence the presence of an anomaly in a dataset is possible if one of the events is true. Therefore

$$\mathcal{P}(\mathcal{A}) = P(\mathcal{E} > \alpha_{high} \cup \mathcal{F} < \alpha_{low})$$
$$\mathcal{P}(\mathcal{A}) = \mathcal{P}(\mathcal{E} > \alpha_{high}) + \mathcal{P}(\mathcal{F} < \alpha_{low}) - P(\mathcal{E} > \alpha_{high} \cap \mathcal{F} < \alpha_{low})$$

Both the events $\mathcal{E}, \mathcal{F}$ are mutually exclusive. Hence the above Equation can be written as

$$\mathcal{P}(\mathcal{A}) = \mathcal{P}(\mathcal{E} > \alpha_{high}) + \mathcal{P}(\mathcal{F} < \alpha_{low}) \tag{2}$$

$\square$

C BACKPROPAGATION OF LSTM WITH PEF

For backward propagation, it is required to compute the derivatives for all major components of the LSTM. J is the cost function and the relationship between v_t and hidden state h_t is $v_t = w_v * h_t + b_v$. The predicted value $y' = softmax(v_t)$. The derivative of the hidden state can be shown as follow

$$\frac{\partial J}{\partial h_t} = \frac{\partial J}{\partial v_t} \frac{\partial v_t}{\partial h_t}$$
$$\frac{\partial J}{\partial h_t} = \frac{\partial J}{\partial v_t} \frac{\partial(w_v * h_t + b_v)}{\partial h_t}$$
$$\frac{\partial J}{\partial h_t} = \frac{\partial J}{\partial v_t} w_v$$

The variable involved in the output gate is o_t.

$$\frac{\partial J}{\partial o_t} = \frac{\partial J}{\partial h_t} \frac{\partial h_t}{\partial o_t}$$
$$\frac{\partial J}{\partial o_t} = \frac{\partial J}{\partial h_t} \frac{\partial(o_t * PEF(C_t))}{\partial o_t}$$
$$\frac{\partial J}{\partial o_t} = \frac{\partial J}{\partial h_t} PEF(C_t)$$

C_t is the cell state and the chain rule for cell state can be written as

$$\frac{\partial J}{\partial C_t} = \frac{\partial J}{\partial h_t} \frac{\partial h_t}{\partial C_t} \tag{3}$$

$\frac{\partial J}{\partial h_t}$ value already we have calculated as part of hidden state equation.

$$\frac{\partial h_t}{\partial C_t} = \frac{\partial(o_t * PEF(C_t))}{\partial C_t}$$
$$= \frac{\alpha o_t}{(|C_t| + 1)^2}$$

After setting the value of $\frac{\partial h_t}{\partial C_t}$ in equation 4

$$\frac{\partial J}{\partial C_t} = \frac{\partial J}{\partial h_t} \frac{\alpha o_t}{(|C_t| + 1)^2} \tag{4}$$

The chain rule for $\hat{c}_t$ is

$$\frac{\partial J}{\partial \hat{c}_t} = \frac{\partial J}{\partial C_t} \frac{\partial C_t}{\partial \hat{c}_t}$$

We need to derive only $\frac{\partial C_t}{\partial \hat{c}_t}$ since $\frac{\partial J}{\partial C_t}$ is available from equation 5.

$$\frac{\partial C_t}{\partial \hat{c}_t} = \frac{\partial (f_t * C_{t-1} + \hat{c}_t * i_t)}{\partial \hat{c}_t}$$
$$= i_t$$

After replacing the value of $\frac{\partial C_t}{\partial \hat{c}_t}$

$$\frac{\partial J}{\partial \hat{c}_t} = \frac{\partial J}{\partial C_t} * i_t$$

Similar way $\frac{\partial J}{\partial a_c} = \frac{\partial J}{\partial \hat{c}_t} * \frac{\alpha}{(|a_c|+1)^2}$ The following derivatives for input gate

$$\frac{\partial J}{\partial i_t} = \frac{\partial J}{\partial C_t} \hat{c}_t$$
$$\frac{\partial J}{\partial a_i} = \frac{\partial J}{\partial C_t} \hat{c}_t (i_t(1 - i_t))$$

For forget gate, below are the derivatives

$$\frac{\partial J}{\partial f_t} = \frac{\partial J}{\partial C_t} C_{t-1}$$
$$\frac{\partial J}{\partial a_f} = \frac{\partial J}{\partial C_t} C_{t-1} (f_t(1 - f_t))$$

Z_t is the concatenation of the h_{t-1}, x_t. The derivatives of the weights are as follow

$$\frac{\partial J}{\partial w_f} = \frac{\partial J}{\partial a_f} Z_t$$
$$\frac{\partial J}{\partial w_i} = \frac{\partial J}{\partial a_i} Z_t$$
$$\frac{\partial J}{\partial w_v} = \frac{\partial J}{\partial v_t} h_t$$
$$\frac{\partial J}{\partial w_o} = \frac{\partial J}{\partial a_o} Z_t$$

C.1 PARAMETERIZED ELLIOT FUNCTION

One of the major benefit of the parameterized Elliot function is that it further decreases the rate of saturation in comparison to the non-parameterize Elliot function. We have applied one parameter α, which controls the shape of the Elliot function. There will be different derivatives if we apply parameterize Elliot function in LSTM.

$$PEF = \frac{\alpha x}{1 + |x|}$$

After the introduction of the PEF, the hidden state equation is as follow

$$h_t = O_t \alpha_c PEF(C_t)$$

As per the chain rule, the derivative for α_c will be

$$\frac{\partial J}{\partial \alpha_c} = \frac{\partial J}{\partial h_t} \frac{\partial O_t \alpha_c Elliot(C_t)}{\partial \alpha_c}$$

$$\frac{\partial J}{\partial \alpha_c} = \frac{\partial J}{\partial h_t} O_t * Elliot(C_t)$$

After each iteration, the α_c is updated as per equation 5.

$$\alpha_c^{(n+1)} = \alpha_c^n + \delta * \frac{\partial J}{\partial \alpha_c} \tag{5}$$

Similarly, we can derive $\hat{\alpha_c}$ and update the parameter.

D   Intuition with An Example:

Firstly, we attempt to find variance for two sigmoid activations in a network. The derivative of each activation output is approximately $0.25(\sigma'(0) = 0.25)$, as the weights are uniformly initialized, and the input features are assumed to have the same variance. Hence,

$$f'(s_k^l) = 0.25$$

$$Var[z^2] = Var[x]((0.25)^2 n_1 Var[W^{1'}] * (0.25)^2 n_2 Var[W^{2'}])$$

We see that this diminishing factor of 0.25^N steeply drops the variance during the forward pass. Similarly, we observe that the gradient,

$$\frac{\partial Cost}{\partial s_k^l} = f'(s_k^l) W_{k,\cdot}^l \frac{\partial Cost}{\partial s^{l+1}}$$

has $f'(s_k^l)$ as one of the factors, and thus the diminishing factor is tied to the variance. Even when $N = 2$ the variance reduces by a factor of $4^4 = 256$.

Let's compute variance for neural network with two hidden layers using sigmoid and tanh activations. For tanh, if the initial values are uniformly distributed around 0, the derivative is $f'(s_k^l) = 1$. Therefore, the variance for the second layer output is, $Var[z^2] = Var[x] * ((0.25)^2 * n_1 * Var[W^{1'}] * n_2 * Var[W^{2'}])$. We see that the diminishing factor is just $4^2 = 16$, and this results in a much better variance when compared to the previous case. Therefore, using different AFs instead of the same implies a reduction in vanishing gradients and results in a much better flow of information because the variance value is preserved for longer.

E   DATASET PROPERTIES

Dataset Name	Anomaly%	Size	Missing Data	Modal	Distribution	#Variables	TW/ Period
Publicly available actual industrial data							
AWS Dataset$_1$	0.09	1049	No	Unimodal	Weibull	Univariate	84/168
AWS Dataset$_2$	0.08	2486	No	Unimodal	Weibull	Univariate	38/152
AWS Dataset$_3$	0.066	1499	No	Multimodal	Weibull	Univariate	38/152
Yahoo Dataset$_1$	0.14	1421	No	Unimodal	Weibull	Univariate	20/60
Yahoo Dataset$_2$	0.54	1462	No	Unimodal	Gamma	Univariate	30/90
Yahoo Dataset$_3$	0.55	1440	No	Unimodal	Weibull	Univariate	10/120
Yahoo Dataset$_4$	0.28	1422	No	Bimodal	Weibull	Univariate	105/210
Yahoo Dataset$_5$	0.63	1421	No	Bimodal	Log-normal	Univariate	24/72
Yahoo Dataset$_6$	0.28	1421	No	Multimodal	Weibull	Univariate	74/148
Yahoo Dataset$_7$	0.53	1680	No	Unimodal	Weibull	Univariate	125/250
Yahoo Dataset$_8$	0.59	1680	No	Unimodal	Log-normal	Univariate	116/232
Yahoo Dataset$_9$	0.47	1680	No	Unimodal	Weibull	Univariate	30/90
Machine Temperature Dataset	0.19	501	No	Multimodal	Weibull	Univariate	38/114
Private actual industrial data							
GE Dataset$_1$	0.18	1609	No	Unimodal	Exponential	Univariate	117/234
GE Dataset$_2$	1.47	544	No	Multimodal	Weibull	Univariate	50/150
Publicly available synthetic industrial data							
AWS DatasetSyn$_1$	1.03	1059	No	Unimodal	Exponential	Univariate	84/168
AWS DatasetSyn$_2$	0.877	2506	No	Unimodal	Weibull	Univariate	38/152
AWS DatasetSyn$_3$	0.72	1509	No	Unimodal	Gamma	Univariate	38/152
Yahoo DatasetSyn$_1$	0.83	1431	No	Unimodal	Weibull	Univariate	20/60
Yahoo DatasetSyn$_2$	1.22	1472	No	Unimodal	Gamma	Univariate	30/90
Yahoo DatasetSyn$_3$	1.24	1450	No	Unimodal	Weibull	Univariate	10/120
Yahoo DatasetSyn$_4$	0.977	1432	No	Bimodal	Weibull	Univariate	105/210
Yahoo DatasetSyn$_5$	1.32	1431	No	Bimodal	Weibull	Univariate	24/72
Yahoo DatasetSyn$_6$	0.97	1431	No	Multimodal	Weibull	Univariate	74/148
Yahoo DatasetSyn$_7$	1.12	1690	No	Unimodal	Weibull	Univariate	125/250
Yahoo DatasetSyn$_8$	1.18	1690	No	Multimodal	Log-normal	Univariate	116/232
Yahoo DatasetSyn$_9$	1.065	1690	No	Bimodal	Weibull	Univariate	30/90
Private synthetic industrial data							
GE DatasetSyn$_1$	0.80	1619	No	Unimodal	Log-normal	Univariate	117/232
GE DatasetSyn$_2$	3.30	554	No	Multimodal	Exponential	Univariate	50/150

Table 6: Anomaly Dataset Properties.

F   COMPARISON ON NON-INDUSTRIAL DATASETS

Since, we used industrial datasets in the initial comparison with multiple deep learning based anomaly detection techniques, thus to provide further survey, here we use non-industrial datasets

(See Table 7). Here, Deviation Networks gives NA because it does not work for single anomaly containing datasets.

Dataset	Anomaly	quantile-LSTM		Autoencoder		GAN		DevNet	
		Precision	Recall	Precision	Recall	Precision	Recall	Precision	Recall
TravelTime$_{387}$	3	0.011	0.67	1	0.33	0.024	0.33	0.01	0.33
TravelTime$_{451}$	1	0.006	1	0	0	0.016	1	NA	NA
Occupancy$_{6005}$	1	0.03	1	0	0	0.007	1	NA	NA
Occupancy$_{t4013}$	2	0.06	1	0.438	0.5	0.014	0.5	0.02	1
Speed$_{6005}$	1	0.014	1	0.103	1	0.009	1	NA	NA
Speed$_{7578}$	4	0.086	1	0.792	1	0.2	0.9	0.16	0.75
Speed$_{t4013}$	2	0.053	1	0.75	0.5	0.043	1	0.1	1

Table 7: Performance comparison of various quantile LSTM techniques on non-industrial datasets.

G COMPARISON WITH TREE BASED ALGORITHMS

In this section, we have compared the quantile-LSTM with other tree based algorithms, such as UVMGTree, MGTree (Sarkar et al., 2022). In table 8, two performance metrics, Precision and Recall have been considered. It has been noticed from the same table that quantile-LSTM has produced better Recall, compared with other tree based anomaly identifier algorithms. However, both the tree based anomaly identifier algorithms have better Precision in comparison to quantile-LSTM. Since, Recall has been given higher priority, quantile-LSTM is competitive enough with other tree based anomaly detection algorithms.

Dataset	UVMGTree(K-means)		MGTree(K-means)		quantile-LSTM	
	Precision	Recall	Precision	Recall	Precision	Recall
AWS Dataset$_1$	100%	100%	100%	100%	5.2%	100%
AWS Dataset$_2$	18%	100%	100%	50%	2.2%	100%
Yahoo Dataset$_1$	15%	100%	50%	50%	3.6%	100%
Yahoo Dataset$_2$	66%	22%	100%	12%	61%	100%
Yahoo Dataset$_3$	87%	87%	100%	12%	11%	87%
Yahoo Dataset$_5$	33%	33%	100%	33%	10%	33%
Yahoo Dataset$_6$	100%	100%	100%	100%	22%	100%
Yahoo Dataset$_7$	77%	63%	50%	27%	16%	63%
Yahoo Dataset$_8$	60%	60%	100%	10%	14%	80%
Yahoo Dataset$_9$	100%	100%	100%	62%	33%	100%

Table 8: The performance comparison of UVMGTree with other standard anomaly identifier algorithms

H   PERFORMANCE COMPARISON BETWEEN ELLIOT FUNCTION AND PEF AS ACTIVATION FUNCTION

In order to compare performance of Elliot function and parameterized Elliot function as activation functions, we experimented them by using them as activation functions in the LSTM layer of the models and comparing the results after they run on multiple datasets. The results are shown in Table 9.

Dataset	Elliot Function		Parameterized Elliot Function	
	Precision	Recall	Precision	Recall
AWS Dataset$_1$	0	0	0.041	1
AWS Dataset$_2$	0.002	1	0.0042	1
AWS Dataset$_3$	0.04	1	0.0181	1
AWS DatasetSyn$_1$	0.02	0.73	1	0.909
AWS DatasetSyn$_2$	0.39	0.77	0.6875	1
AWS DatasetSyn$_3$	0.06	0.73	1	1
Yahoo Dataset$_1$	0.006	0.25	0.0465	1
Yahoo Dataset$_2$	0.02	1	1	0.375
Yahoo Dataset$_3$	0.05	1	0.088	1
Yahoo Dataset$_5$	0.001	0.33	0.022	0.66
Yahoo Dataset$_6$	0.002	0.17	0.0275	1
Yahoo Dataset$_7$	0.03	0.09	0.066	0.54
Yahoo Dataset$_8$	0.017	0.4	0.028	0.3
Yahoo Dataset$_9$	0.43	0.75	0.0208	0.75
Yahoo DatasetSyn$_1$	0.14	0.86	0.375	1
Yahoo DatasetSyn$_2$	0.04	0.72	1	0.611
Yahoo DatasetSyn$_3$	0.1	0.78	0.6	1
Yahoo DatasetSyn$_5$	0.004	0.31	0.0625	0.578
Yahoo DatasetSyn$_6$	0.015	0.69	0.764	0.928
Yahoo DatasetSyn$_7$	0.35	0.43	0.411	0.66
Yahoo DatasetSyn$_8$	0.024	0.5	0.197	0.7
Yahoo DatasetSyn$_9$	0.27	0.67	1	0.94

Table 9: Comparison of Precision and Recall score for LSTM with Elliot Function and parameterized Elliot Function as Activation Function.

According to the data gathered after running the models, we found that parameterized Elliot function has a better Precision and Recall for as except four of the datasets. Thus, we could conclude that using parameterized Elliot function as an activation function gave better performance for quantile-LSTM.