Factored DRO: Factored Distributionally Robust Policies for Contextual Bandits

Abstract

While there has been extensive work on learning from offline data for contextual multi-armed bandit settings, existing methods typically assume there is no environment shift: that the learned policy will operate in the same environmental process as that of data collection. However, this assumption may limit the use of these methods for many practical situations where there may be distribution shifts. In this work we propose Factored Distributionally Robust Optimization (Factored-DRO), which is able to separately handle distribution shifts in the context distribution and shifts in the reward generating process. Prior work that either ignores potential shifts in the context, or considers them jointly, can lead to performance that is too conservative, especially under certain forms of reward feedback. Our Factored-DRO objective mitigates this by considering the shifts separately, and our proposed estimators are consistent and converge asymptotically. We also introduce a practical algorithm and demonstrate promising empirical results in environments based on real-world datasets, such as voting outcomes and scene classification.

1 Introduction

In many real-world applications we often have access to historical data about past decisions and their associated outcomes. This data can be leveraged for *off-policy learning* to optimize for a decision making rule, called a policy, that is more effective for the given application than that used for data collection. Off-policy learning from historical data for contextual multi-armed bandit settings has been well studied, due in part to the myriad potential applications from personalized recommendation [Strehl et al., 2010] to optimizing medical treatment [Kim et al., 2011]. Prior methods often focus on the stationary setting, where the learned policy will be deployed in a setting with the same underlying data generation process that produces the observed contexts, and rewards upon intervention [Precup, 2000, Liu et al., 2018, Kallus and Uehara, 2020a,b, Liu et al., 2020]. However, in many settings, this assumption is not true and the distributions may shift.

As a motivating example, consider the problem of increasing political participation during elections using various interventions to encourage voting. In the past, different strategies have been implemented, ranging from reminding people of their own voting history, to reminding them of the voting history of their neighborhood, etc. [Gerber et al., 2008]. Leveraging this historical data, an important question is: *what strategy should be used during the next election to maximize political participation*? Addressing this question requires careful consideration of two potential sources of distribution shift: **(a)** How much has the population demographic in the area changed since the past data was collected? (e.g. the percentage of single person households may have changed due to industrial developments). and **(b)** How much has the effectiveness of each strategy on each demographic group changed? (e.g. as technology develops, the effectiveness of mail-based interventions may change). Such challenges are ubiquitous in real-world problems. For example, in automated healthcare, data from patients of one locality may be used to develop treatments for other localities where the effectiveness of

treatments may differ [Finlayson et al., 2021]. Similarly, online recommendation systems need to account for both the changing interests and the demographic shifts of its user base [Koh et al., 2021]. Developing a general procedure for addressing these challenges can provide a reliable solution for such applications with high stakes in terms of societal behavior, public health, and monetary assets.

Without considering potential shifts, there is a high risk of using suboptimal strategies, however it is often difficult to predict exactly the shifts that will occur. Distributionally robust optimization formulations such as ours attempt to address this uncertainty over potential shifts by learning policies that attain good performance on all potential distributions within a user-defined set of distributions to be considered (denoted the *uncertainty set*). Prior methods [Si et al., 2020, Mo et al., 2021, Kallus et al., 2022] that aim to provide robustness against distribution shifts do not separate the different sources of shifts, and consider them in a joint formulation. These methods may be disadvantageous as they lack the flexibility to separate the sources. Consequently, some of these methods may produce degenerate results under binary reward feedback, an issue theoretically proven to occur in the DRO literature in supervised learning [Hu et al., 2018]. Due to this, methods that better use structure to mitigate this issue have been an active area of research in the supervised learning DRO literature [Sagawa et al., 2019, Duchi et al., 2019]. We leverage this insight that better usage of structure is important, as well as the insight that it is common to have expert opinion about the amount of distribution shift that may occur between the two sources, to obtain better results.

In this work we address such challenges under the framework of contextual bandits. We propose our Factored Distributionally Robust Optimization (FDRO) algorithm that uses past data to search for a policy that has the best worst-case performance, when the *context* (e.g., population demographic) or/and the *reward model* (e.g., influence of strategies on voting behavior) can be different from the ones during data collection. Towards this goal, we make three primary contributions:

(I) A factored distributionally robust optimization formulation for contextual bandits that provides end-users the flexibility to *separately* specify different amounts of potential shifts in the two main sources of uncertainty: the context distribution and the reward distribution. Our factored formulation can overcome some failure cases of non-factored prior methods [Si et al., 2020]. (II) We establish theoretically that the proposed estimators provide asymptotically consistent evaluation of any policy's worst-case performance under distribution shifts. Additionally, the estimators provide asymptotic convergence to a policy with the best worst-case performance. (III) Building on the theoretical insights, we develop a practical algorithm, FDRO, that uses approximations based on moment generating functions. We show that FDRO provides promising empirical results on several domains based on real-world challenges.

2 Related Works

Both off-policy learning for bandits and reinforcement learning, as well as distributionally robust optimization (DRO) for supervised learning and stochastic optimization have rich histories of research. To briefly summarize, methods for off-policy evaluation/learning predominantly assume that the deployment environment for the learned policy will be the same as the environment the historical data was collected in [Precup, 2000, Jiang and Li, 2016, Thomas and Brunskill, 2016a,b, Gelada and Bellemare, 2019, Liu et al., 2018, Imani et al., 2018, Yang et al., 2020, Jiang and Huang, 2020, Kallus and Uehara, 2020a,b, Liu et al., 2020]. In contrast, DRO methods for tackling distributional shifts have predominantly focused on settings like supervised learning and do not consider decision making aspects present in (contextual) bandits [Bertsimas and Sim, 2004, Hu and Hong, 2013, Namkoong and Duchi, 2016, Shapiro, 2017, Duchi et al., 2016, Duchi and Namkoong, 2018, Hashimoto et al., 2018, Duchi et al., 2019, Sagawa et al., 2019, Oren et al., 2019, Michel et al., 2022].

In addition to the prior work already previously mentioned in Section 1, there have been a few recent papers investigating DRO for use in bandits and reinforcement learning. Some works use DRO to account for the mismatch between the true distributions (of the context and rewards) and the observed empirical distributions [Swaminathan and Joachims, 2015a,b, Faury et al., 2020, Sakhi et al., 2020]. These methods account for the potential errors of finite-data estimation, and, under infinite data, they converge to the best training distribution policy. However we are concerned with the setting when the test distribution may be different, and the best training-distribution policy may not be optimal.

There has also been other work that consider settings when different forms of information are available a priori. For example, knowledge about the distribution of covariates during evaluation [Kato et al.,

92 2020], bounds on the ratio of train-eval covariate distribution [Hatt et al., 2021, Giguere et al., 2021],
93 bounds on train-eval performance differences [Chandak et al., 2021], causal directed acyclic graph
94 [Subbaswamy et al., 2019, Singh et al., 2021], or when there is data through time that can be used to
95 model potential non-stationarity [Thomas et al., 2017, Chandak et al., 2020, Xie et al., 2020, Qin and
96 Russo, 2021]. While relevant, they look at complementary problems.

3 Preliminaries

In this work, we consider the batch setting where the goals is to learn from an existing dataset $\mathcal{D}$. We consider a setting with discrete actions, where $\mathcal{A}$ denotes the set of k discrete actions, A. Let $\mathcal{X} \subset \mathbb{R}^d$ denote the set of contexts, X. A policy π denotes a mapping from a context X to a distribution over actions. For a given context X and action A we observe a stochastic reward R. We assume the dataset, $\mathcal{D}$ consists of n independently collected datapoints , each a (context, action, reward) triplet: $\mathcal{D} = \{X_i, A_i, R_i\}_{i=1}^n$. For this dataset, we assume the actions are selected with some data collection policy π_0 where $A_i \sim \pi_0(\cdot|X_i)$. We assume there is an underlying context distribution P_{x_0}, and for each context-action pair there is an underlying reward distribution $P_{r_0|X,A}$. We additionally assume the observed contexts, X_i are independent and identically distributed (i.i.d.) draws from P_{x_0}, and the observed rewards are i.i.d. draws from $P_{r_0|X_i,A_i}$.

We consider using $\mathcal{D}$ to learn a policy π that will achieve the highest worst-case-reward when the deployment environment may be shifted from the one of data collection. Given a fixed policy, there are two ways the environment can shift and change the distribution of future outcomes. First the context distribution can shift so the inputs we see are different. Second the reward generation model can shift, changing the reward distribution of each (context, action) pair. We assume the exact shift is not known, so we would like to learn a policy that would do well on all environments within a user specified set of distributions of the context distribution P_x and reward distributions $P_{R|X,A}$. Formally, given $\mathcal{D}$ we aim to find the policy that optimizes the following distributionally robust objective:

$$\pi^*_{ddro} \in \underset{\pi \in \Pi}{\operatorname{argmax}} \; \inf_{P_x \in \mathbb{P}_{x_0}} \mathbb{E}_{P_x}\left[\mathbb{E}_\pi \left[\inf_{P_r \in \mathbb{P}_{r_0|X,A}} \mathbb{E}_{P_r}[R] \right] \right] \tag{1}$$

In (1), the uncertainty sets $\mathbb{P}_{r_0|X,A}$ and $\mathbb{P}_{x_0}$ describes the set of possible distributions P_r and P_x, and the optimization set $\mathbb{P}_{r_0|X,A}$ is conditioned on random variables $X \sim P_x$ and $A \sim \pi(\cdot|X)$. We term our objective *Factored-DRO* as we have two layers of distributionally robust optimization, first over reward shifts $P_{R|X,A}$, and another over context shifts P_x.

For theoretical analysis, we make the following assumptions common in prior literature [Si et al., 2020, Swaminathan and Joachims, 2015a, Kallus and Uehara, 2020a].

Assumption 1. *Assumptions on π_0 and the reward distribution*

(i) Unconfounded: Rewards are independent with A conditioned on X: $(R_{X,A_1}, R_{X,A_2}...) \perp\!\!\!\perp A|X$

(ii) Bounded reward support: $0 \le R \le R_M$ for all rewards for a finite R_M

(iii) Coverage/Sufficient exploration: $\pi_0(A|X) \ge \epsilon_\pi$ for all $(X, A) \in \mathcal{X} \times \mathcal{A}$ for some $\epsilon_\pi > 0$

(iv) Positive density of rewards: Let $f_{0,R|X,A}$ be the pdf (continuous case) or $p_{R|X,A}$ be the pmf (discrete case) of the reward distribution $P_{R|X,A}$. Then assume $f_{0,R|X,A} \ge \epsilon_r$ (continous) or $p_{R|X,A} \ge \epsilon_r$ (discrete) on the support of of R for all $(X, A) \in \mathcal{X} \times \mathcal{A}$ for some $\epsilon_r > 0$.

We make an additional assumption, which we do not require in our practical algorithm:

Assumption 2. *Discrete contexts with sufficient mass: The context set $\mathcal{X}$ is a finite discrete set and the probability mass of each context is lower bounded with $P_{x_0}(x = X) \ge \epsilon_X$ for some $\epsilon_X > 0$*

Note about model misspecification: Context shifts are an issue when we have model misspecification and cannot model the best action for each context. In these cases, the learned model encodes the biases of the population distribution. Model misspecification can occur when the model is under-specified, for example, to reduce variance (bias-variance tradeoff), for interpretability, or due to unobserved variables. Misspecification also occurs when the model is over-specified, where it may overfit and not generalize (ex. neural networks [Sagawa et al., 2019]). The real world is often complex and difficult to model correctly, so throughout this work we assume the misspecified setting.

139 **Prior Work with Joint Shifts:** Recently Si et al. [2020] proposed an algorithm for solving a
140 DRO formulation for contextual bandits that does not separate the context and reward shift. They
141 consider the optimization problem: $\pi^* = \text{argmax}_\pi \inf_{P \in \mathbb{P}_{P_0}} \mathbb{E}_P[R]$, where P encapsulates the joint
142 distribution of contexts and rewards and $\mathbb{P}_{P_0} = \{P : D_{kl}(P||P_0) \leq \delta\}$.

143 **Degenerate Outcomes with binary rewards under the joint objective:** Unfortunately, the joint
144 formulation may have a key limitation in the common setting of binary reward outcomes (ex, clicked
145 or not-clicked[Chu et al., 2011], voted or did-not-vote[Gerber et al. [2008], etc). In supervised
146 learning (SL), similar DRO formulations have been theoretically proven to fail with certain loss
147 functions. Hu et al. [2018] prove that when features are continous, and 0-1 classification loss is used,
148 the DRO objective is equivalent to the standard, non-robust optimization of the loss function on the
149 training distribution. Intuitively, DRO can be seen as changing the weights of the datapoints based
150 on the incurred loss, and increasing the radius parameters increases the weights on datapoints with
151 larger incurred losses. However, under 0-1 loss, DRO upweights all missclassified examples equally,
152 which does not change the decision boundary. Consequently, in SL, methods that can mitigate this
153 issue by using structure, such as Duchi et al. [2019] or Sagawa et al. [2019], have been proposed.
154 The same issue holds in the binary reward case for the joint formulation and we observe this issue
155 empirically (see Section 6).[1] Intuitively, the lower reward points for each context action pair are all
156 upweighted equally so the learned policy is equivalent to that optimized for the training distribution.
157 Our method which trades-off needing to set an additional hyperparameter with better structure usage
158 to separate out the shifts mitigates this issue.

159 # 4 Factored DRO for Policy Evaluation and Learning

160 In our work, we consider uncertainty sets defined on the KL radius from the data collection
161 distributions. Due to the joint decomposition, we require the user to specify two KL-radius
162 hyperparameters, δ_c and δ_x, for rewards and contexts respectively as opposed to a single hy-
163 perparameter required in prior work. The uncertainty sets defined in Equation 1 are defined as
164 $\mathbb{P}_{r_0|X,A} = \{P_r : D_{kl}(P_r, P_{r_0|X,A}) < \delta_c\}$ and $\mathbb{P}_{x_0} = \{P_x : D_{kl}(P_x, P_{x_0}) < \delta_x\}$.

165 We can decompose our DRO objective from Equation 1 into two steps, first a policy evaluation step
166 which given a policy evaluates the worst case reward policy reward. Notice the policy evaluation step
167 itself can be separated into two steps: a step considering the potential reward generation shift ($Q_{X,A}$)
168 and a step over potential context shift to arrive at the desired value ($V(\pi)$):

$$V(\pi) = \inf_{P_x \in \mathbb{P}_{x_0}} \mathbb{E}_{P_x}\left[\mathbb{E}_\pi\left[Q_{X,A}\right]\right] \quad \text{where} \quad Q_{X,A} = \inf_{P_r \in \mathbb{P}_{r_0|X,A}} \mathbb{E}_{R \sim P_r}[R] \qquad (2)$$

169 Second, we have a policy optimization step over the worst case policy rewards:

$$\pi^*_{DDRO} = \text{argmax}_\pi V(\pi) \qquad (3)$$

170 In this section, we present our estimators for policy evaluation and learning and asymptotic conver-
171 gence guarantees. We give all result from prior work used and all full proofs in the appendix.

172 **4.1 Policy Evaluation:** We start by discussing the policy evaluation step. Equation 2 as written is a
173 difficult constrained optimization over probability distribution space. Fortunately, there exists prior
174 work (such as Hu and Hong [2013]) that uses methods from convex optimization to transform the
175 problem to an equivalent but simpler convex optimization over a single scalar. They use convexity
176 of the original objective and strong duality to derive an equivalent dual objective. We arrive at the
177 following equivalent problem by applying this duality procedure twice, once for each layer.

178 **Theorem 1** (Strong Duality). *The optimization problem in equation 2 is equivalent to solving:*

$$V(\pi) = -\min_{\alpha_x > 0}\left\{\alpha_x \log \mathbb{E}_{X \sim P_{x_0}}\left[\exp\left(\frac{\mathbb{E}_\pi\left[-Q_{X,A}\right]}{\alpha_x}\right) + \alpha_x \delta_x\right]\right\}, \qquad (4)$$

$$\text{where } Q_{X,A} = -\min_{\alpha_c > 0}\left\{\alpha_c \log \mathbb{E}_{R \sim P_{r_0|X,A}}\left[\exp\left(\frac{-R}{\alpha_c}\right)\right] + \alpha_c \delta_c\right\}. \qquad (5)$$

---

[1]Note, Si et al. [2020] show good results in an environment (voting) which originally had binary rewards,
but they transform the environment rewards to non-binary by shifting all rewards by a different offset per action.

179 *Proof Sketch* This follows from applying Theorem 1 of Hu and Hong [2013] twice.

180 We will use this easier to optimize dual form to derive estimators for policy evaluation. We will
181 first consider the potential shift of the reward distribution of each (context, action) pair and calculate
182 estimates of $Q_{X,A}$ of Equation 5. We will then use these values to perform the second DRO layer
183 over context shifts to estimate $V(\pi)$ (Equation 4).

184 **4.1.1 First DRO, Reward Shift:** For theoretical analysis, we consider the setting when the context
185 and action sets are both finite and discrete (Assumptions 1.2 and 2). Therefore we have a finite
186 number of unique (X, A) pairs, each which occurs with a non-zero probability. For a given (X, A)
187 pair, let $\mathcal{R}_{X,A}$ correspond to the set of the observed reward R_i every time (X, A) is observed in $\mathcal{D}$:
188 $\mathcal{R}_{X,A} = \{R_i : (X_i, A_i, R_i) \in \mathcal{D} \text{ if } X_i = X, A_i = A\}$. Additionally, let $m_{xa} = |\mathcal{R}_{X,A}|$ denote
189 the number of datapoints in each (X, A) bin and recall that δ_c denotes the user specified KL-radius
190 of the ambiguity set.[2] For every unique (X, A) we propose the following estimator for worst case
191 context-action reward for $Q_{X,A}$ in equation 5:

$$\hat{Q}_{X,A} = -\min_{\alpha_c > 0} \left\{ \alpha_c \log \left(\frac{1}{m_{xa}} \sum_{R_j \in \mathcal{R}_{|X,A}} \left[\exp\left(\frac{-R}{\alpha_c} \right) \right] \right) + \alpha_c \delta_c \right\} \tag{6}$$

192 Note that the objective inside the minimization in equation 6 is convex in α_c for $\alpha_c > 0$, therefore
193 many optimization methods (ex. gradient descent, bisection search) are able to achieve the global
194 optimum when $\alpha_c \neq 0$. We give the gradients and a proof of convexity in the appendix. Additionally,
195 note the $\hat{Q}_{X,A}$'s only depend on $\mathcal{D}$ and do not depend on π, therefore they only need to be computed
196 once and can be used throughout the rest of the policy evaluation and optimization procedure.

197 **4.1.2 Second DRO, Context Shift:** With the $\hat{Q}_{X,A}$ values estimated above for each (X, A) pair we
198 can complete the policy evaluation. Let δ_x denote the user-specified KL-radius for context distribution
199 shift, then with the computed $\hat{Q}_{X,A}$ for each (X, A) pair, we can complete the policy evaluation
200 estimation and estimate $V(\pi)$ from equation 2.

$$\hat{V}(\pi) = -\min_{\alpha_x > 0} \left\{ \alpha_x \log \sum_{X \in \mathcal{X}} P_{x_0}(x) \exp\left(\frac{-\sum_{a \in \mathcal{A}} \pi(a|X_i)\hat{Q}_{X,a}}{\alpha_x} \right) + \alpha_x \delta_x \right\} \tag{7}$$

201 We can show that when $\delta_c > 0$ and $\alpha_c^* > 0$ policy evaluation converges at rate $O(\sqrt{\log(n)/n})$:

202 **Theorem 2** (Convergence of policy evaluation). *With probability of at least $1 - \delta$ for any π:*

$$\left| V(\pi) - \hat{V}(\pi) \right| \leq \mathcal{O}\left(c\sqrt{\frac{\log(n)\log(|\mathcal{X}||\mathcal{A}|/\delta)}{n}} \right) \quad \text{where } c = \frac{\bar{\alpha}_c R_{max}^4}{\underline{\alpha}_c^4 \exp(-2R_{max}/\underline{\alpha}_c)} \tag{8}$$

203 *and $\underline{\alpha}_c > 0$ and $\bar{\alpha}_c \leq R_{max}/\delta_c$ are the minimum and maximum values of α_c respectively.*

204 *Proof sketch:* We first show our estimator for $\hat{Q}_{X,A}$ converges uniformly using a theorem from
205 stochastic convex optimization and local Lipschitz-continuity of the objective and use this with a to
206 prove the desired result. We additionally further discuss $\underline{\alpha}_c$ and $\bar{\alpha}_c$ in the appendix.

207 Additionally note that the objective inside the minimization in equation 7 is also convex and easy to
208 optimize for $\alpha_x > 0$.

209 **4.2 Policy Learning:** We now consider the optimization over policy of equation 3. Define the
210 optimal value as $\pi^* = \arg\max_\pi V(\pi)$, with optimal robust value $V^* = V(\pi^*)$. We define the
211 empirical optimal as well as $\hat{\pi}^* = \arg\max_\pi \hat{V}(\pi)$ with $\hat{V}^* = V(\hat{\pi}^*)$. We additionally define the
212 set of ϵ-optimal policies $\Pi_\epsilon^* = \{\pi : V(\pi) \geq V^* - \epsilon\}$. We then have the following statement of the
213 convergence of optimal policy and value:

214 **Theorem 3** (Convergence of Policy Learning). *With probability of at least $1 - \delta$:*

$$\left| \hat{V}^* - V^* \right| \leq \mathcal{O}\left(c\sqrt{\frac{\log(n)\log(|\mathcal{X}||\mathcal{A}|/\delta)}{n}} \right) \tag{9}$$

---

[2]Note it is also possible to provide a different $\delta_{c,(X,A)}$ for every unique (X, A), or a different $\delta_{c,A}$ per action,
however this greatly increases the hyperparameter burden on the end-user.

 Equivalently this says

$$P(\hat{\pi} \in \Pi_\epsilon^*) > 1 - \mathcal{O}\left(|\mathcal{X}||\mathcal{A}| \exp\left(-\frac{n\epsilon^2}{\log(n)c^2}\right)\right) \tag{10}$$

216 *Proof sketch:* This result builds on the previous results and local Lipschitz continuity.

217 While this policy optimization is generally non-convex, for many policy classes we can use gradient
218 ascent with multiple restarts. To perform policy optimization, we perform alternating steps of the
219 evaluation step in Section 4.1.2 and this policy optimization.

220 5 Practical Algorithm with Function Approximation

221 Our estimator for solving for the worst case reward shift value, $\hat{Q}_{X,A}$ for each context action
222 pair in our first DRO step (section 4) relies on having a sufficient number of datapoints per each
223 (X, A) to approximate $\mathbb{E}_{R \sim P_{R|X,A}}[\exp(-R/\alpha_c)] = 1/m_{xa} \sum_j \exp(-R_j/\alpha_c)$. However, in many
224 settings contexts may not be discrete, and, in these cases, each continuous context may only be
225 observed once. One approach can be to discretize the context space, however selecting the correct
226 discretization is challenging. Too coarse a discretization introduces looseness and leads to overly
227 conservative results, but too fine a discretization may not leave enough items in each bin to accurately
228 estimate $\mathbb{E}_{R \sim P_{R|X,A}}[\exp(-R/\alpha_c)]$. To handle continuous and/or large contexts spaces, instead of
229 binning we use function approximation that may not have the same convergence guarantees but as
230 we show in Section 6 it can be quite accurate and lead to better results than the baseline methods.
231 We develop an empirically stable method for estimating $\mathbb{E}_{R \sim P_{R|X,A}}[\exp(-R/\alpha_c)]$ using a Taylor
232 series approximation. The key feature of our method is that it does not require fitting the exponential
233 dependence on R and $1/\alpha_c$. In the appendix, we discuss other methods attempted, such as predicting
234 $\mathbb{E}_{R \sim P_{R|X,A}}[\exp(-R/\alpha_c)]$ directly, which resulted in unstable predictions due to the exponential.

235 **Approximating** $\mathbb{E}_{R \sim P_{R|X,A}}[\exp(-R/\alpha_c)]$**:** We can use the Taylor series expansion,
236 $\sum_{i=0}^{\infty} \frac{(1/\alpha_c)^i}{i!}\mathbb{E}[(-R)^i]$, to estimate an order m approximation. We do this by fitting a multi-output
237 function approximator, $\mathcal{F}$ to approximate the first m moments. We train $\mathcal{F}$ such that the j^{th} output
238 predicts $(-R_i)^j$ from (X_i, A_i). When trained on all the data, $\mathcal{F}[j]$ should model the j^{th} moment
239 $\mathbb{E}_{P_{R|X_i,A}}[(-R)^j]$. Let $\mathcal{D}_X$ represent the sequence of contexts in the dataset, then for every context
240 $X_i \in \mathcal{D}_X$ and every $a \in \mathcal{A}$ and any α_c, we use our approximators $\mathcal{F}_j$ to estimate the desired value:

$$\hat{\mathbb{E}}_{P_{R|X_i,a}}\left[\exp\left(\frac{-R}{\alpha_c}\right)\right] = 1 + \frac{1}{\alpha_c}\mathcal{F}_1(X_i,a) + .. + \frac{1}{\alpha_c^m}\frac{\mathcal{F}_m(X_i,a)}{m!}, \quad \text{for any } a \in \mathcal{A}, \alpha_c > 0. \tag{11}$$

241 This approximation achieves better regularity as we are no longer fitting the dependence on α_c.
242 Practically, we find order $m = 5$ can often be quite accurate. Additionally, note that while the context
243 is high dimenstional, the Taylor expansion is only for the scalar α_c.

244 **Complete Algorithm:** With our estimator $\hat{\mathbb{E}}_{P_{R|X_i,A}}[\exp(-R/\alpha_c)]$ we proceed with our method by
245 first calculating $n \times k$ values of $\hat{Q}_{X_i,a}$ for each context in the dataset and each action in the action set.
246 To do this, we iterate through $(X_i, a) \in (\mathcal{D}_X \times \mathcal{A})$ and solve the following *convex* problem in α_c:

$$\hat{Q}_{X_i,a} = -\min_{\alpha_c > 0}\{\alpha_c \log(\hat{\mathbb{E}}_{P_{R|X_i,a}}[\exp(-R/\alpha_c)]) + \alpha_c \delta_c\}. \tag{12}$$

247 We then carry out the procedure detailed in Section 4 onwards with these $\hat{Q}_{X_i,a}$. Algorithm 1 in
248 Appendix provides our full algorithm for policy evaluation and optimization, that considers both the
249 discrete binned case (Section 4) and the function approximation case just discussed.

250 6 Experiments

251 We test and analyze our algorithm empirically in three settings, including two derived from real data.
252 For all experiments, we use the practical algorithm discussed in Section 5. While our method works
253 for any policy that can be optimized, we consider learning the parameters θ of a stochastic softmax
254 linear contextual bandit policy of the form:

$$\pi_\theta(X,A) = \frac{\exp(\phi(X,A)^T\theta)}{\sum_{a \in \mathcal{A}} \exp(\phi(X,a)^T\theta)} \quad \text{where } \phi(X,A) = [X, OneHot(A)] \tag{13}$$

	Simulated	Voting	Scene
n_{total}, (n_{train}, n_{test})	$40K, (20K, 20K)$	$180K, (\sim44K, \sim12K)$	$2.407K, (\sim1.6K, \sim0.8K)$
$|\mathcal{A}|, n_{cgs}, n_{feats\ used}$	4, 4, 5	5, -, 2	6, 2, 294 (projected to 3)
Train % per cg	$(0.1, 0.4, 0.1, 0.4)$	-	$(0.7, 0.3)$
Test % per cg	Various	-	$(0.15, 0.85)$
$\pi_0(a)$	$(.1, .2, .4, .3)$	$(.56, .11, .11, .11, .11)$	$(.17, .17, .17, .17, .17, .17)$
$\mathbb{E}_{train}[R	cg, A]$	$cg_{1,3}$:$(.35, .5, .2, .14)$
$cg_{2,4}$:$(.35, .2, .5, .14)$	-
-	cg_0:$(.25, 0, 0, 0, .36, .34)$
cg_1:$(0, .3, .36, .35, .1, 0)$

Table 1: Environment/Experiment details. The first row lists the approximate number of points in the train and test splits as we randomize the exact splits across runs. 'cg' stands for *coarse group* as described in the text. The last three rows list the percentages/reward values per action in the tuple. Note for voting, we do not have coarse groups as we use a shift between cities. We use random projection to project the feature space of Scene to avoid ill-conditioned behavior.

This policy π_θ is differentiable so we optimize θ using gradient descent. For the function approximators $\mathcal{F}$ discussed in section 5, we use exponential-kernel linear regression models.

We compare against three baselines: (i) **baseline-IS**: The standard non-robust method for maximizing the reward calculated using importance sampling policy evaluation on the training data and does not consider the shift, (ii) **baseline-POEM** [Swaminathan and Joachims, 2015a] POEM improves the baseline-IS method by adding variance regularization to account for finite sample error, and (iii) **baseline-DRO** [Si et al., 2020] as mentioned throughout the text, considers the shift over the joint (context, reward) distribution as opposed to separating them.

6.1 Evaluation Domains

We first provide a brief overview of our evaluation settings and provide full descriptions in the appendix. In one setting, the voting dataset setting, we consider the case when data from one city is used to train a policy deployed in some of the other cities. In the two other settings, to construct example shifts we cluster the datapoints by one of the context covariates into what we denote as *Coarse Groups* (cg). We then consider settings where the training distribution may consist of a different composition of cgs than the deployment/testing distribution. For each environment we give details in Table 1, such as the average reward on the training set of each (cg, action) pair.

Simulated Setting: Our simulated setting has 4 cgs. To mimic potential misspecification that may occur when using real data, unknown to the designer, cg 1 and 3 ($cg_{1,3}$) are identical, as are cgs 2 and 4 ($cg_{2,4}$). Each context is composed of the cg and 4 other values sampled from uniform distributions. For each of the 4 actions and cg, each (cg, action) pair has a set of true reward parameters ϕ^*. The linear combination of ϕ^* and the contexts determine the Bernoulli parameter of the observed reward.

Scene Setting: We additionally test in a setting derived from the multiclass-supervised learning Scene classification dataset from the LibSVM [Chang and Lin, 2011] repository. We use a slightly modified version of the supervised to bandit conversion method from prior literature [Swaminathan and Joachims, 2015a, Agarwal et al., 2014]. In this method we assume we do not observe the correct label directly. Instead each label is an action and selecting the correct action/label gives positive reward, while the wrong action/label gives negative reward. We use the true label to create cgs and consider the case where we do not have access to the coarse group at test time so it cannot be used in learning the policy. This illustrates a more challenging and realistic case where there is shift in the unobserved context features. To create a context distribution shift between train and test, we sampled different proportions of datapoints from each group to put in the train distribution.

Voting Setting: The voting dataset by Gerber et al. [2008] contains data collected from a randomized controlled trial-style study testing various actions (1 control and 4 treatments) to increase voter turnout. We consider a potential real shift in the dataset by using data from one city to train a policy deployed in some of the other cities. To illustrate the worst case that could happen, we chose the training city and the deployment cities such that there is a large context differences between the cities (details in appendix). We consider the recorded binary voting outcome as our reward. Because the non-control actions require additional effort of printing and mailing a letter compared to the control (do nothing), we slightly lower the non-control action rewards by 0.09 to simulate this effort cost.

Figure 1: The dotted line 'Middle' serves as a constant horizontal reference across the two panels in plots (b-e). All plots except (f) are plotted with 95% confidence intervals shaded. Reported results and confidence intervals are averaged over 10 runs in all simulated domains, and 30 runs in Scene and Voting. **Top Row:** We plot our main results and demonstrate FDRO is able to learn more robust policies under context shift in all setting. (a) We vary the shift in the test distribution and plot results as the performance gain over baseline-IS. (b,c) We fix the train and test distributions and plot the performance at different δ/δ_x hyperparameters in Scene and Voting. **Bottom Row:** We present discussion results: (d) Results from a continuous-reward domain: FDRO is able to outperform baselines (e) A domain where the test reward distribution shifts but context does not. (f) We show performance of FDRO at multiple values of δ_c for the Scene dataset.

6.2 Results and Discussion

We use the training dataset to optimize the policies and evaluate on the test dataset. For the voting dataset we use importance sampling to evaluate the policies. For Simulated and Scene, we have the true rewards for all action and use them for evaluation. All the robust algorithms have robustness parameters. FDRO has two, the reward distribution uncertainty set radius, δ_c, the context distribution radius, δ_x. We expect many of our settings predominantly have context shifts. We leverage this information to set our FDRO parameter for reward shift to $\delta_c = 0.001$. In Figure 1f and the appendix we give performance at different values of δ_c and show performance is similar for a range of values. We show our main results in the top row of Figure 1 where we consider the effect of δ_x. Baseline-DRO has a single parameter for the KL-radius over the joint context-reward distribution ambiguity set, δ. Baseline-POEM also has a single parameter, the variance regularization strength, λ. Faury et al. [2020] prove that POEM can be equivalently viewed from a DRO formulation. So for comparison when reporting the results, we first translate λ to the corresponding DRO-radius $\delta = n\lambda^2$. We demonstrate in all three settings, FDRO is able to outperform all the baselines.

In Figure 1a, we consider the case of testing an algorithm fit with a fixed δ_x in different populations. We plot the performance gain of each algorithm over baseline-IS as the test population is increasingly different. We made this environment especially challenging for FDRO by fixing δ_x for FDRO while solving for the **best** δ for *each* different test population for baseline-DRO and baseline-POEM. We see that as expected when the test context distribution is nearly identical to the training context distribution, the robust policy learned by FDRO does not perform as well (negative reward difference). However as the test distribution differs, we see FDRO starts performing much better than the non-robust policy. Also as predicted, setting with binary rewards, empirically, the joint formulation of baseline-DRO suffers from the same issues of degeneration to learning the optimal train-distribution policy in the supervised DRO literature [Hu et al., 2018]. We additionally see that even with the

advantage of using the best parameter per test population, baseline-POEM still does not perform as
well. In Figures 1b and c. We consider fixed training and test distributions and plot performance at
different values of δ/δ_x for the voting and scene settings. We see that with increasing δ_x, FDRO can
learn robust policies that perform well on the test set. Baseline-DRO suffers from the same issue
previously discussed. The performance of baseline-POEM decreases on both distributions. As the
variance regularization weight increases, POEM is incentivized to learn low variance policies, such
as choosing low variance but low reward actions, or reducing the variance from importance sampling
by choosing a policy close to the data-collection policy, which may be suboptimal.

Discussion: Continuous Rewards and Reward Shift We focus on the common bandit setting of
binary rewards in the main result, however we also show results for a continuous rewards setting in a
simulations environment with Gaussian-distributioned rewards. In Figure 1d, we see that baseline-
DRO is able to learn good polices, however FDRO with extra structure information was able to learn
a better policy, with better train performance at the same test performance. Additionally, we explore
reward shifts. We create a new simple environment (described in the appendix) where we can easily
create a test environment with shifted rewards. We fix δ_x and sweep δ_c for FDRO and we see in
Figure 1d, both FDRO and baseline-DRO are able to handle this this case well.

Discussion: When to use FDRO vs. baseline-DRO (equivalence of solutions) One question is if the
parameters can be set such that baseline-DRO and FDRO choose the same solution, and if not when
one is beneficial over the other. To examine this question we can look at the KL-divergence chain rule
decomposition: $D_{kl}(p_0(R, X)||p(R, X)) = D_{kl}(p_0(X)||p(X)) + E_{p_0(x)}[D_{kl}(p_0(R|X)||p(R|X))]$.
Recall $D_{kl}(p_0(R, X)||p(R, X)) = \delta$, $D_{kl}(p_0(X)||p(X)) = \delta_x$, $D_{kl}(p_0(R|X)||p(R|X)) = \delta_c$. We
can see, when δ_c is the same for each context, we have $\delta = \delta_x + \delta_c$. When δ of baseline-DRO is set
to $\delta_x + \delta_c$ baseline-DRO and FDRO consider distributions the same KL distance away, with FDRO
placing additional constraints on the set of distributions searched. From the decomposition, we can
see, with additional stipulations, we can set a family of δ_x and δ_c values for FDRO to achieve the
same solution of baseline-DRO for each δ (details in appendix). However, for a given δ_x and δ_c
it is not possible to find a δ for baseline-DRO that achieves the same solution. Baseline-DRO has
less constraints and can, for example, place the shift "budget" ($\delta_x + \delta_c$) all in the rewards or all in
the contexts if that is the worst case. This causes the degenerate performance in the binary rewards
case for baseline-DRO where reward shift dominates. FDRO can set limits on how much reward
shift is considered and ensures context shift is considered, allows us to overcome this. This example
informs us that generally, if the algorithm designer would like to ensure a certain amount of reward
and context shift are considered, then it may be beneficial to use FDRO and invest the additional
effort to decompose δ between δ_x and δ_c.

Discussion: Setting the δ parameters and potential negative societal impacts One limitation
common to all DRO methods is that choosing the uncertainty set (δ) may be difficult [Rahimian
and Mehrotra, 2019]. Accounting for too large a shift may result in overly conservative policies.
However, empirically we see, our method often works for many values of δ. For example in Figure 1a,
while we may incur a small penalty if the distribution does not shift, we can learn a policy that
has much larger gains if the distribution does shift. Additionally in Figure 1f we show robustness
to δ_c. Additionally, common other approaches is to use other similar datasets or sources to derive
reasonable shifts. Another approach could be to utilize a human in the loop examination approach by
examining the worst case distribution which we can can be easily calculated for KL uncertainty sets.
We demonstrate examining the worst case shift and discuss this further in the appendix. While DRO
methods and FDRO are robust to shifts, if the shift is not as large as predicted, the policy learned
using FDRO may be overly conservative which can potentially cause negative impact in terms of
lower than necessary performance. To mitigate this risk, experimenters can carefully set δ using
methods previously mentioned.

7   Conclusion

In this work we consider the batch learning of contextual bandit policies when the deployment
distribution may shift from that of data collection. We propose a distributionally robust optimization
formulation that separates the reward and context shift. We demonstrated that our proposed estimators
converge asymptotically and then developed a practical algorithm FDRO that is able to overcome
some failure cases of prior methods and learn better performing robust policies.

References

A. Agarwal, D. Hsu, S. Kale, J. Langford, L. Li, and R. Schapire. Taming the monster: A fast and simple algorithm for contextual bandits. In *International Conference on Machine Learning*, pages 1638–1646. PMLR, 2014.

D. Bertsimas and M. Sim. The price of robustness. *Operations research*, 52(1):35–53, 2004.

S. Boyd, S. P. Boyd, and L. Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Y. Chandak, G. Theocharous, S. Shankar, M. White, S. Mahadevan, and P. Thomas. Optimizing for the future in non-stationary mdps. In *International Conference on Machine Learning*, pages 1414–1425. PMLR, 2020.

Y. Chandak, S. Niekum, B. da Silva, E. Learned-Miller, E. Brunskill, and P. S. Thomas. Universal off-policy evaluation. *Advances in Neural Information Processing Systems*, 34, 2021.

C.-C. Chang and C.-J. Lin. Libsvm: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3):1–27, 2011.

W. Chu, L. Li, L. Reyzin, and R. Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214. JMLR Workshop and Conference Proceedings, 2011.

J. Duchi and H. Namkoong. Learning models with uniform performance via distributionally robust optimization. *arXiv preprint arXiv:1810.08750*, 2018.

J. Duchi, P. Glynn, and H. Namkoong. Statistics of robust optimization: A generalized empirical likelihood approach. *arXiv preprint arXiv:1610.03425*, 2016.

J. C. Duchi, T. Hashimoto, and H. Namkoong. Distributionally robust losses against mixture covariate shifts. *Under review*, 2, 2019.

L. Faury, U. Tanielian, E. Dohmatob, E. Smirnova, and F. Vasile. Distributionally robust counterfactual risk minimization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3850–3857, 2020.

S. G. Finlayson, A. Subbaswamy, K. Singh, J. Bowers, A. Kupke, J. Zittrain, I. S. Kohane, and S. Saria. The clinician and dataset shift in artificial intelligence. *The New England journal of medicine*, 385(3):283, 2021.

C. Gelada and M. G. Bellemare. Off-policy deep reinforcement learning by bootstrapping the covariate shift. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3647–3655, 2019.

A. S. Gerber, D. P. Green, and C. W. Larimer. Social pressure and voter turnout: Evidence from a large-scale field experiment. *American political Science review*, 102(1):33–48, 2008.

S. Giguere, B. Metevier, Y. Brun, P. S. Thomas, S. Niekum, and B. C. da Silva. Fairness guarantees under demographic shift. In *International Conference on Learning Representations*, 2021.

T. Hashimoto, M. Srivastava, H. Namkoong, and P. Liang. Fairness without demographics in repeated loss minimization. In *International Conference on Machine Learning*, pages 1929–1938. PMLR, 2018.

T. Hatt, D. Tschernutter, and S. Feuerriegel. Generalizing off-policy learning under sample selection bias. *arXiv preprint arXiv:2112.01387*, 2021.

W. Hu, G. Niu, I. Sato, and M. Sugiyama. Does distributionally robust supervised learning give robust classifiers? In *International Conference on Machine Learning*, pages 2029–2037. PMLR, 2018.

Z. Hu and L. J. Hong. Kullback-leibler divergence constrained distributionally robust optimization. *Available at Optimization Online*, 2013.

E. Imani, E. Graves, and M. White. An off-policy policy gradient theorem using emphatic weightings. *Advances in Neural Information Processing Systems*, 31, 2018.

N. Jiang and J. Huang. Minimax confidence interval for off-policy evaluation and policy optimization. *arXiv preprint arXiv:2002.02081*, 2020.

N. Jiang and L. Li. Doubly robust off-policy value evaluation for reinforcement learning. In *International Conference on Machine Learning*, pages 652–661. PMLR, 2016.

N. Kallus and M. Uehara. Double reinforcement learning for efficient off-policy evaluation in markov decision processes. *Journal of Machine Learning Research*, 21(167):1–63, 2020a.

N. Kallus and M. Uehara. Statistically efficient off-policy policy gradients. In *International Conference on Machine Learning*, pages 5089–5100. PMLR, 2020b.

N. Kallus, X. Mao, K. Wang, and Z. Zhou. Doubly robust distributionally robust off-policy evaluation and learning. *arXiv preprint arXiv:2202.09667*, 2022.

M. Kato, M. Uehara, and S. Yasui. Off-policy evaluation and learning for external validity under a covariate shift. *arXiv preprint arXiv:2002.11642*, 2020.

E. S. Kim, R. S. Herbst, I. I. Wistuba, J. J. Lee, G. R. Blumenschein, A. Tsao, D. J. Stewart, M. E. Hicks, J. Erasmus, S. Gupta, et al. The battle trial: personalizing therapy for lung cancer. *Cancer discovery*, 1(1):44–53, 2011.

P. W. Koh, S. Sagawa, H. Marklund, S. M. Xie, M. Zhang, A. Balsubramani, W. Hu, M. Yasunaga, R. L. Phillips, I. Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. In *International Conference on Machine Learning*, pages 5637–5664. PMLR, 2021.

Q. Liu, L. Li, Z. Tang, and D. Zhou. Breaking the curse of horizon: Infinite-horizon off-policy estimation. *arXiv preprint arXiv:1810.12429*, 2018.

Y. Liu, A. Swaminathan, A. Agarwal, and E. Brunskill. Off-policy policy gradient with stationary distribution correction. In *Uncertainty in Artificial Intelligence*, pages 1180–1190. PMLR, 2020.

P. Michel, T. Hashimoto, and G. Neubig. Distributionally robust models with parametric likelihood ratios. *arXiv preprint arXiv:2204.06340*, 2022.

W. Mo, Z. Qi, and Y. Liu. Learning optimal distributionally robust individualized treatment rules. *Journal of the American Statistical Association*, 116(534):659–674, 2021.

H. Namkoong and J. C. Duchi. Stochastic gradient methods for distributionally robust optimization with f-divergences. *Advances in neural information processing systems*, 29, 2016.

Y. Oren, S. Sagawa, T. B. Hashimoto, and P. Liang. Distributionally robust language modeling. *arXiv preprint arXiv:1909.02060*, 2019.

D. Precup. Eligibility traces for off-policy policy evaluation. *Computer Science Department Faculty Publication Series*, page 80, 2000.

C. Qin and D. Russo. On adaptivity and confounding in contextual bandit experiments. In *NeurIPS 2021 Workshop on Distribution Shifts: Connecting Methods and Applications*, 2021.

H. Rahimian and S. Mehrotra. Distributionally robust optimization: A review. *arXiv preprint arXiv:1908.05659*, 2019.

S. Sagawa, P. W. Koh, T. B. Hashimoto, and P. Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. *arXiv preprint arXiv:1911.08731*, 2019.

O. Sakhi, L. Faury, and F. Vasile. Improving offline contextual bandits with distributional robustness. *arXiv preprint arXiv:2011.06835*, 2020.

S. Shalev-Shwartz, O. Shamir, N. Srebro, and K. Sridharan. Stochastic convex optimization. In *COLT*, volume 2, page 5, 2009.

A. Shapiro. Distributionally robust stochastic programming. *SIAM Journal on Optimization*, 27(4): 2258–2275, 2017.

N. Si, F. Zhang, Z. Zhou, and J. Blanchet. Distributional robust batch contextual bandits. *arXiv preprint arXiv:2006.05630*, 2020.

H. Singh, S. Joshi, F. Doshi-Velez, and H. Lakkaraju. Learning under adversarial and interventional shifts. *arXiv preprint arXiv:2103.15933*, 2021.

A. Strehl, J. Langford, L. Li, and S. M. Kakade. Learning from logged implicit exploration data. *Advances in neural information processing systems*, 23, 2010.

A. Subbaswamy, P. Schulam, and S. Saria. Preventing failures due to dataset shift: Learning predictive models that transport. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3118–3127. PMLR, 2019.

A. Swaminathan and T. Joachims. Batch learning from logged bandit feedback through counterfactual risk minimization. *The Journal of Machine Learning Research*, 16(1):1731–1755, 2015a.

A. Swaminathan and T. Joachims. The self-normalized estimator for counterfactual learning. *advances in neural information processing systems*, 28, 2015b.

P. Thomas and E. Brunskill. Data-efficient off-policy policy evaluation for reinforcement learning. In *International Conference on Machine Learning*, pages 2139–2148, 2016a.

P. S. Thomas and E. Brunskill. Magical policy search: Data efficient reinforcement learning with guarantees of global optimality. In *European workshop on reinforcement learning*, 2016b.

P. S. Thomas, G. Theocharous, M. Ghavamzadeh, I. Durugkar, and E. Brunskill. Predictive off-policy policy evaluation for nonstationary decision problems, with applications to digital marketing. In *Twenty-Ninth IAAI Conference*, 2017.

A. Xie, J. Harrison, and C. Finn. Deep reinforcement learning amidst lifelong non-stationarity. *arXiv preprint arXiv:2006.10701*, 2020.

M. Yang, O. Nachum, B. Dai, L. Li, and D. Schuurmans. Off-policy evaluation via the regularized lagrangian. *arXiv preprint arXiv:2007.03438*, 2020.