INSTANCE–SPECIFIC AUGMENTATION: CAPTURING LOCAL INVARIANCES

ABSTRACT

We introduce *InstaAug*, a method for automatically learning input-specific augmentations from data. Previous data augmentation methods have generally assumed independence between the original input and the transformation applied to that input. This can be highly restrictive, as the invariances that the augmentations are based on are themselves often highly input dependent; e.g., we can change a leaf from green to yellow while maintaining its label, but not a lime. InstaAug instead allows for input dependency by introducing an *invariance module* that maps inputs to tailored transformation distributions. It can be simultaneously trained alongside the downstream model in a fully end-to-end manner, or separately learned for a pre-trained model. We empirically demonstrate that InstaAug learns meaningful input-dependent augmentations for a wide range of transformation classes, which in turn provides better performance on both supervised and self-supervised tasks.

1 INTRODUCTION

Data augmentation is an important tool in deep learning (Shorten & Khoshgoftaar, 2019). It allows one to incorporate inductive biases and invariances into models (Chen et al., 2019; Lyle et al., 2020), providing a highly effective regularization technique that aids generalization (Goodfellow et al., 2016). It has proved particularly successful for computer vision tasks, forming an essential component of many modern supervised (Perez & Wang, 2017; Krizhevsky et al., 2012; Cubuk et al., 2020; Mikołajczyk & Grochowski, 2018) and self-supervised (Bachman et al., 2019; Chen et al., 2020; Tian et al., 2020; Foster et al., 2021) approaches.

Algorithmically, data augmentations apply a *random transformation* $\tau : \mathcal{X} \to \mathcal{X}, \tau \sim p(\tau)$, to each input data point $\mathbf{x} \in \mathcal{X}$, before feeding this *augmented* data into the downstream model. These transformations are resampled each time the data point is used (e.g. at each training epoch), effectively populating the training set with additional samples. Augmentation is also sometimes used at test time by ensembling predictions from multiple transformations of the input. A particular augmentation is defined by the choice of the *transformation distribution* $p(\tau)$, whose construction thus forms the key design choice. Good transformation distributions induce substantial and wide-ranging changes to the input, while preserving the information relevant to the task at hand.

Data augmentation necessarily relies on exploiting problem-specific expertise: though aspects of $p(\tau)$ can be learned from data (Benton et al., 2020), trying to learn $p(\tau)$ from the set of all possible transformation distributions is not only unrealistic, but actively at odds with the core motivations of introducing inductive biases and capturing invariances. One, therefore, restricts τ to transformations that reflect how we desire our model to generalize, such as cropping and color jitter for image data.

Current approaches (Cubuk et al., 2018; Lim et al., 2019; Benton et al., 2020) are generally limited to learning augmentations where the transformation is sampled independently from the input it is applied to, such that $p(\tau)$ has no dependence on $\mathbf{x}$. This means that they are only able to learn *global invariances*, severely limiting their flexibility and potential impact. For example, when using color jittering, changing the color of a leaf from yellow to green would likely preserve its label, but the same transformation would change a lemon to a lime (see Figure 1b). This transformation cannot be usefully applied as a global augmentation, even though it is a useful invariance for the *specific input instance* of a leaf. Similar examples regularly occur for other transformations, as shown in Figure 1.

To address this shortfall, we introduce InstaAug, a new approach that allows one to learn *instance-specific* augmentations that encapsulate *local* invariances of the underlying data generating process,

(a) Rotation   (b) Color jittering   (c) Cropping

Figure 1: Different inputs require different augmentations. In (a), the digit '0' is invariant to any rotation, but rotating the digit '6' by more $90°$ makes it a '9'. In (b), a similar phenomenon is observed for color jittering applied to a leaf and a lemon/lime. The red dashed lines in (a) and (b) are boundaries between different classes. In (c), the same effect is shown for cropping. Solid rectangles represent the patches that preserve the labels of the original images ([left] grass, [right] cattle), while dashed rectangles represent patches with different labels to the original images.

that is invariances specific to a particular region of the input space. InstaAug is based on using a transformation distribution of the form $p(\tau; \phi(\mathbf{x}))$, where ϕ is a deep neural network that maps inputs to transformation distribution parameters. We refer to ϕ as an *invariance module*. It can be trained simultaneously with the downstream model in a fully end-to-end manner, or using a fixed pre-trained model. Both cases only require access to training data and a single objective function that minimizes the training error while maintaining augmentation diversity. As such, *InstaAug* allows one to directly learn powerful and general augmentations, without requiring access to additional annotations.

We evaluate InstaAug in both supervised and self-supervised settings, focusing on image classification and contrastive learning respectively. Our experimental results show that InstaAug is able to uncover meaningful invariances that are consistent with human cognition, and improve model performance for various tasks compared with global augmentations. While we primarily focus on the case where the invariance module is trained alongside the downstream model (to allow data augmentation during training), we find that InstaAug can also provide substantial performance gains when used as a mechanism for learning test-time augmentations for large pre-trained models.

2 BACKGROUND

Data augmentation methods operate as a wrapper algorithm around some downstream model, f, randomly transforming the inputs $\mathbf{x} \in \mathcal{X}$ before they are passed to the model. The outputs of the augmented model are given by $f(\tau(\mathbf{x}))$, where $\tau : \mathcal{X} \mapsto \mathcal{X}$ represents the transformation, sampled from some transformation distribution $p(\tau)$. The aim of this augmentation is to instil inductive biases into the learned model, leading to improved generalization by capturing invariances of the problem. It can be used both during training to provide additional synthetic training data, and/or at test-time, where ensembling the predictions from multiple transformations can provide a useful regularization that often improves performance (Shanmugam et al., 2021).

Some approaches look to learn aspects of the augmentation (Cubuk et al., 2018; 2020; Lim et al., 2019; Ho et al., 2019; Hataya et al., 2020; Li et al., 2020; Zheng et al., 2022). These approaches can be viewed as learning parameters of $p(\tau)$, helping to automate its construction and tuning. Of particular relevance, Benton et al. (2020) provide a mechanism for learning augmentations using a simple end-to-end training scheme, where the parameters of the downstream model and transformation distribution are learned simultaneously using the (empirical) risk minimization

$$\min_{f,\theta} \quad \mathbb{E}_{\mathbf{x},y \sim p_{\text{data}}} \left[\mathbb{E}_{\tau \sim p_\theta(\tau)} \left[\mathcal{L}(f(\tau(\mathbf{x})), y) \right] \right] + \lambda \mathbb{R}(\theta), \tag{1}$$

where $\mathcal{L}$ is a loss function and $\lambda \mathbb{R}(\theta)$ is a regularization term that encourages large transformations.

All of these approaches can be thought of as *global* augmentation schemes, in that transformations are sampled independently to the input. For an unrestricted, universal, class of transformations, this assumption can be justified through the noise outsourcing lemma (Kallenberg & Kallenberg, 1997): any conditional distribution $Y|X = x$ can be expressed as a deterministic function $g : \mathcal{X} \times \mathbb{R}^n \to \mathcal{Y}$ of the input and some independent noise $\varepsilon \sim \mathcal{N}(0, I)$. Thus, using reparameterization, the dependency on $\mathbf{x}$ can, in principle, be entirely dealt with by the transformation itself. However, in practice, the transformation class must be restricted to provide the desired inductive biases, meaning this result no longer holds and so the independence assumption can cause severe restrictions. For example, sampling rotations independently to the input is equivalent to the unrealistic assumption that the labels of all images $\mathbf{x}$ are invariant to the same range of angles (*cf.* Figure 1a).

3 INSTANCE-SPECIFIC AUGMENTATION: CAPTURING LOCAL INVARIANCES

In order to remedy the problems of global augmentations, we propose InstaAug. InstaAug learns an *input dependent* distribution $p(\tau; \phi(\mathbf{x}))$ of information-preserving transformations that actively makes use of the input $\mathbf{x}$ via the *invariance module* ϕ, as opposed to learning a global transformation distribution $p_\theta(\tau)$. This generalizes the hypothesis class of transformation distributions, and significantly increases the flexibility and expressivity of the augmentations we can learn, without undermining our ability to carefully control the inductive biases that are imparted. It can also informally be viewed as a mechanism for learning invariances which are local to the specific input.

We train InstaAug so that the augmentations fulfill two properties. First, the transformations should preserve the information in $\mathbf{x}$ that is necessary for the task at hand. For example, in classification, transformations must preserve sufficient information to correctly classify $\tau(\mathbf{x})$. Second, the set of transformations needs to have sufficient 'diversity' to effectively augment the data. We quantify diversity as the entropy of the transformation distribution $p(\tau; \phi(\mathbf{x}))$. For simplicity, we describe InstaAug on the task of classification in the remainder of this section.

3.1 MODEL STRUCTURE

InstaAug forms a simple plug-in module between the input $\mathbf{x}$ and the classifier f, as shown in Figure 2. We assume a parametric family of distributions $p(\tau; \cdot)$ over some transformation space. Given an input $\mathbf{x}$, the invariance module ϕ, which is a trainable neural network, predicts the parameters $\phi(\mathbf{x})$ of the transformation distribution. During training, we *sample* a transformation $\tau \sim p(\tau; \phi(\mathbf{x}))$, which is

Figure 2: Summary of InstaAug. The invariance module ϕ and the classifier f contain trainable parameters.

applied to $\mathbf{x}$ to generate an augmented sample $\tau(\mathbf{x})$, before feeding this into the classifier f. Taking the example of rotations as the space of transformations, the invariance module outputs $\phi(\mathbf{x}) = (\theta_{\min}, \theta_{\max})$ which represents the maximum and minimum values of a uniform distribution over the angle θ of 2D rotations. We then rotate the input image $\mathbf{x}$ by an angle uniformly sampled from the predicted interval: $\mathbf{x} \mapsto \tau(\mathbf{x}) = R(\theta) \cdot \mathbf{x}$, with $\theta \sim \mathcal{U}(\theta_{\min}, \theta_{\max})$.

3.2 TRAINING

Good augmentations should induce substantial changes to the input $\mathbf{x}$ while providing all necessary information of the task at hand, thereby capturing the maximum possible invariance. Figure 3a illustrates the tension between these two objectives experienced by global augmentation schemes. Wider-ranging transformations are generally beneficial for generalization, but 'excessive' transformations will generate samples that will be incorrectly classified. In Figure 3a we see this in the red area, where the augmentations for a pair of data points have started to overlap, creating ambiguity and inevitably misclassifications. Using instance-specific augmentations (Figure 3b) allows for a better trade-off of these needs. However, to achieve this we need our objective to encourage diversity in augmentations, not

(a) Global augmentation   (b) InstaAug

Figure 3: InstaAug learns more diverse augmentations that also preserve labels compared to global augmentations. ★ and ▲ are samples from two different classes. Blue and green shades represent label-preserving augmentations for each class. In (a), the upper ★ should be further augmented, but some of the augmented samples for the lower ★ are already over-augmented and indistinguishable from another class (see the red intersection). InstaAug solves this problem by learning a different augmentation for each instance, as shown in (b).

just low training error. It should also let the level of diversity vary between inputs, as some points will be able to support larger transformations than others.

Our chosen approach is to minimize a conventional expected cross-entropy loss, while placing a hard constraint on the average entropy of the transformations, $\mathbb{E}_{\mathbf{x} \sim p_{\text{data}}}[\mathbb{H}[p(\tau; \phi(\mathbf{x}))]]$. By appropriately parameterizing $p(\tau; \phi(\mathbf{x}))$ (see Section 3.3), we can write down its entropy in closed form. We can then formulate the problem as the following constrained optimization problem:

$$\min_{f, \phi} \quad \mathbb{E}_{\mathbf{x}, y \sim p_{\text{data}}}\left[\mathbb{E}_{\tau \sim p(\tau; \phi(\mathbf{x}))}[\mathcal{L}(f(\tau(\mathbf{x})), y)]\right], \tag{2a}$$

$$\text{s.t.} \quad \mathbb{E}_{\mathbf{x}, y \sim p_{\text{data}}}[\mathbb{H}[p(\tau; \phi(\mathbf{x}))]] \in [\mathbf{H}_{\min}, \mathbf{H}_{\max}], \tag{2b}$$

where $\mathcal{L}$ is the cross-entropy loss. Here the lower bound avoids $p(\tau; \phi(\mathbf{x}))$ degenerating to a delta function at the identity. The upper bound prevents $p(\tau; \phi(\mathbf{x}))$ exploding at the start of training when the classifier is weak: without this we empirically find that the augmented samples from different classes tend to overlap in the initial phase of training, hindering the training of the classifier f. $\mathbf{H}_{\min}$ and $\mathbf{H}_{\max}$ are hyper-parameters reflecting human preference for augmentation diversity.

The Lagrangian function, $\mathbb{E}_{\mathbf{x}, y \sim p_{\text{data}}}\left[\mathbb{E}_{\tau \sim p(\tau; \phi(\mathbf{x}))}[\mathcal{L}(f(\tau(\mathbf{x})), y)]\right] - \lambda \mathbb{E}_{\mathbf{x}, y \sim p_{\text{data}}}[\mathbb{H}[p(\tau; \phi(\mathbf{x}))]]$, can be used to solve this constrained optimization, where λ is the Lagrangian multiplier. In practice, we initialize λ with a small positive value, and increase (decrease) λ when the average entropy drops below $\mathbf{H}_{\min}$ (exceeds $\mathbf{H}_{\max}$). The invariance module and downstream model can thus be trained simultaneously using end-to-end gradient descent, utilizing the reparameterization trick to deal with the stochasticity of τ when possible (Kingma & Welling, 2014), and the REINFORCE estimator (Williams, 1992) otherwise. The approach can also be extended to regression or self-supervised learning by substituting the loss function $\mathcal{L}$ (*cf.* Appendix B).

3.3 PARAMETERIZATION OF AUGMENTATIONS

We focus on parameterizing transformations that are frequently used in computer vision, though our framework can easily be extended to other domains. Due to the varied characteristics of different image transformations, we design two different parameterization methods for $p(\tau; \phi(\mathbf{x}))$.

Uniform parameterization. For transformations acting on the whole image, such as rotation or color jittering, we find that a uniform distribution is suitable for parameterizing $p(\tau; \phi(\mathbf{x}))$, such that $\phi(\mathbf{x}) = (\theta_{\min}, \theta_{\max})$. To compose multiple transformations τ_k (such as hue, saturation and brightness in color jittering), we further make a mean-field assumption that the joint distribution $p(\tau_1, \ldots, \tau_K; \phi(\mathbf{x}))$ factorises along each transformation τ_k.

Location-related parameterization. It is less straightforward to parameterize local transformations such as cropping. Using independent uniform distributions on the centers and sizes of the crop has two failure modes. First, the distribution of 'good' patches may be multi-modal, since important information may exist in different parts of an image. Second, the center coordinates and patch sizes are highly correlated, which goes against a mean-field assumption. For example, smaller sizes are sufficient for patches around the head of an animal, but not around its torso.

To get around these issues, our approach for cropping transformations is to use a categorical distribution over a large number of fixed crops of various sizes. We parameterize this distribution using a CNN where the logits are given by the activations at the intermediary layers of the network and the crops are the corresponding receptive fields of those activations, as shown in Figure 4. This parametrization proved more effective than simply taking the logits as an output of a conventional network, likely due to greater parameter sharing between related patches. We note that this parameterization can be directly extended to other local transformations, such as masking, local blurring, pixel-wise perturbation, and local color jittering.

Figure 4: Location-related parameterization of crops by a CNN. The shaded area (bottom right) shows a simplified 3-layer CNN, and squares represent activations at different convolutional layers. Each activation corresponds to the patch in the input image (shown in the same color) given by the activation's receptive field. The value of the activation gives the unnormalized log probability for that patch.

3.4 Test-time augmentation

Besides augmenting data during training, the learned invariance can also be applied to test-time augmentation. Given a test image $\mathbf{x}$, we sample n different transformations τ_i from $p(\tau; \phi(\mathbf{x}))$ and apply them to $\mathbf{x}$ to generate n different views $\tau_i(\mathbf{x})$. After feeding these views to the classifier, f, we use the mean logit $\frac{1}{n} \sum_{i=1}^{n} f(\tau_i(\mathbf{x}))$ to predict $\mathbf{x}$'s label. When only learning invariance for test-time augmentation, InstaAug can be trained with a fixed pre-trained classifier at a lower computation cost.

4 Related Work

Hard-coded invariance. Much recent work has been devoted to hard-coding global invariance in neural networks. For example, various models have been designed to be invariant to translation (Chaman & Dokmanic, 2021; Zhang, 2019), rotation (Worrall et al., 2017; Zhou et al., 2017; Marcos et al., 2017), scaling (Worrall & Welling, 2019; Sosnovik et al., 2019) or other group actions (Cohen & Welling, 2016; Xu et al., 2021). Unfortunately, they require the set of invariant transformations to be closed under composition, leaving out many practical transformations that do not form a group.

Learning augmentations. There have been numerous prior works that automatically learn *global* augmentations and invariance from data. AutoAugment (Cubuk et al., 2018) uses reinforcement learning to find augmentation strategies that increase accuracy on a separate validation set. Various follow-up works have improved its efficiency and/or performance (Lim et al., 2019; Ho et al., 2019; Hataya et al., 2020; Li et al., 2020; Cubuk et al., 2020; Tang et al., 2019; Zheng et al., 2022). A small number of works have further looked to learn augmentation policies that have some dependency on the input or just the class label (Zhou et al., 2021; Cheung & Yeung, 2022). These approaches focus on choosing *which type(s)* of transformation to apply from a fixed list—e.g. choosing from crop, blur, or color jitter—which may include a small number of discrete options for transformation strength. By comparison, InstaAug keeps the type of transformation fixed and learns instance-specific parameter for the transform distribution, such as the positions and sizes of patches for cropping. In principle, it should be possible to combine these complementary approaches with InstaAug, though we note they require a separate validation dataset and cannot be used in unsupervised settings, unlike InstaAug.

Other related work. The spatial transformer (Jaderberg et al., 2015) aims to learn instance-specific transformations, but only applies a single transformation to each input rather than a distribution of transformations, making it distinct from data augmentation. Luo et al. (2020) and Kim et al. (2020) both also learn instance-specific augmentations. However, the latter consider only test-time augmentation, while the former introduces an approach that is highly specialized to test recognition and cannot be applied in more general settings we consider. Tamkin et al. (2020) and (Chen et al., 2021) both utilize adversarial augmentations to increase robustness. Zhou et al. (2020) learn symmetries shared across several datasets through a meta-learning scheme.

5 Supervised Learning Experiments

We now conduct several image classification experiments to assess InstaAug's learning of instance-specific augmentations using rotation, color jittering, and cropping. Full details are given in Appendix C.

5.1 Rotated 2D images

We first consider a toy synthetic dataset proposed in Benton et al. (2020). The dataset contains four categories, (1) upright Mario; (2) upside-down Mario; (3) upright Iggy; and (4) upside-down Iggy. Each of the four base images is randomly rotated in the interval of $[-\pi/4, \pi/4]$ to form the training dataset. The task is to predict the correct character (Mario

(a) Augerino   (b) InstaAug (Ours)

Figure 5: Learned invariances for the Mario and Iggy dataset. The blue arcs show the training data range, while the green arcs show the learned transformation distributions for some examples.

vs Iggy) and the orientation (up vs down). We assess whether InstaAug is able to learn the 'best' rotation range for each sample—i.e. the maximum range that avoids 'up' and 'down' classes from overlapping.

Figure 5 shows that InstaAug almost fully recovers the broadest range of rotations for each image while preserving labels, while Augerino only learns a subset of these ranges. This can be most easily seen by the fact that the transformation distributions (shown in green) always extend to very close to the true class boundary for InstaAug, but not for Augerino. These gains are because Augerino learns a *single* global augmentation distribution shared across all images (note the shared transformation distribution arcs), which are inevitably limited for any given input.

5.2 CROPPING

We now move to more realistic images and to the most common and effective form of image augmentation: cropping. We first evaluate the performance of jointly training InstaAug and the classifier on Tiny-Imagenet (TinyIN, 64×64), as it inherits the image complexity of ImageNet whilst being within our computational budget. TinyIN is a standard testbed for data augmentations that contains 100k images divided into 200 classes.

We benchmark InstaAug alongside several augmentation baselines, including Augerino, no augmentation, and random resized cropping (random augmentation). Random cropping uniformly samples patch sizes and then randomly selects a patch inside the image. Since the effect of cropping crucially relies on scales of patches, we carefully tune this baseline by sweeping over all possible scale intervals between $[0, 1]$ with a stride of 0.1. We further compare to other prior works that have obtained competitive results on TinyIN (Ramé et al., 2021; Yun et al., 2019; Zhang et al., 2018). In order to ablate the effects of input-dependency and location-related parameterization on InstaAug, we additionally assess the performance of *InstaAug (without LRP)* which relies on the same uniform parameterization as Augerino rather than our location-related parametrization (LRP, described in Figure 4), and *InstaAug (without input)* that uses the LRP and general InstaAug setup, but shares the transformation distribution across all inputs rather than learning an input-specific augmentation. Following prior works, we choose the PreActResNet-18 architecture (He et al., 2016b) with width $= 1$ as the classifier for all methods.

Table 1 shows the top-1 accuracy for each method. In agreement with prior works, we find that random cropping increases top-1 accuracy by 9.4% over no augmentation, which is achieved where cropping scale $= [0.1, 1]$. InstaAug outperforms random cropping and its own global version without input by 1.5% and 2.8% respectively, highlighting the effect of learning instance-specific augmentation. We also find model performance is generally not sensitive to the choice of the entropy interval $[\mathrm{H}_{\min}, \mathrm{H}_{\max}]$ in InstaAug. Any subinterval of $[3, 4]$ yields the best accuracy, which can be easily found by hyper-parameter sweeping. Intervals below 3 or above 4 would lead to performance degradation because of insufficient or excessive augmentations. We empirically observed that methods with mean-field uniform parameterization (including Augerino and InstaAug without LRP) are easily stuck at local minima with low cropping diversity, leading to similar performance as *no augmentation*. It shows the importance of location-related parameterization on cropping. Meanwhile, instance dependence allows InstaAug to outperform carefully tuned random augmentation.

Table 1: InstaAug improves generalization on Tiny-ImageNet by learning instance-specific cropping. 'Instance' and 'LRP' refer respectively to 'instance-specific' and 'location-related parameterization'. InstaAug, Augerino and the random augmentation baseline, leverage test-time augmentation in probability space over 50 augmentations. Statistics are computed over 10 runs, except for MixMo, CutMix and Mixup, whose results are from Ramé et al. (2021). Other learnable augmentation methods are actually learning the size ranges of cropping. We leave their results out because we are already performing this learning in the random cropping results through our hyperparameter tuning.

Method	Instance	LRP	Accuracy (%)
MixMo (Ramé et al., 2021)	—	—	64.80
CutMix (Yun et al., 2019)	—	—	65.09
Mixup (Zhang et al., 2018)	—	—	63.74
No augmentation	✗	✗	$55.06_{\pm 0.10}$
Random crop	✗	✗	$64.49_{\pm 0.12}$
Augerino (Benton et al., 2020)	✗	✗	$55.02_{\pm 0.29}$
InstaAug (without LRP)	✓	✗	$55.39_{\pm 0.19}$
InstaAug (without input)	✗	✓	$63.20_{\pm 0.12}$
InstaAug	✓	✓	$\mathbf{66.02}_{\pm 0.18}$

(A) Random	(B) InstaAug (without input)			(C) InstaAug		
(a)	(b)	(c)	(d)	(e)	(f)	(g)

Figure 6: InstaAug (C) learns more sensible crops compared to random (A) and learned global (B) augmentations. Columns (a, b, e) show examples of sampled crops, with red edges indicating higher probability. Columns (c, f) show density maps for the crop centres, with brighter color meaning higher probability. Columns (d, g) give the proportion of crops (red) above a particular size threshold, showing that InstaAug produces fewer large crops.

Figure 6 shows example crops and learned transformation distributions for InstaAug, random crops, and a global augmentation scheme (InstaAug without input). We see that InstaAug is able to learn a cropping scheme that focuses on the key aspect of the input image, while the baselines cannot.

5.3 APPLYING INSTAAUG TO A FIXED CLASSIFIER

InstaAug can also be used to learn suitable augmentations for a fixed pre-trained classifier. This can most notably be useful as a means to learn test-time augmentations. As the invariance module is itself only a small network, this can be done relatively cheaply, even when the dataset and downstream model are very large. We exploit this on the larger Imagenet dataset (224×224) (Deng et al., 2009).

To learn the augmentation module, we solve the constrained optimization problem in Section 3.2 with respect to the parameters of the invariance module ϕ, while keeping the classifier f fixed. Note here that we are simply discovering invariances, without affecting the training of the classifier. The learned augmentation module is then applied at test-time to enhance the performance of the fixed classifier, as per Section 3.4. We train ϕ using a pre-trained ResNet-50 (He et al., 2016a) from Wightman (2019).

As shown in Table 2, test time augmentation with random cropping, AutoAugment (Cubuk et al., 2018) or Fast AutoAugment (Lim et al., 2019) is detrimental to performance, whereas InstaAug increases accuracy by 0.75%. In order to evaluate the generalization performance of our learned augmentation module, we further apply the augmentation trained on ResNet-50 to two different models: ResNet-18 (He et al., 2016a) and XCiT (Ali et al., 2021). We find that the learned augmentations transfer very effectively to these different models, which implies that the local invariances InstaAug learns reflect the natural invariances of the underlying classification problem, rather than being specific to the model that was used to train the augmentation module.

Table 2: InstaAug boosts the test accuracy (%) with test-time augmentation on Imagenet. Invariance modules learned on ResNet-50 can also be directly applied to other models such as ResNet-18 and XCiT to improve generalization without fine-tuning. By contrast, we see that global augmentation schemes are actually detrimental to test-time augmentation.

Method	#Sample	ResNet50	ResNet18	XCiT
No aug	1	80.43	69.73	86.34
Random crop	4	78.45±0.04	66.13±0.04	82.05±0.01
AutoAug	4	77.84±0.05	59.50±0.01	81.40±0.00
FastAutoAug	4	77.87±0.06	61.43±0.02	81.42±0.01
InstaAug	4	**80.92**±0.04	**70.59**±0.05	**86.43**±0.04
Random crop	10	79.60±0.01	67.87±0.01	82.84±0.00
AutoAug	10	79.20±0.04	63.96±0.03	82.43±0.02
FastAutoAug	10	79.28±0.01	65.65±0.02	82.45±0.02
InstaAug	10	**81.18**±0.02	**70.96**±0.03	**86.47**±0.02

5.4 COLOR JITTERING ON TEXTURES

Color jittering is another important type of data augmentation, which can help models generalize to different lighting conditions. We benchmark on the texture classification dataset RawFooT (Bianco et al., 2017), a common testbed for color-related tasks. RawFooT includes 68 different samples of raw food and each sample has an image taken under each of 46 different lighting conditions (see Figure C.1 for some examples). We crop the original images to create the train set and test set. For each original image with a resolution of 800×800, we randomly sample 200 different 200×200 patches in the upper half as training images. The same procedure is taken on the lower half to produce test images, giving a train set and a test set for each different lighting condition. To evaluate the generalization ability of each method to a broader range of lighting conditions, we evenly mix test images from all lighting conditions to form a general test set, while controlling the lighting conditions present during training.

We first train on a single lighting condition D45 (4500K, daylight) resembling natural light. Table 3 shows that InstaAug outperforms all baselines with and without test-time augmentation. In this task, we find that Augerino (with relaxed symmetry restrictions on learned intervals) underperforms random augmentation because its parameters ϕ are often stuck in a neighborhood around their initial values. We believe this is due to the conservative nature of using global augmentations (*cf.* Figure 3), where even a small change in the parameters may largely increase the training loss, which prohibits wide-ranging augmentations.

Table 3: InstaAug achieves higher general accuracy than baseline methods when trained on D45 (Daylight, 4500K).

Method	Test aug?	Accuracy (%)
No aug	✗	$72.87_{\pm 0.10}$
Random aug	✗	$79.99_{\pm 0.13}$
Augerino	✗	$78.97_{\pm 0.10}$
InstaAug	✗	$\mathbf{81.11}_{\pm 0.20}$
Random aug	✓	$80.55_{\pm 0.16}$
Augerino	✓	$79.34_{\pm 0.14}$
InstaAug	✓	$\mathbf{81.35}_{\pm 0.19}$

We also compare in-distribution and out-of-distribution generalization by splitting the 46 test sets into two groups, according to the similarity of their lighting conditions to D45—see Appendix C.2 for the details on the splitting method. In Figure 7 we can see that above a certain in-distribution performance, there exists a trade-off for random augmentation between in-distribution accuracy and out-of-distribution generalization, controlled through the hyperparameter settings. InstaAug, meanwhile, delivers higher out-of-distribution performance than any of the hyperparameter configurations, while also simultaneously giving better in-distribution accuracy to the vast majority of them as well.

We can further vary the difficulty of the classification task by using different numbers of lighting conditions in the training data. In Table 4, we randomly select a set number of lighting conditions to use as the training set for each baseline. As expected, the accuracy increases with the number of lighting conditions for all meth-

Figure 7: In-distribution and out-of-distribution test accuracy for models trained on RawFooT D45. The round dots are random augmentation with different hyperparameter settings. The colors of dots change from yellow to red as hue jittering increases; more saturated dots indicate higher saturation jittering; larger dots mean higher brightness jittering. Each thick line connects dots with the same hue and brightness jitter and thin lines link dots with the same hue and saturation jitter.

ods. However, the effect of random augmentation saturates: it performs similarly to no augmentation with 8 lighting conditions. By contrast, InstaAug always provides improvements. In Appendix C, we show that these gains come at very little computational overhead at both train and test time.

6 INSTAAUG FOR CONTRASTIVE LEARNING

Contrastive learning aims to learn features that are approximately invariant to certain augmentations. Typical contrastive learning methods, such as SimCLR (Chen et al., 2020; Ermolov et al., 2021),

Table 4: InstaAug significantly outperforms baseline methods in general test accuracy (%) on different difficulty levels. For each difficulty level, we randomly sample lighting conditions used for training and repeat each experiment 10 times. Test time augmentation is included for random and InstaAug.

Method / #Lighting conditions for training	1	2	4	8
No aug	$68.5_{\pm 2.6}$	$78.1_{\pm 1.8}$	$84.8_{\pm 0.7}$	$87.8_{\pm 0.5}$
Random augmentation	$72.7_{\pm 2.7}$	$80.8_{\pm 1.3}$	$85.9_{\pm 0.6}$	$87.3_{\pm 0.3}$
InstaAug	$\mathbf{76.0}_{\pm 2.5}$	$\mathbf{83.6}_{\pm 1.1}$	$\mathbf{88.2}_{\pm 0.5}$	$\mathbf{89.6}_{\pm 0.3}$

first sample two independent transformations, $\tau_1, \tau_2 \sim p(\tau)$, and apply them to an input image $\mathbf{x}$, generating two views $\mathbf{x}_1$ and $\mathbf{x}_2$. They then feed the transformed images to a neural encoder f, which is trained to maximize the similarity between $f(\mathbf{x}_1)$ and $f(\mathbf{x}_2)$, measured with a contrastive loss.

As the choice of augmentations directly influences the learned invariance of the encoder, it is a crucial ingredient of contrastive learning (Bachman et al., 2019; Chen et al., 2020; Tian et al., 2020). However, existing schemes use global augmentations which often introduce unrealistic assumptions. For example, if there are multiple entities in an image, such as grass and cattle in Figure 1c, random cropping will pull features for different entities closer to each other. Consequently, we propose InstaAug as a more flexible instance-specific augmentation method for contrastive learning.

Applying InstaAug to contrastive learning is similar to the supervised case shown in Section 3. The main difference is, given an input $\mathbf{x}$, we sample two τ independently from the input-specific distribution $p(\tau; \phi(\mathbf{x}))$, before they are applied to $\mathbf{x}$. The training objective is correspondingly changed to minimizing the contrastive loss while keeping the diversity in a reasonable range.

(a)   (b)   (c)

Figure 8: Some examples (bird houses) of learned cropping in contrastive learning.

We again consider TinyIN and evaluate three methods: InstaAug, InstaAug (without input), and random crop. We exclude methods with uniform parameterization, because of their poor performance in the simpler supervised setting. All experiments are based on the SimCLR framework and use the PreActResNet-18 network as the encoder. We train each model with a batch size of 512 for 500 epochs. We then train a linear classifier to evaluate feature quality. We use test time augmentation—with 10 sampled crops—as it has been shown to improve performance (Foster et al., 2021).

From Table 5, we see that InstaAug outperforms the random and global augmentation schemes. We observe from the examples shown in Figure 8 that InstaAug focuses on the salient features containing important information. We also notice that the sizes of learned patches are correlated to the sizes of the main objects in images. Thus, InstaAug is able to learn sensible instance-specific augmentations from the contrastive loss signal in a fully unsupervised setting.

Table 5: Representations learned by InstaAug perform better in the downstream linear classification task than baselines.

Method	Accuracy (%)
Random crop	$51.63_{\pm 0.30}$
InstaAug (without input)	$54.20_{\pm 0.23}$
InstaAug	$\mathbf{55.05}_{\pm 0.21}$

7 DISCUSSION

In this paper we introduced InstaAug, a method for learning instance-specific data augmentations that capture local invariances of the underlying data generating process. This is achieved by training an augmentation module that parametrizes an input-dependent distribution over transformations, whose samples are used to augment the training data on the fly and/or for test-time augmentation. The main benefits of InstaAug stem from its applicability to a wide range of settings, its ease of use, and crucially its capacity to learn meaningful augmentations that in turn improve performance. Empirically, we demonstrated these benefits for both classification and contrastive learning problems, considering several classes of transformations—rotation, color jittering, and cropping.

REFERENCES

Alaaeldin Ali, Hugo Touvron, Mathilde Caron, Piotr Bojanowski, Matthijs Douze, Armand Joulin, Ivan Laptev, Natalia Neverova, Gabriel Synnaeve, Jakob Verbeek, et al. Xcit: Cross-covariance image transformers. *Advances in neural information processing systems*, 34:20014–20027, 2021.

Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. *Advances in neural information processing systems*, 32, 2019.

Gregory Benton, Marc Finzi, Pavel Izmailov, and Andrew Gordon Wilson. Learning invariances in neural networks. *Advances in Neural Information Processing Systems*, 2020.

Simone Bianco, Claudio Cusano, Paolo Napoletano, and Raimondo Schettini. Improving cnn-based texture classification by color balancing. *Journal of Imaging*, 3(3):33, 2017.

Anadi Chaman and Ivan Dokmanic. Truly shift-invariant convolutional neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3773–3783, 2021.

Shuxiao Chen, Edgar Dobriban, and Jane H. Lee. Invariance reduces variance: Understanding data augmentation in deep learning and beyond. *CoRR*, abs/1907.10905, 2019. URL http://arxiv.org/abs/1907.10905.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Xiangning Chen, Cihang Xie, Mingxing Tan, Li Zhang, Cho-Jui Hsieh, and Boqing Gong. Robust and accurate object detection via adversarial learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16622–16631, 2021.

Tsz-Him Cheung and Dit-Yan Yeung. Adaaug: Learning class- and instance-adaptive data augmentation policies. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=rWXfFogxRJN.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*. PMLR, 2016.

Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation policies from data. *Conference on Computer Vision and Pattern Recognition*, 2018.

Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 702–703, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Aleksandr Ermolov, Aliaksandr Siarohin, Enver Sangineto, and Nicu Sebe. Whitening for self-supervised representation learning. In *International Conference on Machine Learning*, pp. 3015–3024. PMLR, 2021.

Adam Foster, Rattana Pukdee, and Tom Rainforth. Improving transformation invariance in contrastive representation learning. In *International Conference on Learning Representations*, 2021.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Ryuichiro Hataya, Jan Zdenek, Kazuki Yoshizoe, and Hideki Nakayama. Faster autoaugment: Learning augmentation strategies using backpropagation. In *European Conference on Computer Vision*, pp. 1–16. Springer, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pp. 630–645. Springer, 2016b.

Daniel Ho, Eric Liang, Xi Chen, Ion Stoica, and Pieter Abbeel. Population based augmentation: Efficient learning of augmentation policy schedules. In *International Conference on Machine Learning*, pp. 2731–2741. PMLR, 2019.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, et al. Spatial transformer networks. *Advances in neural information processing systems*, 28, 2015.

Olav Kallenberg and Olav Kallenberg. *Foundations of modern probability*, volume 2. Springer, 1997.

Ildoo Kim, Younghoon Kim, and Sungwoong Kim. Learning loss for test-time augmentation. *Advances in Neural Information Processing Systems*, 33:4163–4174, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR (Poster)*, 2015.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

Yonggang Li, Guosheng Hu, Yongtao Wang, Timothy Hospedales, Neil M Robertson, and Yongxin Yang. Dada: differentiable automatic data augmentation. *arXiv preprint arXiv:2003.03780*, 2020.

Sungbin Lim, Ildoo Kim, Taesup Kim, Chiheon Kim, and Sungwoong Kim. Fast autoaugment. *Advances in Neural Information Processing Systems*, 2019.

Canjie Luo, Yuanzhi Zhu, Lianwen Jin, and Yongpan Wang. Learn to augment: Joint data augmentation and network optimization for text recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13746–13755, 2020.

Clare Lyle, Mark van der Wilk, Marta Kwiatkowska, Yarin Gal, and Benjamin Bloem-Reddy. On the benefits of invariance in neural networks. *arXiv preprint arXiv:2005.00178*, 2020.

Diego Marcos, Michele Volpi, Nikos Komodakis, and Devis Tuia. Rotation equivariant vector field networks. In *Proceedings of the IEEE International Conference on Computer Vision*, 2017.

Agnieszka Mikołajczyk and Michał Grochowski. Data augmentation for improving deep learning in image classification problem. In *2018 international interdisciplinary PhD workshop (IIPhDW)*. IEEE, 2018.

Luis Perez and Jason Wang. The effectiveness of data augmentation in image classification using deep learning. *arXiv preprint arXiv:1712.04621*, 2017.

Alexandre Ramé, Rémy Sun, and Matthieu Cord. Mixmo: Mixing multiple inputs for multiple outputs via deep subnetworks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 823–833, 2021.

Divya Shanmugam, Davis Blalock, Guha Balakrishnan, and John Guttag. Better aggregation in test-time augmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1214–1223, 2021.

Connor Shorten and Taghi M Khoshgoftaar. A survey on image data augmentation for deep learning. *Journal of big data*, 6(1):1–48, 2019.

Ivan Sosnovik, Michał Szmaja, and Arnold Smeulders. Scale-equivariant steerable networks. In *International Conference on Learning Representations*, 2019.

Alex Tamkin, Mike Wu, and Noah Goodman. Viewmaker networks: Learning views for unsupervised representation learning. In *International Conference on Learning Representations*, 2020.

Zhiqiang Tang, Xi Peng, Tingfeng Li, Yizhe Zhu, and Dimitris N Metaxas. Adatransform: Adaptive data transformation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2998–3006, 2019.

Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? *Advances in Neural Information Processing Systems*, 33:6827–6839, 2020.

Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

Daniel Worrall and Max Welling. Deep scale-spaces: Equivariance over scale. *Advances in Neural Information Processing Systems*, 2019.

Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

Jin Xu, Hyunjik Kim, Thomas Rainforth, and Yee Teh. Group equivariant subsampling. *Advances in Neural Information Processing Systems*, 2021.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 6023–6032, 2019.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

Richard Zhang. Making convolutional networks shift-invariant again. In *International conference on machine learning*. PMLR, 2019.

Yu Zheng, Zhi Zhang, Shen Yan, and Mi Zhang. Deep autoaugment. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=St-53J9ZARf.

Allan Zhou, Tom Knowles, and Chelsea Finn. Meta-learning symmetries by reparameterization. *arXiv preprint arXiv:2007.02933*, 2020.

Fengwei Zhou, Jiawei Li, Chuanlong Xie, Fei Chen, Lanqing Hong, Rui Sun, and Zhenguo Li. Metaaugment: Sample-aware data augmentation policy learning. *Thirty-Fifth AAAI Conference on Artificial Intelligence*, 2021.

Yanzhao Zhou, Qixiang Ye, Qiang Qiu, and Jianbin Jiao. Oriented response networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

APPENDIX A   DETAILS OF AUGERINO

As a method to learn invariance, Augerino (Benton et al., 2020) is quite different from the previous approaches, which usually require an extra validation set. The basic idea behind Augerino is to use a few parameters (θ) to control the transformation distribution on input images and learn these parameters with the training loss of the classifier. Specifically, it minimizes the loss

$$\mathcal{L}_\lambda(\mathbf{x}; y) \triangleq \mathbb{E}[\mathcal{L}(\mathbf{x}; y)] + \lambda \cdot \mathbb{R}(\theta), \tag{A.1a}$$

where $\mathcal{L}(\mathbf{x}; y)$ is the cross-entropy loss and $\mathbb{R}(\theta)$ is a regularization function on the volume of the support of the distribution weighted by the hyper-parameter λ.

Comparison with InstaAug.   InstaAug shares with Augerino the idea of tuning augmentation parameters by the classifier loss, but they are different in the following aspects. The most significant difference is that InstaAug is instance-specific, while Augerino learns global augmentations. Besides, Augerino uses a single scalar θ to parameterize a symmetric uniform distribution ($\mathcal{U}[-\theta, \theta]$) over each type of transformations, which lacks the flexibility to model more complex augmentations, such as cropping.

In addition, Augerino uses a fixed weight λ to balance the training loss and augmentation diversity. However, we find that, in more complicated settings, this is quite impractical. Specifically, we need different λ in different stages of training. If we use a large λ from the start of training, the diversity will quickly diverge to maximum, because the classifier is very weak and the loss is consequently dominated by the diversity term. This will block the training of the classifier because transformed samples from different classes are quite mixed with each other. Otherwise, if we choose a small λ, the diversity will converge to zero after a few epochs, yielding similar results as the vanilla model without augmentation. In neither of the case can we learn a useful augmentation. Consequently, InstaAug directly constrains the diversity to keep it stable during training.

APPENDIX B   METHOD DETAILS

B.1   REGRESSION AND SELF-SUPERVISED LEARNING

In Section 3, we use classification as an example to introduce InstaAug. However, InstaAug can be easily applied to other tasks including regression and self-supervised learning. For regression, the classifier (see Figure 2) is replaced by a regressor and the loss function $\mathcal{L}$ in Equation (2a) is changed accordingly to absolute or square error. For self-supervised contrastive learning, we replace the classifier and cross-entropy loss with the feature extractor and contrastive loss (such as SimCLR loss (Chen et al., 2020)), respectively. In addition, the sampler samples 2 rather than 1 transformations to generate multiple views for an input $\mathbf{x}$.

B.2   IMPLEMENTATION OF LOCATION-RELATED PARAMETERIZATION

As an example, we show how to implement location-related parameterization with a basic CNN structure in the following algorithm,.

Algorithm 1: Location related parameterization

Input: Image $\mathbf{x}$, channel numbers M_i, and layer number n_layer
Output: Probability of patches $\mathbf{p}$
$\mathbf{F}'_0 = \mathbf{x}$;
for ($i = 1$; $i \leq n\_layer$; $i = i + 1$)
  $\mathbf{F_i} = \text{Conv2d}(\mathbf{F}'_{i-1}, \text{kernel=2, stride=1, output\_channel=}M_i)$;   // CNN Operation
  $\mathbf{F}'_i = \text{Pooling}(\mathbf{F_i}, \text{kernel=2})$;   // CNN Operation
  $\mathbf{F}''_i = \text{Conv2d}(\mathbf{F}'_i, \text{kernel=1, stride=1, output\_channel=1})$; // To a single channel
  $\mathbf{logit_i} = \text{Flatten}(\mathbf{F}''_i)$;   // Logit vector at each level
$\mathbf{logits} = \text{Concat}([\mathbf{logit_i}])$;   // Logit vector at all levels
$\mathbf{p} = \text{Normalize}(\text{Exp}(\mathbf{logits}))$;   // Probability after normalization

---

D45   D50   D55   D60   D65 (I=1) D65 (I=0.75) D27 (A=90) D65+D95 D65+D27 D95+D27 Red   Green

Figure C.1: Examples of RawFooT data. Each row contains images in the same class (corn, candies, floor, red cabbage) under different lighting conditions. The left and right half of lighting conditions are in the easy and hard group, respectively.

B.3 OTHER PARAMETRIZATION METHODS

Besides the uniform and location-related parameterization, we also tried VAE-like methods to parameterize augmentations, such as cropping. The main idea is to have a Gaussian latent variable and a neural decoder to map the latent Gaussian distributions to a continuous distribution on transformation parameters (in this case, the centers and sizes of crops). However, similar to the uniform parameterization, we find the VAE-like parameterization unstable and easily stuck at local minima.

APPENDIX C   EXPERIMENTAL DETAILS

C.1 CROPPING

Supervised training   Based on the Mixmo codebase[1] (Ramé et al., 2021), we use stochastic gradient descent (SGD) optimizer to train baselines and InstaAug. For the classifier, the initial learning rate is set to 0.2 (with momentum 0.9 and weight decay $1e-4$). A scheduler is used to decrease the learning rate by a factor of 0.9 once validation accuracy doesn't increase for 10 epochs. The learning rate of the augmentation module ϕ is fixed at $1e-5$. Batch size is set to 100 and we pre-train InstaAug for 10 epochs without augmentation. We train the model until convergence and the maximum epoch is set to 150.

Contrastive training   We directly apply InstaAug on the codebase[2] from Ermolov et al. (2021). Because of the characteristics of contrastive learning, we set the batch size to 512. Same as the supervised case, we use SGD optimizer to train the augmentation module ϕ. Differently, we use Adam optimizer (Kingma & Ba, 2015) (with learning rate $1e-3$ and weight decay $1e-6$) to train the base model. We train each model for 500 epochs and decrease the learning rate by a factor of 0.8 at step 450 and 475.

C.2 COLOR JITTERING ON TEXTURES

Training.   We use PreActResNet-18 ($width = 1$) on texture recognition task on RawFooT and train it with SGD optimizer. The learning rate is 0.02 (with momentum 0.9 and weight decay $1e-4$) for the classifier and $1e-5$ for the augmentation module ϕ. We train each model for 50 epochs and learning rate schedulers are not necessary in this task.

Random augmentation baseline.   We sweep over the variation range on each channel to find the best hyperparameters for the random augmentation baseline. For hue (h-jittering), we sweep between $[0, 0.5]$ with stride 0.1, and for saturation (s-jittering) as well as brightness value (v-jittering), we

---

[1] https://github.com/alexrame/mixmo-pytorch.git, under Apache License v2.0.
[2] https://github.com/htdt/self-supervised.git, under Apache License v2.0.

sweep between $[0, 1.0]$ with stride 0.2, which yields 216 different settings in total. The best accuracy shown in Table 3 is achieved where h,s,v= $0.0, 0.2, 0.8$.

In-distribution vs. out-of-distribution generalization. To further investigate the effect of each augmentation method, we additionally split the 46 test sets into two equally-sized groups. The first group contains lighting conditions similar to D45, such as daylight with different temperatures, for which the

Table C.1: Splitting of Lighting conditions.

Group	Lighting id
Easy (1)	1-4,10,14-31
Hard (2)	5-9, 11-13, 32-46

vanilla model without augmentation trained on D45 has high test accuracy. The second group contains lighting conditions that are dramatically different from D45, for example, pure red light, which are more difficult for the vanilla method. Then the average accuracy on the first group can be regarded as a measure of in-distribution generalization, while the accuracy on the second group reflects out-of-distribution generalization.

C.3 TIME COMPLEXITY

We notice that InstaAug on color jittering has a similar training speed (0.37s/iter) as random augmentation (0.40s/iter) on a single Nvidia 1080Ti GPU, though it takes more epochs (about 40) compared with random augmentation, which usually converges after 25 epochs. We also find the speed for evaluation is very fast even with test time augmentation (sample number =10), which is about 0.004s/sample. However, the training speed of InstaAug on cropping (0.25s/iter) is slower than random augmentation (0.15s/iter) due to optimization issues on the more complex parameterization method. Training InstaAug alone takes a similar amount of time for each epoch compared with joint training, but it requires fewer epochs (less than 30) to converge and we can cache the outputs of the classifier for faster training. The evaluation speed is 0.011s/sample when sample number is set to 50 for test-time augmentation.

APPENDIX D ADDITIONAL RESULTS

D.1 RAWFOOT

Figure D.1 shows some examples of learned color jittering. Though it's not easy to fully understand them, we can still find some patterns. For example, InstaAug tends to increase the brightness of darker images (row 1 and 3) and decrease the brightness of brighter images (row 4). Also InstaAug is more likely to change saturation compared with hue and brightness, which is consistent with the common belief that saturation contains less information than hue and brightness. InstaAug's behavior is quite different on different samples. It even decides not to augment the H and V channels of the image in the second row. In comparison, Augerino adds or multiplies noise to each channel with the same distribution across all samples, which is harmful in many cases. For example, the input image in the last row is already very bright. but Augerino allows further increasing its brightness. Then brightness values of many pixels will be capped at 1.0, which leads to loss of information.

Figure D.1: Examples of learned color jittering. (a) Original image; (b, f) Average hue (H) of original image (blue dot) and learned hue jittering (red arc) for InstaAug and Augerino, respectively; (c,g) learned saturation (S) and brightness value (V) of original image (blue dot) and learned hue jittering (red line segment) for InstaAug and Augerino; (d,e) examples of images transformed by InstaAug.