LiftPool: Bidirectional ConvNet Pooling

Abstract

Pooling is a critical operation in convolutional neural networks for increasing robustness to input variations. Most existing pooling operations downsample the feature map, which may remove discriminative details. Moreover, they are not inversible: upsampling a down-scaled feature map loses much information. By adopting the philosophy of the classical Lifting Scheme from signal processing, we propose LiftPool for bidirectional pooling layers, including LiftDownPool and LiftUpPool. LiftDownPool decomposes a feature map into various down-sized sub-bands, each of which contains correlated structures or details of the feature map. As the pooling function in LiftDownPool is perfectly reversable, by performing LiftDownPool backwards, a corresponding up-pool layer LiftUpPool is able to generate a refined upsampled feature map using the detail sub-bands, which is useful for image-to-image translation challenges. Experiments show the proposed methods achieve better results on image classification and semantic segmentation, using various backbones. Moreover, LiftDownPool offers a better robustness to input corruptions and perturbations.

1 Introduction

Spatial pooling has been a critical ConvNet operation since its inception (Fukushima, 1979; LeCun et al., 1990; Krizhevsky et al., 2012; He et al., 2016; Chen et al., 2018). Several simple operations, such as average pooling or max pooling, have been explored for aggregating features in a local area. Springenberg et al. (2015) employ a convolutional layer with an increased stride to replace a pooling layer, which is equivalent to down-sampling. While effective and efficient, all these methods could erase details deemed important for the discriminability of the network (Boureau et al., 2010; Saeedan et al., 2018) and the pooling functions are not inversible. Different from existing pooling operations, we propose in this paper a bidirectional pooling called LiftPool, including LiftDownPool for downsizing feature maps and LiftUpPool for upsampling feature maps.

LiftPool is inspired by the classical Lifting Scheme (Sweldens, 1998) from signal processing, which is commonly used for information compression (Pesquet-Popescu & Bottreau, 2001), reconstruction (Dogiwal et al., 2014) and denoising (Wu et al., 2004). The Lifting Scheme decomposes an input signal into various sub-bands with down-scaled size and this process is perfectly reversible. Applying the idea of Lifting Scheme, LiftDownPool factorizes an input feature map into several down-sized spatial sub-bands with different correlation structures. As shown in Figure 1, for an image feature map, the LL sub-band is an approximation removing several details. The LH, HL and HH represent details along horizontal, vertical and diagonal directions. LiftDownPool respects preserving any sub-band(s) as the pooled result. Moreover, due to the invertibility of the pooling function, LiftUpPool is introduced for up-sampling feature maps. Upsampling a feature map is more challenging as seen for the MaxUpPool (Badrinarayanan et al., 2017), which generates an output with many 'holes' (shown in Figure 1). LiftUpPool utilizes the recorded details to recover a refined output by performing LiftDownPool backwards.

We analyze the proposed LiftPool from several viewpoints. LiftDownPool allows a flexible choice for any sub-band(s) as the pooled result. It outperforms baselines on image classification with various ConvNet backbones. LiftDownPool also presents better stability to corruptions and perturbations of inputs. By performing LiftDownPool backwards, LiftUpPool generates a refined upsampling feature map for semantic segmentation.

Figure 1: **Illustration of the proposed LiftDownPool and LiftUpPool** *vs.* MaxPool and MaxUp-Pool on an image from CIFAR-100. Where MaxPool takes the maximum activations from the input, LiftDownPool decomposes the input into four sub-bands: LL, LH, HL and HH. LL contains low-pass coefficients. It better reduces aliasing compared to MaxPool. LH, HL and HH represent details along horizontal, vertical and diagonal directions. For simplicity, we just upsample the down-pooled results for illustrating the up-pooling. MaxUpPool generates a sparse map with lost details. LiftUpPool produces a refined output from the recorded details by performing LiftDownPool backwards.

2 METHODS

The down-pooling operator is formulated as minimizing the information loss caused by downsizing feature maps, as in image downscaling by Saeedan et al. (2018); Kobayashi (2019a). The Lifting Scheme (Sweldens, 1998) naturally matches the problem. The Lifting Scheme was originally designed to exploit the correlated structures present in signals to build a down-sized approximation and several detail sub-bands in the spatial domain (Daubechies & Sweldens, 1998). The inverse transform is realizable and always provides a perfect reconstruction of the input. LiftPool is derived from the Lifting Scheme for bidirectional pooling layers.

2.1 LIFTDOWNPOOL

Taking a one-dimension (1D) signal as an example, LiftDownPool decomposes a given signal $\boldsymbol{x} = [x_1, x_2, x_3, ..., x_n], x_n \in \mathbb{R}$ into a *downscaled* approximation signal $\boldsymbol{s}$ and a difference signal $\boldsymbol{d}$ by,

$$\boldsymbol{s}, \boldsymbol{d} = F(\boldsymbol{x}). \tag{1}$$

where $F(\cdot) = f_{\text{update}} \circ f_{\text{predict}} \circ f_{\text{split}}(\cdot)$, consists of three functions: split (down-sample), predict and update. The LiftDownPool-1D is illustrated in Figure 2(a). Specifically,

Split $f_{\text{split}} : \boldsymbol{x} \mapsto (\boldsymbol{x}^e, \boldsymbol{x}^o)$. The given signal $\boldsymbol{x}$ is split into two disjoint sets $\boldsymbol{x}^e = [x_2, x_4, ..., x_{2k}]$ with even indices and $\boldsymbol{x}^o = [x_1, x_3, ..., x_{2k+1}]$ with odd indices. The two sets are typically highly correlated.

Predict $f_{\text{predict}} : (\boldsymbol{x}^e, \boldsymbol{x}^o) \mapsto \boldsymbol{d}$. Given one set *e.g.* $\boldsymbol{x}^e$, another set $\boldsymbol{x}^o$ is able to be predicted by a predictor $\mathcal{P}(\cdot)$. The predictor is not required to be precise, so the difference, or detail with high-pass coefficients $\boldsymbol{d}$ is defined as:

$$\boldsymbol{d} = \boldsymbol{x}^o - \mathcal{P}(\boldsymbol{x}^e). \tag{2}$$

Update $f_{\text{update}} : (\boldsymbol{x}^e, \boldsymbol{d}) \mapsto \boldsymbol{s}$. Taking $\boldsymbol{x}^e$ as an approximation of $\boldsymbol{x}$ causes a serious aliasing because $\boldsymbol{x}^e$ is simply down-sampled from $\boldsymbol{x}$. Particularly, the running average of $\boldsymbol{x}^e$ is not the same as that of $\boldsymbol{x}$. To correct it, a smoothed version $\boldsymbol{s}$ is generated by adding $\mathcal{U}(\boldsymbol{d})$ to $\boldsymbol{x}^e$:

$$\boldsymbol{s} = \boldsymbol{x}^e + \mathcal{U}(\boldsymbol{d}). \tag{3}$$

(a) LiftDownPool   (b) LiftUpPool

Figure 2: **LiftDownPool and Lift-UpPool implementations.** (a) LiftDownPool-1D. x is split into x^e and x^o. Predictor and Updater generate details d and an approximation s. (b) LiftUpPool-1D. By running LiftDownPool backwards, x^e and x^o are generated from s and d, and then merged to x.

The update procedure is equivalent to applying a low-pass filter to x. Thus, s with low-pass coefficients is taken as an approximation of the original signal.

Pre-designing filters in $\mathcal{P}(\cdot)$ and $\mathcal{U}(\cdot)$ is difficult (Zheng et al., 2010). Earlier, Zheng et al. (2010) proposed to optimize these filters by a back-propagation network. All functions in LiftDownPool are differentiable. $\mathcal{P}(\cdot)$ and $\mathcal{U}(\cdot)$ are able to be simply implemented by convolution operators followed by non-linear relu operators (Glorot et al., 2011). We prefer to learn the filters in $\mathcal{P}(\cdot)$ and $\mathcal{U}(\cdot)$ with deep neural networks in an end-to-end fashion. To that end, two constraints need to be added to the final loss function. s is the down-sized approximation of x. As s is updated from x^e according to Eq 3, s is essentially close to x^e. Thus, s is naturally required to be close to x^o as well. Therefore, one constraint term c_u is for minimising the L2-norm distance between s and x^o. With Eq 3,

$$
\begin{aligned}
c_u &= \|s - x^o\|_2 \\
&= \|\mathcal{U}(d) + x^e - x^o\|_2.
\end{aligned}
\tag{4}
$$

The other constraint term c_p is for minimising the detail d, with Eq 2,

$$
c_p = \|x^o - \mathcal{P}(x^e)\|_2.
\tag{5}
$$

Our experiments show that the two terms bring good regularization to the model. LiftDownPool-2D is easily decomposed into two LiftDownPool-1D operations along the two dimensions of the input. Naturally, LiftDownPool-1D can be generalized further for any n-dimensional signal. In Figure 3, we show several feature maps from the first LiftDownPool layer based on VGG13. LL has smoothed features with less details. LH, HL and HH capture the details along horizontal, vertical and diagonal directions.

Discussion MaxPool is usually formulated as first performing Max and then downsampling: $\mathrm{MaxPool}_{k,s} = \mathrm{downsample}_s \circ \mathrm{Max}_k$ (Zhang, 2019). By contrast, LiftDownPool is: $\mathrm{LiftDownPool}_{k,s} = \mathrm{update}_k \circ \mathrm{predict}_k \circ \mathrm{downsample}_s$. First downsampling and then performing two lifting steps (prediction and updating) helps anti-aliasing. A simple analysis is provided in the Appendix. As shown in Figure 1, LiftDownPool keeps more structured information and better reduces aliasing then MaxPool.

2.2 LIFTUPPOOL

LiftPool inherits the reversibility of the Lifting Scheme. Taking the 1D signal as an example, LiftUpPool generates an upsampled signal x from s, d by:

$$
x = G(s, d).
\tag{6}
$$

where $G(\cdot) = f_{\mathrm{merge}} \circ f_{\mathrm{predict}} \circ f_{\mathrm{update}}(\cdot)$, including functions: update, predict and merge. Specifically, $s, d \mapsto x^e, d \mapsto x^e, x^o \mapsto x$ is realized by:

$$
x^e = s - \mathcal{U}(d),
\tag{7}
$$

$$
x^o = d + \mathcal{P}(x^e),
\tag{8}
$$

$$
x = f_{\mathrm{merge}}(x^e, x^o).
\tag{9}
$$

Figure 3: **LiftDownPool visualization.** Selected feature maps of an image in CIFAR-100, from the first LiftDownPool layer in VGG13. LL represents smoothed feature maps with less details. LH, HL and HH represent detailed features along horizontal, vertical and diagonal directions. Each sub-bands contains different correlation structures.

Discussion   Up-pooling has been used in image-to-image translation tasks such as semantic segmentation (Chen et al., 2017), super-resolution (Shi et al., 2016), and image colorization (Zhao et al., 2018). It is generally used in encoder-decoder networks such as SegNet (Badrinarayanan et al., 2017) and UNet (Ronneberger et al., 2015). However, most existing pooling functions are not invertible. Taking MaxPool as the baseline, it is required to record the maximum indices during max pooling. For simplicity, we use the down-pooled results as inputs to the up-pooling in Figure 1. When performing MaxUpPool, the values of the input feature maps are directly filled on the corresponding maximum indices of the output and other indices will be given zeros. By doing so, the output looks sparse and loses much of the structured information, which is harmful for generating good-resolution outputs. LiftUpPool performing an inverse transformation of LiftDownPool, is able to produce finer outputs by using the multiphase sub-bands.

3 RELATED WORK

Taking the average over a feature map region was the pooling mechanism of choice in the Neocognitron (Fukushima, 1979; 1980) and LeNet (LeCun et al., 1990). Average pooling is equivalent to blurred-downsampling. Max pooling later proved even more effective (Scherer et al., 2010) and became popular in deep ConvNets. Yet, averaging activations or picking the maximum activations causes loss of details. Zeiler & Fergus (2013) and Zhai et al. (2017) introduced a stochastic process to pooling and downsampling, respectively, for a better regularization. Lee et al. (2016) mixed AveragePool and MaxPool by a gated mask to adapt to complex and variable input patterns. Saeedan et al. (2018) introduced detail-preserving pooling (DPP) for maintaining structured details. By contrast, Zhang (2019) proposed a BlurPool by applying a low-pass filter, which removes details. Interestingly, both methods improved image classification, indicating that (empirically) determining the best pooling strategy is beneficial (Saeedan et al., 2018). Williams & Li (2018) introduced the wavelet transform into pooling for reducing jagged edges and other artifacts. Rippel et al. (2015) suggested pooling in the frequency domain, which enabled flexibility in the choice of the pooling output dimensionality. Pooling based on a probabilistic model was proposed in (Kobayashi, 2019a) and (Kobayashi, 2019b). Kobayashi (2019a) first used a Gaussian distribution to model the local activations and then aggregates the activations into the two statistics of mean and standard deviation. Kobayashi (2019b) estimated parameters from global statistics in the input feature map, to flexibly represent various pooling types. Our proposed LiftDownPool decomposes the input feature map into a down-sized approximation and several details. It is flexible to choose any sub-band(s) as pooled result.

While most existing pooling functions are not invertible, our proposed LiftPool is able to perform both down-pooling and up-pooling. Previously, MaxUpPool (Badrinarayanan et al., 2017) was introduced for semantic segmentation. As the max pooling function is not invertible, the lost details can not be recovered during up-pooling. Hence, the output suffers from aliasing. Although adding a BlurPool to MaxUpPool may help to reduce the aliasing (Zhang, 2019), several details are still lost. LiftUpPool, performing the LiftDownPool functions backwards, is capable of producing a refined high-resolution output with the help of the details sub-bands.

Table 1: **Flexibility.** Top-1 image classification error rate with varying sub-bands on CIFAR-100. Mixing low-pass and high-pass obtains the best result.

	Top-1
LL	25.64 ± 0.04
LH	25.71 ± 0.04
HL	24.88 ± 0.05
HH	25.18 ± 0.08
$LL+LH+HL+HH$	$\mathbf{24.35} \pm 0.11$

Kernel	Top-1
2	25.53 ± 0.13
3	25.06 ± 0.22
4	24.89 ± 0.07
5	$\mathbf{24.35} \pm 0.11$

	Top-1
Skip (Springenberg et al., 2015)	27.09 ± 0.11
MaxPool	25.71 ± 0.13
AveragePool	25.87 ± 0.03
LiftDownPool	$\mathbf{24.35} \pm 0.11$

Table 2: **Effectiveness.** Top-1 image classification error rate with varying kernel size on CIFAR-100. Larger kernel size achieve better result.

Table 3: **Effectiveness.** Top-1 image classification error rate with various pooling methods on CIFAR-100. LiftDownPool outperforms baselines.

4 EXPERIMENTS

4.1 CONVNET TESTBEDS

Image Classification We first verify the proposed LiftDownPool for image classification on **CIFAR-100** (Krizhevsky & Hinton, 2009) with 32×32 low-resolution images. CIFAR-100 has 100 classes with 600 images each. There are 500 training images and 100 testing images per class. A VGG13 (Simonyan & Zisserman, 2015) network is trained on this dataset. For experiments conducted on CIFAR-100, we repeat each experiment three times with different initial random seeds during training and report the averaged error rate with the standard deviation. We also report on **ImageNet** (Deng et al., 2009) with 1.2M training images and 5000 validation images for 1000 classes. We plug the LiftDownPool into several popular ConvNet backbones including ResNet18, ResNet50 (He et al., 2016) and MobileNet-V2 (Sandler et al., 2018) to verify its generalizability for image classification. We replace the local pooling layers by LiftDownPool in all the networks. Error rate is utilized as the evaluation metric. Specific training settings are seen in Appendix.

Semantic Segmentation We also test the LiftDownPool and LiftUpPool for semantic segmentation on **PASCAL-VOC12** (Everingham et al., 2010), which contains 20 foreground object classes and one background class. An augmented version with 10582 training images and 1449 validation images is used. We consider SegNet (Badrinarayanan et al., 2017) with VGG13 and DeeplabV3Plus (Chen et al., 2018) with ResNet50 as ConvNets for semantic segmentation. The performance is measured in terms of pixel mean-intersection-over-union (*mIoU*) across the 21 classes. *Code and ConvNets for all experiments will be released.*

4.2 ABLATION STUDY

Flexibility We first test VGG13 on CIFAR-100. Different from previous pooling methods, LiftDownPool generates four sub-bands, each of which contains a different type of information. LiftDownPool allows to flexibly choose which sub-band(s) to keep as the final pooled results. In Table 1, we show the *Top-1* error rate for the classification based on different sub-bands. Interestingly, it is observed that vertical details contribute more for image classification. Low-pass coefficients and high-pass coefficients along horizontal direction get similar error rate. These findings may stimulate researchers to rethink whether the two spatial dimensions should be treated equally, although this was justified by the statistics of natural images (Huang & Mumford, 1999). To realize a less lossy pooling, we combine all the sub-bands by summing them up with almost no additional compute cost. Such a pooling significantly improves the results. Moreover, seen from Table 1 and Table 3, we further conclude LiftDownPool outperforms other baselines even based on any single sub-band. We believe the learned LiftDownPool provides an effective regularization to the model.

	ResNet18		ResNet50		MobileNet-V2	
	Top-1	*Top-5*	*Top-1*	*Top-5*	*Top-1*	*Top-5*
Skip	30.22	10.23	24.31	7.34	28.66	9.70
MaxPool	28.60	9.77	24.26	7.22	28.65	9.82
AveragePool	28.03	9.55	24.40	7.35	28.32	9.72
S³Pool (Zhai et al., 2017)	33.91	13.09	27.98	9.34	40.56	17.91
WaveletPool (Williams & Li, 2018)	30.33	10.82	24.43	7.36	29.27	10.26
BlurPool (Zhang, 2019)	29.88	10.58	24.60	7.73	30.58	11.26
DPP (Saeedan et al., 2018)	29.12	10.21	24.62	7.49	29.85	10.53
SpectralPool (Rippel et al., 2015)	28.69	9.87	24.81	7.57	33.38	12.56
GatedPool (Lee et al., 2016)	27.78	9.44	23.79	7.06	28.94	9.90
MixedPool (Lee et al., 2016)	27.76	9.50	24.08	7.32	29.00	9.97
GFGP (Kobayashi, 2019b)	26.88	8.66	22.76	6.34	28.42	9.59
GaussPool (Kobayashi, 2019a)	26.58	8.86	22.95	6.30	27.13	8.92
LiftDownPool	**25.80**	**8.14**	**22.36**	**6.11**	**26.09**	**8.22**

Table 4: **Generalizability** of LiftDownPool on ImageNet. LiftDownPool outperforms alternative pooling methods, no matter what ConvNet backbone is used.

	Normalized		Unnormalized	
	ImageNet-C	ImageNet-P	ImageNet-C	ImageNet-P
	mCE	*mPR*	*mCE*	*mPR*
Skip	72.71	61.75	57.05	7.56
MaxPool	73.09	62.64	57.40	7.57
AveragePool	72.09	56.23	56.56	6.90
LiftDownPool	**68.45**	**52.91**	**53.80**	**6.55**

Table 5: **Out-of-distribution robustness** of LiftDownPool on ImageNet-C and ImageNet-P. LiftDownPool is more robust to corruptions and perturbations compared to baselines.

Effectiveness Table 2 ablates the performance when varying kernel sizes for the filters in $\mathcal{P}(\cdot)$ and $\mathcal{U}(\cdot)$. A larger kernel size, covering more local information, performs slightly better. Unless specified otherwise, we use for all experiments from now on a kernel size of 5 and we sum up all the sub-bands. We also compare our LiftDownPool with the commonly-used MaxPool, AveragePool, as well as the convolutional layer with stride 2 (Springenberg et al., 2015), which is called Skip by Kobayashi (2019a). Seen from Table 3, LiftDownPool outperforms other pooling methods on CIFAR-100, which illustrates the effectiveness of our proposal.

Generalizability For larger scale image classification on ImageNet, we apply LiftDownPool to several backbones including ResNet18, ResNet50 and MobileNet-V2. In Table 4, LiftDownPool has 2% lower *Top-1* error rate than MaxPool and AveragePool. While combining MaxPool and AveragePool in a Gated (Lee et al., 2016) or Mixed (Lee et al., 2016) fashion, still has a 1% gap with LiftDownPool. The recent Gauss (Kobayashi, 2019a) and GFGP (Kobayashi, 2019b) are comparable to LiftDownPool with ResNet50, but not with lighter networks. Compared to Spectral pooling (Rippel et al., 2015) and Wavelet pooling (Williams & Li, 2018), which are applied in the frequency or space-frequency domain, LiftDownPool offers an advantage by learning correlated structures and details in the spatial domain. Compared to DPP (Saeedan et al., 2018), which preserves details, and BlurPool (Zhang, 2019), smoothing feature maps by a low-pass filter, our LiftDownPool retains all sub-bands which proves to be more powerful for image classification. Stochastic approaches like S³Pool obtain poor results on the large-scale dataset because randomness in pooling hampers network training, as earlier observed by Kobayashi (2019b). To conclude, compared to most existing pooling methods, LiftDownPool achieves the lowest *Top-1* and *Top-5* error rate, no matter what backbone is used.

Figure 4: **Shift Robustness** comparisons between various pooling methods including MaxPool, Skip, AveragePool and the proposed LiftDownPool. LiftDownPool improves classification consistency and meanwhile boosts the accuracy, independent of the backbone used.

4.3 STABILITY ANALYSIS

Out-of-distribution Robustness A good down-pooling method is expected to be stable to perturbations and noise. Following Zhang (2019), we test the robustness of LiftDownPool to corruptions on *ImageNet-C* and stability to perturbations on *ImageNet-P* using ResNet50. Both datasets come from Hendrycks & Dietterich (2019). We report the mean Corruption Error (*mCE*) and mean Flip Rate (*mFR*) for the two tasks, with both unnormalized raw values and normalized values by AlexNet's *mCE* and *mFR* following Hendrycks & Dietterich (2019).

The generated corruptions on ImageNet-C consist of 15 different types, covering noise, blur, weather, and digital categories. From Table 5, LiftDownPool effectively reduces raw *mCE* by 3% compared to the three baselines. We show *CE* for each corruption type for further analysis in Figure 8 in the Appendix. LiftDownPool enables robustness to both "high-frequency" corruptions, such as noise or spatter, and "low-frequency" corruptions, like blur and jpeg compression. We believe LiftDownPool benefits from the mechanism that all sub-bands are used. A similar conclusion is obtained for robustness to perturbations on ImageNet-P from Table 5 and Figure 8 in the Appendix. ImageNet-P contains short video clips of a single image with small perturbations added. Such perturbations are generated by several types of noise, blur, geometric changes, and simulated weather conditions. The metric *FR* measures how often the Top-1 classification changes in consecutive frames. It is designed for testing a model's stability under small deformations. Again, LiftDownPool achieves lower *FR* for most perturbations.

Shift Robustness We then test the shift-invariance of our model. Following Zhang (2019), we use classification consistency to measure the shift-invariance. It represents how often the network outputs the same classification, given the same image with two different shifts. We test the models with varying backbones trained on ImageNet. In Figure 4, LiftDownPool boosts classification accuracy as well as consistency no matter which backbone is used. Besides, We have other interesting findings. Deeper network ResNet50 has more stable shift-invariance. Various pooling methods including MaxPool, Skip, AveragePool, do not make significant difference on consistency. However, a lighter ResNet18 network is influenced much by the pooling method. LiftDownPool brings more than 10% improvement on consistency using ResNet18. We believe such findings will stimulate one to think how the depth of the network affects the sift-invariance of the network itself.

4.4 RESULTS FOR SEMANTIC SEGMENTATION

Invertibility LiftDownPool functions are invertible as described in Eq 7 and Eq 8. It naturally benefits a corresponding up-pooling operation, which is popularly used in Encoder-Decoder networks for image-to-image translation tasks. Usually, the Encoder down-sizes feature maps layer by layer to generate a high-level embedding for understanding the image. Then the Decoder needs to translate the embedding with a tiny spatial size to a required map with the same spatial size as the original input image. Interpreting details is pivotal for producing high-resolution outputs. We replace all down-pooling and up-pooling layers with LiftDownPool and LiftUpPool in SegNet for semantic segmentation on PASCAL-VOC12. For LiftDownPool we only keep the LL sub-band. For LiftUpPool, the detail-preserving sub-bands LH, HL and HH are used for generating upsampled feature maps. MaxUpPool is taken as the baseline. We also test MaxUpPool followed by a Blur-

| | | | | |
| Image | MaxUpPool | MaxUpPool+BlurPool | LiftUpPool | Ground-truth |

Figure 5: **Invertibility.** Visualization of semantic segmentation maps on PASCAL-VOC12 based on SegNet with varying up-pooling methods. LiftUpPool presents more completed, precise segmentation maps with smooth edges.

	mIoU
MaxUpPool (Badrinarayanan et al., 2017)	62.7
MaxUpPool + BlurPool (Zhang, 2019)	64.0
LiftUpPool	**68.9**

Table 6: **Invertibility.** Semantic segmentation results on PASCAL-VOC12 based on SegNet with varying up-pooling methods. LiftUpPool performs well.

	mIoU
Skip	76.1
MaxPool	76.2
AveragePool	76.4
Gauss (Kobayashi, 2019a)	77.4
LiftDownPool	**78.7**

Table 7: **Transferability.** Semantic segmentation results on PASCAL-VOC12 based on DeepLabV3Plus with various pooling methods. LiftDownPool performs best.

Pool (Zhang, 2019), which is expected to help anti-aliasing. Table 6 reveals LiftUpPool improves over the baselines with a considerable margin. As illustrated in Figure 1, MaxUpPool is unable to compensate for the lost details. Although BlurPool helps smoothing local areas, it can only provide a small improvement. As LiftUpPool is capable of refining the feature map by fusing it with details, it is beneficial for per-pixel prediction tasks like semantic segmentation. We show several examples for semantic segmentation in Figure 5. LiftUpPool is observed more precise on details and edges. We also show the feature maps per predicted class in the Appendix.

Transferability As discussed, LiftDownPool helps to lift ConvNets on accuracy and stability for image classification. ImageNet-trained ConvNets often serve as the backbones for downstream tuning, it is expected to transfer the nature of LiftDownPool to other tasks. We still consider semantic segmentation as our example. We leverage the state-of-the-art DeeplabV3Plus-ResNet50. Same as before, all local pooling layers are replaced by LiftDownPool. We use the pre-trained weights for image classification to initialize the corresponding model. As shown in Table 7, LiftDownPool outperforms all the baselines with considerable gaps.

5 CONCLUSION

Applying classical signal processing theory to modern deep neural networks, we propose a novel pooling method: LiftPool. LiftPool is able to perform both down-pooling and up-pooling. LiftDownPool improves both accuracy and robustness for image classification. LiftUpPool, generating refined upsampling feature maps, outperforms MaxUpPool by a considerable margin on semantic segmentation. Future work may focus on applying LiftPool to fine-grained image classification or super-resolution tasks, which have high requirements for details.

REFERENCES

Vijay Badrinarayanan, Alex Kendall, and Roberto Cipolla. Segnet: A deep convolutional encoder-decoder architecture for image segmentation. *TPAMI*, 2017. 1, 4, 5, 8

Y-Lan Boureau, Jean Ponce, and Yann LeCun. A theoretical analysis of feature pooling in visual recognition. In *ICML*, pp. 111–118, 2010. 1

Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *TPAMI*, 2017. 4

Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. *ECCV*, 2018. 1, 5

Ingrid Daubechies and Wim Sweldens. Factoring wavelet transforms into lifting steps. *Journal of Fourier analysis and applications*, 4(3), 1998. 2

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009. 5

Sanwta Ram Dogiwal, YS Shishodia, and Abhay Upadhyaya. Efficient lifting scheme based super resolution image reconstruction using low resolution images. In *Advanced Computing, Networking and Informatics*, pp. 259–266. Springer, 2014. 1

Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *IJCV*, 88(2):303–338, 2010. 5

Kunihiko Fukushima. Neural network model for a mechanism of pattern recognition unaffected by shift in position-neocognitron. *IEICE Technical Report, A*, 62(10):658–665, 1979. 1, 4

Kunihiko Fukushima. A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biol. Cybern.*, 36:193–202, 1980. 4

Xavier Glorot, Antoine Bordes, and Yoshua Bengio. Deep sparse rectifier neural networks. In *International conference on artificial intelligence and statistics*, 2011. 3

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016. 1, 5

Dan Hendrycks and Thomas G Dietterich. Benchmarking neural network robustness to common corruptions and surface variations. *ICLR*, 2019. 7, 12

Jinggang Huang and David Mumford. Statistics of natural images and models. In *CVPR*, 1999. 5

Takumi Kobayashi. Gaussian-based pooling for convolutional neural networks. In *NeurIPS*, 2019a. 2, 4, 6, 8

Takumi Kobayashi. Global feature guided local pooling. In *ICCV*, 2019b. 4, 6

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009. 5

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NIPS*, 2012. 1

Yann LeCun, Bernhard E Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne E Hubbard, and Lawrence D Jackel. Handwritten digit recognition with a back-propagation network. In *NIPS*, 1990. 1, 4

Chen-Yu Lee, Patrick W Gallagher, and Zhuowen Tu. Generalizing pooling functions in convolutional neural networks: Mixed, gated, and tree. In *AISTATS*, pp. 464–472, 2016. 4, 6

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017. 12

Béatrice Pesquet-Popescu and Vincent Bottreau. Three-dimensional lifting schemes for motion compensated video compression. In *IEEE International Conference on Acoustics, Speech, and Signal Processing*, 2001. 1

Oren Rippel, Jasper Snoek, and Ryan P Adams. Spectral representations for convolutional neural networks. In *NeurIPS*, 2015. 4, 6

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *MICCAI*, 2015. 4

Faraz Saeedan, Nicolas Weber, Michael Goesele, and Stefan Roth. Detail-preserving pooling in deep networks. In *CVPR*, 2018. 1, 2, 4, 6

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *CVPR*, 2018. 5

Dominik Scherer, Andreas Müller, and Sven Behnke. Evaluation of pooling operations in convolutional architectures for object recognition. In *ICANN*, pp. 92–101, 2010. 4

Wenzhe Shi, Jose Caballero, Ferenc Huszár, Johannes Totz, Andrew P Aitken, Rob Bishop, Daniel Rueckert, and Zehan Wang. Real-time single image and video super-resolution using an efficient sub-pixel convolutional neural network. In *CVPR*, 2016. 4

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *ICLR*, 2015. 5, 12

Jost Tobias Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for simplicity: The all convolutional net. In *ICLR*, 2015. 1, 5, 6

Wim Sweldens. The lifting scheme: A construction of second generation wavelets. *SIAM journal on mathematical analysis*, 29(2):511–546, 1998. 1, 2, 11, 12

Travis Williams and Robert Li. Wavelet pooling for convolutional neural networks. In *ICLR*, 2018. 4, 6

Yonghong Wu, Quan Pan, Hongcai Zhang, and Shaowu Zhang. Adaptive denoising based on lifting scheme. In *International Conference on Signal Processing*, 2004. 1

Matthew D Zeiler and Rob Fergus. Stochastic pooling for regularization of deep convolutional neural networks. *arXiv preprint arXiv:1301.3557*, 2013. 4

Shuangfei Zhai, Hui Wu, Abhishek Kumar, Yu Cheng, Yongxi Lu, Zhongfei Zhang, and Rogerio Feris. S3pool: Pooling with stochastic spatial sampling. In *CVPR*, 2017. 4, 6

Richard Zhang. Making convolutional networks shift-invariant again. *ICML*, 2019. 3, 4, 6, 7, 8

Jiaojiao Zhao, Li Liu, Cees GM Snoek, Jungong Han, and Ling Shao. Pixel-level semantics guided image colorization. *BMVC*, 2018. 4

Yi Zheng, Ruijin Wang, and Jianping Li. Nonlinear wavelets and bp neural networks adaptive lifting scheme. In *International Conference on Apperceiving Computing and Intelligence Analysis Proceeding*, pp. 316–319, 2010. 3

Figure 6: Comparisons between MaxPool and LiftDownPool, MaxUpPool and LiftUpPool. Max-Pool looses details. With the recorded maximum indices, MaxUpPool generates a very sparse output. LiftDownPool decomposes the input into an approximation and several details sub-bands. It realizes a pooling by summing up all sub-bands. LiftUpPool produces a refined output by performing LiftDownPool backwards.

A   APPENDIX

We show additional analysis and results for robustness and semantic segmentation in this part.

LiftDownPool vs. MaxPool   We make a schematic diagram in Figure 6 for further illustrating the difference between MaxPool and LiftDownPool, MaxUpPool and LiftUpPool. Taking kernel size 2, stride 2 as an example, MaxPool selects the maximum activations in a local neighbourhood. Hence, it looses 75% information. The lost details could be important for image recognition. LiftDownPool decomposes a feature map into LL, LH, HL and HH. LL containing low-pass coefficients is an approximation of the input. It is designed for capturing correlated structures of the input. Other sub-bands contain detail coefficients along different directions. The pooling is implemented by summing up all the sub-bands. The final pooled result containing both the approximation and details is expected to be more effective for image classification.

LiftUpPool vs. MaxUpPool   The pooling function in MaxPool is not invertible. MaxPool records the maximum indices for performing the corresponding MaxUpPool. MaxUpPool takes the activations at the corresponding positions for the recorded maximum indices on the output. For other indices, there will be zeros. The final upsampled output has many 'holes'. On the contrary, the pooling functions in LiftDownPool is invertible. Leveraging the property, LiftUpPool, performing a LiftDownPool backwards, is able to generate a refined output from an input, including the recorded details.

Anti-aliasing   LiftDownPool effectively reduces aliasing following the Lifting Scheme (Sweldens, 1998) compared to naive down-sizing. Figure 7 provides a simple illustration. The bold line is an original signal x. According to Eq 1, the predictor $\mathcal{P}(\cdot)$ for the odd part x_{2k+1} could easily take the average of its two even neighbors.

$$d_k = x_{2k+1} - (x_{2k} + x_{2k+2})/2 \qquad (10)$$

Thus, if x is linear in a local area, the detail d_k is zero. The prediction step takes care of some of the spatial correlation. If an approximation s of the original signal x is simply taken from the even part x^e, it is really down-sizing the signal shaped in the red line. There is serious aliasing. The running average of x^e is not the same as that of the original signal x. The updater $\mathcal{U}(\cdot)$ in Eq 2 is for correcting this by replacing x^e with smoothed values s. Specifically, $\mathcal{U}(\cdot)$ restores the correct running average and thus reduces aliasing.

$$s_k = x_{2k} + (d_{k-1} + d_k)/4 \qquad (11)$$

As shown in Figure 7, d_k is the difference between the odd sample x_{2k+1} and the average of two even samples. This causes a loss $d_k/2$ in the area with the red shade. To preserve the running average, this

Figure 7: Illustration of how LiftDownPool reduces aliasing compared to down-sizing (Sweldens, 1998). Bold line means original signal. Red line is after down-sizing. Blue line is after LiftDownPool. The blue and bold lines cover the same area.

area is redistributed to the two neighbouring even samples x_{2k} and x_{2k+2}, which shapes a coarser piecewise linear signal s in the blue line. The signal after LiftDownPool, drawn in blue line, covers the same area with the original signal bold line. LiftDownPool reduces aliasing compared to the down-sizing drawn in the red line.

Experiment Settings For the VGG13 (Simonyan & Zisserman, 2015) network trained on CIFAR-100, it is optimized by SGD with a batch size of 100, weight decay of 0.0005, momentum of 0.9. The learning rate starts from 0.1 and is reduced by multiplying 0.1 after 80 and 120 epochs for a total of 160 epochs. We train ResNets for 100 epochs and MobileNet for 150 epochs on ImageNet, following the standard training recipe from the public PyTorch (Paszke et al., 2017) repository.

Out-of-distribution Robustness We show the robustness of pooling methods per kind of corruption and perturbation in Figure 8. Corruption Error (*CE*) is the metric of the robustness to corruptions on ImageNet-C. And Flip Rate (*FR*) is reported for the robustness to perturbation on ImageNet-P. Following (Hendrycks & Dietterich, 2019), we report both unnormalized raw values and normalized values by AlexNet's *CE* and *FR*. Lower values are better. As seen in Figure 8(a) and (c), LiftDownPool gets the lowest *CE* for most of the "high frequency" corruptions including gaussian noise and spatter, as well as the "low frequency" corruptions such as motion blur, zoom blur. In Figure 8(b) and (d), it clearly shows LiftDownPool has less sensitivity to most of the perturbations such as speckle noise and gaussian blur.

Visualiztion of Up-pooling In Figure 9, we show the feature map for each predicted category from the last layer of SegNet using varying up-pooling methods. Using MaxUpPool, the feature maps look noisy and less continuous due to the fact that MaxUpPool generates the output with many 'zeros', where there is no information. By applying a BlurPool following the MaxUpPool, the feature maps turn more smooth, while still with less details. LiftUpPool, benefiting from the recorded details during LiftDownPool, produces finer feature maps for each category. It has smooth edges, continuous segmentation maps and less aliasing.

Figure 8: Comparisons between the robustness of various pooling methods to per kind of corruption on ImageNet-C and perturbation on ImageNet-P. LiftDownPool presents stronger robustness to almost all the corruptions and perturbations.

Figure 9: Visualization of feature maps per-predicted-category from the last layer of SegNet. LiftUpPool generates more precise predictions for each category.