Answer Only as Precisely as Justified: Calibrated Claim-Level Specificity Control for Agentic Systems

Tianyi Huang [1] **Samuel Xu** [2] **Jason Tansong Dang** [2] **Samuel Yan** [2] **Kimberley Yin** [2]

Abstract

Agentic systems often fail not by being entirely wrong, but by being too precise: a response may be generally useful while particular claims exceed what the evidence supports. We study this failure mode as *overcommitment control* and introduce *compositional selective specificity* (CSS), a post-generation layer that decomposes an answer into claims, proposes coarser backoffs, and emits each claim at the most specific calibrated level that appears admissible. The method is designed to express uncertainty as a local semantic backoff rather than as a whole-answer refusal. Across a full LongFact run and HotpotQA pilots, calibrated CSS improves the risk-utility trade-off of fixed drafts. On the full LongFact run, it raises overcommitment-aware utility from 0.846 to 0.913 relative to the no-CSS output while achieving 0.938 specificity retention. These results suggest that claim-level specificity control is a useful uncertainty interface for agentic systems and a target for future distribution-free validity layers.

1. Introduction

Modern language-model systems increasingly retrieve evidence, call tools, and assemble multi-claim artifacts for users or downstream components (Lewis et al., 2021; Karpas et al., 2022; Yao et al., 2023; Schick et al., 2023). In such systems, uncertainty is not simply a confidence score attached to a final string. It is a control signal that should influence what the system says, how specifically it says it, and which semantic commitments are safe to propagate. This motivates a shift from answer-level uncertainty to *compositional uncertainty*: uncertainty over the claims that make up an agent output.

A common failure mode in this setting is *overcommitment*. The response may be directionally correct but unjustifiably specific: it may identify the relevant event while attaching an unsupported date, summarize the right trend while supplying an exact number the evidence does not warrant, or name the correct entity while asserting an unsupported subtype or relation. Outright refusal is often too conservative in these cases, yet the original wording still overstates what is known. The practical question is therefore not only whether the model should answer, but also how much semantic precision it should retain for each emitted claim.

This question sits at the intersection of selective prediction, calibration, and factuality control. Selective prediction and conformal prediction provide principled ways to abstain or broaden prediction sets when uncertainty is high (Geifman & El-Yaniv, 2017; Angelopoulos & Bates, 2022; Quach et al., 2024; Mohri & Hashimoto, 2024). Long-form factuality work has shown that answer-level judgments are often too coarse because generations mix supported and unsupported statements within the same response (Min et al., 2023; Wei et al., 2024). Recent specificity-aware methods further suggest that less-specific rewrites can be more useful than all-or-nothing abstention (Jiang et al., 2025; Goren et al., 2026). We build on this line of work, but focus on agentic outputs as compositional objects whose parts may warrant different levels of commitment.

We propose *compositional selective specificity* (CSS). Given a draft answer, CSS decomposes it into claims. For each claim, it constructs a small specificity ladder consisting of the original fine-grained statement, a coarser backoff, and omission. A support estimator scores which candidates appear justified by the available evidence, and a selector emits the most specific admissible option. The resulting response can remain precise where evidence is strong, back off where support is partial, and omit only claims whose specificity cannot be justified. Uncertainty is thereby expressed as a structured editing policy over semantic granularity rather than as vague hedging or global refusal.

The deployed method in this paper is *calibrated* CSS. Calibration is the operational core: it turns noisy support scores into a claim-selection rule. We compare calibrated CSS against no post-processing, whole-answer abstention, claim

[1]Ryquo [2]App-In Club. Correspondence to: Tianyi Huang <tianyi@ryquo.com>.

Accepted to the ICML 2026 Workshop on Statistical Frameworks for Uncertainty in Agentic Systems, Seoul, South Korea, 2026.

deletion, and a fixed-threshold CSS ablation. We also report oracle CSS as a non-deployable upper bound, using it to estimate the headroom available if support estimation were nearly perfect.

Our empirical evidence comes from two benchmarks: Long-Fact and HotpotQA (Wei et al., 2024; Yang et al., 2018). The complete LongFact run is the main scale evaluation; it compares calibrated CSS against the above baselines on all 2,280 LongFact prompts under a claimwise protocol. The LongFact pilot and the GPT-5.4 HotpotQA pilot provide smaller controlled checks of the calibration effect on fixed drafts. The Claude Sonnet 4.6 HotpotQA pilot provides an auxiliary check under a different frontier model.

The paper makes three main contributions. First, it formulates overcommitment control as a claim-level uncertainty problem for agentic outputs. Second, it presents a black-box CSS pipeline whose deployable form is a calibrated selector over claim-level backoff choices. Third, it provides evidence that calibration can preserve substantially more supported specificity than fixed-threshold or coarse-abstention alternatives, especially in the long-form multi-claim settings. We view these results as a step toward, and not a substitute for, stronger finite-sample guaranties.

2. Related Work

Selective prediction and conformal uncertainty. Selective prediction equips a model with a reject option, trading coverage for lower risk on retained examples (Geifman & El-Yaniv, 2017). Conformal prediction generalizes this idea by wrapping black-box predictors with distribution-free uncertainty sets and abstention mechanisms (Angelopoulos & Bates, 2022). For language generation, conformal language modeling adapts this viewpoint to structured natural-language outputs, while conformal factuality studies correctness guarantees for language-model responses (Quach et al., 2024; Mohri & Hashimoto, 2024). Our setting is adjacent but distinct: rather than accepting or rejecting an entire response, we control the granularity of each claim within that response.

Long-form factuality and verification. Long-form generations routinely contain mixtures of supported and unsupported content, which makes binary answer-level judgments inadequate. FActScore formalizes factual precision through atomic facts, and LongFact scales this perspective with claim decomposition and search-based checking (Min et al., 2023; Wei et al., 2024). Verification-oriented methods such as SelfCheckGPT and Chain-of-Verification similarly emphasize post-hoc verification rather than raw generation confidence (Manakul et al., 2023; Dhuliawala et al., 2023). Our work shares the claimwise lens, but asks a different control question: once support is heterogeneous within a re-

sponse, how should the answer be edited so that unsupported specificity is removed while useful content is preserved?

Specificity-aware control. The closest prior work studies uncertainty-aware rewrites that trade specificity for reliability. Conformal Linguistic Calibration connects factuality and imprecision through a conformal answer-set view, while Selective Abstraction shows that less-specific reformulations can outperform pure claim removal in long-form generation (Jiang et al., 2025; Goren et al., 2026). We are sympathetic to both views. Our emphasis differs in two ways. First, we target agentic deployment: the output is a structured allocation of semantic commitment that downstream modules could use for escalation, auditing, or re-retrieval. Second, we emphasize calibration as the deployable mechanism that selects a useful operating point for a fixed support estimator.

3. Problem Setup

Let x denote a prompt, E the evidence available for that prompt, and A a draft answer produced by an upstream generator. A claim extractor maps A to atomic claims,

$$A \mapsto (c_1, \ldots, c_m). \tag{1}$$

In our implementation, each claim c_i is paired with a coarse backoff $\tilde{c}_i$ and omission as the null action. Thus each claim has three possible output levels,

$$\pi_i \in \{\text{fine}, \text{coarse}, \text{omit}\}. \tag{2}$$

The fine level emits the original claim, the coarse level emits a less-specific reformulation, and the omit level emits nothing.

A support estimator assigns scores $s_i^{\text{fine}}, s_i^{\text{coarse}} \in [0, 1]$ to the non-null candidates. For offline evaluation, we also obtain binary support labels $y_i^{\text{fine}}, y_i^{\text{coarse}} \in \{0, 1\}$ indicating whether the corresponding formulation is supported by the evidence. These labels are used only for scoring and for the oracle upper bound; they are not available to the deployable selector.

Definition 3.1 (Overcommitment). A selected claim is *overcommitted* if it is emitted at the chosen specificity level but unsupported by the evidence at that level.

The no-CSS identity policy keeps every original fine-grained claim. CSS instead chooses one action π_i for each claim. We define specificity weights

$$w(\text{omit}) = 0, \qquad w(\text{coarse}) = \gamma, \qquad w(\text{fine}) = 1, \tag{3}$$

with $\gamma = 0.6$ in all experiments. For convenience, define $y_i^{\text{omit}} = 0$, let $e_i = \mathbf{1}\{\pi_i \neq \text{omit}\}$, and write $y_i^{\text{sel}} := y_i^{\pi_i}$

for the support label of the emitted level. Aggregating over all claims in an evaluation split, we report

$$\text{Prec} = \frac{\sum_i e_i y_i^{\text{sel}}}{\sum_i e_i}, \tag{4}$$

$$\text{Ret} = \frac{1}{m} \sum_i w(\pi_i), \tag{5}$$

$$\text{SuppSpec} = \frac{1}{m} \sum_i w(\pi_i) y_i^{\text{sel}}, \tag{6}$$

$$\text{OAU} = \frac{1}{m} \sum_i \left(w(\pi_i) y_i^{\text{sel}} - e_i(1 - y_i^{\text{sel}}) \right). \tag{7}$$

Precision is defined when at least one claim is emitted, as in all reported runs. The OAU score rewards supported specificity, assigns zero to omitted claims, and penalizes unsupported emitted claims.

4. Method: Calibrated Compositional Selective Specificity

4.1. Pipeline

CSS is a post-generation layer. It does not retrain the upstream model or alter the retrieval stack. Instead, it edits a fixed draft answer through four stages.

Draft generation. An upstream language model produces an initial response given the prompt and available evidence.

Claim extraction and backoff proposal. The draft answer is decomposed into individual claims. For each claim, the system proposes a coarse backoff that preserves the central content while removing potentially unsupported detail. The selector then chooses among three actions: keep the fine claim, emit the coarse backoff, or omit the claim.

Support scoring. Each fine or coarse candidate is evaluated against the evidence. Our implementation combines language-model-based support judgments with lightweight lexical and entity-based features through a hybrid scorer. Its precise combiner is not the contribution here: within each run, the scorer is fit once and then held fixed across all policy comparisons. The contribution of this paper is the selection layer that consumes those support scores, not a new verifier.

Claimwise selection. The selector chooses the level for each claim. If the fine claim clears the fine threshold, it is kept. Otherwise, if the coarse backoff clears the coarse threshold, the claim is emitted in coarse form. If neither clears, the claim is omitted.

4.2. Policies and Baselines

No CSS. This identity baseline emits every original fine-grained claim. It measures how much overcommitment is present before claim-level control.

Whole-answer abstention. This coarse baseline applies a response-level accept-or-abstain decision. Operationally, it either returns the draft unchanged or emits no answer at all; it does not perform claimwise editing. It is included to quantify the cost of treating uncertainty as a whole-answer event rather than as a claimwise editing problem.

Claim-drop. This baseline omits claims that do not clear a support threshold but does not emit a coarser alternative. Operationally, it either keeps the original fine-grained claim or deletes it; it never emits a coarse backoff. It tests whether CSS helps beyond deletion by preserving partially supported content through backoff.

Uncalibrated CSS. This deployable ablation uses fixed thresholds for all runs. In our implementation, the defaults are $\tau_{\text{fine}} = 0.78$ and $\tau_{\text{coarse}} = 0.58$. It does not adapt thresholds to the score distribution of a run.

Calibrated CSS. This is the deployed method. A held-out calibration split is used to choose thresholds $(\tau_{\text{fine}}, \tau_{\text{coarse}})$ that maximize utility subject to a conservative upper bound on unsupported emissions. For each threshold pair, we count unsupported emitted claims k and emitted claims n on the calibration set, form a one-sided Clopper–Pearson upper confidence bound (Clopper & Pearson, 1934), and keep only pairs satisfying

$$\text{CPUpper}(k, n; \delta) \le \alpha, \tag{8}$$

with $\alpha = 0.10$ and $\delta = 0.05$ in the reported runs. In the reported runs, at least one threshold pair satisfied this constraint, so the degenerate no-valid-pair case did not arise. Among valid pairs, the selector chooses the one with the highest calibration OAU. This makes calibration explicit, conservative, and aligned with the claim-level utility used in evaluation. Because the same calibration split is used to select among threshold pairs, we treat this step as a conservative calibration rule rather than as a full end-to-end conformal guarantee.

Oracle CSS. This non-deployable upper bound selects the fine claim if it is evaluation-supported, otherwise the coarse claim if the coarse version is evaluation-supported, otherwise omission. Oracle CSS estimates the headroom available if support estimation were much stronger; it is not a competing method.

Two points are important for interpretation. First, calibrated CSS is the method we advocate as a deployable uncer-

Figure 1. Illustrative behavior of claim-level specificity control. The evidence supports that the agreement was signed in Geneva, but does not support the exact year in the draft. A whole-answer abstention policy returns no answer, while a conservative fixed-threshold CSS selector may omit the claim. Calibrated CSS can instead back off only the unsupported detail and preserve the supported claim at a coarser specificity level. The example illustrates the intended role of CSS: expressing uncertainty through localized semantic backoff rather than global refusal or unsupported precision.

tainty layer. Second, all policies operate on fixed drafts within a run. The relevant comparison is therefore between post-generation selection policies, not between different generators.

5. Experimental Setup

LongFact full run. Our main experiment uses all 2,280 LongFact prompts introduced by Wei et al. (2024). Because our interest is claim-level specificity control rather than the SAFE/F1@K benchmark pipeline, we evaluated these prompts with the claimwise protocol. The run uses a five-fold out-of-fold evaluation: every prompt is scored in a held-out fold, while scorer fitting and threshold calibration are performed on the remaining folds. The completed run contains 11,705 extracted claims and uses GPT-5.4, accessed through the OpenAI API, as the draft generator (OpenAI, 2026).

Pilot runs. We also report a 200-example LongFact pilot and two 200-example HotpotQA validation pilots (Yang et al., 2018). Each pilot is split into 30 fit, 30 calibration, and 140 test examples. The LongFact pilot contains 757 extracted claims on the test split; the GPT-5.4 HotpotQA pilot contains 470 claims (OpenAI, 2026); and the Claude Sonnet 4.6 HotpotQA pilot, run through Anthropic's API, contains 648 claims (Anthropic, 2026). Claim counts differ because claim extraction is performed on generated drafts.

What is being compared? The full-run comparison asks whether calibrated CSS improves the specificity–risk trade-

off relative to no post-processing, whole-answer abstention, claim deletion, and fixed-threshold CSS. The pilot comparisons ask whether the calibration effect replicates on smaller fixed-draft subsets. Oracle rows are reported as ceilings.

LongFact protocol. LongFact was introduced together with SAFE and F1@K as its official benchmark machinery (Wei et al., 2024). Our goal here is narrower: we evaluate claim-level post-generation editing on LongFact prompts. Concretely, extracted fine/coarse claim candidates are assigned binary support labels with respect to the prompt evidence, and all reported LongFact metrics are computed from these claim-level support labels. The LongFact numbers in this paper should therefore be read as results under the claimwise protocol, not as SAFE/F1@K leaderboard numbers.

6. Results

We begin with the full LongFact run, which is the paper's main scale evaluation. The no-CSS draft keeps all 11,705 extracted claims and therefore achieves perfect specificity retention by construction, but only 0.9230 support precision and 0.8460 OAU. Calibrated CSS instead emits 11,085 claims, raises support precision to 0.9865, and improves OAU to 0.9130 while still achieving 0.9381 specificity retention. The interesting point is that the selector becomes safer while preserving most of the useful content in the original drafts.

The baseline comparisons clarify what calibrated CSS is

Figure 2. Full LongFact policy comparison by overcommitment-aware utility (OAU). Calibrated CSS is the deployed selector, gray bars are reference baselines, and the dark bar is the non-deployable oracle ceiling.

buying. As Figure 2 and Table 1 show, whole-answer abstention is not a competitive route to reliability: although it attains high support precision, it discards too much content, reducing specificity retention to 0.6292 and OAU to 0.6072. Claim-drop is much stronger, reaching 0.9877 support precision and 0.9019 OAU, but calibrated CSS still improves upon it by preserving partially supported content through coarse backoff rather than deleting it outright. Uncalibrated CSS is the strongest conservative deployable baseline, with 0.9934 support precision, but it achieves only 0.8633 specificity retention and reaches 0.8521 OAU. Relative to this fixed-threshold selector, calibration gives up 0.0069 support-precision points while gaining 0.0609 OAU points and 0.0675 supported-specificity points.

This is the central empirical result of the paper. On the full LongFact run, a calibrated claim-level selector improves over the original draft, a whole-answer abstention baseline, a deletion-only baseline, and a fixed-threshold CSS ablation on the same fixed full-run drafts. The relevant operating regime is therefore not perfect precision at any cost, but high precision together with high retained supported specificity.

6.1. Calibration on Pilots

The pilot runs ask a narrower question: given fixed drafts, does calibration materially improve the selector? Across all three pilots, the answer is yes.

On the LongFact pilot, calibration raises specificity retention from 0.5900 to 0.9411 and OAU from 0.5836 to 0.9289, while support precision decreases only from 0.9958 to 0.9931. On the GPT-5.4 HotpotQA pilot, calibration raises specificity retention from 0.6209 to 0.9000, supported specificity from 0.6111 to 0.8809, and OAU from 0.5962 to 0.8617, while support precision moves only from 0.9829 to 0.9790. The Claude Sonnet 4.6 HotpotQA pilot shows a similar pattern: calibration increases specificity retention from 0.7191 to 0.9475, supported specificity from 0.7142

to 0.9395, and OAU from 0.7080 to 0.9302, while support precision decreases from 0.9936 to 0.9904.

The consistency of this pattern matters more than any single pilot in isolation. In all three cases, the fixed-threshold selector identifies an ultra-safe but overly conservative operating point. Calibration then moves the selector to a much more useful part of the trade-off curve, preserving substantially more supported detail while paying only a small precision cost. This is a lesson of the paper: calibration is not a cosmetic refinement, but the mechanism that converts noisy claimwise support scores into a practical uncertainty layer.

6.2. Oracle Ceilings Quantify Headroom

Oracle CSS should be interpreted only as a ceiling. On the full LongFact run, oracle CSS reaches 0.9359 OAU with perfect support precision, compared with 0.9130 for calibrated CSS. This gap is meaningful but not large, suggesting that the calibrated selector already captures a substantial fraction of the available benefit and that further gains will depend primarily on stronger support estimation. The pilot ceilings tell a similar story: oracle CSS reaches 0.9440 OAU on the LongFact pilot, 0.8996 on the GPT-5.4 HotpotQA pilot, and 0.9599 on the Claude Sonnet 4.6 HotpotQA pilot.

These results show that the underlying claim-level backoff problem is structurally favorable: when support information is sufficiently accurate, a selector can preserve most of a response's specificity without paying a penalty in unsupported detail.

6.3. What the Completed Runs Show

Taken together, the completed runs support four conclusions. First, claim-level specificity control remains effective at the full LongFact scale. Second, calibration is the central deployable lever: across the full run and all three pilots, calibrated CSS consistently trades a small amount of precision for a much larger gain in retained supported specificity. Third, coarse answer-level abstention and deletion-only control are informative baselines, but they are not adequate substitutes for compositional specificity control. Fourth, the oracle ceilings indicate that meaningful headroom remains, especially if support scoring improves.

7. Discussion and Limitations

The paper's framing has two main implications. Methodologically, it suggests that answer-level accuracy is often the wrong object for evaluating post-generation uncertainty layers. The more relevant question is whether the system says *only as much as it knows*. Our metrics make that question explicit by separating retained specificity from supported specificity and by penalizing unsupported emitted claims.

Table 1. Claim-level results from the completed runs. Calibrated CSS is the deployed method. Uncalibrated CSS is the fixed-threshold ablation. Oracle CSS is a non-deployable upper bound.

Dataset / run	Policy	Ex.	Claims emitted / total	Support precision	Specificity retention	Supported specificity	OAU
LongFact full / GPT-5.4	No CSS	2280	11705 / 11705	0.9230	1.0000	0.9230	0.8460
LongFact full / GPT-5.4	Whole abstain	2280	7365 / 11705	0.9825	0.6292	0.6182	0.6072
LongFact full / GPT-5.4	Claim-drop	2280	10823 / 11705	0.9877	0.9246	0.9133	0.9019
LongFact full / GPT-5.4	Uncalibrated	2280	10948 / 11705	0.9934	0.8633	0.8583	0.8521
LongFact full / GPT-5.4	Calibrated	2280	11085 / 11705	0.9865	0.9381	0.9258	0.9130
LongFact full / GPT-5.4	Oracle	2280	11056 / 11705	1.0000	0.9359	0.9359	0.9359
LongFact pilot / GPT-5.4	Uncalibrated	140	721 / 757	0.9958	0.5900	0.5876	0.5836
LongFact pilot / GPT-5.4	Calibrated	140	724 / 757	0.9931	0.9411	0.9355	0.9289
LongFact pilot / GPT-5.4	Oracle	140	723 / 757	1.0000	0.9440	0.9440	0.9440
HotpotQA pilot / GPT-5.4	Uncalibrated	140	409 / 470	0.9829	0.6209	0.6111	0.5962
HotpotQA pilot / GPT-5.4	Calibrated	140	429 / 470	0.9790	0.9000	0.8809	0.8617
HotpotQA pilot / GPT-5.4	Oracle	140	426 / 470	1.0000	0.8996	0.8996	0.8996
HotpotQA pilot / Claude Sonnet 4.6	Uncalibrated	140	622 / 648	0.9936	0.7191	0.7142	0.7080
HotpotQA pilot / Claude Sonnet 4.6	Calibrated	140	628 / 648	0.9904	0.9475	0.9395	0.9302
HotpotQA pilot / Claude Sonnet 4.6	Oracle	140	630 / 648	1.0000	0.9599	0.9599	0.9599

Systems-wise, claim-level specificity control creates an uncertainty interface that downstream components can use directly. Claims that survive at fine granularity can move forward with less friction; claims that are downgraded or omitted can trigger re-retrieval, human review, or escalation to a stronger verifier. In this sense, CSS is a modular control layer for multi-stage systems.

Several limitations remain. First, the LongFact experiment uses the claimwise evaluation pipeline on LongFact prompts rather than the SAFE/F1@K pipeline (Wei et al., 2024). This is appropriate for the paper's goal—evaluating claim-level post-generation editing rather than whole-response benchmark ranking—but it means the LongFact numbers should be interpreted accordingly. Second, the pilot comparisons use 200-example subsets with 140 evaluated test examples. Third, oracle CSS is only an upper bound and should not be mistaken for deployable performance. Fourth, the selector can inherit errors from claim extraction, back-off generation, and support estimation. Finally, the present paper does not study sequential or continuously monitored settings.

We view these limitations as next steps in the problem formulation. The completed runs suggest that claimwise specificity control is a meaningful and measurable uncertainty problem. The next stage is to attach stronger statistical guarantees to this control layer and to evaluate it inside broader agent pipelines with tool use, escalation, and external feedback loops.

8. Conclusion

Many agentic failures are failures of specificity, not simply failures of correctness. This paper treats that observation as a control problem: for each claim in a generated response, decide the most precise formulation justified by the available evidence. Calibrated CSS is a step in this direction. It is empirically useful on the completed LongFact and HotpotQA runs, while still leaving room for stronger support estimation and formal risk guarantees. We hope the framing helps connect long-form factuality, selective prediction, and uncertainty-aware agent design around a common question: not only whether a system should answer, but how precise the truth allows it to be.

Impact Statement

This work studies a mechanism for reducing unsupported specificity in language-model outputs. Such mechanisms can improve reliability in reporting, question answering, and decision support by preventing systems from stating more than their evidence warrants. However, claim-level backoff could also be misused to make weak systems appear trustworthy through vagueness alone. For that reason, we emphasize joint reporting of support precision, retained specificity, and supported specificity, rather than rewarding imprecision for its own sake. We do not view CSS as a substitute for domain validation, expert review, or stronger verification in high-stakes settings.

References

Angelopoulos, A. N. and Bates, S. A gentle introduction to conformal prediction and distribution-free uncertainty quantification, 2022. URL https://arxiv.org/abs/2107.07511.

Anthropic. Introducing claude sonnet 4.6, February 2026. URL https://www.anthropic.com/news/claude-sonnet-4-6.

Clopper, C. J. and Pearson, E. S. The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika*, 26(4):404–413, 1934. ISSN 00063444, 14643510. URL http://www.jstor.org/stable/2331986.

Dhuliawala, S., Komeili, M., Xu, J., Raileanu, R., Li, X., Celikyilmaz, A., and Weston, J. Chain-of-verification reduces hallucination in large language models, 2023. URL https://arxiv.org/abs/2309.11495.

Geifman, Y. and El-Yaniv, R. Selective classification for deep neural networks, 2017. URL https://arxiv.org/abs/1705.08500.

Goren, S., Galil, I., and El-Yaniv, R. When should llms be less specific? selective abstraction for reliable long-form text generation, 2026. URL https://arxiv.org/abs/2602.11908.

Jiang, Z., Liu, A., and Durme, B. V. Conformal linguistic calibration: Trading-off between factuality and specificity, 2025. URL https://arxiv.org/abs/2502.19110.

Karpas, E., Abend, O., Belinkov, Y., Lenz, B., Lieber, O., Ratner, N., Shoham, Y., Bata, H., Levine, Y., Leyton-Brown, K., Muhlgay, D., Rozen, N., Schwartz, E., Shachaf, G., Shalev-Shwartz, S., Shashua, A., and Tenenholtz, M. Mrkl systems: A modular, neuro-symbolic architecture that combines large language models, external knowledge sources and discrete reasoning, 2022. URL https://arxiv.org/abs/2205.00445.

Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., tau Yih, W., Rocktäschel, T., Riedel, S., and Kiela, D. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021. URL https://arxiv.org/abs/2005.11401.

Manakul, P., Liusie, A., and Gales, M. J. F. Selfcheck-gpt: Zero-resource black-box hallucination detection for generative large language models, 2023. URL https://arxiv.org/abs/2303.08896.

Min, S., Krishna, K., Lyu, X., Lewis, M., tau Yih, W., Koh, P. W., Iyyer, M., Zettlemoyer, L., and Hajishirzi, H. Factscore: Fine-grained atomic evaluation of factual precision in long form text generation, 2023. URL https://arxiv.org/abs/2305.14251.

Mohri, C. and Hashimoto, T. Language models with conformal factuality guarantees, 2024. URL https://arxiv.org/abs/2402.10978.

OpenAI. Introducing gpt-5.4, March 2026. URL https://openai.com/index/introducing-gpt-5-4/.

Quach, V., Fisch, A., Schuster, T., Yala, A., Sohn, J. H., Jaakkola, T. S., and Barzilay, R. Conformal language modeling, 2024. URL https://arxiv.org/abs/2306.10193.

Schick, T., Dwivedi-Yu, J., Dessì, R., Raileanu, R., Lomeli, M., Zettlemoyer, L., Cancedda, N., and Scialom, T. Toolformer: Language models can teach themselves to use tools, 2023. URL https://arxiv.org/abs/2302.04761.

Wei, J., Yang, C., Song, X., Lu, Y., Hu, N., Huang, J., Tran, D., Peng, D., Liu, R., Huang, D., Du, C., and Le, Q. V. Long-form factuality in large language models, 2024. URL https://arxiv.org/abs/2403.18802.

Yang, Z., Qi, P., Zhang, S., Bengio, Y., Cohen, W. W., Salakhutdinov, R., and Manning, C. D. Hotpotqa: A dataset for diverse, explainable multi-hop question answering, 2018. URL https://arxiv.org/abs/1809.09600.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., and Cao, Y. React: Synergizing reasoning and acting in language models, 2023. URL https://arxiv.org/abs/2210.03629.