Sym-NCO: Leveraging Symmetricity for Neural Combinatorial Optimization

Abstract

Deep reinforcement learning (DRL)-based combinatorial optimization (CO) methods (i.e., DRL-NCO) have shown significant merit over the conventional CO solvers as DRL-NCO is capable of learning CO solvers less relying on problem-specific expert domain knowledge (heuristic method) and supervised labeled data (supervised learning method). This paper presents a novel training scheme, Sym-NCO, which is a regularizer-based training scheme that leverages universal symmetricities in various CO problems and solutions. Leveraging symmetricities such as rotational and reflectional invariance can greatly improve the generalization capability of DRL-NCO because it allows the learned solver to exploit the commonly shared symmetricities in the same CO problem class. Our experimental results verify that our Sym-NCO greatly improves the performance of DRL-NCO methods in four CO tasks, including traveling salesman problem (TSP), capacitated vehicle routing problem (CVRP), prize collecting TSP (PCTSP), and orienteering problem (OP), without utilizing problem-specific expert domain knowledge. Remarkably, Sym-NCO outperformed not only the existing DRL-NCO methods but also a competitive conventional solver, the iterative local search (ILS), in PCTSP at $240\times$ faster speed. Source code will be available after the decision is made.

1 Introduction

Combinatorial optimization problems (COPs), mathematical optimization problems on discrete input space, have been used to solve numerous valuable applications, including vehicle routing problems (VRPs) [1, 2], drug discovery [3, 4], and semi-conductor chip design [5, 6, 7]. However, finding an optimal solution to COP is difficult due to its NP-hardness. Therefore, computing near-optimal solutions fast is essential from a practical point of view.

Conventionally, COPs are solved by integer program (IP) solvers or hand-crafted (meta) heuristics. Recent advances in computing infrastructures and deep learning have conceived the field of neural combinatorial optimization (NCO), a deep learning-based COP solving strategy. Depending on the training scheme, NCO methods are generally classified into supervised learning [8, 9, 10, 11, 12] and reinforcement learning (RL) [13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25]. Depending on the solution generation scheme, NCO methods are also classified into improvement [15, 14, 13, 26, 16, 17, 23] and constructive heuristics [18, 19, 20, 21, 22, 24, 25]. Among the NCO approaches, deep RL (DRL)-based constructive heuristics (i.e., DRL-NCO) are favored over conventional approaches for two major reasons. First, RL can be applied to train the NCO model in less explorered CO tasks because training RL does not require domain expert knowl-

(a) Problem symmetricity   (b) Solution symmetricity

Figure 2: Illustration of symmetricities in CO (exampled in TSP)

edge and supervised labels from a verified solver. Second, it is easy to produce qualified feasible solutions because the constructive process can easily avoid constraint-violated actions [19]. Despite the strength of DRL-NCO, there exists a performance gap between the state-of-the-art conventional heuristics and DRL-NCO. In an effort to close the gap, there have been attempts to employ problem-specific heuristics to existing DRL-NCO methods [21, 27]. However, devising a general training scheme to improve the performance of DRL-NCO still remains challenging.

In this study, we propose the Symmetric Neural Combinatorial Optimization (Sym-NCO), a general training scheme applicable to universal CO problems. Sym-NCO is a regularization-based training scheme that leverages the symmetricities commonly found in COPs to increase the performance of existing DRL-NCO methods. Sym-NCO leverages two types of symmetricities innate in COP that are defined on the Euclidean graph. First, the problem symmetricity is derived from the rotational invariance of the solution; the rotated graph must exhibit the same optimal solution as the original graph as shown in Fig. 2a. Second, the solution symmetricity refers to the property that solutions have identical output values (See Fig. 2b).

To train an effective NCO solver while leveraging the symmetricities, we employ REINFORCE algorithm with the baselines terms specially designed to impart solution and problem symmetricities. REINFORCE algorithm is used because the well-known effective NCO solvers are trained by REINFORCE; thus, we can improve such solvers by just modifying their baseline with our symmetricity-considered baseline terms. Specifically, we sample multiple solutions from the transformed problems and use the average return of them. Then, REINFORCE pushes each solution sampled by the solver to excel this baseline during training, thus improving the policy and making all the solutions the same, i.e., the problem and solution symmetricities are realized.

Figure 1: Illustration that describes an advantage of Sym-NCO. An optimal training parameter is in symmetric space. Sym-NCO makes a more compact training space compared with previous DRL-NCO and supports the NCO model efficiently converges in near-optimal parameters. Equivariant neural network (ENN) scheme provably guarantees to trained in symmetric space; more expression power is needed for CO tasks.

Motivation for learning symmetricity. Leveraging symmetricity is important to train CO models for two major reasons. Firstly, symmetricity is a strong inductive bias that can support the training process of DRL by making compact training space as shown in Fig. 1. Secondly, learning symmetricity is beneficial to increasing generalization capability for unseen CO problems because symmetricity induces the invariant representation that every COP contains.

Novelty. The major novelty of the proposed learning strategy is that it can be easily used to boost the performances of the existing powerful CO models such as AM and POMO. The existing equivariant graph neural network (EGNN) [28] scheme also can leverage symmetricity; however, it requires a lot of additional effort to design high expressive model for solving CO tasks (See Fig. 1 and Section 6.1).

2 Symmetricity in Combinatorial Optimization Markov Decision Process

This section presents several symmetric characteristics found in combinatorial optimization, which is formulated in the Markov decision process. The objective of NCO is to train the θ-parameterized

solver F_θ by solving the following problem:

$$\theta^* = \arg\max_\theta \mathbb{E}_{\boldsymbol{P} \sim \rho}\big[\mathbb{E}_{\boldsymbol{\pi}(\boldsymbol{P}) \sim F_\theta(\boldsymbol{P})}\big[R(\boldsymbol{\pi}(\boldsymbol{P}))\big]\big] \tag{1}$$

where $\boldsymbol{P} = (\boldsymbol{x}, \boldsymbol{f})$ is a problem instance with the N node coordinates $\boldsymbol{x} = \{x_i\}_{i=1}^N$ and corresponding N features $\boldsymbol{f} = \{f_i\}_{i=1}^N$. The ρ is a problem generating distribution, $\boldsymbol{\pi}(\boldsymbol{P})$ is a solution of $\boldsymbol{P}$, and $R(\boldsymbol{\pi}(\boldsymbol{P}))$ is the objective value of $\boldsymbol{\pi}(\boldsymbol{P})$.

2.1 Combinatorial optimization Markov decision process

We define the combinatorial optimization Markov decision process (CO-MDP) as the sequential construction of a solution of COP. For a given $\boldsymbol{P}$, the components of the corresponding CO-MDP are defined as follows:

- **State.** The state $\boldsymbol{s}_t = (\boldsymbol{a}_{1:t}, \boldsymbol{x}, \boldsymbol{f})$ is the t-th (partially complete) solution, where $\boldsymbol{a}_{1:t}$ represents the previously selected nodes. The initial and terminal states $\boldsymbol{s}_0$ and $\boldsymbol{s}_T$ are equivalent to the empty and completed solution, respectively. In this paper, we denote the solution $\boldsymbol{\pi}(\boldsymbol{P})$ as the completed solution.

- **Action.** The action a_t is the selection of a node from the un-visited nodes (i.e., $a_t \in \mathbb{A}_t = \{\{1, ..., N\} \setminus \{\boldsymbol{a}_{1:t-1}\}\}$).

- **Reward.** The reward $R(\boldsymbol{\pi}(P))$ is the objective of COP. We assume that the reward is a function of $\boldsymbol{a}_{1:T}$ (solution sequences), $||x_i - x_j||_{i,j \in \{1,...N\}}$ (relative distances) and $\boldsymbol{f}$ (nodes features). In TSP, capacitated VRP (CVRP), and prize collecting TSPs (PCTSP), the reward is the negative of the tour length. In orienteering problem (OP), the reward is the sum of the prizes.

Having defined CO-MDP, we define the solution mapping as follows: $\boldsymbol{\pi}(P) \sim F_\theta(P) = \prod_{t=1}^T p_\theta(a_t|\boldsymbol{s}_t(P))$ where $p_\theta(a_t|\boldsymbol{s}_t(\boldsymbol{P}))$ is the policy that produces a_t at $\boldsymbol{s}_t$, and T is the maximum number of states in the solution construction process.

2.2 Symmetricities in CO-MDP

Symmetricities are found in various COPs. We conjecture that imposing those symmetricities on F_θ improves the generalization and sample efficiency of F_θ. We define the two identified symmetricities that are commonly found in various COPs:

Definition 2.1 (**Problem Symmetricity**). Problem $\boldsymbol{P}^i$ and $\boldsymbol{P}^j$ are problem symmetric ($\boldsymbol{P}^i \xleftrightarrow{\text{sym}} \boldsymbol{P}^j$) if their optimal solution sets are identical.

Definition 2.2 (**Solution Symmetricity**). Two solutions of problem P ($\boldsymbol{\pi}^i(\boldsymbol{P})$ and $\boldsymbol{\pi}^j(\boldsymbol{P})$) are solution symmetric ($\boldsymbol{\pi}^i \xleftrightarrow{\text{sym}} \boldsymbol{\pi}^j$) if $R(\boldsymbol{\pi}^i) = R(\boldsymbol{\pi}^j)$.

An exemplary problem symmetricity found in various COPs is the rotational symmetricity:

Theorem 2.1 (**Rotational symmetricity**). For any orthogoanl matrix Q, the problem $\boldsymbol{P}$ and $Q(\boldsymbol{P}) \triangleq \{\{Qx_i\}_{i=1}^N, \boldsymbol{f}\}$ are problem symmetric: i.e., $\boldsymbol{P} \xleftrightarrow{\text{sym}} Q(\boldsymbol{P})$. See Appendix A for the proof.

Rotational problem symmetricity is identified in every Euclidean COPs. On the other hand, solution symmetricity cannot be identified easily as the properties of the solutions are distinct for every COP.

3 Symmetric Neural Combinatorial Optimization

This section presents Sym-NCO, an effective training scheme that leverages the symmetricities of COPs. Sym-NCO learns a solve F_θ by minimizing the total loss function:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{Sym-RL}} + \alpha\mathcal{L}_{\text{inv}} = \mathcal{L}_{\text{ps}} + \beta\mathcal{L}_{\text{ss}} + \alpha\mathcal{L}_{\text{inv}} \tag{2}$$

where $\mathcal{L}_{\text{Sym-RL}}$ is REINFORCE loss term supported by symmetricity and $\mathcal{L}_{\text{inv}}$ is the regularization loss to induce that invariant representation. The $\mathcal{L}_{\text{Sym-RL}}$ is composed with $\mathcal{L}_{\text{ss}}$, the REINFORCE

Figure 3: An overview of Sym-NCO

loss term of Eq. (1) with solution symmetricity regularizing mechanism, and $\mathcal{L}_{\text{ps}}$, the REINFORCE loss term of Eq. (1) with both solution and problem symmetricity regularization. $\alpha, \beta \in [0, 1]$ are the weight coefficients. In the following subsections, we explain each loss term in detail.

3.1 Regularizing REINFORCE with problem and solution symmetricities via $\mathcal{L}_{\text{Sym-RL}}$

As discussed in Section 2.2, COPs have problem and solution symmetricities. We explain how to learn solver F_θ using REINFORCE with the specially designed baseline to approximately impose symmetricities. We provide the policy gradients to $\mathcal{L}_{\text{ss}}(\boldsymbol{\pi}(\boldsymbol{P}))$ and $\mathcal{L}_{\text{ps}}(\boldsymbol{\pi}(\boldsymbol{P}))$ in the context of the REINFORCE algorithm [29] with the proposed baseline schemes.

Leveraging solution symmetricity. As defined in Definition 2.2, the symmetric solutions must have the same objective values. We propose the REINFORCE loss $\mathcal{L}_{\text{ss}}$ with the baseline specially designed to exploit the solution symmetricity of CO as follows:

$$\mathcal{L}_{\text{ss}} = -\mathbb{E}_{\boldsymbol{\pi} \sim F_\theta(\cdot|\boldsymbol{P})}\big[R(\boldsymbol{\pi}(\boldsymbol{P}))\big] \tag{3}$$

$$\nabla_\theta \mathcal{L}_{\text{ss}} = -\mathbb{E}_{\boldsymbol{\pi} \sim F_\theta(\cdot|\boldsymbol{P})}\Big[\big[R(\boldsymbol{\pi}(\boldsymbol{P})) - b(\boldsymbol{P})\big]\nabla_\theta \log F_\theta\Big] \tag{4}$$

$$\approx -\frac{1}{K}\sum_{k=1}^{K}\Big[\big[R(\boldsymbol{\pi}^k) - \frac{1}{K}\sum_{k=1}^{K}R(\boldsymbol{\pi}^k)\big]\nabla_\theta \log F_\theta\Big] \tag{5}$$

where $\{\boldsymbol{\pi}^k\}_{k=1}^{K}$ are the solutions of P sampled from $F_\theta(\boldsymbol{\pi}|\boldsymbol{P})$, $\log F_\theta$ is the log-likelihood of F_θ, K is the number of sampled solutions, $b(\boldsymbol{P})$ is a shared baseline which is the average reward from K solutions for the identical problem $\boldsymbol{P}$.

The $\mathcal{L}_{\text{ss}}$ approximately imposes solution symmetricity using REINFORCE algorithm with a novel baseline $b(\boldsymbol{P})$. The sum of advantage in the solution group $\{\boldsymbol{\pi}^k\}_{k=1}^{K}$ is always zero:

$$\frac{1}{K}\sum_{k=1}^{K}\Big[\big[R(\boldsymbol{\pi}^k) - \frac{1}{K}\sum_{k=1}^{K}R(\boldsymbol{\pi}^k)\big]\big] = 0 \tag{6}$$

The $\mathcal{L}_{\text{ss}}$ induces competition among the rewards, $R(\boldsymbol{\pi}^1), ..., R(\boldsymbol{\pi}^K)$ which can be seen as a zero-sum game. Therefore, $\mathcal{L}_{\text{ss}}$ improves the overall reward quality of the solution group using the proposed competitive REINFORCE scheme, making the solver generate high rewarded solutions but a small reward deviation between solutions. The small reward-deviation indicates $\mathcal{L}_{\text{ss}}$ approximately imposes solution symmetricity to solver F_θ.

The POMO [21] employed a similar training technique with our $\mathcal{L}_{\text{ss}}$, that finds symmetric solutions by forcing F_θ to visit all possible initial cities when solving TSP and CVRP. However, the reward of COPs, including CVRP, PCTSP, and OP, is usually sensitive to first city selection. Therefore, POMO can be an excellent standalone method for TSP but can be further improved using our $\mathcal{L}_{\text{ss}}$ loss term.

Leveraging problem symmetricity. As discussed in Section 2.2, the rotational problem symmetricity is common in various COPs. We propose the REINFORCE loss $\mathcal{L}_{\text{ps}}$ which is equipped with problem

symmetricity:

$$\mathcal{L}_{\text{ps}} = -\mathbb{E}_{Q^l \sim \mathbf{Q}} \mathbb{E}_{\boldsymbol{\pi} \sim F_\theta(\cdot | Q^l(\boldsymbol{P}))} \big[R(\boldsymbol{\pi}(\boldsymbol{P})) \big] \tag{7}$$

$$\nabla_\theta \mathcal{L}_{\text{ps}} = -\mathbb{E}_{Q^l \sim \mathbf{Q}} \bigg[\mathbb{E}_{\boldsymbol{\pi} \sim F_\theta(\cdot | Q^l(\boldsymbol{P}))} \Big[\big[R(\boldsymbol{\pi}(\boldsymbol{P})) - b(\boldsymbol{P}, \boldsymbol{Q}) \big] \nabla_\theta \log F_\theta \Big] \bigg] \tag{8}$$

$$\approx \frac{1}{LK} \sum_{l=1}^{L} \sum_{k=1}^{K} \Big[\big[R(\boldsymbol{\pi}^{l,k}) - \frac{1}{LK} \sum_{l=1}^{L} \sum_{k=1}^{K} R(\boldsymbol{\pi}^{l,k}) \big] \nabla_\theta \log F_\theta \Big] \tag{9}$$

where $\mathbf{Q}$ is the distribution of random orthogonal matrices, Q^l is the l^{th} sampled rotation matrix, and $\boldsymbol{\pi}^{l,k}$ is the k^{th} sample solution of the l^{th} rotated problem. We construct L problem symmetric problems, $Q^1(\boldsymbol{P}), ..., Q^L(\boldsymbol{P})$, by using the sampled rotation matrices, and smaple K symmetric solutions from each of the L problems. Then, the shared baseline $b(\boldsymbol{P}, \boldsymbol{Q})$ is constructed by averaging $L \times K$ solutions.

Similar to the regularization scheme of $\mathcal{L}_{\text{ss}}$, the advantage term of $\mathcal{L}_{\text{ps}}$ also induces competition between solutions sampled from rotationally symmetric problems. Since the rotational symmetricity is defined such that x and $Q_l(x)$ have the same solution, the negative advantage value forces the solver to find a better solution. As mentioned in Section 2.2, problem symmetricity in COPs is usually pre-identified (i.e. there is provable guaranteed symmetricity such as rotational symmetricity Theorem 2.1); $\mathcal{L}_{\text{ps}}$ are applicable to general COPs. Moreover, multiple solutions are sampled for each symmetric problem so that $\mathcal{L}_{\text{ps}}$ can also identify and exploit the solution symmetricity with a similar approach taken for $\mathcal{L}_{\text{ss}}$. We provide detailed implementation and design guides regarding the integration strategy of $\mathcal{L}_{\text{ss}}$ and $\mathcal{L}_{\text{ps}}$ in Appendix C.2.

3.2 Learning invariant representation with Pre-identified Symmetricity: $\mathcal{L}_{\text{inv}}$.

By Theorem 2.1, the original problem x and its rotated problem $Q(x)$ have identical solutions. Therefore the encoder of F_θ can be enforced to have invariant representation by leveraging the pre-identified symmetricity: rotation symmetricity.

We denote $h(x)$ and $h(Q(x))$ as the hidden representations of x and $P(x)$, respectively. To impose the rotational invariant property on $h(x)$, we train solver F_θ with an additional regularization loss term $\mathcal{L}_{\text{inv}}$ defined as:

$$\mathcal{L}_{\text{inv}} = -S_{\text{cos}} \bigg(g\Big(h(x) \Big), g\Big(h\big(Q(x) \big) \Big) \bigg) \tag{10}$$

where $S_{\text{cos}}(a, b)$ is the cosine similarity between a and b. $g(\cdot)$ is the MLP-parameterized projection head.

For learning the invariant representation on rotational symmetricity, we penalize the difference between the projected representation $g(h(x))$ and $g((h(Q(x))))$, instead of directly penalizing the difference between $h(x)$ and $(h(Q(x))$. This penalizing scheme allows the use of an arbitrary encoder network architecture while maintaining the diversity of h [30]. We empirically verified that this approach attains stronger solvers as described in Section 6.1.

4 Related Works

Deep construction heuristics Bello et al. [18] propose one of the earliest DRL-NCO methods, based on PointerNet [8], and trained it with an actor-critic method. Attention model (AM) [19] successfully extends [18] by swapping PointerNet with Transformer [31], and it is currently the *de-facto* standard method for NCO. Notably, AM verifies its problem agnosticism by solving several classical routing problems and their practical extensions [7, 17]. POMO [21] extends AM by exploiting the solution symmetricities in TSP and CVRP. Even though POMO shows significant improvements from AM, it relies on problem-specific solution symmetricities (i.e., not problem agnostic). MDAM [24] extends AM by employing an ensemble of decoders. However, such an

extension is inapplicable for stochastic routing problems (i.e., not problem agnostic). Among these promising DRL-NCO methods, Sym-NCO achieved SOTA performances with *problem-agnostic* properties.

Equivariant deep learning In deep learning, symmetricities are often enforced by employing specific network architectures. EDP-GNN [32] proposes a permutation equivariant graph neural network (GNN) that produces equivariant outputs to the input order permutations. $SE(3)$-Transformer [33] restricts the Transformer so that it is equivariant to $SE(3)$ group input transformation. Similarly, EGNN [28] proposes a GNN architecture that produces $O(n)$ group equivariant output. These network architectures can dramatically reduce the search space of the model parameters. Some research applies equivariant neural networks to RL tasks to improve sample efficiency [34]. Also, there are several works that exploited the symmetric nature of CO. Ouyang et al. [35] proposed equivariant encoding scheme by giving rule-based input transformation to input graph. Hudson et al. [36] suggested a line-graph embedding scheme, which is beneficial to process CO graphs with rotational equivariant. Our Sym-NCO is a regularization method that is capable of learning existing powerful CO models without giving rule-based hard constraints to the structure. We empirically study the benefit of Sym-NCO over other symmetricity-based approaches in Section 6.1 and Appendix D.5

5 Experiments

This section provides the experimental results of Sym-NCO for TSP, CVRP, PCTSP, and OP. Focusing on the fact that Sym-NCO can be applied to any encoder-decoder-based NCO method, we implement Sym-NCO on top of POMO [21] to solve TSP and CVRP, and AM [19] to solve PCTSP and OP, respectively. We additionally validate the effectiveness of Sym-NCO on PointerNet [8].

5.1 Tasks and baseline selections

TSP aims to find the Hamiltonian cycle with minimum tour length. We employ Concorde [37] and LKH-3 [38] as the non-learnable baselines, and PointerNet [8], S2V-DQN [39], RL [20] AM [19], POMO [21] and MDAM [24] as the neural constructive baselines.

CVRP is an extension of TSP that aims to find a set of tours with minimal total tour lengths while satisfying the capacity limits of the vehicles. We employ LKH-3 [38] as the non-learnable baselines, and RL[20], AM [19], POMO [21] and MDAM [24] as the constructive neural baselines.

PCTSP is a variant of TSP that aims to find a tour with minimal tour length while satisfying the prize constraints. We employ the iterative local search (ILS) [19] as the non-learnable baseline, and AM [19] and MDAM [24] as the constructive neural baselines.

OP is a variant of TSP that aims to find the tour with maximal total prizes while satisfying the tour length constraint. We employ *compass* [40] as the non-learnable baseline, and AM [19] and MDAM [24] as the constructive neural baselines.

5.2 Experimental setting

Problem size. We provide the results of problems with $N = 100$ for the four problem classes, and real-world TSP problems with $50 < N < 250$ from TSPLIB.

Hyperparameters We apply Sym-NCO to POMO, AM, and PointerNet. To make fair comparisons, we use the same network architectures and training-related hyperparameters from their original papers to train their Sym-NCO-augmented models. Please refer to Appendix Appendix C.1 for more details.

Dataset and Computing Resources We use the benchmark dataset [19] to evaluate the performance of the solvers. To train the neural solvers, we use *Nvidia* A100 GPU. To evaluate the inference speed, we use an *Intel* Xeon E5-2630 CPU and *Nvidia* RTX2080Ti GPU to make fair comparisons with the existing methods as proposed in [24].

Table 1: Performance evaluation results for TSP and CVRP. Bold represents the best performances in each task. '-' indicates that the solver does not support the problem. 's' indicates multi-start sampling, 'bs' indicates the beam search. '×5 for the MDAM indicates the 5 decoder ensemble.

Method		TSP ($N = 100$)			CVRP ($N = 100$)		
		Cost ↓	Gap	Time	Cost ↓	Gap	Time
Handcrafted Heuristic-based Classical Methods							
Concorde	Heuristic [37]	7.76	0.00%	3m		–	
LKH3	Heuristic [38]	7.76	0.00%	21m	15.65	0.00%	13h
RL-based Deep Constructive Heuristic methods with greedy rollout							
PointerNet {*greedy.*}	NIPS'15 [8, 18]	8.60	6.90 %	–		–	
S2V-DQN {*greedy.*}	NIPS'17 [39]	8.31	7.03 %	–		–	
RL {*greedy.*}	NeurIPS'18 [20]		–		17.23	10.12%	–
AM {*greedy.*}	ICLR'19 [19]	8.12	4.53%	2s	16.80	7.34%	3s
MDAM {*greedy.×* 5}	AAAI'21 [23]	7.93	2.19%	36s	16.40	4.86%	45s
POMO {*greedy.*}	NeurIPS'20 [21]	7.85	1.04%	2s	16.26	3.93%	3s
POMO + Sym-NCO {*greedy.*}	*This work*	**7.84**	**0.94**%	2s	**16.10**	**2.88**%	3s
RL-based Deep Constructive Heuristic methods with multi-start rollout							
RL {*bs.*10}	NeurIPS'18 [20]		–		16.96	8.39%	–
AM {*s.*1280}	ICLR'19 [19]	7.94	2.26%	41m	16.23	3.72%	54m
POMO {*s.* 100}	NeurIPS'20 [21]	7.80	0.44%	13s	15.90	1.67%	16s
MDAM {*bs.* 30 × 5}	AAAI'21 [23]	7.80	0.48%	20m	16.03	2.49%	1h
POMO + Sym-NCO {*s.*100}	*This work*	**7.79**	**0.39%**	13s	**15.87**	**1.46%**	16s

5.3 Performance metrics

This section provides detailed performance metrics:

Average cost. We report an average cost of 10,000 benchmark instances which is proposed by [19].

Evaluation speed. We report the evaluation speeds of solvers in a out-of-the-box manner as they are used in practice. In that regard, the execution time of non-neural and neural methods are measured on CPU and GPU, respectively.

Greedy/Multi-start performance. For neural solvers, it is a common practice to measure *multi-start* performance as its final performance. However, when those are employed in practice, such resource consuming multi-start may not be possible. Hence, we discuss greedy and multi-start separately.

5.4 Experimental results

Results of TSP and CVRP As shown in Table 1, Sym-NCO outperforms the NCO baselines in both the greedy rollout and multi-start settings with the fastest inference speed. Remarkably, Sym-NCO achieves a 0.95% gap in TSP using the greedy rollout. In the TSP greedy setting, it solves TSP 10,000 instances in a few seconds.

Results of PCTSP and OP As shown in Table 2, Sym-NCO outperforms the NCO baselines in both the greedy rollout and multi-start settings. In the multi-start setting, Sym-NCO outperforms the classical PCTSP baseline (i.e., ILS) with the $\frac{43200}{180} \approx 240\times$ faster speed.

Results of the real-world TSP We evaluate POMO and Sym-NCO on TSPLib [41]. Table 3 shows that Sym-NCO outperforms POMO. Please refer to Appendix D.2 for the full benchmark results.

	Gap
POMO	1.87%
Sym-NCO	**1.62%**

Table 3: Optimality gap on TSPLIB

Application to various DRL-NCO methods As discussed in Section 3, Sym-NCO can be applied to various various DRL-NCO methods. We validate that Sym-NCO significantly improves the existing DRL-NCO methods as shown in Fig. 4.

Table 2: Performance evaluation results for PCTSP and OP. Notations are the same with Table 1.

Method		PCTSP ($N = 100$)			OP ($N = 100$)		
		Cost ↓	Gap	Time	Obj ↑	Gap	Time
Handcrafted Heuristic-based Classical Methods							
ILS C++	Heuristic [19]	5.98	0.00%	12h		–	
Compass	Heuristic [40]		–		33.19	0.00%	15m
RL-based Deep Constructive Heuristic methods with greedy rollout (zero-shot inference)							
AM {*greedy.*}	ICLR'19 [19]	6.25	4.46%	2s	31.62	4.75%	2s
MDAM {*greedy.*× 5}	AAAI'21 [23]	6.17	3.13%	34s	32.32	2.61%	32s
AM + Sym-NCO {*greedy.*}	*This work*	**6.05**	**1.23%**	2s	**32.51**	**2.03%**	2s
RL-based Deep Constructive Heuristic methods with multi-start rollout (Post-processing)							
AM {s. 1280}	ICLR'19 [19]	6.08	1.67%	27m	32.68	1.55%	25m
MDAM {bs. 30× 5}	AAAI'21 [23]	6.07	1.46%	16m	32.91	0.84%	14m
AM + Sym-NCO {s. 200}	*This work*	**5.98**	**-0.02%**	3m	**33.04**	**0.45%**	3m

    (a) PointerNet   (b) AM   (c) POMO

Figure 4: The applications of Sym-NCO to DRL-NCO methods in TSP ($N = 100$)

Time-performance analysis for multi-starts Multi-starts is a common method that improves the solution qualities while requiring a longer time budget. We use the rotation augments [21] to produce multiple inputs (i.e., starts). As shown in Fig. 5, Sym-NCO achieves the Pareto frontier for all benchmark datasets. In other words, Sym-NCO exhibits the best solution quality among the baselines within the given time consumption.

6 Discussion

6.1 Discussion of Regularization based Symmetricity Learning

In this section, we provide the discussion and ablations study for invariant representation learning using problem symmetricity.

Ablation Study of $\mathcal{L}_{\mathbf{inv}}$ As shown in Fig. 6b, $\mathcal{L}_{\mathrm{inv}}$ increases the cosine similarity of the projected representation (i.e., $g(h)$). We can conclude that $\mathcal{L}_{inv}$ contributes to the performance improvements (see Fig. 6a). We further verify that imposing similarity on h degrades the performance as demonstrated in Fig. 6c. This proves the importance of maintaining the expression power of the encoder as we mentioned in Section 3.2.

Comparison with EGNN EGNN [28] provably guarantees to process coordinate graph with rotational equivalency. Also, EGNN empirically verified its' high performance in point cloud tasks. However, we observed that EGNN significantly underperforms than Sym-NCO and fails to converge as shown Fig. 7b. This is because the euclidian CO has a fully connected input graph containing informative coordinates, and we believe the equivariant neural network should be carefully crafted to consider such unique input graph structures of CO tasks. On the other hand, Sym-NCO could leverage the existing powerful NCO model without fine modification of the neural network. These numerical results conform well with our hypothesis that equivariance is necessary but not sufficient for obtaining the optimal parameters for the solver (see Fig. 1). Therefore, we expect our approach

| (a) TSP ($N = 100$) | (b) CVRP ($N = 100$) | (c) PCTSP ($N = 100$) | (d) OP ($N = 100$) |

Figure 5: Time vs. cost plots. Green, orange, and blue colored lines visualize the results of hand-craft heuristics, neural baselines, and Sym-NCO, respectively. For OP (d), higher y-axis values are better.

| (a) Cost curves of the loss designs | (b) Cosine similarity curves | (c) Projection head ablation results |

Figure 6: Loss design ablation results (a) Effect of loss components to the costs, (b) Cosine similarity curves of the models with and with $\mathcal{L}_{inv}$, (c) Costs of the models with and without $g(\cdot)$.

can be simply extended to other domains requiring symmetricity and geometricity as positioned to leverage the existing legacy of powerful non-equivariant neural networks.

6.2 Limitations & future directions

Extended problem symmetricities. In this work, we employ the rotational symmetricity (Theorem 2.1) as the problem symmetricity. However, for some COPs, different problem symmetricities, such as scaling and translating P, can also be considered. Employing these additional symmetricities may further enhance the performance of Sym-NCO. We leave this for future research.

Large scale adaptation. Large scale applicability is essential to NCO (this work solves $N < 250$). Hence, we expect that the transfer- [42], curriculum- [43], and meta-learning approaches may improve the generalizability of NCO to larger-sized problems.

Extension to the graph COP. This work finds the problem symmetricity that is universally applicable for *Euclidean* COPs. However, some COPs are defined in non-Euclidean spaces such as asymmetric TSP. Furthermore, there are also a bunch of existing neural combinatorial optimization models that can solve graph COP [44, 45, 46, 47, 48, 49], where we can improve with a symmetricity regularization scheme. We also leave finding the universal symmetricities of non-Euclidean COPs and applying them to existing graph COP models for future research.

| (a) Cosine similarity curves | (b) Cost curves |

Figure 7: Comparisons of Sym-NCO and EGNN

References

[1] Stefan Irnich, Paolo Toth, and Daniele Vigo. *Chapter 1: The Family of Vehicle Routing Problems*, pages 1–33.

[2] Matthew Veres and Medhat Moussa. Deep learning for intelligent transportation systems: A survey of emerging trends. *IEEE Transactions on Intelligent Transportation Systems*, 21(8):3152–3168, 2020.

[3] Sungsoo Ahn, Junsu Kim, Hankook Lee, and Jinwoo Shin. Guiding deep molecular optimization with genetic exploration. *Advances in neural information processing systems*, 33:12008–12021, 2020.

[4] Sungsoo Ahn, Binghong Chen, Tianzhe Wang, and Le Song. Spanning tree-based graph generation for molecules. In *International Conference on Learning Representations*, 2021.

[5] Azalia Mirhoseini, Hieu Pham, Quoc V. Le, Benoit Steiner, Rasmus Larsen, Yuefeng Zhou, Naveen Kumar, Mohammad Norouzi, Samy Bengio, and Jeff Dean. Device placement optimization with reinforcement learning. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2430–2439. PMLR, 06–11 Aug 2017.

[6] Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Jiang, Ebrahim M. Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Sungmin Bae, Azade Nazi, Jiwoo Pak, Andy Tong, Kavya Srinivasa, William Hang, Emre Tuncer, Anand Babu, Quoc V. Le, James Laudon, Richard C. Ho, Roger Carpenter, and Jeff Dean. Chip placement with deep reinforcement learning. *CoRR*, abs/2004.10746, 2020.

[7] Haiguang Liao, Qingyi Dong, Xuliang Dong, Wentai Zhang, Wangyang Zhang, Weiyi Qi, Elias Fallon, and Levent Burak Kara. Attention routing: track-assignment detailed routing using attention-based reinforcement learning, 2020.

[8] Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 28, pages 2692–2700. Curran Associates, Inc., 2015.

[9] Chaitanya K. Joshi, Quentin Cappart, Louis-Martin Rousseau, Thomas Laurent, and Xavier Bresson. Learning tsp requires rethinking generalization, 2020.

[10] Wouter Kool, Herke van Hoof, Joaquim A. S. Gromicho, and Max Welling. Deep policy dynamic programming for vehicle routing problems. *CoRR*, abs/2102.11756, 2021.

[11] Zhang-Hua Fu, Kai-Bin Qiu, and Hongyuan Zha. Generalize a small pre-trained model to arbitrarily large tsp instances, 2020.

[12] André Hottung, Bhanu Bhandari, and Kevin Tierney. Learning a latent search space for routing problems using variational autoencoders. In *International Conference on Learning Representations*, 2020.

[13] André Hottung and Kevin Tierney. Neural large neighborhood search for the capacitated vehicle routing problem. *CoRR*, abs/1911.09539, 2019.

[14] Yaoxin Wu, Wen Song, Zhiguang Cao, Jie Zhang, and Andrew Lim. Learning improvement heuristics for solving routing problems, 2020.

[15] Paulo R d O da Costa, Jason Rhuggenaath, Yingqian Zhang, and Alp Akcay. Learning 2-opt heuristics for the traveling salesman problem via deep reinforcement learning. In Sinno Jialin Pan and Masashi Sugiyama, editors, *Proceedings of The 12th Asian Conference on Machine Learning*, volume 129 of *Proceedings of Machine Learning Research*, pages 465–480, Bangkok, Thailand, 18–20 Nov 2020. PMLR.

[16] Sungsoo Ahn, Younggyo Seo, and Jinwoo Shin. Learning what to defer for maximum independent sets. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 134–144. PMLR, 13–18 Jul 2020.

[17] Minsu Kim, Jinkyoo Park, and Joungho Kim. Learning collaborative policies to solve np-hard routing problems. In *Advances in Neural Information Processing Systems*, 2021.

[18] Irwan Bello, Hieu Pham, Quoc V. Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning, 2017.

[19] Wouter Kool, Herke van Hoof, and Max Welling. Attention, learn to solve routing problems! In *International Conference on Learning Representations*, 2019.

[20] MohammadReza Nazari, Afshin Oroojlooy, Lawrence Snyder, and Martin Takac. Reinforcement learning for solving the vehicle routing problem. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31, pages 9839–9849. Curran Associates, Inc., 2018.

[21] Yeong-Dae Kwon, Jinho Choo, Byoungjip Kim, Iljoo Yoon, Youngjune Gwon, and Seungjai Min. Pomo: Policy optimization with multiple optima for reinforcement learning. *Advances in Neural Information Processing Systems*, 33:21188–21198, 2020.

[22] Junyoung Park, Jaehyeong Chun, Sang Hun Kim, Youngkook Kim, and Jinkyoo Park. Learning to schedule job-shop problems: representation and policy learning using graph neural network and reinforcement learning. *International Journal of Production Research*, 59(11):3360–3377, 2021.

[23] Yining Ma, Jingwen Li, Zhiguang Cao, Wen Song, Le Zhang, Zhenghua Chen, and Jing Tang. Learning to iteratively solve routing problems with dual-aspect collaborative transformer. *Advances in Neural Information Processing Systems*, 34, 2021.

[24] Liang Xin, Wen Song, Zhiguang Cao, and Jie Zhang. Multi-decoder attention model with embedding glimpse for solving vehicle routing problems. In *Proceedings of 35th AAAI Conference on Artificial Intelligence*, pages 12042–12049, 2021.

[25] Junyoung Park, Sanjar Bakhtiyar, and Jinkyoo Park. Schedulenet: Learn to solve multi-agent scheduling problems with reinforcement learning. *arXiv preprint arXiv:2106.03051*, 2021.

[26] Xinyun Chen and Yuandong Tian. Learning to perform local rewriting for combinatorial optimization. In *Advances in Neural Information Processing Systems*, 2019.

[27] Hansen Wang, Zefang Zong, Tong Xia, Shuyu Luo, Meng Zheng, Depeng Jin, and Yong Li. Rewriting by generating: Learn heuristics for large-scale vehicle routing problems, 2021.

[28] Viéctor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E (n) equivariant graph neural networks. In *International Conference on Machine Learning*, pages 9323–9332. PMLR, 2021.

[29] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

[30] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[31] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30, pages 5998–6008. Curran Associates, Inc., 2017.

[32] Chenhao Niu, Yang Song, Jiaming Song, Shengjia Zhao, Aditya Grover, and Stefano Ermon. Permutation invariant graph generation via score-based generative modeling. In *International Conference on Artificial Intelligence and Statistics*, pages 4474–4484. PMLR, 2020.

[33] Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. *Advances in Neural Information Processing Systems*, 33:1970–1981, 2020.

[34] Elise van der Pol, Daniel Worrall, Herke van Hoof, Frans Oliehoek, and Max Welling. Mdp homomorphic networks: Group symmetries in reinforcement learning. *Advances in Neural Information Processing Systems*, 33:4199–4210, 2020.

[35] Wenbin Ouyang, Yisen Wang, Paul Weng, and Shaochen Han. Generalization in deep rl for tsp problems via equivariance and local search. *arXiv preprint arXiv:2110.03595*, 2021.

[36] Benjamin Hudson, Qingbiao Li, Matthew Malencia, and Amanda Prorok. Graph neural network guided local search for the traveling salesperson problem. *arXiv preprint arXiv:2110.05291*, 2021.

[37] Vašek Chvátal David Applegate, Robert Bixby and William Cook. Concorde tsp solver.

[38] Keld Helsgaun. An extension of the lin-kernighan-helsgaun tsp solver for constrained traveling salesman and vehicle routing problems. 12 2017.

[39] Elias Khalil, Hanjun Dai, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30, pages 6348–6358. Curran Associates, Inc., 2017.

[40] Gorka Kobeaga, María Merino, and Jose A Lozano. An efficient evolutionary algorithm for the orienteering problem. *Computers & Operations Research*, 90:42–59, 2018.

[41] Gerhard Reinelt. Tsplib—a traveling salesman problem library. *ORSA journal on computing*, 3(4):376–384, 1991.

[42] André Hottung, Yeong-Dae Kwon, and Kevin Tierney. Efficient active search for combinatorial optimization problems. *arXiv preprint arXiv:2106.05126*, 2021.

[43] Michal Lisicki, Arash Afkanpour, and Graham W Taylor. Evaluating curriculum learning strategies in neural combinatorial optimization. *arXiv preprint arXiv:2011.06188*, 2020.

[44] Thomas Barrett, William Clements, Jakob Foerster, and Alex Lvovsky. Exploratory combinatorial optimization with reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3243–3250, 2020.

[45] Iddo Drori, Anant Kharkar, William R Sickinger, Brandon Kates, Qiang Ma, Suwen Ge, Eden Dolev, Brenda Dietrich, David P Williamson, and Madeleine Udell. Learning to solve combinatorial optimization problems on real-world graphs in linear time. In *2020 19th IEEE International Conference on Machine Learning and Applications (ICMLA)*, pages 19–24. IEEE, 2020.

[46] Thomas D Barrett, Christopher WF Parsonson, and Alexandre Laterre. Learning to solve combinatorial graph partitioning problems via efficient exploration. *arXiv preprint arXiv:2205.14105*, 2022.

[47] Shenshen Gu and Yue Yang. A deep learning algorithm for the max-cut problem based on pointer network structure with supervised learning and reinforcement learning strategies. *Mathematics*, 8(2), 2020.

[48] Kenshin Abe, Zijian Xu, Issei Sato, and Masashi Sugiyama. Solving np-hard problems on graphs with extended alphago zero. *arXiv preprint arXiv:1905.11623*, 2019.

[49] Zhuwen Li, Qifeng Chen, and Vladlen Koltun. Combinatorial optimization with graph convolutional networks and guided tree search. *Advances in neural information processing systems*, 31, 2018.