# Self-Supervised Set Representation Learning for Unsupervised Meta-Learning

## Abstract

*Unsupervised meta-learning* (UML) essentially shares the spirit of self-supervised learning (SSL) in that their goal aims at learning models without any human supervision so that the models can be adapted to downstream tasks. Further, the learning objective of self-supervised learning, which pulls positive pairs closer and repels negative pairs, also resembles metric-based meta-learning. Metric-based meta-learning is one of the most successful meta-learning methods, which learns to minimize the distance between representations from the same class. One notable aspect of metric-based meta-learning, however, is that it is widely interpreted as a *set-level* problem since the inference of discriminative class prototypes (or set representations) from few examples is crucial for the performance of downstream tasks. Motivated by this, we propose Set-SimCLR, a novel self-supervised set representation learning framework for targeting UML problem. Specifically, our Set-SimCLR learns a set encoder on top of instance representations to maximize the agreement between two sets of augmented samples, which are generated by applying stochastic augmentations to a given image. We theoretically analyze how our proposed set representation learning can potentially improve the generalization performance at the meta-test. We also empirically validate its effectiveness on various benchmark datasets, showing that Set-SimCLR largely outperforms both UML and instance-level self-supervised learning baselines.

## 1 Introduction

One of the most challenging and long-standing problems in machine learning is *unsupervised learning* which aims at learning generalizable representations without human supervision, which can be transferred to diverse downstream tasks. Meta-learning (Finn et al., 2017; Snell et al., 2017) is a popular framework for learning models that quickly adapt to novel tasks

Figure 1: A graphical illustration of UML.

on the fly with few examples, and thus shares the spirit of unsupervised learning in that it seeks more efficient and effective learning procedures than learning from scratch. However, the essential difference between unsupervised learning and meta-learning is that most meta-learning approaches have been built on a supervised learning scheme and require human-crafted task distributions. In order to tackle this limitation, several previous works (Hsu et al., 2019; Khodadadeh et al., 2019; 2021; Lee et al., 2021) have proposed *unsupervised meta-learning* (UML) frameworks which combine unsupervised learning and meta-learning. They train a model with unlabeled data such that the model can adapt to unseen tasks with few labels. We illustrate the problem setting of UML in Figure 1.

Meanwhile, self-supervised learning (Chen et al., 2020a;b; He et al., 2020; Chen et al., 2020c; 2021; Grill et al., 2020; Zbontar et al., 2021) (SSL) is rising as a promising learning paradigm to learn transferable representations from unlabeled data in a *task-agnostic* manner. These methods rely on pretext tasks generated from data, and a popular pretext task is to maximize the agreement between different views of the same image in the latent space. The different views are easily obtained by sequentially applying pre-defined stochastic augmentations to an image. The main applications of these SSL methods essentially resemble the problem scenarios of UML, where we aim to transfer the learned representations to various downstream tasks. Further, the learning objective of SSL

is also closely related to metric-based meta-learning (Ni et al., 2022), which is one of the most successful meta-learning methods. Metric-based meta-learning (Snell et al., 2017) learns to minimize the distance between representations from the same class, while SSL pulls positive pairs closer and repels negative pairs. This motivates us to design a SSL method for addressing the UML problem.

Most SSL methods have focused on learning meaningful instance visual features. The importance of the instance feature is clear for generalization to unseen tasks coming with few examples, however, a meta-learning problem is often interpreted as a *set*-level problem in the literature of metric-based meta-learning. It has been widely shown that inference of discriminative class prototypes (or set representations) from few examples is crucial for the performance of downstream tasks. For example, Snell et al. (2017) basically takes an average of features belonging to the same class as a prototype (set representation). Similarly, Gordon et al. (2019); Iakovleva et al. (2020) propose Bayesian framework to learn stochastic prototypes using multi-layer perceptron and properly reflect uncertainty originating from few examples. Further, Triantafillou et al. (2019) propose to fine-tune the prototype with supervised loss. Inspired by the successes of set representation in few-shot learning, we propose a self-supervised set representation learning framework for UML.

The underlying assumption of SSL is that two different views of an image share most visual semantics. Built upon this idea, we construct two sets where each set consists of different views of the same image and maximize the agreement between them. Concretely, we repeatedly apply stochastic augmentations to each image of the mini-batch multiple times and construct a set consisting of the augmented images. Then we divide the set by half into two sets which are considered to be a positive pair of sets. Given a positive set pair, similar to Chen et al. (2020a), the other sets within mini-batch are considered as negative sets. We use attention-based set encoder (Vaswani et al., 2017; Lee et al., 2019) to obtain set representations. The set encoder is trained to reduce the distance of positive sets and increase that of negative sets. We dub our framework Set-SimCLR. At meta-test, we initialize each row of the weight for a linear classifier with the learned representation of the set composed of instances belonging to the same class, and the classifier is then optimized with supervised loss.

We motivate our algorithmic design of Set-SimCLR based on theoretical analysis. Specifically, we study how our set representation can potentially improve the final performance and the reason why we use set representations as the initialization of classifier weights. We then empirically validate our Set-SimCLR by comparing it against four UML methods and four instance-level SSL methods. We find that our method outperforms the baselines on six benchmark datasets, including Mini-ImageNet (Ravi & Larochelle, 2017), Tiny-ImageNet (Le & Yang, 2015), CIFAR100 (Krizhevsky et al., 2009), Aircraft (Maji et al., 2013), Stanford Cars (Krause et al., 2013) and CUB (Wah et al., 2011) datasets.

We summarize our contributions as follows:

- We introduce Set-SimCLR framework for solving unsupervised meta-learning problem, which learns instance and set representations simultaneously for downstream tasks.

- We provide a theoretical motivation of Set-SimCLR and study how the set representation potentially improves few-shot classification performance.

- The proposed Set-SimCLR outperforms the previous UML baselines and self-supervised learning baselines by significant margins in all the datasets we consider.

## 2 RELATED WORK

**Unsupervised Meta-Learning (UML)**  To tackle the limitation of supervised meta-learning, several UML methods are proposed. CACTUs (Hsu et al., 2019) run off-the-shelf unsupervised embedding algorithm, episodically perform clustering on the embedding space to construct a task and then conduct supervised meta-learning algorithms on the task. UMTRA (Khodadadeh et al., 2019) assumes that each example within a mini-batch belongs to a different class and leverages data augmentation to construct a task. LASIUM (Khodadadeh et al., 2021) trains generative models to harvest synthetic examples and construct a task by assuming that nearby latent codes produce in-class examples. Contrary to the works focusing on generating pseudo tasks, Meta-GMVAE (Lee et al., 2021) introduces a Mixture of Gaussian priors by performing Expectation-Maximization during the meta-training and the meta-test. To our knowledge, none of the existing works have proposed to tackle UML with self-supervised set representation learning, although Lee et al. (2021) and Ericsson et al. (2021) use a backbone network pretrained with instance-level SSL objective.

**Set Representation** DeepSets (Zaheer et al., 2017) independently processes elements and aggregates them with either min, max, mean or sum operation to obtain permutation invariant set encoding. To tackle the lack of expressiveness of Deepsets, Set Transformer (Lee et al., 2019) utilize self-attention to model the pairwise interaction of elements in a set. Instead of designing a more expressive neural architecture for set encoding, several methods are proposed to learn set representation by minimizing the distance between an input set and a trainable reference set. RepSet (Skianis et al., 2020) leverages a bipartite matching to minimize some cost between them. OTKE (Mialon et al., 2020) first introduces ideas from optimal transport (OT) by aligning features of a set to a trainable reference distribution. WEGL (Kolouri et al., 2020) proposes Wasserstein embedding as a pooling operator for set representation. Similarly, POT (dan Guo et al., 2022) minimizes the optimal transport distance between the empirical distribution of set elements and the distribution over global prototypes to improve set encoding. Note that our self-supervised set representation learning framework is agnostic to any set encoding architecture and any of them can be utilized for our method.

**Self-supervised Learning** Recently, a large volume of works has proposed self-supervised learning methods. The core idea is the representation of differently augmented views of the same image should be similar. Note that we introduce just a few of them which we consider as baselines in our experiments. SimCLR (Chen et al., 2020a;b) is one of the most representative contrastive frameworks where two views of the same image are pulled together while the negative pairs are repulsed. MOCO (He et al., 2020; Chen et al., 2020c; 2021) builds a dynamic feature dictionary using a queue and momentum encoder and learns to minimize contrastive loss from the dictionary. Meanwhile, several works show that non-contrastive approaches can learn meaningful representation without a latent feature collapse. For example, BYOL (Grill et al., 2020) leverages two identical networks where one of them is a momentum encoder to encode different views of images and minimizes the distance between positive pairs. Barlow Twins (Zbontar et al., 2021) computes a cross-correlation matrix between a different view of images and optimize it to be close to an identity matrix. Recently, MAE (He et al., 2022) masks an image and reconstructs the masked input to learn a meaningful representation of images. In this work, we exploit the effectiveness of self-supervised learning on UML, especially combined with our proposed set representation learning.

## 3 METHOD

In this section, we describe problem setting of unsupervised meta-learning (UML) and self-supervised set representation learning, Set-SimCLR. We depict an overview of our method in Figure 2.

### 3.1 PROBLEM STATEMENT

For UML problem, we can only access to an unlabeled dataset $\mathcal{D}^u = \{\mathbf{x}_i\}_{i=1}^U$ for meta-training. Same as most existing meta-learning works (Finn et al., 2017; Snell et al., 2017), we assume meta-test data follows the same data distribution of unlabeled dataset $\mathcal{D}^u$ while having a different set of classes. At meta-test time, we are given a set of $N$-way $S$-shot classification tasks and each task consists of a support set $\mathcal{D}^s = \{(\mathbf{x}_i^s, y_i^s)\}_{i=1}^{N \times S}$, and a query set $\mathcal{D}^q = \{\mathbf{x}_i^q\}_{i=1}^{N \times Q}$. The final goal is to leverage the model trained on the unlabeled data to predict labels of the query set with the help of the support set.

### 3.2 SELF-SUPERVISED CONTRASTIVE REPRESENTATION LEARNING

Before introducing our method, we first describe one of the most successful self-supervised learning methods SimCLR (Chen et al., 2020a). SimCLR is a contrastive learning framework that maximizes agreement between differently augmented views of the same instance in the latent space. Specifically, it first randomly samples a mini-batch of $M$ images $\{\mathbf{x}_m\}_{m=1}^M$ and obtains two different views of each image using stochastic data augmentation, resulting in $2M$ instances $\{(\mathbf{x}_{m,1}, \mathbf{x}_{m,2})\}_{m=1}^M$. There are two components: 1) a base encoder $f$ extracting feature representations and 2) a projection head $g$ mapping the representation to the latent space where the contrastive loss is applied. With the encoder and projection head, the latent representation of each image is obtained as $\mathbf{z}_{m,j} = g(f(\mathbf{x}_{m,j}))$. Then, the contrastive loss for the mini-batch of $M$ images is defined as

$$
\begin{aligned}
\mathcal{L}^{\text{SimCLR}}\left(\{(\mathbf{z}_{m,1}, \mathbf{z}_{m,2})\}_{m=1}^M\right) = -\frac{1}{2M} \sum_{m=1}^M & \log \frac{\exp(\text{sim}(\mathbf{z}_{m,1}, \mathbf{z}_{m,2})/\tau)}{\sum_{j,k} \mathbb{1}_{[\mathbf{z}_{k,j} \neq \mathbf{z}_{m,1}]} \exp(\text{sim}(\mathbf{z}_{m,1}, \mathbf{z}_{k,j})/\tau)} \\
& + \log \frac{\exp(\text{sim}(\mathbf{z}_{m,2}, \mathbf{z}_{m,1})/\tau)}{\sum_{j,k} \mathbb{1}_{[\mathbf{z}_{k,j} \neq \mathbf{z}_{m,2}]} \exp(\text{sim}(\mathbf{z}_{m,2}, \mathbf{z}_{k,j})/\tau)},
\end{aligned}
\tag{1}
$$

Figure 2: (**Left**): A conceptual illustration of Set-SimCLR with three images. We first encode each augmented image into instance representation using the base encoder $f$. Then we partition the set of $V$ augmented images into two sets and obtain set representations with the set encoder $\varphi$. We finally compute set- and instance-level loss. (**Right**): At meta-test, we use set representation of each class as an initialization of linear classifier weight.

where $\mathtt{sim}$ is a measure of similarity (e.g., cosine similarity) and $\mathbb{1}_{[\mathbf{z}_{k,j} \neq \mathbf{z}_{m,1}]} \in \{0, 1\}$ is an indicator function. The temperature $\tau$ is a hyperparameter controling the sharpness of the distribution.

### 3.3 SELF-SUPERVISED SET REPRESENTATION LEARNING WITH SIMCLR

Existing self-supervised learning has focused on instance-level visual features. The importance of the instance-level features is clear for generalization on unseen tasks, however, a meta-learning problem is often interpreted as a *set*-level problem rather than instance-level. For example, Snell et al. (2017) takes the average of features belonging to the same class as a prototype (or a set representation), or Gordon et al. (2019); Iakovleva et al. (2020) propose Bayesian framework to learn stochastic prototypes using multi-layer perceptron. Further, Triantafillou et al. (2019) propose to finetune a prototype with a supervised loss. Inspired by the successes, we propose a self-supervised contrastive learning framework for learning *set representation* to more effectively address UML problems.

**Set Representation** The underlying assumption of self-supervised learning methods is that two different views of an image share most of the visual semantics. We extend this idea to set-level representation by constructing two sets where each set consists of multiple different views of the same image and maximizing agreement between the two sets. Specifically, we repeatedly apply stochastic augmentations to an image for $V$ times and construct a set $\{\mathbf{x}_{m,v}\}_{v=1}^{V}$ for each image of a mini-batch, where $V$ is an even number. Then we independently encode each augmented image with the base encoder $f$ to obtain instance-level feature representations $\mathbf{h}_{m,v} = f(\mathbf{x}_{m,v}) \in \mathbb{R}^d$ for $m = 1, \dots, M$ and $v = 1, \dots, V$, where $d$ is the dimension of the feature representation. This results in $M$ different sets of instance-level representations $\mathbf{H}_m = \{\mathbf{h}_{m,v}\}_{v=1}^{V}$ for $m = 1, \dots, M$. Then we divide each set $\mathbf{H}_m$ by half to obtain positive pairs of sets, i.e., $\mathbf{H}_{m,1} = \{\mathbf{h}_{m,v}\}_{v=1}^{V/2}$ and $\mathbf{H}_{m,2} = \{\mathbf{h}_{m,v}\}_{v=V/2+1}^{V}$, and get a set representation by applying a set encoder to each set. Any permutation-invariant set encoder that takes a set of vectors as an input and outputs a vector can be employed. Here, we design a set encoder with self-attention for better representation:

$$\mathbf{T}_{m,j} = \mathtt{TransformerEncoder}(\mathbf{H}_{m,j}) \in \mathbb{R}^{V/2 \times d}, \mathbf{H}_{m,j} \in \mathbb{R}^{V/2 \times d}$$
$$\mathbf{s}_{m,j} = \mathtt{MLP}(\mathtt{concat}\left(\mathtt{mean}(\mathbf{T}_{m,j}); \mathtt{std}(\mathbf{T}_{m,j}); \mathtt{max}(\mathbf{T}_{m,j}); \mathtt{min}(\mathbf{T}_{m,j})\right)) \in \mathbb{R}^d, \quad (2)$$

where we define a set encoding function $\varphi : \mathbf{H}_{m,j} \in \mathbb{R}^{V/2 \times d} \mapsto \mathbf{s}_{m,j} \in \mathbb{R}^d$. For $\mathtt{TransformerEncoder}$, we use the multi-head self-attention mechanism proposed by Vaswani et al. (2017); Lee et al. (2019). Please see Appendix A for more detail. We take the row-wise operations on the outputs $\mathbf{T}_{m,j} \in \mathbb{R}^{V/2 \times d}$ of $\mathtt{TransformerEncoder}$ to compute mean, standard deviation, maximum and minimum (denoted as $\mathtt{mean}, \mathtt{std}, \mathtt{max}$ and $\mathtt{min}$), where each results in a $d$-dimensional vector. Then we concatenate them, denoted as $\mathtt{concat}$, which is a $4d$-dimensional vector, and feed it into multi-layer perceptron $\mathtt{MLP}$ to obtain the final set representation $\mathbf{s}_{m,j} \in \mathbb{R}^d$.

**Contrastive Loss for Set Representation Learning**    We now obtain positive pair of set representations $\mathbf{s}_{m,1}$ and $\mathbf{s}_{m,2}$, by applying the set encoder in Eq. 2 to each set $\mathbf{H}_{m,1}$ and $\mathbf{H}_{m,2}$. Following self-supervised literature, we project this set representation into the latent space with the same head $g$ used for instance-level feature learning. Finally, we compute set-level contrastive loss by plugging the projected set representations into Eq. 1, i.e., $\mathcal{L}^{\mathrm{SimCLR}}(\{(g(\mathbf{s}_{m,1}), g(\mathbf{s}_{m,2})\}_{m=1}^{M})$. The difference between our loss and SimCLR loss is that instead of instance-level representation, we pull positive pair of set-level representation and repulse the negative set pairs. Further, we find that sharing the projection head encourages the set-level and instance-level features to be consistent with each other, which empirically shows better results. Then the final loss is a combination of the set-level and the instance-level SimCLR losses as follows:

$$\underbrace{\mathcal{L}^{\mathrm{SimCLR}}\left(\{(g(\mathbf{h}_{m,1}), g(\mathbf{h}_{m,2}))\}_{m=1}^{M}\right)}_{\text{Instance-level}} + \underbrace{\mathcal{L}^{\mathrm{SimCLR}}\left(\{(g(\mathbf{s}_{m,1}), g(\mathbf{s}_{m,2}))\}_{m=1}^{M}\right)}_{\text{Set-level}} \tag{3}$$

**Linear Evaluation for Downstream Tasks**    We now describe how we utilize the learned instance-level and set-level representations on downstream few-shot classification tasks. For a $N$-way $S$-shot task at meta-test time, we are given the support set $\mathcal{D}^s = \{(\mathbf{x}_i^s, y_i^s)\}_{i=1}^{N \times S}$ and supposed to predict the labels of the query set $\mathcal{D}^q = \{\mathbf{x}_i^q\}_{i=1}^{N \times Q}$. We first apply the base encoder $f$ to obtain instance feature representations of the support set $\{(\mathbf{h}_i^s, y_i^s)\}_{i=1}^{N \times S}$ and the query set $\{\mathbf{h}_i^q\}_{i=1}^{N \times Q}$. For each class $c = 1, \ldots, N$, we encode $\mathbf{H}_c^s = \{\mathbf{h}_i^s \mid y_i^s = c\}$, a set of instances belonging to the class $c$, with the mapping $\varphi$ as described in Eq. 2. Let the set representation of $c$-th class be $\mathbf{s}_c = \varphi(\mathbf{H}_c^s) \in \mathbb{R}^d$.

We then initialize a weight of a linear classifier with the set representations $\mathbf{s}_1, \ldots, \mathbf{s}_N$ and train the classifier with the support set while freezing the base encoder $f$, which is similar to the linear evaluation of self-supervised learning (Chen et al., 2020a). We find that this is more suitable for our few-shot setting than the strategy of finetuning the full model to prevent the risk of overfitting to few data. Specifically, we initialize the weight $W$ of the classifier by stacking the learned set representation $s_c$ as row vectors, denoted as $W_0$, and optimize it by minimizing the cross-entropy loss with weight-decay as follows:

$$\underset{W}{\text{minimize}} \; \mathcal{L}_{\mathrm{CE}}(W; \mathcal{D}^s) \text{ via algorithm } \mathcal{A} \text{ as } W^* = \mathcal{A}(\mathcal{L}_{\mathrm{CE}}; W_0, \mathcal{D}^s)$$

$$\mathcal{L}_{\mathrm{CE}}(W; \mathcal{D}^s) = \frac{1}{|\mathcal{D}^s|} \sum_{\mathbf{x}_i^s, y_i^s \in \mathcal{D}^s} \ell\left(\mathtt{softmax}(W f(\mathbf{x}_i^s)), y_i^s\right), \; W_0 = [\mathbf{s}_1 \cdots \mathbf{s}_N]^\top \in \mathbb{R}^{N \times d}, \tag{4}$$

where $\ell$ is the cross-entropy loss and $\mathcal{A}(\mathcal{L}_{\mathrm{CE}}; W_0, \mathcal{D}^s)$ denotes gradient descent algorithm with weight-decay and the initialization $W_0$. After the optimization, we predict a label for each instance in the query set $\mathcal{D}^q$ as $y_i^q = \arg\max_c p_c^{(i)}$, where $(p_1^{(i)}, \ldots, p_N^{(i)})^\top = \mathtt{softmax}(W^* f(\mathbf{x}_i^q))$.

### 3.4 Theoretical Motivation

In this section, we provide theoretical motivations on several aspects of our algorithmic design. Namely, we study how the set representation can potentially improve the final performance and why it makes sense to initialize $W$ with the set representation and optimize it further to obtain $W^*$ with the cross-entropy loss. In appendix B, we show that the proposed method is equivalent to the metric-based inference with the fine-tuning of the class prototypes $\mathbf{s}_c$, where the initial class prototypes $\mathbf{s}_c$ are obtained with the set representation by $\mathbf{s}_c = \varphi(\mathbf{H}_c^s)$ and each input $\mathbf{x}$ is represented by instance-level representation $f(x)$. Thus, in the following, we discuss how such metric-based inference behaves with respect to the supervised loss in the downstream task.

To obtain theoretical insights, this section focuses on the binary classification without the head $g$ and considers the following abstract data-generating process: each of the unknown labels $y^+$ and $y^-$ is drawn independently from a uniform distribution $U$ on $\{1, 2\}$, and then each of the unlabeled positive examples $vx^+$ and $x^{++}$ is drawn from the conditional distribution $\mathcal{D}_{y^+}$ conditioned on the label $y^+$ while the negative example $x^-$ is drawn from the conditional distribution $\mathcal{D}_{y^-}$. Accordingly, this hidden process forms the joint distribution $\mathcal{D}(x, y) = \mathcal{D}_y(x)U(y)$. In this setting, we can write the contrastive unsupervised loss $L^{\mathrm{SimCLR}}$ of the representation $f$ and the corresponding supervised loss $L_s$ of our classifier $W_t f$ by $L^{\mathrm{SimCLR}}(f) =$
$$\mathbb{E}_{y^+ \sim U, y^- \sim U} \mathbb{E}_{vx^+, x^{++} \sim \mathcal{D}_{y^+}^2, x^- \sim \mathcal{D}_{y^-}} \left[-\log\left(\frac{\exp(f(x^{++})^\top f(vx^+))}{\exp(f(x^{++})^\top f(vx^+)) + \exp(f(x^{++})^\top f(x^-))}\right)\right] \qquad \text{and}$$

$L_{\mathrm{s}}(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}}[-\log(\frac{\exp((W_t f(x))_y)}{\sum_{k=1}^{2}\exp((W_t f(x))_k)})]$, where the matrix $W_t \in \mathbb{R}^{2\times d}$ is defined by $\lim_{t\to\infty} W_t = W^*$ and $W_t = [\varphi[\mathbf{H}_1^s] + (\Delta_t)_1, \ \varphi[\mathbf{H}_2^s] + (\Delta_t)_2]^\top$. Here, $\Delta_t = [(\Delta_t)_1, (\Delta_t)_2]^\top = W_t - W_0 \in \mathbb{R}^{2\times d}$ is the elements added during the training with the support set. Importantly, $y^+$ and $y^-$ can be the same as $y^+ = y^-$ since we do not know the true labels in the unsupervised loss. This is reflected by the fact that they are sampled from the same (unknown) probability measure on labels $U$. We also define the corresponding supervised loss with the average pooling (instead of our set representation) by $L_{\mathrm{s}}^A(f) = \mathbb{E}_{(x,y)\sim\mathcal{D}}[-\log(\frac{\exp((Af(x))_y)}{\sum_{k=1}^{2}\exp((Af(x))_k)})]$, where $A = [\mathbb{E}_{x\sim\mathcal{D}_1}[f(x)], \ \mathbb{E}_{x\sim\mathcal{D}_2}[f(x)]]^\top$. We define the performance difference between the average pooling and our set representation in terms of supervised loss by $\gamma = L_{\mathrm{s}}^A(f) - L_{\mathrm{s}}(f)$. Define the probability of $y^+$ and $y^-$ being the same by $\mathbb{P}(y^+ = y^-) = \mathbb{E}_{y^+,y^-\sim U^2}[\mathbb{1}\{y^+ = y^-\}]$. Similarly, $\mathbb{P}(y^+ \neq y^-) = \mathbb{E}_{y^+,y^-\sim U^2}[\mathbb{1}\{y^+ \neq y^-\}]$. We define $c = \mathbb{P}(y^+ \neq y^-)^{-1}$ and $\zeta = c \cdot \mathbb{P}(y^+ = y^-)\log(2)$.

The following theorem provides a theoretical motivation on the use of the set representation to increase $\gamma$ at $t = 0$ and on the fine-tuning of $W_0$ to further increase $\gamma$ at $t > 0$, in order to minimize the supervised loss $L_{\mathrm{s}}$ in the downstream task:

**Theorem 1.** *For any $f \in \mathcal{F}$, $L_{\mathrm{s}}(f) \leq cL^{\mathrm{SimCLR}}(f) - \zeta - \gamma$.*

The proof is deferred to appendix B. There are two ways to interpret the theorem. The first way is obtained by setting the probability measures for the expectations to be the empirical measures. Then, Theorem 1 is all about the empirical losses; i.e., $L^{\mathrm{SimCLR}}(f)$ is the empirical contrastive loss, $L_{\mathrm{s}}$ is the empirical supervised loss, and $\mathbb{P}(y^+ = y^-)$ is the rate of the positive and negative labels colliding in the empirical contrastive loss. In this interpretation, we can see that the $\gamma$ is expected to be positive even at $t = 0$ since $\varphi$ can recover the average pooling to obtain $L_{\mathrm{s}}^A(f) - L_{\mathrm{s}}(f) = 0$ and $\varphi$ is optimized to be better than the average pooling. As we increase $t$, we can further increase $\gamma$ to a certain degree until the correlation between the gradients on the support set and the unlabeled dataset is positive. Once the correlation becomes negative, $\gamma$ starts to decrease, resulting into the overfitting to the support set by increasing the (unknown) supervised loss at the unlabeled data. Thus, it makes sense to train $W_t$ by setting $\Delta_t \neq 0$ but we should regularize $W_t$ so that $\gamma$ does not decrease during the fine-tuning of $W_t$ with the support set. The second interpretation is obtained by setting the probability measures to be the probability measures, with which we have qualitatively the same conclusion as discussed in appendix B. Therefore, in both interpretations, Theorem 1 provides a theoretical motivation on the use of the set representation (to increase $\gamma$ at $t = 0$) and on the fine-tuning of $W_t$ (and $W^*$) with weight-decay (to further increase $\gamma$ at $t > 0$).

## 4 EXPERIMENT

In this section, we empirically validate the effectiveness of our set representation learning framework on several downstream few-shot classification tasks, and compare our Set-SimCLR against UML baselines and instance-level self-supervised baselines in subsection 4.1 and 4.2, respectively.

### 4.1 COMPARISON TO UNSUPERVISED META-LEARNING (UML)

**Dataset** We use the Mini-ImageNet dataset introduced by Ravi & Larochelle (2017), which is a subset of ILSVRC-2012 (Deng et al., 2009). It consists of 100 classes and each class contains 600 different images. We use the resolution of $3 \times 84 \times 84$, which is widely used in the meta-learning literature. We use 64 classes for unsupervised meta-training, 16 classes for meta-validation, and the remaining 20 classes for meta-test. Following the standard protocol of unsupervised meta-learning, we evaluate our method on 1000 randomly sampled tasks from the meta-test set.

**Baselines** We compare Set-SimCLR with four UML methods as the baselines: **1) CACTUs** (Hsu et al., 2019), **2) UMTRA** (Khodadadeh et al., 2019), **3) LASIUM** (Khodadadeh et al., 2021) and **4) Meta-GMVAE** (Lee et al., 2021). In addition, we provide the performance of two supervised meta-learning methods as "*oracles*": **MAML (oracle)** (Finn et al., 2017) and **ProtoNets (oracle)** (Snell et al., 2017). The detailed explanation of the baselines is in Appendix D.

**Implementation Details** We use Conv5 architecture as the base encoder for the fair comparison. We provide the details of neural architectures for base encoder, set encoder and head in Appendix F. We follow SimCLR (Chen et al., 2020a;b) for random augmentation, which is detailed in Appendix H.

Table 1: Results for 5-way $S$-shot classification on Mini-ImageNet. The base encoder is either Conv4 or Conv5. We report mean and standard deviation of accuracy evaluated on 1000 episodes with 5 different runs for ours. Note that we take the accuracy of baselines from the previous works Khodadadeh et al. (2021); Lee et al. (2021).

| Method | Clustering | 1-shot | 5-shot | 20-shot | 50-shot |
|---|---|---|---|---|---|
| *Training from Scratch* | N/A | 27.59 | 38.48 | 51.53 | 59.63 |
| CACTUs-MAML | BiGAN | 36.24 | 51.28 | 61.33 | 66.91 |
| CACTUs-ProtoNets | BiGAN | 36.62 | 50.16 | 59.56 | 63.27 |
| CACTUs-MAML | ACAI/DC | 39.90 | 53.97 | 63.84 | 69.64 |
| CACTUs-ProtoNets | ACAI/DC | 39.18 | 53.36 | 61.54 | 63.55 |
| UMTRA | N/A | 39.93 | 50.73 | 61.11 | 67.15 |
| LASIUM-MAML-RO/N | N/A | 40.19 | 54.56 | 65.17 | 69.13 |
| LASIUM-ProtoNets-RO/N | N/A | 40.05 | 52.53 | 59.45 | 61.43 |
| Meta-GMVAE | N/A | 42.82 | 55.73 | 63.14 | 68.26 |
| **Set-SimCLR (ours)** | N/A | **43.55** $_{\pm.17}$ | **58.74** $_{\pm.21}$ | **69.09** $_{\pm.26}$ | **72.43** $_{\pm.16}$ |
| *MAML (oracle)* | N/A | 46.81 | 62.13 | 71.03 | 75.54 |
| *ProtoNets (oracle)* | N/A | 46.56 | 62.29 | 70.05 | 72.04 |

Figure 3: **(a)**: 5-way 5-shot classification results on six datasets. **(b)**: 5-way 1, 5, 20, 25-shot classification results on Mini-ImageNet dataset. The base encoder is ResNet-18. We report mean and standard deviation of accuracy evaluated on 1000 episodes with 5 different runs. See Appendix J for the results in tabular format.

We apply the composed augmentations to 64 mini-batch images eight times (i.e., $M = 64, V = 8$), resulting in 4 elements in each set. We optimize the base encoder, set encoder and head network for 400 epochs using Adam optimizer (Kingma & Ba, 2015) with default settings (i.e., $\beta_1 = 0.9$ and $\beta_2 = 0.999$). We use constant learning rate of 0.001. For downstream tasks, we use scikit-learn (Pedregosa et al., 2011) package with default settings to optimize a linear classifier.

**Results** Table 1 shows the performance of the baselines and our Set-SimCLR for 5-way 1, 5, 20 and 50-shot classification on the Mini-ImageNet dataset, where Set-SimCLR outperforms all the baselines by considerable margins. For an instance, it achieves $+0.73\%, +3.01\%, +3.92\%$, and $+2.79\%$ performance improvement over the best performing baseline on 1- 5-, 20- and 50-shot settings. Notably, the performance gain of Set-SimCLR over the baselines gets larger as we increase the number of instances for a support set, i.e., shot. We can observe the similar pattern when comparing MAML-variant and ProtoNet-variant within baselines, e.g., CACTUs-MAML vs CACTUs-ProtoNets and LASIUM-MAML-RO/N vs LASIUM-ProtoNets-RO/N. This is because the adaptation with the support set at meta-test gets more effective since the model is less likely to overfit to larger shot.

## 4.2 COMPARISON TO SELF-SUPERVISED LEARNING (SSL)

**Dataset** We use the Mini-ImageNet dataset for training and evaluating models. Further, to verify the effectiveness of the proposed method on transfer learning scenarios, we evaluate the models trained with Mini-ImageNet on the conventional meta-test split of Tiny-ImageNet (Le & Yang, 2015), CIFAR100 (Krizhevsky et al., 2009), Aircraft (Maji et al., 2013), Stanford Cars (Krause et al., 2013) and CUB (Wah et al., 2011) datasets. See Appendix C for the number of classes of meta-splits for each dataset. Since all the models are trained on $84 \times 84$ images from the source dataset Mini-ImageNet, we resize the image to $84 \times 84$ resolution for all the target datasets. Following UML literature, we evaluate our method on 1,000 randomly sampled tasks from the meta-test set.

**Baselines** Although there are a vast number of SSL methods, in this work, we want to show the effectiveness of SSL compared to learning instance representation. Thus, we choose following four representative contrastive SSL baselines as follows: **1) SimCLR (Chen et al., 2020a;b), 2) MOCO (He et al., 2020; Chen et al., 2020c; 2021), 3) BYOL (Grill et al., 2020), 4) Barlow**

Figure 4: The results of ablation study on the 5-way 1, 5, 20, 50-shot classification using Mini-ImageNet. We study the effectiveness of **(a)**: different set encoder architectures, **(b)**: the depth of `TransformerEncoder` layers, and **(c)**: the number of set elements w.r.t SimCLR. We report the results over 3 different random seeds.

**Twins (Zbontar et al., 2021).** All the details are deferred to Appendix D. Note that we have tried a very recent SSL method — MAE (He et al., 2022), however, it fails to achieve comparable performance to ours and baselines. Please see details in Appendix E.

**Implementation Details** For the base encoder $f$, we use ResNet-18 architecture (He et al., 2016) which is widely used for evaluating self-supervised learning methods. For a fair comparison, we use the same architecture of head network $g$, for all SSL methods except for MOCO since MOCO does not use the head. We provide details of neural architectures and augmentations in Appendix G and H, respectively. For our method Set-SimCLR, we apply the augmentations 8 times to the mini-batch of 64 images (i.e., $M = 64, V = 8$), resulting in 4 elements in each set, while performing the same augmentation twice on the mini-batch of 256 images (i.e., $M = 256, V = 2$) for the baselines. For all the methods, we train each model for 400 epochs using Adam optimizer with default settings. We do not use learning rate scheduling which is not effective for any methods in our experiments. We search for an adequate learning rate in $\{0.001, 0.0005, 0.0001\}$ using a meta-validation split. Following SSL literature, we train a linear classifier for downstream tasks using scikit-learn package with default settings. Please see Appendix I for the results of other meta-test algorithms such as ProtoNet.

**Results** Figure 3a shows 5-way 5-shot experimental results of all the models on the Mini-ImageNet, Tiny-ImageNet, CIFAR100, Aircraft, Stanford Cars, CUB datasets. We can see that Set-SimCLR outperforms all the SSL baselines by considerable margins, from $+0.84\%$ to $+2.17\%$. MOCO shows slightly better result ($+0.26\%$) than ours on the Stanford Cars dataset, however, the difference is not significant considering its standard deviation ($0.57$). We further evaluate ours and baselines over various shots, e.g., 1-, 10-, 20 and 50-shot on the Mini-ImageNet dataset. As shown in Figure 3b, our Set-SimCLR obtains outstanding performance gains of $4.95\%, 1.55\%, 1.79\%, 1.72\%$ over the best performing baselines on 1-, 10-, 20-, 50-shot settings. Notably, that performance gain of Set-SimCLR is much larger in 1-shot setting than the other shots. It shows that SSL baselines are vulnerable to overfitting to the single shot. In contrast, the classifiers obtained by Set-SimCLR shows much robustness in the 1-shot setting due to the initialization with learned set representations.

## 4.3 Ablation Study and Analysis

In this subsection, we conduct ablation studies to verify a necessity of each components. We further provide analysis on our Set-SimCLR in comparison to SSL baselines.

**Set Encoder Architecture** We replace the architecture of the set encoder described in Eq. 2 with mean pooling, Deep Set (Zaheer et al., 2017), Rep the Set (Skianis et al., 2020), or Set Transformer (Lee et al., 2019). Figure 4a shows the 5-way 5-shot test accuracy of different set encoder architectures on the Mini-ImageNet dataset. We find that Rep the Set architecture works well on 1-shot setting, and our set encoder $\varphi$ in Equation 2 shows slightly better performance on 5-, 20- and 50-shot settings than the others. Note that our Set-SimCLR is set representation learning framework that is agnostic to the choice of set encoder architecture. Furthermore, even with the simplest architecture (mean pooling), it still shows slightly better performance than the best-performing self-supervised baseline (SimCLR) which is denoted as dotted lines.

**The Depth of Set Encoder** Another important compoment of our model is the number of `TransformerEncoder` layers in Equation 2. First, we start without `TransformerEncoder` layer, i.e., identity function, and increase the depth of the set encoder. Figure 4b shows the 5-way 5-shot

(a)  (b)  (c)

Figure 5: Analysis of the proposed Set-SimCLR on the Mini-ImageNet dataset. **(a)**: 5-way 5-shot test accuracy of baselines as a function of training epochs. **(b)**: T-SNE visualization of our adaptation process on a 5-way 5-shot task. **(c)**: 5-shot test accuracy of different ways. We report the results over 3 different runs.

test accuracy on the Mini-ImageNet dataset with varying the number of layers. We find that the set encoder with a single layer is the most effective on the overall settings considering the computational cost due to extra layers. Note that all of our models with the different number of layers outperform the best performing self-supervised baseline (SimCLR) which is denoted as dotted lines.

**Cardinality of Set**  In order to study effects of the number of set elements for Set-SimCLR, we plot 5-way 5-shot test accuracy improvement over SimCLR, denoted as $\Delta$ Test Acc., as a function of the cardinality of set. In Figure 4c, the performance of the downstream tasks is not sensitive to the size of sets, which results in consistent improvement over SimCLR with all the cardinality we consider.

**Training Budgets Analysis**  It takes more time to train our Set-SimCLR than self-supervised baselines we consider, since ours requires multiple (more than two) stochastic augmentations to construct a set. One may wonder whether the baseline can be comparable or even better if we train it with similar computational budgets to ours. To address this question, we train the self-supervised learning baselines for 800 epochs, which is twice larger than the before, and observe test accuracy over training. Figure 5a shows the 5-way 5-shot test accuracy of self-supervised learning baselines on the Mini-ImageNet dataset. We find that the our Set-SimCLR evaluated at 400 epochs largely outperforms the self-supervised baselines for all the training budgets we consider.

**Qualitative Analysis on Adaptation of Set Representation**  We now qualitatively analyze the adaptation process of our set representation at meta-test time. To do so, we visualize the set representations before and after the adaptation (i.e., each row of the classifier weight $W_0$ and $W^*$), and instances from support and query set. We normalize all the examples to be length 1 and project them to 2d space with T-SNE (Van der Maaten & Hinton, 2008). Figure 5b shows instance representation from query and support set and set representations, denoted as circle, cross and star, respectively. We represent arrows as the adaptation process of set representation, and the color stands for each class. We find that the set representation is not that discriminative at the beginning, however, it represents each class very well after the adaptation. This shows the necessity of our proposed adaptation process of set representation to achieve better performance of the downstream tasks.

**Accuracy with Various Ways**  We finally conduct experiments to show the performance of each model with varying the way of meta-test tasks. Figure 5c shows the 2-, 5-, 10- and 20-way 5-shot test accuracy of the self-supervised learning baselines and ours on the Mini-ImageNet dataset. We find that our Set-SimCLR consistently outperforms the baselines on all the way we consider here.

## 5  CONCLUSION

In this paper, we proposed self-supervised set representation learning framework for unsupervised meta-learning (UML). Our Set-SimCLR learns set representation by maximizing the agreement between positive sets in latent space, where the positive sets are constructed with repeated stochastic augmentations of an image. Based on theoretical analysis, we studied how the learned set representation can improve generalization ability and why it makes sense to initialize of the weight of linear classifier with the learned set representation for downstream tasks. We further validated the empirical efficacy of proposed Set-SimCLR and compared it against UML and self-supervised baselines using several benchmark few-shot classification datasets. Note that our main idea of minimizing distance between semantically similar sets constructed with repeated augmentations is not limited to SimCLR framework. Based on this, we plan to expand our framework to various self-supervised learning methods to exploit their potential merits.

## REPRODUCIBILITY STATEMENT

We clearly specify implementation details for reproducibility, including data split, baselines for comparisons, neural architecture, training process and augmentation in Appendix C, D, F, G, and H. In Supplementary File, we further provide the code for reproducing the main experimental results in Table 1 and Figure 3. Note that all the numerical results are based on more than three runs. Lastly, we will release our full code and the checkpoint of models to be publicly available after acceptance.

## REFERENCES

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

David Berthelot, Colin Raffel, Aurko Roy, and Ian Goodfellow. Understanding and improving interpolation in autoencoders via an adversarial regularizer. In *International Conference on Learning Representations*, 2019.

Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 132–149, 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020a.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey E Hinton. Big self-supervised models are strong semi-supervised learners. *Advances in neural information processing systems*, 33:22243–22255, 2020b.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020c.

Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9640–9649, 2021.

Dan dan Guo, Long Tian, Minghe Zhang, Mingyuan Zhou, and Hongyuan Zha. Learning prototype-oriented set representations for meta-learning. In *International Conference on Learning Representations*, 2022.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2009), 20-25 June 2009, Miami, Florida, USA*, pp. 248–255. IEEE Computer Society, 2009.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. In *International Conference on Learning Representations*, 2017.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

Linus Ericsson, Henry Gouk, and Timothy M Hospedales. How well do self-supervised models transfer? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5414–5423, 2021.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pp. 1126–1135. PMLR, 2017.

Jonathan Gordon, John Bronskill, Matthias Bauer, Sebastian Nowozin, and Richard Turner. Meta-learning probabilistic inference for prediction. In *International Conference on Learning Representations*, 2019.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. *Advances in neural information processing systems*, 33:21271–21284, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Dan Hendrycks and Kevin Gimpel. Gaussian error linear units (gelus). *arXiv preprint arXiv:1606.08415*, 2016.

Kyle Hsu, Sergey Levine, and Chelsea Finn. Unsupervised learning via meta-learning. In *International Conference on Learning Representations*, 2019.

Ekaterina Iakovleva, Jakob Verbeek, and Karteek Alahari. Meta-learning with shared amortized variational inference. In *International Conference on Machine Learning*, pp. 4572–4582. PMLR, 2020.

Siavash Khodadadeh, Ladislau Boloni, and Mubarak Shah. Unsupervised meta-learning for few-shot image classification. *Advances in neural information processing systems*, 32, 2019.

Siavash Khodadadeh, Sharare Zehtabian, Saeed Vahidian, Weijia Wang, Bill Lin, and Ladislau Boloni. Unsupervised meta-learning through latent-space interpolation in generative models. In *International Conference on Learning Representations*, 2021.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Soheil Kolouri, Navid Naderializadeh, Gustavo K Rohde, and Heiko Hoffmann. Wasserstein embedding for graph learning. *arXiv preprint arXiv:2006.09430*, 2020.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *4th International IEEE Workshop on 3D Representation and Recognition (3dRR-13)*, Sydney, Australia, 2013.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7(7):3, 2015.

Dong Bok Lee, Dongchan Min, Seanie Lee, and Sung Ju Hwang. Meta-GMVAE: Mixture of gaussian VAE for unsupervised meta-learning. In *International Conference on Learning Representations*, 2021.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International conference on machine learning*, pp. 3744–3753. PMLR, 2019.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

Subhransu Maji, Esa Rahtu, Juho Kannala, Matthew Blaschko, and Andrea Vedaldi. Fine-grained visual classification of aircraft. *arXiv preprint arXiv:1306.5151*, 2013.

Grégoire Mialon, Dexiong Chen, Alexandre d'Aspremont, and Julien Mairal. A trainable optimal transport embedding for feature aggregation and its relationship to attention. *arXiv preprint arXiv:2006.12065*, 2020.

Renkun Ni, Manli Shu, Hossein Souri, Micah Goldblum, and Tom Goldstein. The close relationship between contrastive learning and meta-learning. In *International Conference on Learning Representations*, 2022.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

Edgar Riba, Dmytro Mishkin, Daniel Ponsa, Ethan Rublee, and Gary Bradski. Kornia: an open source differentiable computer vision library for pytorch. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 3674–3683, 2020.

Konstantinos Skianis, Giannis Nikolentzos, Stratis Limnios, and Michalis Vazirgiannis. Rep the set: Neural networks for learning set representations. In *International conference on artificial intelligence and statistics*, pp. 1410–1420. PMLR, 2020.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30, 2017.

Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, et al. Meta-dataset: A dataset of datasets for learning to learn from few examples. *arXiv preprint arXiv:1903.03096*, 2019.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of machine learning research*, 9(11), 2008.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The caltech-ucsd birds-200-2011 dataset. Technical Report CNS-TR-2011-001, California Institute of Technology, 2011.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations*, pp. 38–45, 2020.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. *Advances in neural information processing systems*, 30, 2017.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In *International Conference on Machine Learning*, pp. 12310–12320. PMLR, 2021.

# A  TRANSFORMER ENCODER

We describe the TransformerEncoder from Eq. 2 in more detail. Let $X \in \mathbb{R}^{n \times d}$ be a stack of $n$ $d$-dimensional row vectors. Let $W_j^Q, W_j^K, W_j^V \in \mathbb{R}^{d \times d_k}$ be weight matrices for self-attention and let $b_j^Q, b_j^K, b_j^V \in \mathbb{R}^{d_k}$ be bias vectors for $j = 1, \ldots, 4$. For encoding the input $X$, we compute self-attention as follows:

$$
\begin{aligned}
Q^{(j)} &= X W_j^Q + \mathbf{1}(b_{1,j}^Q)^\top \in \mathbb{R}^{n \times d_k} \\
K^{(j)} &= X W_j^Q + \mathbf{1}(b_{1,j}^K)^\top \in \mathbb{R}^{n \times d_k} \\
V^{(j)} &= X W_j^K + \mathbf{1}(b_{i,j}^V)^\top \in \mathbb{R}^{n \times d_k} \\
A^{(j)}(X) &= \text{LayerNorm}\left(Q_1^{(j)} + \text{softmax}\left(Q_1^{(j)}(K_1^{(j)})^\top / \sqrt{d_k}\right) V_1^{(j)}\right) \in \mathbb{R}^{n \times d_k} \\
O(X) &= \text{Concat}(A_1^{(1)}(X), \ldots, A_1^{(4)}(X)) \in \mathbb{R}^{n \times d}
\end{aligned}
\tag{5}
$$

where $\mathbf{1} = (1, \ldots, 1)^\top \in \mathbb{R}^n$ is a vector of ones, $d = 4 d_k$, and softmax is applied for each row. After self-attention, we add a skip connection with layer normalization (Ba et al., 2016) as follows:

$$
\texttt{TransformerEncoder}(X) = \text{LayerNorm}(O(X)) + \text{ReLU}\left(W O(X) + \mathbf{1} b^\top\right)
\tag{6}
$$

where $W \in \mathbb{R}^{d \times d}, b \in \mathbb{R}^d$.

# B  ON THEORETICAL MOTIVATION

## B.1  ON THE RELATIONSHIP WITH METRIC-BASED INFERENCE

The metric-based inference using the instance-level representation $h$ of $x$ with the class prototypes $s_c$ can be written by

$$
\hat{y}(x) = \arg\min_c d(s_c, h).
$$

By choosing the metric to be the negative dot product as $d(s_c, h) = -s_c^\top h$, we can write

$$
\hat{y}(x) = \arg\min_c -s_c^\top h = \arg\min_c -\log \frac{\exp(s_c^\top h)}{\sum_k \exp(s_k^\top h)} = \arg\min_c \mathcal{L}_{\text{CE}}(\texttt{softmax}(W_0 f(x)), c),
$$

where the second line follows from the fact that the output of $\arg\min_c$ does not change by adding the constant in $c$. In other words, the prediction of the metric-based inference with $d(s_c, h) = -s_c^\top h$ (without further fine-tuning) is equivalent to the proposed method at the initialization of $W_0$. Thus, the proposed method can be understood as the metric-based inference with the fine-tuning of the class prototypes $s_c$ based on the support set, where the initial class prototypes $s_c$ are obtained by the set representation and each input $x$ represented by instance-level representation $h$.

In this view, a naive approach of fine-tuning of the class prototypes $s_c$ is to fine-tune the parameters of $\varphi$ to minimize $-\log \frac{\exp(s_c^\top h)}{\sum_k \exp(s_k^\top h)}$ with the support set where $s_c = \varphi(\mathbf{H}_c)$. However, since $\varphi$ has many parameters, changing $\varphi$ allows to change $s_c = \varphi(\mathbf{H}_c)$ freely without restrictions on the space of $s_c$. Thus, instead of fine-tuning the parameters of $\varphi$, we can directly optimize the values of $s_c$ by initializing $s_c = \varphi(\mathbf{H}_c)$ and untying $s_c$ from $\varphi(\mathbf{H}_c)$. This is what is done in the proposed algorithm. This results in the faster computation and the well-behaving convex optimization when compared to the fine-tuning of parameters of $\varphi$.

## B.2  ON INTERPRETATION OF THEOREM 1

There are two ways to interpret the theorem. The first interpretation is obtained by setting the probability measures for the expectations to be the empirical measures. The second interpretation is obtained by setting the probability measures for the expectations to be the true unknown probability measures. The first way is discussed in the main text. Thus, we now focus on the second interpretation. In the the second interpretation, Theorem 1 is all about the expected losses; i.e., $L^{\text{SimCLR}}(f)$ is the expected contrastive loss, $L_{\text{s}}$ is the expected supervised loss, and $\mathbb{P}(y^+ = y^-)$ is the probability of

the positive and negative labels colliding. In this interpretation, we can see that the $\gamma$ is still expected to be positive even at $t = 0$ since $\varphi$ can act as an empirical approximation of the average pooling to obtain $L_s^A(f) - L_s(f) \approx 0$ and $\varphi$ is optimized to be better than the average pooling. As we increase $t$, we tend to further increase the $\gamma$ since we are reducing the empirical loss of the support set, and the generalization gap between the empirical loss of the support set and the expected loss can be bounded by standard generalization bounds. Once this generalization gap start to increase, $\gamma$ starts to decrease, resulting into the overfitting to the support set. Thus, it still makes sense to train $W_t$ by setting $\Delta_t \neq 0$ but we should regularize $W_t$ so that the $\gamma$ does not decrease during the fine-tuning of $W_t$ with the support set. This is qualitatively the same conclusion as that of the first interpretation.

### B.3    PROOF OF THEOREM 1

*Proof.* Define the function $\ell$ by

$$\ell(q) = \log(1 + \exp(-q)).$$

Then,

$$
\begin{aligned}
&\ell\left(f(x^{++})^\top(f(vx^+) - f(x^-))\right) \\
&= \log(1 + \exp(-f(x^{++})^\top(f(vx^+) - f(x^-))) \\
&= \log\left((1 + \exp(-f(x^{++})^\top f(vx^+) + f(x^{++})^\top f(x^-))) \times \frac{\exp(f(x^{++})^\top f(vx^+))}{\exp(f(x^{++})^\top f(vx^+))}\right) \\
&= \log\left(\frac{\exp(f(x^{++})^\top f(vx^+)) + \exp(f(x^{++})^\top f(x^-)))}{\exp(f(x^{++})^\top f(vx^+))}\right) \\
&= -\log\left(\frac{\exp(f(x^{++})^\top f(vx^+))}{\exp(f(x^{++})^\top f(vx^+)) + \exp(f(x^{++})^\top f(x^-)))}\right).
\end{aligned}
$$

Thus, we have that

$$L^{\mathrm{SimCLR}}(f) = \mathbb{E}_{\substack{y^+ \sim U \\ y^- \sim U}} \mathbb{E}_{\substack{vx^+, x^{++} \sim \mathcal{D}_{y^+}^2 \\ x^- \sim \mathcal{D}_{y^-}}} \left[\ell\left(f(x^{++})^\top(f(vx^+) - f(x^-)))\right)\right].$$

Then, from the convexity of $\ell$, Jensen's inequality and the linearity of the expectation, we have that

$$L^{\mathrm{SimCLR}}(f) \geq \mathbb{E}_{\substack{y^+ \sim U \\ y^- \sim U}} \mathbb{E}_{x^{++} \sim \mathcal{D}_{y^+}} \left[\ell\left(f(x^{++})^\top(\mathbb{E}_{vx^+ \sim \mathcal{D}_{y^+}}[f(vx^+)] - \mathbb{E}_{x^- \sim \mathcal{D}_{y^-}}[f(x^-)])\right)\right].$$

By decomposing the expectation with sums of conditional expectations, conditioned on the event of $y^+ = y^-$ and its complement of $y^+ \neq y^-$,

$$L^{\mathrm{SimCLR}}(f) \geq \mathbb{P}(y^+ = y^-)\kappa_1 + \mathbb{P}(y^+ \neq y^-)\kappa_2 \tag{7}$$

where

$$\kappa_1 = \mathbb{E}_{\substack{y^+ \sim U \\ y^- \sim U}} \left[\mathbb{E}_{x^{++} \sim \mathcal{D}_{y^+}} \left[\ell\left(f(x^{++})^\top(\mathbb{E}_{vx^+ \sim \mathcal{D}_{y^+}}[f(vx^+)] - \mathbb{E}_{x^- \sim \mathcal{D}_{y^-}}[f(x^-)])\right)\right] \mid y^+ = y^-\right]$$

and

$$\kappa_2 = \mathbb{E}_{\substack{y^+ \sim U \\ y^- \sim U}} \left[\mathbb{E}_{x^{++} \sim \mathcal{D}_{y^+}} \left[\ell\left(f(x^{++})^\top(\mathbb{E}_{vx^+ \sim \mathcal{D}_{y^+}}[f(vx^+)] - \mathbb{E}_{x^- \sim \mathcal{D}_{y^-}}[f(x^-)])\right)\right] \mid y^+ \neq y^-\right].$$

For the first term, since $y^+ = y^-$ inside the loss $\ell$, we have that

$$\kappa_1 = \ell(0) = \log(2) \tag{8}$$

For the second term,

$$
\begin{aligned}
\kappa_2 &= \mathbb{E}_{y^+ \sim U} \left[\mathbb{E}_{x^{++} \sim \mathcal{D}_{y^+}} \left[\ell\left(f(x^{++})^\top(\mathbb{E}_{vx^+ \sim \mathcal{D}_{y^+}}[f(vx^+)] - \mathbb{E}_{x^- \sim \mathcal{D}_{r(y^+)}}[f(x^-)])\right)\right]\right] \\
&= \mathbb{E}_{(x,y) \sim \mathcal{D}} \left[\ell\left(g_\varphi(x)_y - g_\varphi(x)_{\sigma(y)}\right)\right] + \tilde{\gamma} \tag{9}
\end{aligned}
$$

where $g_\varphi(x) = W_t f(x)$, $g_A(x) = A f(x^{++})$, $\tilde{\gamma} = \mathbb{E}_{(x,y)\sim\mathcal{D}}[\ell\left(g_A(x)_y - g_A(x)_{\sigma(y)}\right) - \ell\left(g_\varphi(x)_y - g_\varphi(x)_{\sigma(y)}\right)]$ and $\sigma$ is defined as

$$\sigma(y) = \begin{cases} 1 & \text{if } y = 2 \\ 2 & \text{if } y = 1, \end{cases}$$

we have that

$$\ell\left(g(x)_y - g(x)_{\sigma(y)}\right) = \log\left(\left(1 + \exp(-g(x)_y + g(x)_{\sigma(y)})\right) \times \frac{\exp(g(x)_y)}{\exp(g(x)_y)}\right)$$

$$= -\log\left(\frac{\exp(g(x)_y)}{\exp(g(x)_y) + \exp(g(x)_{\sigma(y)})}\right)$$

$$= -\log\left(\frac{\exp(g(x)_y)}{\sum_{k=1}^2 \exp(g(x)_k)}\right). \tag{10}$$

By combining equation 9 and equation 10,

$$\kappa_2 = \mathbb{E}_{(x,y)\sim\mathcal{D}}\left[-\log\left(\frac{\exp(g_\varphi(x)_y)}{\sum_{k=1}^2 \exp(g_\varphi(x)_k)}\right)\right] + \gamma, \tag{11}$$

By combining equation 7, equation 8 and equation 11, we have

$$L^{\text{SimCLR}}(f) \geq \mathbb{P}(y^+ \neq y^-)\left(\mathbb{E}_{(x,y)\sim\mathcal{D}}\left[-\log\left(\frac{\exp(g_\varphi(x)_y)}{\sum_{k=1}^2 \exp(g_\varphi(x)_k)}\right)\right] + \gamma\right)$$
$$+ \mathbb{P}(y^+ = y^-)\log(2)$$

This implies that

$$L_s(f) \leq c L^{\text{SimCLR}}(f) - \zeta \log(2) - \gamma.$$

$\square$

## C    META-SPLIT OF DATASETS

Table 2: The number of classes for meta-split of all datasets.

| Dataset | Meta Train | Meta Valid | Meta Test |
|---|---|---|---|
| Mini-ImageNet | 64 | 16 | 20 |
| Tiny-ImageNet | 100 | 40 | 60 |
| CIFAR100 | 50 | 20 | 30 |
| Aircraft | 50 | 20 | 30 |
| Stanford Cars | 98 | 39 | 59 |
| CUB | 100 | 40 | 60 |

In Table 2, we provide the number of classes for meta-split of all datasets we consider in this paper. Note that we only use meta-test split of Tiny-ImageNet, CIFAR100, Aircraft, Stanford Cars and CUB datasets for the evaluation in Section 4.2.

## D    DETAILS OF BASELINES

In this section, we detail the supervised meta-learning, unsupervised meta-learning and instance-level self-supervised learning baselines. We first introduce two supervised meta-learning approaches which we consider as "*oracles*" and four different unsupervised meta-learning baselines as follows;

**1) MAML (oracle) (Finn et al., 2017)**: Model Agnostic Meta Learning where it learns the initialization of the parameters of the model such that few steps of gradient descent on a support set leads to generalization on a query set. We compare against its performance reported in Hsu et al. (2019).

**2) ProtoNets (oracle) (Snell et al., 2017)**: Euclidean distance-based meta-learning framework. It learns a metric embedding space where we perform prediction by computing a distance between class prototype and instances from query sets. We also compare against it using its performance reported in Hsu et al. (2019).

**3) CACTUs (Hsu et al., 2019)**: Clustering to Automatically Construct Tasks for Unsupervised meta-learning. It automatically constructs tasks by clustering the unsupervised dataset in embedding space learned by ACAI (Berthelot et al., 2019), BiGAN (Donahue et al., 2017), or DeepCluster (Caron et al., 2018). Then it train either MAML or ProtoNets using the cluster indices as pseudo-labels.

**4) UMTRA (Khodadadeh et al., 2019)**: Unsupervised Meta-learning with Tasks constructed by Random sampling and Augmentation. For constructing a K-way 1-shot task, it randomly samples K-way data points from unsupervised dataset and augments each data point. Then MAML is trained on the constructed tasks.

**5) LASIUM (Khodadadeh et al., 2021)**: It trains generative models on the given unlabeled data and sample $N$ different latent vector such that each pair-wise distance is greater than a predefined threshold. Each latent vector is fed into the generative model and decoded to a training instance belonging to distinct class. Then it adds some noise to each latent vector to generate $S$ examples and the generated ones are labeled with the class of the original latent vector. Finally, it trains MAML or ProtoNets using the synthetic $N$-way $S$-shot task.

**6) Meta-GMVAE (Lee et al., 2021)**: Meta-level Gaussian Mixture Variational AutoEncoder. It learns a latent representation by matching set-level amortized variational posterior and task-specific multi-modal prior optimized by EM algorithm.

We then present the four representative self-supervised baselines used in our experiments as follows:

**1) SimCLR (Chen et al., 2020a;b)**: It is a constrative learning framework which learns by maximizing agreement between differently augmented views of the same data example in the latent space.

**2) MOCO (He et al., 2020; Chen et al., 2020c; 2021)**: It builds a dynamic feature dictionary using a queue and momentum encoder and learns to minimize contrastive loss from the dictionary.

**3) BYOL (Grill et al., 2020)**: From pair views of an image, it learns visual representation by matching momentum encoder, which is exponentially moving average of the encoder.

**4) Barlow Twins (Zbontar et al., 2021)**: This method measure the cross-correlation matrix between the feature representations of two different views and learns by making it close to identity matrix.

# E  MASKED AUTOENCODERS

Table 3: The hyperparameters of MAE, which produces the similar number of parameters as ResNet-18 (i.e., VIT: $12,782,080$ and ResNet-18: $11,176,512$). The name of hyperparameter is based on huggingface transformers library (Wolf et al., 2020).

| Hyperparameters | Value |
|---|---|
| hidden_size | 512 |
| num_hidden_layers | 8 |
| num_attention_heads | 8 |
| intermediate_size | 512 |
| hidden_act | gelu (Hendrycks & Gimpel, 2016) |
| hidden_drop_prob | 0.0 |
| initializer_range | 0.02 |
| layer_norm_eps | $10^{-12}$ |
| is_encoder_decoder | False |
| image_size | 84 |
| patch_size | 6 |
| num_channels | 3 |
| qkv_bias | True |
| decoder_num_attention_heads | 8 |
| decoder_hidden_size | 128 |
| decoder_num_hidden_layers | 3 |
| decoder_intermediate_size | 128 |
| mask_ratio | 0.75 |
| norm_pix_loss | True |

Table 4: Results for 5-way $S$-shot classification on Mini-ImageNet. We report mean and standard deviation of accuracy evaluated on 1000 episodes with 5 different runs, except for MAE. For MAE, we report mean for accuracy for one run.

| Method | Base Encoder | 1-shot | 5-shot | 20-shot | 50-shot |
|---|---|---|---|---|---|
| SimCLR | | $46.23_{\pm0.31}$ | $67.08_{\pm0.26}$ | $76.51_{\pm0.23}$ | $80.14_{\pm0.45}$ |
| MOCO | | $43.96_{\pm0.35}$ | $62.64_{\pm0.14}$ | $72.21_{\pm0.35}$ | $78.02_{\pm0.20}$ |
| BYOL | ResNet-18 | $45.59_{\pm1.57}$ | $64.19_{\pm1.29}$ | $73.97_{\pm1.26}$ | $76.55_{\pm1.63}$ |
| Barlow Twins | | $45.12_{\pm0.19}$ | $63.44_{\pm0.27}$ | $72.13_{\pm0.27}$ | $75.92_{\pm0.25}$ |
| **Set-SimCLR (ours)** | | $\mathbf{51.18}_{\pm0.30}$ | $\mathbf{69.25}_{\pm0.17}$ | $\mathbf{78.30}_{\pm0.09}$ | $\mathbf{81.86}_{\pm0.14}$ |
| MAE with lr $= 0.002$ | | 34.47 | 46.40 | 56.62 | 62.94 |
| MAE with lr $= 0.001$ | VIT in Table 3 | 31.46 | 42.55 | 53.84 | 59.91 |
| MAE with lr $= 0.0005$ | | 32.38 | 45.83 | 58.61 | 65.65 |

MAE (He et al., 2022) is a recent self-supervised learning method based on masked auto-encoding objective. We tried to use MAE as a baseline, and the experimental setups are as follows. It assumes VIT (Dosovitskiy et al., 2021) as a base encoder, therefore, we use the hyperparameters in Table 3 which produce the similar amount of parameters as ResNet-18 (i.e., VIT: 12782080 and ResNet-18: 11176512). We use huggingface transformers library (Wolf et al., 2020) for implementation. Following the original implementation of MAE, we optimize MAE using AdamW (Loshchilov & Hutter, 2019) with 0.05 for 400 epochs. The mini-batch size is set to 512. We search the adequate learning rate in 0.002, 0.001, 0.0005 using meta-validation split. We use cosine learning rate scheduler with 40 warm-up epochs. We use `ResizedCrop`, `HorizontalFlip` for augmentations. In Table 4 shows the mean accuracy of ours, self-supervised learning baselines and MAE on the Mini-ImageNet 5-way few-shot classification tasks. We found that MAE fails to achieve comparable performance in our UML setting, therefore, we exclude it in our main text.

## F    IMPLEMENTATION DETAILS OF SECTION 4.1

Table 5: The architecture of Conv5 used as a base encoder $f$ for the experiments in Sec 4.1.

| Output Size | Layers |
|---|---|
| $3 \times 84 \times 84$ | Input Image |
| $64 \times 42 \times 42$ | $\texttt{Conv2d}(3 \times 3, \text{stride} = 1, \text{pad} = 1), \texttt{BatchNorm2D}, \texttt{ReLU}, \texttt{Maxpool}(2 \times 2, \text{stride} = 2)$ |
| $64 \times 21 \times 21$ | $\texttt{Conv2d}(3 \times 3, \text{stride} = 1, \text{pad} = 1), \texttt{BatchNorm2D}, \texttt{ReLU}, \texttt{Maxpool}(2 \times 2, \text{stride} = 2)$ |
| $64 \times 10 \times 10$ | $\texttt{Conv2d}(3 \times 3, \text{stride} = 1, \text{pad} = 1), \texttt{BatchNorm2D}, \texttt{ReLU}, \texttt{Maxpool}(2 \times 2, \text{stride} = 2)$ |
| $64 \times 5 \times 5$ | $\texttt{Conv2d}(3 \times 3, \text{stride} = 1, \text{pad} = 1), \texttt{BatchNorm2D}, \texttt{ReLU}, \texttt{Maxpool}(2 \times 2, \text{stride} = 2)$ |
| $64 \times 2 \times 2$ | $\texttt{Conv2d}(3 \times 3, \text{stride} = 1, \text{pad} = 1), \texttt{BatchNorm2D}, \texttt{ReLU}, \texttt{Maxpool}(2 \times 2, \text{stride} = 2)$ |
| $256$ | $\texttt{Flatten}$ |

Table 6: The architecture of set encoder $\varphi$ used for the experiments in Sec 4.1.

| Output Size | Layers |
|---|---|
| $M \times 256$ | $M$ Input Features |
| $M \times 256$ | $\texttt{TransformerEncoder}(d_{\text{model}} = 256, d_{\text{ff}} = 256, \text{num\_heads} = 4, \texttt{ReLU})$ |
| $1024$ | $\texttt{concat}\,(\texttt{mean}(\cdot); \texttt{std}(\cdot); \texttt{max}(\cdot); \texttt{min}(\cdot))$ |
| $256$ | $\texttt{Linear}(1024, 256), \texttt{ReLU}$ |
| $256$ | $\texttt{Linear}(256, 256), \texttt{ReLU}$ |
| $256$ | $\texttt{Linear}(256, 256)$ |

Table 7: The architecture of head $g$ used for the experiments in Sec 4.1.

| Output Size | Layers |
|---|---|
| $256$ | Input Feature |
| $256$ | $\texttt{Linear}(256, 256), \texttt{BatchNorm1d}, \texttt{LeakyReLU}$ |
| $64$ | $\texttt{Linear}(256, 64)$ |

We provide pytorch-like architecture implementations of base encoder $f$, set encoder $\varphi$ and head $g$ in Table 5, 6 and 7, respectively. We follow SimCLR (Chen et al., 2020a;b) for random augmentation, which is detailed in Appendix H. We apply the composed augmentations to 64 mini-batch images eight times (i.e., $M = 64, V = 8$), resulting in 4 elements in each set. We optimize the base encoder, set encoder and head network for 400 epochs using Adam optimizer (Kingma & Ba, 2015) with default settings (i.e., $\beta_1 = 0.9$ and $\beta_2 = 0.999$). We use constant learning rate of 0.001. For downstream tasks, we use scikit-learn (Pedregosa et al., 2011) package with default settings to optimize a linear classifier.

## G    IMPLEMENTATION DETAILS OF SECTION 4.2

Table 8: The architecture of set encoder $\varphi$ used for the experiments in Sec 4.2.

| Output Size | Layers |
|---|---|
| $M \times 512$ | $M$ Input Features |
| $M \times 512$ | $\texttt{TransformerEncoder}(d_{\text{model}} = 512, d_{\text{ff}} = 512, \text{num\_heads} = 4, \texttt{ReLU})$ |
| $2048$ | $\texttt{concat}\,(\texttt{mean}(\cdot); \texttt{std}(\cdot); \texttt{max}(\cdot); \texttt{min}(\cdot))$ |
| $512$ | $\texttt{Linear}(2048, 512), \texttt{ReLU}$ |
| $512$ | $\texttt{Linear}(512, 512), \texttt{ReLU}$ |
| $512$ | $\texttt{Linear}(512, 512)$ |

For the base encoder $f$, we use ResNet-18 architecture. Please see the original paper (He et al., 2016) for implementation details. We provide pytorch-like architecture implementations of set encoder $\varphi$ and head $g$ in Table 8 and 9, respectively. For a fair comparison, we use the same architecture of head network $g$ in Table 9, for all self-supervised learning methods except for MOCO. MOCO does not use the head as firstly proposed in the original paper. We use the same random augmentations described

Table 9: The architecture of head $g$ used for the experiments in Sec 4.2.

| Output Size | Layers |
|---|---|
| 512 | Input Feature |
| 512 | $\texttt{Linear}(512, 512), \texttt{BatchNorm1d}, \texttt{LeakyReLU}$ |
| 128 | $\texttt{Linear}(512, 128)$ |

Table 10: The selected learning rate of each method.

| Method | Learning Rate |
|---|---|
| SimCLR | 0.001 |
| MOCO | 0.001 |
| BYOL | 0.0005 |
| Barlow Twins | 0.001 |
| Set-SimCLR (ours) | 0.0005 |

in Appendix H. For our method Set-SimCLR, we apply the augmentations 8 times to the mini-batch of 64 images (i.e., $M = 64, V = 8$), resulting in 4 elements in each set, while performing the same augmentation twice on the mini-batch of 256 images (i.e., $M = 256, V = 2$) for the other baselines. For all the methods, we optimize the models for 400 epochs using Adam optimizer (Kingma & Ba, 2015) with default settings (i.e., $\beta_1 = 0.9$ and $\beta_2 = 0.999$). We do not use learning rate scheduling which is not effective for any methods in our experiments. We search for an adequate learning rate in $0.001, 0.0005, 0.0001$ for baselines and ours using a meta-validation split. We provide the selected learning rate of each method in Table 10. We use scikit-learn (Pedregosa et al., 2011) package with default settings to optimize classifiers for downstream tasks.

## H RANDOM AUGMENTATION

Table 11: The application probability and hyperparameters of each augmentation.

| Augmentation | Probability | Hyperparameters |
|---|---|---|
| $\texttt{ResizedCrop}$ | 1.0 | size $= (84, 84)$, scale $= (0.08, 1.0)$, ratio $= (0.75, 1.3...)$ |
| $\texttt{HorizontalFlip}$ | 0.5 | N/A |
| $\texttt{ColorJitter}$ | 0.8 | brightness $= 0.8$, contrast $= 0.8$, saturation $= 0.8$, hue $= 0.2$ |
| $\texttt{GrayScale}$ | 0.2 | N/A |
| $\texttt{GaussianBlur}$ | 0.5 | kernel_size $= (85, 85)$, $\sigma \sim U(0.1, 2.0)$ |

For random augmentation, we compose $\texttt{ResizedCrop}$, $\texttt{HorizontalFlip}$, $\texttt{ColorJitter}$, $\texttt{GrayScale}$ and $\texttt{GaussianBlur}$. The application probability and hyperparameters of each augmentation is shown in Table 11. Note that we perform $\texttt{ResizedCrop}$ on a larger resolution of $224 \times 224$ images than the resolution of $84 \times 84$ images we target, which is found to be more effective. We implement the augmentation using Kornia framework (Riba et al., 2020), which allows a faster augmentations on GPU.

# I    META-TEST ALGORITHMS OF SSL BASELINES

Table 12: 5-way 1, 5, 20, 25-shot classification results on Mini-ImageNet dataset of different meta-test algorithms. The base encoder is ResNet-18. "Proto" means ProtoNet-based inference, "LC" denotes the linear classifier, and "Proto+LC" learns the linear classifier whose weights are initialized by class prototypes. We report the mean and standard deviation with 5 different random seeds.

| Method | Meta-Test | 1-shot | 5-shot | 20-shot | 50-shot |
|---|---|---|---|---|---|
| | Proto | $50.60 \pm_{0.34}$ | $67.64 \pm_{0.25}$ | $74.90 \pm_{0.28}$ | $76.20 \pm_{0.21}$ |
| SimCLR | LC | $46.23 \pm_{0.31}$ | $67.08 \pm_{0.26}$ | $76.51 \pm_{0.23}$ | $80.14 \pm_{0.45}$ |
| | Proto+LC | $50.15 \pm_{0.38}$ | $67.83 \pm_{0.23}$ | $76.52 \pm_{0.41}$ | $79.96 \pm_{0.24}$ |
| | Proto | $47.47 \pm_{0.29}$ | $64.10 \pm_{0.34}$ | $72.24 \pm_{0.33}$ | $74.56 \pm_{0.37}$ |
| MOCO | LC | $43.96 \pm_{0.35}$ | $62.64 \pm_{0.14}$ | $71.21 \pm_{0.35}$ | $78.02 \pm_{0.20}$ |
| | Proto+LC | $46.67 \pm_{0.38}$ | $62.93 \pm_{0.22}$ | $72.27 \pm_{0.28}$ | $75.98 \pm_{0.23}$ |
| | Proto | $48.08 \pm_{1.04}$ | $62.79 \pm_{1.73}$ | $69.56 \pm_{1.77}$ | $71.14 \pm_{1.96}$ |
| BYOL | LC | $46.23 \pm_{0.31}$ | $67.08 \pm_{0.26}$ | $76.51 \pm_{0.23}$ | $80.14 \pm_{0.45}$ |
| | Proto+LC | $47.22 \pm_{1.36}$ | $63.18 \pm_{1.57}$ | $72.42 \pm_{1.46}$ | $76.41 \pm_{1.43}$ |
| | Proto | $46.50 \pm_{0.23}$ | $62.83 \pm_{0.24}$ | $69.56 \pm_{0.19}$ | $71.06 \pm_{0.17}$ |
| Barlow Twins | LC | $46.23 \pm_{0.31}$ | $67.08 \pm_{0.26}$ | $76.51 \pm_{0.23}$ | $80.14 \pm_{0.45}$ |
| | Proto+LC | $46.51 \pm_{0.29}$ | $63.23 \pm_{0.28}$ | $72.24 \pm_{0.25}$ | $75.94 \pm_{0.17}$ |
| **Set-SimCLR (ours)** | Set+LC | **$51.18 \pm_{0.30}$** | **$69.25 \pm_{0.17}$** | **$78.30 \pm_{0.09}$** | **$81.86 \pm_{0.14}$** |

In the main paper, we follow the previous self-supervised learning literature and train linear classifier for downstream tasks. However, one can wonder the performance of baselines when they are combined with different meta-test algorithms, such as ProtoNet-based inference (Snell et al., 2017). Further, the prototype (same as `meanpooling`) can be used for an initialization of linear classifier weight, as our Set-SimCLR. Table 12 provides the results of baselines when they are combined with 3 different types of meta-test algorithm, dented as "Proto", "LC" and "Proto+LC". We see that ProtoNet-based inference show better than others in 1-shot setting, however, its performance largely degenerate for 5-, 20- and 50-shot settings.

# J    FULL TABLES FOR FIGURE 3

Table 13: 5-way 5-shot classification results on Aircraft, Stanford Cars, CIFAR100, CUB, Mini-ImageNet and Tiny-ImageNet datasets. The base encoder is ResNet-18. We report the mean and standard deviation with 5 different random seeds.

| Method | Mini | Tiny | CIFAR100 | Aircraft | Cars | CUB |
|---|---|---|---|---|---|---|
| SimCLR | $67.08 \pm_{0.26}$ | $66.06 \pm_{0.34}$ | $64.27 \pm_{1.35}$ | $46.36 \pm_{0.11}$ | $37.05 \pm_{0.12}$ | $47.30 \pm_{0.30}$ |
| MOCO | $62.64 \pm_{0.14}$ | $60.67 \pm_{0.41}$ | $60.75 \pm_{0.83}$ | $46.81 \pm_{0.54}$ | **$38.33 \pm_{0.57}$** | $47.02 \pm_{0.13}$ |
| BYOL | $64.19 \pm_{1.52}$ | $63.83 \pm_{1.31}$ | $65.95 \pm_{1.73}$ | $44.29 \pm_{0.49}$ | $35.90 \pm_{0.92}$ | $45.95 \pm_{1.03}$ |
| Barlow Twins | $63.44 \pm_{0.27}$ | $62.20 \pm_{0.26}$ | $63.25 \pm_{0.52}$ | $46.05 \pm_{0.45}$ | $34.70 \pm_{0.23}$ | $44.73 \pm_{0.25}$ |
| **Set-SimCLR (ours)** | **$69.25 \pm_{0.17}$** | **$66.90 \pm_{0.16}$** | **$67.57 \pm_{1.23}$** | **$47.91 \pm_{0.35}$** | $38.07 \pm_{0.34}$ | **$48.64 \pm_{0.16}$** |

Table 14: 5-way 1, 5, 20, 25-shot classification results on Mini-ImageNet dataset. The base encoder is ResNet-18. We report the mean and standard deviation with 5 different random seeds.

| Method | 1-shot | 5-shot | 20-shot | 50-shot |
|---|---|---|---|---|
| SimCLR | $46.23 \pm_{0.31}$ | $67.08 \pm_{0.26}$ | $76.51 \pm_{0.23}$ | $80.14 \pm_{0.45}$ |
| MOCO | $43.63 \pm_{0.35}$ | $62.64 \pm_{0.14}$ | $72.21 \pm_{0.35}$ | $78.02 \pm_{0.20}$ |
| BYOL | $45.59 \pm_{1.57}$ | $64.19 \pm_{1.29}$ | $73.97 \pm_{1.26}$ | $76.55 \pm_{1.63}$ |
| Barlow Twins | $45.12 \pm_{0.19}$ | $63.44 \pm_{0.27}$ | $72.13 \pm_{0.27}$ | $75.92 \pm_{0.25}$ |
| **Set-SimCLR (ours)** | **$51.18 \pm_{0.30}$** | **$69.25 \pm_{0.17}$** | **$78.30 \pm_{0.09}$** | **$81.86 \pm_{0.14}$** |