RTFormer: Efficient Design for Real-Time Semantic Segmentation with Transformer

Abstract

Recently, transformer-based networks have shown impressive results in semantic segmentation. Yet for real-time semantic segmentation, pure CNN-based approaches still dominate in this field, due to the time-consuming computation mechanism of transformer. We propose RTFormer, an efficient transformer for real-time semantic segmenation, which achieves better trade-off between performance and efficiency than CNN-based models. To achieve high inference efficiency on GPU-like devices, our RTFormer leverages GPU-Friendly Attention with linear complexity and discards the multi-head mechanism. Besides, we find that cross-resolution attention is more efficient to gather global context information for high-resolution branch by spreading the high level knowledge learned from low-resolution branch. Extensive experiments on mainstream benchmarks demonstrate the effectiveness of our proposed RTFormer, it achieves state-of-the-art on Cityscapes and CamVid, and shows promising results on ADE20K.

1 Introduction

Semantic segmentation is a fundamental computer vision task which usually serves as critical perception module in autonomous driving, mobile applications, robot sensing and so on. In pace with the development of these applications, the demand of executing semantic segmentation in real-time grows stronger increasingly. Existing real-time segmentation methods mainly focus on exploiting CNN architectures, including designing high-efficiency backbones and decoders[40, 35, 34, 15, 19, 11] by handcraft and exploring neural architecture search methods to find better trade-off between accuracy and efficiency[39, 21, 20, 7]. And significant improvement has been achieved by these great works so far.

More recently, vision transformers have been drawn lots of attention for their strong visual recognition capability[10, 26, 22, 29, 30]. And inherited from them, a series of transformer-based architectures like[43, 32, 36] are proposed and show very promising performance on general semantic segmentation task. Comparing with CNN-based networks, the main distinction of these transformer-based architectures is the heavy usage of

Figure 1: **Accuracy(mIoU%) vs. Inference Speed(FPS) on CamVid[4] testing set.** Our methods are presented in red dots while other methods are presented in blue dots.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

self-attention, and self-attention is good at capturing long-range context information which is essential in semantic segmentation. So, we consider that attention structure should also be effective in real-time semantic segmentation task.

But up to now, only a few works[32] have explored the application of attention in this field, and the state-of-the-arts are still dominated by CNN-based architectures. We suppose the main obstacles of applying attention in real-time setting might come from the following two aspects. One is that the computation properties of most existing types of attention are not quite inference friendly for GPU-liked devices, such as the quadratic complexity and the multi-head mechanism. The quadratic complexity introduces large computation burden when processing high resolution features, especially in dense prediction tasks like semantic segmentation. Although several works such as[29, 32] shrink down the size of keys and values, the property of quadratic complexity remains. While the multi-head mechanism splits the matrix multiplication into multiple groups, which makes the attention operation to be time consuming on GPU-like devices, analogue to the situation that executing group convolution. The other is that conducting attention only on high resolution feature map itself like[32, 36] may not be the most effective way for capturing long-range context with high level semantic information, as a single feature vector from high resolution feature map has limited receptive field.

We propose a novel transformer block, named RTFormer block, as shown in Figure 2, which aims to achieve better trade-off between performance and efficiency on GPU-like devices with transformer. For the low-resolution branch, a newly proposed GPU-Friendly Attention, derived from external attention[13], is adopted. It inherits the linear complexity property from external attention, and alleviates the weakness of multi-head mechanism for GPU-like devices by means of discarding the channel split within matrix multiplication operations.Instead, it enlarges the number of external parameters and splits the second normalization within double-norm operation proposed by external attention into multiple groups. This enables GPU-Friendly Attention to be able to maintain the superiority of multi-head mechanism to some extent. For the high-resolution branch, we adopt cross-resolution attention instead of only conducting attention within high-resolution feature itself. Besides, unlike the parallel formulation of multi-resolution fusion from[27, 15, 36], we arrange the two resolution branches into a stepped layout. Therefore, the high-resolution branch can be enhanced more effectively by the assistant of the high level global context information learned from low-resolution branch. Based on the proposed RTFormer block, we construct a new real-time semantic segmentation network, named RTFormer. In order to learn enough local context, we still use convolution blocks at the earlier stages and place RTFormer block at the last two stages. By taking extensive experiments, we find RTFormer can make use of global context more effectively and achieve better trade-off than previous works. Figure 1 shows the comparison between RTFormer with other methods on CamVid. Finally, we summarize the contribution of RTFormer as following three aspects:

- A novel RTFormer block is proposed, which achieves better trade-off between performance and efficiency on GPU-like devices for semantic segmentation task.

- A new network architecture RTFormer is proposed, which can make full use of global context for improving semantic segmentation by utilizing attention deeply without lost of efficiency.

- RTFormer achieves state-of-the-art on Cityscapes and CamVid, and show promising performance on ADE20K. In addition, it provides a new perspective for practice on real-time semantic segmentation task.

2   Related Work

Generic Semantic segmentation. Traditional segmentation methods utilized the hand-crafted features to solve the pixel-level label assigning problems,e.g., threshold selection[25],the super-pixel[1] and the graph algorithm[3]. With the success of deep learning, a series of methods[5, 2, 42] based on FCN (fully convolutional neural network) [23] achieve superior performance on various benchmarks. These methods improved FCN from different aspects. The Deeplabv3 [5] and the PSPNet[42] enlarge the receptive field and fused different level features by introducing the atrous spatial pyramid pooling module and the pyramid pooling module. The SegNet[2] recover the high-resolution map through the encoder-decoder structure. However, most of these approaches are computational demanding because of the dilation convolution and the various connections in the encoder-decoder architecture. In this

Figure 2: Illustration of RTFormer block. For low resolution, GPU-Friendly Attention is applied. And for high resolution, we use Cross-resolution Attention which draws K and V from low resolution branch. Besides, we make up FFN with two 3×3 convolution layers.

paper, we propose a new architecture which achieves good trade-off between accuracy and inference.

Real-time Semantic segmentation. To solve the real-time segmentation problem, various methods[40, 35, 34, 15, 11, 7] have been proposed. ICNet[40] solves this problem by using a well-designed multi-resolution image cascade network. FasterSeg[7] utilizes neural architecture search (NAS) to reach the goal of balancing high accuarcy and low latency. BiSeNetV1[35] and BiSeNetV2 [34] adopt a two-stream paths network and a feature fusion module to achieve a well balance between speed and segmentation performance. STDC[11] rethinks and improves BiSeNet by proposing a single-steam structure with detail guidance module. DDRNets[15] achieves better performance by designing a two deep branch network with multiple bilateral fusions and a Deep Aggregation Pyramid Pooling Module.

Attention mechanism in visual tasks. The attention mechanism has been vigorous developed in computer vision field [31, 37, 16, 17, 12, 33] SE block proposed by [17] applies the attention function to channels and improves the representation capability of the network. [16] uses an attention-module to model object relation and help the objection detection. [31] presents a non-local operation which can capture the long-range dependencies and shows promising results on video classification task. [33] uses attention in point cloud recognition task. Self-attention is a special case of the attention mechanism that has been widely used in recent years[37, 12, 28]. However, self-attention has quadratic complexity that limit its usage. EANet [13] proposes an efficient attention method called external attention. Inspired by this method, we developed a GPU-Friendly attention module that has low latency and high performance.

Transformer in Semantic segmentation. Very recently, SETR [43] proposes a sequence-to sequence method and achieves impressing result. SETR uses pretrained VIT [38] as its backbone and has no downsampling in spatial resolution. However, it is difficult to use it for real-time segmentation task due to its heavy Transform backbone and very high resolution. SegFormer [32] increases efficiency by introducing a hierarchical transformer encoder and a lightweight all MLP decoder. Compared with SETR, SegFormer has both higher efficiency and higher performance. However, the efficiency of SegFormer is still relatively low compared to some state-of-the-art CNN based real-time segmentation model. By introducing our RTFormer block, our method can take advantage of the attention mechanism while achieving the real-time speed.

3 Methodology

In this section, we elaborate the details of our proposed approach. We first describe the RTFormer block, then we present how to construct RTFormer based on RTFormer block.

3.1 RTFormer block

RTFormer block is dual-resolution module which inherits the multi-resolution fusion paradigm from[27, 15, 36]. In contrast to the previous works, RTFormer block is comprised of two types of attention along with their feed forward network, and arranged as stepped layout, as shown in Figure 2. In the low-resolution branch, we use a GPU-Friendly Attention to capture high level global context. While in the high-resolution branch, we introduce a cross-resolution attention to broadcast the high level global context learned from low-resolution branch to each high-resolution pixel, and the stepped layout is served to feed more representative feature from the low-resolution branch into the cross-resolution attention.

GPU-Friendly Attention. Comparing the different existing types of attention, we find that external attention[13](EA) can be a potential choice for being executed on GPU-like devices due to its gratifying property of linear complexity, and our GPU-Friendly Attention(GFA) is derived from it. Thus, before detailing GFA, we review EA first. Let $X \in \mathbb{R}^{N \times d}$ denotes an input feature, where N is the number of elements(or pixels in images) and d is the feature dimension, then the formulation of EA can be expressed as:

$$EA(X, K, V) = DN(X \cdot K^T) \cdot V \tag{1}$$

where $K, V \in \mathbb{R}^{M \times d}$ are learnable parameters, M is the parameter dimension, DN is the Double Normalization operation proposed by[13]. And the multi-head version of EA can be expressed as:

$$\begin{aligned} MHEA(X) &= Concat(h_1, h_2, ..., h_H) \\ h_i &= EA(X_i, K', V'), \quad i \in [1, H] \end{aligned} \tag{2}$$

where $K', V' \in \mathbb{R}^{M \times d'}$, $d' = d/H$ and H is the number of heads, while X_i is the ith head of X. As shown in upper part of Figure 3, the multi-head mechanism generates H attention maps for improving upon the capacity of EA, and this makes the matrix multiplication be splitted into several groups, which is similar as group convolution. Although EA uses shared K' and V' for different heads, which can speed up the calculation a lot, the splitted matrix multiplication remains.

To avoid the latency reduction on GPU-like devices due to the multi-head mechanism, we propose a simple and effective GPU-Friendly Attention. It evolves from the basic external attention expressed by Equation 1, which can be formulated as:

$$GFA(X, K_g, V_g) = GDN(X \cdot K_g^T) \cdot V_g \tag{3}$$

where $K_g, V_g \in \mathbb{R}^{M_g \times d}$, $M_g = M \times H$ and GDN denotes Grouped Double Normalization, which splits the second normalization of the original double normalization into H groups, as shown in the left lower part of Figure 3. From Equation 3 we can find that GFA has two main improvements. On the one hand, it makes the matrix multiplication to be integrated, which is quite friendly for GPU-like devices. Benefit from this, we can enlarge the size of external parameters from (M, d') to (M_g, d). Therefore, more parameters can be tuned for improving performance. On the other hand, it maintains the superiority of multi-head mechanism to some extent by taking advantage of the grouped double normalization. For intuitive comprehension, it can be regarded that GFA also generates H different attention maps for capturing different

Figure 3: Comparison between Multi-Head External Attention and GPU-Friendly Attention. Multi-head external attention splits the matrix multiplication into several groups while our GPU-Friendly Attention makes matrix multiplication to be integrated which is more friendly for GPU-like devices.

relations between tokens, but more feature elements are involved for computing similarity and all the attention maps contribute to the final output.

Cross-resolution Attention. Multi-resolution fusion has been proven to be effective for dense prediction task. And for the design of multi-resolution architecture, we can intuitively apply the GFA in different resolution branches independently, and exchange features after the convolution module or attention module being executed like[27, 36]. But in high-resolution branch, pixels focus on local information more than high level global context. Thus, we suppose that directly conducting attention on high-resolution feature map for learning global context is not effective enough. To obtain the global context more effectively, we propose a cross-resolution attention, which aims to make

Figure 4: Illustrating the RTFormer architecture. We place RTFormer block at the last two stages which indicated by pink block and use convolution blocks at the earlier stages which indicated by blue block. Besides, we add a DAPPM module for segmentation head, drawing on the successful experience from[15].

full use of the high level semantic information learned from low-resolution branch. As exhibited in Figure 2, unlike GFA, cross-resolution attention is adopted in high-resolution branch for gathering global context. And the calculation of this cross-resolution attention is expressed as:

$$
CA(X_h, K_c, V_c) = Softmax(\frac{X_h \cdot K_c^T}{\sqrt{d_h}}) \cdot V_c
$$
$$
K_c, V_c = \phi(X_c) \quad X_c = \theta(X_l)
$$
(4)

where X_h, X_l denote the feature maps on high-resolution branch and low-resolution branch respectively, ϕ is a set of matrix operations including splitting, permutation and reshaping, d_h means the feature dimension of high-resolution branch. It is worth to explain that, the feature map X_c, denoted as cross-feature in the following text, is computed from X_l by function θ which is composed of pooling and convolution layers. And the spatial size of X_c indicates the number of tokens generated from the X_l. Experimentally, we only adopt softmax upon the last axis of attention map for normalization, as a single softmax performs better than double normalization when the key and value are not external parameters. Specially, for fast inference on GPU-like devices, multi-head mechanism is also discarded here.

Feed Forward Network. In the previous transformer-based segmentation methods like[32, 36], the Feed Forward Network(FFN) is typically consist of two MLP layers and a depth-wise 3×3 convolution layer, where the depth-wise 3×3 layer works for supplementing position encoding or enhancing locality. Besides, the two MLP layers expand the hidden dimension to be two or four times of the input dimension. This type of FFN can achieve better performance with relative less parameters. But in the scenario where latency on GPU-like devices should be considered, the typical structure of FFN is not very efficient. In order to balance the performance and efficiency, we adopt two 3×3 convolution layers without dimension expansion in the FFN of RTFormer block. And it shows even better result than the typical FFN configuration.

3.2 RTFormer

Figure 4 illustrates the overall architecture of RTFormer. Besides, the detailed configurations of RTFormer-Slim and RTFormer-Base will be provided in the supplementary material.

Backbone Architecture. For extracting enough local information which is needed by high-resolution feature map, we combines convolution layers with our proposed RTFormer block to construct RTFormer. Concretely, we let RTFormer start from a stem block consist of two 3×3 convolution layers and make up the first two stages with several successive basic residual blocks[14]. Then, from stage3, we use dual-resolution modules which enable feature exchange between high-resolution and low-resolution branches, inspired by[15]. And for the high-resolution branches of the last three stages, the feature strides keep as 8 unchanged, while for the low-resolution branches, the feature strides are 16, 32, 32 respectively. Specially, we arrange the dual-resolution module into stepped

layout for boosting the semantic representation of high-resolution feature with the help of the output of low-resolution branch. Most importantly, we construct the stage4 and stage5 with our proposed RTFormer block which is illustrated in Figure 2 for efficient global context modeling, while the stage3 is still composed by basic residual blocks.

Segmentation Head. For the segmentation head of RTFormer, we add a DAPPM module after low-resolution output feature, drawing on the successful experience from[15]. And after fusing the output of DAPPM with high-resolution feature, we obtain the output feature map with stride=8. Finally, this output feature is passed into a pixel-level classification head for predicting dense semantic labels. And the classification head is consist of a 3×3 convolution layer and a 1×1 convolution layer, with the hidden feature dimension being same with input feature dimension.

4 Experiments

In this section, we valid RTFormer on Cityscapes[8], Camvid[4] and ADE20K[44]. We first introduce the dataset with the training details. Then, we compare RTFormer with state-of-the-art real-time methods on Cityscapes and CamVid. Besides, more experiments on ADE20K[44] are summarised to further prove the generality of our method. Finally, ablation studies of different design modules within RTFormer block on ADE20K[44] are provided.

4.1 Implementation Details

Before finetuning on semantic segmentation, all models are pretained on ImageNet[9]. And the training details for ImageNet[9] will be provided in the supplementary material.

Cityscapes. Cityscapes[8] is a widely-used urban street scene parsing dataset, which contains 19 classes used for semantic segmentation task. And it has 2975, 500 and 1525 fine annotated images for training, validation, and testing respectively. We train all models using the AdamW optimizer with the initial learning rate 0.0004 and the weight decay of 0.0125. We adopt the poly learning policy with the power of 0.9 to drop the learning rate and implement the data augmentation method including random cropping into 512×1024, random scaling in the range of 0.5 to 2.0, and random horizontal flipping. All models are trained with 484 epochs (about 120K iterations), a batch size of 12, and syncBN on four V100 GPUs. For a fair comparison with other algorithms, online hard example mining(OHEM) is not used.

CamVid. CamVid[4] contains 701 densely annotated frames and the resolution of each frame is 720×960. These frames are divided into 367 training images, 101 validation images, and 233 testing images. CamVid[4] have 32 categories which has the subset of 11 classes are used for segmentation experiments. We merge the training set and validation set for training and evaluate our models on the testing set. We set the initial learning rate to 0.001 and the weight decay to 0.05. The power of poly learning policy is set to 1.0. We train all models for 968 epochs. Data augmentation includes color jitter, random horizontal flipping, random cropping into 720×960 and random scaling of [288, 1152]. Unlike previous methods[11], we do not pretrain our model on Cityscapes[8]. All other training details are the same as for Cityscapes[8].

ADE20K. ADE20K[44] is a scene parsing dataset covering 150 fine-grained semantic concepts, which split 20K, 2K, and 3K images for training, validation, and testing, respectively. Our models are trained with a batch size of 16 for 160k iterations. And we set the initial learning rate to 0.0001 and the weight decay to 0.05, and the other training settings are identical to those for Cityscapes[8].

4.2 Comparison with State-of-the-arts

In this part, we compare our RTFormer with state-of-the-art methods on Cityscapes[8] and CamVid[4]. Table 1 shows our results including parameters, FPS and mIoU for Cityscapes[8] and CamVid[4].

Results On Cityscapes[8], our RTFormer owns the best speed-accuracy trade-off among all other real-time methods. For example, our RTFormer-Slim achieves 76.3% mIoU at 110.0 FPS which is faster and provides better mIoU compared to STDC2-Seg75[11] and DDRNet-23-Slim[12]. Besides, our RTFormer-Base achieves 39.1 FPS and 79.3% mIoU which establishes new state-of-the-art result. Further more, using only ImageNet[9] pre-training, our method achieves 82.5% mIoU at 94.0 FPS on CamVid[4], significantly outperforms all other real-time methods including STDC2-Seg[11] which

Table 1: **Comparisons with other with other state-of-the-art real-time methods on Cityscapes and CamVid.** Performances are measured with a single crop of 1024×2048, 720×960 for Cityscapes and CamVid respectively. #Params refers to the number of parameters. FPS is calculateted under the same input scale as performance measuring. In this table, * means we retrain this method follows its original training setting, and $\dot{+}$ means we measure the FPS on single RTX 2080Ti GPU.

Method	Encoder	#Params↓	GPU	Cityscapes		CamVid	
				FPS↑	val mIoU(%)↑	FPS↑	test mIoU(%)↑
ICNet [41]	-	-	TitanX M	30.3	67.7	27.8	67.1
DFANet A [18]	Xception A	7.8M	TitanX	100.0	-	120.0	64.7
DFANet B [18]	Xception B	4.8M	TitanX	120.0	-	160.0	59.3
CAS [39]	-	-	TitanX	108.0	71.6	169.0	71.2
GAS [21]	-	-	TitanX	108.4	72.4	153.1	72.8
DF1-Seg-d8 [20]	DF1	-	GTX 1080Ti	136.9	72.4	-	-
DF1-Seg [20]	DF1	-	GTX 1080Ti	106.4	74.1	-	-
DF2-Seg1 [20]	DF2	-	GTX 1080Ti	67.2	75.9	-	-
DF2-Seg2 [20]	DF2	-	GTX 1080Ti	56.3	76.9	-	-
BiSeNet1 [35]	Xception39	5.8M	GTX 1080Ti	105.8	69.0	175.0	65.6
BiSeNet2 [35]	ResNet18	49.0M	GTX 1080Ti	65.5	74.8	116.3	68.7
BiSeNetV2[34]	-	-	GTX 1080Ti	156.0	73.4	124.5	72.4
BiSeNetV2-L [34]	-	-	GTX 1080Ti	47.3	75.8	32.7	73.2
SFNet [19]	ResNet18	12.9M	RTX 2080Ti	-	-	62.9$\dot{+}$	73.8
FasterSeg [7]	-	4.4M	RTX 2080Ti	136.2$\dot{+}$	73.1	-	71.1
STDC1-Seg75[11]	STDC1	14.2M	RTX 2080Ti	74.6$\dot{+}$	74.5	-	-
STDC2-Seg75[11]	STDC2	22.2M	RTX 2080Ti	73.5$\dot{+}$	77.0	-	-
STDC1-Seg[11]	STDC1	14.2M	RTX 2080Ti	-	-	125.6$\dot{+}$	73.0
STDC2-Seg[11]	STDC2	22.2M	RTX 2080Ti	-	-	100.5$\dot{+}$	73.9
DDRNet-23-Slim [15]	-	5.7M	RTX 2080Ti	101.0$\dot{+}$	76.1	217.0$\dot{+}$	74.7
DDRNet-23 [15]	-	20.1M	RTX 2080Ti	38.3$\dot{+}$	78.9*	97.1$\dot{+}$	76.3
RTFormer-Slim(Ours)	-	4.8M	RTX 2080Ti	110.0$\dot{+}$	76.3	190.7$\dot{+}$	81.4
RTFormer-Base(Ours)	-	16.8M	RTX 2080Ti	39.1$\dot{+}$	79.3	94.0$\dot{+}$	82.5

| (a) Image | (b) Ground Truth | (c) DDRNet-23 | (d) RTFormer-Base |

Figure 5: **Qualitative results on CamVid[4] testing set.** Compared to DDRNet-23[12], RTFormer predicts masks with finer details and reduces long-range errors as highlighted in white.

uses additional Cityscapes[8] pre-training. Moreover, Our RTFormer-Slim yields 81.4 mIoU at 190.7 FPS with only 4.8M, which is faster and better than other models like STDC2-Seg[11] at 125.6FPS and DDRNet-23[15] at 97.1FPS. Figure 5 shows the qualitative results on CamVid[4] testing set, where RTFormer-base provides better detail than DDRNet-23[15], especially for the Column Pole class , which requires more global context. In summary, these results demonstrate the superiority of RTFormer in real-time semantic segmentation in terms of accuracy, latency, and model size.

4.3 Generalization Capability

To further prove the effectiveness of our RTFormer on more generalized scene, we show additional results on ADE20K[44].

Table 2: **Comparisons with other with other state-of-the-art real-time methods on ADE20K.** The #Params, FLOPs and FPS are measured at resolution 512×2048. #Params refers to the number of parameters. In this table, * means that we retrain this model by ourself on ADE20K[44]. $\dotplus$ means we measure the FPS using single RTX 2080Ti GPU. Method without $\dotplus$ is using its reported #Params, FLOPs, FPS and mIoU.

Method	Encoder	#Params↓	FLOPs↓	FPS↑	val mIoU(%)↑
FCN [24]	MobileNetV2	9.8M	39.0G	64.4	19.7
PSPNet[42]	MobileNetV2	13.7M	52.9G	57.7	29.6
DeepLabV3+ [6]	MobileNetV2	15.4M	69.4G	43.1	34.0
SegFormer [32]	MiT-B0	3.8M	8.4G	50.5	37.4
DDRNet-23-Slim [15]	-	5.6M	18.2G	189.1$\dotplus$	33.3*
DDRNet-23[15]	-	20.1M	71.6G	71.2$\dotplus$	38.8*
RTFormer-Slim(Ours)	-	4.8M	17.5G	187.9	36.7
RTFormer-Base(Ours)	-	16.8M	67.4G	71.4	42.1

(a) Image (b) Ground Truth (c) DDRNet-23 (d) GFDFormer-base

Figure 6: **Qualitative results on ADE20K[44] validation set.** As shown, RTFormer is good at focusing on global context.

Results. Tabel 2 presents our result on ADE20K[44].Our RTFormer-Base archieves the superior mIoU of 42.1% and with 71.4FPS, which outperforms all other methods. For instances, in contrast to DDRNet-23-Slim[15], RTFormer-Slim achieves better mIoU 36.7% and maintains nearly the same speed. Figure 6 shows qualitative results on ADE20K validation set. Compared with DDRNet-23[15], our RTFormer shows better details and context information. In summary, these results demonstrate that RTFormer also shows very promising performance on real-time semantic segmentation in generalized scene.

4.4 Ablation study on ADE20K

Training Setup. We provide ablation results with RTFormer-Slim. To make quick evaluations, we train RTFormer-slim from scratch with the initial learning rate being set to 0.001, and the other settings are same with experiments on ADE20K[44] above.

Comparison on different types of attention. To verify the effectiveness of our proposed attentions, we replace the attentions used in RTFormer block with different types and combinations. As shown in Table 3a, we give the results of different combinations of multi-head external attention, GPU-Friendly attention and cross-resolution attention. For instance, "GFA+CA" means using GFA in low-resolution branch and CA in high-resolution branch. In addition, we adjust the hyper parameter M in multi-head external attention by $M = d \times r$, where r is a reduction ratio. We can find that GPU-Friendly attention outperforms all settings of multi-head external attention and faster than the best one when $M = d$. That indicates GPU-Friendly attention achieves better trade-off between performance and efficiency than multi-head external attention on GPU-like devices. When we introduce cross-resolution attention, the performance improves further, while the FPS only drops less than 2.

Table 3: **Ablation studies on different types of attention, FFN and different settings of hyper parameters.**

(a) Comparison on different types of attention. EA, GFA, CA denote External Attention, GPU-Friendly Attention and Cross-resolution Attention respectively.

Attention	FPS↑	mIoU(%)↑
EA+EA (r=1)	180.8	32.2
EA+EA (r=0.125)	196.9	31.9
EA+EA (r=0.25)	189.6	32.0
GFA+GFA	189.8	32.8
GFA+CA	187.9	33.0

(b) Comparison of different types of FFN. The typical FFN is composed of two MLP layers and a 3×3 depth-wise convolution layer, and our FFN design is two 3×3 convolution layers.

Method	FPS↑	mIoU(%)↑
Typical FFN	178.5	32.15
Our FFN	187.9	33.0

(c) Comparison of different number of groups in Grouped Double Normalization.

# of Groups	FPS↑	mIoU(%)↑
1, 1	189.8	32.2
4, 1	189.8	32.3
8, 2	189.8	32.8

(d) Comparison of different spatial size of the cross-feature in Cross-resolution Attention.

# of Parameters	FPS↑	mIoU(%)↑
6×6	191.6	32.85
8×8	189.8	33.00
12×12	175.6	32.94

Comparison on different types of FFN. Table 3b illustrates the results of typical FFN which is consist of two MLP layers and a 3×3 depth-wise convolution layer and our proposed FFN containing two 3×3 convolution layers. It is shown that our proposed FFN outperforms typical FFN not only on mIoU but also on FPS. That indicates that our proposed FFN is more suitable in the scenario when latency on GPU-like devices should be considered.

Influence of the number of groups within grouped double normalization. We study the influence of the number of group in grouped double normalization under the setting of using GPU-Friendly Attention for both branches. And Table 3c shows the results of different configurations. For example, "8+2" means using 8 groups in low-resolution branch and 2 groups in high-resolution. Specially, when the number of groups is set to 1, grouped double normalization degrades to the original double normalization. Here, the best mIoU is achieved when the numbers of groups are 8 and 2, which illustrates that the grouped double normalization performs better than the original double normalization. And it is worth to be noted that, changing the number of groups in grouped double normalization does not affect the inference efficiency, which makes GPU-Friendly attention being able to keep high FPS when the number of groups is large.

Influence of the spatial size of cross-feature in Cross-resolution Attention. We also investigate the spatial size of cross-feature in cross-resolution attention, including applying 6×6, 8×8, and 12×12. As presented in Table 3d, 8×8 spatial size of cross-feature for RTFormer-Slim is the best according to the trade-off between FPS and mIoU. To some extent, it indicates that the spatial size of cross-feature which is close to the dimension of high-resolution feature is appropriate, as the high-resolution feature dimension of RTFormer-Slim is 64 which equals to 8×8.

5 Conclusion

In this paper, we present RTFormer which can efficiently capture the global context to improve the real-time semantic segmentation performance. Extensive experiments demonstrate that our method not only achieves new state-of-the-art results on common datasets for real-time segmentation but also shows superior performance on challenging dataset for general semantic segmentation. Due to the efficiency of RTFormer, we hope our method can encourage new design of real-time semantic segmentation with transformer. One limitation is that although our RTFormer-Slim only has 4.8M parameters, it may be needed more parameter efficiency in a chip of edge device. We leave it for future work.

References

[1] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Süsstrunk. Slic superpixels compared to state-of-the-art superpixel methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 34(11):2274–2282, 2012.

[2] Vijay Badrinarayanan, Alex Kendall, and Roberto Cipolla. Segnet: A deep convolutional encoder-decoder architecture for image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(12):2481–2495, 2017.

[3] Y.Y. Boykov and M.-P. Jolly. Interactive graph cuts for optimal boundary amp; region segmentation of objects in n-d images. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*, volume 1, pages 105–112 vol.1, 2001.

[4] Gabriel J. Brostow, Jamie Shotton, Julien Fauqueur, and Roberto Cipolla. Segmentation and recognition using structure from motion point clouds. In *ECCV (1)*, pages 44–57, 2008.

[5] Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *CoRR*, abs/1706.05587, 2017.

[6] Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In *Proceedings of the European conference on computer vision (ECCV)*, pages 801–818, 2018.

[7] Wuyang Chen, Xinyu Gong, Xianming Liu, Qian Zhang, Yuan Li, and Zhangyang Wang. Fasterseg: Searching for faster real-time semantic segmentation. *arXiv preprint arXiv:1912.10917*, 2019.

[8] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. *CoRR*, abs/1604.01685, 2016.

[9] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[10] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *CoRR*, abs/2010.11929, 2020.

[11] Mingyuan Fan, Shenqi Lai, Junshi Huang, Xiaoming Wei, Zhenhua Chai, Junfeng Luo, and Xiaolin Wei. Rethinking bisenet for real-time semantic segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9716–9725, 2021.

[12] Jun Fu, Jing Liu, Haijie Tian, Yong Li, Yongjun Bao, Zhiwei Fang, and Hanqing Lu. Dual attention network for scene segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3146–3154, 2019.

[13] Meng-Hao Guo, Zheng-Ning Liu, Tai-Jiang Mu, and Shi-Min Hu. Beyond self-attention: External attention using two linear layers for visual tasks. *arXiv preprint arXiv:2105.02358*, 2021.

[14] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[15] Yuanduo Hong, Huihui Pan, Weichao Sun, and Yisong Jia. Deep dual-resolution networks for real-time and accurate semantic segmentation of road scenes. *arXiv preprint arXiv:2101.06085*, 2021.

[16] Han Hu, Jiayuan Gu, Zheng Zhang, Jifeng Dai, and Yichen Wei. Relation networks for object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3588–3597, 2018.

[17] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7132–7141, 2018.

[18] Hanchao Li, Pengfei Xiong, Haoqiang Fan, and Jian Sun. Dfanet: Deep feature aggregation for real-time semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9522–9531, 2019.

[19] Xiangtai Li, Ansheng You, Zhen Zhu, Houlong Zhao, Maoke Yang, Kuiyuan Yang, Shaohua Tan, and Yunhai Tong. Semantic flow for fast and accurate scene parsing. In *European Conference on Computer Vision*, pages 775–793. Springer, 2020.

[20] Xin Li, Yiming Zhou, Zheng Pan, and Jiashi Feng. Partial order pruning: for best speed/accuracy trade-off in neural architecture search. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9145–9153, 2019.

[21] Peiwen Lin, Peng Sun, Guangliang Cheng, Sirui Xie, Xi Li, and Jianping Shi. Graph-guided architecture search for real-time semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4203–4212, 2020.

[22] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *CoRR*, abs/2103.14030, 2021.

[23] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. *CoRR*, abs/1411.4038, 2014.

[24] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3431–3440, 2015.

[25] Nobuyuki Otsu. A threshold selection method from gray-level histograms. *IEEE Transactions on Systems, Man, and Cybernetics*, 9(1):62–66, 1979.

[26] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. *CoRR*, abs/2012.12877, 2020.

[27] Jingdong Wang, Ke Sun, Tianheng Cheng, Borui Jiang, Chaorui Deng, Yang Zhao, Dong Liu, Yadong Mu, Mingkui Tan, Xinggang Wang, et al. Deep high-resolution representation learning for visual recognition. *IEEE transactions on pattern analysis and machine intelligence*, 43(10):3349–3364, 2020.

[28] Qiangchang Wang, Tianyi Wu, He Zheng, and Guodong Guo. Hierarchical pyramid diverse attention networks for face recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8326–8335, 2020.

[29] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 568–578, 2021.

[30] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pvt v2: Improved baselines with pyramid vision transformer. *Computational Visual Media*, pages 1–10, 2022.

[31] Xiaolong Wang, Ross Girshick, Abhinav Gupta, and Kaiming He. Non-local neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7794–7803, 2018.

[32] Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. *Advances in Neural Information Processing Systems*, 34, 2021.

[33] Saining Xie, Sainan Liu, Zeyu Chen, and Zhuowen Tu. Attentional shapecontextnet for point cloud recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4606–4615, 2018.

[34] Changqian Yu, Changxin Gao, Jingbo Wang, Gang Yu, Chunhua Shen, and Nong Sang. Bisenet v2: Bilateral network with guided aggregation for real-time semantic segmentation. *International Journal of Computer Vision*, 129(11):3051–3068, 2021.

[35] Changqian Yu, Jingbo Wang, Chao Peng, Changxin Gao, Gang Yu, and Nong Sang. Bisenet: Bilateral segmentation network for real-time semantic segmentation. In *Proceedings of the European conference on computer vision (ECCV)*, pages 325–341, 2018.

[36] Yuhui Yuan, Rao Fu, Lang Huang, Weihong Lin, Chao Zhang, Xilin Chen, and Jingdong Wang. Hrformer: High-resolution vision transformer for dense predict. *Advances in Neural Information Processing Systems*, 34, 2021.

[37] Yuhui Yuan, Lang Huang, Jianyuan Guo, Chao Zhang, Xilin Chen, and Jingdong Wang. Ocnet: Object context network for scene parsing. *arXiv preprint arXiv:1809.00916*, 2018.

[38] Xiaohua Zhai, Alexander Kolesnikov, Neil Houlsby, and Lucas Beyer. Scaling vision transformers. *CoRR*, abs/2106.04560, 2021.

[39] Yiheng Zhang, Zhaofan Qiu, Jingen Liu, Ting Yao, Dong Liu, and Tao Mei. Customizable architecture search for semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11641–11650, 2019.

[40] Hengshuang Zhao, Xiaojuan Qi, Xiaoyong Shen, Jianping Shi, and Jiaya Jia. Icnet for real-time semantic segmentation on high-resolution images. In *Proceedings of the European conference on computer vision (ECCV)*, pages 405–420, 2018.

[41] Hengshuang Zhao, Xiaojuan Qi, Xiaoyong Shen, Jianping Shi, and Jiaya Jia. Icnet for real-time semantic segmentation on high-resolution images. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

[42] Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2881–2890, 2017.

[43] Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip HS Torr, et al. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 6881–6890, 2021.

[44] Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba. Semantic understanding of scenes through the ADE20K dataset. *CoRR*, abs/1608.05442, 2016.