Contrastive Neural Ratio Estimation

Abstract

Likelihood-to-evidence ratio estimation is usually cast as either a binary (NRE-A) or a multiclass (NRE-B) classification task. In contrast to the binary classification framework, the current formulation of the multiclass version has an intrinsic and unknown bias term, making otherwise informative diagnostics unreliable. We propose a multiclass framework free from the bias inherent to NRE-B at optimum, leaving us in the position to run diagnostics that practitioners depend on. It also recovers NRE-A in one corner case and NRE-B in the limiting case. For fair comparison, we benchmark the behavior of all algorithms in both familiar and novel training regimes: when jointly drawn data is unlimited, when data is fixed but prior draws are unlimited, and in the commonplace fixed data and parameters setting. Our investigations reveal that the highest performing models are distant from the competitors (NRE-A, NRE-B) in hyperparameter space. We make a recommendation for hyperparameters distinct from the previous models.

1 Introduction

We begin with a motivating example: Consider the task of inferring the mass of an exoplanet θ_o from the light curve observations x_o of a distant star. We design a computer program that maps hypothetical mass θ to a simulated light curve x using relevant physical theory. Our simulator computes x from θ, but the inverse mapping is unspecified and likely intractable. *Simulation-based inference* (SBI) puts this problem in a probabilistic context [13, 61]. Although we cannot analytically evaluate it, we assume that the simulator is sampling from the conditional probability distribution $p(x \mid \theta)$. After specifying a prior $p(\theta)$, the inverse amounts to estimating the posterior $p(\theta \mid x_o)$. This problem setting occurs across scientific domains [1, 7, 10, 11, 29] where θ generally represents input parameters of the simulator and x the simulated output observation. Our design goal is to produce a surrogate model $\hat{p}(\theta \mid x)$ approximating the posterior for any data x while limiting excessive simulation.

Figure 1: Conceptual, interpolated map from investigated hyperparameters of proposed algorithm NRE-C to a measurement of posterior exactness using the Classifier Two-Sample Test. Best 0.5, worst 1.0. Red dot indicates NRE-A's hyperparameters, $\gamma = 1$ and $K = 1$ [30]. Purple line implies NRE-B [16] with $\gamma = \infty$ and $K \geq 1$. NRE-C covers the entire plane, generalizing other methods. Best performance occurs with $K \gg 1$ and $\gamma \approx 1$, in contrast with the settings of existing algorithms.

Density estimation [5, 51, 52] can fit the likelihood [2, 15, 43, 53] or posterior [6, 21, 42, 50] directly; however, an appealing alternative for practitioners is estimating a *ratio* between distributions [12, 16, 30, 34, 65]. Specifically, the likelihood-to-evidence ratio $\frac{p(\boldsymbol{\theta} \mid \boldsymbol{x})}{p(\boldsymbol{\theta})} = \frac{p(\boldsymbol{x} \mid \boldsymbol{\theta})}{p(\boldsymbol{x})} = \frac{p(\boldsymbol{\theta}, \boldsymbol{x})}{p(\boldsymbol{\theta})p(\boldsymbol{x})}$. Unlike the other methods, ratio estimation enables easy aggregation of independent and identically drawn data $\boldsymbol{x}$, an importance sampling-based diagnostic, and estimating the mutual information, see Appendix D

Estimating $\frac{p(\boldsymbol{x} \mid \boldsymbol{\theta})}{p(\boldsymbol{x})}$ can be formulated as a binary classification task [30], where the classifier $\sigma \circ f_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x})$ distinguishes between pairs $(\boldsymbol{\theta}, \boldsymbol{x})$ sampled either from the joint distribution $p(\boldsymbol{\theta}, \boldsymbol{x})$ or the product of its marginals $p(\boldsymbol{\theta})p(\boldsymbol{x})$. We call it NRE-A. The optimal classifier has

$$f_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x}) \approx \log \frac{p(\boldsymbol{\theta} \mid \boldsymbol{x})}{p(\boldsymbol{\theta})}. \tag{1}$$

Here, σ represents the sigmoid function, $\circ$ implies function composition, and $f_{\boldsymbol{w}}$ is a neural network with weights $\boldsymbol{w}$. As a part of an effort to unify different SBI methods and to improve simulation-efficiency, Durkan et al. [16] reformulated the classification task to identify which of K possible $\boldsymbol{\theta}_k$ was responsible for simulating $\boldsymbol{x}$. We refer to it as NRE-B. At optimum

Figure 2: Schematic depicts how the loss is computed in NRE algorithms. $(\boldsymbol{\theta}, \boldsymbol{x})$ pairs are sampled from distributions at the top of the figure, entering the loss functions as depicted. NRE-C controls the number of contrastive classes with K and the weight of independent and dependent terms with p_0 and p_K. NRE-C generalizes other algorithms. Hyperparameters recovering NRE-A and NRE-B are listed next to the name within the dashed areas. Notation details are defined in Section 2.1.

$$g_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x}) \approx \log \frac{p(\boldsymbol{\theta} \mid \boldsymbol{x})}{p(\boldsymbol{\theta})} + c_{\boldsymbol{w}}(\boldsymbol{x}), \tag{2}$$

where an additional bias, $c_{\boldsymbol{w}}(\boldsymbol{x})$, appears. $g_{\boldsymbol{w}}$ represents another neural network, see Section 2.1.

The $c_{\boldsymbol{w}}(\boldsymbol{x})$ term nullifies many of the advantages ratio estimation offers. Practitioners wishing to perform necessary verification of their SBI results can no longer perform an importance sampling-based diagnostic. $c_{\boldsymbol{w}}(\boldsymbol{x})$ can be arbitrarily pathological in $\boldsymbol{x}$, meaning that the normalizing constant can take on extreme values.

Details about SBI are in Appendix A. There is a distinction in deep learning-based SBI between *amortized* and *sequential* algorithms which produce surrogate models that estimate any posterior $p(\boldsymbol{\theta} \mid \boldsymbol{x})$ or a specific posterior $p(\boldsymbol{\theta} \mid \boldsymbol{x}_o)$ respectively. Amortized algorithms sample parameters from the prior, while sequential algorithms use an alternative proposal distribution–increasing efficiency at the expense of flexibility. Tejero-Cantero et al. [64] implement both kinds of SBI models.

Contribution We design a more general formulation of likelihood-to-evidence ratio estimation as a multiclass problem in which the bias inherent to NRE-B is discouraged by the loss function and it does not appear at optimum. Figure 1 diagrams the interpolated performance as a function of hyperparameters. It shows which settings recover NRE-A and NRE-B, also indicating that highest performance occurs with settings distant from these. Figure 2 shows the relationship of the loss functions. We call our framework NRE-C[1] and expound the details in Section 2.

An existing importance sampling diagnostic [30] tests whether a classifier can distinguish $p(\boldsymbol{x} \mid \boldsymbol{\theta})$ samples from from samples from $p(\boldsymbol{x})$ weighted by the estimated ratio. We demonstrate that our proposed NRE-C passes this diagnostic while NRE-B does not.

---

[1]The code for our project is forthcoming and to be released under the Apache License 2.0.

80 We evaluate NRE-B and NRE-C in a fair comparison in several training regimes in Section 3. We
81 perform a hyperparameter search on three simulators with tractable likelihood by benchmarking the
82 behavior when (a) jointly drawn pairs $(\boldsymbol{\theta}, \boldsymbol{x})$ are unlimited or when jointly drawn pairs $(\boldsymbol{\theta}, \boldsymbol{x})$ are
83 fixed but we (b) can draw from the prior $p(\boldsymbol{\theta})$ without limit or (c) are restricted to the initial pairs. We
84 also perform the SBI benchmark of Lueckmann et al. [44] with our recommended hyperparameters.

2 Methods

86 The ratio between probability distributions can be estimated using the "likelihood ratio trick" by
87 training a classifier to distinguish samples [12, 19, 27, 30, 47, 62, 65]. We first summarize the
88 loss functions of NRE-A and NRE-B which approximate the *intractable* likelihood-to-evidence ratio
89 $r(\boldsymbol{x} \mid \boldsymbol{\theta}) \coloneqq \frac{p(\boldsymbol{x} \mid \boldsymbol{\theta})}{p(\boldsymbol{x})}$. We then elaborate on our proposed generalization, NRE-C. Finally, we explain
90 how to recover NRE-A and NRE-B within our framework and comment on the normalization properties.

91 **NRE-A** Hermans et al. [30] train a binary classifier to distinguish $(\boldsymbol{\theta}, \boldsymbol{x})$ pairs drawn dependently
92 $p(\boldsymbol{\theta}, \boldsymbol{x})$ from those drawn independently $p(\boldsymbol{\theta})p(\boldsymbol{x})$. This classifier is parameterized by a neural
93 network $f_{\boldsymbol{w}}$ which approximates $\log r(\boldsymbol{x} \mid \boldsymbol{\theta})$. We seek optimal network weights

$$\boldsymbol{w}^* \in \arg\min_{\boldsymbol{w}} -\frac{1}{2B} \left[\sum_{b=1}^{B} \log \left(1 - \sigma \circ f_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b)}, \boldsymbol{x}^{(b)}) \right) + \sum_{b'=1}^{B} \log \left(\sigma \circ f_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b')}, \boldsymbol{x}^{(b')}) \right) \right] \quad (3)$$

94 $\boldsymbol{\theta}^{(b)}, \boldsymbol{x}^{(b)} \sim p(\boldsymbol{\theta})p(\boldsymbol{x})$ and $\boldsymbol{\theta}^{(b')}, \boldsymbol{x}^{(b')} \sim p(\boldsymbol{\theta}, \boldsymbol{x})$ over B samples. NRE-A's ratio estimate converges
95 to $f_{\boldsymbol{w}^*} = \log \frac{p(\boldsymbol{x} \mid \boldsymbol{\theta})}{p(\boldsymbol{x})}$ given unlimited model flexibility and data. Details can be found in Appendix A.

96 **NRE-B** Durkan et al. [16] train a classifier that selects from among K parameters $(\boldsymbol{\theta}_1, \ldots, \boldsymbol{\theta}_K)$
97 which could have generated $\boldsymbol{x}$, in contrast with NRE-A's binary possibilities. One of these parameters
98 $\boldsymbol{\theta}_k$ is *always* drawn jointly with $\boldsymbol{x}$. The classifier is parameterized by a neural network $g_{\boldsymbol{w}}$ which
99 approximates $\log r(\boldsymbol{x} \mid \boldsymbol{\theta})$. Training is done over B samples by finding

$$\boldsymbol{w}^* \in \arg\min_{\boldsymbol{w}} \left[-\frac{1}{B} \sum_{b'=1}^{B} \log \frac{\exp \circ g_{\boldsymbol{w}}(\boldsymbol{\theta}_k^{(b')}, \boldsymbol{x}^{(b')})}{\sum_{i=1}^{K} \exp \circ g_{\boldsymbol{w}}(\boldsymbol{\theta}_i^{(b')}, \boldsymbol{x}^{(b')})} \right] \quad (4)$$

100 where $\boldsymbol{\theta}_1^{(b')}, \ldots, \boldsymbol{\theta}_K^{(b')} \sim p(\boldsymbol{\theta})$ and $\boldsymbol{x}^{(b')} \sim p(\boldsymbol{x} \mid \boldsymbol{\theta}_k^{(b')})$. Given unlimited model flexibility and data
101 NRE-B's ratio estimate converges to $g_{\boldsymbol{w}^*}(\boldsymbol{\theta}, \boldsymbol{x}) = \log \frac{p(\boldsymbol{\theta} \mid \boldsymbol{x})}{p(\boldsymbol{\theta})} + c_{\boldsymbol{w}^*}(\boldsymbol{x})$. Details are in Appendix A.

2.1 Contrastive Neural Ratio Estimation

103 Our proposed algorithm NRE-C trains a classifier to identify which $\boldsymbol{\theta}$ among K candidates is
104 responsible for generating a given $\boldsymbol{x}$, inspired by NRE-B. We added another option that indicates $\boldsymbol{x}$
105 was drawn independently, inspired by NRE-A. The introduction of the additional class yields a ratio
106 without the specific $c_{\boldsymbol{w}}(\boldsymbol{x})$ bias at convergence. Define $\boldsymbol{\Theta} \coloneqq (\boldsymbol{\theta}_1, ..., \boldsymbol{\theta}_K)$ and conditional probaiblity

$$p_{\text{NRE-C}}(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = k) \coloneqq \begin{cases} p(\boldsymbol{\theta}_1) \cdots p(\boldsymbol{\theta}_K) p(\boldsymbol{x}) & k = 0 \\ p(\boldsymbol{\theta}_1) \cdots p(\boldsymbol{\theta}_K) p(\boldsymbol{x} \mid \boldsymbol{\theta}_k) & k = 1, \ldots, K \end{cases}. \quad (5)$$

107 We set marginal probabilities $p(y = k) \coloneqq p_K$ for all $k \geq 1$ and $p(y = 0) \coloneqq p_0$. Yielding the
108 relationship $p_0 = 1 - K p_K$. Let the odds of any pair being drawn dependently to completely
109 independently be $\gamma \coloneqq \frac{K p_K}{p_0}$. We now use Bayes' formula to compute the conditional probability

$$\begin{aligned} p(y = k \mid \boldsymbol{\Theta}, \boldsymbol{x}) &= \frac{p(y = k)\, p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = k)/p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = 0)}{\sum_{i=0}^{K} p(y = i)\, p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = i)/p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = 0)} \\ &= \frac{p(y = k)\, p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = k)/p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = 0)}{p(y = 0) + \sum_{i=1}^{K} p(y = i)\, p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = i)/p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y = 0)} \\ &= \begin{cases} \frac{K}{K + \gamma \sum_{i=1}^{K} r(\boldsymbol{x} \mid \boldsymbol{\theta}_i)} & k = 0 \\ \frac{\gamma\, r(\boldsymbol{x} \mid \boldsymbol{\theta}_k)}{K + \gamma \sum_{i=1}^{K} r(\boldsymbol{x} \mid \boldsymbol{\theta}_i)} & k = 1, \ldots, K \end{cases}. \end{aligned} \quad (6)$$

We dropped the NRE-C subscript and substituted in γ to replace the $p(y)$ class probabilities. We train a classifier, parameterized by neural network $h_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x})$ with weights $\boldsymbol{w}$, to approximate (6) by

$$q_{\boldsymbol{w}}(y = k \mid \boldsymbol{\Theta}, \boldsymbol{x}) = \begin{cases} \frac{K}{K + \gamma \sum_{i=1}^{K} \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}_i, \boldsymbol{x})} & k = 0 \\ \frac{\gamma \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}_k, \boldsymbol{x}))}{K + \gamma \sum_{i=1}^{K} \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}_i, \boldsymbol{x})} & k = 1, \dots, K. \end{cases} \tag{7}$$

We note that (7) still satisfies $\sum_{k=0}^{K} q_{\boldsymbol{w}}(y = k \mid \boldsymbol{\Theta}, \boldsymbol{x}) = 1$, no matter the parameterization.

Optimization We design a loss function that encourages $h_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x}) = \log \frac{p(\boldsymbol{x} \mid \boldsymbol{\theta})}{p(\boldsymbol{x})}$ at convergence, and holds at optimum with unlimited flexibility and data. We introduce the cross entropy loss

$$\ell(\boldsymbol{w}) := \mathbb{E}_{p(y, \boldsymbol{\Theta}, \boldsymbol{x})} \left[-\log q_{\boldsymbol{w}}(y \mid \boldsymbol{\Theta}, \boldsymbol{x}) \right]$$

$$= -p_0 \mathbb{E}_{p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y=0)} \left[\log q_{\boldsymbol{w}}(y = 0 \mid \boldsymbol{\Theta}, \boldsymbol{x}) \right] - p_K \sum_{k=1}^{K} \mathbb{E}_{p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y=k)} \left[\log q_{\boldsymbol{w}}(y = k \mid \boldsymbol{\Theta}, \boldsymbol{x}) \right]$$

$$= -p_0 \mathbb{E}_{p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y=0)} \left[\log q_{\boldsymbol{w}}(y = 0 \mid \boldsymbol{\Theta}, \boldsymbol{x}) \right] - K p_K \mathbb{E}_{p(\boldsymbol{\Theta}, \boldsymbol{x} \mid y=K)} \left[\log q_{\boldsymbol{w}}(y = K \mid \boldsymbol{\Theta}, \boldsymbol{x}) \right] \tag{8}$$

and minimize it towards $\boldsymbol{w}^* \in \arg\min_{\boldsymbol{w}} \ell(\boldsymbol{w})$. We point out that the final term is symmetric up to permutation of $\boldsymbol{\Theta}$, enabling the replacement of the sum by multiplication with K. When γ and K are known, $p_0 = \frac{1}{1+\gamma}$ and $p_K = \frac{1}{K} \frac{\gamma}{1+\gamma}$ under our constraints. Without loss of generality, we let $\boldsymbol{\theta}_1, \dots, \boldsymbol{\theta}_K \sim p(\boldsymbol{\theta})$ and $\boldsymbol{x} \sim p(\boldsymbol{x} \mid \boldsymbol{\theta}_K)$. An empirical estimate of the loss on B samples is therefore

$$\hat{\ell}_{\gamma, K}(\boldsymbol{w}) := -\frac{1}{B} \left[\frac{1}{1+\gamma} \sum_{b=1}^{B} \log q_{\boldsymbol{w}} \left(y = 0 \mid \boldsymbol{\Theta}^{(b)}, \boldsymbol{x}^{(b)} \right) \right.$$

$$\left. + \frac{\gamma}{1+\gamma} \sum_{b'=1}^{B} \log q_{\boldsymbol{w}} \left(y = K \mid \boldsymbol{\Theta}^{(b')}, \boldsymbol{x}^{(b')} \right) \right]. \tag{9}$$

In the first term, the classifier sees a completely independently drawn sample of $\boldsymbol{x}$ and $\boldsymbol{\Theta}$ while $\boldsymbol{\theta}_K$ is drawn jointly with $\boldsymbol{x}$ in the second term. In both terms, the classifier considers K choices. In practice, we bootstrap both $\boldsymbol{\theta}_1^{(b)}, \dots, \boldsymbol{\theta}_K^{(b)}$ and $\boldsymbol{\theta}_1^{(b')}, \dots, \boldsymbol{\theta}_{K-1}^{(b')}$ from the same mini-batch and compare them to the same $\boldsymbol{x}$, similarly to NRE-A and NRE-B. All proof is in Appendix B.

Recovering NRE-A and NRE-B NRE-C is general because specific hyperparameter settings recover NRE-A and NRE-B. To recover NRE-A one should set $\gamma = 1$ and $K = 1$ in (9) yielding

$$\hat{\ell}_{1,1}(\boldsymbol{w}) = -\frac{1}{2B} \left[\sum_{b=1}^{B} \log \frac{1}{1 + \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b)}, \boldsymbol{x}^{(b)})} + \sum_{b'=1}^{B} \log \frac{\exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b')}, \boldsymbol{x}^{(b')})}{1 + \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b')}, \boldsymbol{x}^{(b')})} \right]$$

$$= -\frac{1}{2B} \left[-\sum_{b=1}^{B} \log \left(1 - \sigma \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b)}, \boldsymbol{x}^{(b)}) \right) + \sum_{b'=1}^{B} \log \left(\sigma \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}^{(b')}, \boldsymbol{x}^{(b')}) \right) \right] \tag{10}$$

where we dropped the lower index. Recovering NRE-B requires taking the limit $\gamma \to \infty$ in the loss function. In that case, the first term goes to zero, and second term converges to the softmax function.

$$\hat{\ell}_{\infty, K}(\boldsymbol{w}) = \lim_{\gamma \to \infty} \hat{\ell}_{\gamma, K}(\boldsymbol{w}) = -\frac{1}{B} \left[\sum_{b'=1}^{B} \log \frac{\exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}_k, \boldsymbol{x}))}{\sum_{i=1}^{K} \exp \circ h_{\boldsymbol{w}}(\boldsymbol{\theta}_i, \boldsymbol{x})} \right] \tag{11}$$

is determined by substitution into (9). Both equations are obviously the same as their counterparts.

Estimating a normalized posterior In the limit of infinite data and infinite neural network capacity (width, depth) the optimal classifier trained using NRE-C (with $\gamma \in \mathbb{R}^+$) satisfies the equality:

$$h_{\boldsymbol{w}^*}(\boldsymbol{\theta}, \boldsymbol{x}) = \log \frac{p(\boldsymbol{\theta} \mid \boldsymbol{x})}{p(\boldsymbol{\theta})}. \tag{12}$$

In particular, we have that the following normalizing constant is trivial:

$$Z(\boldsymbol{x}) := \int \exp\left(h_{\boldsymbol{w}^*}(\boldsymbol{\theta}, \boldsymbol{x})\right) p(\boldsymbol{\theta})\, d\boldsymbol{\theta} = \int p(\boldsymbol{\theta} \mid \boldsymbol{x})\, d\boldsymbol{\theta} = 1. \tag{13}$$

This is a result of Lemma 1 in Appendix B. However, practitioners never operate in this setting, rather they use finite sample sizes and neural networks with limited capacity that are optimized locally. The non-optimal function $\exp(h_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x}))$ does not have a direct interpretation as a ratio of probability distributions, rather as the function to weigh the prior $p(\boldsymbol{\theta})$ to approximate the unnormalized posterior. In other words, we find the following approximation for the posterior $p(\boldsymbol{\theta} \mid \boldsymbol{x})$:

$$p_{\boldsymbol{w}}(\boldsymbol{\theta} \mid \boldsymbol{x}) := \frac{\exp(h_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x}))}{Z_{\boldsymbol{w}}(\boldsymbol{x})} p(\boldsymbol{\theta}), \qquad Z_{\boldsymbol{w}}(\boldsymbol{x}) := \int \exp\left(h_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x})\right) p(\boldsymbol{\theta})\, d\boldsymbol{\theta}, \tag{14}$$

where in general the normalizing constant is not trivial, i.e. $Z_{\boldsymbol{w}}(\boldsymbol{x}) \neq 1$. As stated above, the NRE-C (and NRE-A) objective encourages $Z_{\boldsymbol{w}}(\boldsymbol{x})$ to converge to 1. This is in sharp contrast to NRE-B, where even at optimum with an unrestricted function class a non-trivial $\boldsymbol{x}$-dependent bias term can appear.

There is no restriction on how pathological the NRE-B bias $c_{\boldsymbol{w}}(\boldsymbol{x})$ can be. Consider a minimizer of (4), the NRE-B loss function, $h_{\boldsymbol{w}^*} + c_{\boldsymbol{w}^*}(\boldsymbol{x})$. Adding any function $d(\boldsymbol{x})$ cancels out in the fraction and is also a minimizer of (4). This freedom complicates any numerical computation of the normalizing constant and renders the importance sampling diagnostic from Section 2.2 generally inapplicable. We report Monte Carlo estimates of $Z_{\boldsymbol{w}}(\boldsymbol{x})$ on a test problem across hyperparameters in Figure 13.

2.2 Measuring performance & ratio estimator diagnostics

SBI is difficult to verify because, for many use cases, the practitioner cannot compare surrogate $p_{\boldsymbol{w}}(\boldsymbol{\theta} \mid \boldsymbol{x})$ to the intractable ground truth $p(\boldsymbol{\theta} \mid \boldsymbol{x})$. Incongruous with the practical use case for SBI, much of the literature has focused on measuring the similarity between surrogate and posterior using two-samples tests on tractable problems. For comparison with literature, we first reference a two-sample exactness metric which requires a tractable posterior. We then discuss diagnostics which do not require samples from $p(\boldsymbol{\theta} \mid \boldsymbol{x})$, commenting on the relevance for each NRE algorithm with empirical results. In Appendix D, we find that a known variational bound to the mutual information is tractable to estimate within SBI, and that it bounds the average Kullback-Leibler divergence between surrogate and posterior. We use it to evaluate various models fairly at every epoch in Figure 5.

Comparing to a tractable posterior with estimates of exactness Quite a number of assessments of approximate posterior quality are available when samples can be drawn from both the ground truth posterior $\boldsymbol{\theta} \sim p(\boldsymbol{\theta} \mid \boldsymbol{x})$ and the approximation $\boldsymbol{\theta} \sim q(\boldsymbol{\theta} \mid \boldsymbol{x})$. In the deep learning-based SBI literature, exactness is measured as a function of computational cost, usually simulator calls. We investigate the simulation-efficiency of NRE-C in Section 3.3.

Based on the recommendations of Lueckmann et al. [44] our experimental results are measured using the Classifier Two-Sample Test (C2ST) [17, 40, 41]. A classifier is trained to distinguish samples from either the surrogate or the ground truth posterior. An average classification probability on holdout data of 1.0 implies that samples from each distribution are easily identified; 0.5 implies either the distributions are the same or the classifier does not have the capacity to distinguish them.

Importance sampling diagnostic An accurate likelihood-to-evidence weight transforms the data distribution into the likelihood by $p(\boldsymbol{x} \mid \boldsymbol{\theta}) = p(\boldsymbol{x}) r(\boldsymbol{x} \mid \boldsymbol{\theta})$. Since NRE necessitates simulator access, we can test the ratio estimator by training a classifier to distinguish unweighted $p(\boldsymbol{x} \mid \boldsymbol{\theta})$ samples from weighted $p(\boldsymbol{x}) \hat{r}(\boldsymbol{x} \mid \boldsymbol{\theta})$ samples, where $\hat{r}$ implies an estimate. Indistinguishability between samples implies either that the approximate ratio is accurate for parameter $\boldsymbol{\theta}$ or that the classifier does not have sufficient power to find predictive features. Issues with classification power can be detected by assessing the classifier's ability to distinguish $p(\boldsymbol{x})$ from $p(\boldsymbol{x} \mid \boldsymbol{\theta})$. The performance can be visualized in a receiver operating curve (ROC) or measured by the area under the curve (ROC AUC). This diagnostic has been used for ratio estimators before [12, 30] but it comes from training models under covariate shift [59]. It is particularly appealing because it does not require samples from $p(\boldsymbol{\theta} \mid \boldsymbol{x})$.

(a) Posteriors

(b) Likelihood and reweighted marginal generative models.

(c) Receiver operating characteristic.

Figure 3: The figures visualize the importance sampling diagnostic on ratio estimators trained using NRE-B and NRE-C. (a) Both methods produce satisfactory posterior estimates that agree with $p(\boldsymbol{\theta} \,|\, \boldsymbol{x})$. (b) $p(\boldsymbol{x} \,|\, \boldsymbol{\theta})$ is shown along with $p(\boldsymbol{x})$ samples weighted by NRE-A $\exp \circ f_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x})$ and NRE-B $\exp \circ g_{\boldsymbol{w}}(\boldsymbol{\theta}, \boldsymbol{x})$. Each plot corresponds to a different $\boldsymbol{\theta}$. Despite high posterior accuracy, the NRE-B estimates are distinct from $p(\boldsymbol{x} \,|\, \boldsymbol{\theta})$. (c) Two classifier's ROC curves, each trained to distinguish $p(\boldsymbol{x} \,|\, \boldsymbol{\theta})$ samples from $p(\boldsymbol{x})$ samples weighted by the corresponding NRE's $\hat{r}$ estimate. The classifier failed to distinguish likelihood samples from the NRE-C weighted data samples, but successfully identified NRE-B weighted samples. NRE-B accurately approximates the posterior, but fails the diagnostic. NRE-C produces an accurate posterior surrogate and passes the diagnostic.

Durkan et al. [16] do not mention this diagnostic in their paper, but due to its intrinsic bias NRE-B does not fulfill the identity necessary for this diagnostic to hold at convergence. The unknown factor that depends on $\boldsymbol{x}$ implies $p(\boldsymbol{x} \,|\, \boldsymbol{\theta}) \neq p(\boldsymbol{x}) \exp \circ g_{\boldsymbol{w}}(\boldsymbol{x} \,|\, \boldsymbol{\theta})$. We provide empirical evidence of this issue in Figure 3. Although NRE-B accurately approximates the true posterior, it demonstrably fails the diagnostic. Given the limited options for verification of SBI results, this presents a major problem by significantly limiting the trustworthiness of NRE-B on any problem with an intractable posterior. In Appendix B, we show that the unrestricted nature of the NRE-B-specific $c_{\boldsymbol{w}}(\boldsymbol{x})$ bias means approximating $p(\boldsymbol{x} \,|\, \boldsymbol{\theta})$ with normalized importance weights is ill-posed, i.e., the problem is *not* solved by estimating the partition function.

Empirical expected coverage probability   For a candidate distribution to qualify as the posterior, integrating over data must return the prior. A measurement that follows from calibration to the prior is called expected coverage probability. Expected coverage probability can be estimated with samples from $p(\boldsymbol{\theta}, \boldsymbol{x})$ and any amortized SBI method. Although important, ability to compute this metric does not distinguish NRE-C. We refer the interested reader to Hermans et al. [31]. We note that popular sequential techniques generally render this diagnostic inapplicable, with exceptions [10, 45, 46].

3   Experiments

We perform experiments in three settings to measure the exactness of surrogate models under various hyperparameters and training regimes. Section 3.1 aims to identify whether data or architecture is the bottleneck in accuracy by drawing from the joint with every mini-batch. The next experiments aim to determine how to optimally extract inference information given a limited amount of simulation data. Section 3.2 leverages a cheap prior by drawing new contrastive parameters with every mini-batch. Finally, Section 3.3 applies the commonplace training regime for deep learning-based SBI literature of fixed data and bootstrapped contrastive parameters. In this setting, we also benchmark NRE-C on ten inference tasks from Lueckmann et al. [44] using our recommended hyperparameters.

On all hyperparameter searches we consider three simulators from the simulation-based inference benchmark, namely SLCP, Two Moons, and Gaussian Mixture [44]. SLCP is a difficult inference task which has a simple likelihood and complex posterior [21, 53]. Parameters are five dimensional and the data are four samples from a two dimensional random variable. Two Moons is two dimensional

with a crescent-shaped bimodal posterior. Finally, the Gaussian Mixture data draws from a mixture of two, two-dimensional normal distributions with extremely different covariances [3, 60, 61, 66].

Our surrogate models are parameterized by one of two neural network architectures. *Small NN* conforms to the benchmark, up to the use of batch normalization, and has 50 hidden units and two residual blocks, *Large NN* has 128 hidden units and three residual blocks. We compare their performance on a grid of γ and K values. We report post-training results using the C2ST, and mid-training validation loss for insight into convergence rate. We generally use residual networks [28] with batch normalization [33] and train them using adam [37]. We also run NRE-B with the same architecture for comparison. To compare with NRE-B we set the number of total contrastive parameters equal.

What does fair comparison mean in our experimentation? We compare models across fixed number of gradient steps. This implies that models with more classes, i.e., greater K, evaluate the classifier-in-training on more pairs at a given training step than a model with fewer classes. An alternative which we do *not* apply in this paper: Vary the number of gradient steps, holding the number of pair evaluations fixed, i.e., a model with higher K sees the same number of pairs as a model with lower K but the model with lower K has been updated more times. We leave this analysis for future work.

Figure 4: Exactness of NRE posterior surrogates is computed for various contrastive parameter counts, γ values, and architectures on an *average* of three tasks from the SBI benchmark [44]. C2ST assigns 1.0 to inaccurate and 0.5 to accurate posterior approximation. (top) $p(\boldsymbol{\theta}, \boldsymbol{x})$ was sampled at every mini-batch during training. The accuracy strongly depends on K. (mid) A fixed number of dependent $(\boldsymbol{\theta}, \boldsymbol{x})$ pairs were drawn, but $p(\boldsymbol{\theta})$ was sampled at every mini-batch during training. In this regime, K has a smaller effect. (bot) The training data is completely fixed. Contrastive parameters are drawn in a bootstrap from the mini-batch. On the problems with fixed simulation data $\boldsymbol{x}$, higher K improves accuracy and small γ with larger architectures slightly improves performance. The effects of the architecture are more clearly seen on difficult problems like SLCP in Appendix C.

3.1 Behavior with unlimited data

What is responsible for inaccuracies of the surrogate model when training has saturated? (a) the amount of training data (b) the flexibility of the model? In this section we provide new simulation and parameter data with every mini-batch and train until saturation, thereby eliminating the possibility of (a). To produce the contrastive parameters, we bootstrap the newly drawn $\boldsymbol{\Theta}$, this is explained in Appendix A.

The setting is similar to REJ-ABC where simulations are drawn until the posterior has converged. The results of this study will provide a baseline to compare with limited-data results and help us understand how the deep learning architecture's limitations are affected by our introduced hyperparameters. The results are reported in the top row of Figure 4.

The trend is that increasing the number of contrastive examples helps NRE-B and NRE-C. There is not a clear trend with respect to γ in the C2ST. Study of the detailed validation losses in Appendix C reveals that high γ is associated with higher variance validation loss during training, but here it does not seem to strongly affect convergence rate. Saturation is reached before the maximum number of epochs have elapsed and Large NN converges to a better result. Although obfuscated in the averaged results in Figure 4, the result is obvious on SLCP, the most difficult inference task that provides an opportunity for a more flexible architecture to improve.

We argue that generally the performance bottleneck has to do with the number of contrastive parameters, network flexibility, or training details rather than the amount of data. Despite saturating validation losses, the C2ST improves based on these factors. Intuitively a flexible model can continue to extract information from this unlimited set of jointly drawn $(\boldsymbol{\theta}, \boldsymbol{x})$. This has consequences because network flexibility may limit performance in the benchmark case. See Appendix C.

3.2 Leveraging fast priors (drawing theta)

In practice, the simulator is often slow but one can often draw from the prior at the same pace as training a neural network for one mini-batch. Our goal is to understand how our hyperparameter are affected by this setting and whether it is valuable to use this technique in practice. To our knowledge, this training regime has not been explored in the deep learning-based SBI literature.

Initially we draw a fixed set of around 20,000 samples $(\boldsymbol{\theta}, \boldsymbol{x}) \sim p(\boldsymbol{\theta}, \boldsymbol{x})$. For every mini-batch during training, we sample all necessary contrastive parameters from the prior. For each term in $\hat{\ell}_{\gamma, K}$ we take the same batch of contrastive parameters and reshuffle them, thereby equalizing the number of samples seen by NRE-B and NRE-C, up to bootstrap. The averaged C2ST results from the three inference tasks are reported in the middle row of Figure 4.

The resulting estimators are markedly less sensitive to the number of contrastive parameters than in Section 3.1. The number of network parameters has a positive effect, although again this is best seen on the hardest task, SLCP, in the Appendix C. Empirically, lower values of γ improve performance with Large NN; however, there is still high variance and this result may be from noise. In this setting, $\gamma \neq 1$ has a very small negative effect on convergence rate compared to unity, as seen in the validation loss plots in Appendix C. Since training has saturated, we claim this result implies drawing contrastive parameters from the prior helps extract the maximum amount of information from fixed simulation data $\boldsymbol{x}$–without being strongly affected by the number of contrastive parameters K.

(a) NRE-B   (b) NRE-C

Figure 5: A negative bound on the mutual information $-\hat{I}_{\boldsymbol{w}}^{(0)}(\boldsymbol{\theta}; \boldsymbol{x})$, computation technique shown in Appendix D, for the SLCP task estimated over the validation set versus training epochs using (a) NRE-B and (b) NRE-C with various values of γ and K, a Large NN architecture, and fixed training data. The bound permits visualization of the convergence rates and pairwise comparison across models. A grid search indicates that increasing K leads to earlier convergence at fixed γ, when $\gamma > 0.001$. With K fixed, $\gamma < 1$ has a negative effect on convergence rate with a slight improvement in performance. $\gamma > 1$ also decreases convergence rate but tends to reduce performance.

3.3 Simulation-based inference benchmark

In this section, we assume the traditional literature setting of limited simulation and prior budget. Once we've selected hyperparameters based on a grid search of a subset of the SBI benchmark, we perform the entire benchmark with those hyperparameters.

Hyperparameter search To compare to the previous two sections, the amount of training data was fixed such that each epoch was comparable to Section 3.1, this amounts to about 20,000 samples. We first inspect the C2ST results in the last row of Figure 4. The sensitivity to K appears less than in Section 3.1 but more than in Section 3.2. Smaller γ slightly improves Large NN's performance but the noise makes this result uncertain. The larger network performs better–best seen in Appendix C.

We do a Monte Carlo estimate a mutual information bound, denoted $-\hat{I}_{\boldsymbol{w}}^{(0)}(\boldsymbol{\theta}; \boldsymbol{x})$, to show performance on the SLCP task as a function of epochs in Figure 5. For both NRE-B and NRE-C, increasing

285 K tends to positively affect the convergence rate. In NRE-C, $\gamma < 1$ slows convergence and slightly
286 increases performance compared to unity; while $\gamma > 1$ slows convergence and reduces performance.

287 Our take-away recommendation is that $\gamma \in [0.1, 10]$ has a small effect, but generally $\gamma = 1$ has the
288 fastest convergence rate with smaller γ performing slightly better with flexible networks. Generally,
289 we saw improved performance on the C2ST by increasing contrastive parameters K. However,
290 larger K also increases the magnitude of the normalizing constant, see Appendix D. Since we
291 bootstrap parameters, we note the natural upper limit given a mini-batch of B parameters, namely
292 $B/2$ compares the maximum contrastive parameters to each $\boldsymbol{x}$ without reusing any $\boldsymbol{\theta}$.

293 **Benchmark**   We performed the benchmark tasks from Lueckmann et al. [44] with NRE-C. Our
294 architecture and hyperparameters deviate based on the results of the last paragraph. We applied the
295 largest number of computationally practical contrastive parameters, namely $K = 99$, and set $\gamma = 1$.
296 Since we identified potential architecture bottlenecks in Sections 3.1 and 3.3, we used Large NN for
297 our results. The averaged results are visible in Table 1. Note that we trained a collection of amortized
298 estimators then predicted the posterior for each of the ten observations $\boldsymbol{x}_1, \ldots, \boldsymbol{x}_{10}$ per inference
299 problem, whereas Lueckmann et al. [44] trained an estimator for every $\boldsymbol{x}$.

300 NRE-C performed better than NRE-B at all budgets and generally well among the amortized algorithms.
301 (Those are ones *without* an S prefix.) The high performance at 10^5 simulation budget implies that our
302 design has high capacity and may scale well. Sequential methods naturally lead to high exactness
303 since they are tailored to the specific observation $\boldsymbol{x}_o$, but they come with drawbacks since they cannot
304 practically perform empirical expected coverage tests [31, 46] nor bound the mutual information, as
305 we do in Figure 5. Detailed results per task can be found in Appendix C.

4 Conclusion

307 We introduced a generalization of NRE-A and
308 NRE-B which discourages the NRE-B specific
309 $c_{\boldsymbol{w}}(\boldsymbol{x})$ bias term and produces an unbiased es-
310 timate of the likelihood-to-evidence ratio at op-
311 timum. This property has implications for the
312 importance sampling diagnostic, which is criti-
313 cal to practitioners. We used a variational bound
314 on the mutual information as a model-selection
315 metric that allowed us to compare models with
316 different hyperparameters. Further discussion in
317 Appendix D.

318 In the context of NRE-C, we found that increas-
319 ing K improved the C2ST in most cases, at
320 the price of increasing the normalizing constant.
321 Setting $\gamma \approx 1$ was generally the fastest to satu-
322 rate and lower values seemed to slightly improve
323 performance with the Large NN and fixed simu-

Table 1: Averaged C2ST for various budgets on the simulation-based inference benchmark [44]. Notation clarifications are in parenthesis.

Simulation budget Algorithm	10^3	10^4	C2ST 10^5
NRE-C (ours)	0.854	0.757	0.688
REJ-ABC	0.965	0.920	0.871
NLE	0.826	0.753	0.723
NPE	0.838	0.736	0.654
NRE (NRE-B)	0.867	0.811	0.762
SMC-ABC	0.948	0.873	0.816
SNLE	0.783	0.704	0.655
SNPE	0.796	0.677	0.615
SNRE (SNRE-B)	0.788	0.703	0.610

324 lation data. These results indicate that better performance can be achieved by using NRE-C with these
325 hyperparameters than the other version of NRE. When both training parameters $\boldsymbol{\theta}$ and simulation data
326 $\boldsymbol{x}$ are unlimited, the architecture size plays an important role in the quality of surrogate model. We
327 tried drawing contrastive parameters from the prior, a commonly available practical use-case, and
328 found that it damped the effect of K on the C2ST. Generally, for highest accuracy with a fixed budget
329 set K large, up to the mini-batch size divided by 2, and $\gamma \approx 1.0$ for the best convergence rate. When
330 the prior is sampled for every mini-batch, applying a higher K may be less valuable. In situations
331 where the normalizing constant should be very close to unity, i.e., for practitioners who want to run
332 diagnostics on their results, drawing $\boldsymbol{\theta}$ from the prior with every mini-batch and using a small K is
333 likely best as it provided good accuracy with small values for the normalizing constant.

References

[1] J. Alsing, B. Wandelt, and S. Feeney. Massive optimal data compression and density estimation for scalable, likelihood-free inference in cosmology. *Monthly Notices of the Royal Astronomical Society*, 477(3):2874–2885, 2018.

[2] J. Alsing, T. Charnock, S. Feeney, and B. Wandelt. Fast likelihood-free cosmology with neural density estimators and active learning. *Monthly Notices of the Royal Astronomical Society*, 488 (3):4440–4458, 2019.

[3] M. A. Beaumont, J.-M. Cornuet, J.-M. Marin, and C. P. Robert. Adaptive approximate bayesian computation. *Biometrika*, 96(4):983–990, 2009.

[4] M. I. Belghazi, A. Baratin, S. Rajeswar, S. Ozair, Y. Bengio, A. Courville, and R. D. Hjelm. Mine: mutual information neural estimation. *arXiv preprint arXiv:1801.04062*, 2018.

[5] C. M. Bishop. Pattern recognition and machine learning (information science and statistics), 2006.

[6] M. G. Blum and O. François. Non-linear regression models for approximate bayesian computation. *Statistics and computing*, 20(1):63–73, 2010.

[7] J. Brehmer, K. Cranmer, G. Louppe, and J. Pavez. Constraining effective field theories with machine learning. *Physical review letters*, 121(11):111801, 2018.

[8] J. Brehmer, G. Louppe, J. Pavez, and K. Cranmer. Mining gold from implicit models to improve likelihood-free inference. *Proceedings of the National Academy of Sciences*, 117(10): 5242–5249, 2020.

[9] J. Chan, V. Perrone, J. Spence, P. Jenkins, S. Mathieson, and Y. Song. A likelihood-free inference framework for population genetic data using exchangeable neural networks. *Advances in neural information processing systems*, 31, 2018.

[10] A. Cole, B. K. Miller, S. J. Witte, M. X. Cai, M. W. Grootes, F. Nattino, and C. Weniger. Fast and credible likelihood-free cosmology with truncated marginal neural ratio estimation. *arXiv preprint arXiv:2111.08030*, 2021.

[11] A. Coogan, K. Karchev, and C. Weniger. Targeted likelihood-free inference of dark matter substructure in strongly-lensed galaxies. *arXiv preprint arXiv:2010.07032*, 2020.

[12] K. Cranmer, J. Pavez, and G. Louppe. Approximating likelihood ratios with calibrated discriminative classifiers. *arXiv preprint arXiv:1506.02169*, 2015.

[13] K. Cranmer, J. Brehmer, and G. Louppe. The frontier of simulation-based inference. *Proc. Natl. Acad. Sci. U. S. A.*, May 2020.

[14] N. Dalmasso, R. Izbicki, and A. Lee. Confidence sets and hypothesis testing in a likelihood-free inference setting. In *International Conference on Machine Learning*, pages 2323–2334. PMLR, 2020.

[15] C. C. Drovandi, C. Grazian, K. Mengersen, and C. Robert. Approximating the likelihood in abc. *Handbook of approximate bayesian computation*, pages 321–368, 2018.

[16] C. Durkan, I. Murray, and G. Papamakarios. On contrastive learning for likelihood-free inference. In *International Conference on Machine Learning*, pages 2771–2781. PMLR, 2020.

[17] J. H. Friedman. On multivariate goodness–of–fit and two–sample testing. *STATISTICAL PROBLEMS IN PARTICLE PHYSICS, ASTROPHYSICS AND COSMOLOGY*, page 311, 2003.

[18] M. Glöckler, M. Deistler, and J. H. Macke. Variational methods for simulation-based inference. In *International Conference on Learning Representations*, 2021.

[19] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial networks. *Communications of the ACM*, 63(11):139–144, 2020.

[20] S. Gratton. Glass: A general likelihood approximate solution scheme. *arXiv preprint arXiv:1708.08479*, 2017.

[21] D. Greenberg, M. Nonnenmacher, and J. Macke. Automatic posterior transformation for likelihood-free inference. In *International Conference on Machine Learning*, pages 2404–2414. PMLR, 2019.

[22] M. Gutmann and A. Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 297–304. JMLR Workshop and Conference Proceedings, 2010.

[23] M. U. Gutmann and A. Hyvärinen. Noise-contrastive estimation of unnormalized statistical models, with applications to natural image statistics. *Journal of machine learning research*, 13 (2), 2012.

[24] M. U. Gutmann, J. Corander, et al. Bayesian optimization for likelihood-free inference of simulator-based statistical models. *Journal of Machine Learning Research*, 2016.

[25] M. U. Gutmann, S. Kleinegesse, and B. Rhodes. Statistical applications of contrastive learning. *arXiv preprint arXiv:2204.13999*, 2022.

[26] C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. del R'ıo, M. Wiebe, P. Peterson, P. G'erard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant. Array programming with NumPy. *Nature*, 585(7825):357–362, Sept. 2020. doi: 10.1038/s41586-020-2649-2. URL https://doi.org/10.1038/s41586-020-2649-2.

[27] T. Hastie, R. Tibshirani, J. H. Friedman, and J. H. Friedman. *The elements of statistical learning: data mining, inference, and prediction*, volume 2. Springer, 2009.

[28] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016. doi: 10.1109/CVPR.2016.90.

[29] J. Hermans, N. Banik, C. Weniger, G. Bertone, and G. Louppe. Towards constraining warm dark matter with stellar streams through neural simulation-based inference. *arXiv preprint arXiv:2011.14923*, 2020.

[30] J. Hermans, V. Begy, and G. Louppe. Likelihood-free mcmc with amortized approximate ratio estimators. In *International Conference on Machine Learning*, pages 4239–4248. PMLR, 2020.

[31] J. Hermans, A. Delaunoy, F. Rozet, A. Wehenkel, and G. Louppe. Averting a crisis in simulation-based inference. *arXiv preprint arXiv:2110.06581*, 2021.

[32] J. D. Hunter. Matplotlib: A 2d graphics environment. *Computing in Science & Engineering*, 9 (3):90–95, 2007. doi: 10.1109/MCSE.2007.55.

[33] S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. PMLR, 2015.

[34] R. Izbicki, A. Lee, and C. Schafer. High-dimensional density ratio estimation with extensions to approximate likelihood computation. In *Artificial intelligence and statistics*, pages 420–429. PMLR, 2014.

[35] M. Järvenpää, M. U. Gutmann, A. Vehtari, and P. Marttinen. Parallel gaussian process surrogate bayesian inference with noisy likelihood evaluations. *Bayesian Analysis*, 16(1):147–178, 2021.

[36] N. Jeffrey and B. D. Wandelt. Solving high-dimensional parameter inference: marginal posterior densities & moment networks. *arXiv preprint arXiv:2011.05991*, 2020.

[37] D. P. Kingma and J. L. Ba. Adam: A method for stochastic gradient descent. In *ICLR: International Conference on Learning Representations*, pages 1–15, 2015.

[38] T. Kluyver, B. Ragan-Kelley, F. Pérez, B. Granger, M. Bussonnier, J. Frederic, K. Kelley, J. Hamrick, J. Grout, S. Corlay, P. Ivanov, D. Avila, S. Abdalla, C. Willing, and J. development team. Jupyter notebooks - a publishing format for reproducible computational workflows. In F. Loizides and B. Scmidt, editors, *Positioning and Power in Academic Publishing: Players, Agents and Agendas*, pages 87–90, Netherlands, 2016. IOS Press. URL `https://eprints.soton.ac.uk/403913/`.

[39] A. Lacoste, A. Luccioni, V. Schmidt, and T. Dandres. Quantifying the carbon emissions of machine learning. *arXiv preprint arXiv:1910.09700*, 2019.

[40] E. L. Lehmann, J. P. Romano, and G. Casella. *Testing statistical hypotheses*, volume 3. Springer, 2005.

[41] D. Lopez-Paz and M. Oquab. Revisiting classifier two-sample tests. In *International Conference on Learning Representations*, 2017.

[42] J.-M. Lueckmann, P. J. Gonçalves, G. Bassetto, K. Öcal, M. Nonnenmacher, and J. H. Macke. Flexible statistical inference for mechanistic models of neural dynamics. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 1289–1299, 2017.

[43] J.-M. Lueckmann, G. Bassetto, T. Karaletsos, and J. H. Macke. Likelihood-free inference with emulator networks. In *Symposium on Advances in Approximate Bayesian Inference*, pages 32–53. PMLR, 2019.

[44] J.-M. Lueckmann, J. Boelts, D. Greenberg, P. Goncalves, and J. Macke. Benchmarking simulation-based inference. In A. Banerjee and K. Fukumizu, editors, *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, volume 130 of *Proceedings of Machine Learning Research*, pages 343–351. PMLR, 13–15 Apr 2021. URL `http://proceedings.mlr.press/v130/lueckmann21a.html`.

[45] B. K. Miller, A. Cole, G. Louppe, and C. Weniger. Simulation-efficient marginal posterior estimation with swyft: stop wasting your precious time. *arXiv preprint arXiv:2011.13951*, 2020.

[46] B. K. Miller, A. Cole, P. Forré, G. Louppe, and C. Weniger. Truncated marginal neural ratio estimation. *Advances in Neural Information Processing Systems*, 34:129–143, 2021.

[47] S. Mohamed and B. Lakshminarayanan. Learning in implicit generative models. *arXiv preprint arXiv:1610.03483*, 2016.

[48] R. M. Neal. Slice sampling. *Annals of statistics*, pages 705–741, 2003.

[49] T. pandas development team. pandas-dev/pandas: Pandas, Feb. 2020. URL `https://doi.org/10.5281/zenodo.3509134`.

[50] G. Papamakarios and I. Murray. Fast ε-free inference of simulation models with bayesian conditional density estimation. *Advances in neural information processing systems*, 29, 2016.

[51] G. Papamakarios, T. Pavlakou, and I. Murray. Masked autoregressive flow for density estimation. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 2335–2344, 2017.

[52] G. Papamakarios, E. Nalisnick, D. J. Rezende, S. Mohamed, and B. Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *arXiv preprint arXiv:1912.02762*, 2019.

[53] G. Papamakarios, D. Sterratt, and I. Murray. Sequential neural likelihood: Fast likelihood-free inference with autoregressive flows. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 837–848. PMLR, 2019.

[54] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[55] B. Poole, S. Ozair, A. Van Den Oord, A. Alemi, and G. Tucker. On variational bounds of mutual information. In *International Conference on Machine Learning*, pages 5171–5180. PMLR, 2019.

[56] D. Prangle. Distilling importance sampling. *arXiv preprint arXiv:1910.03632*, 2019.

[57] P. Ramesh, J.-M. Lueckmann, J. Boelts, Á. Tejero-Cantero, D. S. Greenberg, P. J. Goncalves, and J. H. Macke. Gatsbi: Generative adversarial training for simulation-based inference. In *International Conference on Learning Representations*, 2021.

[58] G. Rodrigues, D. J. Nott, and S. A. Sisson. Likelihood-free approximate gibbs sampling. *Statistics and Computing*, 30(4):1057–1073, 2020.

[59] H. Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of statistical planning and inference*, 90(2):227–244, 2000.

[60] U. Simola, J. Corander, and U. Picchini. Adaptive mcmc for synthetic likelihoods and correlated synthetic likelihoods. *Bayesian analysis*, 2020.

[61] S. A. Sisson, Y. Fan, and M. Beaumont. *Handbook of approximate Bayesian computation*. CRC Press, 2018.

[62] M. Sugiyama, T. Suzuki, and T. Kanamori. *Density ratio estimation in machine learning*. Cambridge University Press, 2012.

[63] S. Talts, M. Betancourt, D. Simpson, A. Vehtari, and A. Gelman. Validating bayesian inference algorithms with simulation-based calibration. *arXiv preprint arXiv:1804.06788*, 2018.

[64] A. Tejero-Cantero, J. Boelts, M. Deistler, J.-M. Lueckmann, C. Durkan, P. J. Gonçalves, D. S. Greenberg, and J. H. Macke. sbi: A toolkit for simulation-based inference. *Journal of Open Source Software*, 5(52):2505, 2020. doi: 10.21105/joss.02505. URL https://doi.org/10.21105/joss.02505.

[65] O. Thomas, R. Dutta, J. Corander, S. Kaski, M. U. Gutmann, et al. Likelihood-free inference by ratio estimation. *Bayesian Analysis*, 2016.

[66] T. Toni, D. Welch, N. Strelkowa, A. Ipsen, and M. P. H. Stumpf. Approximate bayesian computation scheme for parameter inference and model selection in dynamical systems. *J. R. Soc. Interface*, 6(31):187–202, Feb. 2009.

[67] A. Van den Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv e-prints*, pages arXiv–1807, 2018.

[68] P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski, P. Peterson, W. Weckesser, J. Bright, S. J. van der Walt, M. Brett, J. Wilson, K. J. Millman, N. Mayorov, A. R. J. Nelson, E. Jones, R. Kern, E. Larson, C. J. Carey, İ. Polat, Y. Feng, E. W. Moore, J. VanderPlas, D. Laxalde, J. Perktold, R. Cimrman, I. Henriksen, E. A. Quintero, C. R. Harris, A. M. Archibald, A. H. Ribeiro, F. Pedregosa, P. van Mulbregt, and SciPy 1.0 Contributors. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17:261–272, 2020. doi: 10.1038/s41592-019-0686-2.

[69] M. L. Waskom. seaborn: statistical data visualization. *Journal of Open Source Software*, 6(60): 3021, 2021. doi: 10.21105/joss.03021. URL https://doi.org/10.21105/joss.03021.

[70] Wes McKinney. Data Structures for Statistical Computing in Python. In Stéfan van der Walt and Jarrod Millman, editors, *Proceedings of the 9th Python in Science Conference*, pages 56 – 61, 2010. doi: 10.25080/Majora-92bf1922-00a.