FILLING THE G_AP_S: MULTIVARIATE TIME SERIES IMPUTATION BY GRAPH NEURAL NETWORKS

ABSTRACT

Dealing with missing values and incomplete time series is a labor-intensive, tedious, inevitable task when handling data coming from real-world applications. Effective spatio-temporal representations would allow imputation methods to reconstruct missing temporal data by exploiting information coming from sensors at different locations. However, standard methods fall short in capturing the nonlinear time and space dependencies existing within networks of interconnected sensors and do not take full advantage of the available – and often strong – relational information. Notably, most state-of-the-art imputation methods based on deep learning do not explicitly model relational aspects and, in any case, do not exploit processing frameworks able to adequately represent structured spatio-temporal data. Conversely, graph neural networks have recently surged in popularity as both expressive and scalable tools for processing sequential data with relational inductive biases. In this work, we present the first assessment of graph neural networks in the context of multivariate time series imputation. In particular, we introduce a novel graph neural network architecture, named GRIN, which aims at reconstructing missing data in the different channels of a multivariate time series by learning spatio-temporal representations through message passing. Empirical results show that our model outperforms state-of-the-art methods in the imputation task on relevant real-world benchmarks with mean absolute error improvements often higher than 20%.

1 INTRODUCTION

Imputation of missing values is a prominent problem in multivariate time-series analysis (TSA) from both theoretical and practical perspectives (Little & Rubin, 2019). In fact, in a world of complex interconnected systems such as those characterizing sensor networks or the Internet of Things, faulty sensors and network failures are widespread phenomena that cause disruptions in the data acquisition process. Luckily, failures of these types are often sparse and localized at the single sensor level, i.e., they do not compromise the entire sensor network at once. In other terms, it is often the case that, at a certain time step, missing data appear only at some of the channels of the resulting multivariate time series. In this context, spatio-temporal imputation methods (Yi et al., 2016; Yoon et al., 2018b) aim at reconstructing the missing parts of the signals by possibly exploiting both temporal and spatial dependencies. In particular, effective spatio-temporal approaches would reconstruct missing values by taking into account past and future values, and the concurrent measurements of spatially close neighboring sensors too. Here, *spatial similarity* does not necessarily mean physical (e.g., geographic) proximity, but rather indicates that considered sensors are related w.r.t. a generic (quantifiable) functional dependency (e.g., Pearson correlation or Granger causality – Granger, 1969) and/or that are close in a certain latent space. Relational information, then, can be interpreted as a set of constraints – linking the different time series – that allows replacing the malfunctioning sensors with virtual ones.

Among different imputation methods, approaches based on deep learning (LeCun et al., 2015; Schmidhuber, 2015; Goodfellow et al., 2016) have become increasingly popular (Yoon et al., 2018a; Cao et al., 2018; Liu et al., 2019). However, these methods often completely disregard available relational information or rely on rather simplistic modifications of standard neural architectures tailored for sequence processing (Hochreiter & Schmidhuber, 1997; Chung et al., 2014; Bai et al., 2018; Vaswani et al., 2017). We argue that stronger, structural, inductive biases are needed to advance the

state of the art in time series imputation and allow to build effective inference engines in the context of large and complex sensor networks as those found in real-world applications.

In this work, we model input multivariate time series as sequences of graphs where edges represent relationships among different channels. We propose graph neural networks (GNNs) (Scarselli et al., 2008; Bronstein et al., 2017; Battaglia et al., 2018) as the building block of a novel, bi-directional, recurrent neural network for multivariate time series imputation (MTSI). Our method, named *Graph Recurrent Imputation Network* (`GRIN`), has at its core a recurrent neural network cell where gates are implemented by message-passing neural networks (MPNNs; Gilmer et al., 2017). Two of these networks process the input multivariate time series in both forward and backward time directions at each node, while hidden states are processed by a message-passing imputation layer which is constrained to learn how to perform imputation by looking at neighboring nodes.

Our contributions are manifold: 1) we introduce a methodological framework to exploit graph neural networks in the context of MTSI, 2) we propose a novel, practical and effective implementation of a GNN-based architecture for MTSI, and 3) we achieve state-of-the-art results on several and varied MTSI benchmarks. Our method does not rely on any assumption on the distribution of the missing values (e.g., presence and duration of transient dynamics and/or length of missing sequences) other than stationarity of the underlying process. The rest of the paper is organized as follows. In Section 2 we discuss the related works. Then, in Section 3, we formally introduce the problem settings and the task of MTSI. We present our approach to MTSI in Section 4, by describing the novel framework to implement imputation architectures based on GNNs. We proceed with an empirical evaluation of the presented method against state-of-the-art baselines in Section 5 and, finally, we draw our conclusions in Section 6.

2 RELATED WORKS

Time series imputation There exists a large literature addressing missing value imputation in time series. Besides the simple and standard interpolation methods based on linear and polynomial curve fitting, popular approaches aim at filling up missing values by taking advantage of the similarities among time series. For example, several approaches rely on k-nearest neighbors (Troyanskaya et al., 2001; Beretta & Santaniello, 2016) or matrix factorization (Cichocki & Phan, 2009; Mei et al., 2017). Other standard methods exploit the *expectation-maximization* algorithm (Ghahramani & Jordan, 1994; Nelwamondo et al., 2007) or linear predictors and state-space models (Durbin & Koopman, 2012; Kihoro et al., 2013). A more advanced method, namely STMVL (Yi et al., 2016), incorporates spatial and temporal information by combining temporal interpolation and spatial imputation methods to fill missing values in geographically tagged time series.

More recently, several deep learning approaches have been proposed for MTSI. Among the others, deep autoregressive methods based on recurrent neural networks (RNNs) found widespread success (Lipton et al., 2016; Che et al., 2018; Luo et al., 2018; Yoon et al., 2018b; Cao et al., 2018). GRU-D (Che et al., 2018) learns how to process sequences with missing data by controlling the decay of the hidden states of a gated RNN. Cao et al. (2018) propose *BRITS*, a bidirectional GRUD-D-like RNN for multivariate time series imputation that takes into account correlation among different channels to perform spatial imputation. Other successful strategies in the literature have been proposed that exploit the adversarial training framework to generate realistic reconstructed sequences (Yoon et al., 2018a; Fedus et al., 2018; Luo et al., 2018; 2019). Notably, GAIN (Yoon et al., 2018a) uses GANs (Goodfellow et al., 2014) to learn models that perform imputation in the i.i.d. settings. Luo et al. (2018; 2019) aim, instead, at learning models that generate realistic synthetic sequences and exploit them to fill missing values. Miao et al. (2021) use an approach similar to GAIN, but condition the generator on the predicted label for the target incomplete time series. Concurrently to our work, Kuppannagari et al. (2021) developed a graph-based spatio-temporal denoising autoencoder for spatio-temporal data coming from smart grids with known topology. Liu et al. (2019), instead, uses adversarial learning to train a multi-scale model that imputes highly sparse time series in a hierarchical fashion. However, we argue that none of the above-cited methods can take full advantage of relational information and nonlinear spatio-temporal dependencies. Most importantly, the above methods do not fully exploit the flexibility and expressiveness enabled by operating in the context of graph processing.

Figure 1: Representation of a multivariate time series as a sequence of graphs. Red circles denote nodes with missing values, nodes are identified.

Graph neural networks for TSA Graph neural networks have been exploited in TSA mostly to implement spatio-temporal forecasting methods. The basic idea behind most of the methods present in the literature is to modify standard neural network architectures for sequential data by relying on operators that work in the graph domain. For example, Seo et al. (2018) propose a gated recurrent graph neural network where the standard gates used by a GRU cell (Chung et al., 2014) are implemented by spectral GNNs (Defferrard et al., 2016); Li et al. (2018) propose an analogous architecture replacing spectral GNNs with a diffusion-convolutional network (Atwood & Towsley, 2016). Yu et al. (2017) and Wu et al. (2019; 2020) propose, instead, spatio-temporal convolutional neural networks that alternate convolutions on temporal and spatial dimensions. Similar approaches have also been studied in the context of attention-based sequence models (Vaswani et al., 2017) with Transformer-like architectures alternating spatial and temporal attention layers (Zhang et al., 2018; Cai et al., 2020). Another particularly interesting line of research is related to the problem of learning, end-to-end, the best graph structure to process an input multivariate time series (Kipf et al., 2018; Wu et al., 2020; Shang et al., 2020). While the previously mentioned approaches focus on multivariate time series prediction and use the graph structure only for representation learning, other methods aim at predicting changes in the graph topology (Zambon et al., 2019; Paassen et al., 2020). Finally, methods such as Temporal Graph Networks (Rossi et al., 2020) are tailored to learn node embeddings in dynamical graphs and adopt an event-based paradigm that is out of the scope of this work. Finally, recent works have proposed GNNs for imputing missing features in the context of i.i.d. data. Among the others, Spinelli et al. (2020) propose an adversarial framework to train GNNs on the data reconstruction task, while You et al. (2020) propose a bipartite graph representation for feature imputation. To the best of our knowledge, no previous GNN-based method targeted missing value imputation in the context of generic multivariate time series.

3 PRELIMINARIES

Sequences of graphs We consider sequences of weighted directed graphs, where we observe a graph $\mathcal{G}_t$ with N_t nodes at each time step t. A graph is a couple $\mathcal{G}_t = \langle \boldsymbol{X}_t, \boldsymbol{W}_t \rangle$, where $\boldsymbol{X}_t \in \mathbb{R}^{N_t \times d}$ is the node-attribute matrix whose i-th row contains the d-dimensional node-attribute vector $\boldsymbol{x}_t^i \in \mathbb{R}^d$ associated with the i-th node; entry $w_t^{i,j}$ of the adjacency matrix $\boldsymbol{W}_t \in \mathbb{R}^{N_t \times N_t}$ denotes the scalar weight of the edge (if any) connecting the i-th and j-th node. Fig. 1 exemplifies this modelling framework. We assume nodes to be identified, i.e., to have a unique ID that enables time-wise consistent processing. This problem setting can be easily extended to more general classes of graphs with attributed edges and global attributes. In this work, we mainly focus on problems where the topology of the graph is fixed and does not change over time, i.e., at each time step $\boldsymbol{W}_t = \boldsymbol{W}$ and $N_t = N$.

Any generic multivariate time series fits the above framework by letting each channel of the sequence (i.e., each sensor) correspond to a node and using the available relation information to build an adjacency matrix. If no relational information is available, one could use the identity matrix, but this would defeat the purpose of the formulation. A more proper choice of $\boldsymbol{W}_t$ can be made using any standard similarity score (e.g., Pearson correlation) or a (thresholded) kernel. A more advanced approach instead could aim at learning an adjacency directly from data by using, for instance, spatial attention scores or resorting to graph learning techniques, e.g., Kipf et al. (2018). From now on we assume that input multivariate time series have homogeneous channels, i.e., sensors are of the same type. Note that this assumption does not imply a loss in generality: it is always possible to standardize node features by adding *sensor type* attributes and additional dimensions to accommodate the different types of sensor readings. Alternatively, one might directly model the problem by exploiting heterogeneous graphs (Schlichtkrull et al., 2018).

Multivariate time series imputation   To model the presence of missing values, we consider, at each step, a binary mask $M_t \in \{0, 1\}^{N_t \times d}$ where each row m_t^i indicates which of the corresponding node attributes of x_t^i are available in X_t. It follows that, $m_t^{i,j} = 0$ implies $x_t^{i,j}$ to be missing; conversely, if $m_t^{i,j} = 1$, then $x_t^{i,j}$ stores the actual sensor reading. We denote by $\widetilde{X}_t$ the *unknown* ground truth node-attribute matrix, i.e., the complete node-attribute matrix without any missing data. We assume stationarity of missing data distribution and, in experiments, we mostly focus on the missing at random (MAR) scenario (Rubin, 1976). We neither make assumptions on the number of concurrent sensor failures, nor on the length of missing data blocks, i.e., multiple failures extended over time are accounted for. Clearly, one should expect imputation performance to scale with the number of concurrent faults and the time length of missing data bursts.

The objective of MTSI is to impute missing values in a sequence of input data. More formally, given a graph sequence $\mathcal{G}_{[t,t+T]}$ of length T, we can define the missing data reconstruction error as

$$\mathcal{L}\left(\widehat{X}_{[t,t+T]}, \widetilde{X}_{[t,t+T]}, \overline{M}_{[t,t+T]}\right) = \sum_{h=t}^{t+T} \sum_{i=1}^{N_t} \frac{\left\langle \overline{m}_h^i, \ell\left(\hat{x}_h^i, \tilde{x}_h^i\right)\right\rangle}{\left\langle \overline{m}_h^i, \overline{m}_h^i\right\rangle}, \tag{1}$$

where $\hat{x}_h^i$ is the reconstructed $\tilde{x}_h^i$; $\overline{M}_{[t,t+T]}$ and $\overline{m}_h^i$ are respectively the logical binary complement of $M_{[t,t+T]}$ and m_h^i, $\ell(\,\cdot\,,\,\cdot\,)$ is an element-wise error function (e.g., absolute or squared error) and $\langle\,\cdot\,,\,\cdot\,\rangle$ indicates the standard dot product. Note that, in practice, it is impossible to have access to $\widetilde{X}_{[t,t+T]}$ and, as a consequence, it is necessary to define a surrogate optimization objective by, for example, using a forecasting loss or generating synthetic missing values.

In the context of trainable, parametric, imputation methods we consider two different operational settings. In the first one, named *in-sample imputation*, the model is trained to reconstruct missing values in a given *fixed* input sequence $X_{[t,t+T]}$, i.e., the model is trained on all the available data except those that are missing and those that have been removed from the sequence to emulate additional failures for evaluation. Differently, in the second one (referred to as *out-of-sample imputation*), the model is trained and evaluated on disjoint sequences. Note that in both cases the model does not have access to the ground-truth data used for the final evaluation. The first operational setting simulates the case where a practitioner fits the model directly on the sequence to fill up its gaps. The second, instead, simulates the case where one wishes to use a model fitted on a set of historical data to impute missing values in an unseen target sequence.

4   GRAPH RECURRENT IMPUTATION NETWORK

In this section, we present our approach, the *Graph Recurrent Imputation Network* (GRIN), a graph-based, recurrent neural architecture for MTSI. Given a multivariate time series $X_{[t,t+T]}$ with mask $M_{[t,t+T]}$, our objective is to reconstruct missing values in the input sequence by combining the information coming from both the temporal and spatial dimensions. To do so, we design a *novel bi-directional graph recurrent neural network* which progressively processes the input sequence both forward and backward in time by performing two stages of imputation for each direction. Then, a feed-forward network takes as input the representation learned by the forward and backward models and performs a final – refined – imputation for each node of the graph and step of the sequence. More precisely, the final imputation depends on the output of two GRIN modules whose learned representations are finally processed (space and time wise) by a last decoding multilayer perceptron (MLP). An overview of the complete architecture is given in Fig. 2. As shown in the figure, the two modules impute missing values iteratively, using at each time step previously imputed values as input. We proceed by first describing in detail the unidirectional model, and then we provide the bidirectional extension.

Unidirectional model   Each GRIN module is composed of two blocks, a spatio-temporal encoder and a spatial decoder, which process the input sequence of graphs in two stages. The spatio-temporal encoder maps the input sequence $X_{[t,t+T]}$ in a spatio-temporal representation $H_{[t,t+T]} \in \mathbb{R}^{N_t \times l}$ by exploiting an ad-hoc designed recurrent GNN. The spatial decoder, instead, takes advantage of the learned representations to perform two consecutive rounds of imputation. A first-stage imputation is obtained from the representation by using a linear readout; the second one exploits available relational, spatial, information at time step t. In particular, the decoder is implemented by an MPNN

Valid value ▢ Missing value ▢ Imputed value ▢ 1st stage imputation ▢ 2nd stage imputation ▢

Figure 2: An overview of the bi-directional architecture. Here, each unidirectional `GRIN` module is processing the τ-th step of an input sequence with 4 dimensions (sensors). Two values are missing at the considered time step. `GRIN` performs a first imputation, which is then processed and refined by the spatial decoder. These second-stage imputations are then used to continue the processing at the next step. An MLP processes learned representations node and time wise to obtain final imputations.

which learns to infer the observed values at each i-th node – $\boldsymbol{x}_t^i$ – by refining first-stage imputations considering – locally – $\boldsymbol{H}_{t-1}$ and values observed at neighboring nodes.

Spatio-temporal Encoder In the encoder, the input sequence $\boldsymbol{X}_{[t,t+T]}$ and mask $\boldsymbol{M}_{[t,t+T]}$ are processed sequentially one step at a time, by means of a recurrent neural network with gates implemented by message-passing layers. Any message-passing operator could be used in principle. In particular, given $\boldsymbol{z}_{t,k-1}^i$, i.e., the node features vector at layer $k-1$, we consider the general class of MPNNs described as

$$\text{MPNN}_k(\boldsymbol{z}_{t,k-1}^i, \boldsymbol{W}_t) = \gamma_k\left(\boldsymbol{z}_{t,k-1}^i, \sum_{j\in\mathcal{N}(i)} \rho_k\left(\boldsymbol{z}_{t,k-1}^i, \boldsymbol{z}_{t,k-1}^j\right)\right) = \boldsymbol{z}_{t,k}^i, \tag{2}$$

where $\mathcal{N}(i)$ is the set of neighbors of the i-th node in $\mathcal{G}_t$, γ_k and ρ_k are generic, differentiable, update and message functions (e.g., MLPs), and Σ is a permutation invariant, differentiable aggregation function (e.g., sum or $mean$). In particular, function Σ specifies how to aggregate messages received from neighbors. Note that several definitions of *neighborhood* are possible, e.g., one might consider nodes connected by paths up to a certain length l. For the sake of simplicity, from now on we indicate with $\text{MPNN}(\boldsymbol{z}_t^i, \boldsymbol{W}_t)$ the forward pass of a generic K-layered message-passing neural network. In the following, we use MPNNs as the building blocks for our spatio-temporal feature extractors. To learn the dynamics of the system, we leverage on gated recurrent units (GRUs; Cho et al., 2014). As previously mentioned, similarly to Seo et al. (2018) and Li et al. (2018), we implement the GRU gates by relying on the message-passing layers defined above. At the node level, the elements of the message-passing GRU (MPGRU) can be described as:

$$\boldsymbol{r}_t^i = \sigma\left(\text{MPNN}\left(\left[\hat{\boldsymbol{x}}_t^{i(2)}||\boldsymbol{m}_t^i||\boldsymbol{h}_{t-1}^i\right], \boldsymbol{W}_t\right)\right) \tag{3}$$

$$\boldsymbol{u}_t^i = \sigma\left(\text{MPNN}\left(\left[\hat{\boldsymbol{x}}_t^{i(2)}||\boldsymbol{m}_t^i||\boldsymbol{h}_{t-1}^i\right], \boldsymbol{W}_t\right)\right) \tag{4}$$

$$\boldsymbol{c}_t^i = \tanh\left(\text{MPNN}\left(\left[\hat{\boldsymbol{x}}_t^{i(2)}||\boldsymbol{m}_t^i||\boldsymbol{r}_t^i\odot\boldsymbol{h}_{t-1}^i\right], \boldsymbol{W}_t\right)\right) \tag{5}$$

$$\boldsymbol{h}_t^i = \boldsymbol{u}_t^i\odot\boldsymbol{h}_{t-1}^i + (1-\boldsymbol{u}_t^i)\odot\boldsymbol{c}_t^i \tag{6}$$

where $\boldsymbol{r}_t^i, \boldsymbol{u}_t^i$ are the reset and update gates, respectively, $\boldsymbol{h}_t^i$ is the hidden representation of the i-th node at time t, and $\hat{\boldsymbol{x}}_t^{i(2)}$ is the output of the decoding block at the previous time-step (see next paragraph). The symbols $\odot$ and $||$ denote the Hadamard product and the concatenation operator, respectively. The initial representation $\boldsymbol{H}_{t-1}$ can either be initialized as a constant or with a learnable embedding. Note that for the steps where input data are missing, the encoder is fed with predictions from the decoder block, as explained in the next subsection. By carrying out the above computation time and node wise, we get the encoded sequence $\boldsymbol{H}_{[t,t+T]}$.

Spatial Decoder   As a first decoding step, we generate one-step-ahead predictions from the hidden representations of the MPGRU by means of a linear readout

$$\widehat{Y}_t^{(1)} = H_{t-1} V_h + b_h, \tag{7}$$

where $V_h \in \mathbb{R}^{l \times d}$ is a learnable weight matrix and $b_h \in \mathbb{R}^d$ is a learnable bias vector. We then define the *filler* operator as

$$\Phi(Y_t) = M_t \odot X_t + \overline{M}_t \odot Y_t; \tag{8}$$

intuitively, the filler operator replaces the missing values in the input X_t with the values at the same positions in Y_t. By feeding $\widehat{Y}_t^{(1)}$ to the filler operator, we get the *first-stage imputation* $\widehat{X}_t^{(1)}$ such that the output is X_t with missing values replaced by the one-step-ahead predictions $\widehat{Y}_t^{(1)}$. The resulting node-level predictions are then concatenated to the mask M_t and the hidden representation H_{t-1}, and processed by a final *one-layer* MPNN which computes for each node an *imputation representation* s_t^i as

$$s_t^i = \gamma \left(h_{t-i}^i, \sum_{j \in \mathcal{N}(i)/i} \rho \left(\left[\Phi(\hat{x}_t^{j(1)}) || h_{t-1}^j || m_t^j \right] \right) \right). \tag{9}$$

Notice that, as previously highlighted, the imputation representations only depend on messages received from neighboring nodes and the representation at the previous step. In fact, by aggregating only messages from the one-hop neighborhood, the representations s_t^i are independent of the input features x_t^i of the i-th node itself. This constraint forces the model to learn how to reconstruct a target input by taking into account spatial dependencies. Afterward, we concatenate imputation representation S_t with hidden representation H_{t-1}, and generate second-stage imputations by using a second linear readout and applying the filler operator:

$$\widehat{Y}_t^{(2)} = [S_t || H_{t-1}] V_s + b_s; \qquad \widehat{X}_t^{(2)} = \Phi(\widehat{Y}_t^{(2)}) \tag{10}$$

Finally, we feed $\widehat{X}_t^{(2)}$ as input to the MPGRU (Eq. 3 – 6) to update the hidden representation and proceed to process the next input graph $\mathcal{G}_{t+1}$.

Bidirectional Model   Extending GRIN to account for both forward and backward dynamics is straightforward and can be achieved by duplicating the architecture described in the two previous paragraphs. The first module will process the sequence in the forward direction (from the beginning of the sequence towards its end), while the second one in the other way around. The final imputation is then obtained with an MLP aggregating representations extracted by the two modules:

$$\widehat{y}_t^i = \text{MLP} \left(\left[s_t^{i,fwd} || h_{t-1}^{i,fwd} || s_t^{i,bwd} || h_{t+1}^{i,bwd} \right] \right), \tag{11}$$

where fwd and bwd denote the forward and backward modules, respectively. The final output can then be easily obtained as $\widehat{X}_{[t,t+T]} = \Phi(\widehat{Y}_{[t,t+T]})$. Note that by construction our model can exploit all the available relevant spatio-temporal information, since the only value explicitly masked out for each node is x_t^i. At the same time, it is important to realize that our model does not merely reconstruct the input as an autoencoder, but it is specifically tailored for the imputation task due to its inductive biases. The model is trained by minimizing the reconstruction error of all imputation stages in both directions (see Appendix A).

5   EMPIRICAL EVALUATION

In this section, we empirically evaluate our approach against state-of-the-art baselines on four datasets coming from three relevant application domains. Our approach, remarkably, achieve state-of-the-art performance on all of them.

- **Air Quality (AQI)**: dataset of recordings of several air quality indices from 437 monitoring stations spread across 43 Chinese cities. We consider only the PM2.5 pollutant. Prior works on imputation (Yi et al., 2016; Cao et al., 2018) consider a reduced version of this dataset,including only 36 sensors (**AQI-36** in the following). We evaluate our model on both datasets. We use as adjacency matrix a thresholded Gaussian kernel (Shuman et al., 2013) computed from pairwise geographic distances.

Table 1: Results on the air datasets. Performance averaged over 5 runs.

D	M	In-sample			Out-of-sample		
		MAE	MSE	MRE (%)	MAE	MSE	MRE (%)
AQI-36	Mean	53.48 ± 00.00	4578.08 ± 00.00	76.77 ± 0.00	53.48 ± 0.00	4578.08 ± 00.00	76.77 ± 0.00
	KNN	30.21 ± 0.00	2892.31 ± 00.00	43.36 ± 0.00	30.21 ± 0.00	2892.31 ± 00.00	43.36 ± 0.00
	MF	30.54 ± 0.26	2763.06 ± 63.35	43.84 ± 0.38	$-$	$-$	$-$
	MICE	29.89 ± 0.11	2575.53 ± 07.67	42.90 ± 0.15	30.37 ± 0.09	2594.06 ± 07.17	43.59 ± 0.13
	VAR	13.16 ± 0.21	513.90 ± 12.39	18.89 ± 0.31	15.64 ± 0.08	833.46 ± 13.85	22.02 ± 0.11
	rGAIN	12.23 ± 0.17	393.76 ± 12.66	17.55 ± 0.25	15.37 ± 0.26	641.92 ± 33.89	21.63 ± 0.36
	BRITS	12.24 ± 0.26	495.94 ± 43.56	17.57 ± 0.38	14.50 ± 0.35	662.36 ± 65.16	20.41 ± 0.50
	MPGRU	12.46 ± 0.35	517.21 ± 41.02	17.88 ± 0.50	16.79 ± 0.52	1103.04 ± 106.83	23.63 ± 0.73
	GRIN	$\mathbf{10.51} \pm \mathbf{0.28}$	$\mathbf{371.47} \pm \mathbf{17.38}$	$\mathbf{15.09} \pm \mathbf{0.40}$	$\mathbf{12.08} \pm \mathbf{0.47}$	$\mathbf{523.14} \pm \mathbf{57.17}$	$\mathbf{17.00} \pm \mathbf{0.67}$
AQI	Mean	39.60 ± 0.00	3231.04 ± 00.00	59.25 ± 0.00	39.60 ± 0.00	3231.04 ± 00.00	59.25 ± 0.00
	KNN	34.10 ± 0.00	3471.14 ± 00.00	51.02 ± 0.00	34.10 ± 0.00	3471.14 ± 00.00	51.02 ± 0.00
	MF	26.74 ± 0.24	2021.44 ± 27.98	40.01 ± 0.35	$-$	$-$	$-$
	MICE	26.39 ± 0.13	1872.53 ± 15.97	39.49 ± 0.19	26.98 ± 0.10	1930.92 ± 10.08	40.37 ± 0.15
	VAR	18.13 ± 0.84	918.68 ± 56.55	27.13 ± 1.26	22.95 ± 0.30	1402.84 ± 52.63	33.99 ± 0.44
	rGAIN	17.69 ± 0.17	861.66 ± 17.49	26.48 ± 0.25	21.78 ± 0.50	1274.93 ± 60.28	32.26 ± 0.75
	BRITS	17.24 ± 0.13	924.34 ± 18.26	25.79 ± 0.20	20.21 ± 0.22	1157.89 ± 25.66	29.94 ± 0.33
	MPGRU	15.80 ± 0.05	816.39 ± 05.99	23.63 ± 0.08	18.76 ± 0.11	1194.35 ± 15.23	27.79 ± 0.16
	GRIN	$\mathbf{13.10} \pm \mathbf{0.08}$	$\mathbf{615.80} \pm \mathbf{10.09}$	$\mathbf{19.60} \pm \mathbf{0.11}$	$\mathbf{14.73} \pm \mathbf{0.15}$	$\mathbf{775.91} \pm \mathbf{28.49}$	$\mathbf{21.82} \pm \mathbf{0.23}$

- **Traffic**: we consider the **PEMS-BAY** and **METR-LA** datasets from Li et al. (2018), containing data from traffic sensors from the San Francisco Bay Area and the Los Angeles County Highway. We use the same approach of Li et al. (2018) and Wu et al. (2019) to obtain an adjacency matrix.

- **Smart grids**: we consider data from the Irish Commission for Energy Regulation Smart Metering Project (**CER-E**; Commission for Energy Regulation, 2016). We select only the subset of the available smart meters monitoring the energy consumption of small and medium-sized enterprises (SMEs), i.e., 485 time series with samples acquired every 30 minutes. We build an adjacency matrix by extracting a k-nearest neighbor graph (with $k = 10$) from the similarity matrix built by computing the correntropy (Liu et al., 2007) among the time series.

For the air quality datasets, we adopt the same evaluation protocol of previous works (Yi et al., 2016; Cao et al., 2018) and we show results for both the in-sample and out-of-sample settings. For the traffic and energy consumption datasets we consider only the out-of-sample scenario (except for MF which only works in-sample). We simulate the presence of missing data by considering 2 different settings: 1) *Block missing*, i.e, at each step, for each sensor, we randomly drop 5% of the available data and, in addition, we simulate a failure with probability $p_{failure} = 0.15\%$ and sample its duration uniformly in the interval $[min\_steps, max\_steps]$, where min_steps and max_steps are the number of time steps corresponding respectively to 1 and 4 hours in the traffic case and 2 hours and 2 days for CER-E; 2) *Point missing*, i.e., we simply randomly mask out 25% of the available data. We split all the datasets into training/validation/test sets. We use as performance metrics the *mean absolute error* (MAE), *mean squared error* (MSE) and *mean relative error* (MRE; Cao et al., 2018) computed over the imputation window. For all the experiments, we use as message-passing operator the diffusion convolution introduced by Atwood & Towsley (2016). We consider BRITS (Cao et al., 2018) as the principal competing alternative among non-adversarial deep autoregressive approaches, as it shares architectural similarities with our methods. As additional baselines we consider: 1) MEAN, i.e., imputation using the node-level average; 2) KNN, i.e., imputation by averaging values of the $k = 10$ neighboring nodes with the highest weight in the adjacency matrix $\boldsymbol{W}_t$; 3) MICE (White et al., 2011), limiting the maximum number of iterations to 100 and the number of nearest features to 10; 4) Matrix Factorization (MF) with $rank = 10$; 5) VAR, i.e., a *Vector Autoregressive* one-step-ahead predictor; 6) rGAIN, i.e., an unsupervised version of SSGAN (Miao et al., 2021) which can be seen as GAIN (Yoon et al., 2018a) with bi-directional recurrent encoder and decoder; 7) MPGRU, a one-step-ahead GNN-based predictor similar to DCRNN (Li et al., 2018).

We provide further comment and in depth details on baselines and datasets, together with additional experiments on synthetic data in the appendix.

Table 2: Results on the traffic and smart grids datasets. Performance averaged over 5 runs.

D	M	Block missing			Point missing		
		MAE	MSE	MRE(%)	MAE	MSE	MRE(%)
PEMS-BAY	Mean	5.46 ± 0.00	87.56 ± 0.00	8.75 ± 0.00	5.42 ± 0.00	86.59 ± 0.00	8.67 ± 0.00
	KNN	4.30 ± 0.00	49.90 ± 0.00	6.90 ± 0.00	4.30 ± 0.00	49.80 ± 0.00	6.88 ± 0.00
	MF	3.28 ± 0.01	50.14 ± 0.13	5.26 ± 0.01	3.29 ± 0.01	51.39 ± 0.64	5.27 ± 0.02
	MICE	2.94 ± 0.02	28.28 ± 0.37	4.71 ± 0.03	3.09 ± 0.02	31.43 ± 0.41	4.95 ± 0.02
	VAR	2.09 ± 0.10	16.06 ± 0.73	3.35 ± 0.16	1.30 ± 0.00	6.52 ± 0.01	2.07 ± 0.01
	rGAIN	2.18 ± 0.01	13.96 ± 0.20	3.50 ± 0.02	1.88 ± 0.02	10.37 ± 0.20	3.01 ± 0.04
	BRITS	1.70 ± 0.01	10.50 ± 0.07	2.72 ± 0.01	1.47 ± 0.00	7.94 ± 0.03	2.36 ± 0.00
	MPGRU	1.59 ± 0.00	14.19 ± 0.11	2.56 ± 0.01	1.11 ± 0.00	7.59 ± 0.02	1.77 ± 0.00
	GRIN	$\mathbf{1.14} \pm \mathbf{0.01}$	$\mathbf{6.60} \pm \mathbf{0.10}$	$\mathbf{1.83} \pm \mathbf{0.02}$	$\mathbf{0.67} \pm \mathbf{0.00}$	$\mathbf{1.55} \pm \mathbf{0.01}$	$\mathbf{1.08} \pm \mathbf{0.00}$
METR-LA	Mean	7.48 ± 0.00	139.54 ± 0.00	12.96 ± 0.00	7.56 ± 0.00	142.22 ± 0.00	13.10 ± 0.00
	KNN	7.79 ± 0.00	124.61 ± 0.00	13.49 ± 0.00	7.88 ± 0.00	129.29 ± 0.00	13.65 ± 0.00
	MF	5.46 ± 0.02	109.61 ± 0.78	9.46 ± 0.04	5.56 ± 0.03	113.46 ± 1.08	9.62 ± 0.05
	MICE	4.22 ± 0.05	51.07 ± 1.25	7.31 ± 0.09	4.42 ± 0.07	55.07 ± 1.46	7.65 ± 0.12
	VAR	3.11 ± 0.08	28.00 ± 0.76	5.38 ± 0.13	2.69 ± 0.00	21.10 ± 0.02	4.66 ± 0.00
	rGAIN	2.90 ± 0.01	21.67 ± 0.15	5.02 ± 0.02	2.83 ± 0.01	20.03 ± 0.09	4.91 ± 0.01
	BRITS	2.34 ± 0.01	17.00 ± 0.14	4.05 ± 0.01	2.34 ± 0.00	16.46 ± 0.05	4.05 ± 0.00
	MPGRU	2.57 ± 0.01	25.15 ± 0.17	4.44 ± 0.01	2.44 ± 0.00	22.17 ± 0.03	4.22 ± 0.00
	GRIN	$\mathbf{2.03} \pm \mathbf{0.00}$	$\mathbf{13.26} \pm \mathbf{0.05}$	$\mathbf{3.52} \pm \mathbf{0.01}$	$\mathbf{1.91} \pm \mathbf{0.00}$	$\mathbf{10.41} \pm \mathbf{0.03}$	$\mathbf{3.30} \pm \mathbf{0.00}$
CER-E	Mean	1.49 ± 0.00	5.96 ± 0.00	72.47 ± 0.00	1.51 ± 0.00	6.09 ± 0.00	71.51 ± 0.00
	KNN	1.15 ± 0.00	6.53 ± 0.00	56.11 ± 0.00	1.22 ± 0.00	7.23 ± 0.00	57.71 ± 0.00
	MF*	0.97 ± 0.01	4.38 ± 0.06	47.20 ± 0.31	1.01 ± 0.01	4.65 ± 0.07	47.87 ± 0.36
	MICE	0.96 ± 0.01	3.08 ± 0.03	46.65 ± 0.44	0.98 ± 0.00	3.21 ± 0.04	46.59 ± 0.23
	VAR	0.64 ± 0.03	1.75 ± 0.06	31.21 ± 1.60	0.53 ± 0.00	1.26 ± 0.00	24.94 ± 0.02
	rGAIN	0.74 ± 0.00	1.77 ± 0.02	36.06 ± 0.14	0.71 ± 0.00	1.62 ± 0.02	33.45 ± 0.16
	BRITS	0.64 ± 0.00	1.61 ± 0.01	31.05 ± 0.05	0.64 ± 0.00	1.59 ± 0.01	30.07 ± 0.11
	MPGRU	0.53 ± 0.00	1.84 ± 0.01	25.88 ± 0.09	0.41 ± 0.00	1.22 ± 0.01	19.51 ± 0.03
	GRIN	$\mathbf{0.42} \pm \mathbf{0.00}$	$\mathbf{1.07} \pm \mathbf{0.01}$	$\mathbf{20.24} \pm \mathbf{0.04}$	$\mathbf{0.29} \pm \mathbf{0.00}$	$\mathbf{0.53} \pm \mathbf{0.00}$	$\mathbf{13.71} \pm \mathbf{0.03}$

5.1 RESULTS

Empirical results show that GRIN can achieve large improvements in imputation performance on several scenarios, as well as increased flexibility. In fact, differently from the other state-of-the-art baselines, GRIN can handle input with a variable number of dimensions. Tab. 1 shows the experimental results on the air quality datasets. In the in-sample settings, we compute metrics using as imputation the value obtained by averaging predictions over all the overlapping windows; in the out-of-sample settings, instead, we simply report results by averaging the *error* over windows. GRIN largely outperforms other baselines on both in-sample and out-of-sample settings. In particular, in the latter case, GRIN decreases MAE w.r.t. the closest baseline by more than 20% in AQI. Interestingly, GRIN consistently outperforms BRITS in imputing missing values also for sensors corresponding to isolated (disconnected) nodes, i.e., nodes corresponding to stations more than 40 km away from any other station (see B.1): this is empirical evidence of the positive regularization effect of the inductive biases encoded into GRIN. Our method achieves more accurate imputation also in the 36-dimensional dataset, where we could expect the graph representation to have a lower impact. Results for the traffic and smart grids datasets are shown in Tab. 2. In the traffic dataset, our method outperforms BRITS (which is consistently the most competitive baseline) by a wide margin in all the considered settings while using a much lower number of parameters (see A). In the traffic datasets, on average, GRIN reduces MAE by $\approx 29\%$ w.r.t. BRITS and, in particular, in the Point missing setting of the PEMS-BAY dataset, the error is more than halved. In CER-E,

GRIN consistently achieves the best performance, clearly outperforming other baselines. Besides showing the effectiveness of our approach in a relevant application field, this experiment also goes to show that GRIN can be exploited in settings where relational information is not readily available.

Finally, Tab. 3 show results – in terms of MAE – of an ablation study on the out-of-sample scenario in AQI, METR-LA (in the Block Missing settings), and CER-E (Point Missing setting). In particular, we compare GRIN against 3 baselines to assess the impact of the spatial decoder and of the bidirectional architecture. The first baseline is basically a bi-directional MPGRU

Table 3: Ablation study. Averages over 5 runs.

Model	AQI	METR-LA	CER-E
GRIN	**14.73** $\pm$ **0.15**	**2.03** $\pm$ **0.00**	**0.29** $\pm$ **0.00**
w/o sp. dec.	15.40 $\pm$ 0.14	2.32 $\pm$ 0.01	**0.29** $\pm$ **0.00**
w/ denoise dec.	17.23 $\pm$ 1.12	2.96 $\pm$ 0.18	0.32 $\pm$ 0.00
MPGRU	18.76 $\pm$ 0.11	2.57 $\pm$ 0.01	0.41 $\pm$ 0.00

where values are imputed by a final MLP taking as inputs $\boldsymbol{h}_{t-1}^{fwd}$ and $\boldsymbol{h}_{t+1}^{bwd}$, while the second one has an analogous architecture, but uses hidden representation and time step t (for both directions) and, thus, behaves similarly to a denoising autoencoder. As third baseline, we report for reference the results of the unidirectional MPGRU. Results show that the components we introduce do contribute to significantly reduce imputation error. In particular, it is evident that spatial decoding and the bidirectional architecture are important to obtain accurate missing data reconstruction, especially in realistic settings with blocks of missing data. Interestingly, the denoising model suffers in scenarios with blocks of missing data, while, as one might expect, works well in the Point Missing setting. For an extension of the ablation study on more datasets, see C.2.

5.2 VIRTUAL SENSING

As a final experiment, we provide a quantitative and qualitative assessment of the proposed method in virtual sensing. The idea is to simulate the presence of a sensor by adding a node with no available data and, then, let the model reconstruct the corresponding time series. Note that for the approach to work several assumptions are needed: 1) we have to assume that the physical quantity being monitored can be reconstructed from observations at neighboring sensors; 2) we should assume a high-degree of homogeneity of sensors (e.g., in the case of air quality stations we should assume that sensors are placed at the same height) or that the features characterizing each neighboring sensor (e.g., placement) are available to the model.

Figure 3: Reconstruction of observations from sensors removed from the training set. Plots show that GRIN might be used for virtual sensing.

In this context, it is worth noting that, due to the inductive biases embedded in the model, GRIN performs reconstruction not only by minimizing reconstruction error at the single node, but by regularizing the reconstructed value for imputations at neighboring sensors. We masked out observed values of the two nodes of AQI-36 with highest (station no. 1014) and lowest (no. 1031) connectivity, and trained GRIN on the remaining part of the data as usual. Results, in Fig. 3, qualitatively show that GRIN can infer the trend and scale for unseen sensors. In terms of MAE, GRIN scored 11.74 for sensor 1014 and 20.00 for sensor 1031 (averages over 5 independent runs).

6 CONCLUSIONS

We presented GRIN, a novel approach for MTSI exploiting modern graph neural networks. Our method imputes missing data by leveraging the relational information characterizing the underlying network of sensors and the functional dependencies among them. Compared against state-of-the-art baselines, our framework offers higher flexibility and achieves better reconstruction accuracy on all the considered scenarios. There are several possible directions for future works. From a theoretical perspective, it would be interesting to study the properties that would guarantee an accurate reconstruction. Furthermore, future work should study extensions able to deal with a non-stationary setting and further assess applications of GRIN in virtual and active sensing.

REPRODUCIBILITY STATEMENT

Code to reproduce experiments presented in the paper is provided as supplementary material together with configuration files to replicate reported results. All datasets, except CER-E, are open and downloading links are provided in the supplementary material. The CER-E dataset can be obtained free of charge for research purposes (see appendix). For experiments where failures are emulated, we use random number generators with fixed seed for missing data generation to ensure reproducibility and consistency among experiments and baselines.

REFERENCES

James Atwood and Don Towsley. Diffusion-convolutional neural networks. In *Advances in neural information processing systems*, pp. 1993–2001, 2016.

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. An empirical evaluation of generic convolutional and recurrent networks for sequence modeling. *arXiv preprint arXiv:1803.01271*, 2018.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Lorenzo Beretta and Alessandro Santaniello. Nearest neighbor imputation algorithms: a critical evaluation. *BMC medical informatics and decision making*, 16(3):197–208, 2016.

Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

Ling Cai, Krzysztof Janowicz, Gengchen Mai, Bo Yan, and Rui Zhu. Traffic transformer: Capturing the continuity and periodicity of time series for traffic forecasting. *Transactions in GIS*, 24(3): 736–755, 2020.

Wei Cao, Dong Wang, Jian Li, Hao Zhou, Yitan Li, and Lei Li. Brits: bidirectional recurrent imputation for time series. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 6776–6786, 2018.

Zhengping Che, Sanjay Purushotham, Kyunghyun Cho, David Sontag, and Yan Liu. Recurrent neural networks for multivariate time series with missing values. *Scientific reports*, 8(1):1–12, 2018.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Andrzej Cichocki and Anh-Huy Phan. Fast local algorithms for large scale nonnegative matrix and tensor factorizations. *IEICE transactions on fundamentals of electronics, communications and computer sciences*, 92(3):708–721, 2009.

Commission for Energy Regulation. CER Smart Metering Project - Electricity Customer Behaviour Trial, 2009-2010 [dataset]. *Irish Social Science Data Archive. SN: 0012-00*, 2016. URL `https://www.ucd.ie/issda/data/commissionforenergyregulationcer`.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. *Advances in neural information processing systems*, 29:3844–3852, 2016.

James Durbin and Siem Jan Koopman. *Time series analysis by state space methods*. Oxford university press, 2012.

William Fedus, Ian Goodfellow, and Andrew M Dai. Maskgan: Better text generation via filling in the _. In *International Conference on Learning Representations*, 2018.

Zoubin Ghahramani and Michael Jordan. Supervised learning from incomplete data via an em approach. In J. Cowan, G. Tesauro, and J. Alspector (eds.), *Advances in Neural Information Processing Systems*, volume 6. Morgan-Kaufmann, 1994.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Clive WJ Granger. Investigating causal relations by econometric models and cross-spectral methods. *Econometrica: journal of the Econometric Society*, pp. 424–438, 1969.

Charles R Harris, K Jarrod Millman, Stéfan J van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J Smith, et al. Array programming with numpy. *Nature*, 585(7825):357–362, 2020.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Hosagrahar V Jagadish, Johannes Gehrke, Alexandros Labrinidis, Yannis Papakonstantinou, Jignesh M Patel, Raghu Ramakrishnan, and Cyrus Shahabi. Big data and its technical challenges. *Communications of the ACM*, 57(7):86–94, 2014.

J Kihoro, K Athiany, et al. Imputation of incomplete nonstationary seasonal time series data. *Mathematical Theory and Modeling*, 3(12):142–154, 2013.

Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, pp. 2688–2697. PMLR, 2018.

Sanmukh R. Kuppannagari, Yao Fu, Chung Ming Chueng, and Viktor K. Prasanna. Spatio-temporal missing data imputation for smart power grids. In *Proceedings of the Twelfth ACM International Conference on Future Energy Systems*, e-Energy '21, pp. 458–465, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450383332. doi: 10.1145/3447555.3466586. URL https://doi.org/10.1145/3447555.3466586.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *International Conference on Learning Representations*, 2018.

Zachary C Lipton, David Kale, and Randall Wetzel. Directly modeling missing data in sequences with rnns: Improved classification of clinical time series. In Finale Doshi-Velez, Jim Fackler, David Kale, Byron Wallace, and Jenna Wiens (eds.), *Proceedings of the 1st Machine Learning for Healthcare Conference*, volume 56 of *Proceedings of Machine Learning Research*, pp. 253–270, Northeastern University, Boston, MA, USA, 18–19 Aug 2016. PMLR.

Roderick JA Little and Donald B Rubin. *Statistical analysis with missing data*, volume 793. John Wiley & Sons, 2019.

Weifeng Liu, Puskal P Pokharel, and Jose C Principe. Correntropy: Properties and applications in non-gaussian signal processing. *IEEE Transactions on signal processing*, 55(11):5286–5298, 2007.

Yukai Liu, Rose Yu, Stephan Zheng, Eric Zhan, and Yisong Yue. Naomi: Non-autoregressive multiresolution sequence imputation. *Advances in Neural Information Processing Systems*, 32: 11238–11248, 2019.

Yonghong Luo, Xiangrui Cai, Ying Zhang, Jun Xu, and Yuan Xiaojie. Multivariate time series imputation with generative adversarial networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Yonghong Luo, Ying Zhang, Xiangrui Cai, and Xiaojie Yuan. E²gan: End-to-end generative adversarial network for multivariate time series imputation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pp. 3094–3100. International Joint Conferences on Artificial Intelligence Organization, 7 2019.

Jiali Mei, Yohann De Castro, Yannig Goude, and Georges Hébrail. Nonnegative matrix factorization for time series recovery from a few temporal aggregates. In *International Conference on Machine Learning*, pp. 2382–2390. PMLR, 2017.

Xiaoye Miao, Yangyang Wu, Jun Wang, Yunjun Gao, Xudong Mao, and Jianwei Yin. Generative semi-supervised learning for multivariate time series imputation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 8983–8991, 2021.

Fulufhelo V Nelwamondo, Shakir Mohamed, and Tshilidzi Marwala. Missing data: A comparison of neural network and expectation maximization techniques. *Current Science*, pp. 1514–1521, 2007.

neptune.ai. Neptune: Metadata store for mlops, built for research and production teams that run a lot of experiments, 2021. URL https://neptune.ai.

Benjamin Paassen, Daniele Grattarola, Daniele Zambon, Cesare Alippi, and Barbara Eva Hammer. Graph edit networks. In *International Conference on Learning Representations*, 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32: 8026–8037, 2019.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *the Journal of machine Learning research*, 12:2825–2830, 2011.

Emanuele Rossi, Ben Chamberlain, Fabrizio Frasca, Davide Eynard, Federico Monti, and Michael Bronstein. Temporal graph networks for deep learning on dynamic graphs. *arXiv preprint arXiv:2006.10637*, 2020.

Donald B Rubin. Inference and missing data. *Biometrika*, 63(3):581–592, 1976.

Alex Rubinsteyn and Sergey Feldman. fancyimpute: An imputation library for python. URL https://github.com/iskandr/fancyimpute.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *European semantic web conference*, pp. 593–607. Springer, 2018.

Jürgen Schmidhuber. Deep learning in neural networks: An overview. *Neural networks*, 61:85–117, 2015.

Youngjoo Seo, Michaël Defferrard, Pierre Vandergheynst, and Xavier Bresson. Structured sequence modeling with graph convolutional recurrent networks. In *International Conference on Neural Information Processing*, pp. 362–373. Springer, 2018.

Chao Shang, Jie Chen, and Jinbo Bi. Discrete graph structure learning for forecasting multiple time series. In *International Conference on Learning Representations*, 2020.

David I Shuman, Sunil K Narang, Pascal Frossard, Antonio Ortega, and Pierre Vandergheynst. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. *IEEE signal processing magazine*, 30(3):83–98, 2013.

Indro Spinelli, Simone Scardapane, and Aurelio Uncini. Missing data imputation with adversarially-trained graph convolutional networks. *Neural Networks*, 129:249–260, 2020.

Olga Troyanskaya, Michael Cantor, Gavin Sherlock, Pat Brown, Trevor Hastie, Robert Tibshirani, David Botstein, and Russ B Altman. Missing value estimation methods for dna microarrays. *Bioinformatics*, 17(6):520–525, 2001.

Guido Van Rossum and Fred L. Drake. *Python 3 Reference Manual*. CreateSpace, Scotts Valley, CA, 2009. ISBN 1441412697.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Ian R White, Patrick Royston, and Angela M Wood. Multiple imputation using chained equations: issues and guidance for practice. *Statistics in medicine*, 30(4):377–399, 2011.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. *arXiv preprint arXiv:1906.00121*, 2019.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, Xiaojun Chang, and Chengqi Zhang. Connecting the dots: Multivariate time series forecasting with graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 753–763, New York, NY, USA, 2020. Association for Computing Machinery.

Xiuwen Yi, Yu Zheng, Junbo Zhang, and Tianrui Li. St-mvl: Filling missing values in geo-sensory time series data. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence*, IJCAI'16, pp. 2704–2710. AAAI Press, 2016. ISBN 9781577357704.

Jinsung Yoon, James Jordon, and Mihaela Schaar. Gain: Missing data imputation using generative adversarial nets. In *International Conference on Machine Learning*, pp. 5689–5698. PMLR, 2018a.

Jinsung Yoon, William R Zame, and Mihaela van der Schaar. Estimating missing data in temporal data streams using multi-directional recurrent neural networks. *IEEE Transactions on Biomedical Engineering*, 66(5):1477–1490, 2018b.

Jiaxuan You, Xiaobai Ma, Daisy Yi Ding, Mykel Kochenderfer, and Jure Leskovec. Handling missing data with graph representation learning. *Neural Information Processing Systems (NeurIPS*, 2020.

Bing Yu, Haoteng Yin, and Zhanxing Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. *arXiv preprint arXiv:1709.04875*, 2017.

Daniele Zambon, Daniele Grattarola, Lorenzo Livi, and Cesare Alippi. Autoregressive models for sequences of graphs. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8. IEEE, 2019.

Jiani Zhang, Xingjian Shi, Junyuan Xie, Hao Ma, Irwin King, and Dit Yan Yeung. Gaan: Gated attention networks for learning on large and spatiotemporal graphs. In *34th Conference on Uncertainty in Artificial Intelligence 2018, UAI 2018*, 2018.

Yu Zheng, Licia Capra, Ouri Wolfson, and Hai Yang. Urban computing: concepts, methodologies, and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 5(3):1–55, 2014.

Yu Zheng, Xiuwen Yi, Ming Li, Ruiyuan Li, Zhangqing Shan, Eric Chang, and Tianrui Li. Forecasting fine-grained air quality based on big data. In *Proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 2267–2276, 2015.

APPENDIX

A   DETAILED EXPERIMENTAL SETTINGS

In this appendix, we give more details on the experimental settings used to evaluate our approach. We train all the models by sampling at random 160 batches of 32 elements for each epoch, we fix the maximum number of epochs to 300 and we use early stopping on the validation set with a patience of 40 epochs. All methods are trained using a cosine learning rate scheduler with initial value of 0.001, decayed over the 300 training epochs. During training, we randomly mask out an additional 5% of the input data for each batch to foster robustness to noise and missing data.

For GRIN we minimize the following loss function is

$$
\begin{aligned}
\mathcal{L} = &\ \mathcal{L}\left(\boldsymbol{Y}_{[t,t+T]}, \boldsymbol{X}_{[t,t+T]}, \boldsymbol{M}_{[t,t+T]}\right) \\
&+ \mathcal{L}\left(\boldsymbol{Y}^{(1),fwd}_{[t,t+T]}, \boldsymbol{X}_{[t,t+T]}, \boldsymbol{M}_{[t,t+T]}\right) + \mathcal{L}\left(\boldsymbol{Y}^{(2),fwd}_{[t,t+T]}, \boldsymbol{X}_{[t,t+T]}, \boldsymbol{M}_{[t,t+T]}\right) \\
&+ \mathcal{L}\left(\boldsymbol{Y}^{(1),bwd}_{[t,t+T]}, \boldsymbol{X}_{[t,t+T]}, \boldsymbol{M}_{[t,t+T]}\right) + \mathcal{L}\left(\boldsymbol{Y}^{(2),bwd}_{[t,t+T]}, \boldsymbol{X}_{[t,t+T]}, \boldsymbol{M}_{[t,t+T]}\right),
\end{aligned}
$$

where each $\mathcal{L}\left(\,\cdot\,,\,\cdot\,,\,\cdot\,\right)$ is of the form of Eq. 1 and the element-wise error function is MAE. Note that here we are using $\boldsymbol{X}_{[t,t+T]}$ and $\boldsymbol{M}_{[t,t+T]}$ instead of $\widehat{\boldsymbol{X}}_{[t,t+T]}$ and $\overline{\boldsymbol{M}}_{[t,t+T]}$.

For BRITS, we use the same network hyperparameters of Cao et al. (2018) for the AQI-36 dataset. To account for the larger input dimension, for the other datasets we increase the number of hidden neurons in the RNNs cells to 128 for AQI/METR-LA and 256 for PEMS-BAY/CER-E. The number of neurons was tuned on the validation sets. For rGAIN we use the same number of units in the cells of the bi-directional RNN used by BRITS, but we concatenate a random vector (sampled from a uniform distribution) of dimension $z = 4$ to the input vector in order to model the sampling of the data generating process. To obtain predictions, we average out the outputs of $k = 5$ forward passes. For VAR we used an order of 5 and trained the model with SGD. Since the VAR model needs past 5 observations to predict the next step, we pad each sequence using the mean for each channel. Here we used a batch size to 64 and and a learning rate of 0.0005. The order was selected with a small search in the range $[2, 12]$: we found out a window size of 5 to be ideal for all the considered datasets. For GRIN we use the same hyperparameters in all the datasets: a hidden dimension of 64 neurons for both the spatio-temporal encoder and the spatial decoder and of 64 neurons for the MLP. We use diffusion convolution as message-passing operation, with a diffusion step $k = 2$ in the spatio-temporal encoder and $k = 1$ in the temporal decoder. Note that, due to the architectural differences, the other neural network baselines have a number of parameters that is far higher than GRIN (depending on the considered dataset, up to $\approx 4M$ against $\approx 200K$). For MPGRU we use the same hyperparameters of GRIN(64 units for both the spatio-temporal encoder and the decoder).

For data processing we use the same steps of Li et al. (2018), data are normalized across the feature dimension (which means graph-wise for GRIN and node-wise for BRITS/rGAIN/VAR). Data masked out for evaluation are never used to train any model.

All the models were developed in Python (Van Rossum & Drake, 2009) using the following open-source libraries:

- PyTorch (Paszke et al., 2019);
- numpy (Harris et al., 2020);
- Neptune[1] (neptune.ai, 2021);
- scikit-learn (Pedregosa et al., 2011);
- fancyimpute (Rubinsteyn & Feldman).

The implementation of the diffusion convolutional operator was adapted from the Graph-WaveNet codebase [2]. For the implementation of BRITS, we used the code provided by the authors[3]. The code to reproduce the experiments of the paper is available as supplementary material.

---

[1] https://neptune.ai/

[2] https://github.com/nnzhan/Graph-WaveNet

[3] https://github.com/caow13/BRITS

Table 4: Statistics on adjacency matrices used in the experiments. Self loops are excluded.

Dataset	GRAPH			N. NEIGHBORS		
	type	nodes	edges	mean	median	isolated nodes
AQI	undirected	437	2699	12.35	9.0	14
CER-E	directed	485	4365	9.0	9.0	0
PEMS-BAY	directed	325	2369	7.29	7.0	12
METR-LA	directed	207	1515	7.32	7.0	5

Figure 4: Adjacency matrices of the different datasets.

B DATASETS

In this appendix, we provide more details on the datasets that we used to run experiments. Tab. 4 shows detailed statistics for graph structure associated with each dataset, while Fig. 4 shows the corresponding adjacency matrices. Tab. 5 shows missing data statistics. In the following subsections, we go deeper into details for each dataset.

Table 5: Statistics on missing data distribution. (P) and (B) indicate the Point Missing and Block Missing settings, respectively. With *block*, we refer to missing data bursts longer than 2 time steps and shorter than or equal to 48.

D		ORIGINAL DATA			INJECTED FAULTS		
		% missing	avg. block	median block	%	avg. block	median block
AQI		25.67	6.69	4.0	10.67	7.59	4.0
AQI-36		13.24	7.24	4.0	11.33	6.52	4.0
PEMS-BAY	(P)	0.02	12.0	12.0	25.0	3.33	3.0
	(B)				9.07	27.26	28.0
METR-LA	(P)	8.10	12.44	9.0	23.00	3.33	3.0
	(B)				8.4	25.68	26.0
CER-E	(P)	0.04	48.0	48.0	24.97	3.33	3.0
	(B)				8.38	22.45	21.0

B.1 AIR QUALITY

Air pollution is nowadays an ubiquitous problem. The Urban Computing project (Zheng et al., 2014; 2015) published several datasets containing real measurements of different indices affecting human life in urban spaces. We consider as benchmark the dataset regarding the air quality index (*AQI*). The complete dataset contains hourly measurements of six pollutants from 437 air quality moni­toring stations, spread over 43 cities in China, over a period of one year (from May 2014 to April 2015). Prior works on imputation (Yi et al., 2016; Cao et al., 2018) considered a reduced version of this dataset, including only 36 sensors (*AQI-36*). This dataset is particularly interesting as a bench-

mark for imputation due to the high rate of missing values (25.7% in AQI and 13.2% in AQI-36). Along with Yi et al. (2016), we consider as the test set the months of March, June, September and December. We consider both the in-sample and out-of-sample scenarios. In latter case, we do not consider windows overlapping with any of the test months. We use the same procedure of Yi et al. (2016) to simulate the presence of missing data for evaluation.

We select windows of data of length $T = 24$ for AQI and $T = 36$ for AQI-36 (in line with Cao et al. (2018)). To evaluate the imputation performances, we mask out from the test set and use as ground-truth the value $x_t^{i,j}$ if: (1) the value is not missing ($m_t^{i,j} = 1$) and (2) the value is missing at the same hour and day in the following month. Besides air quality readings, the dataset provides geographic coordinates of each monitoring station. To obtain an adjacency matrix from the geographic distances between nodes, we use a thresholded Gaussian kernel (Shuman et al., 2013): the weight $w_t^{i,j} = w^{i,j}$ of the edge connecting i-th and j-th node is

$$
w^{i,j} = \begin{cases} \exp\left(-\frac{\text{dist}(i,j)^2}{\gamma}\right) & \text{dist}(i,j) \leq \delta \\ 0 & \text{otherwise} \end{cases},
$$

where $\text{dist}(\cdot, \cdot)$ is the geographical distance operator, γ controls the width of the kernel and δ is the threshold. We set γ to the standard deviation of geographical distances in AQI-36 in both datasets. We set δ so that it corresponds to a distance of ≈ 40 km.

B.2 TRAFFIC

The study of traffic networks is key for the development of intelligent transportation systems and a relevant application field for network science. While previous works (Yu et al., 2017; Li et al., 2018; Wu et al., 2019; Shang et al., 2020) have assessed spatio-temporal deep learning methods for the traffic forecasting task, we focus on reconstruction. We use as benchmark the *PEMS-BAY* and *METR-LA* datasets from Li et al. (2018). PEMS-BAY contains 6 months of data from 325 traffic sensors in San Francisco Bay Area, while METR-LA contains 4 months of sensor readings from 207 detectors in the Los Angeles County Highway (Jagadish et al., 2014); for both datasets, the sampling rate corresponds to 5 minutes.

We use input sequences of 24 steps, which correspond to 2 hours of data. For adjacency we use a thresholded Gaussian kernel applied to geographic distances following previous works Wu et al. (2019). We split the data into three folds, using 70% of them for training and the remaining 10% and 20% for validation and testing, respectively.

B.3 SMART GRIDS

We consider data from the Irish Commission for Energy Regulation (CER) Smart Metering Project[4]. We select only the subset of the available smart meters monitoring energy consumption of small and medium-sized enterprises (SMEs), i.e., 485 time series with samples acquired every 30 minutes. Note that access to dataset can be obtained free of charge for research purposes.

We build an adjacency matrix by extracting a k-nearest neighbor graph (with $k = 10$) from the similarity matrix built by computing the week-wise correntropy (Liu et al., 2007) among time series. As in the traffic case, we use a 70%/10%/20% split for training, validation and testing and use a window size of 24 steps. Data were normalized using standard scaling as in the previous settings and we did not perform additional preprocessing steps.

C ADDITIONAL RESULTS

In this appendix, we show an additional experiment in a controlled environment and additional ablation studies.

---

[4]https://www.ucd.ie/issda/data/commissionforenergyregulationcer

C.1 SYNTHETIC DATA

In this experiment, we test our method on the simulated particle system introduced by Kipf et al. (2018)[5]. We simulate the trajectories of $N = 10$ particles in a (10×10) box with elastic collision. Each particle carries a either positive or negative charge $q \in \{1, -1\}$. Two particles attract each other if they have opposite sign, otherwise they repel. Interaction forces between two particles are ruled by Coulomb's law. We collect two datasets, each containing 5000 independent simulations of $T = 36$ steps each. In the first dataset, particles have the same charge in every simulation. In the second one, we sample the charges uniformly at random at the beginning of every simulation. In both scenarios, the initial location and velocity of the particles are drawn randomly. At each step, we randomly remove blocks of consecutive readings with a probability $p_{failure} = 2.5\%$ and a length sampled uniformly from the interval $[4, 9]$. Here, a reading consists of the (x, y) coordinates of the particle's position. We further mask out 2.5% of positions at random. The percentage of values not masked out is $\approx 74\%$. For evaluation purposes, we generate another mask using the same missing data distribution and use the masked values as ground-truth for evaluation. We split dataset in training/validation/test folds using $70\%/10\%/20\%$ splits, respectively.

Table 6: Results on the synthetic datasets. Performance averaged over 5 runs.

Model	Fixed charge		Varying charge	
	MAE	MSE	MAE	MSE
BRITS	0.1203 $_{\pm 0.0003}$	0.0878 $_{\pm 0.0002}$	0.1089 $_{\pm 0.0007}$	0.0840 $_{\pm 0.0001}$
GRIN	**0.0500** $_{\pm \mathbf{0.0055}}$	**0.0061** $_{\pm \mathbf{0.0010}}$	**0.0530** $_{\pm \mathbf{0.0092}}$	**0.0074** $_{\pm \mathbf{0.0033}}$
Improv.	2.41×	14.39×	2.05x	11.35×

We test our method (GRIN) and BRITS in both synthetic datasets. We use 32 units for the hidden layer of BRITS ($\approx 25K$ parameters) and 16 units for both the encoder and decoder of GRIN ($\approx 10K$ parameters). Results are reported in Tab. 6. Both the methods take as input only the particles' positions, with no information about the charges. As can be seen, consistently with what observed by Kipf et al. (2018), relational representations are impressively effective in this scenario. Our method outperforms the baseline by more than an order of magnitude in terms of MSE. Surprisingly, BRITS is less accurate in the setting with varying charge. Our hypothesis is that the added stochasticity acts as a regularization and forces BRITS to learn a more general model.

C.2 ABLATION STUDY

Tab. 7 shows additional results for the ablation study presented in Section 5. Consistently with what we already observed, the spatial decoder and bidirectional architecture improve performance and appear particularly relevant in settings with blocks of missing data.

Table 7: Ablation study. MAE averaged over 5 runs. (P) and (B) indicate the Point Missing and Block Missing settings, respectively.

Model	AQI	METR-LA (B)	METR-LA (P)	CER-E (B)	CER-E (P)
GRIN	**14.73** $_{\pm \mathbf{0.15}}$	**2.03** $_{\pm \mathbf{0.00}}$	**1.91** $_{\pm \mathbf{0.00}}$	**0.42** $_{\pm \mathbf{0.00}}$	**0.29** $_{\pm \mathbf{0.00}}$
w/o sp. dec.	15.40 $_{\pm 0.14}$	2.32 $_{\pm 0.01}$	2.01 $_{\pm 0.00}$	0.49 $_{\pm 0.00}$	**0.29** $_{\pm \mathbf{0.00}}$
w/ denoise dec.	17.23 $_{\pm 1.12}$	2.96 $_{\pm 0.18}$	2.09 $_{\pm 0.02}$	0.61 $_{\pm 0.02}$	0.32 $_{\pm 0.00}$
MPGRU	18.76 $_{\pm 0.11}$	2.57 $_{\pm 0.01}$	2.44 $_{\pm 0.00}$	0.53 $_{\pm 0.00}$	0.41 $_{\pm 0.00}$

---

[5]https://github.com/ethanfetaya/NRI