LEARNING NEURAL EVENT FUNCTIONS FOR ORDINARY DIFFERENTIAL EQUATIONS

ABSTRACT

The existing Neural ODE formulation relies on an explicit knowledge of the termination time. We extend Neural ODEs to implicitly defined termination criteria modeled by *neural event functions*, which can be chained together and differentiated through. Neural Event ODEs are capable of modeling discrete (instantaneous) changes in a continuous-time system, without prior knowledge of when these changes should occur or how many such changes should exist. We test our approach in modeling hybrid discrete- and continuous- systems such as switching dynamical systems and collision in multi-body systems, and we propose simulation-based training of point processes with applications in discrete control.

1 INTRODUCTION

Event handling in the context of solving ordinary differential equations (Shampine & Thompson, 2000) allows the user to specify a termination criteria using an event function. Part of the reason is to introduce discontinuous changes to a system that cannot be modeled by an ODE alone. Examples being collision in physical systems, chemical reactions, or switching dynamics (Ackerson & Fu, 1970). Another part of the motivation is to create discrete outputs from a continuous-time process; such is the case in point processes and event-driven sampling (*e.g.* Steinbrecher & Shaw (2008); Peters et al. (2012); Bouchard-Côté et al. (2018)). In general, an event function is a tool for monitoring a continuous-time system and performing instantaneous interventions when events occur.

The use of ordinary differential equation (ODE) solvers within deep learning frameworks has allowed end-to-end training of Neural ODEs (Chen et al., 2018) in a variety of settings. Examples include graphics (Yang et al., 2019; Rempe et al., 2020; Gupta & Chandraker, 2020), generative modeling (Grathwohl et al., 2018; Zhang et al., 2018; Chen & Duvenaud, 2019; Onken et al., 2020), time series modeling (Rubanova et al., 2019; De Brouwer et al., 2019; Jia & Benson, 2019; Kidger et al., 2020), and physics-based models (Zhong et al., 2019; Greydanus et al., 2019).

However, these existing models are defined with a fixed termination time. To further expand the applications of Neural ODEs, we investigate the parameterization and learning of a termination criteria, such that the termination time is only implicitly defined and will depend on changes in the continuous-time state. For this, we make use of event handling in ODE solvers and derive the gradients necessarily for training event functions that are parameterized with neural networks. By introducing differentiable termination criteria in Neural ODEs, our approach allows the model to efficiently and automatically handle state discontinuities.

1.1 EVENT HANDLING

Suppose we have a continuous-time state $z(t)$ that follows an ODE $\frac{dz}{dt} = f(t, z(t), \theta)$—where θ are parameters of f—with an initial state $z(t_0) = z_0$. The solution at a time value τ can be written as

$$\texttt{ODESolve}(z_0, f, t_0, \tau, \theta) \triangleq z(\tau) = z_0 + \int_{t_0}^{\tau} f(t, z(t), \theta) \, dt. \tag{1}$$

In the context of a Neural ODE, f can be defined using a Lipschitz-continuous neural network. However, since the state $z(t)$ is defined through infinitesimal changes, $z(t)$ is always continuous in t. While smooth trajectories can be a desirable property in some settings, trajectories modeled by

Figure 1: Dynamics of a bouncing ball can be recovered by a Neural Event ODE. Meanwhile, a non-linear Neural ODE has trouble modeling sudden changes and performs poorly at extrapolation.

an ODE can have limited representation capabilities (Dupont et al., 2019; Zhang et al., 2020) and in some applications, it is desirable to model *discontinuities* in the state.

Bouncing ball example   As a motivating example of a system with discontinuous transitions, consider modeling a bouncing ball with classical mechanics. In an environment with constant gravity, a Markov state for representing the ball is a combination of position $x(t) \in \mathbb{R}$ and velocity $v(t) \in \mathbb{R}$,

$$z(t) = [x(t), v(t)], \qquad \frac{dz(t)}{dt} = [v(t), a], \tag{2}$$

where a is a scalar for acceleration, in our context a gravitational constant.

To simulate this system, we need to be mindful that the ball will eventually pass through the ground—when $x(t) \leq r$ for some r that is the radius of the ball—but when it hits the ground, it bounces back up. At the moment of impact, the sign of the velocity is changed instantaneously. However, no such ODE can model this behavior because $v(t)$ needs to change discontinuously at the moment of impact. This simple bouncing ball is an example of a scenario that would be ill-suited for a Neural ODE alone to model.

In order to model this discontinuity in the state, we can make use of *event functions*. Event functions allow the ODE to be terminated when a criteria is satisfied, at which point we can instantaneously modify the state and then resume solving the ODE with this new state. Concretely, let $g(t, z(t), \phi)$ be an event function with ϕ denoting a set of parameters. An ODE solver with event handling capabilities will terminate at the first occurrence when the event function crosses zero, *i.e.* time t^* such that $g(t^*, z(t^*), \phi) = 0$, conditioned on some initial value. We express this relationship as

$$t^*, z(t^*) = \texttt{ODESolveEvent}(z_0, f, g, t_0, \theta, \phi) \tag{3}$$

Note that in contrast to eq. (1), there is no predetermined termination time. The time of termination t^* has to be solved alongside the initial value problem as it depends on the trajectory $z(t)$.

Going back to the bouncing ball example, we can simply introduce an event function to detect when the ball hits the ground, *i.e.* $g(t, z(t), \phi) = x(t) - r$. We can then instantaneously modify the state so that $z'(t^*) = [x(t^*), -(1 - \alpha)v(t^*)]$, where α is the fraction of momentum that is absorbed by the contact, and then resume solving the ODE eq. (2) with this new state $z'(t^*)$.

Figure 1 shows the bouncing ball example being fit by a Neural ODE and a Neural *Event* ODE where both f and g are neural networks. The Neural ODE model parameterizes a non-linear function for f while the Neural Event ODE parameterizes f and g as linear functions of $z(t)$. We see that the Neural Event ODE can perfectly recover the underlying physics and extrapolate seamlessly. Meanwhile, the Neural ODE has trouble fitting to the sudden changes in dynamics when the ball bounces off the ground, and furthermore, does not generalize because the true model requires the trajectory to be discontinuous.

The Neural Event ODE, while being capable of modeling discontinuities in t, is a continuous function of the parameters and hence can be trained with gradient descent. Going forwards, we will discuss how to differentiate t^* w.r.t. the variables that depend on it, such as $z(t^*)$, ϕ and θ. Before this, we briefly summarize how gradients can be computed through any black-box ODE solver.

2 BACKGROUND: DIFFERENTIATING THROUGH ODE SOLUTIONS

Consider a scalar-valued loss function L that depends on the output of an ODE solver,

$$L(z(\tau)) = L(\texttt{ODESolve}(z_0, f, t_0, \tau, \theta)). \tag{4}$$

where $f(t, z, \theta)$ describes the dynamics. To optimize L, we require the gradients with respect to each of the inputs: z_0, t_0, τ and θ. All of these inputs influence the loss function through the intermediate states $z(t)$, for $t \in [t_0, \tau]$, and their gradients can be factored as a function of the *adjoint* state $a(t) \triangleq \frac{dL}{dz(t)}$ which describes how the loss depends on the intermediate states.

The adjoint method (see *e.g.* Pontryagin et al., 1962; Le Cun, 1988; Giles & Pierce, 2000; Chen et al., 2018) provides an identity that quantifies the instantaneous change in the adjoint state:

$$\frac{da(t)}{dt} = -a(t)^{\mathsf{T}} \frac{\partial f(t, z(t), \theta)}{\partial z} \tag{5}$$

which when combined with $z(t)$ is an ordinary differential equation. This lets us compute vector-Jacobian products, such as $\frac{dL}{dz_0} = \frac{dL}{dz(\tau)}^{\mathsf{T}} \frac{dz(\tau)}{dz_0}$, effectively propagating the gradient from the final state, $\frac{dL}{dz(\tau)}$, to the intial state, $\frac{dL}{dz_0}$. The full set of derivatives are

$$\frac{dL}{dz_0} = \frac{dL}{dz(\tau)} \qquad - \int_\tau^{t_0} a(t)^{\mathsf{T}} \frac{\partial f(t, z(t), \theta)}{\partial z} \, dt \tag{6}$$

$$\frac{dL}{dt_0} = \frac{dL}{dz(\tau)}^{\mathsf{T}} \frac{dz(\tau)}{d\tau} - \int_\tau^{t_0} a(t)^{\mathsf{T}} \frac{\partial f(t, z(t), \theta)}{\partial t} \, dt \tag{7}$$

$$\frac{dL}{d\theta} = \qquad - \int_\tau^{t_0} a(t)^{\mathsf{T}} \frac{\partial f(t, z(t), \theta)}{\partial \theta} \, dt \tag{8}$$

We use the method in Chen et al. (2018), which solves all integrals simultaneously backwards-in-time alongside the state $z(t)$. This method does not require intermediate values of $z(t)$ to be stored and only requires invoking a second ODESolve to compute gradients.

There are other notable approaches for solving the adjoint equations, such as storing all intermediate quantities (also known as discrete adjoint) (Zhang & Sandu, 2014), more sophisciated methods of checkpointing (Chen et al., 2016; Gholami et al., 2019; Zhuang et al., 2020), and the use of interpolation schemes to approximate $z(t)$ (Hindmarsh et al., 2005; Daulbaev et al., 2020).

3 DIFFERENTIATING THROUGH EVENT HANDLING

In an event-terminated ODE solve, the final time value t^* is not an input argument but a function of the other inputs. As such, for gradient-based optimization, we would need to propagate gradients from t^* to the input arguments of ODESolveEvent (eq. (3)).

Consider a loss function L that depends on the outputs of ODESolveEvent,

$$L(t^*, z(t^*)) \qquad \text{where } t^*, z(t^*) = \texttt{ODESolveEvent}(z_0, f, g, t_0, \theta, \phi) \tag{9}$$

Without loss of generality, we can move the parameters ϕ inside the state z_0 and set $\frac{d\phi(t)}{dt} = 0$. As long as we can compute gradients w.r.t z_0, these will include gradients w.r.t. ϕ. This simplifies the event function to $g(t, z)$.

Furthermore, we can interpret the event function to be solving an ODE at every evaluation (as opposed to passing the event function as an input to an ODE solver) conditioned on the input arguments. This simplifies the event handling procedure to finding the root of

$$g_{\text{root}}(t, z_0, t_0, \theta) \triangleq g(t, z = \texttt{ODESolve}(z_0, f, t_0, t, \theta)) \tag{10}$$

and factorizes the ODESolveEvent procedure into two steps:

$$\begin{cases} t^* & = \arg\min_t \ t \geq t_0 \text{ such that } g_{\text{root}}(t, z_0, t_0, \theta) = 0 \\ z(t^*) & = \texttt{ODESolve}(z_0, f, t_0, t^*, \theta) \end{cases} \tag{11}$$

It is obviously computationally infeasible to numerically solve an ODE within the inner loop of a root finding procedure, but this factorization allows us to use existing tools to derive the gradients for `ODESolveEvent` which can be simplified to require only solving one ODE backwards-in-time.

First, the implicit function theorem (Krantz & Parks, 2012) gives us the derivative from t^* through the root finding procedure. Let ξ denote any of the inputs (z_0, t_0, θ). Then the gradient satisfies

$$\frac{dt^*}{d\xi} = -\left(\frac{dg_{\text{root}}(t^*, z_0, t_0, \theta)}{dt}\right)^{-1}\left[\frac{\partial g(t^*, z(t^*))}{\partial z}\frac{\partial z(t^*)}{\partial \xi}\right] \tag{12}$$

Though g_{root} requires solving an ODE, the derivative w.r.t. t^* is just $f^* \triangleq f(t^*, z(t^*))$, so

$$\frac{dg_{\text{root}}(t^*, z_0, t_0, \theta)}{dt} = \frac{\partial g(t^*, z(t^*))}{\partial t} + \frac{\partial g(t^*, z(t^*))}{\partial z}^{\mathsf{T}} f^* \tag{13}$$

Taking into account that the loss function may directly depend on both t^* and $z(t^*)$, the gradient from the loss function L w.r.t. an input ξ is

$$\frac{dL}{d\xi} = \underbrace{\left(\frac{\partial L}{\partial t^*} + \frac{\partial L}{\partial z(t^*)}^{\mathsf{T}} f^*\right)}_{\frac{dL}{dt^*}}\underbrace{\left(-\frac{dg_{\text{root}}(t^*, z_0, t_0, \theta)}{dt}^{-1}\left[\frac{\partial g(t^*, z(t^*))}{\partial z}^{\mathsf{T}}\frac{\partial z(t^*)}{\partial \xi}\right]\right)}_{\frac{dt^*}{d\xi}} + \frac{\partial L}{\partial z(t^*)}^{\mathsf{T}}\left[\frac{\partial z(t^*)}{\partial \xi}\right] \tag{14}$$

Re-organizing this equation, we can reduce this to

$$\frac{dL}{d\xi} = v^{\mathsf{T}}\left[\frac{\partial z(t^*)}{\partial \xi}\right] \tag{15}$$

where $v = \left(\frac{\partial L}{\partial t^*} + \frac{\partial L}{\partial z(t^*)}^{\mathsf{T}} f^*\right)\left(-\frac{dg_{\text{root}}(t^*, z_0, t_0, \theta)}{dt}^{-1}\frac{\partial g(t^*, z(t^*))}{\partial z}\right) + \frac{\partial L}{\partial z(t^*)}$.

All quantities in v can be computed efficiently since g and t^* are scalar quantities. As they only require gradients from g, there is no need to differentiate through an ODE solver to compute v. Finally, the vector-Jacobian product in eq. (15) can be computed with a single `ODESolve` over the adjoint equations (eqs. (6) to (8)).

We implemented our method in the `torchdiffeq` (Chen, 2018) library written in the Py-Torch (Paszke et al., 2019) framework, allowing us to make use of GPU-enabled ODE solvers. The gradient computation in eq. (14) is six lines of code. We implemented event handling capabilities for all ODE solvers in the library and will release it to the general public.

4 STATE-DEPENDENT EVENT FUNCTIONS

The state-dependent event function is the most general form and is suitable for modeling systems that have discontinuities when crossing boundaries in the state space. We apply this to modeling switching dynamical system and physical collisions in a multi-body system.

4.1 SWITCHING LINEAR DYNAMICAL SYSTEMS

Switching linear dynamical systems (SLDS) are hybrid discrete and continuous systems that choose which dynamics to follow based on a discrete switch (see *e.g.* Ackerson & Fu 1970; Chang & Athans 1978; Fox et al. 2009; Linderman et al. 2016). They are of particular interest for extracting interpretable models from complex dynamics in areas such as neuroscience Linderman et al. (2016) or finance Fox et al. (2009).

Here, we consider linear switching dynamical systems in the continuous-time setting, placing them in the framework of event handling, and evaluate whether a Neural Event ODE can recover the underlying SLDS dynamics.. At any time, the ground truth state is a continuous variable z and a switch variable $w \in \{1, \ldots, M\}$. The dynamics is then $\frac{dz(t)}{dt} = A^{(w)}z + b^{(w)}$. The switch variable can change instantaneously, resulting in discontinuous dynamics at the boundary of these switches.

| (a) Ground truth | (b) RNN (LSTM) | (c) Neural ODE | (d) Neural Event ODE |

Figure 2: We learn continuous switching linear dynamical systems with Neural Event ODE to model and predict the trajectory of a particle traveling on a loop with discontinuous changes in direction.

Setup We adapt the linear switching dynamical system example of a particle moving around a synthetic race track from Linderman et al. (2016) to continuous-time and use a fan-shaped track. We created a data set with 100 short trajectories for training and 25 longer trajectories as validation and test sets. This was done by sampling a trajectory from the ground-truth system and adding random noise. Figure 2 shows the ground-truth dynamics and sample trajectories. Given observed samples of trajectories from the system we learn to recover the event and state updates by minimizing the squared error between the predicted and actual trajectories.

Results For our Neural Event ODE, we relax the switch state to be a positive real vector that sums to one. At event locations, we instantaneously change the switch state w based on the event location. We evaluated our model in comparison to a (non-linear) Neural ODE that doesn't use event handling and a RNN baseline. We show the test loss in table 1, and the visualization in fig. 2 demonstrates that we are able to recover the components and can generate realistic trajectories with sharp transitions. Notably, since our classifier is only used at event (switching) locations, it does not need to completely recover the true classification boundaries as long as it is accurate at the event locations.

Table 1: Switching linear dynamical system results.

Model	Test Loss (MSE)
RNN (LSTM)	0.261 ± 0.078
Neural ODE	0.157 ± 0.005
Neural Event ODE	0.093 ± 0.037

4.2 Modeling Continuous Physical Systems with Collision

We next consider the use of event handling for modeling physical collisions. Though there exist physics-motivated parameterizations of Neural ODEs (*e.g.* Zhong et al., 2019; Greydanus et al., 2019; Finzi et al., 2020), these cannot model collision effects. Event handling allows us to capture discontinuities in the state (from collisions) that otherwise would be difficult and unnatural to model with a Neural ODE alone. Building on the bouncing ball example from sect. 1.1, we consider a multi-body 2D physics setting with collisions.

Setup We use Pymunk/Chipmunk (Blomqvist, 2011; Lembcke, 2007) to create a data set of trajectories from simulating two balls colliding in a box with random initial positions and velocities. As part of our model, we learn (i) a neural event function to detect collision either between the two balls or between each ball and the ground; (ii) a state update to instantaneously update the state to reflect a change in direction due to contact forces. Both are parameterized as deep neural networks.

Results We evaluate our model in comparison to a non-linear Neural ODE that doesn't use events and a RNN baseline. We report the test loss in table 2, and the percentage of frames where the balls are unrealistically overlapping. Notably, the Neural Event ODE generalizes better than the baselines. Figure 3 shows sample trajectories. We find that the RNN learns to reduce the MSE loss of short bounces by simply hovering the ball in mid-air. On the other hand, the Neural Event ODE can exhibit difficulty recovering from early mistakes which can lead to chaotic behavior for longer sequences.

Figure 3: Test-set motion predictions of two bouncing balls with collisions. The dashed black circle indicates the initial positions of the balls and the solid black circle indicates the final positions. The Neural Event ODE model is able to recover realistic event and state updates that exhibit floating behavior (a-c) and straighter paths (d-e) than a RNN baseline. (c) shows a failure mode of the RNN and Neural Event ODE models where the first collision is not correctly predicted.

Table 2: Test results on the physics prediction task. $@N$ notates evaluating on a sequence length of N discretized steps.

Model	Test Loss (MSE)			Test Overlap %		
	@25	@50	@100	@25	@50	@100
RNN (LSTM)	0.01 ± 0.00	0.07 ± 0.03	0.24 ± 0.02	0.00 ± 0.00	0.00 ± 0.00	2.55 ± 2.15
Neural ODE	0.00 ± 0.00	0.06 ± 0.01	0.18 ± 0.02	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00
Neural Event ODE	0.01 ± 0.00	0.07 ± 0.00	0.19 ± 0.02	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00

5 THRESHOLD-BASED EVENT FUNCTIONS

We next discuss a special class of event functions that are based on an integrate-and-threshold approach. This event function is coupled with the state and depends on an accumulated integral. That is, let $\lambda(t) \in \mathbb{R}^+ \cup \{0\}$ be a non-negative quantity (possibly the solution of an ODE). Then a threshold-based event occurs when the integral over λ reaches some threshold s. The event time is thus the solution to

$$t^* \text{ such that } s = \int_{t_0}^{t^*} \lambda(t) \, dt \qquad (16)$$

which can be implemented with an `ODESolveEvent` by tracking $\Lambda(t) \triangleq \int_{t_0}^{t} \lambda(s)ds$ as part of the state and using the event function $g(t, z(t)) = \Lambda(t) - s$.

Figure 4: Learning TPPs (a,b) through reverse KL and (c,d) for discrete control in continuous-time.

This form appears in multiple areas such as neuronal dynamics (Abbott, 1999; Hodgkin & Huxley, 1952), inverse sampling (Steinbrecher & Shaw, 2008) and more generally temporal point processes. We focus our discussion around temporal point processes as they encompass other applications.

Temporal point processes (TPPs) The TPP framework is designed for modeling random sequences of event times. Let $\mathcal{H} = \{t_i\}_{i=1}^n$ be a sequence of event times, with $t_i \in \mathbb{R}$ and $i \in \mathbb{Z}^+$. Additionally, let $\mathcal{H}(t) = \{t_i \mid t_i < t, t_i \in \mathcal{H}\}$, *i.e.* the history of events predating time t. A temporal point process is then fully characterized by a *conditional intensity function* $\lambda^*(t) = \lambda(t \mid \mathcal{H}(t))$. The star superscript is a common shorthand used to denote conditional dependence on the history (Daley & Vere-Jones, 2003). The only condition is that $\lambda^*(t) \geq 0$. The joint log likelihood of observing $\mathcal{H}$ starting with an initial time value at t_0 is

$$\log p\left(\{t_i\}\right) = \sum_{i=1}^n \log \lambda^*(t_i) - \int_{t_0}^{t_n} \lambda^*(\tau) \, d\tau. \tag{17}$$

Jia & Benson (2019) uses a Neural ODE to parameterize λ^* and noted that the integral in eq. (17) can be estimated using an ODE solver. While this enables training neural TPPs with maximum likelihood, it is much less straightforward to learn from simulations.

In the following, we discuss how the event function framework allows us to backpropagate through simulations of TPPs. This enables training TPPs with the "reverse KL" objective. Another form of simulation-based training appears in reinforcement learning, where a TPP policy (Li et al., 2018) can be used to perform instantaneous interventions on a continuous-time environment.

5.1 REPARAMETERIZATION GRADIENT FOR TEMPORAL POINT PROCESSES

Sampling a single event can be done in two steps: (i) sample $s \sim \text{Exp}(1)$ and (ii) solve for t^* such that $s = \int_0^{t^*} \lambda^*(t) dt$, which is exactly of the form eq. (16). This allows us to reparameterize the sample t^* as a transformation of a noise variable s, thus allows us to take gradients of samples with respect to parameters of the TPP. Consider a conditional intensity function λ_θ^* parameterized by θ,

$$\nabla_\theta \mathbb{E}_{\{t_i\} \sim \text{TPP}(\lambda_\theta^*)} \left[f(\{t_i\})\right] = \mathbb{E}_{\{s_i\} \sim \text{Exp}(1)} \left[\nabla_\theta f(\{t_i(s_i, \theta)\})\right] \tag{18}$$

where $t_i(s_i, \theta)$ is the output of an `ODESolveEvent`, which is differentiable.

We compare the reparameterization gradient against the REINFORCE gradient (Sutton et al., 2000) in training a Neural Jump SDE (Jia & Benson, 2019) with a reverse KL objective

$$\mathcal{D}_{\text{KL}}(p_\theta, p_{\text{target}}) = \mathbb{E}_{\{t_i\} \sim \text{TPP}(\lambda_\theta)} \left[\log p_\theta(\{t_i\}) - \log p_{\text{target}}(\{t_i\})\right] \tag{19}$$

where p_{target} is taken to be a Hawkes point process. This objective requires simulating from the model and requires taking gradients through the event handling procedure. Results are shown in figs. 4a and 4b. The REINFORCE gradient is generally perceived to have a higher variance, which is also reflected in our experiments. The reparameterization gradient performs well with both five and ten events, while the REINFORCE gradient has slower convergence with more events.

Learning discrete control over continuous-time systems   We show that the reparameterization gradient also allows us to model instantaneous interventions in a continuous-time system using Neural Jump SDEs as control policies. We use a multivariate neural TPP as a discrete control, where a sample from a particular index corresponds to changing the discrete state to that index. We test using the human immunodeficiency virus (HIV) dynamics model from Adams et al. (2004) which simulates interventions from treatment strategies with inhibitors. We use a discrete control model for determining whether each of two types of inhibitors should be used, similar the setup in Miller et al. (2020). The reward function we use is the same as that of Adams et al. (2004). Additionally, we perform a control experiment with the Hodgkin-Huxley neuronal dynamics model (Hodgkin & Huxley, 1952), where we have an input stimulus that can switch between being on or off at any given time. The reward is high if the neuron potentials from the Hodgkin-Huxley model match that of a target potential. All experiments are run with three random seeds.

Results are shown in figs. 4c and 4d, which shows that the reparameterization gradient outperforms REINFORCE in both settings. Interestingly, we can also train with a deterministic control policy: instead of randomly sampling s_i, we fix these threshold values. This deterministic policy can outperform both stochastic policies as the underlying continuous-time system is deterministic.

6   SCOPE AND LIMITATIONS

Minibatching   While multiple ODEs can be batched together as a single ODE, this relies on knowing the termination time prior to integration. In general, we cannot batch multiple independent trajectories as the event location is unknown and may be different for each trajectory. *Minibatching is possible in special cases.* As long as the event function crosses zero from the same direction (*e.g.* from negative to positive), it is possible to apply an aggregator (*e.g.* max operation) on the event functions in the minibatch. This is the case for threshold-based event functions, and we expect to look into similarly structured event functions that have minibatching benefits in the future.

Runaway event boundaries   In some cases, a neural event function is never triggered. In such cases, there will be no gradient for the event function parameters and the model degenerates to a Neural ODE alone. In high dimensions, the roots of a neural network are in general unpredictable and a trajectory may never encounter a root. We have found that initializing the parameters of the event function with a large standard deviation helps alleviate this problem for state-based event functions. This is less of a problem for the threshold-based event functions, as the integrand is always positive and there will always be an event if the state is solved for long enough.

Local gradients   We empirically observed that the gradient is very local, in the sense that a learning rate too large can significantly change the number of events, thereby significantly changing the loss function. It is possible that there is no flat local minima as is observed in more standard deep learning setups. However, this is a problem of gradient-based optimization in general. We found that using a smaller momentum coefficient can help stabilize training of neural event function parameters.

7   CONCLUSION

We consider parametrizing event functions with neural networks in the context of solving ODEs, extending Neural ODEs to implicitly defined termination times. Furthermore, we show that event handling in ODE solvers are differentiable, allowing gradient-based optimization of neural event functions. This enables modeling discrete dynamics in continuous-time systems—*e.g.* the criteria and effects of collision in physical systems—and simulation-based training of temporal point processes with applications to discrete control. Notably, we can train deterministic policies with discrete variables, by making use of gradients that only exist in a continuous-time setting.

REFERENCES

Larry F Abbott. Lapicque's introduction of the integrate-and-fire model neuron (1907). *Brain research bulletin*, 50(5-6):303–304, 1999.

G Ackerson and K Fu. On state estimation in switching environments. *IEEE transactions on automatic control*, 15(1):10–17, 1970.

Brian M Adams, Harvey T Banks, Hee-Dae Kwon, and Hien T Tran. Dynamic multidrug therapies for hiv: Optimal and sti control approaches. *Mathematical Biosciences & Engineering*, 1(2):223, 2004.

V Blomqvist. pymunk — http://www.pymunk.org/en/latest/, 2011.

Alexandre Bouchard-Côté, Sebastian J Vollmer, and Arnaud Doucet. The bouncy particle sampler: A nonreversible rejection-free markov chain monte carlo method. *Journal of the American Statistical Association*, 113(522):855–867, 2018.

Chaw-Bing Chang and Michael Athans. State estimation for discrete systems with switching parameters. *IEEE Transactions on Aerospace and Electronic Systems*, (3):418–425, 1978.

Ricky T. Q. Chen. torchdiffeq, 2018. https://github.com/rtqichen/torchdiffeq.

Ricky T. Q. Chen and David Duvenaud. Neural networks with cheap differential operators. In *Advances in Neural Information Processing Systems*, 2019.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *Advances in neural information processing systems*, pp. 6571–6583, 2018.

Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.

Daryl J Daley and David Vere-Jones. An introduction to the theory of point processes, volume 1: Elementary theory and methods. *Verlag New York Berlin Heidelberg: Springer*, 2003.

Talgat Daulbaev, Alexandr Katrutsa, Larisa Markeeva, Julia Gusak, Andrzej Cichocki, and Ivan Oseledets. Interpolated adjoint method for neural ODEs. *arXiv preprint arXiv:2003.05271*, 2020.

Edward De Brouwer, Jaak Simm, Adam Arany, and Yves Moreau. GRU-ODE-bayes: Continuous modeling of sporadically-observed time series. In *Advances in Neural Information Processing Systems*, pp. 7379–7390, 2019.

Emilien Dupont, Arnaud Doucet, and Yee Whye Teh. Augmented neural ODEs. In *Advances in Neural Information Processing Systems*, pp. 3140–3150, 2019.

Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data. *arXiv preprint arXiv:2002.12880*, 2020.

Emily Fox, Erik B Sudderth, Michael I Jordan, and Alan S Willsky. Nonparametric Bayesian learning of switching linear dynamical systems. In *Advances in neural information processing systems*, pp. 457–464, 2009.

Amir Gholami, Kurt Keutzer, and George Biros. Anode: Unconditionally accurate memory-efficient gradients for neural odes. *arXiv preprint arXiv:1902.10298*, 2019.

Michael B Giles and Niles A Pierce. An introduction to the adjoint approach to design. *Flow, turbulence and combustion*, 65(3-4):393–415, 2000.

Will Grathwohl, Ricky T. Q. Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. FFJORD: Free-form continuous dynamics for scalable reversible generative models. *arXiv preprint arXiv:1810.01367*, 2018.

Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In *Advances in Neural Information Processing Systems*, pp. 15379–15389, 2019.

Kunal Gupta and Manmohan Chandraker. Neural mesh flow: 3d manifold mesh generationvia diffeomorphic flows. *arXiv preprint arXiv:2007.10973*, 2020.

Alan C Hindmarsh, Peter N Brown, Keith E Grant, Steven L Lee, Radu Serban, Dan E Shumaker, and Carol S Woodward. SUNDIALS: Suite of nonlinear and differential/algebraic equation solvers. *ACM Transactions on Mathematical Software (TOMS)*, 31(3):363–396, 2005.

Allan L Hodgkin and Andrew F Huxley. The components of membrane conductance in the giant axon of loligo. *The Journal of physiology*, 116(4):473, 1952.

Junteng Jia and Austin R Benson. Neural jump stochastic differential equations. In *Advances in Neural Information Processing Systems*, pp. 9847–9858, 2019.

Patrick Kidger, James Morrill, James Foster, and Terry Lyons. Neural controlled differential equations for irregular time series. *arXiv preprint arXiv:2005.08926*, 2020.

Steven G Krantz and Harold R Parks. *The implicit function theorem: history, theory, and applications*. Springer Science & Business Media, 2012.

Yann Le Cun. A theoretical framework for back-propagation. 1988.

S Lembcke. Chipmunk physics — http://chipmunk-physics.net/, 2007.

Shuang Li, Shuai Xiao, Shixiang Zhu, Nan Du, Yao Xie, and Le Song. Learning temporal point processes via reinforcement learning. In *Advances in neural information processing systems*, pp. 10781–10791, 2018.

Scott W Linderman, Andrew C Miller, Ryan P Adams, David M Blei, Liam Paninski, and Matthew J Johnson. Recurrent switching linear dynamical systems. *arXiv preprint arXiv:1610.08466*, 2016.

John Miller, Chloe Hsu, Jordan Troutman, Juan Perdomo, Tijana Zrnic, Lydia Liu, Yu Sun, Ludwig Schmidt, and Moritz Hardt. Whynot, 2020. URL https://doi.org/10.5281/zenodo.3875775.

Derek Onken, Samy Wu Fung, Xingjian Li, and Lars Ruthotto. OT-Flow: Fast and accurate continuous normalizing flows via optimal transport. *arXiv preprint arXiv:2006.00104*, 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

Elias AJF Peters et al. Rejection-free monte carlo sampling for general potentials. *Physical Review E*, 85(2):026703, 2012.

Lev Semenovich Pontryagin, EF Mishchenko, VG Boltyanskii, and RV Gamkrelidze. The mathematical theory of optimal processes. 1962.

Davis Rempe, Tolga Birdal, Yongheng Zhao, Zan Gojcic, Srinath Sridhar, and Leonidas J Guibas. CaSPR: Learning canonical spatiotemporal point cloud representations. *arXiv preprint arXiv:2008.02792*, 2020.

Yulia Rubanova, Ricky T. Q. Chen, and David Duvenaud. Latent ODEs for irregularly-sampled time series. *arXiv preprint arXiv:1907.03907*, 2019.

LF Shampine and S Thompson. Event location for ordinary differential equations. *Computers & Mathematics with Applications*, 39(5-6):43–54, 2000.

György Steinbrecher and William T Shaw. Quantile mechanics. 2008.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pp. 1057–1063, 2000.

Guandao Yang, Xun Huang, Zekun Hao, Ming-Yu Liu, Serge Belongie, and Bharath Hariharan. Pointflow: 3d point cloud generation with continuous normalizing flows. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 4541–4550, 2019.

Han Zhang, Xi Gao, Jacob Unterman, and Tom Arodz. Approximation capabilities of neural ODEs and invertible residual networks. *International Conference on Machine Learning*, 2020.

Hong Zhang and Adrian Sandu. FATODE: a library for forward, adjoint, and tangent linear integration of ODEs. *SIAM Journal on Scientific Computing*, 36(5):C504–C523, 2014.

Linfeng Zhang, Lei Wang, et al. Monge-amp\ere flow for generative modeling. *arXiv preprint arXiv:1809.10188*, 2018.

Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Symplectic ODE-net: Learning hamiltonian dynamics with control. *arXiv preprint arXiv:1909.12077*, 2019.

Juntang Zhuang, Nicha Dvornek, Xiaoxiao Li, Sekhar Tatikonda, Xenophon Papademetris, and James Duncan. Adaptive checkpoint adjoint method for gradient estimation in neural ODE. *arXiv preprint arXiv:2006.02493*, 2020.