# On the Utility of Existing Fine-Tuned Models on Data-Scarce Domains

## Abstract

Large Language Models (LLMs) have been observed to perform well on a wide range of downstream tasks when fine-tuned on domain-specific data. However, such data may not be readily available in many applications, motivating zero-shot or few-shot approaches using existing *domain or task adjacent (fine-tuned) models*, which we call DAFT. While several fine-tuned models for various tasks are available, finding one appropriate DAFT model for a given task is often not straight forward. In this paper, we explore different utilization techniques of these existing DAFT models for data-scarce problems, i.e., tasks for which data is not available or limited. We observe that for zero-shot problems, ensembling of DAFT models provides an accuracy performance close to that of the single best model. With few-shot problems (few data from target domain available), this performance can be improved further by picking or putting more weights to the DAFT models that are expected to perform better on the target task.

## 1 Introduction

Pre-trained Large Language Models (LLMs) are used for different downstream tasks. Usually, for LLMs that are not directly suitable for downstream tasks, a task-specific header layer, e.g., for classification, is needed at the output. *We define the* base model *as the pre-trained LLM with a task-specific (un-tuned) header layer.* As an example, BERT models Kenton & Toutanova (2019) were trained for sentence completion tasks. In order to perform sentiment classification, we need to add a header layer with output dimension matching the number of classes. Usually, *base models* do not need much training to perform well, because the pre-trained LLMs are already trained on a large corpus of data.

To perform a task with base models, we can fine-tune a base model with task-specific training data, and then use the fine-tuned model. However, it is often the case that appropriate training data for fine-tuning is not readily or abundantly available, i.e., the domain is data-scarce. Moreover, even if one does have the data to fine-tune, one may not have the computational resources, or the time required, to fine-tune. It is worth noting that fine-tuning can be computation, memory and time intensive, even if very few iterations are needed to attain good performance. Hence, we compare different fine-tuning

Figure 1: *Different options for few-shot tasks given LLMs and community created DAFT models*: (1) Directly fine-tune the LLM (FT); (2) Select one DAFT model and use it zero-shot (DAFT$^Z$); (3) Use a DAFT model but with task-specific fine-tuning (DA(FT)$^2$); (4) Ensemble multiple DAFT models and use it zero-shot (DAFT-E$^Z$); (5) Use ensemble of DAFT models with extremely lightweight few-shot adaptation of the ensemble weights (DAFT-E).

solutions with some alternatives that bypass the challenges of fine-tuning and leverage the large number of fine-tuned LLMs already available (in curated repositories like Hugging-face HF (2024c); Kim (2023)). It is important to acknowledge the scale of fine-tuned models being created; for instance, *just three days after LLaMA-3 was released, more than 1,000 fine-tuned LLMs of LLaMA-3* were publicly available on Hugging-face HF (2024b).

> Research Question: Can we use these plethora of fine-tuned LLMs for a data-scarce task?

Here, we investigate the potential of existing and publicly available fine-tuned models (e.g., including those fine-tuned via LORA Sheng et al. (2023) and PEFT Li & Liang (2021)) by leveraging them to perform different tasks. To use a fine-tuned model on a task, e.g., sentiment classification, we need that model to be *domain or task adjacent* (discussed in Section 3). We denote these **D**omain **A**djacent **F**ine-**T**uned models as DAFT. One main property of DAFT is that it can be used without any further fine-tuning (no extra computation) in a zero-shot manner (no data adaptation). Also, inference with DAFT does not require large computational resources when compared to performing fine-tuning.

The availability of DAFT models combined with their ease of use, make them very appealing to use for different tasks. However, the performance of DAFT models on the target domain data (denoted as $D_T$) can be poor depending on the fine-tuning dataset of the respective DAFT models. In this work, we *systematically study four different ways (Fig. 1) of leveraging the DAFT models*, and demonstrate how it is possible to get strong performance with low compute adaptation, demonstrating the utility of these community generated DAFT models. These four options along with fine-tuning the base model using data from target domain (FT in Fig. 1) are defined as follows:

1. **FT** – Fine-tune *base models* with training data obtained from $D_T$.
2. **DAFT $^{\text{Z}}$** – Pick one available DAFT model and use it for zero-shot inference (no training cost).
3. **DA(FT)$^2$** – Pick one available DAFT model and fine-tune with training data from $D_T$.
4. **DAFT-E $^{\text{Z}}$** – Use a subset or all DAFT models and ensemble them for zero-shot inference.
5. **DAFT-E** – Use a subset or all DAFT models for few-shot learning of ensemble weights using training data from $D_T$ and perform inference.

Section 2 discusses related work, followed by Section 3 discussing DAFT models and their potential for various NLP tasks. Section 4 discusses zero-shot and few-shot performance, while Section 5 theoretically characterizes conditions that result in strong performance from the DAFT ensemble.

## 2 Related Work

The two main aspects of our work are: (i) trying to adapt to data-scarce tasks or transfer learning, (ii) leveraging multiple pre-fine-tuned models via ensembling. Here we will briefly discuss related work on transfer learning, ensembling and the closely related blending and mixture-of-experts.

Transfer learning Pan & Yang (2009); Zhuang et al. (2020) is closely related to the goals of our work, as we wish to adapt a model trained on a data-rich source distribution to a data-scarce target problem. The success on the target task often relies heavily on the level of *positive transfer* one can achieve, and various ways of training the model on the source and target data have been developed to maximize the positive transfer (e.g., by extending the already expensive pre-training phase Gururangan et al. (2020)). Here, we consider the DAFT models as the source models for

Table 1: Comparison of different methods to combine pretrained models in terms of the features. **BPF**: Method is LLM backpropagation free. **SLI**: Method needs to perform inference on the target task with a single LLM. **NMWA**: No LLM model weight access is required by the method. **MAE**: Method can handle multi-architecture ensemble. **SFPA**: Method requires a single forward pass for few-shot adaptation.

| Method | 0-shot | BPF | SLI | NMWA | MAE | SFPA |
|---|---|---|---|---|---|---|
| DAFT | ✓ | ✓ | ✓ | ✓ | N/A | N/A |
| Uniform Soup | ✓ | ✓ | ✓ | ✗ | ✗ | N/A |
| DAFT-E $^{\text{Z}}$ | ✓ | ✓ | ✗ | ✓ | ✓ | N/A |
| FT | ✗ | ✗ | ✓ | ✗ | N/A | ✗ |
| DA(FT)$^2$ | ✗ | ✗ | ✓ | ✗ | N/A | ✗ |
| Greedy Soup | ✗ | ✓ | ✓ | ✗ | ✗ | ✗ |
| DAFT-E | ✗ | ✓ | ✗ | ✓ | ✓ | ✓ |

knowledge transfer. However, not every DAFT model may transfer positively, since the DAFT models are obtained from public non-curated pools. Also, for few shot problems, fine-tuning DAFT with target domain data (denoted as $DA(FT)^2$) is a *transfer learning* option that is considered here ($DA(FT)^2$ in Fig. 1).

*Ensembling* is a technique that combines the predictions of multiple classifiers to generate a single decision and has been extensively investigated over the past few decades Breiman (1996); Clemen (1989); Maclin & Opitz (1997); Dietterich (2000). The pre-requisites for effective ensembling are: (i) models with decent performance, and (ii) models that make independent errors, i.e., training diversity in models Ovadia et al. (2019); Lakshminarayanan et al. (2017). The ensemble of models can be the weighted or unweighted average of the model outputs. For weighted averaging, some training is needed to learn the weights Caruana et al. (2004). Isotropic merging Polyak & Juditsky (1992) is a technique similar to ensembling that has been studied alongside ensemble methods over the last few decades and has shown promising performance with LLMs, e.g., Model Soup and its variants Wortsman et al. (2022). One of the main contributions of our work is to focus on understanding the efficacy of ensembling in the context of DAFT models for data-scarce tasks.

The main differences between Model Soup Wortsman et al. (2022) and the proposed ensemble methods (DAFT-E $^Z$ and DAFT-E), are highlighted in Table 1. In the table the following abbreviations are used; SLI: Single LLM inference, NMWA: No (LLM model) weight access, MAE: multi-architecture ensemble, SFPA: single forward pass (for few-shot) adaptation. The table highlights that DAFT-E $^Z$ and DAFT-E provide lightweight LLM backprop-free model combination schemes (similar to Uniform Soup and Greedy Soup), without requiring access to the model weights, and having the ability to combine LLMs with different architectures. Furthermore, the few-shot adaptation in DAFT-E requires only a single forward-pass with the few-shot samples compared to Greedy Soup, which requires multiple forward-passes. However, both Uniform and Greedy Soup finally need to perform inference with a single LLM while DAFT-E $^Z$ and DAFT-E have to perform inference with multiple LLMs.

Another approach related to ensembling is *blending* of models. For instance, LLM-Blender Jiang et al. (2023) performs ensemble of $n$ LLMs by pairwise ranking and generative fusion. The pairwise ranking approach requires creating a custom dataset, training a BERT model, and it incurs substantial computational overhead to perform inference. The proposed generative fusion combines the ranked list from the pairwise ranking with a fine-tuned LLM to generate a response. In contrast, our approaches with DAFT focus on a completely task agnostic (e.g., not just generative tasks) and computationally low-cost solution to leverage multiple fine-tuned LLMs. Another type of blending is introduced in Lu et al. (2024), and is orthogonal to ensemble. The method selects base models at random and combines them by adding the response of an already evaluated model to the input of the subsequent model; a sequential approach that can be readily combined with ensembling.

*Mixture of Experts* (MoE) Jacobs et al. (1991) has been utilized by different ML models for both regression and classification tasks Yuksel et al. (2012). Before recent developments in LLMs, MoE was mainly focused on dense mixture of experts, which has been replaced by a sparse mixture of experts Fedus et al. (2022). One recent work on MoE, Mixtral Jiang et al. (2024) uses a sparse LLM MoE where a routing network (e.g., Rosenbaum et al. (2017)) is pre-trained to map input tokens to a subset of experts. Compared to all these MoE models (which requires multiple back-propagation through all the involved LLMs to train the routing network), the ensemble of DAFT models that we consider require at most a single forward pass through the LLMs for few-shot target task adaptation, and hence are computationally significantly more lightweight.

## 3 DAFT Models

With the rapid expansion of open platforms like Colab and Kaggle to perform model training, and having access to different public datasets, researchers can access LLMs and datasets that can be used to fine-tune these LLMs. This has lead to a large repository of publicly available *fine-tuned base models* (as defined in Section 1) HF (2024c); Kim (2023). In Section 1 we argued that the performance of any such fine-tuned model on some target dataset depends on the source dataset on which it was fine-tuned on. *We call a model a domain adjacent fine-tuned model (DAFT) if it can be used for the same (general) task as the target dataset, i.e., the model was fine-tuned with a dataset that have the same task criterion as the target data.*

Figure 2: a) LEEP score heatmap: LEEP scores signifying the transferability of knowledge from one dataset to another for sentiment analysis datasets. b) *Efficacy of DAFT models*: The vertical axis corresponds to the data used to fine-tune a base LLM (here we show Roberta-base; the heatmaps for the other models show a similar trend and are provided in appendix), and the horizontal axis corresponds to the unseen test data. All datasets, for each of the two tasks, have matching output spaces respectively and pertain to *sentiment classification* and *textual similarity* problem respectively (left and right). The diagonal is the performance of FT– the LLM tested with data from the distribution it was fine-tuned with, denoting the upper watermark for that test data (only exception being SST2 – discussed in text). The off-diagonal entries correspond to the performance of the DAFT– LLM trained on one dataset, and tested on another, highlighting the potential computationally cheap (free!) zero-shot benefit that DAFT models can provide. Note that, for any given test data, the performance of a DAFT LLM can vary significantly. Also, LEEP score heatmap and DAFT models performance shows very similar trend.

## 3.1 Formation of DAFT models

### 3.1.1 Tasks and Datasets

We consider two broad NLP tasks, (1) Sentiment Analysis (positive or negative sentiment) and 2) Textual Similarity (if two sentences are similar). Although there are (currently) 5269 and 936 DAFT models available for sentiment analysis and textual similarity task in Hugging Face platform, to mitigate the risk of benchmark data leakage, we chose to create our own DAFT models by fine-tuning the base models with specific datasets HF (2024a); University (2024); Kaggle (2024). The datasets for Sentiment Analysis are: Amazon polarity, Cornell Movie, IMDB, SST2, Tweet sentiment, and Yelp Polarity; and for Textual Similarity: MRPC, QQP, STS-B (details in Appendix A.1).

### 3.1.2 Models

For both tasks, we chose three LLMs (with fine-tuning) for different performance analyses: (1) Roberta-base, (2) BERT-based-uncased, and (3) xlnet-base-cased. These models with a header layer form base models for our experiments.[1]

### 3.1.3 Base Models

A *base model* is created by adding a header layer to an LLM. Since the base models are not trained to perform any specific task and the header layer has not been fine-tuned, the performance of all the base models is similar to random guessing. For some base model $B$ and dataset $D$, let us denote $\Phi(B, D, n)$ as the fine-tuned version of $B$ on $n$ amount of data from dataset $D$. If the parameter $n$ is missing as the argument, the base model is assumed to be fully fine-tuned ($FFT$) on $D$. In our experiments, with few

---

[1]These three models were chosen from a few other models due to their usually better performance (on the chosen datasets) compared to all the other models of the same size. We also used BART-LARGE-MNLI, ROBERTA-LARGE-MNLI, and OPT-1.3B models for sentiment analysis (zero-shot classification). These models are much larger in size compared to the above-mentioned models, and therefore needs more computational power for inference.

shot fine-tuning, we vary $n$ in the range of $2 - 256$ samples. For the ($FFT$) models, we fine-tune until loss stabilization[2].

## 3.2   Performance of DAFT Models

Let us denote the train and test splits of the target dataset as $D'_T$ and $D''_T$ respectively. Since the standard train and test splits are identically distributed (iid), we expect a model trained on the target data ($D'_T$) to perform the best on the test data $D''_T$. This performance value is the *ceiling benchmark* that we aim to match or surpass. For that purpose, we performed full fine-tuning ($FFT$) on all three base models using training data of all datasets (sentiment analysis and textual similarity), to come up with 18 $FFT$ models for sentiment analysis and 9 $FFT$ models for textual similarity. Hence, for any target dataset, we can have 15 DAFT models for sentiment analysis by excluding the three models that were fully fine-tuned on $D'_T$, and 6 DAFT models for textual similarity task.

We plot the zero-shot performance of model fine-tuned on one dataset and tested on another for both sentiment analysis and textual similarity tasks in Fig. 2 (b). It is important to note from the figure that most of the zero-shot performances are significantly better ($\gg 50\%$) than the performance of a model with untrained header layer (50% for binary classification). We also note that the performance of the Cornell and Tweet datasets do not match the other four datasets' performance on the sentiment analysis task. Our empirical study suggests that the test data of Cornell is distributionally different from the other datasets, and for all FFT models the performance was poor. The Tweet dataset seems to have a different distribution in both its training and testing data (compared to the other 5 datasets). From the Tweet row and column, we observe that apart from the diagonal element, all the other accuracies are small, and a high 94% accuracy is attained when the model is trained and tested on Tweet data. Upon inspecting the row of SST2, another interesting observation can be made, the performance of

Figure 3: *RI of DAFTs compared to the Single Best DAFT* for *sentiment analysis*: For each test dataset, we consider 15 DAFT LLMs (fine-tuned on data different from the test data), and show the RI of DAFT$^Z$ over the single-best DAFT LLM (out of the 15) (the colored circles ●). Values less than 0 indicate performance degradation. The red squares ■ denote the performance of zero-shot prompting on larger LLMs (Bart-large-mnli, Roberta-large-mnli, and Opt-1.3b).

DAFT-Cornell beats that of DAFT-SST2. This is caused by the test dataset of SST2 being more aligned with the training data of Cornell (further details in Appendix A.3). For textual similarity datasets, the performance of DAFT models was not as good as the sentiment analysis, but still show promise. Lastly, to validate the transferability of the DAFT models to a new target domain or task, we looked at the LEEP scores Nguyen et al. (2020) for all the 6 datasets of the sentiment analysis task (Figure 2 (a)). Interestingly, the heat map with the LEEP scores closely follows the heat map that we generated using the performance of the DAFT models (Figure 2 (b)). Thus, the transferability of DAFT models (corresponding LEEP scores) to a target domain is proportional to their (inference) performance on that target domain. These LEEP scores also tells us that a LEEP scored based ensemble method is possible and needs further investigation.

> DAFT models *can potentially* provide competitive zero-shot performance on new tasks.

## 3.2.1   Performance of DAFT$^Z$ *(Zero Shot)*

Fig. 3 shows the relative improvement ($RI$) of all the DAFT models for sentiment analysis task when compared to the single best performing DAFT model.[3] From Fig. 3 it is evident that there are some DAFT models that

---

[2]Fine-tune until the fluctuation of loss is less than $\pm 1\%$.

[3]Thus, all the $RI$ values (corresponding to the other DAFTs) will be non-positive (zero for the best single DAFT). The relative improvement ($RI$) of all the DAFT models for textual similarity task is provided in Appendix (Fig. 16).

Table 2: *Average Relative Improvement of DA(FT)$^2$ compared to FT* (Top 6: sentiment analysis tasks. Bottom 3: textual similarity tasks): Positive values show DA(FT)$^2$ improvement over FT on target (domain); larger values imply higher improvements. Please see Table 9 and 10 in Appendix for detailed results. We see that DA(FT)$^2$ is significantly better than FT in few-shot problems.

| Target | 2-shot | 4-shot | 8-shot | 16-shot | 32-shot | 64-shot | 128-shot |
|---|---|---|---|---|---|---|---|
| Amazon | 75.95 | 75.25 | 79.62 | 65.40 | 53.51 | 34.26 | 0.81 |
| Cornell | 67.95 | 65.61 | 63.26 | 60.72 | 57.77 | 35.85 | 8.85 |
| IMDB | 74.26 | 74.64 | 76.19 | 66.01 | 58.20 | 47.64 | 0.10 |
| SST2 | 73.13 | 72.64 | 71.81 | 71.95 | 71.88 | 58.58 | 12.79 |
| Tweet | 60.67 | 54.25 | 55.53 | 52.25 | 41.82 | 25.92 | 2.34 |
| Yelp | 74.88 | 81.00 | 66.81 | 81.68 | 46.47 | 27.86 | -0.72 |
| MRPC | 44.88 | 42.92 | 48.08 | 4.74 | 32.15 | 23.47 | 20.90 |
| QQP | 72.93 | 75.17 | 84.44 | 86.97 | 65.36 | 48.50 | 13.86 |
| STSB | 48.36 | 49.31 | 49.52 | 53.08 | 49.88 | 29.24 | -0.12 |

are not as good as the single best and for some specific choices (as for Tweet), the performance can be poor. On the other hand, with zero shot prompting, among the three larger models (Bart-large-mnli, Roberta-large-mnli, and Opt-1.3b), one of them (opt-1.3b) showed poor performance on most of the datasets, while the other two performed quite well. However, these (8 times) larger models (with zero shot prompting) still fail to beat the single best DAFT in all cases, except Tweet. The low performance of DAFT models on Tweet is potentially because of the difference in the nature of this dataset (discussed previously in Section 3.2 and is supported by Fig. 2).

> Zero-shot performance of DAFT models can vary significantly, with some DAFT models even outperforming larger LLMs, making the choice of the DAFT model critical.

### 3.2.2 *Few Shot* Comparison of FT & DA(FT)$^2$

When (some) training data is available from the target domain, the general approach is to fine-tune a model with that data to perform the domain specific task. The key research question is: should we fine-tune a base model (FT in Fig. 1), or fine-tune a DAFT (DA(FT)$^2$ in Fig. 1)? [4] Table 2 provides the average performance comparison of the FT and DA(FT)$^2$ models using the *Relative Improvement* (*RI*) metric when the number of samples to fine-tune is varied from $n = 2$ to 128 (Full results are in Appendix, Table 9 and 10) [5]. A positive (negative) value of *RI* means DA(FT)$^2$ is performing better (worse) compared to FT, and the larger (smaller) the value the better (worse) DA(FT)$^2$ is performing. We observe that DA(FT)$^2$ outperforms FT by a large margin when $n$ is small (2 to 64), and see only one negative value in the table ($n = 128$). This indicates that DA(FT)$^2$ is outperforming FT in most (few shot) cases on the target task.

Figure 4: *RI of DAFTs over DAFT-E $^Z$ for sentiment analysis*: For each test dataset, we consider 15 DAFT LLMs (fine-tuned on data different from the test data), and consider the RI of DAFT $^Z$ over DAFT-E $^Z$ of 15 DAFT LLMs. Values less than 0 indicate performance degradation. The red squares ■ denote the performance of zero-shot prompting on larger LLMs (Bart-large-mnli, Roberta-large-mnli, and Opt-1.3b). The results show that DAFT-E $^Z$ usually has significantly better zero-shot performance than DAFT $^Z$. However, there are some cases where some specific DAFT models can outperform the average ensemble (leading to RI > 0).

---

[4]We found that updating the weights of the header layer only does not guarantee good performance and can be surpassed by models designed to perform similar tasks without any fine-tuning (zero-shot). So, we chose to do all performance analysis with fully fine-tuned models. Performance comparison of updating the weights of the entire model versus only the header layer is provided in the Appendix (Table 9).

[5]The *RI* values in the table are generated with *Roberta* as the base models for both DA(FT)$^2$ and FT.

> For few-shot tasks, fine-tuning DAFT models, that is DA(FT)$^2$, is generally more beneficial than fine-tuning base models (FT).

From a practical standpoint, a major advantage of using DAFT models is that we get them for *free.* However, as our results show, there is considerable uncertainty about what is the right DAFT model to choose (especially in the zero-shot setting), as the performance can significantly vary between different DAFT models (Fig. 3). Also, note that while DAFT$^Z$ is zero shot, DA(FT)$^2$ is computationally expensive, needing back-propagation. Hence, in the next section, we explore the use of ensemble methods, which is a cheaper alternative and addresses the model selection problem.

## 4  Ensembling of DAFT Models

In this section, we evaluate the performance of the DAFT models using two distinct *Ensemble* methods and benchmark their performances. Advantages of using ensemble methods are discussed in Appendix A.5.

### 4.1  DAFT-E$^Z$ Performance *(Zero Shot)*

The average Ensemble (DAFT-E$^Z$) method is a zero-shot method that can be used as an alternative to randomly picking one of the DAFT models. In DAFT-E$^Z$, the *output probabilities* from all the DAFT models are averaged and the decision is taken on that value (max-voting is another feasible approach). To perform DAFT-E$^Z$, we run inference on all the DAFT models. However, since these DAFT models do not need any further training or fine-tuning and inference can be run in parallel, it is feasible to utilize them efficiently with the abundance of computational devices (mostly low end) available today. Fig. 4 shows the *Relative Improvement* of all the 15 DAFT models and the three larger models (as previously discussed in 3.1.2) for sentiment analysis, compared to the average ensemble of the DAFT models, i.e., DAFT-E$^Z$. There are very few cases (5/90 for DAFT$^Z$, and 1/18 for larger LLMs) in Fig. 4 where a positive *RI* value is seen, implying that the average ensemble method (DAFT-E$^Z$) is better than most of the DAFT models. Moreover, the performance of the larger LLMs (red squares) are not as good as DAFT-E$^Z$. Furthermore, for the Tweet dataset, for which none of the DAFT models performed well and was beaten in performance by two of the larger models (*Bart-large-mnli*, *Roberta-large-mnli*), we now have *RI* values close to zero. Furthermore, for the zero-shot

Figure 5: *Relative Improvement of DAFTs compared to DAFT-E$^Z$* for Text similarity task: For each test dataset, we consider 6 DAFT FMs (fine-tuned on data different from the test data), and consider the RI of DAFT$^Z$ over the DAFT-E$^Z$. Values less than 0 indicate better performance of DAFT-E$^Z$.

Tweet task, while the larger models outperformed all the DAFT$^Z$ models (Fig 4), DAFT-E$^Z$ is able to match their performance, highlighting the utility of ensembles. Hence, DAFT-E$^Z$ has a performance very close to those larger models and shows the importance of using an ensemble even when individual DAFT models cannot perform well. For text similarity task we see a similar trend in the *RI* performance (Fig. 5). In Section 5, we argue theoretically (Proposition 1) that it is better (in an expected sense) to use DAFT-E$^Z$ over choosing a DAFT model randomly from the set of DAFTs.

> For zero-shot tasks, just a simple ensemble of DAFT models (DAFT-E$^Z$) is on average a better choice than any individual DAFT model.

Table 3: Average $RI$ of DA(FT)$^2$ compared to DAFT-E (Top 6: sentiment analysis tasks. Bottom 3: text similarity tasks). Negative values indicate that DAFT-E is better than DA(FT)$^2$ on target (task); larger values imply higher improvements. Table 11 and 12 in the Appendix gives more details. In the very few-shot setting, DAFT-E outperforms DA(FT)$^2$ in almost all cases.

| Target | 2-shot | 4-shot | 8-shot | 16-shot | 32-shot | 64-shot | 128-shot |
|--------|--------|--------|--------|---------|---------|---------|----------|
| Amazon | -4.03 | -2.48 | -2.38 | -2.42 | -2.66 | -2.95 | -2.06 |
| Cornell | -3.94 | -3.60 | -3.37 | -3.54 | -4.13 | -3.91 | -2.53 |
| IMDB | -2.70 | -3.41 | -3.35 | -3.31 | -3.04 | -2.87 | -2.83 |
| SST2 | -4.67 | -3.32 | -3.94 | -4.87 | -4.11 | -4.68 | -4.21 |
| Tweet | -4.62 | -4.91 | -5.14 | -5.54 | -4.00 | -3.82 | -1.59 |
| Yelp | -2.56 | -2.76 | -2.10 | -2.09 | -1.68 | -2.46 | -2.28 |
| MRPC | -5.19 | -4.34 | -4.11 | -3.60 | -3.12 | 1.53 | 4.74 |
| QQP | -2.85 | -2.64 | -0.46 | -0.06 | 2.01 | 2.41 | 4.42 |
| STSB | -5.29 | -5.77 | -4.07 | -1.89 | -1.97 | 0.57 | 1.28 |

The average ensemble is therefore a great data-agnostic solution; however, when training data from the target domain is available, we show that the data-informed ensembling can be a stronger choice. We thus pursue a weighted ensemble of the DAFT models (DAFT-E) in the following section.

## 4.2 *Few-Shot* DAFT-E and DA(FT)$^2$

We define DAFT-E as the weighted ensemble method, where the weights of the ensemble layer are learned using the training data from the target dataset. To perform the weighted ensemble in DAFT-E we utilized two specific regression methods, a) Random forest-based regression ($RF$) and b) SGD-based linear regression ($LR$)[6]. Since, $LR$ is more lightweight with comparable or better performance than $RF$, we considered $LR$ to generate the results of DAFT-E (More discussion on $LR$ and $RF$ performance comparison with the results are in Appendix: Table 11 and 12).

In Section 3.2.2, we observed that DA(FT)$^2$ usually performs better than FT for few-shot learning. Hence, we compare the performance of DAFT-E (weighted ensemble) with DA(FT)$^2$. For a fair comparison, the same amount of data is used when fine-tuning DA(FT)$^2$ and learning the weights of the ensemble layer. Table 3 shows the average RI of DA(FT)$^2$ compared to DAFT-E. An $RI$ of positive (negative) means that DA(FT)$^2$ performed better (worse, resp.) compared to DAFT-E. From Table 3 it is evident that DAFT-E outperforms DA(FT)$^2$ for sentiment analysis tasks, i.e., *all* values are negative in the table. On the other hand, for textual similarity DAFT-E usually performs well for smaller data samples but under-performs on more-data (positive $RI$ values). However, $RF$ performed well with more samples and actually performs better or similarly to DA(FT)$^2$ for $n > 16$ (Table 13 in the Appendix). This shows that weighted ensembling is effective, with task-specific variations between $RF$ and $LR$. Note that updating the ensemble layer depends on the predictions of the DAFT models, and requires solving either (i) a simple linear equation to optimize the weights of the ensemble layer, or (ii) training a $RF$ with shallow trees. Thus, *only a single inference on each of the DAFT models* with the few-shot samples is necessary [7]. In DA(FT)$^2$, where we fine-tune a DAFT model, we need to perform *computationally expensive* back-propagation through the large model to update weights.

> For few shot tasks, (cheap) *weighted* ensemble of DAFT models (DAFT-E) can outperform (expensive) DA(FT)$^2$.

## 4.3 Overall Comparison

For benchmarking purposes, let us assume that we have the entire training data ($D_T$) of the target domain, and have a model that is fine-tuned on $D_T$ (*FFT on $D_T$*). Let us compare the performance of the ensemble methods with this FFT on different datasets. Fig. 6 and 7 show the performance comparison of DAFT-E$^Z$ (green dash-dot line), DAFT-E (purple dash-dot line), single best DAFT (black dotted line), and FFT on $D_T$

---

[6]Parameters of these methods are given in Appendix A.6.

[7]In our evaluations, we found that DAFT-E puts much more weight on the top few DAFT models and we can filter out those models as the candidate of DAFT-E for inference with test data.

Figure 6: *Performance comparison of DAFT-E $^Z$, DAFT-E, single-best DAFT and FFT.* The error interval for DAFT-E is based on the random choice of the few-shot samples used to learn the weights of the ensemble aggregated over 10 trials. The single best DAFT for different datasets are: Amazon (Roberta - Yelp), Cornell (Roberta - SST2), IMDB (xlnet - amazon), SST2 (xlnet - Cornell), Tweet (xlnet - SST2), Yelp (xlnet - amazon).

| (a) MRPC | (b) QQP | (c) STSB |

Figure 7: *Performance comparison of DAFT-E $^Z$, DAFT-E, single-best DAFT and FFT* for Text Similarity task. The error interval for DAFT-E is based on the random choice of the few-shot samples used to learn the weights of the ensemble, using RF method, aggregated over 10 trials. The single best DAFT for different datasets are: MRPC (Roberta - STSB), QQP (Roberta - STSB), STSB (Roberta - MRPC).

(red dotted line) for all the six datasets of the sentiment analysis task and for all three datasets of the text similarity task respectively. From Fig. 6 and 7, we observe the advantage of using DAFT-E over DAFT-E $^Z$ when training data is available. It is interesting to note that DAFT-E has a strong increasing trend in performance (w.r.t. fine-tuning data size) for most cases, and catches up with either the single best DAFT or FFT for the target domain with the increase of fine-tuning data. The performance of DAFT-E compared to the best solution, i.e., FFT on the target domain, can be bounded theoretically and is given by Proposition 2 in Section 5.

Table 4 shows the overall comparison of the computational cost of all the five options that we have discussed in this paper. It should be noted that none of the ensemble methods suffer from the high computational complexity of back-propagation computation; further, using sparse weighting we can reduce the inference cost in DAFT-E compared to DAFT-E $^Z$. It is straightforward to see that DAFT $^Z$ and DAFT-E $^Z$ are the only ones among the five options discussed here that are zero-shot, and hence incurs zero training cost. In contrast, FT and DA(FT) $^2$ has fine-tuning cost, i.e., back-propagation cost ($C_B$), along with forward propagation cost ($C_F$). For DAFT-E, the training cost is the forward propagation cost of $N$ DAFT models along

Table 4: Computational cost of methods shown in Fig. 1. $n$ denotes the number of few-shot samples. $C_F$ and $C_B$ denote the computational costs of a forward and backward pass for a LLM. $E$ is the number of fine-tuning epochs. $N$ is the number of DAFT models available to ensemble, $\bar{N} \leq N$ is the number of nonzero weights in the weighted ensemble.

| Method | Zero-shot | Training cost | Inference cost |
|---|---|---|---|
| FT | ✗ | $n(C_F + C_B)E$ | $C_F$ |
| DAFT $^Z$ | ✓ | 0 | $C_F$ |
| DAFT-E $^Z$ | ✓ | 0 | $N \cdot C_F$ |
| DA(FT) $^2$ | ✗ | $n(C_F + C_B)E$ | $C_F$ |
| DAFT-E | ✗ | $Nn(C_F + E)$ | $\bar{N} \cdot C_F$ |

Table 5: Performance Comparison of DAFT-E$^Z$ and Uniform Soup. The results show that, for zero-shot sentiment analysis tasks, DAFT-E$^Z$ performs at par or better than Uniform Soup. Note that Uniform Soup requires all models to have matching architectures so as to be able to uniformly combine the model weights. DAFT-E $^Z$ (and DAFT-E) do not have any such requirement.

| Dataset | Uniform Soup | DAFT-E $^Z$ |
|---------|--------------|-------------|
| Amazon | 93.29% | **93.72**% |
| Cornell | 85.09% | **85.37**% |
| IMDB | 92.09% | **92.28**% |
| SST2 | 88.07% | **89.55**% |
| Tweet | 86.09% | **87.33**% |
| Yelp | 94.67% | **95.30**% |

Table 6: Robustness Comparison of DAFT-E $^Z$ and Uniform Soup in terms of the set of models being combined. The results show that as we increase the number of DAFT models, the performance of both Uniform Soup and DAFT-E$^Z$ improves, with DAFT-E$^Z$ consistently outperforming Uniform Soup in the zero-shot setting. As discussed in Table 5, we are able to add many more models into DAFT-E$^Z$ than in Uniform Soup because Uniform Soup requires all models in the ensemble to have matching architectures.

| DAFT models combined | Uniform Soup | DAFT-E $^Z$ |
|----------------------|--------------|-------------|
| SST2, Tweet | 88.78% | **89.09**% |
| SST2, Tweet, Yelp | 90.57% | **90.86**% |
| SST2, Tweet, Yelp, Cornell | 91.19% | **91.39**% |
| SST2, Tweet, Yelp, Cornell, Amazon | 92.09% | **92.28**% |

with the linear cost for learning the weight of the ensemble layer. Lastly, FT, DAFT$^Z$ and DA(FT)$^2$ use only a single (DAFT) model, and hence incurs only a forward propagation cost ($C_F$), whereas DAFT-E $^Z$ and DAFT-E use $N$ and $\tilde{N}$ DAFT models respectively in the inference stage.

> DAFT-E $^Z$ and DAFT-E are strong lightweight methods for leveraging already available DAFT models, often matching the single best DAFT model (only known post-hoc), and at times match the best possible performance of full fine-tuning with a large fine-tuning set.

### 4.4 Comparison with Model Soup

We compare the performance of DAFT-E$^Z$ and DAFT-E to a state-of-the-art zero shot ensemble model, Uniform Soup (Model Soup) Wortsman et al. (2022) [8]. To do performance comparison between the zero-shot version of model soup, i.e., Uniform soup with DAFT-E $^Z$, we used the sentiment analysis task. We observed that when there are 5 DAFT models from some specific architecture (we could not use all 15, since there were 3 different architectures)[9], DAFT-E$^Z$ performs better than Model Soup (Table 5). To check the robustness of the DAFT-E $^Z$ method, we then changed our experiments to check performance of DAFT-E $^Z$ and Uniform soup on IMDB dataset by adding DAFT models to the respective methods. The result is shown in Table 6. Interestingly, DAFT-E $^Z$ showed more resiliency than Uniform soup.

## 5 Theoretical Analysis

**Notations.** The dataset of the target domain is $D_T$, the input data to the model is $\mathbf{x}$ and the output data is $\mathbf{y}$, which the model should predict given the input data. There are $N$ number of DAFT models, and a DAFT model can be built using any base model $B_j \in \mathcal{B}$, with $j = \{1, 2, ..., J\}$ and fine-tuning it on dataset $D_k \in \mathcal{DA}$ with $k = \{1, 2, ..., K\}$, where $\mathcal{DA}$ is the set of domain adjacent datasets. The $i^{th}$ DAFT model is given by $M_i$ and the corresponding base model and fine-tuning dataset are given by $B_{\kappa(i)}$ and $D_{\nu(i)}$, respectively, i.e., $B_{\kappa(i)}$ was fine-tuned on $D_{\nu(i)}$ dataset to get $M_i$. Here, $\kappa(i)$ and $\nu(i)$ are index mapping functions. Also, if we assume that all these DAFT models were created by fine-tuning fully on the given datasets (no fractional fine-tuning), then the total number of DAFT can not be greater than $J \times K$, or $N \leq JK$. Lastly, let $\ell(M(\mathbf{x}), \mathbf{y})$ be the loss in output when model $M$ is used on target dataset input $\mathbf{x}$ and the output is compared with $\mathbf{y}$. Since $\mathbf{x}$ and $\mathbf{y}$ are common for all loss calculation, we can just use $\ell(M)$ to represent $\ell(M(\mathbf{x}), \mathbf{y})$.

---

[8]Methods like mixture of experts (MoE) need training with data and our motivation for ensemble was to avoid any training that needs expensive back-propagation. Hence, we refrained from comparing with techniques that require back-propagation unless it is fine-tuning with in-domain data, i.e., FT and DA(FT)$^2$.

[9]Model Soup only works if all the (DAFT) models are of the same architecture, which is not the case for DAFT-E $^Z$ (or DAFT-E). Furthermore, Model Soup needs all the weights of the models to work, but for ensembling, we do not need that. Just API access to the DAFT models is adequate.

## 5.1 DAFT-E $^Z$ versus DAFT $^Z$

Determining if a DAFT model is going to perform well or not is very hard to know a priori if adequate time or data to train or test the model is not available. Hence, instead of choosing one of the DAFT models in random (DAFT $^Z$), one solution could be to use the ensemble of the output results (DAFT-E $^Z$) from all the DAFT models.

**Proposition 1.** *The performance of the average ensemble of DAFT models (DAFT-E $^Z$) is no worse than the expected performance obtained from choosing the DAFT models uniformly at random.*

Proposition 1 states that in terms of expected performance, using DAFT-E $^Z$ is no worse (strictly better, if $\ell$ is assumed to be strictly convex) than picking from the DAFT models uniformly at random. From the performance of DAFT-E $^Z$ shown in Fig. 4 and 5, we see that Proposition 1 holds, i.e., DAFT-E $^Z$ has better performance than the average performance of the DAFT models. Moreover, for these two specific types of tasks, the ensemble of the DAFT models beats the performance of individual DAFT models in most cases (98 out of 108 in total for both tasks).

## 5.2 DAFT-E versus Optimum

Let us denote $\tilde{M}_i$ as the model that uses the base model $B_{\kappa(i)}$ and is fine-tuned on $D_T$, i.e., $\tilde{M}_i = \Phi(B_{\kappa(i)}, D_T)$. Also, we denote $\tilde{M}_*$ is the best performing model when fine-tuned on $D_T$ (the base model for $\tilde{M}_*$ can be from $\mathcal{B}$ that are used to generate DAFT models or some other large model). The following proposition bounds the difference of loss between the optimum solution and DAFT-E.

**Proposition 2.** *The loss of DAFT-E is bounded as:*

$$\ell(\text{DAFT-E}) \leq \ell(\tilde{M}_*) + \min_{i \in \mathcal{N}} \left[ \mu(\tilde{M}_i, \tilde{M}_*) + \rho(D_{\nu(i)}, D_T) \right], \tag{1}$$

*where $\mu(\tilde{M}_i, \tilde{M}_*)$ is the performance difference between the models $\tilde{M}_i$ and $\tilde{M}_*$ both fine-tuned on $D_T$, and $\rho(D_{\nu(i)}, D_T)$ is an appropriately defined distance measure between $D_{\nu(i)}$ and $D_T$.*

Usually base models (derived from FMs which are all quite large) perform similarly when fine-tuned on the full target dataset. Under that assumption, we can ignore the $\mu()$ term in the bound, resulting in the following corollary.

**Corollary 1.** *The loss of DAFT-E is larger than the optimum loss by no greater than $\min_i \rho(D_{\nu(i)}, D_T)$, with the assumption that the base models of the DAFTs can perform as well as the optimum when fine-tuned on the target domain.*

Proposition 2 and Corollary 1 imply that the performance of DAFT-E depends on the base model on which the DAFT models were trained and the datasets they were fine-tuned on. If the base models (FMs) in the ensemble are nearly as good as the best possible base model (FM) (when the performance of the *FFT* of the base models are compared), then we can ignore the $\mu()$ term in Equation 1, and the performance of DAFT-E depends *only on the dataset that is closest* to the target domain. If the DAFT models are generated from a large number of adjacent datasets from diverse domains, we expect the distance from the target dataset to the closest DAFT dataset to be small, resulting in DAFT-E performing very close to the optimum.

In our experimental setting, the assumption made for the Corollary 1 holds, that is, all three base models are comparable in terms of performance when fine-tuned on the same dataset. Hence, the performance of DAFT-E depends on the adjacency of the datasets used in the DAFT models with the target dataset. For the case of sentiment analysis, we have six datasets, whereas for the text similarity task, we only have three. Thus, it is more probable that the DAFT models of the text similarity task are more diverse and DAFT-E will be able to achieve close to optimum performance. From the results (Fig. 6, and 7) it is evident that DAFT-E was able to perform much better for the sentiment analysis task, compared to the textual similarity task.

## 6 Conclusion

In this paper, we explore 4 ways to leverage the abundance of publicly available fine-tuned LLMs for data-scarce tasks. We investigate how the DAFT models can be utilized for inference under limitations on com-

putation time or data required for training a model on a target task. The DAFT models can be used on the target domain (zero-shot) without any fine-tuning. If chosen properly, the performance of DAFT models on the target domain can be close to the optimal performance. However, this performance depends strongly on the choice of the DAFT model, and ensemble methods can be used to address this issue. Two ensemble methods, DAFT-E $^Z$ and DAFT-E are explored; their performances are empirically evaluated and compared against individual DAFT models and other benchmarks involving larger LLMs and base models trained with the full target domain dataset. Our theoretical results support the conclusions from the empirical findings, and provide insights under what conditions DAFT-E can provide near-optimal performance.

**Broader Impact Statement**

The use of DAFT models can be a great low-resource and easy-to-use solution in data-scarce domains. Due to the current surge of open source DAFT models for different downstream tasks, the community can use these models directly without any (computationally expensive) fine-tuning of LLMs. The main innovation of the proposed ensemble methods, i.e., DAFT-E $^Z$ and DAFT-E, is the utilization of readily available DAFT models to perform lightweight solutions for problems where little or no data from the target domain is available.

On the other hand, there are certain limitations of our method that the users may face and should keep in mind. Firstly, the performance of these methods is highly dependent on the availability of DAFT models. DAFT-E or DAFT-E $^Z$ will not perform well when none of the available DAFT models are adjacent to the target domain. Moreover, while many DAFT models for sentiment analysis and NLI tasks are currently available, DAFTs for some other tasks might not be as widely available soon. Secondly, DAFT-E $^Z$ and DAFT-E require inference with multiple DAFT models. While the multi-model inference can be parallelized, thereby reducing inference time in scenarios where multiple smaller servers are available, inference time would increase if memory is limited or the per-model inference needs to be sequential. Further, with DAFT-E, we can filter out some of the candidate DAFT models, thereby reducing $N$, but that depends on having some data from the target domain. Thirdly, with the proposed methods, the users are supposed to use openly available fine-tuned models; however, the quality or correctness of the fine-tuning datasets and training methods may be questionable. There is also the question of the privacy of the data and the use of the models, which the user might not be aware of.

# References

Leo Breiman. Bagging predictors. *Machine learning*, 24:123–140, 1996.

Rich Caruana, Alexandru Niculescu-Mizil, Geoff Crew, and Alex Ksikes. Ensemble selection from libraries of models. In *Proceedings of the twenty-first international conference on Machine learning*, pp. 18, 2004.

Robert T Clemen. Combining forecasts: A review and annotated bibliography. *International journal of forecasting*, 5(4):559–583, 1989.

Thomas G Dieterich. An experimental comparison of three methods for constructing ensembles of decision trees: Bagging, boosting, and randomization. *Machine learning*, 40:139–157, 2000.

William Fedus, Jeff Dean, and Barret Zoph. A review of sparse expert models in deep learning. *arXiv preprint arXiv:2209.01667*, 2022.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. Don't stop pretraining: Adapt language models to domains and tasks. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8342–8360, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.740. URL https://aclanthology.org/2020.acl-main.740.

Hugging Face HF. Hugging face datasets, 2024a. URL https://huggingface.co/datasets.

Hugging Face HF. Hugging face comment on fine-tuned llama-3 models, 2024b. URL https://huggingface.co/posts/clem/189843726787210.

Hugging Face HF. Hugging face models, 2024c. URL `https://huggingface.co/models`.

Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of local experts. *Neural computation*, 3(1):79–87, 1991.

Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, Gianna Lengyel, Guillaume Bour, Guillaume Lample, Lélio Renard Lavaud, Lucile Saulnier, Marie-Anne Lachaux, Pierre Stock, Sandeep Subramanian, Sophia Yang, Szymon Antoniak, Teven Le Scao, Théophile Gervet, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mixtral of experts, 2024.

Dongfu Jiang, Xiang Ren, and Bill Yuchen Lin. Llm-blender: Ensembling large language models with pairwise ranking and generative fusion, 2023.

Kaggle. Twitter sentiment dataset, 2024. URL `https://www.kaggle.com/datasets/saurabhshahane/twitter-sentiment-dataset`.

Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT*, pp. 4171–4186, 2019.

Sung Kim. List of open sourced fine-tuned large language models (LLM), 2023. URL `https://sungkim11.medium.com/list-of-open-sourced-fine-tuned-large-language-models-llm-8d95a2e0dc76`.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30, 2017.

Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation, 2021.

Xiaoding Lu, Zongyi Liu, Adian Liusie, Vyas Raina, Vineet Mudupalli, Yuwen Zhang, and William Beauchamp. Blending is all you need: Cheaper, better alternative to trillion-parameters llm, 2024.

Richard Maclin and David Opitz. An empirical evaluation of bagging and boosting. *AAAI/IAAI*, 1997: 546–551, 1997.

Cuong Nguyen, Tal Hassner, Matthias Seeger, and Cedric Archambeau. Leep: A new measure to evaluate transferability of learned representations. In *International Conference on Machine Learning*, pp. 7294–7305. PMLR, 2020.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in neural information processing systems*, 32, 2019.

Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359, 2009.

Boris T Polyak and Anatoli B Juditsky. Acceleration of stochastic approximation by averaging. *SIAM journal on control and optimization*, 30(4):838–855, 1992.

Clemens Rosenbaum, Tim Klinger, and Matthew Riemer. Routing networks: Adaptive selection of non-linear functions for multi-task learning, 2017.

Ying Sheng, Shiyi Cao, Dacheng Li, Coleman Hooper, Nicholas Lee, Shuo Yang, Christopher Chou, Banghua Zhu, Lianmin Zheng, Kurt Keutzer, Joseph E. Gonzalez, and Ion Stoica. S-lora: Serving thousands of concurrent lora adapters, 2023.

Cornell University. Movie review data, 2024. URL `https://www.cs.cornell.edu/people/pabo/movie-review-data/`.

Figure 8: Heatmap showing the performance of DAFT models for sentiment analysis task when base model is BERT-based-uncased

Figure 9: Heatmap showing the performance of DAFT models for sentiment analysis task when base model is xlnet-base-cased

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, pp. 23965–23998. PMLR, 2022.

Seniha Esen Yuksel, Joseph N Wilson, and Paul D Gader. Twenty years of mixture of experts. *IEEE transactions on neural networks and learning systems*, 23(8):1177–1193, 2012.

Fuzhen Zhuang, Zhiyuan Qi, Keyu Duan, Dongbo Xi, Yongchun Zhu, Hengshu Zhu, Hui Xiong, and Qing He. A comprehensive survey on transfer learning. *Proceedings of the IEEE*, 109(1):43–76, 2020.

# A   Appendix

## A.1   Datasets and Models

The attributes of the six datasets used for sentiment analysis and the three dataset used for text similarity analysis are given in Table 7 and 8. For 'SST2' we had to use validation dataset as test data, because the test data does not have any labels. The direct link to download these datasets are given as follows: https:// huggingface.co /datasets/amazon_polarity, 'https:// www.cs.cornell.edu /people/pabo/movie-review-data/', 'https://huggingface.co/datasets/ imdb', 'https:// huggingface.co/ datasets/sst2', 'https:// huggingface.co/ datasets/ mteb/tweet_sentiment_extraction', 'https:// huggingface.co/ datasets/ yelp_polarity', 'https://huggingface.co /datasets/nyu-mll/glue' (when copying the links please remove any spaces from the texts). Figure 8 and 9 shows the performance heat-map for sentiment analysis task when the base models are BERT-based-uncased and xlnet-base-cased respectively. The heat maps in general follows a similar pattern as observed in Figure 2, i.e., Tweet test data cannot be predicted well by any other DAFT models, and Cornell test data is also hard to predict. The observation of DAFT trained on tweet data performing poor is true for bert-based-uncased as well, but not always true for xlnet-base-cased. Another interesting observation is that for xlnet, the DAFT model trained on IMDB data seems to perform quite poorly in a few instances (i.e., on test data of Cornell and Tweet).

## A.2   Experimental Settings

The base models were used from huggingface using the 'AutoTokenizer.from_pretrained', and the webpage with descriptions and examples can be found in 'https://huggingface.co/ transformers/v3.0.2/model_doc/auto.html'. To fine-tune and train these models we used Google Colab platform

Table 7: Dataset sizes and classes (Sentiment Analysis)

| Dataset | Train data | Test data | Classes |
|---------|-----------|-----------|---------|
| Amazon | 3,600,000 | 400,000 | 2 |
| Cornell | 7,463 | 2134 | 2 |
| IMDB | 25,000 | 25,000 | 2 |
| SST2 | 67,349 | 1821 | 2 |
| Tweet | 12927 | 3696 | 3 |
| Yelp | 560,000 | 38,000 | 2 |

Table 8: Dataset sizes and classes (Text Similarity)

| Dataset | Train data | Test data | Classes |
|---------|-----------|-----------|---------|
| MRPC | 3,670 | 1,730 | 2 |
| QQP | 364,000 | 40,000 | 2 |
| STSB | 7,500 | 1,500 | 2 |

with the T4 GPU equipped machine. For FT we chose each of the three base models (Roberta, BERT, xlnet) and fine-tuned the models with target data until the loss per epoch did not improve more than 1% or at least a fixed number of data-samples has not been used for training. All these fine-tuned models on the target dataset acted as a suitable candidate for DAFT models. For $DA(FT)^2$ we used any of these DAFT models to fine-tune on another target dataset for few shot training. In the performance comparison of $DA(FT)^2$ we only showed the performance of $DA(FT)^2$ that was fine-tuned on DAFT models having Roberta as its base. For both FT and $DA(FT)^2$ on few shot training, we performed the all the runs five times with five different seeds. For the case of DAFT-E, the weight calculations were done using five different random seeds as well. All the results shown here are the mean values of all those runs.

## A.3 Discussion on Performance Anomalies - SST2

The SST2 dataset obtained from Huggingface did not have any label on its test data, and we had to use the validation data of SST2 as the test data instead. Also, the validation data of SST2 only had 872 samples. Now, in the heat map shown in Figure 2, the performance of DAFT-SST2 achieved 92% accuracy on the SST2 validation data, whereas, DAFT-Cornell achieved 93.1% accuracy on that same test dataset. This is quite counter intuitive, because we expect DAFT-SST2 to be the best performing one on its own domain (SST2 validation data). We did a thorough simulation analysis to check what might be the reason. Since the DAFT-SST2 was generated using randomly chosen $7,000$ samples from the training dataset of SST2, and we initially extracted the rest of the training data and divided it to different batches of $5,000$ samples. Now, with this batches we checked the performance of DAFT- SST2 and DAFT- Cornell. As expected, we got better performance with DAFT- SST2 compared to DAFT- Cornell with these new batches. With this experiment, we concluded that SST2 validation dataset is, for some unknown reason, more similar to the Cornell training dataset than the SST2 training data, and thus giving a counter intuitive result.

## A.4 Fine-tuning the header or whole model

Figure 10 to 15 show the performance comparison of fine-tuning only the header layer of the base model and fine-tuning the whole model of the base models. It is straightforward to see the superior performance of fine-tuning the whole model even though the base models (i.e., BERT, Roberta) have already gone through extensive training with language data.

## A.5 Advantage of Ensemble

Our goal in this work is to find a suitable method that ensures better performance when data from the target domain is scarce, and therefore it is not possible to determine conclusively which of the available fine-tuned foundation models are adjacent to the target domain (if DAFT or not)[10]. The advantage of using Ensemble method are: 1) there is no constraint on the DAFT model size and architecture, 2) no need of knowing the weights of the DAFT models, just an API access to the DAFT models is adequate. In our study, we found that even if we do not know how domain-adjacent the available models are, their aggregate ensemble can still perform well (with zero or very limited training) as long as there are some models in the ensemble that

---

[10]There are a few established methods (e.g. LEEP score) to find the adjacency between two datasets, however these methods for determining domain-adjacency generally require a substantial amount of data from the target domain.

Figure 10: Performance comparison of FT Header layer to FT whole Model - Amazon dataset.

Figure 11: Performance comparison of FT Header layer to FT whole Model - Cornel dataset.

Figure 12: Performance comparison of FT Header layer to FT whole Model - IMDB dataset.

Figure 13: Performance comparison of FT Header layer to FT whole Model - SST2 dataset.

Figure 14: Performance comparison of FT Header layer to FT whole Model - Tweet dataset.

Figure 15: Performance comparison of FT Header layer to FT whole Model - Yelp dataset.

are domain-adjacent (although we may not know which ones). Furthermore, as we have observed in the paper, the weighted ensemble of the DAFT models (DAFT-E) can perform similarly to or better than the best single (available) DAFT model. In summary, without adequate data it may be hard to determine which models are DAFT and which are not, and a very low-data low-resource ensembling method like DAFT-E $^Z$ or DAFT-E can give us good results.

### A.6 Ensemble Layer of DAFT-E

### A.6.1 Weight update of $LR$

Our ensemble technique uses the final layer output of the DAFT models as the input of the ensemble layer. When performing DAFT-E with $LR$, If $w_i$ is the weight of model $i$ in the Ensemble weight layer, then the $LR$ performs the following:

$$\min_{w_i \in \mathbf{w}} \sum_{(X,y) \in D_T} \ell\left(\left(\left(\sum_i w_i M_i(X)\right), y\right)\right) + R(\mathbf{w})$$

where, $\ell$ is the loss calculated using the output from the DAFT models $(M_i(X))$, to the ground truth $y$. Also, the term $R(\mathbf{w})$ can be used to regularize (or control) the number of models $(\tilde{N})$ we want to use for our final ensemble. To keep the method simple, we did not use the regularization when implementing DAFT-E.

### A.6.2 Regression methods: $LR$ and $RF$

We observed the following in terms of performance of the two regression methods: (i) $LR$ has better performance and less variation in performance for smaller sample data, (ii) for higher sample data, i.e., $n>32$, $RF$ usually performs very similar to $LR$, (iii) for sentiment analysis tasks, $LR$ and $RF$ both perform well with similar performance at higher sample data, and (iv) for textual similarity tasks, $LR$ shows minimal performance improvement with more samples, whereas $RF$ shows promising results.

For *LR* we have used SGDRegressor from sklearn.linear_model with maximum iteration of 3. The reason behind this small iteration number is because of the few shot regime. If we had used larger bound on iteration, overfitting might have casued more harm than good. We also used coefficient initialization $= 1/N$, where $N$ is the number of DAFT models used, so that at the start DAFT-E gives same weights to all the models. For *RF* we imported the RandomForestClassifier from sklearn.ensemble, and set the max depth $= 2$. The smaller max depth was chosen to avoid overfitting.

## A.7  Performance of DAFT models and DAFT-E $^Z$ for Textual similarity task

Figure 16 and 5 show the Relative Improvement of DAFTs compared to Single Best DAFT and DAFT-E $^Z$ respectively for the textual similarity task with three datasets. Similar to the results with sentiment analysis task, we observe the performance deviation among the DAFT models and usual better performance of DAFT-E $^Z$.

Figure 16: *Relative Improvement of DAFTs compared to the Single Best DAFT* for Text similarity task: For each test dataset, we consider 6 DAFT FMs (fine-tuned on data different from the test data), and consider the RI of DAFT $^Z$ over the single-best DAFT FM (out of the 6). Values less than 0 indicate performance degradation.

## A.8  Proof of Propositions

**Proof of Proposition 1**   In the following, we let $\mathcal{N} = \{1, 2, \cdots, N\}$ denote the set of indices of the DAFT models in the ensemble.

$$\mathbb{E}(\ell(\mathsf{DAFT}^{\,Z})) = \mathbb{E}(\ell(M_i(X), y)) \quad \forall i \in \mathcal{N}$$

$$= \frac{1}{N} \sum_{i \in \mathcal{N}} \ell(M_i(X), y)$$

$$= \frac{1}{N} \sum_{i \in \mathcal{N}} \ell(\mu_i, y) \ \ [\text{denoting } M_i(X) \text{ as } \mu_i]$$

$$\geq \ell \left( \sum_{i \in \mathcal{N}} \frac{1}{N} \mu_i, y \right) \ \ [\text{assuming } \ell \text{ is convex in } \mu_i]$$

$$= \text{loss of average ensemble} = \ell(\mathsf{DAFT\text{-}E}^{\,Z}). \tag{2}$$

Note that the derivation assumes $\ell$ to be convex in $\mu_i$, the outputs from the DAFT models, which is a common assumption for loss functions. □

**Proof of Proposition 2**   If the ensemble weights for the $i^{th}$ model is $w_i$, then for the weighted ensemble method we have;

$$\ell(\mathsf{DAFT\text{-}E})$$

$$= \text{loss of weighted ensemble}$$

$$= \min_{w_i, i \in \mathcal{N}} \left[ \ell \left( \sum_i w_i M_i \right) \right]$$

$$\leq \ell(M_i), \ \ \forall i \in \mathcal{N}. \tag{3}$$

Note that the above derivation assumes that the set weights $w_i, i \in \mathcal{N}$, have been optimized (trained using the fine-tuning dataset from the target domain) to minimize the loss function $\ell \left( \sum_i w_i M_i \right)$.

Note that the base model that $M_i$ is built from is $B_{\kappa(i)}$. Further, $\tilde{M}_i$ denotes the corresponding FFT, i.e., the model built from $B_{\kappa(i)}$ by fine-tuning on the target dataset $D_T$. Now, let us assume that for two DAFT models $M_1$ and $M_2$ developed from the same base model and fine-tuned on different datasets, i.e., $D_{\nu(1)}$ and $D_{\nu(2)}$, to have the following bound on their losses;

$$|\ell(M_1) - \ell(M_2)| \leq \rho(D_{\nu(1)}, D_{\nu(2)}), \tag{4}$$

where $\rho$ is an appropriately defined distance measure between the datasets $D_{\nu(1)}$ and $D_{\nu(2)}$. Then from Equation 3 we have;

$$\ell(\mathsf{DAFT\text{-}E}) \leq \ell(M_i) \leq \ell(\tilde{M}_i) + \rho(D_{\nu(i)}, D_T), \forall i. \tag{5}$$

Now, let us denote $\tilde{M}_*$ be the model fine-tuned on $D_T$ and performs the best among all the models when fine-tuned on $D_T$ (all possible FFTs). Then from 5 and by defining $\mu(M_1, M_2) \triangleq \ell(M_1) - \ell(M_2)$, we have

$$\ell(\mathsf{DAFT\text{-}E}) \leq \ell(\tilde{M}_*) + \rho(D_{\nu(i)}, D_T)$$
$$+ \mu(\tilde{M}_i, \tilde{M}_*); \quad \forall i. \tag{6}$$

Since Equation 6 holds for all $i \in \mathcal{N}$, Equation 1 follows by taking a minimum over all $i$, completing the proof. $\square$

Note that Equation 1 bounds the gap between the mimimum loss possible under any model and the loss of DAFT-E. The result is intuitive. The term $\mu()$ tells us that the performance gap depends on how good the base models (corresponding to the DAFT models in the ensemble) are, when compared to the best possible model, when they are all trained on the full target dataset. The term $\rho()$ implies that the performance gap also depends on how closely the datasets used to generate the DAFT models represent the target dataset. Note that the minimum over $i$ is taken on the sum of $\mu()$ and $\rho()$, instead of of each of the two terms individually. However, for an ensemble of DAFT models obtained by fine-tuning a "good" set of FMs with a large number of datasets, the approximation term $\mu() + \rho()$ is expected to be small, as argued in Section 5.2.

Table 9: Relative Improvement of $\mathtt{DA(FT)}^2$ compared to $\mathtt{FT}$ (Sentiment Analysis). The base model for all the models ($\mathtt{DAFT}$ and $\mathtt{FT}$) here is Roberta-base.

| Dataset | DAFT Name | $n = 2$ | $n = 4$ | $n = 8$ | $n = 16$ | $n = 32$ | $n = 64$ | $n = 128$ | $n = 256$ |
|---|---|---|---|---|---|---|---|---|---|
| Amazon | DAFT- Cornell | 80.42 | 76.28 | 81.10 | 67.16 | 55.45 | 32.55 | 0.50 | 0.48 |
| | DAFT- IMDB | 78.33 | 77.79 | 83.46 | 68.53 | 57.12 | 37.85 | 2.66 | 1.92 |
| | DAFT- SST2 | 78.11 | 75.33 | 78.67 | 65.6 | 54.45 | 34.45 | 0.57 | 0.77 |
| | DAFT- Tweet | 61.33 | 67.70 | 71.34 | 56.76 | 47.07 | 31.19 | -1.11 | -0.85 |
| | DAFT- Yelp | 81.59 | 79.18 | 83.50 | 68.95 | 53.48 | 35.24 | 1.42 | 1.54 |
| | Average | 75.95 | 75.25 | 79.62 | 65.40 | 53.51 | 34.26 | 0.81 | 0.77 |
| Cornell | DAFT- Amazon | 73.60 | 71.74 | 68.88 | 63.6 | 61.01 | 38.06 | 10.25 | 1.66 |
| | DAFT- IMDB | 68.43 | 64.88 | 64.64 | 62.43 | 61.23 | 38.52 | 9.58 | 3.60 |
| | DAFT- SST2 | 74.8 | 72.11 | 68.89 | 66.71 | 63.54 | 38.97 | 9.64 | 2.67 |
| | DAFT- Tweet | 53.72 | 52.43 | 49.77 | 48.37 | 51.15 | 31.50 | 6.11 | 2.23 |
| | DAFT- Yelp | 69.22 | 66.87 | 64.13 | 62.47 | 51.87 | 32.19 | 8.65 | 0.3 |
| | Average | 67.95 | 65.61 | 63.26 | 60.72 | 57.77 | 35.85 | 8.85 | 2.09 |
| IMDB | DAFT- Amazon | 81.35 | 81.84 | 81.66 | 70.94 | 61.86 | 50.11 | 2.53 | 0.65 |
| | DAFT- Cornell | 77.79 | 77.09 | 80.67 | 66.68 | 57.4 | 49.72 | 2.46 | -0.03 |
| | DAFT- SST2 | 76.10 | 75.28 | 77.99 | 64.86 | 57.45 | 47.36 | -1.33 | -0.977 |
| | DAFT- Tweet | 59.12 | 60.27 | 60.49 | 58.10 | 53.54 | 45.20 | -0.62 | -0.70 |
| | DAFT- Yelp | 76.93 | 78.72 | 80.11 | 69.47 | 60.73 | 45.82 | -2.52 | 0.247 |
| | Average | 74.26 | 74.64 | 76.19 | 66.01 | 58.20 | 47.64 | 0.10 | -0.16 |
| SST2 | DAFT- Amazon | 76.35 | 73.84 | 73.54 | 70.05 | 72.62 | 58.52 | 11.47 | 2.03 |
| | DAFT- Cornell | 82.05 | 78.97 | 78.81 | 80.32 | 77.56 | 64.29 | 16.84 | 5.41 |
| | DAFT- IMDB | 71.55 | 75.20 | 72.81 | 74.51 | 71.62 | 62.14 | 14.46 | 3.85 |
| | DAFT- Tweet | 62.25 | 60.66 | 60.68 | 62.66 | 63.46 | 53.84 | 10.30 | 0.92 |
| | DAFT- Yelp | 73.42 | 74.51 | 73.2 | 72.18 | 74.17 | 54.1 | 10.89 | 2.75 |
| | Average | 73.13 | 72.64 | 71.81 | 71.95 | 71.88 | 58.58 | 12.79 | 2.99 |
| Tweet | DAFT- Amazon | 60.22 | 53.93 | 55.79 | 41.88 | 42.67 | 26.16 | 1.2 | -2.2 |
| | DAFT- Cornell | 56.37 | 49.64 | 50.94 | 52.62 | 39.55 | 23.64 | 1.03 | -1.58 |
| | DAFT- IMDB | 59.72 | 53.76 | 52.58 | 55.26 | 45.22 | 30.19 | 4.69 | 1.59 |
| | DAFT- SST2 | 62.23 | 55.20 | 57.46 | 54.1 | 41.79 | 26.48 | 2.29 | -1.06 |
| | DAFT- Yelp | 64.83 | 58.69 | 60.85 | 57.37 | 39.85 | 23.15 | 2.5 | -1.6 |
| | Average | 60.67 | 54.25 | 55.53 | 52.25 | 41.82 | 25.92 | 2.34 | -0.97 |
| Yelp | DAFT- Amazon | 79.81 | 84.56 | 71.46 | 85.73 | 49.85 | 26.89 | -2.32 | -0.41 |
| | DAFT- Cornell | 74.39 | 83.52 | 67.09 | 81.15 | 45.62 | 29.28 | -0.65 | -0.81 |
| | DAFT- IMDB | 77.45 | 83.51 | 67.84 | 83.75 | 47.97 | 29.62 | 1.02 | 0.29 |
| | DAFT- SST2 | 75.4 | 80.74 | 66.07 | 80.69 | 45.82 | 26.711 | -0.86 | -1.48 |
| | DAFT- Tweet | 67.36 | 72.68 | 61.60 | 77.06 | 43.10 | 26.81 | -0.79 | -1.22 |
| | Average | 74.88 | 81.00 | 66.81 | 81.68 | 46.47 | 27.86 | -0.72 | -0.73 |

Table 10: Relative Improvement of $\mathsf{DA(FT)}^2$ compared to $\mathsf{FT}$ (Text Similarity). The R, B, X at the end of the $\mathsf{DAFT}$ names denote the base model of the $\mathsf{DAFT}$ models, and they denote: Roberta, Bert, Xlnet base models respectively.

| Dataset | DAFT Name | $n=2$ | $n=4$ | $n=8$ | $n=16$ | $n=32$ | $n=64$ | $n=128$ | $n=256$ |
|---|---|---|---|---|---|---|---|---|---|
| MRPC | DAFT- QQP-R | 34.78 | 32.60 | 32.08 | -6.49 | 24.68 | 18.15 | 20.21 | 10.83 |
| | DAFT- STSB-R | 55.83 | 54.79 | 61.86 | 13.01 | 41.26 | 32.65 | 28.13 | 18.20 |
| | DAFT- QQP-B | 36.45 | 34.58 | 39.62 | -1.60 | 24.19 | 16.03 | 12.41 | 8.69 |
| | DAFT- STSB-B | 54.27 | 52.31 | 59.27 | 12.49 | 37.97 | 27.81 | 23.47 | 12.33 |
| | DAFT- QQP-X | 33.75 | 29.95 | 35.87 | -2.57 | 24.02 | 16.12 | 15.38 | 6.05 |
| | DAFT- STSB-X | 54.22 | 53.29 | 59.77 | 13.61 | 40.77 | 30.08 | 25.80 | 16.34 |
| | Average | 44.88 | 42.92 | 48.08 | 4.74 | 32.15 | 23.47 | 20.90 | 12.07 |
| QQP | DAFT- MRPC-R | 75.56 | 78.10 | 88.81 | 86.98 | 66.05 | 47.51 | 16.33 | 4.71 |
| | DAFT- STSB-R | 81.24 | 80.61 | 99.21 | 97.98 | 77.47 | 57.41 | 19.36 | 7.38 |
| | DAFT- MRPC-B | 63.40 | 65.81 | 72.71 | 78.10 | 59.59 | 42.61 | 9.76 | -0.62 |
| | DAFT- STSB-B | 79.18 | 82.73 | 89.69 | 94.59 | 69.40 | 51.00 | 14.10 | 2.03 |
| | DAFT- MRPC-X | 61.59 | 65.76 | 72.62 | 75.59 | 56.21 | 42.88 | 8.57 | -2.41 |
| | DAFT- STSB-X | 76.61 | 78.03 | 83.61 | 88.56 | 63.45 | 49.58 | 15.04 | 1.97 |
| | Average | 72.93 | 75.17 | 84.44 | 86.97 | 65.36 | 48.50 | 13.86 | 2.18 |
| STSB | DAFT- MRPC-R | 46.89 | 53.02 | 50.07 | 51.96 | 45.97 | 28.01 | 1.26 | 0.64 |
| | DAFT- QQP-R | 51.78 | 50.82 | 57.42 | 63.87 | 56.15 | 36.55 | 4.85 | 1.95 |
| | DAFT- MRPC-B | 42.88 | 40.53 | 44.46 | 47.67 | 44.77 | 24.74 | -3.51 | -3.24 |
| | DAFT- QQP-B | 56.55 | 58.26 | 56.90 | 58.49 | 57.51 | 33.36 | 1.83 | 0.89 |
| | DAFT- MRPC-X | 40.73 | 39.28 | 35.59 | 41.34 | 41.23 | 22.05 | -5.52 | -3.76 |
| | DAFT- QQP-X | 51.34 | 53.98 | 52.69 | 55.15 | 53.66 | 30.73 | 0.37 | -0.74 |
| | Average | 48.36 | 49.31 | 49.52 | 53.08 | 49.88 | 29.24 | -0.12 | -0.71 |

Table 11: Relative Improvement of DA(FT)$^2$ compared to DAFT-E (Sentiment Analysis). The base model for all the DAFT models here is Roberta-base.

| Dataset | DAFT Name | $n = 2$ | $n = 4$ | $n = 8$ | $n = 16$ | $n = 32$ | $n = 64$ | $n = 128$ | $n = 256$ |
|---|---|---|---|---|---|---|---|---|---|
| Amazon | DAFT- Cornell | -1.60 | -1.91 | -1.57 | -1.38 | -1.43 | -4.177 | -2.35 | -1.78 |
| | DAFT- IMDB | -2.74 | -1.07 | -0.29 | -0.57 | -0.38 | -0.35 | -0.26 | -0.37 |
| | DAFT- SST2 | -2.85 | -2.43 | -2.89 | -2.3 | -2.06 | -2.80 | -2.30 | -1.50 |
| | DAFT- Tweet | -12.01 | -6.68 | -6.87 | -7.51 | -6.75 | -5.17 | -3.92 | -3.09 |
| | DAFT- Yelp | -0.96 | -0.30 | -0.27 | -0.32 | -2.683 | -2.238 | -1.46 | -0.753 |
| | Average | -4.03 | -2.48 | -2.38 | -2.42 | -2.66 | -2.95 | -2.06 | -1.50 |
| Cornell | DAFT- Amazon | -0.71 | -0.03 | -0.04 | -1.81 | -2.14 | -2.34 | -1.27 | -3.06 |
| | DAFT- IMDB | -3.66 | -4.02 | -2.55 | -2.51 | -2.03 | -2.02 | -1.87 | -1.21 |
| | DAFT- SST2 | -0.02 | 0.187 | -0.04 | 0.05 | -0.62 | -1.70 | -1.82 | -2.10 |
| | DAFT- Tweet | -12.08 | -11.27 | -11.35 | -10.95 | -8.15 | -6.99 | -4.98 | -2.52 |
| | DAFT- Yelp | -3.21 | -2.87 | -2.85 | -2.49 | -7.72 | -6.50 | -2.70 | -4.38 |
| | Average | -3.94 | -3.60 | -3.37 | -3.54 | -4.13 | -3.91 | -2.53 | -2.65 |
| IMDB | DAFT- Amazon | 1.25 | 0.57 | -0.35 | -0.43 | -0.79 | -1.25 | -0.48 | -0.65 |
| | DAFT- Cornell | -0.73 | -2.05 | -0.89 | -2.92 | -3.53 | -1.51 | -0.54 | -1.32 |
| | DAFT- SST2 | -1.675 | -3.05 | -2.36 | -3.98 | -3.50 | -3.06 | -4.22 | -2.25 |
| | DAFT- Tweet | -11.16 | -11.35 | -11.96 | -7.92 | -5.89 | -4.48 | -3.53 | -1.98 |
| | DAFT- Yelp | -1.21 | -1.25 | -1.20 | -1.29 | -1.49 | -4.07 | -5.39 | -1.05 |
| | Average | -2.70 | -3.41 | -3.35 | -3.31 | -3.04 | -2.87 | -2.83 | -1.45 |
| SST2 | DAFT- Amazon | -2.89 | -2.64 | -2.94 | -5.91 | -3.70 | -4.71 | -5.33 | -4.65 |
| | DAFT- Cornell | 0.25 | 0.23 | -0.02 | -0.24 | -0.95 | -1.25 | -0.77 | -1.49 |
| | DAFT- IMDB | -5.53 | -1.88 | -3.38 | -3.45 | -4.26 | -2.54 | -2.79 | -2.95 |
| | DAFT- Tweet | -10.65 | -10.03 | -10.16 | -10.01 | -8.81 | -7.53 | -6.33 | -5.69 |
| | DAFT- Yelp | -4.50 | -2.27 | -3.16 | -4.74 | -2.84 | -7.37 | -5.82 | -3.97 |
| | Average | -4.67 | -3.32 | -3.94 | -4.87 | -4.11 | -4.68 | -4.21 | -3.75 |
| Tweet | DAFT- Amazon | -4.89 | -5.09 | -4.98 | -11.98 | -3.42 | -3.64 | -2.69 | -1.63 |
| | DAFT- Cornell | -7.17 | -7.74 | -7.94 | -5.31 | -5.53 | -5.56 | -2.86 | -1.00 |
| | DAFT- IMDB | -5.19 | -5.21 | -6.93 | -3.68 | -1.69 | -0.57 | 0.67 | 2.18 |
| | DAFT- SST2 | -3.70 | -4.31 | -3.96 | - 4.40 | -4.02 | -3.40 | -1.64 | -0.48 |
| | DAFT- Yelp | -2.15 | -2.17 | -1.89 | -2.36 | -5.33 | -5.94 | -1.44 | -1.02 |
| | Average | -4.62 | -4.91 | -5.14 | -5.54 | -4.00 | -3.82 | -1.59 | -0.39 |
| Yelp | DAFT- Amazon | 0.18 | -0.84 | 0.62 | 0.10 | 0.60 | -3.20 | -3.85 | -0.98 |
| | DAFT- Cornell | -2.83 | -1.40 | -1.93 | -2.37 | -2.25 | -1.37 | -2.21 | -1.37 |
| | DAFT- IMDB | -1.13 | -1.41 | -1.50 | -0.97 | -0.67 | -1.11 | -0.57 | -0.29 |
| | DAFT- SST2 | -2.27 | -2.90 | -2.53 | -2.62 | -2.11 | -3.33 | -2.42 | -2.04 |
| | DAFT- Tweet | -6.75 | -7.22 | -5.16 | -4.58 | -3.94 | -3.26 | -2.34 | -1.79 |
| | Average | -2.56 | -2.76 | -2.10 | -2.09 | -1.68 | -2.46 | -2.28 | -1.29 |

Table 12: Relative Improvement of DA(FT)$^2$ compared to DAFT-E- LR (Text Similarity). The R, B, X at the end of the DAFT names denote the base model of the DAFT models, and they denote: Roberta, Bert, Xlnet base models respectively.

| Dataset | DAFT Name | $n=2$ | $n=4$ | $n=8$ | $n=16$ | $n=32$ | $n=64$ | $n=128$ | $n=256$ |
|---------|-----------|-------|-------|-------|--------|--------|--------|---------|---------|
| MRPC | DAFT- QQP-R | -11.80 | -11.25 | -14.47 | -13.93 | -8.60 | -2.85 | 4.15 | 7.20 |
| | DAFT- STSB-R | 1.98 | 3.60 | 4.81 | 4.01 | 3.56 | 9.08 | 11.00 | 14.33 |
| | DAFT- QQP-B | -10.71 | -9.92 | -9.59 | -9.44 | -8.95 | -4.59 | -2.61 | 5.13 |
| | DAFT- STSB | 0.95 | 1.94 | 3.14 | 3.53 | 1.15 | 5.10 | 6.97 | 8.66 |
| | DAFT- QQP-X | -12.47 | -13.02 | -12.02 | -10.33 | -9.08 | -4.52 | -0.04 | 2.58 |
| | DAFT- STSB-X | 0.92 | 2.60 | 3.46 | 4.56 | 3.20 | 6.96 | 8.99 | 12.54 |
| | Average | -5.19 | -4.34 | -4.11 | -3.60 | -3.12 | 1.53 | 4.74 | 8.41 |
| QQP | DAFT- MRPC-R | -1.37 | -1.01 | 1.90 | -0.05 | 2.44 | 1.73 | 6.68 | 7.89 |
| | DAFT- STSB-R | 1.82 | 0.39 | 7.51 | 5.83 | 9.49 | 8.55 | 9.46 | 10.65 |
| | DAFT- MRPC-B | -8.20 | -7.84 | -6.80 | -4.80 | -1.55 | -1.65 | 0.65 | 2.40 |
| | DAFT- STSB-B | 0.66 | 1.57 | 2.37 | 4.01 | 4.51 | 4.13 | 4.64 | 5.13 |
| | DAFT- MRPC-X | -9.22 | -7.87 | -6.84 | -6.14 | -3.63 | -1.46 | -0.43 | 0.56 |
| | DAFT- STSB-X | -0.78 | -1.05 | -0.91 | 0.79 | 0.83 | 3.16 | 5.50 | 5.07 |
| | Average | -2.85 | -2.64 | -0.46 | -0.06 | 2.01 | 2.41 | 4.42 | 5.28 |
| STSB | DAFT- MRPC-R | -6.23 | -3.43 | -3.72 | -2.61 | -4.53 | -0.39 | 2.68 | 4.96 |
| | DAFT- QQP-R | -3.11 | -4.82 | 0.99 | 5.03 | 2.13 | 6.25 | 6.32 | 6.32 |
| | DAFT- MRPC-B | -8.79 | -11.31 | -7.32 | -5.35 | -5.32 | -2.93 | -2.15 | 0.91 |
| | DAFT- QQP-B | -0.07 | -0.12 | 0.66 | 1.58 | 3.02 | 3.77 | 3.26 | 5.21 |
| | DAFT- MRPC-X | -10.16 | -12.10 | -13.01 | -9.41 | -7.63 | -5.03 | -4.20 | 0.36 |
| | DAFT- QQP-X | -3.39 | -2.82 | -2.04 | -0.56 | 0.50 | 1.73 | 1.78 | 3.51 |
| | Average | -5.29 | -5.77 | -4.07 | -1.89 | -1.97 | 0.57 | 1.28 | 3.55 |

Table 13: Relative Improvement of DA(FT)$^2$ compared to DAFT-E- RF (Text Similarity). The R, B, X at the end of the DAFT names denote the base model of the DAFT models, and they denote: Roberta, Bert, Xlnet base models respectively.

| Dataset | DAFT Name | $n = 2$ | $n = 4$ | $n = 8$ | $n = 16$ | $n = 32$ | $n = 64$ | $n = 128$ | $n = 256$ |
|---------|-----------|---------|---------|---------|----------|----------|----------|-----------|-----------|
| MRPC | DAFT- QQP-R | 12.91 | -2.02 | -10.60 | -14.67 | -11.38 | -7.66 | -3.32 | -0.07 |
| | DAFT- STSB-R | 30.55 | 14.37 | 9.56 | 3.12 | 0.40 | 3.67 | 3.04 | 6.58 |
| | DAFT- QQP-B | 14.31 | -0.56 | -5.49 | -10.21 | -11.73 | -9.32 | -9.59 | -1.99 |
| | DAFT- STSB | 29.24 | 12.54 | 7.81 | 2.65 | -1.94 | -0.11 | -0.70 | 1.29 |
| | DAFT- QQP-X | 12.05 | -3.98 | -8.03 | -11.09 | -11.86 | -9.25 | -7.21 | -4.38 |
| | DAFT- STSB-X | 29.20 | 13.26 | 8.15 | 3.67 | 0.05 | 1.66 | 1.17 | 4.91 |
| | Average | 28.02 | 10.39 | 4.53 | -0.85 | -3.05 | -4.96 | -7.17 | -6.78 |
| QQP | DAFT- MRPC-R | 5.92 | 2.20 | 2.44 | -0.88 | -1.49 | -3.20 | 1.52 | 3.59 |
| | DAFT- STSB-R | 9.35 | 3.64 | 8.08 | 4.95 | 5.29 | 3.29 | 4.17 | 6.23 |
| | DAFT- MRPC-B | -1.42 | -4.85 | -6.29 | -5.59 | -5.32 | -6.42 | -4.21 | -1.69 |
| | DAFT- STSB-B | 8.10 | 4.86 | 2.92 | 3.15 | 0.50 | -0.91 | -0.42 | 0.93 |
| | DAFT- MRPC-X | -2.51 | -4.88 | -6.34 | -6.92 | -7.32 | -6.24 | -5.25 | -3.46 |
| | DAFT- STSB-X | 6.56 | 2.16 | -0.38 | -0.04 | -3.03 | -1.84 | 0.40 | 0.88 |
| | Average | 7.39 | 3.24 | 0.54 | -0.83 | -3.83 | -4.85 | -4.83 | -3.99 |
| STSB | DAFT- MRPC-R | 11.08 | 5.44 | -4.39 | -5.82 | -8.44 | -6.09 | -2.41 | -0.63 |
| | DAFT- QQP-R | 14.77 | 3.92 | 0.29 | 1.56 | -2.06 | 0.18 | 1.05 | 0.66 |
| | DAFT- MRPC-B | 8.05 | -3.17 | -7.96 | -8.48 | -9.20 | -8.49 | -7.00 | -4.47 |
| | DAFT- QQP-B | 18.38 | 9.05 | -0.04 | -1.78 | -1.21 | -2.17 | -1.86 | -0.39 |
| | DAFT- MRPC-X | 6.42 | -4.03 | -13.61 | -12.40 | -11.42 | -10.46 | -8.94 | -4.99 |
| | DAFT- QQP-X | 14.44 | 6.10 | -2.72 | -3.85 | -3.62 | -4.09 | -3.26 | -2.00 |
| | Average | 18.46 | 9.18 | -0.69 | -3.30 | -4.10 | -5.72 | -4.95 | -5.33 |