What Drives LLM Self-Reflection?
A Controlled Ablation of Uncertainty Routing in Armed Conflict Forecasting

Abstract

Self-reflection is widely assumed to improve LLM reasoning, yet which component drives the gain remains poorly understood. We present a controlled six-condition ablation isolating four components of LLM self-reflection: evidence exposure, diagnostic scaffolding, taxonomy vocabulary, and action routing. Two precise null results converge on a single mechanism. First, structured diagnostic questions add no measurable value over unstructured reflection (F1 = 0.296 vs 0.297, $p = 1.000$, 95% CI $[-0.041, +0.040]$). Second, presenting the full uncertainty taxonomy while collapsing the action space to a single generic action also adds no value (ΔF1 = +0.008, overlapping 95% CIs), ruling out taxonomy vocabulary as the mechanism. Typed action routing provides consistent directional gains (F1 = 0.379 vs 0.296); the conservative estimate controlling for taxonomy vocabulary is ΔF1 = +0.075, and the overall gain over the single-shot baseline is significant by bootstrap CI (ΔF1 = +0.101, 95% CI $[+0.020, +0.185]$). The vocabulary-routing decomposition replicates on GPT-4o: taxonomy vocabulary adds no significant value over generic reflection ($p = 0.773$), while action routing provides significant gains ($p = 0.025$), confirming the mechanism holds across backbones. Gains concentrate on structurally novel conflicts: in Myanmar (F1 : 0.000 $\rightarrow$ 0.353) and Ukraine (0.167 $\rightarrow$ 0.500), the vocabulary-only condition recovers no more than generic reflection while action routing breaks the degenerate prior. These findings identify typed action routing — not diagnostic scaffolding or taxonomy vocabulary — as a promising design principle for metacognitive LLM forecasting agents, while motivating larger-scale evaluation across conflict typologies.

1 Introduction

When a large language model is uncertain about a forecast, the intuitive remedy is to ask it to reflect. Self-reflection has emerged as a central design pattern in agentic LLM systems (Yao et al., 2023b; Shinn et al., 2023; Renze and Guven, 2024), and its benefits are well-documented across reasoning, planning, and dialogue tasks. We ask a more precise question: *which component of self-reflection actually drives the gain?*

We decompose LLM self-reflection into four components through a controlled six-condition ablation: evidence exposure, diagnostic scaffolding, taxonomy vocabulary, and action routing. Our results reveal a surprising answer. Diagnostic questions add no value over unstructured reflection (F1 = 0.296 vs 0.297, $p = 1.000$). Taxonomy vocabulary alone adds no value either: a monitor that presents the full seven-type taxonomy but routes every diagnosed type to a single fixed action achieves F1 = 0.304, indistinguishable from generic reflection (ΔF1 = +0.008). Typed action routing lifts performance to F1 = 0.379, with a conservative effect size of ΔF1 = +0.075 against the vocabulary-matched control. Neither the diagnostic scaffold nor the taxonomy vocabulary is the mechanism. The routing is.

We evaluate on 310 real-world armed conflict forecasting cases across five countries, using two LLM backbones. The gains concentrate on structurally novel conflicts: in Myanmar, where the single-shot baseline scores F1 = 0.000, the typed monitor recovers to F1 = 0.353 while the vocabulary-only condition reaches only 0.162, isolating the gain to action routing; in Ukraine, F1 improves from 0.167 to 0.500. Results replicate directionally across both backbones (Llama-3.3-70B and GPT-4o), with mixed transfer to 12 held-out countries.

Our contributions are: (1) a seven-type action-prescriptive uncertainty taxonomy with a deterministic control policy π_{control}; (2) the first six-condition ablation isolating each component of LLM self-reflection with a vocabulary-matched

control that holds the action space constant; and (3) the finding that neither diagnostic scaffolding ($p = 1.000$) nor taxonomy vocabulary ($\Delta F1 = +0.008$) drives self-reflection gains — only typed action routing does ($\Delta F1 = +0.075$ against the vocabulary-matched control).

2   Related Work

LLM self-reflection and reasoning agents. Chain-of-thought (Wei et al., 2022) and self-consistency (Wang et al., 2023) established that intermediate reasoning improves LLM task performance. Tree-of-Thought (Yao et al., 2023a) structures the reasoning space through deliberate search, and metacognitive prompting (Wang and Zhao, 2024) encourages models to monitor their own reasoning — but neither specifies how uncertainty *type* should govern downstream action selection. ReAct (Yao et al., 2023b) interleaves reasoning with external actions, Reflexion (Shinn et al., 2023) adds verbal self-critique stored in episodic memory, and ReflAct (Renze and Guven, 2024) integrates reflection within individual reasoning steps. These frameworks leave unanswered which component drives the gain. We show empirically that neither diagnostic scaffolding ($p = 1.000$) nor taxonomy vocabulary ($\Delta F1 = +0.008$) is the mechanism; what matters is whether different epistemic states route to different corrective actions. This addresses the Degeneration-of-Thought problem (Liang et al., 2024), where unconstrained self-reflection cannot break an incorrect commitment.

Uncertainty quantification in LLMs. Standard uncertainty estimation (Hüllermeier and Waegeman, 2021) classifies uncertainty without specifying how to act on it; recent work documents systematic miscalibration (Xiong et al., 2024) and degraded self-assessment under distribution shift (Kadavath et al., 2022). Semantic uncertainty (Kuhn et al., 2023), conformal prediction (Angelopoulos et al., 2023), and post-hoc calibration (Platt, 1999; Guo et al., 2017) operate on model outputs rather than evidence quality. Our typed monitor addresses *evidence-level* uncertainty before any prediction is made.

Conflict forecasting with LLMs. Random forests outperform logistic regression for civil war onset (Muchlinski et al., 2016), and ensemble methods improve predictive power (Pinckney and Rezaee, 2021). Recent LLM applications include actor embeddings for nowcasting (Croicu and von der Maase, 2024) and human rights violation detection in social media (Nemkova et al., 2023); a direct comparison of parametric vs. retrieval-augmented forecasting shows neither alone is sufficient (Nemkova et al., 2025), motivating an explicit evidence-quality monitoring layer. Our work operationalizes this as a typed control policy (Nelson and Narens, 1990), isolating routing as the mechanism through controlled ablation.

3   Typed Uncertainty Diagnosis

3.1   The Core Problem: Routing, Not Scaffolding

Standard self-reflection prompts a model to assess its own uncertainty and revise its forecast, but provides no structure for *how to respond* to what it finds. A model that diagnoses sparse evidence and a model that diagnoses conflicting sources receive the same generic instruction: reflect and revise. This uniformity is the failure mode.

Our ablation isolates where self-reflection fails. A monitor with five structured diagnostic questions (Q1–Q5) performs identically to one with no questions at all (F1 = 0.296 vs 0.297, $p = 1.000$). Nor is the taxonomy vocabulary the mechanism: a monitor that presents the full seven-type taxonomy but routes every diagnosed type to the same fixed action achieves F1 = 0.304, indistinguishable from generic reflection ($\Delta F1 = +0.008$). What matters is whether the diagnosed epistemic state *routes* to a different corrective action: random routing already outperforms generic reflection (F1 = 0.338); typed routing adds further value (F1 = 0.379). The routing is the mechanism.

The control policy is not a prompt template selector; it is a typed dispatch mechanism whose contribution is isolated by holding prompt complexity constant across conditions D and C.

3.2   The Seven-Type Uncertainty Taxonomy

The taxonomy (Table 1) covers the primary epistemic failure modes in evidence-based forecasting. Each type pairs a diagnostic criterion with a targeted remediation action via a deterministic control policy $\pi_{\text{control}} : \mathcal{U} \to \mathcal{A}$.

The taxonomy is *action-prescriptive* rather than merely descriptive: unlike the standard epistemic/aleatoric distinction (Hüllermeier and Waegeman, 2021), which classifies uncertainty without specifying how to act on it, each type is grounded

Uncertainty Type	Action	Mechanism
INSUFFICIENT_EVIDENCE	Request sources	Broaden evidence search
CONFLICTING_SOURCES	Comparative reasoning	Source-by-source comparison
DISTRIBUTION_SHIFT	Context recalibration	Region-aware baseline adjustment
LOW_QUALITY_DATA	Reweight sources	Discount low-reliability signals
TEMPORAL_INCONSISTENCY	Recency prioritization	Emphasize most recent evidence
MODEL_AMBIGUITY	Sample alternatives	Explore alternative forecast paths
CONFIDENT	Exit	No further deliberation needed

Table 1: The seven-type uncertainty taxonomy and deterministic control policy π_{control}. An eighth type, UNKNOWN_UNCERTAINTY, routes to comparative reasoning as a broad fallback for unclassifiable cases.

in what a reasoning agent should do differently. The distinction between CONFLICTING_SOURCES and MODEL_AMBIGUITY, for example, is operationally important — the former warrants source adjudication, the latter exploration of alternative forecast paths — and DISTRIBUTION_SHIFT warrants context recalibration rather than additional evidence retrieval that would not help if the evidence itself is the source of the anomaly.

3.3 Monitor and Control

Given the current forecast (prediction, confidence, key evidence) plus the structured evidence bundle (ACLED conflict statistics, socioeconomic indicators, ML ensemble scores, source quality assessments), the monitor poses a five-question diagnostic protocol covering evidence volume, recency, ML agreement, counter-argument, and weakness check (full prompts in Appendix 7). After answering, the monitor traverses an ordered decision tree to assign exactly one uncertainty type, with conditions checked sequentially to prevent defaulting to high-entropy categories. Our ablation shows the questions do not themselves drive performance (Condition E matches Condition B exactly); their role is to surface evidence for type assignment.

The control policy π_{control} then deterministically maps the diagnosed type to a remediation action. The mapping is fixed rather than learned: a learned policy would conflate the diagnostic contribution of the taxonomy with the policy's contribution, making it impossible to isolate the value of typed routing. Two complementary control conditions provide the counterfactuals that make this isolation possible: Condition D (random taxonomy) holds

the routing machinery constant but assigns the type at random; Condition F (vocabulary-only) holds the taxonomy vocabulary constant but collapses the action space to a single generic action. The gap between D and C quantifies type specificity; the gap between F and C, with the taxonomy held constant, gives the conservative estimate of typed routing's contribution.

3.4 Ablation Design

We design six conditions to isolate each component:

- **A — Baseline:** Single-shot forecast, no monitor.

- **E — No-questions:** Monitor without Q1–Q5; reflects freely and assigns a type without structured evidence engagement.

- **B — Generic reflection:** Monitor with Q1–Q5 but no typed routing; action space is binary (`exit` or `comparative_reasoning`).

- **F — Vocabulary-only:** Monitor with Q1–Q5 and the full taxonomy; the model assigns a type from evidence, but every non-CONFIDENT diagnosis routes to the same fixed action (`comparative_reasoning`), matching B's action space. F isolates taxonomy vocabulary alone.

- **D — Random taxonomy:** Monitor with Q1–Q5 and typed routing, but the type is drawn uniformly at random from the six substantive types.

- **C — Typed monitor:** Full system; the monitor assigns a typed category and π_{control} deterministically selects the action.

The chain $A \to E \to B \to F \to D \to C$ isolates each component incrementally. E vs B isolates diagnostic questions; F vs B isolates taxonomy vocabulary; D vs F isolates routing structure; C vs D isolates type specificity. Each adjacent pair differs by exactly one architectural change.

4 Experimental Setup

4.1 Task and Data

We evaluate on binary armed conflict escalation forecasting: given a 60-day observation window of structured conflict evidence, predict whether fatalities will exceed 130% of the two-week baseline in the following 14 days. Ground truth is derived from ACLED (Raleigh et al., 2010).

Primary evaluation set. The primary test set covers Sudan, Ethiopia, Somalia, Myanmar, and Ukraine — selected for geographic and structural diversity (interstate war, post-coup civil war, protracted insurgency, multi-actor fragmented conflict, and high-intensity civil war respectively). A per-country temporal split assigns the earliest 60% of cases to training and the most recent 40% to testing, yielding 310 test cases (62 per country) covering late 2023 to early 2026, with an overall escalation rate of 21.0%.

Generalization set. A held-out probe covers 12 unseen countries across four regions (DRC; Belarus, Poland; Israel, Palestine, Lebanon, Iran, Yemen, Syria; Colombia, Haiti, Mexico), with 300 cases (25 per country) and identical labeling thresholds. No system modifications were made based on these results — this is a pure transfer test.

Difficulty tiers. Each test case is assigned to one of three tiers based on observable case properties, independent of any model's predictions: *catchable* (momentum > 0.90); *hard borderline* (observation ratio ≤ 1.40); *hard deceptive* (misleading momentum dip near the prediction window). The primary test set contains 29, 165, and 116 cases respectively.

Evidence bundle. Each case receives a structured bundle of ACLED conflict statistics, socioeconomic indicators, ML ensemble scores (XGBoost and Random Forest with inter-model disagreement), and LDA-derived topic signals. All six conditions receive identical bundles, ensuring performance differences reflect reasoning structure rather than information asymmetry.

4.2 Conditions and Evaluation Protocol

The six ablation conditions (A, E, B, F, D, C) are defined formally in Section 3. Maximum iterations is set to 1 for all monitor conditions (B, C, D, E, F), isolating the contribution of diagnostic structure from loop depth.

Backbones. All primary experiments use Llama-3.3-70B (Dubey et al., 2024) served via the Groq inference API at $T = 0.2$. GPT-4o (OpenAI, 2024) is evaluated as a secondary backbone on all conditions except E (no-questions), with Conditions B, F, and D run as single-run replications to validate the vocabulary-routing decomposition across backbones.

Multi-run protocol. The Llama primary evaluation runs each condition three times independently and aggregates via majority vote for binary predictions and mean confidence for probabilistic estimates. GPT-4o and generalization conditions use single runs.

Metrics. The primary metric is majority-vote F1, appropriate given the class imbalance (21.0% positive rate). Brier score is reported as a secondary descriptive metric only, computed via 5-fold cross-validated Platt scaling on raw confidence post-hoc; it is not used for condition selection or ranking.[1] Statistical significance is assessed via McNemar's test (McNemar, 1947) on binary predictions (primary) and Wilcoxon signed-rank test (Wilcoxon, 1945) on per-case Brier differences (secondary), both at $\alpha = 0.05$.

5 Results

5.1 Main Ablation (Llama-3.3-70B)

Table 2 reports overall escalation forecasting performance across all six conditions on the primary 5-country test set ($n = 310$, positive rate $= 21.0\%$), aggregated over three independent runs via majority vote. Bootstrap 95% confidence intervals are computed over 2,000 stratified resamples.

Finding 1: Diagnostic questions add no value over unstructured reflection. The no-questions monitor (E) scores F1 $= 0.297$, indistinguishable from generic reflection with Q1–Q5 scaffolding

---

[1] Condition F's calibrated Brier was computed via a standalone replication of the same pipeline (LogisticRegression(C=1.0), StratifiedKFold(n_splits=5, random_state=42)), reproducing Condition C's value to within rounding.

Condition	F1	95% CI	Rec.	Brier
A — Baseline	0.278	[0.200, 0.353]	0.385	0.166
E — No-Questions	0.297	[0.233, 0.359]	0.508	0.165
B — Generic Reflect	0.296	[0.232, 0.359]	0.508	0.166
F — Vocab-Only	0.304	[0.221, 0.383]	0.508	0.166
D — Random Taxonomy	0.338	[0.272, 0.400]	0.585	0.166
C — Typed Monitor	**0.379**	**[0.322, 0.436]**	**0.677**	**0.166**

Table 2: Escalation forecasting performance ($n = 310$, Llama-3.3-70B, 3-run majority vote). 95% CIs from 2,000 stratified bootstrap resamples. Brier computed via 5-fold cross-validated Platt scaling. All conditions produce near-identical Brier scores after calibration. Condition F holds the action space constant at B's substantive action while presenting the full taxonomy, isolating the contribution of taxonomy vocabulary.

(B) at F1 = 0.296 (McNemar $p = 1.000$, E right/B wrong = 22, B right/E wrong = 21). The null result is highly stable: bootstrap 95% CI for ΔF1 is $[-0.041, +0.040]$, centered precisely on zero. Structured diagnostic questions do not drive self-reflection gains in this setting.

Finding 2: Taxonomy vocabulary, by itself, also adds no value. The vocabulary-only condition (F) presents the full seven-type taxonomy to the LLM during diagnosis but routes every non-CONFIDENT type to the same fixed action as Condition B. F achieves F1 = 0.304, with three-run F1 stability (per-run F1 = 0.282, 0.291, 0.305; std = 0.009). The gap from generic reflection is ΔF1 = $+0.008$ vs B, with bootstrap 95% CIs overlapping heavily; F and B are statistically indistinguishable. This rules out an obvious confound in the original ablation: that typed routing's advantage stems from the taxonomy vocabulary itself priming the LLM to operate inside a structured epistemic framework. The taxonomy presentation is not the mechanism. Notably, the uncertainty type distribution in F is qualitatively similar to that in Condition C (dominated by MODEL_AMBIGUITY and CONFLICTING_SOURCES diagnoses), indicating that the LLM does engage with the taxonomy during diagnosis — but that engagement does not translate into improved discrimination when the diagnosed type cannot route to a differentiated action.

Finding 3: Typed action routing provides directional gains. Random taxonomy routing (D) outperforms generic reflection (B) by ΔF1 = $+0.042$ (F1 = 0.338 vs 0.296, 95% CI $[-0.036, +0.115]$), and typed routing (C) adds a further ΔF1 = $+0.041$ over random routing (F1 = 0.379 vs 0.338, 95% CI $[-0.027, +0.116]$). The conservative es-

timate of typed routing's contribution, controlling for taxonomy vocabulary via Condition F, is ΔF1 = $+0.075$ (C vs F). All three pairwise comparisons are directional but do not reach statistical significance at $\alpha = 0.05$ (McNemar $p = 0.497$ for D vs B, $p = 0.714$ for D vs C), reflecting modest effect sizes relative to the available positive cases ($n = 65$; post-hoc power for D vs C: 7.4%). These results should be interpreted as suggestive evidence for typed routing rather than definitive confirmation. The overall gain of typed routing over the single-shot baseline is significant by bootstrap CI (ΔF1 = $+0.101$, 95% CI $[+0.020, +0.185]$, though not individually by McNemar at $p = 0.202$). The typed monitor improves recall substantially ($0.385 \to 0.677$), correctly identifying escalation cases that all other conditions miss — including those where Condition F's identical taxonomy engagement produces no recall gain over B ($0.508 \to 0.508$).

5.2 Country-Level Analysis

Table 3 breaks down F1 by country across all six conditions. The chain ordering A $\to$ E $\to$ B $\to$ F $\to$ D $\to$ C holds on Myanmar and Ukraine, the two structurally novel contexts where typed routing provides the largest gains.

The two signature cases are Myanmar (ΔF1 = $+0.353$ over baseline) and Ukraine (ΔF1 = $+0.333$). In Myanmar, all three runs of Condition A score F1 = 0.000, consistent with LLM parametric knowledge interfering with evidence-based reasoning in a rapidly evolving post-coup conflict context. The typed monitor diagnoses DISTRIBUTION_SHIFT and triggers context recalibration, recovering F1 to 0.353. Critically, Condition F (which presents the same taxonomy to the model

Country	A	E	B	F	D	C	ΔC-A
Ethiopia	0.148	0.148	0.148	0.148	0.167	0.167	+0.019
Myanmar	0.000	0.150	0.154	0.162	0.316	**0.353**	+0.353
Somalia	0.427	0.430	0.467	0.430	0.394	0.475	+0.048
Sudan	0.233	0.357	0.347	0.370	0.333	0.373	+0.141
Ukraine	0.167	0.100	0.091	0.100	0.432	**0.500**	+0.333

Table 3: F1 by country (majority vote). Myanmar and Ukraine show the largest gains from typed routing, and Condition F demonstrates that this gain is not driven by taxonomy vocabulary alone: F sits within 0.01 of B in both signature countries. Sudan is the one country where taxonomy vocabulary contributes beyond generic reflection. Ethiopia and Somalia are flat across all conditions.

but routes every diagnosis to a generic action) recovers only to F1 = 0.162 — essentially identical to generic reflection (B = 0.154). The F → D step in Myanmar is particularly informative: introducing any structured routing variation, even random, doubles F1 (0.162 → 0.316). In Ukraine, the same pattern holds with even larger effect sizes: F sits at F1 = 0.100, indistinguishable from B (0.091), while D jumps to 0.432 and C reaches 0.500. The typed monitor in Ukraine diagnoses primarily CON-FLICTING_SOURCES and MODEL_AMBIGUITY, triggering comparative reasoning that adjudicates between ML ensemble signals and qualitative evidence. In both signature countries, the mechanism behind the recovery is action routing, not taxonomy vocabulary.

Sudan presents a different pattern. Here F (F1 = 0.370) is essentially indistinguishable from both D (0.333) and C (0.373), and slightly above B (0.347). Sudan is also the country with the strongest non-trivial baseline (A = 0.233), suggesting that when the LLM's parametric prior is already well-calibrated, taxonomy vocabulary may contribute marginal value beyond generic reflection — but typed routing adds little further. This is consistent with the broader pattern: typed routing's advantage is largest where the baseline is most degenerate.

Ethiopia is the one country where performance is flat across all six conditions (F1 = 0.148–0.167), suggesting that multi-actor fragmented conflict provides insufficient epistemic signal for any typing approach to succeed. Somalia is also broadly flat, with conditions ranging from 0.394 to 0.475 without a clear chain ordering.

5.3 Difficulty Tier Analysis

The typed monitor's largest gain is on catchable cases (F1 = 0.926 vs 0.682 for baseline, +0.244). These cases have clear momentum signals — the typed monitor correctly diagnoses CONFIDENT and exits without unnecessary reflection. The no-questions monitor (E) and generic reflection (B) already achieve 0.792 and 0.816 respectively, confirming that any monitoring structure helps on easy cases; typed routing pushes further to 0.926.

On hard borderline cases ($n = 165$), random taxonomy (D) scores 0.222, outperforming typed routing (0.195). This is the one tier where random routing beats typed routing, consistent with genuinely ambiguous evidence providing insufficient signal for specific type assignment to add value over generic routing.

On hard deceptive cases ($n = 116$), the typed monitor achieves the highest F1 (0.255 vs 0.179 for baseline, +0.076), suggesting that DISTRIBUTION_SHIFT and TEMPORAL_INCONSISTENCY diagnoses correctly identify the misleading momentum pattern.

5.4 Cross-Backbone Replication (GPT-4o)

The GPT-4o baseline is near-degenerate (F1 = 0.028), predicting no-escalation on almost all 310 cases, consistent with stronger parametric knowledge suppressing evidence-based reasoning in the single-shot setting. The key finding is that the ablation chain ordering replicates across backbones: generic reflection (B, F1 = 0.272) and vocabulary-only (F, F1 = 0.304) are statistically indistinguishable (McNemar $p = 0.773$), while action routing (D, F1 = 0.345) significantly outperforms generic reflection ($p = 0.025$) and vocabulary-only ($p = 0.018$). The vocabulary-routing decomposition — the central mechanism claim of this paper

Tier	n	A	E	B	D	C
Catchable	29	0.682	0.792	0.816	0.792	**0.926**
Hard borderline	165	0.125	0.128	0.088	0.222	0.195
Hard deceptive	116	0.179	0.200	0.217	0.203	**0.255**

Table 4: F1 by difficulty tier. Typed routing (C) achieves the highest F1 on catchable and hard deceptive cases. On hard borderline cases, random taxonomy (D) outperforms typed routing, suggesting the taxonomy over-specifies on genuinely ambiguous evidence. Condition F is omitted from this breakdown; tier-level F1s with $n \leq 30$ positive cases are unstable across conditions and we report the main tier comparisons against the four published conditions.

Cond.	F1	ΔF1	Rec.	McNemar p
A — Base.	0.028	—	0.015	—
B — Gen.	0.272	+0.244	0.354	—
F — Vocab.	0.304	+0.276	0.400	0.773[†]
D — Random	**0.345**	+0.317	0.600	0.025[†]
C — Typed	0.328	+0.300	—	<0.001[‡]

Table 5: GPT-4o cross-backbone results (single run, $n = 310$). McNemar p marked † are vs. B; ‡ is vs. A. The chain ordering B $\approx$ F < D replicates across backbones: taxonomy vocabulary adds no significant value over generic reflection ($p = 0.773$), while action routing provides significant gains ($p = 0.025$). Condition C recall not available for this run.

— thus holds on both Llama-3.3-70B and GPT-4o.

The typed monitor (C, F1 = 0.328) sits between D and B on GPT-4o, consistent with the primary evaluation pattern where type-action alignment adds directional but modest gains over random routing. Country-level results partially replicate the primary pattern: Myanmar recovers from F1 = 0.000 under generic reflection to 0.242 under random routing, confirming that action differentiation — not taxonomy vocabulary — breaks the degenerate prior. Somalia ($0.432 \rightarrow 0.560$) and Ethiopia show gains under routing; Ukraine and Sudan are noisier but maintain the B $\approx$ F ordering.

5.5 Generalization to Unseen Countries

The generalization results characterize the boundary conditions of typed routing rather than undermining its primary mechanism. Neither generic reflection (B, F1 = 0.290) nor the typed monitor (C, F1 = 0.280) significantly outperforms the single-shot baseline (0.260) on 12 unseen countries, and generic reflection outperforms the typed monitor in overall F1 — reversing the primary evaluation result. This reversal is itself informative: typed routing is taxonomy-sensitive. When conflict dynamics diverge sufficiently from the five training

contexts, the fixed action mappings in π_{control} do not consistently outperform a generic fallback.

Five of twelve countries (Belarus, DRC, Israel, Mexico, Poland) score F1 = 0.000 across all conditions, reflecting near-zero positive rates where no system can reliably detect rare events — a floor effect independent of routing structure. On the seven active-conflict countries with positive cases, the typed monitor wins on more individual cases than generic reflection (McNemar B vs C: $p = 0.012$, C right/B wrong = 26 vs B right/C wrong = 10), with gains on Iran ($+0.027$), Palestine ($+0.027$), and Yemen ($+0.010$). Generic reflection wins on Colombia ($+0.054$) and Haiti ($+0.090$).

These results identify a clear design implication: the current taxonomy and control policy are calibrated to a specific conflict typology. The primary gains — action differentiation breaking degenerate priors in structurally novel contexts — do not automatically transfer when the routing assumptions themselves are out of distribution. Adapting the taxonomy to broader conflict typologies, or learning routing policies that degrade more gracefully under distribution shift, are the natural next steps.

6 Analysis

6.1 Why Scaffolding and Vocabulary Don't Matter

The no-questions monitor (E) and generic reflection (B) produce identical performance (F1 = 0.297 vs 0.296, $p = 1.000$). Both lower confidence from the baseline indiscriminately — the reduction on true positives is nearly identical to that on true negatives, hedging regardless of what was diagnosed. Without typed routing, diagnostic reasoning has nowhere to go.

The vocabulary-only condition (F) sharpens this account. F presents the full seven-type taxonomy to the LLM but routes every non-CONFIDENT type to the same fixed action as B, achieving

F1 = 0.304 with tight three-run stability (std = 0.009). The uncertainty type distribution in F is qualitatively similar to Condition C — dominated by MODEL_AMBIGUITY and CONFLICTING_SOURCES — showing the LLM genuinely engages with the taxonomy. That engagement does not translate into improved discrimination when the diagnosed type cannot route to a differentiated action. Naming the epistemic states is not sufficient; what matters is that different states produce different downstream behavior.

The chain $B \approx F < D < C$ decomposes self-reflection gains into three components: vocabulary ($B \rightarrow F$, $\Delta F1 = +0.008$), action variation regardless of correctness ($F \rightarrow D$, $\Delta F1 = +0.034$), and type-action alignment ($D \rightarrow C$, $\Delta F1 = +0.041$). The vocabulary contributes essentially nothing; the remaining gain comes from forcing the model to commit to different actions for different diagnosed states, and to the *right* action for each state.

6.2 Why Typed Routing Helps

Random taxonomy routing (D) outperforms generic reflection by $\Delta F1 = +0.042$ despite random type assignment, confirming that routing structure itself provides value: forcing commitment to a specific action improves discrimination over a binary `exit/comparative_reasoning` choice. Typed routing (C) adds $+0.041$ over random routing and $+0.075$ over the vocabulary-only condition F — the conservative estimate of typed routing's contribution after controlling for the taxonomy's presence in the prompt. The typed monitor lowers confidence by only -0.055 overall and does so selectively: on true positives, C reduces confidence by -0.043, compared to -0.232 for B. Typed routing preserves confidence on cases that deserve it.

6.3 The Myanmar and Ukraine Signature Cases

In Myanmar ($F1_A = 0.000$, $F1_B = 0.154$, $F1_F = 0.162$, $F1_D = 0.316$, $F1_C = 0.353$), the typed monitor diagnoses 75.8% of cases as MODEL_AMBIGUITY — the same dominant type seen across all countries — so the gain does not trace to an exotic diagnosis. Two intermediate conditions clarify the mechanism. The vocabulary-only condition F sits within 0.01 of generic reflection despite the LLM seeing the full taxonomy and producing the same type distribution as in C: naming the epistemic state does not break the degenerate no-escalation prior. Random taxonomy routing

(D), by contrast, recovers most of C's gain by simply routing different cases to different actions, regardless of whether the assignment is correct. The mechanism in Myanmar is action variation, not diagnosis specificity.

Ukraine shows the same pattern with sharper effect sizes: $F1_B = 0.091$, $F1_F = 0.100$, $F1_D = 0.432$, $F1_C = 0.500$. Unstructured reflection (B and F) increases hedging and suppresses true positives; typed routing to `comparative_reasoning` forces adjudication between ML ensemble signals and qualitative evidence, recovering F1 to 0.500. In both signature countries, the mechanism behind the recovery is routing commitment, not diagnosis specificity.

6.4 Efficiency and Calibration

The typed monitor achieves its gains at $3\times$ the API cost of the single-shot baseline (6 LLM calls vs. 2); the vocabulary-only condition F incurs identical cost without the discrimination advantage, making typed routing the dominant choice on both performance and per-dollar efficiency. Post-hoc Platt scaling produces near-identical Brier scores across all six conditions (0.165–0.166), confirming that typed routing improves binary discrimination but not probability calibration — these appear to be separable objectives.

7 Conclusion

We decomposed LLM self-reflection into four components and isolated the performance driver: neither diagnostic scaffolding (E vs B, $p = 1.000$) nor taxonomy vocabulary (F vs B, $\Delta F1 = +0.008$) adds value, while typed action routing improves F1 (0.379 vs 0.296), especially on structurally novel conflicts—Myanmar ($+0.353$) and Ukraine ($+0.333$). A vocabulary-matched control isolates routing's contribution ($\Delta F1 = +0.075$), ruling out taxonomy terms alone as the mechanism. Each prediction includes a named uncertainty type and traceable action, making the system more interpretable than static baselines.

The main limitation is remediation depth: typed routing identifies the uncertainty and action to take, but prompt-engineered actions cannot always resolve real-world evidence contradictions. Integrating routing with tool use—retrieval, database queries, and source adjudication—is the natural next step; the taxonomy and control policy already provide the scaffold.

Limitations

Single domain. All experiments are conducted on armed conflict forecasting. While this domain provides a rigorous testbed — heterogeneous evidence, genuine class imbalance, delayed ground truth, and real humanitarian stakes — we cannot claim the typed uncertainty taxonomy or the routing advantage generalizes to other evidence-based forecasting tasks without further validation. The dominant types (76.5% MODEL_AMBIGUITY, 16.8% CONFLICTING_SOURCES) may reflect properties of conflict evidence rather than universal epistemic structure.

Routing without resolution. The typed monitor identifies *what kind* of uncertainty the agent faces, but the actions available to resolve it are prompt-engineered reasoning strategies rather than genuine information retrieval or tool use. A case diagnosed as INSUFFICIENT_EVIDENCE receives a prompt instruction to reason more carefully from available data — it cannot actually retrieve additional sources. This architectural ceiling explains why performance on hard borderline cases remains modest (F1 = 0.195) despite correct diagnosis, and why the gains do not consistently transfer to the generalization set.

Statistical power. The primary test set contains 65 positive cases (21% of 310). While the E vs B and F vs B null results are unambiguous ($p = 1.000$ and overlapping bootstrap CIs respectively), the D vs C comparison ($p = 0.714$) and A vs C overall ($p = 0.202$) are not significant at the individual level. Larger evaluation sets would strengthen conclusions about the magnitude of typed routing gains, particularly for country-level results where per-country positive counts range from 8 (Myanmar) to 18 (Somalia).

Vocabulary-only control scope. Condition F was evaluated on the Llama-3.3-70B primary set (three runs, $n = 310$) but not on the GPT-4o cross-backbone replication or the generalization set, to keep compute focused on the primary ablation chain. The vocabulary-vs-routing decomposition therefore rests on the primary set; extending F to additional backbones and unseen countries is a natural direction for follow-up work.

Single-run supplementary conditions. GPT-4o and generalization conditions are evaluated on single runs. Conclusions from these conditions are directional rather than definitive, pending multi-run replication.

Taxonomy design choices. The seven-type taxonomy was designed with conflict forecasting in mind. The boundaries between types — particularly CONFLICTING_SOURCES vs. MODEL_AMBIGUITY, and DISTRIBUTION_SHIFT vs. TEMPORAL_INCONSISTENCY — involve judgment calls that a domain expert might draw differently for other applications. The taxonomy is a design artifact, not a discovered ontology.

Potential Risks. This work involves conflict forecasting. Predictions should not be used for operational decisions without human oversight. The system may fail on conflict zones outside its training distribution, as shown in our generalization results.

Acknowledgments

We used AI assistance (Claude, Anthropic) to proofread the writing and debug LaTeX code.

References

Anastasios N. Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, and Tal Schuster. 2023. Conformal risk control. In *International Conference on Learning Representations*.

Mihai Croicu and Hakon von der Maase. 2024. Combining transformer-based actor embeddings with gaussian processes for conflict forecasting. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 1321–1330.

Eyke Hüllermeier and Willem Waegeman. 2021. Aleatoric and epistemic uncertainty in machine learning: An introduction to concepts and methods. *Machine Learning*, 110(3):457–506.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, and 1 others. 2022. Language models (mostly) know what they know. In *NeurIPS 2022 Workshop on ML Safety*.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2023. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *International Conference on Learning Representations*.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Zhaopeng Tu, and Shuming Shi. 2024. Encouraging divergent thinking in large language models through multi-agent debate. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*.

Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157.

David Muchlinski, David Siroky, Jingrui He, and Matthew Kocher. 2016. Comparing random forest with logistic regression for predicting class-imbalanced civil war onset data. *Political Analysis*, 24(1):87–103.

Thomas O. Nelson and Louis Narens. 1990. Metamemory: A theoretical framework and new findings. *Psychology of Learning and Motivation*, 26:125–173.

Apollinaire Poli Nemkova, Sarath Chandra Lingareddy, Sagnik Ray Choudhury, and Mark V Albert. 2025. Do large language models know conflict? investigating parametric vs. non-parametric knowledge of llms for conflict forecasting. *arXiv preprint arXiv:2505.09852*.

Poli Nemkova, Solomon Ubani, Suleyman Olcay Polat, Nayeon Kim, and Rodney D. Nielsen. 2023. Detecting human rights violations on social media during the russia–ukraine war. *arXiv preprint arXiv:2306.05370*.

OpenAI. 2024. GPT-4 technical report. Technical report, OpenAI.

Jonathan Pinckney and Sheherezade Rezaee. 2021. Predicting the onset of armed conflict. *Journal of Conflict Resolution*, 65(10):1765–1793.

John C. Platt. 1999. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. In *Advances in Large Margin Classifiers*, pages 61–74. MIT Press.

Clionadh Raleigh, Andrew Linke, Håvard Hegre, and Joakim Karlsen. 2010. Introducing ACLED: An armed conflict location and event dataset. *Journal of Peace Research*, 47(5):651–660.

Matthew Renze and Erhan Guven. 2024. ReflAct: World-grounded decision making in LLM agents via goal-focused reflection. In *Findings of the Association for Computational Linguistics: ACL 2024*.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations*.

Yuqing Wang and Yun Zhao. 2024. Metacognitive prompting improves understanding in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1914–1926.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837.

Frank Wilcoxon. 1945. Individual comparisons by ranking methods. *Biometrics Bulletin*, 1(6):80–83.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. 2024. Can LLMs express their uncertainty? an empirical evaluation of confidence elicitation in LLMs. In *International Conference on Learning Representations*.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2023a. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023b. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*.