# One Model to Edit Them All: Free-Form Text-Driven Image Manipulation with Semantic Modulation

Figure 1: FFCLIP model manipulates each type of image with free-form text prompts. For each input image shown on the first column, our manipulated results with text prompts are shown on their corresponding row. Each text prompt, which is set to contain a single semantic meaning (e.g., 'Blue') during training, is able to convey multiple semantics (e.g., 'Black from sixties') during inference for free-form image manipulation.

## Abstract

The semantic guidance from a text prompt is convenient for representing user intentions during image manipulation. Recently, CLIP [24] facilitates text-driven manipulation methods by using text prompts to find and modify the latent subspace of StyleGAN [17] for cross-modality semantic modulation. We observe that semantic modulation is conducted empirically by the corresponding StyleGAN latent subspace to the text prompt embeddings. This empirical correspondence between StyleGAN latent subspace and explicit text embedding semantics can help them find the specific latent subspace but confines that each manipulation model can only train on one fixed text prompt. In this paper, we introduce a system called Free-Form CLIP (FFCLIP), aiming to build the cross-modality correspondence automatically for free-form text-driven image manipulation. We propose a semantic modulation method that consists of semantic alignment and semantic injection. Our semantic alignment utilizes a cross attention mechanism to establish visual-text correspondences, which effectively aligns the visual representations and semantics of text embeddings via linear transformations. Thus we can find the corresponding StyleGAN implicit latent subspace for each explicit text prompt. After alignment, we inject semantics from explicit text prompts to StyleGAN latent

space for cross-modality semantic modulation. For one type of image (e.g., 'human portrait'), FFCLIP can be learned with free-form text prompts. Meanwhile, we observe that although each text prompt utilized during training contains a single semantic meaning, FFCLIP is able to leverage text prompts with multiple semantic meanings for image manipulation. In the experiments, we evaluate FFCLIP on three types of images (i.e., 'human portraits', 'cars', and 'churches'). Both qualitative and quantitative results show that FFCLIP is effective in producing semantically accurate and visually realistic images.

## 1 Introduction

Neural image synthesis has received tremendous attention since the Generative Adversarial Networks (GANs) [11]. And the StyleGAN family [18, 17, 16] further advanced the image synthesis quality. Recently, researchers started to utilize text prompt embedding to edit StyleGAN latent space for semantic image manipulation [23, 43]. Text prompts are convenient for representing user intentions (i.e., target semantics). With a single word (e.g., 'Blue') as input, the corresponding image semantics can be edited by modulating the StyleGAN latent space.

The quality of text-driven image manipulation resides on how to effectively establish semantic correspondences between implicit StyleGAN latent subspace and explicit text prompt embeddings, so that we can find the suitable latent subspace. For example, when the text prompt is 'Surprise,' we need to identify the related 'Expression' in the latent subspace of StyleGAN. Then, we inject this text embedding to the identified latent subspace for semantic modulation. Pioneering studies like TediGAN [43] and StyleCLIP [23] leverage text prompt embeddings to modify StyleGAN latent subspace. Before modifications, they need to empirically identify which latent subspace corresponds to the target text prompt embedding (i.e., attribute-specific selection in TediGAN and group assignment in StyleCLIP). This empirical identification confines that given one text prompt, they need to train an individual model accordingly, highly limiting their scalability. To this end, we are motivated to explore how to automatically identify StyleGAN latent subspace based on multiple texts prompts at the same time. So a single model can cope with text prompts with different semantic guidance.

In this paper, we propose a free-form method (FFCLIP) to manipulate one image with multiple text prompts. FFCLIP consists of several semantic modulation blocks that take the latent code $w$ in StyleGAN latent space $\mathcal{W}^+$ [1] and a text embedding as inputs. In each block, there are one semantic alignment module and one semantic injection module. The semantic alignment module regards the text embedding as the query, the latent code $w$ as the key and the value. So the cross attention can be computed in both position and channel dimensions separately to formulate two attention maps. The computed cross attention helps us to build the correspondence between text embeddings and StyleGAN latent space. We set the position attention map as the scale parameters, and we reconstruct the value with the channel attention map to calculate a translation parameter. So our semantic alignment module aligns the semantics of the StyleGAN latent space to that of text prompt embeddings through this learnable linear transformations. Through this alignment, we identify each text prompt embedding to its corresponding StyleGAN latent subspace. Then, the semantic injection module modifies the subspace via another linear transformations following HairCLIP [41]. The modulated semantics are represented as the latent space offset $\Delta w$, which is refined progressive through several semantic modulation blocks.

From the perspective of FFCLIP, the empirical group selection of $w$ in [23, 41] is a special form of our scale parameters in the semantic alignment module. The group selection is a binary value to indicate the usage of each position dimension of $w$. On the other hand, the scale parameters in our semantic alignment module adaptively adjust the latent code $w$ to suit different text prompt embeddings. The alignment is further improved via our translation parameters. We observe that the $\mathcal{W}^+$ is not disentangled completely, and our semantic modulation is more suitable for image manipulation based on the latent space without disentanglement. We evaluate our method on the

benchmark datasets and compare FFCLIP to state-of-the-art methods. The results indicate that FFCLIP is superior in generating visually pleasant content and conveying user intentions.

## 2   Related Work

**Latent Space Image Manipulation.** The latent space in StyleGAN [18, 17, 16] has demonstrated great potential in representing the semantics in the image, motivating many works to disentangle the latent space for controllable image manipulation. Specifically, investigations [31, 14, 3, 36, 4] predict the meaningful offsets or directions in the latent space given image annotations as supervision, while studies [32, 38, 13, 39] disentangle the latent space in an unsupervised manner to find the semantic directions. Although these methods achieve great performance in latent space manipulation, they can only find limited semantic directions that confine user intentions. In contrast, we achieve free-form image manipulation conditioned on arbitrary text prompts, giving users more degrees of editing freedom. Our StyleGAN inversion encoder is related to GAN inversion methods [1, 2, 5, 6, 29, 37, 40] that maps the image to the latent code space $w \in \mathcal{W}^+$ [1]. In our work, we use the e4e [37] as StyleGAN inversion encoder following StyleCLIP [23].

**Text-driven Image Generations.** Starting from [27] that leverages text embeddings as the condition for GAN-based image training, several works [46, 47, 48] improve the synthesis quality by introducing multi-scale or hierarchically-nested GANs. And attention modules are introduced in [44] to match the generated images to text. [7, 22, 21, 35] improves image content fidelity is considered from the network structure and training perspectives. The text to image generation performance is further boosted in DALLE [26, 25] where text prompts with multiple semantic guidance are translated into images. Vision transformer [9] and diffusion model [12] also show impressive results in text-driven image manipulations. TediGAN [43] transfers the image and text to a shared StyleGAN latent space, and modulates the image latent vector with text. Recently, CLIP [24] constructs a text-image embedding space to connect the semantics between image and text embeddings. Combining the CLIP model with StyleGAN becomes promising for text-driven image manipulations. Pioneering works such as StyleCLIP [23] use the CLIP model to map semantics from text to images. HairCLIP [41] builds on top of StyleCLIP while focusing more on the hair regions with reference images and semantic injections. These methods need to manually select a specific StyleGAN latent subspace according to the target text. So they fail to train a single model for different text prompts. In comparison, FFCLIP can adaptively match one text embedding to the desired latent subspace, making one model process multiple text prompts for the corresponding image manipulations.

## 3   Method

Fig. 2 shows an overview of the proposed method. Given an input image and a text prompt, we can obtain the StyleGAN latent code $w$ and text embedding $e_t$. We propose $k$ (we set $k = 4$ in practice) semantic modulation blocks where each block first aligns semantics between $w$ and $e_t$ and then edits the latent subspace. The output of each block is an offset $\Delta w$ which adds to the latent code $w$. Finally, a StyleGAN generator decodes the resulting latent code to the manipulated image. In the following, we first briefly review the StyleGAN and the CLIP model, then we illustrate how we align and inject semantics for latent space editing.

**StyleGAN Revisiting.** Studies for StyleGAN [18, 17, 16] generate visually realistic face images with various semantics. In StyleGAN, a latent variable $\mathcal{Z} \in \mathbb{R}^{512}$ from the Gaussian distribution is gradually transformed to a disentangled latent code $\mathcal{W} \in \mathbb{R}^{512}$ with semantic meanings. The latent code $\mathcal{W}$ is then fed into 18 layers for image generation. Later, investigations [1, 28, 42] find that an extension of $\mathcal{W}$ (i.e., $\mathcal{W}^+ \in \mathbb{R}^{18 \times 512}$) is more effective for latent space editing. There is a definite relation between the layers of $\mathcal{W}^+$ and the semantic latent subspace. So the semantic modulation can be formulated as editing some specific layers of $\mathcal{W}^+$. As a result, image manipulation methods [3, 36, 4, 14] based on StyleGAN invert an input image to a latent code $w \in \mathcal{W}^+$ for semantic modification. In this work, we follow [23] to utilize the StyleGAN2 as our generator.

Figure 2: Overview of our pipeline. Given a text embedding $e_t$ and an input latent code $w$, we propose several semantic modulation blocks to produce an offset $\Delta w$ for latent space modification. In each block, there is a semantic alignment module to automatically identify the semantic subspace in $w$ based on $e_t$. Then, we use a semantic injection to modify this subspace to refine $\Delta w$.

**CLIP Revisiting.** The CLIP model [24] is pretrained from 0.4 billion image-text pairs for cross-modality semantic matching. This model consists of an image encoder and a text encoder to project an image and a text prompt into a 512-dimension embedding, respectively. We leverage the text encoder of CLIP model to produce the text prompt embedding. This encoder is versatile to perceive text prompts with different semantic meanings.

## 3.1 Semantic Modulation

Fig. 3 shows the framework of a semantic modulation block where there are $k$ blocks in total. Given an image latent code $w \in \mathcal{W}^+$ converted from an image with e4e [37] and a text embedding $e_t$ extracted from the CLIP model, $k$ semantic modulation blocks progressively refine $\Delta w$. The $\Delta w$ will modify $w$ for latent subspace editing. The output of the $i$-th block is denoted as $\Delta w_i$. In each block, there is a semantic alignment module followed by a semantic injection module, which are illustrated as follows:

**Semantic Alignment Module.** The automatic semantic correspondence between $e_t$ and $w$ enables that one model is able to process text prompts with different semantic meaning. We establish this automatic correspondence by aligning $w$ and $e_t$ via a linear transformation. The parameters of this linear transformation are learned based on the cross attention measurement. Specifically, for the semantic alignment module in the $i$-th block, we compute a cross attention map between $e_t$ and $\Delta w_{i-1}$ ($\Delta w_0 = w$) in both position and channel dimensions similar to the dual attention network [10]. The scale and translation parameters of the linear transformation are computed based on the cross attention maps.

For the position dimension, we set the $e_t$ as the Query $Q_p \in \mathbb{R}^{512}$ and the latent code $\Delta w_{i-1}$ as the Value $V \in \mathbb{R}^{18 \times 512}$ and the Key $K \in \mathbb{R}^{18 \times 512}$. Then, we compute the cross attention map $\text{Attention}_p$ as a scale parameter $S \in \mathbb{R}^{18}$. The scale parameter $S$ models the Value $V$ in position dimension for transforming the latent space to match the text embedding semantics. The cross attention computation on the position dimension can be written as:

$$Q_p = e_t W^Q, K = \Delta w_{i-1} W^K, V = \Delta w_{i-1} W^V,$$
$$\text{Attention}_p = \text{Softmax}(Q_p K^T), \qquad (1)$$
$$S = \text{Attention}_p,$$

where $W^Q, W^K, W^V \in R^{512 \times 512}$. We use these scale parameters to adjust the contribution of each dimension of $\mathcal{W}+$ conditioned on $e_t$. Meanwhile, we observe that the $\mathcal{W}^+$ space is not fully disentangled. One semantic property is reflected not only in a specific element of $w$, but in other elements as well. To this end, we compute the translation parameters in the channel dimension to enhance the semantic alignment.

Figure 3: Our semantic modulation block consists of a semantic alignment module and a semantic injection module. Given $\Delta w_{i-1}$ and $e_t$ as input, we compute their cross attentions in position and channel dimensions to learn a linear transformation. This transformation aligns $\Delta w_{i-1}$ to $e_t$. Then, we use semantic injection to refine $\Delta w_{i-1}$ to $\Delta w_i$ for the input to the next block.

For the channel dimension, we use the same $K$ and $V$ as those in the position dimension, and a new Query $Q_c \in \mathbb{R}^{18 \times 512}$ to calculate the cross attention map Attention$_c$ in the channel dimension. Then, we reconstruct the Value V with the attention map Attention$_c$ and utilize an adaptive average pooling to compute the translation parameters $T \in \mathbb{R}^{512}$. These process can be written as

$$Q_c = e_t^T W_c^Q, K = \Delta w_{i-1} W^K, V = \Delta w_{i-1} W^V,$$
$$\text{Attention}_c = \text{Softmax}(Q_c K), \tag{2}$$
$$T = \text{AAP}(\text{Attention}_c V),$$

where the $W^K$ and $W^V$ are the same as the thaose in the position dimension, and the $W_c^Q \in R^{1 \times 18}$. AAP is the adaptive average pooling operation. After we get the scale and translation parameters, we can align $\Delta w_{i-1}$ to $e_t$ with a linear transformation as follows:

$$x_i = S \times V + T, \tag{3}$$

where the $x_i$ is the output of this semantic alignment module. Then, we inject $e_t$ to this aligned latent subspace via our semantic injection module in the following.

**Semantic Injection Module.** In this module, we inject the semantic from $e_t$ to $x_i$ following that in HairCLIP [41]. Specifically, we adopt the fully-connected layers to map the text embedding $e_t$ into two injection parameters $\beta \in \mathbb{R}^{512}$ and $\gamma \in \mathbb{R}^{512}$, respectively. Then, we inject the text embedding semantics as follows:

$$\Delta w_i = (1 + \gamma) \frac{x_i - \mu_{x_i}}{\sigma_{x_i}} + \beta, \tag{4}$$

where $\mu_{x_i}$ and $\sigma_{x_i}$ represent the mean and the variance of the input $x_i$, respectively. With the aligned semantics, our injection produces the $\Delta w_i$ to modify StyleGAN latent space. The $\Delta w_i$ is further refined through the following semantic modulation blocks to obtain $\Delta w$ for the final image generation.

## 3.2 Training Objectives

In text-driven image manipulation, we focus on two aspects of the output result. First, the semantics of the target object in the image shall be consistent after manipulations. Second, the output image shall be semantically relevant to the text prompt. To this end, we follow [41] and develop two types of loss functions, i.e., semantic preserving loss and text manipulation loss.

**Semantic Preserving Loss.** We aim to preserve the semantic consistency between the input and output images. This semantic shall be represented within the CLIP model. Specifically, we feed the input and output images through the CLIP image encoder to get two image embeddings. If the image subject is consistent, the distance between these two embeddings should be small. So we reduce the distance between these two embeddings. We call it image embedding loss and define it as follows:

$$\mathcal{L}_{embd} = 1 - cos\{E_I^{CLIP}(G(w')), E_I^{CLIP}(G(w))\} \tag{5}$$

where the $G(\cdot)$ denotes the pretrained StyleGAN generator, $cos\{\cdot\}$ means cosine similarity, $E_I^{CLIP}(\cdot)$ is the pretrained CLIP image encoder, $w$ and $w' = w + \Delta w$ are the input and our edited StyleGAN latent codes, respectively. Then we utilize the $L_1$ norm to preserve the irrelevant semantic regions:

$$\mathcal{L}_{norm} = \|\Delta w\|_1. \tag{6}$$

Moreover, for 'human portrait' images, the background loss and the face identity loss are used to improve the performance, and the face identity loss is defined as follows:

$$\mathcal{L}_{id} = 1 - cos\{R(G(w')), R(G(w))\}, \tag{7}$$

where $R(\cdot)$ indicates the pretrained ArcFace network [8]. Also, the background loss can be formulated as:

$$\mathcal{L}_{bg} = \|(G(w') - G(w)) * (P(G(w')) \cap P(G(w)))\|_2 \tag{8}$$

where $P(\cdot)$ is the facial parsing network [20] and $P(G(w'), P(G(w))$ represents the non-facial regions in the input and output images, respectively. The overall semantic preserving loss $\mathcal{L}_{sp}$ can be written as

$$\mathcal{L}_{sp} = \lambda_{embd} \cdot L_{embd} + \lambda_{norm} \cdot L_{norm} + \lambda_{id} \cdot L_{id} + \lambda_{bg} \cdot L_{bg}, \tag{9}$$

where $\lambda_{embd}, \lambda_{norm}, \lambda_{id}$, and $\lambda_{bg}$ are the weights that adjust the contribution of each loss term. We set $\lambda_{embd} = 1.0, \lambda_{norm} = 1.5, \lambda_{id} = 1.0$, and $\lambda_{bg} = 2.0$. In particular, we only introduce $\mathcal{L}_{id}$ and $\mathcal{L}_{bg}$ when we edit face images.

**Text Manipulation Loss.** To evaluate the correlation between output images and text prompt embeddings, we minimize their cosine distance by using the CLIP model. It can be written as:

$$\mathcal{L}_t = 1 - cos\{E_I^{CLIP}(G(w')), e_t\}, \tag{10}$$

where $E_I^{CLIP}(\cdot)$ is the pretrained CLIP image encoder. Overall, the total loss is

$$\mathcal{L}_{\text{total}} = \lambda_{sp} \cdot L_{sp} + \lambda_t \cdot L_t, \tag{11}$$

where $\lambda_{sp}$ and $\lambda_t$ are set as 1 and 1.5 in our method, respectively.

## 4 Experiments

We first illustrate our implementation details. Then we compare FFCLIP with existing methods qualitatively and quantitatively. An ablation study shown in Section A.1 in the Appendix validates the effectiveness of our modules. More results and a video demo are provided in the supplementary files. We will release our implementations to the public.

### 4.1 Implementation Details

We train and evaluate FFCLIP on the CelebA-HQ dataset [15], the LSUN cars dataset [45], and the LSUN Church dataset [45]. To invert images into StyleGAN2's latent codes, we use a pretrained e4e [37] as the image encoder. The dimensions of the latent code are $18 \times 512$, $16 \times 512$ and $14 \times 512$ for face, car and church images, respectively. When training our model, we leverage the text encoder from CLIP, and use the pre-trained StyleGAN2 to generate edited images. For each dataset, we use the corresponding pre-trained StyleGAN2 as the generator. We use 44 text prompts for face images containing emotion, hair color, hairstyle, age, gender, make-up, etc. Meanwhile, we follow the text prompts from StyleCLIP [23] when editing LSUN cars and church datasets. We randomly choose a

Figure 4: Our manipulation results on CelebA-HQ, LSUN cars and churches datasets with different text prompts. The input images are shown on the first column and our results are shown on the corresponding row. Our results are highly semantically relevant to the text prompts while maintaining visually realism.

Figure 5: Visual comparison with TediGAN [43] and StyleCLIP [23] on the CelebA-HQ dataset. The text guidance are described on the left side of each row. FFCLIP is more effective to produce semantic relevant and visually realistic results.

text prompt for an input image for model training. In practice, we use a multi-step learning rate with an initial learning rate of 0.0005. The Adam [19] optimizer is utilized with $\beta 1$ and $\beta 2$ set to 0.9 and 0.999, respectively. For CelebA-HQ dataset, the total training iterations are 150,000 and the batch size is 8. For LSUN church dataset, the total training iterations are 200,000 and the batch size is 4. For LSUN cars dataset, the total training iterations are 100,000 and the batch size is 8. We train our model on a workstation with 8 Nvidia Telsa V100 GPUs.

Figure 6: Our manipulation results with text prompts containing multiple semantic meanings. Our model, trained with text prompts consist of single semantic, is able to manipulate images based on multiple semantic meanings.

## 4.2 Qualitative Evaluation

We compare our method to state-of-the-art text-guided image manipulation methods TediGAN [43] and StyleCLIP [23]. Then, we show our results with diversified text prompts. We also show our model is able to manipulate images with single text prompt containing multiple semantic meanings.

**State-of-the-art Comparisons.** Figure 5 shows the visual comparison results. We observe that the manipulated content does not exactly match the text prompt in the TediGAN's results. An example is shown on the first row with the 'Angry' prompt. The beard appears on the man in the TediGAN' result while it does not exists in the input image. While StyleCLIP improves the manipulation result of TediGAN, it still limits editing input images with high semantic accuracy. The hair still presents in the StyleCLIP result with the 'Bald' prompt. In comparison, our FFLIP is effective to edit images based on the text prompt semantics while maintaining visually realism. Compared to existing methods training each model for one text prompt, our model processes multiple text prompts with only one model. Our superior performance results from the accurate semantic alignment across the text embedding and StyleGAN latent space.

**Free-form Image Manipulations.** Figure 4 shows our image manipulation results where FFCLIP process text prompts with different semantic meaning. For human portrait images, FFCLIP preserves the face identity, produces high-quality edited images, and manipulates images with different semantics. Meanwhile, our results on cars and churches datasets are realistic with accurate semantic transfer. The various manipulation results in multi datasets prove the robustness of our method. We pioneerly develop a single model to process different text prompts for one type of images.

**Text Prompts with Multiple Semantics.** We observe that although we train our model with single word text prompts, FFCLIP is able to edit images with text prompts containing multiple semantics. Figure 6 shows the results. FFCLIP simultaneously transfers multiple text prompt semantics to the input image with realistic appearance. This success is because of the text embedding from the CLIP model with our accurate semantic alignment.

## 4.3 Quantitative Evaluation

There is hardly a straight quantitative measurement to evaluate the image manipulation results. Nevertheless, in the text-driven image manipulation scenario, we believe the image results should correspond to the text prompt semantics. We utilize several text prompts and randomly select 1000

Table 1: Quantitative evaluations on the CelebA-HQ dataset. FFCLIP is more effective to produce semantically relevant results for both editing performance and human subject evaluation. '-' denotes that no quantitative comparison is given as no corresponding classifiers are available.

| Text Prompt | Editing Performance | | | Human Subject Evaluation | | |
|---|---|---|---|---|---|---|
| | TediGAN | StyleCLIP | Ours | TediGAN | StyleCLIP | Ours |
| Bald | 0.2507 | 0.1015 | **0.0279** | 5.7% | 8.6% | **85.7**% |
| Angry | 0.4520 | 0.4860 | **0.5810** | 0.0% | 17.1% | **82.9**% |
| Red hair | 1.0971 | 1.0416 | **0.7171** | 2.9% | 0.0% | **97.1**% |
| Aged 10 | 21.1448 | 17.0053 | **9.8874** | 2.9% | 0.0% | **97.1**% |
| Bowl cut hairstyle | - | - | - | 2.9% | 5.7% | **91.4**% |
| Beard blond mohawk hair | - | - | - | 8.6% | 0.0% | **91.4**% |

testing images from the CelebA-HQ dataset. For each prompt, we produce the results from TediGAN, StyleCLIP and ours. Then, we follow [33] to use the multiple semantic classification model to measure the text-relevance of these results.

Table 1 shows these evaluation results under the editing performance column. We use different configurations to compare these results. When the text prompt is 'Bald', we use the PSPNet [49] to locate the hair region and count the number of pixels within this region. When the text prompt is 'Red hair', we compute the average color difference of the hair region of each result. When the text prompt is 'Angry', we use ESR [34] to determine whether the expression of the results belong to the angry category. When the text prompt is 'Aged 10', we use an age classification method [30] to compute the distance between the estimated ages from the results and 10. For each prompt, we compute the quantitative numbers of all the results. As shown in this table, our method are more effective to transfer text prompt semantics to the images.

**Human Subjective Evaluation.** Besides designing different metrics to evaluate semantic transfer, we conduct human subjective evaluations on the manipulated results from compared methods. We randomly collect 54 images which are manipulated based on 6 text prompts. 35 participants with diverse backgrounds are asked to vote the best results based on the three equally important principles. First, they should select the result where the semantic meaning corresponds to the text prompt most. Second, they should select the result where the human identity is best preserved. Third, they should select the most visually realistic image. We tally the votes as shown in Table 1 under the human subject evaluation column. It indicates that most participants favor our results compared to others, validating the effectiveness of our semantic modulation blocks.

## 5 Concluding Remarks

We propose a method to manipulate image content according to text prompts with different semantic meanings. Our motivation is that existing semantic correspondence is manually established between the text prompt embedding and the StyleGAN latent subspace, leading to the confined application scenario that one model only suites one text prompt.To improve the model flexibility, we design an semantic alignment block which finds the correspondence with cross attention automatically, and the block can get the target latent subspace by using a linear transformation. The parameters of this transformation are learned by computing the cross attentions from the inputs. The automatic correspondence enables our model to process text prompts with different semantic meanings in both single and multiple forms. Experiments in multi datasets show that our method is effective to produce highly semantic relevant and visually realistic results.

A limitation of our method is that we do not completely disentangle the StyleGAN latent code $\mathcal{W}+$, which still remains an open problem for all the existing methods. The negative societal impact is that the edited human portraits could be used for malicious purposes.

# References

[1] Rameen Abdal, Yipeng Qin, and Peter Wonka. Image2stylegan: How to embed images into the stylegan latent space? In *IEEE/CVF International Conference on Computer Vision*, 2019.

[2] Rameen Abdal, Yipeng Qin, and Peter Wonka. Image2stylegan++: How to edit the embedded images? In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[3] Rameen Abdal, Peihao Zhu, Niloy J Mitra, and Peter Wonka. Styleflow: Attribute-conditioned exploration of stylegan-generated images using conditional continuous normalizing flows. *ACM Transactions on Graphics*, 2021.

[4] Yuval Alaluf, Or Patashnik, and Daniel Cohen-Or. Only a matter of style: Age transformation using a style-based regression model. *ACM Transactions on Graphics*, 2021.

[5] Yuval Alaluf, Or Patashnik, and Daniel Cohen-Or. Restyle: A residual-based stylegan encoder via iterative refinement. In *IEEE/CVF International Conference on Computer Vision*, 2021.

[6] David Bau, Hendrik Strobelt, William Peebles, Jonas Wulff, Bolei Zhou, Jun-Yan Zhu, and Antonio Torralba. Semantic photo manipulation with a generative image prior. *arXiv preprint arXiv:2005.07727*, 2020.

[7] Jianbo Chen, Yelong Shen, Jianfeng Gao, Jingjing Liu, and Xiaodong Liu. Language-based image editing with recurrent attentive models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2018.

[8] Jiankang Deng, Jia Guo, Niannan Xue, and Stefanos Zafeiriou. Arcface: Additive angular margin loss for deep face recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4690–4699, 2019.

[9] Ming Ding, Zhuoyi Yang, Wenyi Hong, Wendi Zheng, Chang Zhou, Da Yin, Junyang Lin, Xu Zou, Zhou Shao, Hongxia Yang, et al. Cogview: Mastering text-to-image generation via transformers. *Advances in Neural Information Processing Systems*, 2021.

[10] Jun Fu, Jing Liu, Haijie Tian, Yong Li, Yongjun Bao, Zhiwei Fang, and Hanqing Lu. Dual attention network for scene segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3146–3154, 2019.

[11] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems*, 2014.

[12] Shuyang Gu, Dong Chen, Jianmin Bao, Fang Wen, Bo Zhang, Dongdong Chen, Lu Yuan, and Baining Guo. Vector quantized diffusion model for text-to-image synthesis. *arXiv preprint arXiv:2111.14822*, 2021.

[13] Erik Härkönen, Aaron Hertzmann, Jaakko Lehtinen, and Sylvain Paris. Ganspace: Discovering interpretable gan controls. *Advances in Neural Information Processing Systems*, 2020.

[14] Xianxu Hou, Xiaokang Zhang, Hanbang Liang, Linlin Shen, Zhihui Lai, and Jun Wan. Guidedstyle: Attribute knowledge guided style manipulation for semantic face editing. *Neural Networks*, 2022.

[15] Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

[16] Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Training generative adversarial networks with limited data. *Advances in Neural Information Processing Systems*, 2020.

[17] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019.

[18] Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[19] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[20] Cheng-Han Lee, Ziwei Liu, Lingyun Wu, and Ping Luo. Maskgan: Towards diverse and interactive facial image manipulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[21] Wenbo Li, Pengchuan Zhang, Lei Zhang, Qiuyuan Huang, Xiaodong He, Siwei Lyu, and Jianfeng Gao. Object-driven text-to-image synthesis via adversarial training. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019.

[22] Seonghyeon Nam, Yunji Kim, and Seon Joo Kim. Text-adaptive generative adversarial networks: manipulating images with natural language. In *Advances in Neural Information Processing Systems*, 2018.

[23] Or Patashnik, Zongze Wu, Eli Shechtman, Daniel Cohen-Or, and Dani Lischinski. Styleclip: Text-driven manipulation of stylegan imagery. In *IEEE/CVF International Conference on Computer Vision*, 2021.

[24] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, 2021.

[25] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

[26] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, 2021.

[27] Scott Reed, Zeynep Akata, Xinchen Yan, Lajanugen Logeswaran, Bernt Schiele, and Honglak Lee. Generative adversarial text to image synthesis. In *International Conference on Machine Learning*, 2016.

[28] E. Richardson, Y. Alaluf, O. Patashnik, Y. Nitzan, and D. Cohen-Or. Encoding in style: a stylegan encoder for image-to-image translation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

[29] Elad Richardson, Yuval Alaluf, Or Patashnik, Yotam Nitzan, Yaniv Azar, Stav Shapiro, and Daniel Cohen-Or. Encoding in style: a stylegan encoder for image-to-image translation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

[30] Rasmus Rothe, Radu Timofte, and Luc Van Gool. Dex: Deep expectation of apparent age from a single image. In *IEEE/CVF International Conference on Computer Vision Workshops*, 2015.

[31] Yujun Shen, Jinjin Gu, Xiaoou Tang, and Bolei Zhou. Interpreting the latent space of gans for semantic face editing. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[32] Yujun Shen and Bolei Zhou. Closed-form factorization of latent semantics in gans. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

[33] Alon Shoshan, Nadav Bhonker, Igor Kviatkovsky, and Gerard Medioni. Gan-control: Explicitly controllable gans. In *IEEE/CVF International Conference on Computer Vision*, 2021.

[34] Henrique Siqueira, Sven Magg, and Stefan Wermter. Efficient facial feature learning with wide ensemble-based convolutional neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

[35] Ming Tao, Hao Tang, Songsong Wu, Nicu Sebe, Xiao-Yuan Jing, Fei Wu, and Bingkun Bao. Df-gan: Deep fusion generative adversarial networks for text-to-image synthesis. *arXiv preprint arXiv:2008.05865*, 2020.

[36] Ayush Tewari, Mohamed Elgharib, Gaurav Bharaj, Florian Bernard, Hans-Peter Seidel, Patrick Pérez, Michael Zollhofer, and Christian Theobalt. Stylerig: Rigging stylegan for 3d control over portrait images. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020.

[37] Omer Tov, Yuval Alaluf, Yotam Nitzan, Or Patashnik, and Daniel Cohen-Or. Designing an encoder for stylegan image manipulation. *ACM Transactions on Graphics*, 2021.

[38] Andrey Voynov and Artem Babenko. Unsupervised discovery of interpretable directions in the gan latent space. In *International Conference on Machine Learning*, 2020.

[39] Binxu Wang and Carlos R Ponce. The geometry of deep generative image models and its applications. *arXiv preprint arXiv:2101.06006*, 2021.

[40] Tengfei Wang, Yong Zhang, Yanbo Fan, Jue Wang, and Qifeng Chen. High-fidelity gan inversion for image attribute editing. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.

[41] Tianyi Wei, Dongdong Chen, Wenbo Zhou, Jing Liao, Zhentao Tan, Lu Yuan, Weiming Zhang, and Nenghai Yu. Hairclip: Design your hair by text and reference image. *arXiv preprint arXiv:2112.05142*, 2021.

[42] Tianyi Wei, Dongdong Chen, Wenbo Zhou, Jing Liao, Weiming Zhang, Lu Yuan, Gang Hua, and Nenghai Yu. A simple baseline for stylegan inversion. *arXiv preprint arXiv:2104.07661*, 2021.

[43] Weihao Xia, Yujiu Yang, Jing-Hao Xue, and Baoyuan Wu. Tedigan: Text-guided diverse face image generation and manipulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

[44] Tao Xu, Pengchuan Zhang, Qiuyuan Huang, Han Zhang, Zhe Gan, Xiaolei Huang, and Xiaodong He. Attngan: Fine-grained text to image generation with attentional generative adversarial networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2018.

[45] Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

[46] Han Zhang, Tao Xu, Hongsheng Li, Shaoting Zhang, Xiaogang Wang, Xiaolei Huang, and Dimitris N Metaxas. Stackgan: Text to photo-realistic image synthesis with stacked generative adversarial networks. In *IEEE/CVF International Conference on Computer Vision*, 2017.

[47] Han Zhang, Tao Xu, Hongsheng Li, Shaoting Zhang, Xiaogang Wang, Xiaolei Huang, and Dimitris N Metaxas. Stackgan++: Realistic image synthesis with stacked generative adversarial networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2018.

[48] Zizhao Zhang, Yuanpu Xie, and Lin Yang. Photographic text-to-image synthesis with a hierarchically-nested adversarial network. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2018.

[49] Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2017.


# A  Appendix

## A.1  Ablation Analysis

**Effect of Semantic Alignment Module.** The proposed semantic alignment module modifies Style-GAN's latent code $w$ from the position and channel dimensions by the scale and translation parameters. In order to verify the necessity of modulation with scale and translation, we trained three models: without scale parameter, without translation parameter, and without both parameters, respectively. It is worth mentioning that all three models contain a semantic injection module to inject text information into the latent space. As shown in Figure 7, without scale or translation parameter, we cannot find the latent subspace for the text accurately (e.g., in row1 col4, 'bald' latent subspace is not found), and the latent subspace we find is not disentangled (e.g., in row1 col3, the face ID changes; in row1 col8, the hair color changes; and the result in row1 col9 wears glasses, etc.). Furthermore, only a complete model with both scale and translation parameters can be competent given a combination of texts unseen during training (e.g., beard blond mohawk hair in row2). The associated numerical results are shown in the Table 2.

Figure 7: The effect of semantic alignment module. The guiding texts are given on the side of the pictures, w/o S means without scale parameter, w/o T means without translation parameter, and w/o S&T means without both. Only the model with both scale and translation modulation can find the attribute-specific latent space and obtain disentangled manipulation.

**Effect of the Number of Semantic Modulation Block.** To ablate the number of modulation block ($k$ in Figure 2), we train models with $k = 2, 4, 6, 10$ respectively and evaluate their performance. The visual results are shown in Figure 8. Decreasing the number of modulation blocks will result in poor editing (see $k = 2$). Increasing the number of modulation blocks can improve the performance ($k = 6$), but larger $k$ will cause unstable training and lead to a higher computational cost (see $k = 10$). We finally select $k = 4$ in our method to balance the performance and efficacy. The related numerical results are shown in Table 3

Table 2: Quantitative ablation study of the semantic alignment module.

| Text Prompt | Editing Performance | | | |
|---|---|---|---|---|
| | w/o S | w/o T | w/o S&T | Ours |
| Bald | 0.0630 | 0.2391 | 0.2227 | **0.0279** |
| Angry | 0.7510 | 0.7470 | 0.7640 | **0.5810** |
| Red hair | 0.7082 | 0.7514 | 0.7769 | **0.7171** |
| Aged 10 | 13.9412 | 20.0762 | 15.8426 | **9.8874** |

Figure 8: The effect of the number of semantic modulation blocks. We conduct the ablation experiments with 2, 4, 6, and 10 semantic modulation blocks. We finally choose four blocks in our method.

## A.2 Interpolation Results

FFCLIP can achieve fine-grained image manipulation by interpolation with two output latent codes. As shown in Figure 9 and 10, we generate the intermediate latent code by linear weighting $w'_c = w'_a + \lambda(w'_b - w'_a)$, where $w'_c$ is the intermediate output, $w'_a$ and $w'_b$ are the outputs of FFCLIP which correspond to two different manipulation semantics. By gradually increasing the blending parameter $\lambda$ from 0 to 1, we can generate the results between two semantics (e.g., the visual results between 'Aged 10' and 'Aged 80').

Figure 9: Expression interpolation results. We generate the intermediate results between 'Aged 10' and 'Aged 80'.

Table 3: Quantitative ablation study of the number of the semantic modulation blocks.

| Text Prompt | Editing Performance | | | |
|---|---|---|---|---|
| | $k = 2$ | $k = 4$ | $k = 6$ | $k = 10$ |
| Bald | 0.2371 | 0.0279 | **0.0236** | 0.1720 |
| Angry | 0.5900 | **0.5810** | 0.7380 | 0.6206 |
| Red hair | 0.7233 | 0.7171 | **0.6860** | 0.7515 |
| Aged 10 | 18.5182 | **9.8874** | 13.4156 | 14.9789 |

Input          Happy                                                          Angry

Figure 10: Expression interpolation results. We generate the intermediate results between 'Happy' and 'Angry'.

## A.3 Comparison with HairCLIP

As shown in Figure 11 and Figure 12, we compare with HairCLIP in hair manipulation. The HairCLIP can not reflect the manipulation semantics with hair color and style well(e.g., see 'Red hair' and 'Bob cut hairstyle'). In contrast, our FFCLIP can modify the content more correctly with the capability of finding the latent subspace adaptively. The related numerical comparison as shown in Table 4, for the numerical text prompt 'Gray hair' and 'Blond hair,' we use the similar measurement method of 'Red hair.'

Table 4: Quantitative comparison between HairCLIP and FFCLIP.

| Text Prompt | Editing Performance | |
|---|---|---|
| | HairCLIP | Ours |
| Bald | 0.2481 | **0.0279** |
| Red hair | 1.0474 | **0.7171** |
| Gray hair | 0.6344 | **0.4931** |
| Blond hair | 1.5126 | **1.350** |

## A.4 More Visual Results

We show more visual results on human portrait, cars and churches in Figure 13, Figure 14 and Figure 15 , respectively. Meanwhile, Figure 16 shows the more visual results of multi semantics manipulation. FFCLIP demonstrates the powerful capability of image manipulation in both single and multi text prompt.

Figure 11: Visual comparison with HairCLIP [41] on the CelebA-HQ dataset.The text guidance are described on the left side. FFCLIP is more effective to produce semantic relevant and visually realistic results.

Figure 12: Visual comparison with HairCLIP [41] on the CelebA-HQ dataset. The text guidance are described on the left side. FFCLIP is more effective to produce semantic relevant and visually realistic results.

Figure 13: Our manipulation results of human portraits. All input images are inversions of the real images. The target manipulation semantic used in the text prompt is indicated above each column. FFCLIP has the capability of generating photo-realistic and text-relevant results.

Figure 14: Our manipulation results of cars. All input images are inversions of the real images. The target manipulation semantic used in the text prompt is indicated above each column. FFCLIP has the capability of generating photo-realistic and text-relevant results.

Figure 15: Our manipulation results of churches. All input images are inversions of the real images. The target manipulation semantic used in the text prompt is indicated above each column. FFCLIP has the capability of generating photo-realistic and text-relevant results.

Figure 16: Our manipulation results with text prompts containing multiple semantic meanings.