Robust Reinforcement Learning in Continuous Control Tasks with Uncertainty Set Regularization

Abstract: Reinforcement learning (RL) is recognized as lacking generalization and robustness under environmental perturbations, which excessively restricts its application for real-world robotics. Prior work claimed that adding regularization to the value function is equivalent to learning a robust policy with uncertain transitions. Although the regularization-robustness transformation is appealing for its simplicity and efficiency, it is still lacking in continuous control tasks. In this paper, we propose a new regularizer named **U**ncertainty **S**et **R**egularizer (USR), by formulating the uncertainty set on the parametric space of the transition function. To deal with unknown uncertainty sets, we further propose a novel adversarial approach to generate them based on the value function. We evaluate USR on the Real-world Reinforcement Learning (RWRL) benchmark and the Unitree A1 Robot, demonstrating improvements in the robust performance for perturbed testing environments and sim-to-real scenarios.

Keywords: Reinforcement Learning, Robustness, Robotics

1   Introduction

Reinforcement Learning (RL) is a powerful algorithmic paradigm used to solve sequential decision-making problems and has resulted in great success in various types of environments, e.g., mastering the game of Go [1], playing computer games [2] and operating smart grids [3, 4, 5]. The majority of these successes rely on an implicit assumption that *the testing environment is identical to the training environment*. However, this assumption is too strong for most realistic problems, such as controlling a robot. In more detail, there are several situations where mismatches might appear between training and testing environments in robotics: (1) *Parameter Perturbations* indicates that a large number of environmental parameters, e.g. temperature, friction factor could fluctuate after deployment and thus deviate from the training environment [6]; (2) *System Identification* estimates a transition function from limited experience. This estimation is biased compared with the real-world model [7]; (3) *Sim-to-Real* learns a policy in a simulated environment and performs on real robots for reasons of safety and efficiency [8]. The difference between simulated and realistic environments renders sim-to-real a challenging task.

In this paper, we aim to solve the mismatch between training environment and testing environment as a robust RL problem which regards training environment and testing environment as candidates in the uncertainty set of all possible environments. Robust Markov Decision Processes (Robust MDPs) [9, 10] is a common framework for analyzing the robustness of RL algorithms. Compared with the vanilla MDPs with a single transition model $P(s'|s, a)$, Robust MDPs consider an uncertainty set of transition models $\mathbb{P} = \{P\}$ to better describe the uncertain environments. This formulation is general enough to cover various scenarios for robot learning problems mentioned above.

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Robust RL aims to learn a robust policy under the worst-case scenario for all transition models $P \in \mathbb{P}$. If the transition model P is viewed as an adversarial agent and the uncertainty set $\mathbb{P}$ is its action space, one can reformulate Robust RL as a zero-sum game [11]. In general, solving such a problem is NP-hard [10]. Derman et al. [12], however, adopted the Legendre-Fenchel transform to avoid excessive mini-max computations by converting the minimization over the transition model to a regularization on the value function. Furthermore, it enjoys an additional advantage that it provides more possibilities to design novel regularizers for different types of transition uncertainties. The complexity of these value-function-based regularizers increases with the size of the state space, which leads to a nontrivial extension to continuous control tasks with infinitely large state space. This directly motivates the work of this paper.

We now summarize the contributions of this paper: (1) the robustness-regularization duality method is extended to continuous control tasks in parametric space; (2) the **U**ncertainty **S**et **R**egularizer (USR) on existing RL frameworks is proposed for learning robust policies; (3) the value function is learnt through an adversarial uncertainty set when the actual uncertainty set is unknown in some scenarios; (4) the USR is evaluated on the Real-world Reinforcement Learning (RWRL) benchmark, showing improvements for robust performances in perturbed testing environments with unknown uncertainty sets; (5) the sim-to-real performance of USR is verified through realistic experiments on the Unitree A1 robot.

2 Preliminaries

Robust MDPs. The mathematical framework of Robust MDPs [9, 10] extends regular MDPs in order to deal with uncertainty about the transition function. A Robust MDP can be formulated as a 6-tuple $\langle \mathcal{S}, \mathcal{A}, \mathbb{P}, r, \mu_0, \gamma \rangle$, where $\mathcal{S}, \mathcal{A}$ stand for the state and action space respectively, and $r(s, a) : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ stands for the reward function. Let $\Delta_{\mathcal{S}}$ and $\Delta_{\mathcal{A}}$ be the probability measure on S and A respectively. The initial state is sampled from an initial distribution $\mu_0 \in \Delta_{\mathcal{S}}$, and the future rewards are discounted by the discount factor $\gamma \in [0, 1]$. The most important concept in robust MDPs is the uncertainty set $\mathbb{P} = \{P(s'|s, a) : \mathcal{S} \times \mathcal{A} \rightarrow \Delta_{\mathcal{S}}\}$ that controls the variation of transition P, compared with the stationary transition P in regular MDPs. Let $\Pi = \{\pi(a|s) : \mathcal{S} \rightarrow \Delta_{\mathcal{A}}\}$ be the policy space; the objective of Robust RL can then be formulated as a minimax problem,

$$J^* = \max_{\pi \in \Pi} \min_{P \in \mathbb{P}} \mathbb{E}_{\pi, P} \left[\sum_{t=0}^{+\infty} \gamma^t r(s_t, a_t) \right]. \tag{1}$$

Robust Bellman equation. While Wiesemann et al. [10] has proved NP-hardness of this minimax problem with an arbitrary uncertainty set, most recent studies [13, 9, 14, 11, 15, 12, 16, 17, 18] approximate it by assuming a rectangular structure on the uncertainty set, i.e., $\mathbb{P} = \times_{(s,a) \in \mathcal{S} \times \mathcal{A}} \mathbb{P}_{sa}$, where $\mathbb{P}_{sa} = \{P_{sa}(s') : \Delta_{\mathcal{S}}\}$ denotes the local uncertainty of the transition at (s, a). In other words, the variation of transition is independent at every (s, a) pair. Under the assumption of a rectangular uncertainty set, the robust action value $Q^\pi(s, a)$ under policy π must satisfy the following robust version of the Bellman equation [19] such that

$$Q^\pi(s, a) = r(s, a) + \min_{P_{sa} \in \mathbb{P}_{sa}} \gamma \sum_{s', a'} P_{sa}(s') \pi(a'|s') Q^\pi(s', a') = r(s, a) + \min_{P_{sa} \in \mathbb{P}_{sa}} \gamma \sum_{s'} P_{sa}(s') V^\pi(s'). \tag{2}$$

Nilim and Ghaoui [13] have shown that a robust Bellman operator admits a unique fixed point of Equation 2, the robust action value $Q^\pi(s, a)$.

Robustness-regularization duality. Solving the minimization problem in the RHS of Equation 2 can be further simplified by the Legendre-Fenchel transform [20]. For a function $f : X \rightarrow \mathbb{R}$, its convex conjugate is $f^*(x^*) := \sup\{\langle x^*, x \rangle - f(x) : x \in X\}$. Define $\delta_{\mathbb{P}_{sa}}(P_{sa}) = 0$ if $P_{sa} \in \mathbb{P}_{sa}$ and $+\infty$ otherwise, Equation 2 can be transformed to its convex conjugate (refer to Derman et al. [12] for detailed derivation),

$$Q^\pi(s, a) = r(s, a) + \min_{P_{sa}} \gamma \sum_{s'} P_{sa}(s') V^\pi(s') + \delta_{\mathbb{P}_{sa}}(P_{sa}) = r(s, a) - \delta^*_{\mathbb{P}_{sa}}(-V^\pi(\cdot)). \tag{3}$$

The transformation implies that the robustness condition on transitions can be equivalently expressed as a regularization constraint on the value function, referred to as the robustness-regularization duality. The duality can extensively reduce the cost of solving the minimization problem over infinite transition choices and thus is widely studied in the robust reinforcement learning research community [21, 22, 23].

As a special case, Derman et al. [12] considered a L_2 norm uncertainty set on transitions, i.e., $\mathbb{P}_{sa} = \{\bar{P}_{sa} + \alpha \tilde{P}_{sa} : \|\tilde{P}_{sa}\|_2 \leq 1\}$, where $\bar{P}_{sa}$ is usually called the nominal transition model. It could represent prior knowledge on the transition model or a numerical value of the training environment. The uncertainty set denotes that the transition model is allowed to fluctuate around the nominal model with some degree α. Therefore, the corresponding Bellman equation in Equation 3 becomes $Q^\pi(s, a) = r(s, a) + \gamma \sum_{s'} \bar{P}_{sa}(s') V^\pi(s') - \alpha \|V^\pi(\cdot)\|_2$. Similarly, the L_1 norm has also been used as uncertainty set on transitions [16], i.e., $\mathbb{P}_{sa} = \{\bar{P}_{sa} + \alpha \tilde{P}_{sa} : \|\tilde{P}_{sa}\|_1 \leq 1\}$, and the Bellman equation becomes the form such that $Q^\pi(s, a) = r(s, a) + \gamma \sum_{s'} \bar{P}_{sa}(s') V^\pi(s') - \alpha \max_{s'} |V^\pi(s')|$. This robustness-regularization duality works well with finite state spaces but it's not trivial to directly extend it to infinite state spaces since both $\|V^\pi(\cdot)\|_2$ and $\max_{s'} |V^\pi(s')|$ regularizers need calculations on the infinite-dimensional vector $V^\pi(\cdot)$. In this work, we extend this concept to continuous state space which is a critical characteristic in robotics, which we believe is a novelty with significance.

3 Uncertainty Set Regularized Robust Reinforcement Learning

Having introduced the robustness-regularization duality and the difficulties regarding its extension to continuous state space in Section 2, here, we will first present a novel extension to continuous state space with the uncertainty set defined on the parametric space of the transition function. We will then utilize this extension to derive a robust policy evaluation method that can be directly plugged into existing RL algorithms. Furthermore, to deal with the unknown uncertainty set, we propose an adversarial uncertainty set and visualize it in a simple *moving-to-target* task.

3.1 Uncertainty Set Regularized Robust Bellman Equation (USR-RBE)

For environments with continuous state spaces, the transition model $P(s'|s, a)$ is usually represented as a parametric function $P(s'|s, a; w)$, where w denotes the parameters of the transition function. Instead of defining the uncertainty set on the distribution space, we directly impose a perturbation on w within a set Ω_w. Consequently, the robust objective function (Equation 1) becomes $J^* = \max_{\pi \in \Pi} \min_{w \in \Omega_w} \mathbb{E}_{\pi, P(s'|s, a; w)} \left[\sum_{t=0}^{+\infty} \gamma^t r(s_t, a_t) \right]$. We further assume the parameter w fluctuates around a nominal parameter $\bar{w}$, such that $w = \bar{w} + \tilde{w}$, with $\bar{w}$ being a fixed parameter and $\tilde{w} \in \Omega_{\tilde{w}} = \{w - \bar{w} | w \in \Omega_w\}$ being the perturbation part. Inspired by Equation 3, we can derive a robust Bellman equation on the parametric space for continuous control problems as shown in Proposition 3.1.

Proposition 3.1 (Uncertainty Set Regularized Robust Bellman Equation) *Suppose the uncertainty set of w is Ω_w (i.e., the uncertainty set of $\tilde{w} = w - \bar{w}$ is $\Omega_{\tilde{w}}$), the robust Bellman equation on parametric space can be represented as follows:*

$$Q^\pi(s, a) = r(s, a) + \gamma \int_{s'} P(s'|s, a; \bar{w}) V^\pi(s') ds' - \gamma \int_{s'} \delta^*_{\Omega_{\tilde{w}}} \left[-\nabla_w P(s'|s, a; \bar{w}) V^\pi(s') \right] ds',$$
(4)

where $\delta_{\Omega_w}(w)$ is the indicator function that equals 0 if $w \in \Omega_w$ and $+\infty$ otherwise, and $\delta^*_{\Omega_w}(w')$ is the convex dual function of $\delta_{\Omega_w}(w)$.

The proof is presented in Appendix A.1. Intuitively, Proposition 3.1 shows that ensuring robustness on parameter w can be transformed into an additional regularizer on action value $Q^\pi(s, a)$ that relates to the product of the state value function $V^\pi(s')$ and the derivative of the transition model $\nabla_w P(s'|s, a; \bar{w})$. Taking the L_2 uncertainty set (also used in Derman et al. [12]) as a special case,

i.e., $\Omega_w = \{\bar{w} + \alpha\tilde{w} : \|\tilde{w}\|_2 \leq 1\}$, where $\bar{w}$ stands for the parameter of the nominal transition model $P(s'|s, a'; \bar{w})$, the robust Bellman equation in Proposition 3.1 becomes

$$Q^\pi(s,a) = r(s,a) + \gamma \int_{s'} P(s'|s,a;\bar{w})V^\pi(s')ds' - \alpha \int_{s'} \|\nabla_w P(s'|s,a;\bar{w})V^\pi(s')\|_2 ds'. \quad (5)$$

3.2 Uncertainty Set Regularized Robust Reinforcement Learning (USR-RRL)

To derive a practical robust RL algorithm with the proposed USR-RBE, we follow the policy iteration framework [24] commonly used in RL research.

For the policy evaluation procedure, the following theorem proposes an operator on action value Q^π and ensures its convergence to a unique fixed point by recursively running this operator.

Theorem 3.2 (Convergence of Robust Policy Evaluation) *For any policy $\pi \in \Delta_{\mathcal{A}}$, the following operator T can reach a unique fixed point as the robust action value $Q^\pi(s,a)$ if $0 \leq \gamma + \alpha \max_{s,a} \left| \int_{s'} \|\nabla_w P(s'|s,a;\bar{w})\|_2 ds' \right| \leq 1$.*

$$TQ^\pi(s,a) = r(s,a) + \gamma \int_{s'} P(s'|s,a;\bar{w})V^\pi(s')ds' - \alpha \int_{s'} \|\nabla_w P(s'|s,a;\bar{w})V^\pi(s')\|_2 ds',$$

where $V^\pi(s') = \int_{s'} \pi(a'|s')Q(s',a')da'$.

The proof can be found in Appendix A.2. Intuitively, this theorem indicates that one can acquire a robust action value given a certain policy and uncertainty set if the discount factor γ and the coefficient in the uncertainty set α are properly set, which is satisfied in the practical implementations.

For the policy improvement procedure, all existing techniques (e.g. policy gradient methods) can be adopted to improve the current policy. By iterating the policy evaluation and improvement cycle, the policy will eventually converge to an equilibrium between optimality and robustness.

A practical concern on this algorithm is that calculating USR-RBE requires the knowledge of the transition model $P(s'|s,a;\bar{w})$. This naturally applies to model-based RL, as model-based RL learns a point estimate of the transition model $P(s'|s,a;\bar{w})$ by maximum likelihood approaches [25]. For model-free RL, we choose to construct a local Gaussian model with mean as parameters inspired by previous work [26]. Specifically, suppose one can access a triple (state s, action a and next state x) from the experience replay buffer, a local transition model $P(s'|s,a;\bar{w})$ is constructed as a Gaussian distribution with mean x and covariance Σ (with Σ being a hyperparameter), i.e., the nominal parameter $\bar{w}$ consists of (x, Σ). With this local transition model, we now have the full knowledge of $P(s'|s,a;\bar{w})$ and $\nabla_w P(s'|s,a;\bar{w})$, which allows us to calculate the RHS of Equation 5. To further approximate the integral calculation in Equation 5, we sample M points $\{s'_1, s'_2, ..., s'_M\}$ from the local transition model $P(s'|s,a;\bar{w})$ and use them to approximate the target action value by $Q^\pi(s,a) \approx r(s,a) + \gamma \sum_{i=1}^M \left[V^\pi(s'_i) - \alpha\|\nabla_w P(s'_i|s,a;\bar{w})V^\pi(s_i)\|_2/P(s'_i|s,a;\bar{w}) \right]$, where $\bar{w} = (x, \Sigma)$. With this approximated target value, the Bellman operator is guaranteed to converge to the robust value of the current policy π. Policy improvement can be further applied to learn a more robust policy. We explain how to incorporate USR-RBE into a classic RL algorithm Soft Actor Critic (SAC) [27] in Appendix A.3.

3.3 Adversarial Uncertainty Set

The proposed method in Section 3.2 relies on the prior knowledge of the uncertainty set of the parametric space. The L_p norm uncertainty set is most widely used in the Robust RL and robust optimal control literature. However, such a fixed uncertainty set may not sufficiently adapt to various perturbation types. The L_p norm uncertainty set with its larger region can result in an over-conservative policy, while the one with a smaller region may lead to a risky policy. In this section, we learn an adversarial uncertainty set through the agent's policy and value function.

Generating the Adversarial Uncertainty Set. The basic idea of the adversarial uncertainty set is to provide a broader uncertainty range to parameters that are more sensitive to the value function, which is naturally measured by the derivative. The agent learning on such an adversarial uncertainty set is easier to adapt to the various perturbation types of param-

Figure 1: Illustration of the steps for generating the adversarial uncertainty set.

eters. We generate the adversarial uncertainty set in 5 steps as illustrated in Figure 1, (1) *sample* next state s' according to the distribution $P(\cdot|s, a; \bar{w})$, given the current state s and action a; (2) *forward* pass by calculating the state value $V(s')$ at next state s'; (3) *backward* pass by using the reparameterization trick [28] to compute the derivative $g(\bar{w}) = \nabla_w V(s'; \bar{w})$; (4) *normalize* the derivative by $d(\bar{w}) = g(\bar{w})/[\sum_i^W g(\bar{w})_i^2]^{0.5}$; (5) *generate* the adversarial uncertainty set $\Omega_w = \{\bar{w} + \alpha\tilde{w} : \|\tilde{w}/d(\bar{w})\|_2 \leq 1\}$. The pseudo-code to generate the adversarial uncertainty set is explained in Algorithm 2.

Figure 2: Illustration of different types of uncertainty sets to investigate their characteristics.

Characteristics of the Adversarial Uncertainty Set. To further investigate the characteristics of the adversarial uncertainty set, we visualize it in a simple *moving-to-target* task: controlling a particle to move towards a target point e (Figure 2.a). The two-dimensional state s informs the position of the agent, and the two-dimensional action $a = (a_1, a_2)$ ($\|a\|_2 = 1$ is normalized) controls the force in two directions. The environmental parameter $w = (w_1, w_2)$ represents the contact friction in two directions respectively. The transition function is expressed as $s' \sim \mathcal{N}(s + (a_1w_1, a_2w_2), \Sigma)$, and the reward is defined by the progress of the distance to the target point minus a time cost: $r(s, a, s') = d(s, e) - d(s', e) - 2$. The nominal value $\bar{w} = (1, 1)$ (Figure 2.b) indicates the equal friction factor in two directions for the training environment. It is easy to conjecture that the optimal action is pointing towards the target point, and the optimal value function $V^*(s) = -d(s, e)$. We visualize L_2, L_1 and adversarial uncertainty set of the contact friction w in Figure 2.(c,d,e) respectively, at a specific state $s = (4, 3)$ and the optimal action $a^* = (-0.8, -0.6)$. L_2 and L_1 uncertainty set satisfy $(w_1^2 + w_2^2)^{0.5} \leq 1$ and $|w_1| + |w_2| \leq 1$ respectively. Adversarial uncertainty set is calculated by following the generation procedure in Section 3.3, that the normalized derivative $d(\bar{w})$ is $[0.8, 0.6]^T$ and adversarial uncertainty set is $(w_1^2/0.64 + w_2^2/0.36)^{0.5} \leq 1$, as an ellipse in Figure 2.e. Compared with the L_2 uncertainty set, the adversarial uncertainty set extends the perturbation range of the horizontal dimensional parameter since it is more sensitive to the final return. As a result, the agent learning to resist such an uncertainty set is expected to generally perform well on unseen perturbation types, which will be verified in experiments in the next section.

4 Experiments

In this section, we provide experimental results on the Real-world Reinforcement Learning (RWRL) benchmark [29], to validate the effectiveness of the proposed regularizing USR for resisting perturbations in the environment. Besides, we apply USR on a sim-to-real task to show its potential on real-world robots.

4.1 Experimental Setups

Task Description. RWRL, whose back-end is the Mujoco environment [30], is a continuous control benchmark consisting of real-world challenges for RL algorithms. Using this benchmark, we will evaluate the proposed algorithm regarding the robustness of the learned policy in physical environments with perturbations of parameters of the state equations (dynamics). In more detail, we first train a policy through interaction with the nominal environments (i.e., the environments without any perturbations), and then test the policy in the environments with perturbations within a range over relevant physical parameters. In this paper, we conduct experiments on six tasks: *cartpole_balance*, *cartpole_swingup*, *walker_stand*, *walker_walk*, *quadruped_walk*, *quadruped_run*, with growing complexity in state and action space. More details about the specifications of tasks are shown in Appendix B.1. The perturbed variables and their value ranges can be found in Table 2.

Evaluation metric. A severe problem for Robust RL research is the lack of a standard metric to evaluate policy robustness. To resolve this obstacle, we define a new robustness evaluation metric which we call *Robust-AUC* to calculate the area under the curve of the return with respect to the perturbed physical variables, in analogy to the definition of regular AUC [31]. More specifically, a trained policy π is evaluated in an environment with perturbed variable P whose values v change in the range $[v_{min}, v_{max}]$ and achieves different returns r. Then, these two sets of data are employed to draw a parameter-return curve $C(v, r)$ to describe the relationship between returns r and perturbed values v. We define the relative area under this curve as *Robust-AUC* such that $Robust\text{-}AUC = \frac{Area(C(v,r))}{v_{max} - v_{min}}, v \in [v_{min}, v_{max}]$. Compared to the vanilla AUC, *Robust-AUC* describes the correlation between returns and the perturbed physical variables, which can sensitively reflect the response of a learning procedure (to yield a policy) to unseen perturbations, i.e., the robustness. We further explain the practical implementations to calculate *Robust-AUC* of the experiments in Appendix B.2.

Baselines and Implementation of Proposed Methods. We first compare USR with a standard version of Soft Actor Critic (SAC) [27], which stands for the category of algorithms without regularizers (*None-Reg*). Another category of baselines is to directly impose L_p regularization on the parameters of the value function (*L1-Reg*, *L2-Reg*) [32], which is a common way to improve the generalization of function approximation but without consideration of the environmental perturbations; For a fixed uncertainty set as introduced in Section 3.2, we implement two types of uncertainty sets on transitions, *L2-USR* and *L1-USR*, which can be viewed as an extension of Derman et al. [12] and Wang and Zou [16] for continuous control tasks respectively; finally, we also evaluate the adversarial uncertainty set (Section 3.3), denoted as *Adv-USR*. We conclude all model structures and hyperparameters in Appendix B.3 - B.4.

4.2 Main Results

Table 1: *Robust-AUC* of all algorithms and their uncertainties on RWRL benchmark.

Task Name	Variables	Algorithms					
		None-Reg	*L1-Reg*	*L2-Reg*	*L1-USR*	*L2-USR*	*Adv-USR*
cartpole_swingup	pole_length	393.41 (21.95)	319.73 (23.84)	368.16 (6.33)	**444.93 (12.77)**	424.48 (2.27)	430.91 (2.35)
	pole_mass	155.25 (4.79)	96.85 (4.32)	131.35 (12.42)	175.28 (3.33)	159.61 (2.41)	**193.13 (2.27)**
	joint_damping	137.20 (4.55)	140.16 (0.58)	165.01 (0.16)	164.21 (0.48)	169.88 (2.68)	**170.39 (0.76)**
	slider_damping	783.76 (9.14)	775.73 (16.50)	797.59 (5.52)	793.55 (5.02)	781.02 (5.80)	**819.32 (3.00)**
	average rank	4.5	5.75	3.75	2.5	3.25	**1.25**
walker_stand	thigh_length	487.02 (40.50)	461.95 (50.03)	497.38 (43.98)	488.71 (42.42)	**511.16 (49.84)**	505.88 (50.22)
	torso_length	614.06 (41.10)	586.16 (68.84)	586.20 (44.31)	598.02 (36.17)	610.93 (38.87)	**623.56 (46.47)**
	joint_damping	**607.24 (115.28)**	387.89 (109.53)	443.82 (63.52)	389.77 (76.96)	527.87 (116.75)	514.77 (126.00)
	contact_friction	946.74 (22.20)	**947.24 (29.16)**	941.92 (22.21)	943.11 (21.97)	940.73 (20.89)	945.69 (16.02)
	average rank	2.50	4.75	4.25	4.25	3.00	**2.25**
quadruped_walk	shin_length	492.55 (124.44)	406.77 (90.41)	503.13 (106.50)	540.39 (126.22)	564.60 (135.49)	**571.85 (64.99)**
	torso_density	471.45 (99.14)	600.86 (45.21)	526.22 (79.11)	442.05 (70.73)	472.80 (83.22)	**602.09 (55.36)**
	joint_damping	675.95 (67.23)	711.54 (91.84)	**794.56 (65.64)**	762.50 (79.76)	658.17 (112.67)	785.11 (40.79)
	contact_friction	683.80 (135.80)	906.92 (100.19)	770.44 (158.42)	777.40 (106.04)	767.80 (109.00)	**969.73 (21.24)**
	average rank	5.25	3.50	3.00	3.75	4.25	**1.25**

We show the *Robust-AUC* and its significance value of *cartpole_swingup*, *walker_stand*, *quadruped_walk* in Table 1. Due to page limits, the results of other tasks are presented in Appendix C.1. In addition to calculating *Robust-AUC* under different perturbations, we also rank all algorithms and report the average rank as an overall robustness performance of each task. Notably, *L1-Reg* and *L2-Reg* do not improve on the robustness, and even impair the performance in comparison with the None-Regularized agent on simple domains (*cartpole* and *walker*). In contrast, we observe that both *L2-USR* and *L1-USR* can outperform the default version under certain perturbations (e.g. *L1-USR* in *cartpole_swingup* for pole_length, *L2-USR* in *walker_stand* for thigh_length); they are, however, not effective for all scenarios. We argue that the underlying reason could be that the fixed shape of the uncertainty set cannot adapt to all perturbed cases. This is supported by the fact that *Adv-USR* achieves the best average rank among all perturbed scenarios, showing the best zero-shot generalization performance in continuous control tasks. For complex tasks like *quadruped_run*, it is surprising that *L1-Reg* can achieve competitive results compared with *Adv-USR* but with slightly larger uncertainty on the *Robust-AUC*, probably because the sparsity by L1 regularization can reduce redundant features. We also compare the computational cost of all algorithms both empirically and theoretically in Appendix C.4. It is concluded that *Adv-USR* can improve the robustness in most cases without increasing too much computational burden. More limitations on the computational time are discussed in Section 7. A video (*quadruped_walk.mov* in supplementary material) is provided as an intuitive demonstration of the effect of the *Adv-USR* when a walking quadruped is perturbed by different contact frictions. We also carry out two additional testing scenarios to imitate the perturbation in real: all parameters deviate from the nominal values simultaneously (Appendix C.2) and the perturbed value follows a random walk during the testing episode (Appendix C.3). *Adv-USR* consistently performs best and is well-adapted to different perturbations.

4.3 Study on Sim-to-real Robotic Task

In this section, we further investigate the robustness of *Adv-USR* on a sim-to-real robotic task. Sim-to-real is a commonly adopted setup to apply RL algorithms on real robots, where the agent is first trained in simulation and then transferred to real robots. Unlike the environmental setup in Section 4.1 with additional perturbations during the testing phases, sim-to-real inherently possesses a mismatch between training and testing environ-

(a) Standing (b) Locomotion

Figure 3: Episode returns of all algorithms on sim-to-real task.

ments potentially due to: (1) the simulator possesses a simplified dynamics model and suffers from accumulated error [33] and (2) there are significant differences between simulators and real hardware in robot's parameters, such as a quadruped example in Table 5. As a result, this setup is an ideal testbed and practical application of the proposed robust RL algorithm.

Specifically, we use the Unitree A1 robot [34] and the Bullet simulator [35] as the platform for sim-to-real transfer. The agents learn standing and locomotion in simulations and directly perform on real robots without adaption [36]. Since other baselines cannot generalize well even in pure simulated RWRL environments, we only compare SAC agents with and without *Adv-USR* method. Most previous works [37, 38] utilize domain randomization (DR) techniques [39] to deal with sim-to-real mismatches. DR requires training on multiple randomly initialized simulated instances with diverse environmental parameters, expecting the policy to be generalized in the testing environment (real robot). In contrast, *Adv-USR* only requires training on single nominal parameters, which tremendously improves the efficiency and feasibility. Detailed setup of the sim-to-real task is described in Appendix B.5.

We run 50 testing trials per baseline and report the episodic returns in Figure 3 and an explanatory video (*a1.mp4*) in the supplementary material. Both agents succeed to learn a nearly optimal policy in simulation for both tasks. For the standing task, the agent with *Adv-USR* maintains its performance on real robots while the other agent fails to achieve the standing position. For the more complex locomotion task, *Adv-USR* still performs better than *None-Reg* on real robots, however, the performance deteriorates compared with simulation. To alleviate the extreme sim-to-real difference, combining *Adv-USR* and other sim-to-real techniques could be a more powerful strategy, which would be verified in further work.

5 Related Work

Robust Reinforcement Learning (Robust RL) has recently become a popular topic [9, 29, 40, 41], due to its effectiveness in tackling perturbations. Besides the transition perturbation in this paper, there are other branches relating to action, state and reward. Early works in Robust RL concentrated on action space perturbations. Pinto et al. [42] first proposed an adversarial agent perturbing the action of the principle agent, training both alternately in a mini-max style. This adversarial agent in action space always leads to over-conservative behaviours. Reward perturbation has proved to be converted to transition perturbation by augmenting the reward value in the state [22]. In this paper, we further transform state perturbation to transition perturbation in Appendix E, thus covered by our proposed method.

Sim-to-Real is a key research topic in robot learning. Compared to the Robust RL problem, it aims to learn a robust policy from simulations for generalization in real-world environments. Domain randomization is a common approach to ease this mismatch in sim-to-real problems [39, 8]. However, Mankowitz et al. [15] has demonstrated that it actually optimizes the average case of the environment rather than the worst-case scenario (as seen in our research), which fails to perform robustly during testing. More recent active domain randomization methods [43] resolve this flaw by automatically selecting difficult environments during the training process. The idea of learning an adversarial uncertainty set considered in this paper can be seen as a strategy to actively search for more valuable environments for training. We discuss different types of uncertainty sets and the relation of Robust RL, Bayesian RL and Adaptive RL approaches more fully in Appendix D.

6 Conclusion

In this paper, we adopt the robustness-regularization duality method to design new regularizers in continuous control problems to improve the robustness and generalization of RL algorithms. Furthermore, to deal with unknown uncertainty sets, we design an adversarial uncertainty set according to the learned action state value function and incorporate it into a new regularizer. The proposed method shows great promise regarding generalization and robustness under environmental perturbations in simulated and realistic robotic tasks. Moreover, it does not require training in multiple diverse environments or fine-tuning in testing environments, which makes it an efficient and valuable add-on to RL for robot learning.

7 Limitations

The computational cost of *Adv-USR* is acceptable for the local Gaussian model in the experiments, but is a critical factor when applying it to more complex dynamics with millions of parameters (i.e. common in current model-based RL research [44]). Therefore, methods to automatically detect important variables could be required. Finally, it is desirable to combine *Adv-USR* with domain randomization in more sophistical robotic tasks.

References

[1] D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, Y. Chen, T. Lillicrap, F. Hui, L. Sifre, G. van den Driessche, T. Graepel, and D. Hassabis. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, Oct. 2017. ISSN 1476-4687. [doi:10.1038/nature24270](https://doi.org/10.1038/nature24270).

[2] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, I. Antonoglou, D. Wierstra, and M. Riedmiller. Playing atari with deep reinforcement learning, Dec. 2013.

[3] J. Wang, W. Xu, Y. Gu, W. Song, and T. C. Green. Multi-agent reinforcement learning for active voltage control on power distribution networks. *Advances in Neural Information Processing Systems*, 34:3271–3284, 2021.

[4] D. Qiu, J. Wang, J. Wang, and G. Strbac. Multi-agent reinforcement learning for automated peer-to-peer energy trading in double-side auction market. In *IJCAI*, pages 2913–2920, 2021.

[5] D. Qiu, J. Wang, Z. Dong, Y. Wang, and G. Strbac. Mean-field multi-agent reinforcement learning for peer-to-peer multi-energy trading. *IEEE Transactions on Power Systems*, 2022.

[6] J. Kober, J. A. Bagnell, and J. Peters. Reinforcement learning in robotics: A survey. *The International Journal of Robotics Research*, 32(11):1238–1274, 2013.

[7] S. Schaal. Learning from demonstration. In *Advances in Neural Information Processing Systems*, volume 9. MIT Press, 1996.

[8] OpenAI, M. Andrychowicz, B. Baker, M. Chociej, R. Jozefowicz, B. McGrew, J. Pachocki, A. Petron, M. Plappert, G. Powell, A. Ray, J. Schneider, S. Sidor, J. Tobin, P. Welinder, L. Weng, and W. Zaremba. Learning dexterous in-hand manipulation, Jan. 2019.

[9] G. N. Iyengar. Robust dynamic programming. *Mathematics of Operations Research*, 30(2): 257–280, May 2005. ISSN 0364-765X, 1526-5471. [doi:10.1287/moor.1040.0129](https://doi.org/10.1287/moor.1040.0129).

[10] W. Wiesemann, D. Kuhn, and B. Rustem. Robust markov decision processes. *Math. Oper. Res.*, 38(1):153–183, 2013. [doi:10.1287/moor.1120.0566](https://doi.org/10.1287/moor.1120.0566).

[11] C. P. Ho, M. Petrik, and W. Wiesemann. Fast bellman updates for robust mdps. In *Proceedings of the 35th International Conference on Machine Learning*, pages 1979–1988. PMLR, July 2018.

[12] E. Derman, M. Geist, and S. Mannor. Twice regularized mdps and the equivalence between robustness and regularization. In *Advances in Neural Information Processing Systems*, May 2021.

[13] A. Nilim and L. Ghaoui. Robustness in markov decision problems with uncertain transition matrices. In *Advances in Neural Information Processing Systems*, volume 16. MIT Press, 2004.

[14] A. Roy, H. Xu, and S. Pokutta. Reinforcement learning under model mismatch. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[15] D. J. Mankowitz, N. Levine, R. Jeong, A. Abdolmaleki, J. T. Springenberg, Y. Shi, J. Kay, T. Hester, T. Mann, and M. Riedmiller. Robust reinforcement learning for continuous control with model misspecification. In *International Conference on Learning Representations*, Sept. 2019.

[16] Y. Wang and S. Zou. Online robust reinforcement learning with model uncertainty. In *Advances in Neural Information Processing Systems*, May 2021.

[17] J. Grand-Clément and C. Kroer. Scalable first-order methods for robust mdps. *arXiv:2005.05434 [cs, math]*, Jan. 2021.

[18] E. Derman, D. J. Mankowitz, T. A. Mann, and S. Mannor. Soft-robust actor-critic policy-gradient. page 11.

[19] R. Bellman. Dynamic programming. *Science*, 153(3731):34–37, July 1966. doi:10.1126/science.153.3731.34.

[20] R. T. Rockafellar. *Convex Analysis*, volume 18. Princeton university press, 1970.

[21] H. Husain, K. Ciosek, and R. Tomioka. Regularized policies are reward robust. In *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, pages 64–72. PMLR, Mar. 2021.

[22] B. Eysenbach and S. Levine. Maximum entropy rl (provably) solves some robust rl problems. In *International Conference on Learning Representations*, Sept. 2021.

[23] R. Brekelmans, T. Genewein, J. Grau-Moya, G. Delétang, M. Kunesch, S. Legg, and P. Ortega. Your policy regularizer is secretly an adversary. *arXiv:2203.12592 [cs, stat]*, Mar. 2022.

[24] R. S. Sutton and A. G. Barto. Reinforcement learning: An introduction. page 352.

[25] B. Kégl, G. Hurtado, and A. Thomas. Model-based micro-data reinforcement learning: What are the crucial model properties and which model to choose? *arXiv:2107.11587 [cs]*, July 2021.

[26] D. Nguyen-Tuong, M. Seeger, and J. Peters. Model learning with local gaussian process regression. *Advanced Robotics*, 23(15):2015–2034, Jan. 2009. ISSN 0169-1864, 1568-5535. doi:10.1163/016918609X12529286896877.

[27] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor, Aug. 2018.

[28] D. P. Kingma and M. Welling. Auto-encoding variational bayes, May 2014.

[29] G. Dulac-Arnold, D. Mankowitz, and T. Hester. Challenges of real-world reinforcement learning. *arXiv:1904.12901 [cs, stat]*, Apr. 2019.

[30] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033, Vilamoura-Algarve, Portugal, Oct. 2012. IEEE. ISBN 978-1-4673-1736-8 978-1-4673-1737-5 978-1-4673-1735-1. doi:10.1109/IROS.2012.6386109.

[31] J. Huang and C. Ling. Using auc and accuracy in evaluating learning algorithms. *IEEE Transactions on Knowledge and Data Engineering*, 17(3):299–310, Mar. 2005. ISSN 1558-2191. doi:10.1109/TKDE.2005.50.

[32] Z. Liu, X. Li, B. Kang, and T. Darrell. Regularization matters in policy optimization. Sept. 2019.

[33] T. Erez, Y. Tassa, and E. Todorov. Simulation tools for model-based robotics: Comparison of bullet, havok, mujoco, ode and physx. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 4397–4404, May 2015. doi:10.1109/ICRA.2015.7139807.

[34] U. A1. Unitree. a1: More dexterity, more posibility, 2018. https://www.unitree.com/a1/, Jan. 2018.

[35] E. Coumans and Y. Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. http://pybullet.org, 2016–2021.

[36] J. Lee, J. Hwangbo, and M. Hutter. Robust recovery controller for a quadrupedal robot using deep reinforcement learning, Jan. 2019.

[37] A. Kumar, Z. Fu, D. Pathak, and J. Malik. Rma: Rapid motor adaptation for legged robots, July 2021.

[38] R. Yang, M. Zhang, N. Hansen, H. Xu, and X. Wang. Learning vision-guided quadrupedal loco- motion end-to-end with cross-modal trans- formers. page 21, 2022.

[39] X. B. Peng, M. Andrychowicz, W. Zaremba, and P. Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3803–3810, May 2018. doi:10.1109/ICRA.2018.8460528.

[40] R. Kirk, A. Zhang, E. Grefenstette, and T. Rocktäschel. A survey of generalisation in deep reinforcement learning. *arXiv:2111.09794 [cs]*, Jan. 2022.

[41] J. Moos, K. Hansel, H. Abdulsamad, S. Stark, D. Clever, and J. Peters. Robust reinforcement learning: A review of foundations and recent advances. *Machine Learning and Knowledge Extraction*, 4(1):276–315, Mar. 2022. ISSN 2504-4990. doi:10.3390/make4010013.

[42] L. Pinto, J. Davidson, R. Sukthankar, and A. Gupta. Robust adversarial reinforcement learning. *arXiv:1703.02702 [cs]*, Mar. 2017.

[43] B. Mehta, M. Diaz, F. Golemo, C. J. Pal, and L. Paull. Active domain randomization. In *Proceedings of the Conference on Robot Learning*, pages 1162–1176. PMLR, May 2020.

[44] M. Janner, J. Fu, M. Zhang, and S. Levine. When to trust your model: Model-based policy optimization. *arXiv:1906.08253 [cs, stat]*, Nov. 2021.

[45] Y. Tassa, Y. Doron, A. Muldal, T. Erez, Y. Li, D. d. L. Casas, D. Budden, A. Abdol- maleki, J. Merel, A. Lefrancq, T. Lillicrap, and M. Riedmiller. Deepmind control suite. *arXiv:1801.00690 [cs]*, Jan. 2018.

[46] D. Yarats and I. Kostrikov. Soft actor-critic (sac) implementation in pytorch, 2020.

[47] H. van Hasselt, A. Guez, and D. Silver. Deep reinforcement learning with double q-learning, Dec. 2015.

[48] L. Smith, I. Kostrikov, and S. Levine. A walk in the park: Learning to walk in 20 minutes with model-free reinforcement learning, Aug. 2022.

[49] C. Tessler, Y. Efroni, and S. Mannor. Action robust reinforcement learning and applications in continuous control. *arXiv:1901.09184 [cs, stat]*, May 2019.

[50] P. Kamalaruban, Y.-T. Huang, Y.-P. Hsieh, P. Rolland, C. Shi, and V. Cevher. Robust reinforce- ment learning via adversarial training with langevin dynamics. page 12, 2020.

[51] E. Vinitsky, Y. Du, K. Parvate, K. Jang, P. Abbeel, and A. Bayen. Robust reinforcement learning using adversarial populations. *arXiv:2008.01825 [cs, stat]*, Sept. 2020.

[52] A. Pattanaik, Z. Tang, S. Liu, G. Bommannan, and G. Chowdhary. Robust deep reinforcement learning with adversarial attacks. *arXiv:1712.03632 [cs]*, Dec. 2017.

[53] H. Zhang, H. Chen, C. Xiao, B. Li, M. Liu, D. Boning, and C.-J. Hsieh. Robust deep rein- forcement learning against adversarial perturbations on state observations. *arXiv:2003.08938 [cs, stat]*, July 2021.

[54] T. Oikarinen, W. Zhang, A. Megretski, T.-W. Weng, and L. Daniel. Robust deep reinforcement learning through adversarial loss. page 20, 2021.

[55] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. Intriguing properties of neural networks. *arXiv:1312.6199 [cs]*, Feb. 2014.

[56] J. X. Wang, Z. Kurth-Nelson, D. Tirumala, H. Soyer, J. Z. Leibo, R. Munos, C. Blundell, D. Kumaran, and M. Botvinick. Learning to reinforcement learn, Jan. 2017.