Solving Is Not Drawing: A Benchmark for Diagrammatic Reasoning in Olympiad Geometry

Hsien Xin Peng [*1] **Anthony Kim** [*1] **Alvin Li** [*1] **Calvin Supasanya** [*1] **Shivank Garg** [1] **Kevin Zhu** [1]

Abstract

Foundation models such as GPT and Claude now solve olympiad-level mathematics with remarkable proficiency, so much so that geometry problem solving has become a standard proxy for their mathematical reasoning. Yet solving a geometry problem and drawing the figure it depends on are not the same skill: progress often hinges on a faithful diagram with the right auxiliary constructions and incidences, and it is unclear that a model which reasons its way to the answer can also produce one. A growing collection of benchmarks, including MathVista, and MathVerse, measures whether models reach the correct answer, but to our knowledge, none isolate the distinct ability to construct the diagram itself, leaving this capability unmeasured. We introduce an open-source benchmark that targets this gap: 954 self-contained olympiad geometry problems, with a 297-problem hard subset, each paired with its solution and a human-authored, high-fidelity diagram in renderable Asymptote code, together with a suite of text-, code-, image-, VLM-, and constraint-based metrics for what we term diagrammatic reasoning. Evaluating current foundation models reveals a pronounced gap between solving and drawing: their diagrams are markedly less faithful, with an average compile success rate of only 36.14%. Strong mathematical reasoning, we find, does not imply the ability to construct accurate geometric diagrams. Our benchmark and dataset can be accessed at https://huggingface.co/datasets/max98765/hard_geometry_problems_with_diagrams.

[1]Algoverse AI Research. Correspondence to: Shivank Garg <shivank@algoverseairesearch.org>.

The 3^{rd} *AI for Math Workshop* at the 43^{rd} International Conference on Machine Learning (ICML), Seoul, South Korea, 2026. Copyright 2026 by the author(s).

1. Introduction

Recently, foundation models have achieved exceptional scores on math olympiad problems, so much so that these problems are now used as a general proxy for a model's mathematical reasoning. However, many olympiad problems rely on more than textual reasoning. Geometry is a prominent example, as progress frequently depends on an accurate, representative diagram, complete with the right auxiliary constructions and the correct incidences between points, lines, and circles. Solving the problem and drawing the figure it rests on are not obviously the same skill.

Our experiments show that they are not. Despite their textual problem-solving ability, foundation models exhibit a clear discrepancy between solve accuracy and faithful diagram generation, and this gap persists even when a model is handed the full reference solution and asked only to render a consistent figure. Since geometric construction and visualization are central to solving geometry problems, we define *diagrammatic reasoning* as a model's ability to produce a geometrically consistent, high-fidelity diagram from a problem, and we treat it as a capability distinct from problem solving. Measuring it matters in practice: a model that reasons correctly but draws an inconsistent figure cannot be trusted to support geometric work, to verify its own constructions, or to feed reliable diagrams to downstream agents.

A growing collection of benchmarks evaluates the mathematical and geometric problem-solving abilities of foundation models, including OlympiadBench, MathVista, MathVerse, and We-Math. These efforts measure whether a model reaches the correct answer or follows a valid reasoning trace, but they consume diagrams as input or treat them as incidental. To our knowledge, none isolate the distinct ability to construct the diagram itself, so a model can score well while holding an inconsistent or impossible picture of the configuration.

We address this gap with an open-source benchmark of 954 self-contained olympiad geometry problems, including a 297-problem hard subset, each paired with its full solution and a human-authored, high-fidelity ground-truth diagram available as both an image and renderable code.

We require models to express diagrams as Asymptote code, since its native geometric primitives make it better suited to precise compass-and- straightedge constructions than general-purpose plotting libraries, while keeping the task in the model's native text modality and yielding figures that are precise, modifiable, and easy to compare against ground truth diagrams. That the gap persists in this code setting indicates it is not an artifact of weak multimodal generation; even when confined to text, models struggle to extract and correctly represent geometric constraints. We pair the dataset with a suite of text-, code-, image-, VLM-, and constraint-based metrics for diagrammatic reasoning.

Evaluating current foundation models on this benchmark confirms a pronounced gap between solving and drawing. Their diagrams are markedly less faithful than their solve accuracy would suggest, with an average compile success rate of only 36.14% and fidelity well below their problem-solving performance, as reported in Table 1. To summarize, our main contributions are as follows:

1. We define and standardize *diagrammatic reasoning*, the ability to generate a geometrically consistent, high-fidelity diagram, as a capability distinct from problem solving.

2. We release an open-source dataset of 954 olympiad geometry problems, each with a full solution and a human-made, high-fidelity diagram available as both an image and renderable Asymptote code, together with a suite of text-, code-, image-, VLM-, and constraint-based metrics for evaluation.

3. We benchmark state-of-the-art foundation models and show that strong mathematical reasoning does not imply the ability to construct accurate geometric diagrams.

2. Related Works

2.1. Geometric Diagram Generation

A range of approaches exist for generating accurate geometry diagrams. Manual tools such as GeoGebra (Hohenwarter, 2007) let users construct figures directly, while code-based generation relies on libraries such as matplotlib (Hunter, 2007) or specialized languages such as Asymptote (Hammerlindl et al., 2026); a separate line of work defines formal geometry languages and uses solvers to satisfy geometric constraints (Lu et al., 2021; Wang et al., 2025; Zhang et al., 2025). More recently, the field has shifted toward learning-based generation (Wang et al., 2025; Zhang et al., 2025; Cheng et al., 2025). Diffusion models produce high-fidelity images (Ho et al., 2020; Rombach et al., 2022) but tend to sacrifice the mathematical precision that geometry demands, which has motivated Multi-modal Large Language Model

(MLLM) approaches that combine textual and visual modalities (Lu et al., 2024; Cheng et al., 2025). GeoUni (Cheng et al., 2025), for instance, trains a unified model with GRPO (Shao et al., 2024) and several geometry-specific rewards to generate accurate diagrams, but this requires training a dedicated MLLM where a text- and code-based approach could suffice.

Foundation models such as GPT-5.4 (OpenAI, 2026a) and Claude Sonnet 4.6 (Anthropic, 2026) are already strong textual and mathematical reasoners, and can generate matplotlib or Asymptote code that renders into a diagram without any dedicated training or additional modality. Whether the diagrams rendered from this code are geometrically faithful to the original problem has not, to our knowledge, been systematically evaluated. This is the gap our work targets. We determine whether an existing foundation model can produce geometrically consistent, code-based diagrams.

2.2. Geometry Metrics and Evaluations

Prior geometry benchmarks typically measure whether a model reaches the correct answer or produces a valid reasoning trace (Chen et al., 2021; Lu et al., 2021; Chen et al., 2022; Lu et al., 2024), but not whether a model conceptualizes the geometric structure correctly; a model can reach the right answer through textual reasoning while holding an inconsistent diagrammatic representation (Zhang et al., 2024; Qiao et al., 2025). Comparing a generated diagram against a ground-truth construction instead requires fidelity metrics.

For images, learned perceptual distances such as LPIPS (Zhang et al., 2018) captures visual similarity. For code, text-overlap metrics such as BLEU (Papineni et al., 2002) and chrF++ (Popović, 2017) count shared word and character n-grams and CodeBLEU (Ren et al., 2020) adds syntactic and semantic signals, though all compare token distributions rather than geometric behavior. Using an LLM or Vision-Language Model as a judge (Zheng et al., 2023; Chen et al., 2024) assesses geometric reasoning more directly, which we adopt alongside the metrics above.

2.3. Geometry Datasets

Existing geometry datasets focus on problem solving rather than diagram fidelity. For instance, GeoQA (Chen et al., 2021) and Geometry3K (Lu et al., 2021) pair problems with diagrams and formal annotations for answer prediction; Uni-Geo (Chen et al., 2022) unifies calculation and proof, and MathVista (Lu et al., 2024), MathVerse (Zhang et al., 2024), and We-Math (Qiao et al., 2025) target general visual mathematical reasoning. Separately, scientific vector graphics benchmarks show that code-based diagrams can serve as evaluation targets. For example, AutomaTikZ (Belouadi et al., 2024a), DeTikZify (Belouadi et al., 2024b), Text2arch

(Garg et al., 2026) and vTikZ (Reux et al., 2025) all focus on general diagrams rather than theorem-driven geometry, which we address.

3. Dataset Curation

Problem Sources   We source problems from a range of mathematical olympiad exams, primarily the American Mathematics Competition (AMC), American Invitational Mathematics Exam (AIME), USA Math Olympiad (US-AMO) and Junior Math Olympiad (USAJMO) (Mathematical Association of America, 2026a;b), and the International Mathematical Olympiad (IMO) (International Mathematical Olympiad, 2026). We web-scraped problems dating back to the 1980s and their online solutions (Art of Problem Solving, 2026). We keep only solutions whose diagrams were generated with human-authored Asymptote code, which we treat as ground truth. We then prompted GPT-5.4-mini (OpenAI, 2026b) to, for each problem, (1) determine whether it is geometric, (2) determine whether it was self-contained, and (3) summarize the reference solution's approach. In total, we curated a dataset of 954 problems, each paired with a human-authored, Asymptote code-based diagram, and isolate a subset of 297 problems as part of a more challenging dataset. An overview of the curation and evaluation pipeline is shown in Figure 1, and a full dataset breakdown appears in Appendix C.2.

Self-Containment   We define a problem as "self-contained" if its solution is fully reproducible from the problem statement alone, and we exclude any problem that depends on an input image. This serves two purposes. First, it keeps the benchmark accessible to text-only models. Second, it removes a source of error propagation, since a mis-read input diagram would corrupt a model's reasoning from the outset. A purely text-based input avoids both problems.

Difficulty Filtering   We prompted GPT-5.4-mini to rate each problem's difficulty on a scale from 1 to 10. We then retained only problems scoring 7 or above, yielding a hard subset of 297 problems. We chose this cutoff for two reasons: it keeps the benchmark sufficiently challenging to be discriminative, and keeps it comparable in size to other evaluation benchmarks. A more detailed breakdown of the data is in Appendix C.2.

4. Methodology

4.1. Models

We evaluate Claude Sonnet 4.6, Gemini 3.1 Flash-lite, GPT-5.4-mini, Kimi K2.5, and GLM 5.1 on their ability to generate high-quality, code-based diagrams.

4.2. Experiments

We run two settings per model, differing in how much guidance the model receives toward our ground-truth solution. We initially considered providing only the problem statement, but since the problems admit many valid solution paths, a model may diverge from our ground truth and have its diagram unfairly penalized against a single reference; we therefore add a second setting in which the model is anchored to the intended construction via the full reference solution. In the with-solution setting, we provide the statement together with the full reference solution and prompt the model to render a consistent diagram, directly measuring whether it can produce a diagram faithful to a given solution. In the without-solution setting, we provide only the problem statement and prompt the model to both reason through the solution and draw it, jointly evaluating textual and geometric reasoning. Prompts are given in Appendix A.

4.3. Metrics

We evaluate models with a mix of text-, code-, image-, and VLM-based metrics that together capture code similarity and final diagram fidelity. Full details are given in Appendix B.

Text- and Code-Based Metrics   We report a Keyword Match F1 score that cross-references key Asymptote functions in the generated code against those in the ground truth, along with a family of overlap metrics: BLEU (Papineni et al., 2002) and chrF++ (Popović, 2017) measure shared word and character n-grams, CodeBLEU (Ren et al., 2020) adds syntactic and semantic program signals, and ROUGE-L (Lin, 2004) measures longest-common-subsequence overlap. These metrics are cheap and give a rough indication of how close a generated program is to the ground truth. They cannot, however, capture geometric relations between elements: a high score may reflect only shared boilerplate, while a correct diagram built from different Asymptote functions may be penalized. Since Asymptote code is highly formulaic, we retain them as coarse indicators of consistency rather than measures of geometric correctness.

Image-Based Metrics   For visual fidelity, we use Learned Perceptual Image Patch Similarity (LPIPS) (Zhang et al., 2018), which compares deep feature representations of the rendered diagrams; lower values indicate greater similarity.

VLM-Based Metrics   We use GPT-5.4-mini as a vision-language judge, scoring each generated diagram against the ground truth on geometric similarity. The prompt is given in Appendix A.

Compilation Metrics   We report a Compile Success Rate, the fraction of generated Asymptote programs that render

Figure 1. Overview of the Data Curation and Evaluation Processes. We web-scrape high-quality mathematical olympiad problems, namely from national and international competitions with well-documented solutions. We then extract human-made Asymptote code to generate the diagrams corresponding to each solution. To create our dataset, we filter our data, eliminating problems that are not self-contained or not geometric. We then prompt GPT-5.4-mini to generate a difficulty score and a summary of each solution's approach for further analysis. Using a difficulty cutoff, we curate a subset of harder geometry problems. We evaluate foundation models on a range of metrics with two different experimental settings: 1) a baseline with solely the problem statement and 2) including the full reference solution and approach.

without error, as a basic check of whether a model's output is usable at all.

5. Results

We present a comprehensive list of our results in Table 1.

5.1. Solving Performance Does Not Predict Diagram Fidelity

Across every model, diagram-fidelity scores fall well short of what the same models' problem-solving accuracy would suggest. The text- and code-based metrics remain low (BLEU between 13.9 and 19.1, CodeBLEU between 12.4 and 17.7), and the VLM critic, our most direct measure of geometric faithfulness, never exceeds 53.2 on a 0-100 scale. A model that solves a problem correctly can still produce a diagram sharing little geometric structure with the reference, confirming that diagrammatic reasoning is a capability distinct from textual problem solving rather than a by-product of it.

5.2. Rendering More Is Not Rendering Better

Compile success and geometric fidelity are only weakly aligned. Gemini 3.1 Flash-lite compiles most reliably (around 59% in both settings) yet scores below the across-run mean on the VLM critic, whereas Kimi K2.5 and Claude Sonnet 4.6 earn the highest judge scores while compiling far less often. Figure 2 illustrates that the models with the highest compile rates are not those with the highest judge

scores. Compile rate alone is therefore a poor proxy for diagrammatic quality, since a model can produce renderable code while still drawing the wrong figure.

5.3. Effect of Providing the Reference Solution

Supplying the full reference solution improves surface-level code similarity but does little for rendered fidelity. Figure 3 shows the per-metric difference between the with-solution and no-solution settings. Every text- and code-similarity metric improves modestly and consistently with the solution, indicating that models reuse recognizable structure from the provided text. The rendered-image metrics, by contrast, change little and often negatively. The solution context shifts the generated code toward the reference text without making the resulting diagram more geometrically correct, which places the bottleneck in construction rather than in understanding the solution.

5.4. Comparison with Baseline Performance

Due to compute constraints, we did not re-run the models on the problem-solving task. Instead, we report each model's published accuracy on AIME 2025, a competition that contributes a large share of our dataset, as drawn from the respective system cards and reputable secondary sources. On this benchmark the evaluated models are near-saturated: the GPT-5 line reports up to 94.6% without tools and a perfect 100% with code execution (OpenAI, 2025), and the Claude Sonnet line similarly reports roughly 87% without tools and 100% with tools (Anthropic, 2026), with compa-

Table 1. Experimental Results (Mean Score Scaled to 100). LPIPS is lower-is-better. VLM Critic raw scores were on a 0–10 scale and have been linearly rescaled to 0–100 for consistency. "With" denotes that the model was given the full reference solution and approach as context; "Without" denotes that the model was given only the problem statement.

Method	GPT5.4-mini		Claude Sonnet 4.6		Gemini 3.1 Flash-lite		Kimi K 2.5		Glm 5.1	
	With	Without	With	Without	With	Without	With	Without	With	Without
Text/Code-Based Metrics										
↑ Keyword Match F1	55.4	51.4	55.9	52.8	47.4	42.1	49.4	47.9	54.6	51.5
↑ BLEU	18.5	16.8	15.7	15.3	16.6	13.9	19.1	16.4	17.8	16.3
↑ chrF++	35.7	32.9	34.7	32.4	30.5	27.2	33.8	30.1	35.1	31.9
↑ CodeBLEU	17.1	15.1	15.1	14.3	14.8	12.4	17.7	15.4	16.4	15.0
↑ ROUGE-L	22.4	21.6	20.2	20.2	24.8	23.4	24.9	24.0	22.6	21.9
Image-Based Metrics										
↓ LPIPS	54.0	53.7	50.6	51.3	52.6	52.7	47.9	49.5	50.8	53.3
VLM-as-a-Judge										
↑ VLM Critic	37.9	46.4	49.5	51.0	42.6	45.2	50.8	53.2	44.2	45.0
Compilation Metrics										
↑ Compile Success Rate	21.7	20.8	27.6	41.3	59.2	59.3	30.9	22.0	40.0	38.6

Figure 2. Mean VLM judge score against VLM-evaluable rate for each model and prompt setting (circle: with solution; diamond: no solution). Dashed lines mark the across-run means. Higher evaluable rates do not correspond to higher judge scores: the most reliably renderable models score below the mean on geometric fidelity, while the best-judged runs render less often.

Figure 3. Change in each metric when the full reference solution is provided, relative to the no-solution setting (with minus without), per model. Left: text- and code-similarity metrics improve uniformly. Right: rendered-image metrics change little and often negatively, indicating that solution context raises code overlap without improving diagram fidelity.

rable figures across the other models we evaluate. Placing these solving accuracies beside the diagram-fidelity results in Table 1 exposes a large and consistent gap: models that solve the underlying problems almost perfectly produce diagrams whose VLM-critic fidelity remains below $54/100$ and whose programs compile only 36.14% of the time on average. Foundation models thus reliably solve textual geometry while falling short of constructing the accurate, high-fidelity diagrams that geometric reasoning depends on.

6. Conclusion

In this paper, we address the issue of diagrammatic reasoning in existing foundation models. While these models are exceptional at mathematical reasoning tasks, we demonstrate that they fail to generate diagrams that are consistent with textual solutions, even when those solutions are pro-

vided to them. These skills are highly pertinent to problems that require geometric reasoning and awareness. To measure it, we introduce a high-quality benchmark of olympiad geometry problems, each paired with a human-authored solution and a ground-truth diagram in renderable Asymptote code, together with a suite of text-, code-, image-, and VLM-based metrics. Benchmarking current foundation models on this dataset provides, to our knowledge, the first concrete evaluation of their diagrammatic reasoning, and reveals a pronounced gap between solving and drawing: generated diagrams achieve an average compile success rate of just 36.14% and an average VLM-critic score of 46.58%, far below the models' problem-solving ability. These results highlight a continuing need to bring foundation models' diagrammatic reasoning and geometric awareness up to par with their textual reasoning.

7. Limitations

Due to compute constraints and high API costs associated with model inference we did not run the evaluated models on the problem-solving task ourselves, and instead drew baseline accuracies (such as AIME 2025 performance) from published system cards. For the same reason, we generated only a single diagram per problem from each model rather than sampling multiple times; because generation is stochastic, our reported compile-success and fidelity scores reflect one sample per problem and may vary across runs. Our automatic metrics are not perfect proxies for geometric correctness: text- and code-overlap scores reward shared Asymptote boilerplate, and metrics such as SymPy-based symbolic match, could improve evaluation reliability. Our most direct fidelity measure relies on a VLM judge, which inherits the judge model's own visual and geometric limitations and may misjudge borderline diagrams.

References

Anthropic. Introducing Claude Sonnet 4.6, 2026. URL https://www.anthropic.com/news/claude-sonnet-4-6. Accessed 2026-05-01.

Art of Problem Solving. AoPS Wiki: Competition problems and solutions, 2026. URL https://artofproblemsolving.com/wiki/index.php. Accessed 2026-05-01.

Belouadi, J., Lauscher, A., and Eger, S. Automatikz: Text-guided synthesis of scientific vector graphics with tikz. In *The Twelfth International Conference on Learning Representations*, 2024a. URL https://openreview.net/forum?id=v3K5TVP8kZ.

Belouadi, J., Ponzetto, S. P., and Eger, S. Detikzify: Synthesizing graphics programs for scientific figures and sketches with tikz. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024b. URL https://openreview.net/forum?id=bcVLFQCOjc.

Chen, D., Chen, R., Zhang, S., Wang, Y., Liu, Y., Zhou, H., Zhang, Q., Wan, Y., Zhou, P., and Sun, L. Mllm-as-a-judge: Assessing multimodal llm-as-a-judge with vision-language benchmark. In *Forty-first International Conference on Machine Learning*, 2024.

Chen, J., Tang, J., Qin, J., Liang, X., Liu, L., Xing, E., and Lin, L. GeoQA: A geometric question answering benchmark towards multimodal numerical reasoning. In Zong, C., Xia, F., Li, W., and Navigli, R. (eds.), *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 513–523, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.findings-acl.46. URL https://aclanthology.org/2021.findings-acl.46/.

Chen, J., Li, T., Qin, J., Lu, P., Lin, L., Chen, C., and Liang, X. UniGeo: Unifying geometry logical reasoning via reformulating mathematical expression. In Goldberg, Y., Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 3313–3323, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.218. URL https://aclanthology.org/2022.emnlp-main.218/.

Cheng, J.-K., Zhang, Z., Chen, R., Deng, J., Qin, Z., and Ma, J. Geouni: A unified model for generating geometry diagrams, problems and problem solutions. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pp. 3057–3066. ACM, 2025. doi: 10.1145/3746027.3754965. URL https://doi.org/10.1145/3746027.3754965.

Garg, S., Mittal, S., and Gupta, M. Text2arch: A dataset for generating scientific architecture diagrams from natural language descriptions. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=dHWtOTiceO.

Hammerlindl, A., Bowman, J., and Prince, T. *Asymptote: The Vector Graphics Language*, 2026. URL https://asymptote.sourceforge.io/doc/. Version 3.10-32.

Ho, J., Jain, A., and Abbeel, P. Denoising diffusion probabilistic models, 2020. URL https://arxiv.org/abs/2006.11239.

Hohenwarter, M. Dynamic mathematics with geogebra. *Journal of Online Mathematics and its Applications*, 7, 2007. ISSN 1935-6439.

Hunter, J. D. Matplotlib: A 2d graphics environment. *Computing in Science & Engineering*, 9(3):90–95, 2007. doi: 10.1109/MCSE.2007.55.

International Mathematical Olympiad. Problems, 2026. URL https://www.imo-official.org/problems.aspx. Accessed 2026-05-01.

Lin, C.-Y. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL https://aclanthology.org/W04-1013/.

Lu, P., Gong, R., Jiang, S., Qiu, L., Huang, S., Liang, X., and Zhu, S.-C. Inter-GPS: Interpretable geometry problem solving with formal language and symbolic reasoning. In Zong, C., Xia, F., Li, W., and Navigli, R. (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 6774–6786, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.528. URL https://aclanthology.org/2021.acl-long.528/.

Lu, P., Bansal, H., Xia, T., Liu, J., Li, C., Hajishirzi, H., Cheng, H., Chang, K.-W., Galley, M., and Gao, J. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *International Conference on Learning Representations (ICLR)*, 2024. URL https://mathvista.github.io/.

Mathematical Association of America. American mathematics competitions, 2026a. URL https://maa.org/student-programs/amc/. Accessed 2026-05-01.

Mathematical Association of America. MAA invitational competitions, 2026b. URL https://maa.org/maa-invitational-competitions/. Accessed 2026-05-01.

OpenAI. GPT-5 system card, 2025. URL https://cdn.openai.com/gpt-5-system-card.pdf. Accessed 2026-05-01.

OpenAI. Introducing GPT-5.4, 2026a. URL https://openai.com/index/introducing-gpt-5-4/. Accessed 2026-05-01.

OpenAI. OpenAI API models, 2026b. URL https://platform.openai.com/docs/models. Accessed 2026-05-01.

Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. Bleu: a method for automatic evaluation of machine translation. In Isabelle, P., Charniak, E., and Lin, D. (eds.), *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL https://aclanthology.org/P02-1040/.

Popović, M. chrF++: words helping character n-grams. In Bojar, O., Buck, C., Chatterjee, R., Federmann, C., Graham, Y., Haddow, B., Huck, M., Yepes, A. J., Koehn, P., and Kreutzer, J. (eds.), *Proceedings of the Second Conference on Machine Translation*, pp. 612–618, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4770. URL https://aclanthology.org/W17-4770/.

Qiao, R., Tan, Q., Dong, G., MinhuiWu, M., Sun, C., Song, X., Wang, J., GongQue, Z., Lei, S., Zhang, Y., Wei, Z., Zhang, M., Qiao, R., Zong, X., Xu, Y., Yang, P., Bao, Z., Diao, M., Li, C., and Zhang, H. We-math: Does your large multimodal model achieve human-like mathematical reasoning? In Che, W., Nabende, J., Shutova, E., and Pilehvar, M. T. (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 20023–20070, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.983. URL https://aclanthology.org/2025.acl-long.983/.

Ren, S., Guo, D., Lu, S., Zhou, L., Liu, S., Tang, D., Sundaresan, N., Zhou, M., Blanco, A., and Ma, S. Codebleu: a method for automatic evaluation of code synthesis, 2020. URL https://arxiv.org/abs/2009.10297.

Reux, C., Acher, M., Khelladi, D. E., Quinton, C., and Barais, O. Llm code customization with visual results: A benchmark on tikz. In *Proceedings of the 29th International Conference on Evaluation and Assessment in Software Engineering*, EASE '25, pp. 1086–1096. ACM, June 2025. doi: 10.1145/3756681.3757003. URL http://dx.doi.org/10.1145/3756681.3757003.

Rombach, R., Blattmann, A., Lorenz, D., Esser, P., and Ommer, B. High-resolution image synthesis with latent diffusion models, 2022. URL https://arxiv.org/abs/2112.10752.

Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y. K., Wu, Y., and Guo, D. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL https://arxiv.org/abs/2402.03300.

Wang, J., Zhang, T., Yu, H., Wang, J., and Huang, H. Magicgeo: Training-free text-guided geometric diagram generation, 2025. URL https://arxiv.org/abs/2502.13855.

Zhang, C., Ning, M., Liu, T., Zhou, Z., Sun, J., Wang, Q., and Huang, K. Geosdf: Plane geometry diagram synthesis via signed distance field, 2025. URL https://arxiv.org/abs/2506.13492.

Zhang, R., Isola, P., Efros, A. A., Shechtman, E., and Wang, O. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 586–595, 2018.

Zhang, R., Jiang, D., Zhang, Y., Lin, H., Guo, Z., Qiu, P., Zhou, A., Lu, P., Chang, K.-W., Qiao, Y.,

Gao, P., and Li, H. *MATHVERSE: Does Your Multimodal LLM Truly See the Diagrams in Visual Math Problems?*, pp. 169–186. Springer Nature Switzerland, October 2024. ISBN 9783031732423. doi: 10.1007/978-3-031-73242-3_10. URL http://dx.doi.org/10.1007/978-3-031-73242-3_10.

Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E., et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36: 46595–46623, 2023.

A. Prompts

A.1. Experiments

For our evaluations of foundation models, we use with the following system prompt:

```
You are an expert data visualization programmer specializing in research-quality diagrams using Asymptote.
Generate a complete, self-contained Asymptote script that creates a diagram based on the user's request.
Rules:
1. Use Asymptote (asy) for all diagrams. Import packages as needed, e.g.:
   - import graph;   // for 2-D function/data plots
   - import stats;   // for histograms, bar charts
   - import three;   // for 3-D diagrams
2. Do NOT specify an output file inside the script. The output path is passed via the -o CLI flag.
3. Set canvas size with size(width, height) or size(300) at the top of the script.
4. Follow research publication standards:
   - Clear axis labels with units where applicable
   - Descriptive title using label() or xaxis()/yaxis() labels
   - Legible font sizes
   - Professional colors (use Asymptote named colors or rgb() values; avoid garish colors)
   - Include a legend when multiple series are present
5. Use synthetic/example data if the user does not provide specific data. Make it realistic and meaningful.
6. IMPORTANT: cos() and sin() take RADIANS. Use dir(degrees) for unit vectors at a given angle in degrees.
7. IMPORTANT: label() only accepts ONE pen argument. Combine pens with +: label("$x$", p, blue+fontsize(10pt)) not
   ↪ label("$x$", p, fontsize(10pt), blue).
8. Output ONLY the Asymptote code inside a single ```asy code block. No other text.
```

We then follow up with the following user prompt for evaluations in the with-solution setting.

```
Create a diagram for:

\{question\}

Solution:

\{solution\}

**Approach to use:**

\{approach\}
```

For evaluations without a solution and approach, we use this user prompt instead:

```
Create a diagram for:

\{question\}
```

A.2. VLM Critic

For our VLM-as-a-judge metric, we use GPT-5.4-mini as our judge. We used the following prompt and appended the two rendered images (the ground truth image and the generated image) to create our full prompt.

```
You are evaluating geometry diagram generation for a research benchmark.
You will see two rendered images:
1. The reference image rendered from the ground-truth Asymptote code.
2. The generated image rendered from a model's Asymptote code.

Judge geometric similarity, not artistic style. Focus on whether the generated
diagram contains the same geometric objects, labels, incidences, relative
layout, angle/parallel/perpendicular markings, and important construction
elements as the reference. Ignore minor rendering artifacts such as antialiasing,
line thickness, small font differences, and harmless scaling/cropping.

Return only JSON with these fields:
{
  "score_0_10": number,
  "summary": string,
  "missing_elements": list[string],
  "wrong_geometry": list[string],
  "extra_elements": list[string],
  "label_issues": list[string]
}

Scoring:
- 9-10: essentially the same geometry and labels.
- 7-8: mostly correct with minor missing or misplaced details.
- 5-6: recognizable core construction but several meaningful issues.
```

```
- 3-4: major geometry mismatch, but some relevant structure remains.
- 1-2: mostly wrong or unreadable.
- 0: blank, non-diagram, or completely unrelated.
```

B. Metrics

Text- and Code-Based Matching Metrics We use a Keyword Match F1 score that cross-references key Asymptote functions present in the generated code against those in the ground truth. Alongside it we report a family of overlap metrics: BLEU, chrF++, CodeBLEU, and ROUGE-L. At its core, BLEU measures n-gram precision according to:

$$\text{BLEU} = \text{BP} \cdot \exp\left(\sum_{n=1}^{N} w_n \log p_n\right) \tag{1}$$

where w_n are the weights and BP is the brevity penalty,

$$\text{BP} = \begin{cases} 1 & \text{if } c > r \\ e^{(1-r/c)} & \text{if } c \leq r \end{cases} \tag{2}$$

and p_n is the modified precision for n-grams of size n,

$$p_n = \frac{\sum_{\text{ngram}} \min\big(\text{Count}_{\text{cand}}(\text{ngram}), \text{Count}_{\text{ref}}(\text{ngram})\big)}{\sum_{\text{ngram}} \text{Count}_{\text{cand}}(\text{ngram})}. \tag{3}$$

chrF++ measures character n-gram precision and recall, CodeBLEU augments n-gram overlap with syntactic and semantic program signals, and ROUGE-L measures longest-common-subsequence overlap rather than n-gram overlap. We chose this family for its ability to identify direct matches between generated and ground-truth code; the metrics are cheap and give a rough indication of how close a model's output is to the reference. They are limited, however, in that they cannot capture the geometric relations between elements: a high score may reflect only shared boilerplate, while a correct diagram built from different Asymptote functions may be penalized. Since Asymptote code is highly formulaic and reuses many of the same functions, we retain these metrics as coarse indicators of consistency rather than measures of geometric correctness.

Image-Based Metrics For visual fidelity, we use Learned Perceptual Image Patch Similarity (LPIPS) (Zhang et al., 2018), which compares deep feature representations of the rendered diagrams. It is computed as:

$$d(x, x_0) = \sum_l \frac{1}{H_l W_l} \sum_{h,w} \left\| w_l \odot \left(\hat{\phi}_{l,hw}^{(x)} - \hat{\phi}_{l,hw}^{(x_0)} \right) \right\|_2^2 \tag{4}$$

where $\hat{\phi}_{l,hw}^{(x)}$ is the normalized activation tensor from layer l of image x at spatial position (h, w), H_l and W_l are the height and width of the feature map at layer l, and w_l is a learned weight. Lower values indicate greater similarity.

VLM-Based Metrics We use GPT-5.4-mini as a vision-language judge, scoring each generated diagram against the ground truth on a scale from 0 to 10, which we rescale to 0-100 for consistency with our other metrics. The full prompt is given in Appendix A.

Compilation Metrics We report a Compile Success Rate, the fraction of generated Asymptote programs that render to an image without error. It captures only whether a model's output is usable, not whether the resulting diagram is geometrically correct, and so serves as a lower bound on diagram quality.

C. Dataset

C.1. Curation

Figure 4 provides an overview of our filtering pipeline during the dataset curation process.

Figure 4. Overview of the Problems Filtered during the Dataset Curation Process. We web-scraped a total of 1441 raw datapoints, before filtering out the problems that were not geometric and not self-contained.

C.2. Breakdown

A full breakdown of our dataset according to the original problem source and difficulty score is as follows:

Table 2. Final Dataset Breakdown based on Difficulty

Dataset	1	2	3	4	5	6	7	8	9	10	Total
AMC	0	14	29	91	95	84	51	15	0	0	379
AIME	0	0	13	63	83	116	105	52	8	0	440
USAJMO	0	0	0	2	5	6	3	5	0	0	21
USAMO	0	0	1	3	3	5	14	15	6	1	48
IMO	0	0	0	0	1	1	3	1	2	0	8
Others	0	0	5	12	12	16	9	4	0	0	58
Total	0	14	48	171	199	225	188	92	16	1	954

Figure 5. Breakdown of Problems by Difficulty Score

Figure 6. Breakdown of All Problems by Difficulty Score