IMED-RL: Regret optimal learning of ergodic Markov decision processes

Abstract

We consider reinforcement learning in a discrete, undiscounted, infinite-horizon Markov decision problem (MDP) under the average reward criterion, and focus on the minimization of the regret with respect to an optimal policy, when the learner does not know the rewards nor transitions of the MDP. In light of their success at regret minimization in multi-armed bandits, popular bandit strategies, such as the optimistic `UCB`, `KL-UCB` or the Bayesian Thompson sampling strategy, have been extended to the MDP setup. Despite some key successes, existing strategies for solving this problem either fail to be provably asymptotically optimal, or suffer from prohibitive burn-in phase and computational complexity when implemented in practice. In this work, we shed a novel light on regret minimization strategies, by extending to reinforcement learning the computationally appealing Indexed Minimum Empirical Divergence (`IMED`) bandit algorithm. Traditional asymptotic problem-dependent lower bounds on the regret are known under the assumption that the MDP is *ergodic*. Under this assumption, we introduce `IMED-RL` and prove that its regret upper bound asymptotically matches the regret lower bound. We discuss both the case when the supports of transitions are unknown, and the more informative but a priori harder-to-exploit-optimally case when they are known. Rewards are assumed light-tailed, semi-bounded from above. Last, we provide numerical illustrations on classical tabular MDPs, *ergodic* and *communicative* only, showing the competitiveness of `IMED-RL` in finite-time against state-of-the-art algorithms. `IMED-RL` also benefits from a lighter complexity.

1 Introduction

We study Reinforcement Learning (RL) with an unknown finite Markov Decision Problem (MDP) under the average-reward criterion in which a learning algorithm interacts sequentially with the dynamical system, without any reset, in a single and infinite sequence of observations, actions, and rewards while trying to maximize its total accumulated rewards over time. Formally, we consider a finite MDP $\mathbf{M} = (\mathcal{S}, \mathcal{A}, \mathbf{p}, \mathbf{r})$ where $\mathcal{S}$ is the finite set of states, $\mathcal{A} = (\mathcal{A}_s)_{s \in \mathcal{S}}$ specifies the set of actions available in each state and we introduce the set of pairs $\mathcal{X}_\mathbf{M} = \{(s,a) : s \in \mathcal{S}, a \in \mathcal{A}_s\}$ for convenience. Further, $\mathbf{p} : \mathcal{X}_\mathbf{M} \to \mathcal{P}(\mathcal{S})$ is the transition distribution function and $\mathbf{r} : \mathcal{X}_\mathbf{M} \to \mathcal{P}(\mathbb{R})$ the reward distribution function, with corresponding mean reward function denoted by $\mathbf{m} : \mathcal{X}_\mathbf{M} \to \mathbb{R}$. An agent interacts with the MDP at discrete time steps $t \in \mathbb{N}^*$ and yields a random sequence $(s_t, a_t, r_t)_t$ of states, actions, and rewards in the following way. At each time step t, the agent observes the current state s_t and decides the action a_t to take based on s_t and possibly past information, *i.e.* previous elements of the sequence. After playing a_t, it observes a reward $r_t \sim \mathbf{r}(s_t, a_t)$, the current state of the MDP changes to $s_{t+1} \sim \mathbf{p}(\cdot|s_t, a_t)$ and the agent proceeds sequentially. In the *average-reward setting*, one is interested in maximizing the limit, $\frac{1}{T} \sum_{t=1}^{T} r_t$, when $T \to \infty$, providing it exists. This setting is a popular framework for studying sequential decision making problems; it can

be traced back to seminal papers such as those of Graves and Lai [1997] and Burnetas and Katehakis [1997] This theoretical framework allows to study the *exploration-exploitation* trade-off that arises from the sequential optimization problem a learner is trying to solve while being uncertain about the very problem it is optimizing.

In this paper, one is interested in developing a sampling strategy that is *optimal* amongst strategies that aim at maximizing the average-reward, *i.e.* balancing exploration and exploitation in an optimal way. To assert optimality, we define the notion of *regret* and state a *regret lower bound* with the purpose of defining a theoretically sound notion of optimality that is *problem dependent*. While *regret* defines the discrepancy to optimality of a learning strategy, a *problem dependent regret lower bound* will formally assess the minimal regret that any learning algorithm must incur on a given MDP problem by computing a minimal rate of exploration. Because this minimal rate of exploration depends on the problem, it is said to be problem dependent, as opposed to worst case regret study that can exist in the MDP literature (*e.g.* Jaksch et al. [2010b]). Regret lower bounds currently exist in the literature when the MDP $\mathbf{M}$ is assumed to be *ergodic*[1]. Hence we hereafter make this assumption, in order to be able to compare the regret of our algorithm to an optimal bound. Similarly, to ensure fast enough convergence of the empirical estimate of the reward to the true mean, an assumption controlling the rate of convergence to the mean is necessary.

Assumption 1 (Light-tail rewards). *For all $x \in \mathcal{X}$, the moment generating function of the reward exists in a neighborhood of 0: $\exists \lambda_x > 0, \forall \lambda \in \mathbb{R}$ such that $|\lambda| < \lambda_x, \mathbb{E}_{R \sim \mathbf{r}(x)}[\exp(\lambda R)] < \infty$.*

Policy   Regret and ergodicity are defined using properties of the set of stationary deterministic policies $\Pi(\mathbf{M})$ on $\mathbf{M}$. On $\mathbf{M}$, each stationary deterministic policy $\pi : \mathcal{S} \to \mathcal{A}_s$ defines a Markov reward process, *i.e.* a Markov chain on $\mathcal{S}$ with kernel $\mathbf{p}_\pi : s \in \mathcal{S} \mapsto \mathbf{p}(\cdot|s, \pi(s)) \in \mathcal{P}(\mathcal{S})$ together with rewards $\mathbf{r}_\pi : s \in \mathcal{S} \mapsto \mathbf{r}(s, \pi(s)) \in \mathcal{P}(\mathbb{R})$ and associated mean rewards $\mathbf{m}_\pi : s \in \mathcal{S} \mapsto \mathbf{m}(s, \pi(s)) \in \mathbb{R}$. The t-steps transition kernel of π on $\mathbf{M}$ is denoted $\mathbf{p}_\pi^t$. We denote $\overline{\mathbf{p}}_\pi = \lim_{T \to \infty} \frac{1}{T} \sum_{t=1}^{T} \mathbf{p}_\pi^{t-1} : \mathcal{S} \to \mathcal{P}(\mathcal{S})$ the Cesaro-average of $\mathbf{p}_\pi$. A learning agent is executing a sequence of policies $\pi_t \in \Pi(\mathbf{M})$, $t \geqslant 1$, where π_t depends on past information $(s_{t'}, a_{t'}, r_{t'})_{t' < t}$. With a slight abuse of notation, a sequence of identical decision rules, $\pi_t = \pi$ for all t, is also denoted π.

Gain   The cumulative reward (value) at time T, starting from an initial state s_1 of policy $\pi = (\pi_t)_t$ is formally given by

$$V_{s_1}(\mathbf{M}, \pi, T) = \mathbb{E}_{\pi, \mathbf{M}, s_1}\left[\sum_{t=1}^{T} r_t \right] = \mathbb{E}_{\pi, \mathbf{M}, s_1}\left[\sum_{t=1}^{T} \mathbf{m}(s_t, a_t) \right] = \sum_{t=1}^{T} \Big(\prod_{t'=1}^{t-1} \mathbf{p}_{\pi_{t'}} \mathbf{m}_{\pi_{t'}} \Big)(s_1). \quad (1)$$

For $\pi \in \Pi(\mathbf{M})$, the average-reward $\frac{1}{T} V_{s_1}(\mathbf{M}, \pi, T)$ tends to $(\overline{\mathbf{p}}_\pi \mathbf{m})(s_1)$ as $T \to \infty$. The gain of policy $\pi \in \Pi(\mathbf{M})$, when starting from state s_1 is defined by $\mathbf{g}_\pi(s_1) = (\overline{\mathbf{p}}_\pi \mathbf{m})(s_1)$ and the optimal gain is defined as $\mathbf{g}^\star(s_1) = \max_{\pi \in \Pi(\mathbf{M})} \mathbf{g}_\pi(s_1)$. $\mathcal{O}_s(\mathbf{M}) = \{\pi \in \Pi : \mathbf{g}_\pi(s) = \mathbf{g}^\star(s)\}$ is the set of policies achieving maximal gain on $\mathbf{M}$ starting from state s.

Definition 1 (Regret). *The regret at time T of a learning policy $\pi = (\pi_t)_t$ starting at state s on a MDP $\mathbf{M}$ is defined with respect to any $\pi^\star \in \mathcal{O}_s(\mathbf{M})$, as*

$$\mathcal{R}_{s_1}(\mathbf{M}, \pi, T) = V_{s_1}(\mathbf{M}, \pi^\star, T) - V_{s_1}(\mathbf{M}, \pi, T). \quad (2)$$

In this paper, we aim to find a learning algorithm with minimal regret. In the considered setting, the learning agent interacts with the MDP without any reset. The minimal assumption would be to allow the agent to come back with positive probability from any initial mistake in finite time, so that the agent is not stuck in a sub-optimal area of the system. This is assuming that the MDP is *communicating*, that is $\forall s, s', \exists \pi, t \in \mathbb{N} : \mathbf{p}_\pi^t(s'|s) > 0$. However, in the literature, lower bounds on the regret are stated for MDPs satisfying a stronger assumption, *ergodicity*. Since one is interested in crafting an algorithm matching a lower bound, we consider this stronger assumption.

Assumption 2 (Ergodic MDP). *The MDP $\mathbf{M}$ is ergodic, that is $\forall s, s', \forall \pi, \exists t \in \mathbb{N} : \mathbf{p}_\pi^t(s'|s) > 0$.*

---

[1] We prefer the term *ergodic* over the more accurate one, *irreducible* as it is a standard abuse of terminology in the MDP community. Mathematically, an MDP is ergodic if both irreducible, aperiodic and positive recurrent.

Intuitively, this means that for all policies and all couples of states, there exists a finite trajectory of positive probability between the states. Interestingly, the ergodic property can be assumed on the MDP or on the set of policies in which we seek an optimal one. For instance, in any communicating MDP all ε-soft policies[2] are ergodic; more in the experiment section 5 and appendix E.

Related work Had the MDP only one state, it would be a bandit problem. Lower bound on the bandit regret and algorithms matching this lower bound, sometimes up to a constant factor, are well studied in the bandit literature. Therefore, bandit sampling strategies with known theoretical guarantees have inspired RL algorithms. The KL-UCB algorithm (Burnetas and Katehakis [1996], Maillard et al. [2011]), has inspired the strategy of the seminal paper of Burnetas and Katehakis [1997], as well the more recent KL-UCRL strategy (Filippi et al. [2010] Talebi and Maillard [2018]). Inspired by the infamous UCB algorithm (Agrawal [1995], Auer et al. [2002]), a number of strategies implementing the optimism principle have emerged such as UCRL (Auer and Ortner [2006]), UCRL2 (Jaksch et al. [2010a]) and UCRL3 (Bourel et al. [2020] (and beyond, for the related episodic setup). The strategy PSRL (Osband et al. [2013]) is inspired by Thompson sampling (Thompson [1933]).

Outline and contribution In this work, we build on the IMED strategy (Honda and Takemura [2015]), a bandit algorithm that benefits from practical and optimal guarantees but has never been used by the RL community. We fill this gap by proposing the IMED-RL algorithm which we prove to be asymptotically optimal for the average-reward criterion. We revisit the notion of skeleton (equation 11) introduced in the seminal work of Burnetas and Katehakis [1997], with a subtle but key modification that prevents a prohibitive burn-in phase (see Appendix G for further details). Further, this novel notion of skeleton enables IMED-RL to remove any tracking or hyper-parameter and mimic a *stochastic-policy-iteration-like* algorithm. [3] Further, this skeleton scales naturally with the studied MDP as it does not explicitly refer to absolute quantities such as the time. We prove that our proposed IMED-RL is asymptotically optimal and show its numerical competitivity.

Building on IMED, we make an additional assumption on the reward that is less restrictive than the common bounded reward hypothesis made in the RL community.

Assumption 3 (Semi-bounded rewards). *For all $x \in \mathcal{X}$, $r(x)$ belongs to a subset $\mathcal{F}_x \subset \mathcal{P}(\mathbb{R})$ known to the learner.[4] There exists a known quantity $m_{\max}(x) \in \mathbb{R}$ such that for all $x \in \mathcal{X}$, the support $\mathtt{Supp}(\mathbf{r}(x))$ of the reward distribution is semi-bounded from above, $\mathtt{Supp}(\mathbf{r}(x)) \subset]-\infty, m_{max}(x)]$, and its mean satisfies $\mathbf{m}(x) < m_{\max}(x)$.*

2 Regret lower bound

In this section, we recall the regret lower bound for ergodic MDPs and provide a few insights about it.

Characterizing optimal policies Relying on classical results that can be found in the books of Puterman [1994] and Hernández-Lerma and Lasserre [1996], we give a useful characterization of optimal policies that is used to derive a regret lower bound. Under the ergodic assumption 2 of MDP $\mathbf{M}$, for all policy $\pi \in \Pi(\mathbf{M})$, the gain is independent from the initial state, *i.e.* $\mathbf{g}_\pi(s) = \mathbf{g}_\pi(s')$ for all states s and s', and we denote it $\mathbf{g}_\pi$. Similarly, the set of optimal policies $\mathcal{O}(\mathbf{M})$ is state-independent since $\mathcal{O}_s(\mathbf{M}) = \mathcal{O}_{s'}(\mathbf{M})$. Any policy π satisfy the following fixed point property

$$\text{(Poisson equation)} \qquad \mathbf{g}_\pi + \mathbf{b}_\pi(s) = \mathbf{m}_\pi(s) + (\mathbf{p}_\pi \mathbf{b}_\pi)(s), \tag{3}$$

where $\mathbf{b}_\pi : \mathcal{S} \to \mathbb{R}$ is called the bias function and is defined up to an additive constant by $\mathbf{b}_\pi(s) = \left(\sum_{t=1}^{\infty}(\mathbf{p}_\pi^{t-1} - \overline{\mathbf{p}}_\pi)\mathbf{m}_\pi\right)(s)$. We highlight that bias plays a role similar to the value function in the discounted reward setting in which the gain is always zero and equation 3 reduces to the Bellman equation, giving a direction in which extend our results to this other RL setting. Interestingly, for any communication and a fortiori ergodic MDP, the span $\mathbb{S}(\mathbf{b}_\pi) = \max_{s \in \mathcal{S}} \mathbf{b}_\pi(s) - \min_{s \in \mathcal{S}} \mathbf{b}_\pi(s)$ of the bias function of any policy is bounded, which allows to decompose the regret in the useful following way.

---

[2]A policy $\pi : \mathcal{S} \to \mathcal{P}(\mathcal{A}_s)$ is ε-soft if $\pi(a|s) \geqslant \varepsilon/|\mathcal{A}_s|$ for all s and a.

[3]The skeleton in Burnetas and Katehakis [1997] is sometimes empty at some states, when t is too small, this causes the strategy to work well only after t is large enough to ensure that the skeleton contains at least one action in each state.

[4]*e.g.* Bernoulli, multinomial with unknown support, beta, truncated Gaussians, a mixture of those, *etc*.

Lemma 1 (Regret decomposition)**.** *Under the ergodic assumption 2, for all optimal policy $\star \in \mathcal{O}(\mathbf{M})$, the regret of any policy $\pi = (\pi_t)_t$ can be decomposed as*

$$\mathcal{R}_{s_1}(\mathbf{M}, \pi, T) = \sum_{x \in \mathcal{X}_{\mathbf{M}}} \mathbb{E}_{\pi, s_1}[N_x(T)] \Delta_x(\mathbf{M}) + \underbrace{\left(\left[\prod_{t=1}^{T} \mathbf{p}_{\pi_t} - \mathbf{p}_{\star}^t\right] b_{\star}\right)(s_1)}_{\leqslant \mathbb{S}(\mathbf{b}_{\star})}, \tag{4}$$

where $N_{s,a}(T) = \sum_{t=1}^{T} \mathbb{1}\{s_t = s, a_t = a\}$ counts the number of time the state-action pair (s, a) has been sampled and $\Delta_{s,a}(\mathbf{M})$ is the sub-optimality gap of the state-action pair (s, a) in $\mathbf{M}$,

$$\Delta_{s,a}(\mathbf{M}) = \mathbf{m}(s,a) + \mathbf{p}_a \mathbf{b}_{\star}(s) - \mathbf{m}_{\star}(s) - \mathbf{p}_{\star} \mathbf{b}_{\star}(s) = \mathbf{m}(s,a) + \mathbf{p}_a \mathbf{b}_{\star}(s) - \mathbf{g}_{\star} - \mathbf{b}_{\star}(s) \tag{5}$$

with $\mathbf{p}_a = \mathbf{p}(\cdot|s, a)$ by a slight abuse of notation. Action $a \in \mathcal{A}_s$ is optimal if and only if $\Delta_{s,a}(\mathbf{M}) = 0$, otherwise, it is said sub-optimal.

This result can be found in Puterman [1994] and is rederived in C. Under the ergodic assumption 2 of MDP $\mathbf{M}$, all optimal policies satisfy a Poisson equation while also being characterized by the optimal Poisson equation (see Hernández-Lerma and Lasserre [1996])

$$\mathbf{g}^{\star, \mathbf{M}} + \mathbf{b}^{\star, \mathbf{M}}(s) = \max_{a \in \mathcal{A}_s} \left\{ \mathbf{m}(s, a) + \sum_{s' \in \mathcal{S}} \mathbf{p}(s'|s, a) \mathbf{b}^{\star, \mathbf{M}}(s') \right\}. \tag{6}$$

Lower bound   To assess the minimal sampling complexity of a sub-optimal state action pair, one must compute how far a sub-optimal state-action pair is from being optimal from an information point-of-view. A sub-optimal state-action pair $(s, a) \in \mathcal{X}_{\mathbf{M}}$ is said to be *critical* if it can be made optimal by changing reward $\mathbf{r}(s, a)$ and transition $\mathbf{p}(\cdot|s, a)$ while respecting the assumptions on the rewards and transitions. Formally, let $\varphi_{\mathbf{M}}(\nu \otimes q) = \mathbb{E}_{R \sim \nu}[R] + q \mathbf{b}^{\star, \mathbf{M}}$ denotes the potential function of $\nu \otimes q$ in $\mathbf{M}$, where $\nu \otimes q$ is the product measure of ν and q. A pair $(s, a) \in \mathcal{X}_{\mathbf{M}}$ is *critical* if it is sub-optimal and there exists $\nu \in \mathcal{F}_{s,a}$ and $q \in \mathcal{P}(\mathcal{S})$ such that

$$\varphi_{\mathbf{M}}(\nu \otimes q) > \gamma_s(\mathbf{M}) \quad \text{where } \gamma_s(\mathbf{M}) \overset{\text{def}}{=} \mathbf{g}^{\star, \mathbf{M}} + \mathbf{b}^{\star, \mathbf{M}}(s). \tag{7}$$

Note that $\gamma_s(\mathbf{M}) = \max_{a \in \mathcal{A}_s} \varphi_{\mathbf{M}}(\mathbf{r}(s, a) \otimes \mathbf{p}(s, a))$ by the optimal Poisson equation (6).

Definition 2 (Sub-optimality cost)**.** *The **sub-optimality cost** of a sub-optimal state-action pair $(s, a) \in \mathcal{X}_{\mathbf{M}}$ is defined as $\underline{\mathbf{K}}_{sa}(\mathbf{M}) \overset{\text{def}}{=} \underline{\mathbf{K}}_{sa}(\mathbf{M}, \gamma_s(\mathbf{M}))$ where*

$$\underline{\mathbf{K}}_{sa}(\mathbf{M}, \gamma) = \inf_{\substack{\nu \in \mathcal{F}_{sa} \\ q \in \mathcal{P}(\mathcal{S})}} \left\{ \mathrm{KL}\left(\mathbf{r}(s, a) \otimes \mathbf{p}(\cdot|s, a), \nu \otimes q\right) \mid \varphi_{\mathbf{M}}(\nu \otimes q) > \gamma \right\}. \tag{8}$$

A lower bound on the regret may now be stated for a certain class of learner, the set of uniformly consistent learning algorithm, *i.e.* those policies $\pi = (\pi_t)_t$ such that $\mathbb{E}_{\pi, \mathbf{M}}(N_{sa}(T)) = o(T^{\alpha})$ for all sub-optimal state-action pair (s, a) and $0 < \alpha < 1$ (see Agrawal et al. [1989]).

Theorem 1 (Regret lower bound Burnetas and Katehakis [1997])**.** *Let $\mathbf{M} = (\mathcal{S}, \mathcal{A}, \mathbf{p}, \mathbf{r})$ be an MDP satisfying assumption 1, 2, 3. For all uniformly consistent learning algorithm π,*

$$\liminf_{T \to \infty} \frac{\mathbb{E}_{\pi, \mathbf{M}}(N_{sa}(T))}{\log T} \geqslant \frac{1}{\underline{\mathbf{K}}_{sa}(\mathbf{M})} \tag{9}$$

with the convention that $1/\infty = 0$. The regret lower bound is

$$\liminf_{T \to \infty} \frac{\mathcal{R}_{\pi}(\mathbf{M}, T)}{\log T} \geqslant \sum_{(s,a) \in \mathcal{C}(\mathbf{M})} \frac{\Delta_{sa}(\mathbf{M})}{\underline{\mathbf{K}}_{sa}(\mathbf{M})} \tag{10}$$

where $\mathcal{C}(\mathbf{M}) = \{(s, a) \mid 0 < \underline{\mathbf{K}}_{sa}(\mathbf{M}) < \infty\}$ is called the set of critical state-action pairs. Those are the state-action pairs (s, a) that could be confused for an optimal one if we were to change their associated rewards and transitions distributions at the displacement cost of $\underline{\mathbf{K}}_{sa}(\mathbf{M})$.

3   The `IMED-RL` Algorithm

In this section we introduce and detail the `IMED-RL` algorithm, whose regret matches this fundamental lower bound and extends the `IMED` strategy from Honda and Takemura [2015] to ergodic MDPs.

157 **Empirical quantities** `IMED-RL` is a *model-based* algorithm that keeps empirical estimates of the
158 transitions $\mathbf{p}$ and rewards $\mathbf{r}$ as opposed to *model-free* algorithm such as Q-learning. We denote by
159 $\hat{\mathbf{r}}_t(s,a) = \hat{\mathbf{r}}(s,a; N_{s,a}(t))$ and $\hat{\mathbf{p}}_t(s,a) = \hat{\mathbf{p}}(s,a; N_{s,a}(t))$ the empirical reward distributions and
160 transition vectors after t time steps, *i.e.* using $N_{s,a}(t)$ samples from the distribution $\mathbf{r}(s,a)$. Initially,
161 $\hat{\mathbf{p}}(s,a;0)$ is the uniform probability over the state space and $\hat{\mathbf{p}}(s,a;k) = (1 - 1/k)\hat{\mathbf{p}}(s,a;k-1) +$
162 $(1/k)\mathbf{s}$, where $\mathbf{s}$ is a vector of zeros except for a one at index s, the k^{th} samples drawn from $\mathbf{p}(\cdot|s,a)$.
163 This defines at each time step t an empirical MDP $\widehat{\mathbf{M}}_t = (\mathcal{S}, \mathcal{A}, \hat{\mathbf{p}}_t, \hat{\mathbf{r}}_t)$. On this empirical MDP,
164 for each state, some actions have been sampled more than others and their empirical quantities are
165 therefore better estimated. We call *skeleton* at time t the subset of state-action pairs that can be
166 considered sampled enough at time t; it is defined by restricting $\mathcal{A}_s$ to $\mathcal{A}_s(t)$ for all state $s \in \mathcal{S}$, with

$$\mathcal{A}_s(t) = \left\{ a \in \mathcal{A}_s \mid N_{s,a}(t) \geqslant \log^2 \left(\max_{a' \in \mathcal{A}_s} N_{sa'}(t) \right) \right\}. \tag{11}$$

167 Since $x > \log^2 x$, $\mathcal{A}_s(t) \neq \emptyset$, hence $\mathcal{A}(t) = (\mathcal{A}_s(t))_s$ contains at least one deterministic policy. We
168 note that the MDP $\mathbf{M}(\mathcal{A}(t)) \stackrel{\text{def}}{=} (\mathcal{S}, \mathcal{A}(t), \mathbf{p}, \mathbf{r})$ defined by restricting the set of actions to $\mathcal{A}(t) \subseteq \mathcal{A}$
169 is an ergodic MDP. The restricted empirical MDP $\widehat{\mathbf{M}}_t(\mathcal{A}(t)) \stackrel{\text{def}}{=} (\mathcal{S}, \mathcal{A}(t), \hat{\mathbf{p}}_t, \hat{\mathbf{r}}_t)$ also is ergodic
170 thanks to the ergodic initialization of the estimate $\hat{\mathbf{p}}$. Inspired by `IMED`, we define the `IMED-RL` index.

171 **Definition 3** (`IMED-RL` index)**.** *For all state-action pairs* $(s,a) \in \mathcal{X}_{\mathbf{M}}$*, let us define* $\mathbf{K}_{sa}(t) \stackrel{\text{def}}{=}$
172 $\underline{\mathbf{K}}_{sa}\left(\widehat{\mathbf{M}}_t(\mathcal{A}(t)), \hat{\gamma}_s(t)\right)$ *with empirical threshold* $\hat{\gamma}_s(t) \stackrel{\text{def}}{=} \max_{a \in \mathcal{A}_s} \varphi_{\hat{\mathbf{M}}_t(\mathcal{A}(t))}(\hat{\mathbf{r}}(s,a) \otimes \hat{\mathbf{p}}(s,a))$ *Then,*
173 *the* `IMED-RL` *index of* (s,a) *at time* t*,* $\mathbf{H}_{sa}(t)$*, is defined as*

$$\mathbf{H}_{sa}(t) \quad = \quad N_{sa}(t)\underline{\mathbf{K}}_{sa}(t) + \log N_{sa}(t), \tag{12}$$

174 Note that $\hat{\gamma}_s(t) \neq \gamma_s(\hat{\mathbf{M}}_t(\mathcal{A}(t)))$ as the maximum is taken over all $a \in \mathcal{A}_s$ an not just $a \in \mathcal{A}_s(t)$.

175 **Known support of transitions** Were the support of transition known, the infimum in
176 sub-optimality cost $\underline{\mathbf{K}}_{sa}$ defined by equation 8 would be redefined as one over the set
177 $\{q \in \mathcal{P}(\mathcal{S}) : \text{Supp}(q) = \text{Supp}(\mathbf{p}(\cdot|s,a))\}$, modifying both the lower bound and `IMED-RL` index.

178 `IMED-RL` **algorithm** The `IMED-RL` algorithm consists in playing at each time step t, an action a_t of
179 minimal `IMED-RL` index at the current state s_t. The intuition behind the `IMED-RL` index is similar to
180 the one of the `IMED` index for bandits and stems from a Bayesian point-of-view of the lower bound.
181 At a given time t, the frequency of play $\frac{N_{sa}(t)}{N_s(t)}$ of action $a \in \mathcal{A}_s$ in state $s \in \mathcal{S}$, should be larger than
182 or equal to its posterior probability of being the optimal action in that state, $\exp(-N_{sa}(t)\underline{\mathbf{K}}_{sa}(t))$,
183 that is to say $\frac{N_{sa}(t)}{N_s(t)} \geqslant \exp(-N_{sa}(t)\underline{\mathbf{K}}_{sa}(t))$. Taking the logarithm and rearranging the terms,
184 this condition rewrites $\mathbf{H}_{sa}(t) \geqslant \log N_s(t)$ at each time step t. The action that is the closest to
185 violate this condition or that violates this condition the most is the one of minimal `IMED-RL` index,
186 $\arg\min_a \mathbf{H}_{sa}(t)$, the one `IMED-RL` decides to play.

Algorithm 1 `IMED-RL`: **I**ndexed **M**inimum **E**mpirical **D**ivergence for **R**einforcement **L**earning

Require: State-Action space $\mathcal{X}_{\mathbf{M}}$ of MDP $\mathbf{M}$, Assumptions 1, 2, 3
Require: Initial state s_1
   for $t \geqslant 1$ **do**
      Sample $a_t \in \arg\min_{a \in \mathcal{A}_{s_t}} \mathbf{H}_{sa}(t)$
   end for

---

187 Intuitions of the `IMED-RL` algorithm root to the control theory of MDPs and optimal bandit theory;
188 `IMED-RL` intertwines the two and the regret proof exactly follows from the following intuitions.

189 **Control** In control theory, we assume that both the expected rewards and transitions probabilities
190 of a MDP $\mathbf{M}$ are known. Policy iteration (see Puterman [1994], Bertsekas and Shreve [1978]) is an
191 algorithm that computes a sequence $(\pi_n)_n$ of deterministic policies that are increasingly strictly better
192 until an optimal policy is reached. In the average-reward setting and under the ergodic assumption,

a policy π is strictly better than another policy π' if $g_\pi(\mathbf{M}) > g_{\pi'}(\mathbf{M})$. The policy iteration algorithm computes the sequence of policies recursively in the following way. Initially, an arbitrary deterministic policy π_0 is chosen. At step $n + 1 \in \bar{\mathbb{N}}^*$, it computes $\mathbf{m}_{\pi_n}$ and $\mathbf{b}_{\pi_n}$ then swipes through the states $s \in \mathcal{S}$ in an arbitrary order until it reaches one state s such that there exists $a \in \mathcal{A}(s)$ with $\mathbf{m}(s, a) + \mathbf{p}(\cdot|s, a)\mathbf{b}_{\pi_n} > \mathbf{m}_{\pi_n}(s) + \mathbf{p}_\pi(s)\mathbf{b}_{\pi_n}$. If such an s does not exist, then it returns π_n as an optimal policy. Otherwise, π_{n+1} is defined as $\pi_{n+1}(s') = \pi_n(s')$ for all $s \neq s'$ and $\pi_{n+1}(s) \in \arg\max\{\mathbf{m}(s, a) + \mathbf{p}(\cdot|s, a)\mathbf{b}_{\pi_n}\}$. Such a step is called a policy improvement step. Policy iteration is guaranteed to finish in a finite number as the cardinal of $\Pi(\mathbf{M})$ is finite. At each step $n \in \mathbb{N}^*$, $\varphi_{\mathbf{M}(\pi_n)}$ is a local function that takes into account the whole dynamic of the MDP and allows to compute, *via* an *argmax*, an optimal choice of improvement (or optimal action) based on local information; $\varphi_{\mathbf{M}(\pi_n)}(\mathbf{r}(s, a) \otimes \mathbf{p}(\cdot|s, a)) = \mathbf{m}(s, a) + \mathbf{p}(s, a)\mathbf{b}_{\pi_n}$. IMED-RL uses $\varphi_{\widehat{\mathbf{M}}(\mathcal{A}(t))}$ and improves the skeleton similarly to policy iteration as it can be seen in the analysis 4.

Bandit control   A degenerate case of MDP would be one where there is only one state s with $\varphi_{\mathbf{M}(\varphi)}(\mathbf{r}(s, a)) = \mathbf{m}(s, a)$ by choosing the bias function to be zero[5]. Playing optimally consists in playing an action with largest expected reward at each time step t, $a_t \in \arg\max_{a \in \mathcal{A}_s} \mathbf{m}(s, a)$.

Bandit   Learning occurs when rewards are unknown; this is the bandit problem. In that case, a lower bound on the regret similar to 1 exists. Under some assumptions on the reward distributions, optimal algorithms whose regret upper bounds asymptotically match the lower bound can derived. IMED Honda and Takemura [2015], KL-UCB Maillard et al. [2011], Cappé et al. [2013] are two such examples that use indexes, *i.e.* computes a number $I_{s,a}(t)$ at each time step and play $a_t \in \arg\min I_{s,a}(t)$. Such indexes are crafted to correctly handle the *exploration-exploitation* trade-off.

RL in Ergodic MDPs   The delayed rewards caused by the dynamic of the system is the main source of difficulty arising from having more than one state. IMED-RL combines control and bandit theory in the following way. At each time step t, a restricted MDP $\widehat{\mathbf{M}}_t(\mathcal{A}(t))$ is built from the empirical one $\widehat{\mathbf{M}}_t$. If the condition to belong to the skeleton is selective enough, then the potentials on the restricted empirical MDP $\widehat{\mathbf{M}}_t(\mathcal{A}(t))$ may become close to those of the restricted true MDP $\mathbf{M}(\mathcal{A}(t))$, that is $\|\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))} - \varphi_{\mathbf{M}(\mathcal{A}(t))}\|_\infty$ is small. We want to make policy improvements by finding, at each state s an action $a' \in \arg\max \varphi_{\mathbf{M}(\mathcal{A}(t))}(\mathbf{r}(s, a) \otimes \mathbf{p}(\cdot|s, a))$, play it enough that it belongs to the skeleton which will modify φ and repeat until $\varphi_{\mathbf{M}(\mathcal{A}(t))} = \varphi_{\mathbf{M}}$. Using φ, the global dynamic is reduced to a local function so that at each state, the agent is presented a bandit problem. This bandit problem is well estimated if $\|\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))} - \varphi_{\mathbf{M}(\mathcal{A}(t))}\|_\infty$ is small. As opposed to the control setting, the learning agent cannot choose the state in which to make the policy improvement step and it may be possible that no policy improvement step is possible at state s_t. However, thanks to the ergodic assumption 2 the agent is guaranteed to visit such a state in finite time, if it exists. There is a trade-off between the adptativity of the skeleton, *i.e.* how quickly one can add an improving action to define a new φ, and concentration of statistical quantities defined on the restricted MDP.

4   Regret of IMED-RL

In this section we state the main theoretical result of this paper, which consists in the IMED-RL regret upper bound. We then sketch a few key ingredients of the proof.

Theorem 2 (Regret upper bound for Ergodic MDPs). *Let* $\mathbf{M} = (\mathcal{S}, \mathcal{A}, \mathbf{p}, \mathbf{r})$ *be a MDP satisfying assumptions 1, 2, 3. Let* $0 < \varepsilon \leqslant \frac{1}{3} \min\limits_{\pi \in \mathcal{D}(\mathbf{M})} \min\limits_{(s,a) \in \mathbf{M}} \min\{|\Delta_{sa}(\mathbf{M}_\pi)| : |\Delta_{sa}(\mathbf{M}_\pi)| > 0\}$. *The regret of* IMED-RL *is upper bounded,*

$$\mathcal{R}_{\textit{IMED-RL}}(\mathbf{M}, T) \leqslant \left(\sum_{(s,a) \in \mathcal{C}(\mathbf{M})} \frac{\Delta_{sa}(\mathbf{M})}{\underline{\mathbf{K}}_{sa}(\mathbf{M}) - \varepsilon \Gamma_s(\mathcal{M})} \right) \log T + O(1), \tag{13}$$

---

[5]recall that the bias function is defined up to an additive constant

where $\Gamma_s(\mathcal{M})$ is constant that depends on the MDP $\mathcal{M}$ and state s; it is made explicit in the proof detailed in appendix D. A Taylor expansion allows to write the regret upper bound as

$$\mathcal{R}_{\texttt{IMED-RL}}(\mathcal{M}, T) \leqslant \left(\sum_{(s,a) \in \mathcal{C}(\mathcal{M})} \frac{\Delta_{sa}(\mathbf{M})}{\underline{\mathbf{K}}_{sa}(\mathcal{M})} \right) \log T + O\left((\log T)^{10/11} \right). \tag{14}$$

Were the semi-bounded reward assumption changed to a bounded reward one with known upper and lower bound, the $O\left((\log T)^{10/11} \right)$ could be made a $O(1)$ as explained in appendix E.

This Theorem proves the optimality of `IMED-RL` since the upper bound on the regret matches the lower bound of Theorem 1. Such a bound was asymptotically matched by the algorithm proposed by Burnetas and Katehakis [1997] and we recall that this algorithm and its problems are discussed in Appendix G. On the other hand, the current state-of-the-art algorithms `UCRL3` and `PSRL`, while having some theoretical guarantees, have not been proved to match the regret lower bound. On the practical side, Q-learning is often used without much theoretical guarantee because of its usually strong practical performances. In the experiments, we will compare `IMED-RL` to those three algorithms.

Sketch of proof   While a full proof is given in appendix D we sketch here the main proof ideas that follow directly from the intuitions behind the `IMED-RL` conception. The regret is decomposed into three terms, the **bandit** term when the local bandit problems defined by $\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))}$ is well estimated, the **concentration on the skeleton** term that controls how long one must wait before $\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))}$ is a good approximation of $\varphi_{\mathbf{M}(\mathcal{A}(t))}$, and the **skeleton improvement** term that controls the probability that an optimal policy belong to the skeleton by controlling the number of policy improvement steps.

The main theorem 2 follows from the following proposition that is proved in appendix D.

Proposition 1. *For all sub-optimal state-action pair* $(s, a) \in \mathcal{X}_{\mathbf{M}}$,

$$N_{sa}(T) \leqslant B_{sa}(T) + E(T) + S(T) \tag{15}$$

where we introduced the following terms

$$B_{sa}(T) = \sum_{t=1}^{T} \mathbb{1} \left\{ \begin{array}{c} s_t = s, a_t = a, \\ \|\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))} - \varphi_{\mathbf{M}}\|_\infty \leqslant \varepsilon, \\ \mathcal{O}\left(\hat{P}^t, \mathcal{A}_t \right) \subseteq \mathcal{O}(P, \mathcal{A}) \end{array} \right\} \qquad \textit{Bandit term} \tag{16}$$

$$E(T) = \sum_{t=1}^{T} \mathbb{1} \left\{ \begin{array}{c} \|\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))} - \varphi_{\mathbf{M}}\|_\infty > \varepsilon, \\ \mathcal{O}\left(\widehat{\mathbf{M}}_t(\mathcal{A}(t)) \right) \subseteq \mathcal{O}(\mathbf{M}) \end{array} \right\} \qquad \textit{Skeleton concentration} \tag{17}$$

$$S(T) = \sum_{t=1}^{T} \mathbb{1} \left\{ \mathcal{O}\left(\widehat{\mathbf{M}}_t(\mathcal{A}(t)) \right) \nsubseteq \mathcal{O}(\mathbf{M}) \right\} \qquad \textit{Skeleton improvement} \tag{18}$$

Furthermore, $\mathbb{E}(S(T)) = O(1)$, $\mathbb{E}(E(T)) = O(1)$, *and for a critical state-action pair* (s, a),

$$\mathbb{E}(B_{sa}(T)) \leqslant \frac{\Delta_{sa}(\mathbf{M})}{\underline{\mathbf{K}}_{sa}(\mathbf{M}) - \varepsilon \Gamma_s(\mathcal{M})} \log T + O(1)$$

while for a non-critical state-action pair, $\mathbb{E}(B_{sa}(T)) = 0$.

5   Numerical experiments

In this section, we discuss numerical issues regarding `IMED-RL`.

Computing `IMED-RL` index   At each time step, we run the value iteration algorithm on $\widehat{\mathbf{M}}_t(\mathcal{A}(t))$ to compute the optimal bias and the associated potential function $\varphi_{\widehat{\mathbf{M}}_t(\mathcal{A}(t))}$. This task is standard. Once done, one must compute the value of the optimization problem $\underline{\mathbf{K}}_{sa}(t)$ which belongs to the category of convex optimization problem with linear constraint. Such problems have been studied under the name of *partially-finite convex optimization, e.g.* in Borwein and Lewis [1991]. It is possible to compute $\underline{\mathbf{K}}_{sa}(t)$ by considering the Legendre-Fenchel dual and one does not need to compute the optimal distribution to know the value of the optimization problem.

Proposition 2 (Index computation, Honda and Takemura [2015] Theorem 2). *Let (s, a) be in $\mathcal{S}_{\mathbf{M}}$, $M = m_{max}(s, a) + \max_{s' \in \mathcal{S}} \mathbf{b}^{\star, \mathbf{M}}(s)$, and $\gamma > \varphi_{\mathbf{M}}(\mathbf{r}(s, a) \otimes \mathbf{p}(\cdot|s, a))$, then*

$$\underline{\mathbf{K}}_{sa}(\mathbf{M}, \gamma) = \begin{cases} \max\limits_{0 \leqslant x \leqslant \frac{M}{M - \gamma}} \mathbb{E}_{\substack{R \sim \mathbf{r}(s, a) \\ S \sim \mathbf{p}(\cdot|s, a)}} \left[\log \left(M - \left(R + \mathbf{b}^{\star, \mathbf{M}}(S) - \gamma \right) x \right) \right] & \text{if } M > \gamma \\ +\infty & \text{otherwise} \end{cases}. \quad (19)$$

If $\gamma \leqslant \varphi_{\mathbf{M}}(\mathbf{r}(s, a) \otimes \mathbf{p}(\cdot|s, a))$, then $\underline{\mathbf{K}}_{sa}(\mathbf{M}, \gamma) = 0$.

In particular, this proposition 2 sometimes allows to write $\mathbf{K}_{sa}(t)$ almost in close form, *e.g.* when $\mathcal{F}_{s,a}$ defined in Asumptions 3 is a set of multinomials with unknown support (and only the upper bound m_{max} is known). In Appendix F, we discuss this numerical computation further.

Environments In different environments, we illustrate in Figure 2 and Figure 3 the performance of `IMED-RL` against the strategies `UCRL3` Bourel et al. [2020], `PSRL`Osband et al. [2013] and Q-learning (run with discount $\gamma = 0.99$ and optimistic initialization). As stated during the introduction, any finite communicating MDP can be turned into an ergodic one, since on such MDPs, any stochastic policy $\pi : \mathcal{S} \to \mathcal{P}(\mathcal{A}_s)$ with full support $\text{Supp}(\pi(s)) = \mathcal{A}_s$ is ergodic. Hence by mixing its transition $\mathbf{p}$ with that obtained from playing a uniform policy, formally $\mathbf{p}_\varepsilon(\cdot|s, a) = (1 - \varepsilon)\mathbf{p}(\cdot|s, a) + \varepsilon \sum_{a' \in \mathcal{A}_s} \mathbf{p}(\cdot|s, a')/|\mathcal{A}_s|$, for an arbitrarily small $\varepsilon > 0$ one obtain an ergodic MDP. In the experiments, we consider an ergodic version of the classical n-state river-swim environment, 2-room and 4-room with $\varepsilon = 10^{-3}$, and classical communicating versions ($\varepsilon = 0$).

Figure 1: The ergodic n-state *RiverSwim* MDP. In each of the n states, there are two actions `RIGHT` and `LEFT`. The left action is represented with a dashed line and the `RIGHT` with plain line. Rewards are located at the extremities of the MDP.

Figure 2: Average regret and quantiles (0.1 and 0.9) curves of algorithms on a standard communicating 6-states RiverSwim (left) and an ergodic 6-states RiverSwim (right).

n-states *RiverSwim* environment As illustrated by Figure 2, the performances of `IMED-RL` are particularly good and the regret of `IMED-RL` is below the regrets of all its competitors, even when the MDP is communicating only. This numerical performance grounds numerically the previous theoretical analysis. While using `IMED-RL` in communicating MDPs is not endorsed by our theoretically analysis, it is interesting to see how much this hypothesis amounts in the numerical performances of `IMED-RL`. We therefore ran an experiment on another classical environment, 2-rooms.

Figure 3: Average regret and quantiles (0.1 and 0.9) curves of algorithms (right) corresponding to learning on a 4-room (left) grid-world environment, with 20 states: the starting state is shown in red, and the rewarding state is shown in yellow. From the yellow state, all actions bring the learner to the red state. Other transitions are noisy as in a *frozen-lake* environment.

n-rooms environment   As illustrated by Figure 3, the performances of `IMED-RL` are particularly good, even surprisingly good, in this communicating only environment. Those experiments are a clue that the `IMED-RL` strategy may still reasonable, although not necessarily optimal in some communicating MDPs. All experiments take less than an hour to run on a standard CPU.

6   Conclusion

In this paper, we introduced `IMED-RL`, a numerically efficient algorithm to solve the average-reward criterion problem under the ergodic assumption for which we derive an upper bound on the regret matching the known regret lower bound. Further, its surprisingly good numerical performances in communicating only MDPs open the path to future work in MDPs that are communicating only.

References

R. Agrawal. Sample mean based index policies with O(log n) regret for the multi-armed bandit problem. *Advances in Applied Probability*, 27(4):1054–1078, 1995.

R. Agrawal, D. Teneketzis, and V. Anantharam. Asymptotically efficient adaptive allocation schemes for controlled iid processes: Finite parameter space. *IEEE Transactions on Automatic Control*, 34(3), 1989.

P. Auer and R. Ortner. Logarithmic online regret bounds for undiscounted reinforcement learning. In B. Schölkopf, J. C. Platt, and T. Hoffman, editors, *Proceedings of the 20th conference on advances in Neural Information Processing Systems*, NIPS '06, pages 49–56, Vancouver, British Columbia, Canada, dec 2006. MIT Press. ISBN 0-262-19568-2.

P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2-3):235–256, 2002.

D. P. Bertsekas and S. E. Shreve. *Stochastic Optimal Control (The Discrete Time Case)*. Academic Press, New York, 1978.

J. Borwein and A. Lewis. Duality relationships for entropy-like minimization problem. *SIAM Journal on Computation and Optimization*, 29(2):325–338, 1991.

H. Bourel, O. Maillard, and M. S. Talebi. Tightening exploration in upper confidence reinforcement learning. In *International Conference on Machine Learning*, pages 1056–1066. PMLR, 2020.

A. Burnetas and M. Katehakis. Optimal adaptive policies for Markov decision processes. *Mathematics of Operations Research*, pages 222–255, 1997.

A. N. Burnetas and M. N. Katehakis. Optimal adaptive policies for sequential allocation problems. *Advances in Applied Mathematics*, 17(2):122–142, 1996.

O. Cappé, A. Garivier, O.-A. Maillard, R. Munos, and G. Stoltz. Kullback–Leibler upper confidence bounds for optimal sequential allocation. *Annals of Statistics*, 41(3):1516–1541, 2013.

S. Filippi, O. Cappé, and A. Garivier. Optimism in reinforcement learning and Kullback-Leibler divergence. In *Proceedings of the 48th Annual Allerton Conference on Communication, Control, and Computing*, Monticello, US, 2010.

T. L. Graves and T. L. Lai. Asymptotically efficient adaptive choice of control laws incontrolled markov chains. *SIAM journal on control and optimization*, 35(3):715–743, 1997.

O. Hernández-Lerma and J.-B. Lasserre. *Discrete-Time Markov Control Processes*. Springer New York, 1996. doi: 10.1007/978-1-4612-0729-0. URL `https://hal.laas.fr/hal-02095866`.

J. Honda and A. Takemura. Non-asymptotic analysis of a new bandit algorithm for semi-bounded rewards. *Machine Learning*, 16:3721–3756, 2015.

T. Jaksch, R. Ortner, and P. Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 99:1563–1600, August 2010a. ISSN 1532-4435.

T. Jaksch, R. Ortner, and P. Auer. Near-optimal regret bounds for reinforcement learning. *The Journal of Machine Learning Research*, 11:1563–1600, 2010b.

O.-A. Maillard, R. Munos, and G. Stoltz. A finite-time analysis of multi-armed bandits problems with Kullback-Leibler divergences. In *Proceedings of the 23rd Annual Conference on Learning Theory*, Budapest, Hungary, 2011.

I. Osband, D. Russo, and B. Van Roy. (more) efficient reinforcement learning via posterior sampling. *Advances in Neural Information Processing Systems*, 26, 2013.

M. L. Puterman. *Markov Decision Processes — Discrete Stochastic Dynamic Programming*. John Wiley & Sons, Inc., New York, NY, 1994.

M. S. Talebi and O.-A. Maillard. Variance-aware regret bounds for undiscounted reinforcement learning in mdps. In *Algorithmic Learning Theory*, pages 770–805, 2018.

W. R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.