LEARNING DISTRIBUTIONS GENERATED BY SINGLE-LAYER ReLU NETWORKS IN THE PRESENCE OF ARBITRARY OUTLIERS

ABSTRACT

We consider a set of data samples such that a constant fraction of the samples are arbitrary outliers and the rest are the output samples of a single-layer neural network (NN) with rectified linear unit (ReLU) activation. The goal of this paper is to estimate the parameters (weight matrix and bias vector) of the NN assuming the bias vector to be non-negative. Our proposed method is a two-step algorithm. We first estimate the norms of the rows of the weight matrix and the bias vector using the gradient descent algorithm. Here, we also incorporate either the median or the trimmed mean based filters to mitigate the effect of the arbitrary outliers. Next, we estimate the angles between any two row vectors of the weight matrix. Combining the estimates of the norms and the angles, we obtain the final estimate of the weight matrix. Further, we prove that $O(\frac{1}{\epsilon p^4} \log \frac{d}{\delta})$ samples are sufficient for our algorithm to estimate the NN parameters within an error of ϵ with probability $1 - \delta$ when the probability of a sample being uncorrupted is p and the problem dimension is d. Our theoretical and simulation results provide insights on how the estimation of the NN parameters depends on the probability of a sample being uncorrupted, the number of samples, and the problem dimension.

1 INTRODUCTION

A fundamental challenge in machine learning and statistics is to estimate a high dimensional distribution given a set of observed data samples from the distribution. One solution technique is the deep generative method that models the unknown distribution as the output distribution of a neural network (NN) when the input of the NN is drawn from a known distribution like standard Gaussian (Goodfellow et al. (2014); Arjovsky et al. (2017); Radford et al. (2015); Kingma & Welling (2013); Van Oord et al. (2016)). Then, the unknown distribution is estimated by learning the NN parameters from the data samples. Several approaches like generative adversarial networks (Goodfellow et al. (2014); Arjovsky et al. (2017); Radford et al. (2015)), variational autoencoders (Kingma & Welling (2013)), and autoregressive models (Van Oord et al. (2016)) have been proposed to train the NN. However, they do not provide theoretical guarantees for the parameter learning. So, we address the problem of computing the sample complexity for the parameter estimation of a single-layer NN with rectified linear unit (ReLU) activation using a corrupted dataset. Here, the corrupted dataset refers to the model wherein every known output sample is an arbitrary outlier with a fixed probability and this model is relevant to the datasets impacted by a Byzantine. Motivated by the deep generative models, we consider the unsupervised learning framework, i.e., we assume the knowledge of the output samples but, the corresponding inputs are unknown and drawn from the standard Gaussian distribution.

We start with a brief review of the related literature in the next subsection.

1.1 RELATED WORKS

An important NN parameter estimation model is the supervised learning framework in which we estimate the parameters using noiseless output samples of a NN. A large class of algorithms for supervised learning is available in the literature, which relies on the stochastic gradient descent

(SGD)-based algorithms (Goel et al. (2018); Allen-Zhu et al. (2019); Chen et al. (2020); Oymak (2019)) or the gradient descent (GD)-based approach (Cao & Gu (2019); Du et al. (2019)). Some studies have also considered the unsupervised learning framework wherein the output labels corresponding to the input samples of the NN are unavailable (Mazumdar & Rawat (2018); Wu et al. (2019); Lei et al. (2020)). A major shortcoming of these works is that they assume that the available samples are not corrupted by noise or outliers. Therefore, we address an unsupervised learning framework wherein the output samples are potentially outliers with a fixed probability.

Several works in the literature have addressed the problem of corrupted samples in the context of supervised learning. The existing works have considered the learning of the parameters of a NN with ReLU activation using both SGD-based (Bakshi et al. (2019); Goel et al. (2019); Mukherjee & Muthukumar (2020)) and GD-based algorithms(Zhang et al. (2019); Frei et al. (2020); Vempala & Wilmes (2019)). However, to the best of our knowledge, the estimation of a NN in the presence of noise or outliers in the unsupervised learning framework has not been studied in the literature.

Our setting of unsupervised parameter estimation is also related to the area of robust statistics as described below. We recall that the goal of our paper is to estimate the parameters of a NN using corrupted output samples assuming that the input distribution is Gaussian. Mathematically, this problem is equivalent to estimating the parameters of a truncated Gaussian distribution (see Section 2 for details). The area of robust statistics also deals with the estimation of high dimensional distributions like Gaussian, Gaussian product, and Gaussian mixture distributions where a constant fraction of the samples were corrupted by noise (Huber (2004); Hampel et al. (2011); Lai et al. (2016); Diakonikolas et al. (2019); Diakonikolas & Kane (2019); Kane (2021)). However, in this paper, we consider parameter estimation from truncated Gaussian samples in the adversarial setting which has not been studied in the literature.

1.2 OUR CONTRIBUTIONS

In this subsection, we present our major contributions as the following.

- *Parameter Estimation (Sections 2 and 3):* We estimate the parameters (weight matrix and bias vector) of a single-layer NN with ReLU in the unsupervised learning framework where each output sample can potentially be an arbitrary outlier with a fixed probability. We propose an estimation algorithm that has two steps: (i) we estimate the row norms of the weight matrix and the bias vector using GD along with either the median or trimmed mean-based filters to mitigate the effect of arbitrary outliers, and (ii) we estimate the angles between any two row vectors of the weight matrix using a simple geometric result (Williamson & Shmoys, 2011, Lemma 6.7).

- *Theoretical guarantees (Section 4):* We show that the proposed algorithm requires $O(\frac{1}{\epsilon p^4} \log \frac{d}{\delta})$ samples to estimate the network parameters within an error of ϵ with probability $1 - \delta$ when the probability of a sample being uncorrupted is p. Here, $\epsilon > 0$ represents the estimation error.

- *Empirical validation (Section 5):* We evaluate the performance of our algorithm empirically in terms of its relation to the probability of a sample being uncorrupted, number of samples, and dimension (see Figs. 1 and 2). We see that our proposed filtering schemes ensure robustness to the arbitrary outliers. Also, the performance of our algorithm improves with the increase in the probability of a sample being uncorrupted and the number of samples, as expected. Further, we note that the estimation error increases slowly as the dimension grows for a fixed number of samples in the presence of arbitrary outliers. These observations from the empirical results are consistent with our theoretical results.

To summarize, in this paper, we estimate the parameters of a single-layer NN with ReLU activation in the presence of arbitrary outliers. The results obtained in this paper provide insights to generalize to a multi-layer NN with various activation functions and obtain generalization bounds.

2 LEARNING A NEURAL NETWORK MODEL USING CORRUPTED OUTPUT SAMPLES

We consider a single-layer ReLU NN. Let the weight matrix of the NN be denoted by $\mathbf{W} \in \mathbb{R}^{d \times k}$ and the bias vector by $\mathbf{b} \in \mathbb{R}^d$. The input to the NN is denoted by the latent variable $\mathbf{z} \in \mathbb{R}^k$. We

assume that the variable $\mathbf{z}$ is drawn from the standard Gaussian distribution. Thus, the output of the network is the random vector (RVe) $\mathbf{x} \in \mathbb{R}^d$ given by

$$\mathbf{x} = \text{ReLU}(\mathbf{W}\mathbf{z} + \mathbf{b}), \text{ where } \mathbf{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_k), \tag{1}$$

where $\mathcal{N}(\mathbf{0}, \mathbf{I}_k)$ denotes the Gaussian distribution with mean $\mathbf{0}$ and covariance matrix $\mathbf{I}_k$ which is the identity matrix of size $k \times k$. Let the distribution of the RVe $\mathbf{x}$ be denoted by $\mathcal{D}(\mathbf{W}, \mathbf{b})$. Then, our goal is to estimate the unknown parameters $\mathbf{W}$ and $\mathbf{b}$ of the distribution $\mathcal{D}(\mathbf{W}, \mathbf{b})$ using the knowledge of n output samples $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n$. Here, we assume that a fraction of the samples are arbitrary outliers. The distribution of the observed samples are modeled using the *Huber's p-contamination model* [1] defined as the following.

Definition 2.1 (Huber's p-Contamination Model Huber (1964)). The observed samples are said to be following Huber's contamination model if any given sample is drawn from the true distribution $\mathcal{D}$ and an arbitrary distribution $\mathcal{G}$ with probability p, and $1 - p$, respectively. In other words, the observed samples are drawn from the mixture distribution, $\mathcal{D}_p(\mathbf{W}, \mathbf{b})$ given by

$$\mathcal{D}_p(\mathbf{W}, \mathbf{b}) = p\mathcal{D}(\mathbf{W}, \mathbf{b}) + (1 - p)\mathcal{G}. \tag{2}$$

Note that if $\mathbf{b}$ has large negative values, then most of the output samples are zeros due to the ReLU operation. Further, if $\mathbf{W}$ is a zero matrix, then any negative coordinate of $\mathbf{b}$ cannot be identified as it is reset to zero after the ReLU operation. Hence, we assume $\mathbf{b}$ to be non-negative.

Our estimation problem is challenging due to two reasons: 1) ReLU operation is not invertible, and therefore, estimation of $\mathbf{W}$ and $\mathbf{b}$ utilizing maximum likelihood of the probability density function of RVe $\mathbf{x}$ is intractable; 2) the distribution of the corrupted samples is unknown. We tackle these issues using a new formulation combining the gradient decent algorithm and a filtering technique. The proposed algorithm is presented in the next section.

3 ESTIMATION OF PARAMETERS OF SINGLE-LAYER NN

To design our algorithm, we first note that only $\mathbf{W}\mathbf{W}^\mathsf{T}$ can be identified from $\mathcal{D}(\mathbf{W}, \mathbf{b})$. This is because of the fact that for any vector $\mathbf{b}$ and any matrices $\mathbf{W}_1$ and $\mathbf{W}_2$ satisfying $\mathbf{W}_1\mathbf{W}_1^\mathsf{T} = \mathbf{W}_2\mathbf{W}_2^\mathsf{T}$, we have $\mathcal{D}(\mathbf{W}_1, \mathbf{b}) = \mathcal{D}(\mathbf{W}_2, \mathbf{b})$ (Wu et al. (2019)). Therefore, our proposed algorithm estimates $\mathbf{W}\mathbf{W}^\mathsf{T} \in \mathbb{R}^{d \times k}$ and $\mathbf{b} \in \mathbb{R}^d$ from the observed samples from $\mathcal{D}_p(\mathbf{W}, \mathbf{b})$. Next, we note that (i, j)-th entry $(\mathbf{W}\mathbf{W}^\mathsf{T})(i, j)$ of the symmetric matrix $\mathbf{W}\mathbf{W}^\mathsf{T}$ is $\|\mathbf{W}(i, :)\|_2 \|\mathbf{W}(j, :)\|_2 \cos(\theta_{ij})$, where $\theta_{ij} = \theta_{ji}$ is the angle between vectors $\mathbf{W}(i, :)$ and $\mathbf{W}(j, :)$ which are the i-th and j-th rows of matrix $\mathbf{W}$, respectively. Also, note that the ℓ_p norm of a vector is given by $\|\mathbf{x}\|_p = (\sum_i |\mathbf{x}(i)|^p)^{1/p}$. Thus, we can construct the matrix $\mathbf{W}\mathbf{W}^\mathsf{T}$ using the row norms $\{\|\mathbf{W}(i, :)\|_2\}_{i=1}^d$ and angles $\{\theta_{ij}\}_{i,j=1}^d$.

Our estimation algorithm consists of two steps: 1) estimation of row norms of $\mathbf{W}$ and bias vector $\mathbf{b}$; and 2) estimation of angles between the row vectors of $\mathbf{W}$. We describe the two steps in the following subsections.

3.1 ESTIMATION OF ROW NORMS AND BIAS VECTOR

In this subsection, we estimate $\|\mathbf{W}(i, :)\|_2 \in \mathbb{R}$ and $\mathbf{b}(i) \in \mathbb{R}$, for $i \in [d] = \{1, 2, \ldots, d\}$. Suppose $\mathbf{x} \sim \mathcal{D}(\mathbf{W}, \mathbf{b})$. Its i-th coordinate can be written as

$$\mathbf{x}(i) = \text{ReLU}(\mathbf{W}(i, :)^\mathsf{T}\mathbf{z} + \mathbf{b}(i)), \tag{3}$$

where $\mathbf{W}(i, :)^\mathsf{T}\mathbf{z} + \mathbf{b}(i) \sim \mathcal{N}(\mathbf{b}(i), \|\mathbf{W}(i, :)\|_2^2)$. Thus, to compute $\mathbf{b}(i)$ and $\|\mathbf{W}(i, :)\|_2^2$, it is enough to consider the i-th entries of the observed samples. Also, in (3), the ReLU operator sets $\mathbf{x}(i)$ to zero if $\mathbf{W}(i, :)^\mathsf{T}\mathbf{z} + \mathbf{b}(i)$ is negative. Consequently, we estimate $\mathbf{b}(i)$ and $\|\mathbf{W}(i, :)\|_2^2$ using the positive entries of the observed samples. Hence, estimation of $\mathbf{b}(i)$ and $\|\mathbf{W}(i, :)\|_2$ is equivalent to estimating the parameters of a one-dimensional normal distribution using positive samples, i.e., the samples that belong to the set $\mathbb{R}_{>0} := \{\mathbf{x}(i) \in \mathbb{R} : \mathbf{x}(i) > 0\}$. We use $\mu^* = \mathbf{b}(i)$ and $\sigma^{*2} = \|\mathbf{W}(i, :)\|_2$ to denote the parameters of this one-dimensional normal distribution. The estimation of μ^* and σ^{*2} using corrupted samples is discussed next.

---

[1]Our algorithm and its analysis follow even if the outliers are not sampled from the same arbitrary distributions $\mathcal{G}$. However, we need to assume that all the true samples come from the same distribution $\mathcal{D}$.

Algorithm 1: Learning one-layer ReLU NN with outliers

Input: Samples $\mathbf{x}_1, \ldots, \mathbf{x}_n \in \mathbb{R}^d$
1 **for** $i \in [d]$ **do**
2      $\mathcal{X}_{>0} \leftarrow \{\mathbf{x}_m, m \in [n] : \mathbf{x}_m(i) > 0\}$
3      $\hat{\mathbf{v}} = \text{ProjGD}(\mathcal{X}_{>0})$
4      $\hat{\boldsymbol{\Sigma}}_{i,i} \leftarrow 1/\hat{\mathbf{v}}(1)$
5      $\hat{\mathbf{b}}(i) \leftarrow \max\{0, \hat{\mathbf{v}}(2)/\hat{\mathbf{v}}(1)\}$
6 **for** $i < j \in [d]$ **do**
7   Compute $\hat{\theta}_{ij}$ using (12)
8      $\hat{\boldsymbol{\Sigma}}(i,j) \leftarrow \sqrt{\hat{\boldsymbol{\Sigma}}(i,i)\hat{\boldsymbol{\Sigma}}(j,j)}\cos(\hat{\theta}_{ij})$
9      $\hat{\boldsymbol{\Sigma}}(j,i) \leftarrow \hat{\boldsymbol{\Sigma}}(i,j)$

Output: $\hat{\boldsymbol{\Sigma}} \in \mathbb{R}^{d \times d}$, $\hat{\mathbf{b}} \in \mathbb{R}^d$

Algorithm 2: ProjGD

Input: Samples $\mathcal{X}_{>0}$, Parameters T, γ_t, and n_b
1 Compute $\{\overline{\mathbf{x}_j(i)}\}_{j=1}^{n_b}$ from $\mathcal{X}_{>0}$ using (7)
2 $\tilde{\mathbf{g}}_\mathbf{x} \leftarrow \text{filter}\left(\{\overline{\mathbf{x}_j(i)}\}_{j=1}^{n_b}\right)$
3 $\mathbf{v}_0 \leftarrow [0 \quad 0]$
4 **for** $t = 1, 2, \ldots, T$ **do**
5      $\mu \leftarrow \mathbf{v}_{t-1}(2)/\mathbf{v}_{t-1}(1)$
6      $\sigma^2 \leftarrow 1/\mathbf{v}_{t-1}(1)$
7      $\tilde{\mathbf{g}}_\mathbf{z} \leftarrow \left[-(\breve{\sigma}^2 + \breve{\mu}^2)/2 \quad \breve{\mu}\right]^\mathsf{T}$ using (5) and (6)
8      $\tilde{\mathbf{g}}_t \leftarrow \tilde{\mathbf{g}}_\mathbf{x} + \tilde{\mathbf{g}}_\mathbf{z}$
9      $\tilde{\mathbf{v}}_t \leftarrow \mathbf{v}_{t-1} - \gamma_{t-1}\tilde{\mathbf{g}}_{t-1}$
10      $\mathbf{v}_t \leftarrow P(\tilde{\mathbf{v}}_t)$ using (10)

Output: $\mathbf{v}_T \in \mathbb{R}^2$

We determine the parameters of the univariate normal distribution using maximum likelihood estimation. For this, we define $\ell(\mu, \sigma; \mathbf{x}(i))$ as the negative log-likelihood that $\mathbf{x}(i) \sim \mathcal{N}(\mu, \sigma^2; \mathbb{R}_{>0})$ is drawn from the truncated normal distribution derived from $\mathcal{N}(\mu, \sigma^2)$ by bounding the random variable (RV) to the set of nonnegative real numbers. Since the maximum likelihood estimate minimizes the negative likelihood, the parameter estimates are given by $\arg\min_{\mu,\sigma} \ell(\mu, \sigma; \mathbf{x}(i))$.

Further, from Daskalakis et al. (2018), $\ell(\mu, \sigma; \mathbf{x}(i))$ is a convex function with respect to the reparameterization: $\mathbf{v} = [1/\sigma^2; \mu/\sigma^2] \in \mathbb{R}^2$. We use $\ell(\mathbf{v}; \mathbf{x}(i))$ to denote the negative log-likelihood after the reparameterization. Thus, the estimate of the new parameter $\mathbf{v} \in \mathbb{R}^2$ is given by $\arg\min_\mathbf{v} \bar{l}(\mathbf{v})$, where $\bar{\ell}(\mathbf{v}) = \mathbb{E}_{\mathbf{x}(i)}[\ell(\mathbf{v}; \mathbf{x}(i))]$ is the expected negative log-likelihood with respect to $\mathbf{x}(i)$.

The above optimization problem can be solved using a learning algorithm like GD or SGD. The SGD algorithm utilizes only one sample for the gradient computation which introduces large variance due to the stochasticity and low reliability in the presence of arbitrary outliers. Therefore, we use the GD algorithm that utilizes all the samples for the gradient.

To derive the GD algorithm, we compute the gradient of $\nabla\bar{\ell}(\mathbf{v}) = \mathbb{E}_{\mathbf{x},\mathbf{z}}[\mathbf{g}(i)]$ where

$$\mathbf{g}(i) = \mathbf{g}_\mathbf{x}(i) + \mathbf{g}_\mathbf{z}(i) = \left[\mathbf{x}^2(i)/2 \quad -\mathbf{x}(i)\right]^\mathsf{T} + \left[-\mathbf{z}^2(i)/2 \quad \mathbf{z}(i)\right]^\mathsf{T}. \tag{4}$$

Here, $\mathbf{x}(i) \sim \mathcal{N}(\mu^*, \sigma^{*2}; \mathbb{R}_{>0})$ and $\mathbf{z}(i) \sim \mathcal{N}(\mu, \sigma^2; \mathbb{R}_{>0})$. Also, μ^* and σ^{*2} are the parameters of the true distribution, and μ and σ^2 are functions of $\mathbf{v}$. In (4), $\mathbb{E}_\mathbf{z}[\mathbf{g}_\mathbf{z}(i)]$ admits a closed form expression (Johnson et al. (1995)), $\tilde{\mathbf{g}}_\mathbf{z} = \mathbb{E}_\mathbf{z}[\mathbf{g}_\mathbf{z}(i)] = \left[-(\breve{\sigma}^2 + \breve{\mu}^2)/2 \quad \breve{\mu}\right]^\mathsf{T}$. Here, we define

$$\breve{\mu} = \mathbb{E}[\mathbf{z}(i)|0 < \mathbf{z}(i) < \infty] = \mu + \frac{\phi(-\mu/\sigma)}{1 - \Phi(-\mu/\sigma)}\sigma, \tag{5}$$

$$\breve{\sigma}^2 = \text{Var}(\mathbf{z}(i)|0 < \mathbf{z}(i) < \infty) = \sigma^2\left(1 - \frac{\mu}{\sigma}\frac{\phi(-\mu/\sigma)}{1 - \Phi(-\mu/\sigma)} - \left(\frac{\phi(-\mu/\sigma)}{1 - \Phi(-\mu/\sigma)}\right)^2\right), \tag{6}$$

where $\phi(\cdot)$ and $\Phi(\cdot)$ denote the probability density function and the cumulative distribution function of the standard normal distribution, respectively. We also need $\mathbb{E}_\mathbf{x}[\mathbf{g}_\mathbf{x}(i)]$ to compute $\mathbb{E}_{\mathbf{x},\mathbf{z}}[\mathbf{g}(i)]$. Since the value of $\mathbb{E}_\mathbf{x}[\mathbf{g}_\mathbf{x}(i)]$ is not known, we use the sample mean to estimate $\mathbb{E}_\mathbf{x}[\mathbf{g}_\mathbf{x}(i)]$. For this, all the positive samples are partitioned into n_b batches. Let S_j be the j-th batch. We then compute the vector $\overline{\mathbf{x}_j(i)} \in \mathbb{R}^2$ as follows:

$$\overline{\mathbf{x}_j(i)} = \frac{1}{|S_j|}\left[\sum_{\mathbf{x}(i) \in S_j}\mathbf{x}(i)^2/2 \quad -\sum_{\mathbf{x}(i) \in S_j}\mathbf{x}(i)\right]^\mathsf{T}. \tag{7}$$

We then combine the n_b vectors $\{\overline{\mathbf{x}_j(i)}\}_{j=1}^{n_b}$ to estimate $\mathbb{E}_{\mathbf{x},\mathbf{z}}[\mathbf{g}(i)]$. Recall that the observed samples are from the mixture distribution $\mathcal{D}_p(\mathbf{W}, \mathbf{b})$. Therefore, to compute the expectation with respect to the true distribution $\mathcal{D}(\mathbf{W}, \mathbf{b})$, a filter is applied on this set of n_b vectors to mitigate the effect of the arbitrary outliers and obtain $\mathbb{E}_\mathbf{x}[\mathbf{g}_\mathbf{x}(i)]$. We consider two filters: median and trimmed mean.

1. *Median:* The median based filter possesses the following robustness property. Typically, a median is the value separating the higher half from the lower half of a given set of points. If more than half of a given set of points are in $[-M, M]$ for some $M > 0$, then their median must be in $[-M, M]$. Thus, the median of $\{\overline{\mathbf{x}_j(i)}\}_{j=1}^{n_b}$ is the vector computed either from all the true samples or outliers whose magnitudes are comparable to the true samples.

2. *Trimmed Mean:* The trimmed mean removes the vectors among the set of n_b vectors with relatively large and small values and computes the estimate of $\mathbb{E}_{\mathbf{x}}[\mathbf{g}_{\mathbf{x}}(i)]$ as the mean of the remaining vectors. Here, we use the parameter β to indicate the number of vectors to be discarded. This technique prunes the vectors $\overline{\mathbf{x}_j(i)}$, $j \in [n_b]$ that are computed from the batches with outliers having relatively high or low magnitudes.

Therefore, we obtain the gradient estimate as

$$\tilde{\mathbf{g}}(i) = \text{filter}\left(\left\{\overline{\mathbf{x}_j(i)}\right\}_{j=1}^{n_b}\right) + \left[(\breve{\sigma}^2 + \breve{\mu}^2)/2 \quad \breve{\mu}\right]^{\mathsf{T}}, \tag{8}$$

where *filter* is either median or trimmed mean, and $\breve{\mu}$ and $\breve{\sigma}^2$ are given in (5) and (6), respectively.

Having computed the gradient estimate, we next present the proposed GD algorithm. In the t-th iteration, the algorithm performs the following three steps:

1. *Gradient Computation Step:* In this step, the gradient $\tilde{\mathbf{g}}_t \in \mathbb{R}^2$ is computed from the observed positive samples using (8).

2. *Update Step:* The gradient computed in the previous step is used to perform the GD update:

$$\tilde{\mathbf{v}}_t = \mathbf{v}_{t-1} - \gamma_{t-1}\tilde{\mathbf{g}}_{t-1}, \tag{9}$$

where $\gamma_{t-1} > 0$ is the diminishing step size.

3. *Projection Step:* The gradient of $\bar{l}(\mathbf{v})$ is a strongly convex function of $\mathbf{v}$, if $\mathbf{v}$ belongs to a bounded region. To control the strong-convexity of the objective function, we *project* the update vector $\mathbf{v}$ into the domain $D_r = \{\mathbf{v} \in \mathbb{R}^2 : 1/r \leq \mathbf{v}(1) \leq r, |\mathbf{v}(2)| \leq r\}$. Thus, the projection is

$$P(\mathbf{v}) = [\min\{\max\{\mathbf{v}(1), 1/r\}, r\} \quad \min\{\max\{\mathbf{v}(2), -r\}, r\}]. \tag{10}$$

The GD algorithm is run for T iterations where T is the algorithm parameter. The overall algorithm is summarized in Algorithm 2.

In short, this subsection presented the first step of our algorithm that uses the GD algorithm to obtain the estimate of the bias vector and the row norms of the weight matrix. We next discuss the estimation of the angle between row vectors.

3.2 ESTIMATION OF ANGLES BETWEEN THE ROWS

To estimate θ_{ij}, we utilize the fact that the angle between any two vectors can be estimated from their inner products with a random Gaussian vector (Williamson & Shmoys, 2011, Lemma 6.7), i.e., for any two non-zero vectors $\mathbf{u}, \mathbf{v} \in \mathbb{R}^k$, the following holds:

$$\arccos\left(\frac{\langle \mathbf{u}, \mathbf{v}\rangle}{\|\mathbf{u}\|_2\|\mathbf{v}\|_2}\right) = \pi - 2\pi \cdot \mathbb{P}_{\mathbf{z} \sim \mathcal{N}(0, \mathbf{I}_k)}[\mathbf{u}^{\mathsf{T}}\mathbf{z} > 0 \text{ and } \mathbf{v}^{\mathsf{T}}\mathbf{z} > 0]. \tag{11}$$

Also, for the true samples, we have $\mathbf{x}(i) = \text{ReLU}(\mathbf{W}(i,:)^{\mathsf{T}}\mathbf{z} + \mathbf{b}(i)) \neq 0$ if $\mathbf{b}$ is non-negative and $\mathbf{W}(i,:)^{\mathsf{T}}\mathbf{z} > 0$. Thus, we estimate $\hat{\theta}_{ij}$ as given below:

$$\hat{\theta}_{ij} = \pi - 2\pi \left(\frac{1}{n}\sum_{m=1}^{n} \mathbb{1}(\mathbf{x}_m(i) > \hat{\mathbf{b}}(i))\mathbb{1}(\mathbf{x}_m(j) > \hat{\mathbf{b}}(j))\right), \tag{12}$$

where $\mathbb{1}(\cdot)$ denotes the indicator function and $\hat{\mathbf{b}}$ is the estimate of the bias vector computed in the previous step using the projected GD algorithm.

Combining the procedures in Sections 3.1 and 3.2, we obtain the overall estimation algorithm. The algorithm is summarized in Algorithm 1 where $\hat{\boldsymbol{\Sigma}}$ is the estimate of $\mathbf{W}\mathbf{W}^{\mathsf{T}}$. Here, Steps 1-5 estimate the row norms of $\mathbf{W}$ and $\mathbf{b}$, and Steps 6-9 estimate the angles between any two row vectors of $\mathbf{W}$.

We note that our algorithm is different from the unsupervised learning algorithm in Wu et al. (2019) in the following aspects. We do not rescale the unknown parameters (see Step 1 of Algorithm 2 in Wu et al. (2019)). We employ median or trimmed mean based filter to compute the full gradient and utilize the GD algorithm instead of SGD used in Wu et al. (2019).

4 THEORETICAL GUARANTEES FOR PARAMETER ESTIMATION

In this section, we provide our main result which characterizes the sample complexity required to achieve a given small error in parameter estimation. To arrive at the main result, we first present the error bounds for the two steps of Algorithm 1, which are described in Secs. 3.1 and 3.2, respectively.

The following proposition provides the estimation error bounds for the first step, i.e., the estimation of the bias vector $\mathbf{b}$ and the norms of the row vectors of $\mathbf{WW}^\mathsf{T}$. It shows that we can estimate $\mathbf{b}(i)$ within an additive error of $\Xi\|\mathbf{W}(i,:)\|$ and $\mathbf{\Sigma}(i,i)$ within an additive error of $\Xi\|\mathbf{W}(i,:)\|^2$ where Ξ decreases with both the number of samples and the total number of iterations T.

Proposition 4.1. *Suppose we initialize the projected gradient step (Algorithm 2) such that $\|\mathbf{v}_0 - \mathbf{v}^*\| = V$ and choose the step size $\gamma_t = \gamma$ and the number of iterations as T. Then, there exists $\gamma > 0$ such that for any $\delta \in (0,1)$, the output $(\hat{\mathbf{\Sigma}}(i,i), \hat{\mathbf{b}}(i))$ of the projected GD step of our algorithm for any $i \in [d]$ satisfies*

$$|\hat{\mathbf{\Sigma}}(i,i) - \|\mathbf{W}(i,:)\|^2| \leq \Xi\|\mathbf{W}(i,:)\|^2 \tag{13}$$

$$|\hat{\mathbf{b}}(i) - \mathbf{b}(i)| \leq \Xi\|\mathbf{W}(i,:)\|, \tag{14}$$

with probability at least $1 - \delta$ if the number of data samples $n \geq \frac{1}{p^2(p\Psi_\epsilon - 1/2)^2} \log \frac{1}{\delta}$. Here, the error bound is $\Xi = V\left(1 - \frac{L}{\eta+L}\right)^T + \frac{2\epsilon(L+\eta)}{L\eta}$ with $\eta, L > 0$ being constants that depend only on the parameter r. Also, p is the probability of a sample being uncorrupted and $\Psi_\epsilon \in [1/2p, 1]$ is such that $O(\epsilon^3) \leq \Psi_\epsilon \leq O(\sqrt{\epsilon})$ with $\epsilon > O\left(p^{-1/3}\right)$ where the order constants depend only on r.

The following proposition bounds the estimation error in the second step, i.e., the estimation of the angle between any two row vectors $\mathbf{W}(i,:)$ and $\mathbf{W}(j,:)$ (where $i \neq j \in [d]$). The result shows that we can estimate θ_{ij} within an additive error of Ξ.

Proposition 4.2. *Assume that (13) and (14) hold. Then, for a fixed pair of $i \neq j \in [d]$ and $\delta \in (0,1)$, the estimate $\hat{\theta}_{ij}$ of Algorithm 1 satisfies*

$$|\cos\hat{\theta}_{ij} - \cos\theta_{ij}| < \sqrt{2}\pi p(p\Psi_\epsilon - 1/2) + 3\pi(1-p) + 2\pi(2-p)\Xi, \tag{15}$$

with probability at least $1 - \delta$ if the number of data samples $n \geq \frac{1}{p^2(p\Psi_\epsilon - 1/2)^2} \log \frac{1}{\delta}$. Here, the error bound is $\Xi = V\left(1 - \frac{L}{\eta+L}\right)^T + \frac{2\epsilon(L+\eta)}{L\eta}$ with $\eta, L > 0$ being constants that depend only on the parameter r. Also, p is the probability of a sample being uncorrupted and $\Psi_\epsilon \in [1/2p, 1]$ is such that $O(\epsilon^3) \leq \Psi_\epsilon \leq O(\sqrt{\epsilon})$ with $\epsilon > O\left(p^{-1/3}\right)$ where the order constants depend only on r.

Combining Propositions 4.1 and 4.2, we next present the sample complexity needed to achieve a small parameter estimation error. Specifically, the diagonal entries, $\mathbf{\Sigma}(i,i)$, for $i \in [d]$ are obtained from Proposition 4.1. Further, the off-diagonal entries of $\mathbf{\Sigma}$ are obtained by combining the Propositions 4.1 and 4.2 to obtain the final result as follows:

Theorem 4.3. [2] *Suppose we initialize the projected gradient step (Algorithm 2) such that $\|\mathbf{v}_0 - \mathbf{v}^*\| = V$ and choose the step size $\gamma_t = \gamma$ and the number of iterations as T. Then, there exists $\gamma > 0$ such that for $\delta \in (0,1)$, the output of Algorithm 1, $(\hat{\mathbf{\Sigma}}, \hat{\mathbf{b}})$ satisfies*

$$\|\hat{\mathbf{\Sigma}} - \mathbf{WW}^\mathsf{T}\|_F \leq \left(\sqrt{2}\pi p(p\Psi_\epsilon - 1/2) + \pi(2-p)(3+2\Xi)\right)\|\mathbf{W}\|_F^2 \tag{16}$$

$$\|\hat{\mathbf{b}} - \mathbf{b}\| \leq \Xi\|\mathbf{W}\|_F, \tag{17}$$

with probability at least $1 - \delta$ if the number of data samples $n = O(\frac{1}{\epsilon p^4} \log \frac{d}{\delta})$. Here, p is the probability of a sample being uncorrupted and $\Psi_\epsilon \in [1/2p, 1]$ is such that $O(\epsilon^3) \leq \Psi_\epsilon \leq O(\sqrt{\epsilon})$ with $\epsilon > O\left(p^{-1/3}\right)$ where the order constants depend only on r.

---

[2]We have included the proofs in the full version in the supplementary material.

We note that in Propositions 4.1 and 4.2, and Theorem 4.3, η, L and the other order constants depend on the parameter $r > 0$. Recall that the parameter r is required for the convexity region D_r and we can choose r to be a large constant. Thus, r is a relatively insensitive parameter which does not require any hand-tuning.

The two terms in the error bound in Theorem 4.3 can be interpreted as the following. The first term $\left(1 - \frac{L}{\eta+L}\right)^T V$ captures the convergence error due to the GD algorithm. For any upper bound on the convergence error $\Omega > 0$, Algorithm 1 runs in time $(\log \Omega - \log V)/\log\left(\frac{\eta}{\eta+L}\right)$. This relation shows that smaller convergence errors require more iterations. The second term $\frac{2\epsilon(L+\eta)}{L\eta}$ captures the error due to the gradient computed using the observed samples. Two factors contribute to this error: 1) difference between the (true) sample mean and the true mean, and 2) the arbitrary outliers. Also, the difference between the sample mean and true mean decreases with the number of samples. Consequently, for smaller error ϵ, we need a large number of samples $n = O(\frac{1}{\epsilon p^4} \log \frac{d}{\delta})$. We also note that the lower bound on ϵ decreases with p.

As the probability of a sample being uncorrupted p reduces, we observe that the error bound in (16) becomes larger as expected. Also, as the probability of a sample being uncorrupted decreases, the number of samples n required for the error bound increases. Moreover, the obtained error bounds increase with the problem dimension for a fixed number of samples.

Our results are also comparable with the existing error bounds for ReLU parameter estimation without outliers from (Wu et al., 2019, Theorem 1). Specifically, if there are no outliers, for any $\zeta, \delta \in (0, 1)$, the number of samples $n = O(\frac{1}{\zeta^2} \log \frac{d}{\delta})$ are sufficient for the SGD algorithm in Wu et al. (2019) to achieve the following error bounds with probability at least $1 - 2\delta$,

$$\|\hat{\mathbf{\Sigma}} - \mathbf{W}\mathbf{W}^\mathsf{T}\|_F \leq \zeta\|\mathbf{W}\|_F^2 \text{ and } \|\hat{\mathbf{b}} - \mathbf{b}\| \leq \zeta\|\mathbf{W}\|_F. \tag{18}$$

Comparing the above bounds with (16) and (17), we observe that our bounds are larger due to the presence of arbitrary outliers. In particular, the first term $V\left(1 - \frac{L}{\eta+L}\right)^T < 1$ in our error bounds is similar to $\zeta < 1$ in (18). However, the second error term $\frac{2\epsilon(L+\eta)}{L\eta}$ is not present in (18). Additionally, in (16), the extra term $3\pi(2 - p)$ further increases the bound compared to the error bound in (18). Further, our sample complexity depends on the probability of a sample being uncorrupted p and the second error term ϵ whereas the complexity in (Wu et al., 2019, Theorem 1) depends on the square of the convergence error term ζ in their sample complexity. Also, when there is no outlier ($p = 1$), the two sample complexities do not match because the two results deal with different algorithms (GD and SGD).

5 SIMULATION RESULTS

In this section, we provide numerical results to verify the performance of our algorithm. In our setup, the columns of $\mathbf{W}$ are chosen as the left singular vectors of random matrices from the standard Gaussian distribution. For $\mathbf{b}$, we use a random vector from the standard normal distribution whose negative values are replaced with zeros. The mixture of samples are generated such that a sample comes from $\mathcal{D}(\mathbf{W}, \mathbf{b})$ with probability p and from $\mathcal{G} = \mathcal{N}(5, 1)$ with probability $1 - p$. The hyperparameters in our proposed algorithm are set as $r = 3$ and $\gamma_t = \frac{1}{0.1t}$. Also, we choose the total number of GD iterations T to be $|\mathcal{X}_{>0}|/100$ where $|\mathcal{X}_{>0}|$ is the number of positive output samples.

We compute two error metrics from the estimated parameters and the ground truth, $\|\hat{\mathbf{\Sigma}} - \mathbf{W}\mathbf{W}^\mathsf{T}\|_F/\|\mathbf{W}\|_F^2$ and $\|\hat{\mathbf{b}} - \mathbf{b}\|_2/\|\mathbf{W}\|_F$. Also, we compare our algorithm with two other schemes: oracle scheme (estimation using the true samples only), and scheme without filter.

The results are shown in Figs. 1 and 2, and Table 1, and the observations from them are as follows.

Effect of filters: From Fig. 2, we observe that the GD schemes perform better than the corresponding SGD schemes. Further, the performance is improved when we use median based filter along with GD or SGD (for instance, as seen by comparing the performances of GD without Filter and GD with Median in Fig. 1). Thus, the filter ensures that the effect of the outliers is reduced, and the curves are

Figure 1: Comparison of the different GD schemes as a function of p (first column), n (second column), and d (third column). The figures indicate that utilizing the filters improves the performance of GD algorithm for mixture of samples.

Figure 2: Comparison of GD and SGD schemes as a function of p (first column), n (second column), and d (third column). We infer that SGD is more sensitive to corrupted samples compared to GD.

closer to the Oracle GD scheme. Finally, from Fig. 1, we also infer that the median-based approach performs slightly better than the trimmed mean-based approach.

Dependence on probability of a sample being uncorrupted p: The variation in the error estimation as a function of p is shown in Figs. 1a and 2a. The performance of the proposed schemes improve with p, as expected. This trend is because as p increases, the fraction of outliers in the observed samples decreases, which leads to better performance. Note that the oracle schemes assume the knowledge of true samples. Thus, their performance does not change with p. On the contrary, the performance of the schemes without filters and SGD schemes with filter do not have a monotonic behavior with

Table 1: Runtime of various schemes when $p = 0.95$, $n = 20000$, and $d = 5$. The table indicates that SGD schemes are faster than their GD counterparts.

Scheme	Oracle	Without Filter	With Median	With Trimmed Mean
GD	16.95 s	17.73 s	34.44 s	60.78 s
SGD	1.24 s	1.60 s	2.11 s	3.62 s

p. This observation shows that these schemes are not able to handle the outliers effectively. Further, all the schemes converge to the corresponding oracle schemes when $p = 1$.

Dependence on number of samples n: Figs. 1b and 2b show how the estimation error of different schemes varies with n. We observe that the parameter estimation errors computed using Oracle SGD and Oracle GD schemes decrease as the number of samples increases. This trend is because the oracle schemes consider only the true samples. Also, the Oracle GD scheme performs better than the Oracle SGD scheme. Further, the estimation errors computed using our proposed schemes with median and trimmed mean based filters perform better than GD without filter. Hence, the filters mitigate the effect of arbitrary outliers and having more samples reduces the estimation errors.

Dependence on dimension d: In Figs. 1c and 2c, we plot the error in different schemes as a function of the dimension d. We note that due to the presence of arbitrary outliers, the errors increase as the dimension increases for GD without filter. Further, we observe a performance improvement using our proposed schemes with median and trimmed mean-based filters compared to the other benchmarking schemes, supporting our previous conclusions that the filters mitigate the effect of outliers. However, we observe a slow increase in the parameter estimation errors using our proposed schemes with median and trimmed mean based filters as we increase the dimension for fixed number of samples. We observe that the errors when using the oracle schemes also increase slowly as the dimension is increased (Wu et al. (2019)).

Comparison of runtimes: From Table 1, we observe that the SGD schemes run faster than their GD counterparts. This is because the SGD utilizes only one sample for the gradient whereas GD utilizes all the samples for the gradient. Further, the usage of median and trimmed mean based filters along with SGD or GD increases their computation times. However, we reiterate that using the GD scheme with filters offers the best performance in terms of error (see Fig. 2). Further, the runtimes of the trimmed mean-based schemes are significantly higher than those of the median-based schemes.

To summarize, from our results, we conclude that GD schemes offer better performance than the SGD schemes. Also, we deduce that compared to the trimmed mean-based scheme, the median-based filter is computationally more efficient while offering similar or lower estimation error. Moreover, the median-based scheme is parameter free (the trimmed mean depends on the parameter β) and enjoys strong theoretical guarantees (see Theorem 4.3). Overall, the median-based GD algorithm is the most effective approach to estimate the NN parameters in the presence of the outliers and performs slightly better than trimmed mean-based GD algorithm. Further, we observe that GD schemes with filters perform better than Oracle SGD scheme.

6 CONCLUSION

In this paper, we proposed an algorithm for estimation of the parameters of a single-layer ReLU neural network from the truncated Gaussian samples where each sample was assumed to be an arbitrary outlier with a fixed probability. Our only assumption was that the bias vector was non-negative. We derived a GD-based algorithm for parameter estimation and incorporated filters to handle the outliers. We analyzed the sample complexity of the proposed algorithm in terms of the parameter estimation error. The efficacy of our approach was also demonstrated using numerical experiments. Removing the non-negativity assumption on the bias vector is a promising direction for future work. Also, extending our results to multi-layer neural networks is also an interesting problem to consider in the future.

We provide our code for reference in the supplementary material along with a *read me* file for instructions.

REFERENCES

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *International Conference on Machine Learning*, pp. 242–252. PMLR, 2019.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International Conference on Machine Learning*, pp. 214–223. PMLR, 2017.

Ainesh Bakshi, Rajesh Jayaram, and David P Woodruff. Learning two layer rectified neural networks in polynomial time. In *Conference on Learning Theory*, pp. 195–268. PMLR, 2019.

Yuan Cao and Quanquan Gu. Tight sample complexity of learning one-hidden-layer convolutional neural networks. *arXiv preprint arXiv:1911.05059*, 2019.

Sitan Chen, Adam R Klivans, and Raghu Meka. Learning deep ReLU networks is fixed-parameter tractable. *arXiv preprint arXiv:2009.13512*, 2020.

Constantinos Daskalakis, Themis Gouleakis, Chistos Tzamos, and Manolis Zampetakis. Efficient statistics, in high dimensions, from truncated samples. In *2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS)*, pp. 639–649. IEEE, 2018.

Ilias Diakonikolas and Daniel M Kane. Recent advances in algorithmic high-dimensional robust statistics. *arXiv preprint arXiv:1911.05911*, 2019.

Ilias Diakonikolas, Gautam Kamath, Daniel Kane, Jerry Li, Ankur Moitra, and Alistair Stewart. Robust estimators in high-dimensions without the computational intractability. *SIAM Journal on Computing*, 48(2):742–864, 2019.

Simon Du, Jason Lee, Haochuan Li, Liwei Wang, and Xiyu Zhai. Gradient descent finds global minima of deep neural networks. In *International Conference on Machine Learning*, pp. 1675–1685. PMLR, 2019.

Spencer Frei, Yuan Cao, and Quanquan Gu. Agnostic learning of a single neuron with gradient descent. *arXiv preprint arXiv:2005.14426*, 2020.

Surbhi Goel, Adam Klivans, and Raghu Meka. Learning one convolutional layer with overlapping patches. In *International Conference on Machine Learning*, pp. 1783–1791. PMLR, 2018.

Surbhi Goel, Sushrut Karmalkar, and Adam Klivans. Time/accuracy tradeoffs for learning a ReLU with respect to gaussian marginals. *arXiv preprint arXiv:1911.01462*, 2019.

Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

Frank R Hampel, Elvezio M Ronchetti, Peter J Rousseeuw, and Werner A Stahel. *Robust statistics: The approach based on influence functions*, volume 196. John Wiley & Sons, 2011.

Peter J. Huber. Robust Estimation of a Location Parameter. *The Annals of Mathematical Statistics*, 35(1):73 – 101, 1964.

Peter J Huber. *Robust statistics*, volume 523. John Wiley & Sons, 2004.

Norman L Johnson, Samuel Kotz, and Narayanaswamy Balakrishnan. *Continuous univariate distributions, volume 1*, volume 289. John wiley & sons, 1995.

Daniel M Kane. Robust learning of mixtures of Gaussians. In *Proceedings of the 2021 ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pp. 1246–1258. SIAM, 2021.

Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Kevin A. Lai, Anup B. Rao, and Santosh Vempala. Agnostic estimation of mean and covariance. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pp. 665–674, 2016. doi: 10.1109/FOCS.2016.76.

Qi Lei, Jason Lee, Alex Dimakis, and Constantinos Daskalakis. SGD learns one-layer networks in WGANs. In *International Conference on Machine Learning*, pp. 5799–5808. PMLR, 2020.

Arya Mazumdar and Ankit Singh Rawat. Representation learning and recovery in the ReLU model. *arXiv preprint arXiv:1803.04304*, 2018.

Anirbit Mukherjee and Ramchandran Muthukumar. Guarantees on learning depth-2 neural networks under a data-poisoning attack. *arXiv preprint arXiv:2005.01699*, 2020.

Samet Oymak. Stochastic gradient descent learns state equations with nonlinear activations. In *Conference on Learning Theory*, pp. 2551–2579. PMLR, 2019.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Aaron Van Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *International Conference on Machine Learning*, pp. 1747–1756. PMLR, 2016.

Santosh Vempala and John Wilmes. Gradient descent for one-hidden-layer neural networks: Polynomial convergence and SQ lower bounds. In *Conference on Learning Theory*, pp. 3115–3117. PMLR, 2019.

David P Williamson and David B Shmoys. *The design of approximation algorithms*. Cambridge university press, 2011.

Shanshan Wu, Alexandros G Dimakis, and Sujay Sanghavi. Learning distributions generated by one-layer ReLU networks. *Advances in Neural Information Processing Systems*, 32:8107–8117, 2019.

Xiao Zhang, Yaodong Yu, Lingxiao Wang, and Quanquan Gu. Learning one-hidden-layer ReLU networks via gradient descent. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1524–1534. PMLR, 2019.