Interesting Object, Curious Agent: Learning Task-Agnostic Exploration

Abstract

Common approaches for task-agnostic exploration learn tabula-rasa –the agent assumes isolated environments and no prior knowledge or experience. However, in the real world, agents learn in many environments and always come with prior experiences as they explore new environments. Exploration is a lifelong process. In this paper, we propose a paradigm change in the formulation and evaluation of task-agnostic exploration. More specifically, in this setup, the agent first *learns to explore* across many environments without any extrinsic goal in a task-agnostic manner. Later on, the agent effectively transfers the learned *exploration policy* to better explore new environments when solving tasks. In this context, we evaluate several baseline exploration strategies and present a simple yet effective approach to learning task-agnostic exploration policies. Our key idea is that there are two components of exploration: (1) an agent-centric component encouraging exploration of unseen parts of the environment based on an agent's belief; (2) an environment-centric component encouraging exploration of inherently interesting objects. We show that our formulation is effective and provides the most consistent exploration across several training-testing environment pairs. We also introduce benchmarks and metrics for the evaluation task-agnostic exploration strategies.

1 Introduction

Exploration is one of the key unsolved problems in building intelligent agents capable of behaving like humans. In reinforcement learning (RL), exploration is usually studied under two different settings. The first is task-driven exploration, where the reward is well-defined and the agent's goal is to explore in order to maximize long-term rewards. However, in real life, external rewards are either sparse or unknown altogether. In this setting, exploration is task-agnostic: given a new environment, the agent has to explore it in absence of any external reward. Common approaches to encourage task-agnostic exploration use intrinsically motivated rewards such as prediction curiosity [35, 46], empowerment [38], or visitation counts [4, 34]. But does this setup represent how humans explore?

We argue that the commonly-used task-agnostic exploration setup is unrealistic, both from practical and academic viewpoints. This setup assumes environments in isolation and agents exploring tabula-rasa, i.e., with no prior knowledge or experience. By contrast, we as humans do not learn from one environment in isolation and we do not throw away our past knowledge every time we encounter a new environment [14]. Exploration is rather a lifelong process: every time we encounter new environments, we use our prior knowledge and experience to develop new efficient exploration strategies. In this paper, we view the exploration problem from a continual learning lens. More specifically, in this setup, the learning agent interacts with one or many environments without any extrinsic goal. At this time, the agent *learns to explore* the environments. Later on, the agent effectively transfers the learned *exploration policy* to explore new environments, rather than exploring the new environment tabula-rasa.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: **Change-Based Exploration Transfer.** We train a task-agnostic exploration agent that can transfer to unseen environments. Here the agent learns that keys are interesting, as they allow further interaction with the environment (opening doors). Later, when tasked with reaching a box behind a door, the agent starts by picking up the key.

A key question in learning how to explore is what to learn and how to transfer prior knowledge from one environment to another. Most existing task-agnostic exploration approaches, such as visitation counts, curiosity, or empowerment, define intrinsic rewards in an *agent-centric* manner: they encourage exploration of unseen parts of the environment based on the agent's own belief. In these approaches, exploration is driven by what the agent knows about the world. However, most do not make a distinction between what the agent believes it is interested in and states that would make any agent interested. For example, if the agent uses a visitation count model and has seen many objects of one kind in one environment, it would not explore the same type of objects again in a new environment. This seems to be in stark contrast to how humans, especially babies, explore. Consider a switch with a bell sign. Even though we might have pressed hundreds of doorbell switches (and even this instance), we are still attracted to press it. Some objects in the world just demand curiosity. We argue that apart from an 'agent-centric' component, there is an 'environment-centric' component to exploration, which can be learned from prior knowledge and experiences.

In this paper, we propose a paradigm change to move away from stand-alone isolated task-agnostic environment exploration to a more realistic multi-environment transfer-exploration setup[1]. We show how to learn exploration policies both from single- and multi-environment interaction, and how to transfer them to unseen environments. This transfer-exploration setup allows agents to use prior experiences for learning task-agnostic exploration. We observe that these approaches were designed for tabula-rasa exploration and hence only explore in an agent-centric manner. They fail to capture the inherent interestingness of some environment components. With this insight, we propose Change-Based Exploration Transfer (C-BET), a simple yet effective approach learning joint agent-centric and environment-centric exploration. The key idea is for an agent to seek out both surprises (unseen areas) and high-impact (interesting) components of the environment. The experiments show that C-BET (a) learns more effectively when placed in a multi-environment setup, and (b) either outperforms or performs competitively with prior methods across several unseen testing environments. We hope this paper will inspire exploration research to focus more on learning from multiple environments and transferring experiences rather than tabula-rasa exploration.

2 Preliminaries and Related Work

We consider environments governed by Markov Decision Processes (MDPs). In MDPs, an agent receives observations s from the environment and selects actions a according to a policy $\pi(a|s)$. In turn, the environment changes, providing a new observation s' and a reward r. Through environment interaction, the agent collects episodes, i.e., a sequence of states, actions and rewards $(s_t, a_t, r_t)_{t=1...T}$. The goal of RL is to learn a policy maximizing the sum of rewards during episodes. In this setting, exploration poses many questions. If the environment provides sparse or no rewards, what should the agent look for? When should the agent act greedily with respect to the rewards it has already found and stop looking for more? In the history of RL, different approaches have been proposed to tackle these questions. On one hand, we find classic single-environment approaches ranging from intrinsic motivation with visitation counts [2, 4, 13, 26, 52], optimism [1, 5, 25, 27, 31], or curiosity [7, 24, 35, 44, 48, 50], to bootstrapping [12, 33] or empowerment [29, 38]. On the other hand, we find approaches to incrementally learn tasks, such as transfer learning [57], continual learning [28], curriculum learning [32], and meta learning [37]. Below, we review approaches closely related to our method.

---

[1]While it can be argued that the real world has no explicit distinction between training and testing, we use this dichotomy only for the purpose of evaluation.

Exploration Training

Figure 2: **C-BET pre-training.** Our agent interacts with environments and learns using intrinsic rewards computed from state and change counts.

Exploration Transfer

Figure 3: **Our transfer paradigm.** The pretrained exploration policy is fixed and guides task-specific policy learning in new environments.

Intrinsic motivation. Exploration strategies relying on intrinsic rewards date back to Schmidhuber [46], who proposed to encourage exploration by visiting hard-to-predict states. More recently, the idea of auxiliary rewards to make up for the lack of external rewards has been extensively studied in RL, supported by evidence from psychology and neuroscience [20]. Several intrinsic rewards have been proposed, ranging from visitation count bonuses [4, 52] to bonuses based on prediction error of some quantity. For example, the agent may learn a dynamics model and try to predict the next state [24, 35, 47, 50]. By giving a bonus proportional to the prediction error, the agent is incentivized to explore unpredictable states. Schultheis et al. [48], instead, proposed to learn intrinsic rewards function by maximizing extrinsic rewards by meta-gradient.

However, in these approaches exploration is agent-centric, i.e., based on an agent's belief such as the forward model error. In contrast, with this work we propose additionally learning *environment-centric* exploration policies. C-BET neither requires a model nor knowledge of extrinsic rewards. Instead, it encourages the agent to perform actions causing *interesting changes* to the environment. We should note that while Raileanu and Rocktäschel [36] proposed a similar approach, their exploration policy lacks the transfer component and also requires learned models.

Transfer learning. The idea of agents capable of incrementally learning tasks is well-known in the field of machine learning, with the first approach dating back to the 90s' [39, 40, 55]. In RL, recent methods have focused on policy and feature transfer. In the former, a pre-trained agent (teacher) is used to transfer behaviors to a new agent (student). Examples include policy distillation, where the student is trained to minimize the Kullback-Leibler divergence to the teacher [43] or to multiple teachers at the same time [54]. Alternative approaches, instead, directly reuse policies from source tasks to build the student policy [3, 17, 21]. In feature transfer, during a pre-learned state representation is used to encourage exploration when tasks are presented to the agent [22, 58]. Similar to transfer RL, continual RL studies how learning on one or more tasks can help accelerate learning on different tasks, and how to prevent catastrophic forgetting [28, 41, 49]. Meta RL, instead, tries to exploit underlying common structures between tasks to learn new tasks more quickly [18, 37].

However, the setup in these approaches is not task-agnostic, i.e., task-specific policies are transferred rather than exploration policies. For example, after learning a policy maximizing the rewards of one task, the agent starts exploring guided by the same policy as a second task is given. Transfer is task-centric rather than task-agnostic and environment-centric. Consequently, if tasks are too dissimilar information cannot be reused, even if the environments are similar. By contrast, in this work we propose learning task-agnostic exploration from one or many environments and show transfer to unseen environments. We should note that while Pathak et al. [35] did demonstrate fine-tuning on different maze maps, their focus and large-scale evaluations remain on tabula-rasa exploration.

3 Learning to Explore

Our goal is to decouple the environment-centric nature of exploration from its agent-centric component. Contrary to prior methods, we propose first learning an environment-centric exploration policy and transferring it to unseen environments. C-BET's policy is driven by the inherent interestingness of states and is learned over time via interaction. First, during a pre-training phase, the agent interacts with many environments without any tasks and learns an exploration policy. Then, when new environments and tasks are presented, the agent uses the previously learned policy to explore more efficiently and learn task-specific policies. C-BET's key components are (1) the introduction of a novel intrinsic reward and the learning of a policy to disentangle exploration from exploitation, and (2) the use of such policy to help exploration for new tasks. Figures 2 and 3 summarize our framework.

Turn Left **Turn Right** **Move Forward** **Pick**

$\frac{1}{\sqrt{N(s')}}$

$\frac{||s-s'||^2}{\sqrt{N(s')}}$

$\frac{1}{\sqrt{N(s')N(c)}}$

The agent is facing down and has collected samples acting randomly.

Figure 4: **Intrinsic reward visualizations.** Brighter color denotes higher reward. In this gridworld with a key and a door, observations are full and cells are encoded by an integer depending on its content. Considering only state counts (top), the reward does not provide useful information; going to the corners is rewarded more than picking up the key. Considering the L2 norm of state changes (middle), the agent is biased in favor of moving, because its position is encoded with the highest value in the observation space. The resulting policy will prefer to navigate the grid without picking up the key. In contrast, for C-BET's intrinsic reward (bottom), picking up the key gets the highest reward.

3.1 Interestingness of State-Action Pairs

The natural world is filled with states or scenarios that are inherently interesting and our goal is to capture this inherent interestingness via intrinsic rewards. In this paper, we propose adding an environment-centric component of interestingness to the existing agent-centric component of surprise. Specifically, we hypothesize that the environment can *change* on interaction, and the changes are *rare* are inherently interesting. That is, we penalize actions not affecting the environment, and favor actions producing rare changes. For instance, moving around, bumping into walls, or trying to open locked doors without keys all result in no change and thus will be of low interest.

We also want to keep the agent-centric component in exploration –that is, the exploration policy should look for surprises or unseen states. Therefore, we further reward actions leading to less-visited states. By combining these two components, the resulting interest-based reward is defined as

$$i(s, a, s') = 1/\sqrt{N(c)N(s')}, \tag{1}$$

where $c(s, a, s')$ defines the *change* of a transition (s, a, s') and N denote a (pseudo)counts of changes and states. This quantity is high for actions leading to rare states (agent-centric) and rare changes (environment-centric) in the environment suggesting their interestingness. Figure 4 empirically shows the effectiveness of this quantity. In Section 4 we discuss different change encodings.

3.2 Exploration Learning

In this phase, we want to learn task-agnostic exploration policies from interaction with many environments. Ideally, we would like to treat the problem of learning exploration as an MDP with intrinsic rewards only and train the agent to maximize interest-based rewards. However, both common intrinsic rewards [7, 35, 36] and the C-BET intrinsic reward would decrease over time as the agent explores, to the point where they vanish to zero. While this is not an issue in the classic tabula-rasa setup where the agent also receives extrinsic rewards, it can be problematic in the proposed task-agnostic exploration framework. Any policy, in fact, would be optimal if all rewards are zero.

To address this issue we introduce count resets, already proposed by Raileanu and Rocktäschel [36]. Every time a new episode begins, state and change counts of Eq. (1) are reset. This prevents vanishing rewards, yet the agent is still encouraged to visit new states and interact as much as possible with the environments. Within an episode, visiting the same state or repeating the same actions over and over –picking up the key, dropping it, picking it up again– will yield lower cumulative rewards compared to exploring new states and having unique interactions with the environment.

The resulting MDP with rewards of Eq. (1) and count resets can be solved by any RL algorithm. However, we should note that this MDP is non-stationary, because the agent may receive different rewards for the same state, depending on how many times the state has been visited in the past. Nonetheless, the use of classic intrinsic rewards –even in tabula-rasa exploration– either based on prediction errors [35, 36] or counts (both with and without resets) also introduces non-stationarity because these rewards change over time as well. In practice, this non-stationarity is not an issue, because the intrinsic rewards change slowly over time.

Figure 5: **Example environments.** In Gym MiniGrid (left), the agent navigates through a grid and interacts with different objects (keys, doors, boxes, and balls) to fulfill a task. In Habitat (right), the agent navigates through visually realistic rooms.

3.3 Exploration Transfer

The interest-based exploration policy learned in the previous phase is then used to drive exploration as tasks are presented to the agent. In order not to forget interestingness over time, the exploration policy is added as a fixed bias to the task-specific policy of the learning algorithm, similarly to what Hailu and Sommer [21] proposed. Thanks to the decoupling of the interest-based policy (based on the intrinsic reward) from the task-value policy (based on the extrinsic reward), the latter can be also learned independently via any RL algorithm.

In our experiments, we use IMPALA [16] for learning both policies. During pre-training, we learn the interest-value function $Q_i(s, a)$ by using intrinsic rewards only. In this phase, the exploration policy is $\pi_{\text{EXP}}(a|s) = \sigma(Q_i(s, a))$, where σ is the softmax function. At transfer, the interest-value function is fixed and a new one $Q_e(s, a)$ is learned with extrinsic rewards. In this phase, the exploration policy is $\pi_{\text{TASK}}(a|s) = \sigma(Q_e(s, a) + Q_i(s, a))$, where interestingness acts as fixed bias to encourage interaction. Initially the policy follows Q_i since Q_e is initialized randomly. As we collect extrinsic rewards, $Q_i + Q_e$ becomes greedier w.r.t. extrinsic rewards, and Q_e slowly overtakes Q_i[2].

4 Experiments

Our experiments are designed to highlight the benefits of disentangling the environment-centric nature of exploration from agent-centric behavior by learning a separate exploration policy and then transferring it to new environments. We stress that for learning task-agnostic exploration there are no standard benchmark environments, experimental setups, well-defined evaluation metrics, or even baselines to compare against. One of our contributions is to provide an exhaustive evaluation framework for the transfer exploration paradigm.

Environments. The experiments are divided into two main sections. The first is about MiniGrid [10] (Section 4.1), a set of procedurally-generated environments where the agent can interact with many objects. The second is about Habitat [45] (Section 4.2), a navigation simulator showcasing the generality of our MiniGrid experiments to a visually realistic domain.

Baselines. We evaluate against the following algorithms. For more details, refer to Appendix A.1.

- *Count* [4]. The intrinsic reward is the inverse of state visitation counts.
- *Random Network Distillation (RND)* [7]. The intrinsic reward is the prediction error of states' random features between a trained network and a fixed one. This can be interpreted as similar to using state counts because the prediction improves as a state is seen more often.
- *Rewarding Impact-Driven Exploration (RIDE)* [36]. The intrinsic reward is the prediction error between consecutive embedded states, normalized by the state visit count.
- *Curiosity* [35]. The intrinsic reward is the prediction error between consecutive states.

4.1 MiniGrid Experiments

MiniGrid environments [10] are procedurally-generated gridworlds where the agent can interact with objects, such as keys, doors, and boxes (Figure 5). Exploration is challenging because rewards are sparse, observations are partial, and specific actions are needed to visit all states (e.g., pickup key to open door). With MiniGrid, we can generate several pairs of train and test environments that are related but still different in many ways. These pairs enable evaluation of both the learning and transfer abilities of an exploration method and its ability to deal with unseen components.

---

[2]If exploration and the task goals are misaligned, we can decay exploration, e.g., $\pi_{\text{TASK}}(a|s) = \sigma(\alpha Q_i(s, a) + Q_e(s, a))$, where α decays over time, similarly to common ϵ-greedy policies.

Implementation details. All environments use a $7 \times 7 \times 3$ partial observation encoding the content of the 7×7 tiles in front of the agent (including the agent's tile). The agent cannot see through walls, closed doors, or inside boxes. The action space is discrete with seven actions: left, right, forward, pick up, drop, toggle, and done. For a complete description of the environments, we refer to Appendix A.4.

Change encoding. The change of a transition is $c(s, a, s') := [s_1 \neq s'_1, s_2 \neq s'_2, \ldots]$, i.e., a binary vector saying which parts of the state have changed after an action. For instance, trying to pick up out-of-range objects, open locked doors, or hitting walls all result in the same change (0s vector).

Setups. We present three setups, to study different exploration transfers against tabula-rasa.

- *MultiEnv (many-to-many transfer).* The agent loops over three environments episode by episode, and learns the exploration policy using intrinsic rewards only. The Count baseline keeps one state count for all three environments rather than a separate count for each. The environments are: KeyCorridorS3R3, BlockedUnlockPickup, and MultiRoom-N4-S5, and have been chosen for size and interaction variety: the first has both a locked and an unlocked door, a key, and a ball; the second adds a box; the third has more rooms. Note that even if these environments have all object types, the agent cannot experience all kinds of interactions. For example, it will not know that keys can be hidden in boxes, as in the ObstructedMazes. The policy is then transferred to ten new environments, seven of which are new. A good intrinsic reward should help learn better exploration faster from multiple environments, thanks to sharing experience from diverse interaction.
- *SingleEnv (one-to-many transfer).* The policy is pre-trained on a single environment. DoorKey and KeyCorridor are used for pre-training because they have some –but not all– objects.
- *Tabula-rasa (baseline, no transfer).* There is no pre-training, and agents learn a task-specific policy as in classic intrinsic motivation, i.e., by summing intrinsic and extrinsic rewards. While this is a non-realistic setting, it is the most common approach for task-agnostic exploration, and thus serves as the baseline against the proposed transfer framework.

Evaluation metrics. Our goal is to learn exploration policies that (1) encourage interaction with the environments, and (2) transfer well to new environments, i.e., that can further be trained to solve extrinsic tasks faster. Therefore, we evaluate (1) pre-trained exploration policies on the number of interactions, and (2) task-specific policies learned after transfer on the expected return, i.e., the average sum of extrinsic rewards. All plots show the mean and standard error across five random seeds per method, smoothed over 300 epochs (960,000 frames) with a sliding window.

4.1.1 MiniGrid Pre-Training Results

Policies are trained on intrinsic rewards only and are evaluated on the number of environment interactions (picking keys, opening/closing doors, opening boxes, or moving balls). Figure 6 shows that C-BET's intrinsic reward encourages the agent to interact the most in all setups, especially MultiEnv. RIDE, Curiosity, and RND baselines perform poorly. This is unsurprising if we consider that they rely on predictive models and that MiniGrid dynamics are deterministic and simple. Dynamics and embeddings models are learned quickly, without giving the policy time to explore. This problem is prominent in MultiEnv, where the agent gets to see diverse data quickly from the different environments. Count uses state counts instead of models, but without resets its rewards vanish as well over time, resulting in worse exploration than C-BET. On the contrary, C-BET never stops exploring thanks to count resets. In Appendix B.2 we provide additional plots showing intrinsic rewards that highlight this behavior.

Figure 6: **MiniGrid pre-training.** Interactions are a proxy metric for exploration success. MultiEnv is used for the 'many-to-many' setup. DoorKey and KeyCorridor are used for the 'one-to-many' setup. The C-BET intrinsic reward performs best, encouraging the agent to interact the most.

Figure 7: **MiniGrid task learning, for both transfer and tabula-rasa exploration.** The hardest tasks are outlined in red. C-BET (blue) from MultiEnv (top row under each environment) performs the best, starting with nearly optimal policies in most environments. This demonstrates the effectiveness of pre-training on multiple environments using C-BET's intrinsic reward.

4.1.2 MiniGrid Transfer Results

We transfer the exploration policies learned in Figure 6 as discussed in Section 3.3. Figure 7 shows how the proposed transfer frameworks (many-to-many and one-to-many) perform against tabula-rasa exploration. Recall that seven out of ten environments are new to agents trained in MultiEnv, and nine out of ten for agents trained in DoorKey and KeyCorridor. Consequently, pre-trained task-agnostic exploration policies must generalize to unseen environments in order to perform well.

The first takeaway is that policies pre-trained with the C-BET intrinsic reward outperform baselines in both transfer and tabula-rasa. In MultiEnv transfer, C-BET performs the best, especially on the hardest environments (outlined in red). In particular, only C-BET is able to solve ObstructedMaze-2Dlhb, despite never having seen an ObstructedMaze during pre-training. Our interest-reward is also the only helping tabula-rasa exploration solving MultiRoom-N6, together with Count. Contrary to Count, though, C-BET achieves non-zero return in MultiRooms from the beginning when exploration is transferred from MultiEnv. In Appendix B.3, we also report the policy performance at transfer and before extrinsic training starts.

The second takeaway is that baselines relying on models are not suited to the transfer framework. Curiosity and RND perform better with tabula-rasa exploration in all environments except for the easiest (Unlock and DoorKey), meaning that transfer is actually harmful. RIDE performance also decreases when pre-trained on MultiEnv and KeyCorridor. These results are in line with Figure 6, where Curiosity and RND do not learn useful policies, and RIDE shows signs of interactions only in DoorKey. Furthermore, all three methods perform worst when transfer is from MultiEnv, highlighting that their intrinsic rewards are not suited to transfer, especially in a multi-environment setup.

Finally, no algorithm learns MultiRooms when transferring from SingleEnv. MultiRooms are notably different from other grids, as all doors are already unlocked and there is no object to pick up. Thus, pre-training on only DoorKey or KeyCorridor does not generalize to such diverse environments.

Figure 8: **Habitat pre-training.** The C-BET policy explores the scene more quickly and achieves the highest unique state count.

Figure 9: **Habitat offline transfer.** Each bar denotes the unique state count in an new scene during one episode (200 steps for 'rooms', 500 steps for others). C-BET outperforms baselines in five out of seven scenes.

4.2 Habitat Experiments

To demonstrate that C-BET's efficacy extends to realistic settings with visual inputs, we perform experiments on Habitat [45] with Replica scenes [51].

Implementation details. In all environments, the agent's policy takes an input an egocentric image with resolution $64{\times}64{\times}3$. The action space is discrete with three actions: forward 1 meter, turn $90°$ left, and turn $90°$ right. For more details of the environments, we refer to Appendix A.5.

Pseudo-counts. Rather than counting egocentric images, we count $360°$ panoramic images, as this is a rotation-invariant representation of state. Similar to Chaplot et al. [8], we concatenate four egocentric images taken from $0°$, $90°$, $180°$, and $270°$ to form a single panoramic image with size $64{\times}256{\times}3$. This image is not accessible by the policy. Because these images are much larger than MiniGrid's observations, counting them is computationally expensive. Instead, we use #Exploration [53] with SimHash [9] to map panoramic images to hash codes and count their occurrences with a hash table.

Change encoding. The change of a transition is the difference between consecutive panoramic images s_p, i.e., $c(s_p, a, s'_p) := s'_p - s_p$.

Setups. Different from MiniGrid, we use no extrinsic rewards in Habitat. The evaluation setup is similar to the *one-to-many transfer* described in Section 4.1. First, we pre-train exploration policies on intrinsic rewards only in one environment. Then, we evaluate the exploration policies on new scenes, but without updating the policies any further.

Evaluation metrics. Habitat does not have objects or extrinsic tasks as MiniGrid does, so we use different evaluation metrics. Since the agent has to navigate through rooms and spaces, we evaluate exploration using state coverage as measured by the agent's true state in Cartesian coordinates (not accessible by the agent). Faster and larger coverage corresponds to better exploration. All plots show the mean and standard error across five random seeds per method with no sliding window smoothing.

4.2.1 Habitat Pre-Training Results

We pre-train Habitat exploration policies on Apartment 0 (Figure 5), the largest Replica scene in the dataset. Figure 8 shows state coverage throughout pre-training for each method. C-BET explores more efficiently, visiting ~25% more states than RIDE and Count, the next best baselines. In Appendix A.5 we also report heatmaps showing state coverage at the end of pre-training.

4.2.2 Habitat Transfer Results

Here, we evaluate state coverage of pre-trained policies in seven unseen scenes. For each scene, each policy explores the environment for a fixed number of steps, starting from the same initial position. For larger scenes (multi-room apartments) the episode ends after 500 steps, while for smaller scenes (single rooms) after 200. A better exploration policy will exhibit generalization by covering a larger portion of the scene as evenly as possible, an impressive feat given the visual complexity of the observations. Figure 9 shows transfer state coverage averaged over five random seeds. C-BET generalizes the best in five of the seven unseen Habitat scenes. It performs competitively in Room 1, attaining equal performance to Count. In Room 2, it attains the second-best results after RIDE.

Figure 10: **Visualization of Habitat exploration policy transfer.** Each heatmap shows the distribution of states visited by each pre-trained policy during one episode in Apartment 2 at transfer. Darker red cells denote higher visitation rates. C-BET is the only policy visiting the top-right corner.

Finally, Figure 10 shows the states visited by each algorithm in Apartment 2 after transfer. C-BET visits most of the scene within one episode, and it is the only policy visiting the top-right corner of the apartment. Curiosity and RND get stuck in corners, performing even more poorly than the random policy.

5 Discussion

In this paper, we proposed a paradigm change in task-agnostic exploration. Instead of studying task-agnostic exploration in isolated environments, we proposed to (1) learn task-agnostic exploration policies from one or multiple environments, and (2) transfer learned exploration policies to unseen environments at testing time. In our setup, the agent interacts with the environment without any extrinsic goal and learns to explore environments in a task-agnostic manner. To this end, we proposed a novel intrinsic reward to encourage interaction with the environment and the visitation of unseen states. Subsequently, our agent effectively transfers its exploration policy to unseen environments.

Advantages. The proposed two-phase framework achieves two important features, making it fundamentally different from prior work. First, we account for *environment interestingness* without relying on additional models. Instead, we use a data-driven approach, estimating the rarity of states and environment changes. Rare changes are considered more interesting, actions causing them receive higher intrinsic rewards, and the agent is encouraged to perform them again. For instance, when navigating through rooms, opening doors will be more interesting due to rarity: the agent must navigate to the corresponding key, collect it, navigate to the door, and finally open it. Thus opening a door is rarer than picking up a key, in turn rarer than simple navigation movements. Furthermore, relying on environment-centric intrinsic rewards rather than task-centric extrinsic rewards facilitates learning from multiple environments at the same time.

Second, contrary to prior transfer and continual learning algorithms we transfer policies learned on *interestingness of the environment* rather than task-specific policies. In the interest-based pre-training phase, we learn through interaction with the environment in a task-agnostic fashion, i.e., the agent freely explores the environment without any extrinsic task.

Limitations. In this paper, we assumed that interacting with the environment while looking for rare changes helps find better extrinsic rewards faster. However, exploration and the task goals may be misaligned, thus a highly exploratory policy may slow down the discovery of extrinsic rewards. For instance, the environment may have dangerous states or harmful objects that the agent should avoid, even though they would make it curious during pre-training. Furthermore, C-BET is currently tied to (pseudo)counts to compute the rarity of states and changes. While extensions to continuous spaces exist, count-based metrics are more suited for discrete spaces.

Impact. RL can positively contribute to several real-world applications, including assistive robotics [15], healthcare [19], and tackling climate change [42]. However, RL also has possible negative impacts, e.g., in autonomous weapons or workforce displacement [6]. Our work focuses on exploration in RL. Better understanding of what is interesting to do or visit helps exploration in unseen environments, as the agent will not waste time doing random actions. Similarly, transferring policies learned in a related setting –as we do– can help narrow the range of the agent's expected behavior. Conversely, in many real-world scenarios exploration by curiosity and interestingness is unacceptable. For instance, autonomous cars cannot run over pedestrians just for the sake of curiosity. At present, our work is far from these impacts, but we hope to direct research to focus more on learning from multiple environments and transferring experiences, while at the same time ensuring the safety and reliability of autonomous agents.

References

[1] P. Auer and R. Ortner. Logarithmic online regret bounds for undiscounted reinforcement learning. In *Advances in Neural Information Processing Systems (NIPS)*, pages 49–56, 2007. 2

[2] P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2-3):235–256, 2002. 2

[3] A. Barreto, W. Dabney, R. Munos, J. J. Hunt, T. Schaul, H. Van Hasselt, and D. Silver. Successor features for transfer in reinforcement learning. In *International Conference on Neural Information Processing Systems (NeurIPS)*, 2017. 3

[4] M. G. Bellemare, S. Srinivasan, G. Ostrovski, T. Schaul, D. Saxton, and R. Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems (NIPS)*, 2016. 1, 2, 3, 5

[5] R. I. Brafman and M. Tennenholtz. R-MAX - A general polynomial time algorithm for near-optimal reinforcement learning. *Journal of Machine Learning Research (JMLR)*, 3(Oct): 213–231, 2002. 2

[6] E. Brynjolfsson and T. Mitchell. What can machine learning do? workforce implications. *Science*, 358(6370), 2017. 9

[7] Y. Burda, H. Edwards, A. Storkey, and O. Klimov. Exploration by random network distillation. In *International Conference on Learning Representations (ICLR)*, 2019. 2, 4, 5

[8] D. S. Chaplot, R. Salakhutdinov, A. Gupta, and S. Gupta. Neural topological slam for visual navigation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12875–12884, 2020. 8

[9] M. S. Charikar. Similarity estimation techniques from rounding algorithms. In *Symposium on Theory of Computing*, 2002. 8

[10] M. Chevalier-Boisvert, L. Willems, and S. Pal. Minimalistic Gridworld Environment for OpenAI Gym, 2018. URL https://github.com/maximecb/gym-minigrid. 5

[11] D.-A. Clevert, T. Unterthiner, and S. Hochreiter. Fast and accurate deep network learning by exponential linear units (ELUs), 2015. 15

[12] C. D'Eramo, A. Cini, and M. Restelli. Exploiting Action-Value uncertainty to drive exploration in reinforcement learning. In *International Joint Conference on Neural Networks (IJCNN)*, 2019. 2

[13] K. Dong, Y. Wang, X. Chen, and L. Wang. Q-learning with UCB exploration is sample efficient for Infinite-Horizon MDP. In *International Conference on Learning Representation (ICLR)*, 2020. 2

[14] R. Dubey, P. Agrawal, D. Pathak, T. L. Griffiths, and A. A. Efros. Investigating human priors for playing video games. In *International Conference on Machine Learning (ICML)*, 2018. 1

[15] Z. Erickson, V. Gangaram, A. Kapusta, C. K. Liu, and C. C. Kemp. Assistive gym: A physics simulation framework for assistive robotics. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 10169–10176. IEEE, 2020. 9

[16] L. Espeholt, H. Soyer, R. Munos, K. Simonyan, V. Mnih, T. Ward, Y. Doron, V. Firoiu, T. Harley, I. Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pages 1407–1416. PMLR, 2018. 5, 15

[17] F. Fernández and M. Veloso. Probabilistic policy reuse in a reinforcement learning agent. In *International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, 2006. 3

[18] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning (ICML)*, 2017. 3

[19] O. Gottesman, F. Johansson, M. Komorowski, A. Faisal, D. Sontag, F. Doshi-Velez, and L. A. Celi. Guidelines for reinforcement learning in healthcare. *Nature medicine*, 25(1):16–18, 2019. 9

[20] J. Gottlieb, P. Oudeyer, M. Lopes, and A. Baranes. Information-seeking, curiosity, and attention: computational and neural mechanisms. *Trends in Cognitive Sciences*, 17(11):585–593, 2013. 3

[21] G. Hailu and G. Sommer. On amount and quality of bias in reinforcement learning. In *International Conference on Systems, Man, and Cybernetics (SMC)*, 1999. 3, 5

[22] S. Hansen, W. Dabney, A. Barreto, T. Van de Wiele, D. Warde-Farley, and V. Mnih. Fast task inference with variational intrinsic successor features. In *International Conference on Learning Representations (ICLR*, 2020. 3

[23] S. Hochreiter and J. Schmidhuber. Long short-term memory. *Neural Computation*, 9(8): 1735–1780, 1997. 15

[24] R. Houthooft, X. Chen, Y. Duan, J. Schulman, F. De Turck, and P. Abbeel. VIME: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems (NIPS)*, 2016. 2, 3

[25] T. Jaksch, R. Ortner, and P. Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research (JMLR)*, 11(Apr):1563–1600, 2010. 2

[26] C. Jin, Z. Allen-Zhu, S. Bubeck, and M. I. Jordan. Is Q-learning provably efficient? In *Advances in Neural Information Processing Systems (NIPS)*, 2018. 2

[27] M. Kearns and S. Singh. Near-optimal reinforcement learning in polynomial time. *Machine Learning*, 49(2-3):209–232, 2002. 2

[28] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell. Overcoming catastrophic forgetting in neural networks. *National Academy of Sciences*, 114(13):3521–3526, 2017. 2, 3

[29] A. S. Klyubin, D. Polani, and C. L. Nehaniv. All else being equal be empowered. In *European Conference on Artificial Life*, 2005. 2

[30] H. Küttler, N. Nardelli, T. Lavril, M. Selvatici, V. Sivakumar, T. Rocktäschel, and E. Grefenstette. TorchBeast: A PyTorch Platform for Distributed RL, 2019. URL https://github.com/facebookresearch/torchbeast. 15

[31] T. Lai and H. Robbins. Asymptotically efficient adaptive allocation rules. *Adv. Appl. Math.*, 6 (1):4–22, Mar 1985. 2

[32] S. Narvekar, B. Peng, M. Leonetti, J. Sinapov, M. E. Taylor, and P. Stone. Curriculum learning for reinforcement learning domains: A framework and survey. *Journal of Machine Learning Research*, 21(181):1–50, 2020. 2

[33] I. Osband, B. V. Roy, D. J. Russo, and Z. Wen. Deep exploration via randomized value functions. *Journal of Machine Learning Research (JMLR)*, 20(124):1–62, 2019. 2

[34] G. Ostrovski, M. G. Bellemare, A. van den Oord, and R. Munos. Count-based exploration with neural density models. In *International Conference on Machine Learning (ICML)*, 2017. 1

[35] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning (ICML)*, 2017. 1, 2, 3, 4, 5

[36] R. Raileanu and T. Rocktäschel. RIDE: Rewarding Impact-Driven Exploration for Procedurally-Generated Environments. In *International Conference on Learning Representations (ICLR)*, 2020. 3, 4, 5, 15, 16

[37] K. Rakelly, A. Zhou, C. Finn, S. Levine, and D. Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *International Conference on Machine Learning (ICML)*, 2019. 2, 3

[38] D. Rezende and S. Mohamed. Variational inference with normalizing flows. In *International Conference on Machine Learning (ICML)*, 2015. 1, 2

[39] M. B. Ring. *Continual learning in reinforcement environments*. PhD thesis, University of Texas at Austin Austin, Texas 78712, 1994. 3

[40] M. B. Ring. CHILD: A first step towards continual learning. In *Learning to learn*, pages 261–292. Springer, 1998. 3

[41] D. Rolnick, A. Ahuja, J. Schwarz, T. Lillicrap, and G. Wayne. Experience replay for continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019. 3

[42] D. Rolnick, P. L. Donti, L. H. Kaack, K. Kochanski, A. Lacoste, K. Sankaran, A. S. Ross, N. Milojevic-Dupont, N. Jaques, A. Waldman-Brown, et al. Tackling climate change with machine learning. *arXiv preprint arXiv:1906.05433*, 2019. 9

[43] A. A. Rusu, S. G. Colmenarejo, C. Gulcehre, G. Desjardins, J. Kirkpatrick, R. Pascanu, V. Mnih, K. Kavukcuoglu, and R. Hadsell. Policy distillation. In *International Conference on Learning Representations (ICLR)*, 2015. 3

[44] R. M. Ryan and E. L. Deci. Intrinsic and extrinsic motivations: Classic definitions and new directions. *Contemporary Educational Psychology*, 25(1):54–67, 2000. 2

[45] M. Savva, A. Kadian, O. Maksymets, Y. Zhao, E. Wijmans, B. Jain, J. Straub, J. Liu, V. Koltun, J. Malik, D. Parikh, and D. Batra. Habitat: A Platform for Embodied AI Research. In *International Conference on Computer Vision (ICCV)*, 2019. 5, 8

[46] J. Schmidhuber. A possibility for lmplementing curiosity and boredom in Model-Building neural controllers. In *International Conference on Simulation of Adaptive Behavior (SAB)*, 1991. 1, 3

[47] J. Schmidhuber. Developmental robotics, optimal artificial curiosity, creativity, music, and the fine arts. *Connection Science*, 18(2):173–187, 2006. 3

[48] M. Schultheis, B. Belousov, H. Abdulsamad, and J. Peters. Receding horizon curiosity. In *Conference on Robot Learning (CoRL)*, 2019. 2, 3

[49] J. Schwarz, J. Luketina, W. M. Czarnecki, A. Grabska-Barwinska, Y. W. Teh, R. Pascanu, and R. Hadsell. Progress & compress: A scalable framework for continual learning. In *International Conference on Machine learning (ICML)*, 2018. 3

[50] B. C. Stadie, S. Levine, and P. Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. In *NIPS Workshop on Deep Reinforcement Learning*, 2015. 2, 3

[51] J. Straub, T. Whelan, L. Ma, Y. Chen, E. Wijmans, S. Green, J. J. Engel, R. Mur-Artal, C. Ren, S. Verma, A. Clarkson, M. Yan, B. Budge, Y. Yan, X. Pan, J. Yon, Y. Zou, K. Leon, N. Carter, J. Briales, T. Gillingham, E. Mueggler, L. Pesqueira, M. Savva, D. Batra, H. M. Strasdat, R. D. Nardi, M. Goesele, S. Lovegrove, and R. Newcombe. The Replica dataset: A digital replica of indoor spaces, 2019. 8

[52] A. L. Strehl and M. L. Littman. An analysis of model-based interval estimation for Markov decision processes. *Journal of Computer and System Sciences (JCSS)*, 74(8):1309–1331, 2008. 2, 3

[53] H. Tang, R. Houthooft, D. Foote, A. Stooke, O. X. Chen, Y. Duan, J. Schulman, F. DeTurck, and P. Abbeel. #Exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems (NIPS)*, 2017. 8

[54] Y. W. Teh, V. Bapst, W. M. Czarnecki, J. Quan, J. Kirkpatrick, R. Hadsell, N. Heess, and R. Pascanu. Distral: Robust multitask reinforcement learning. In *International Conference on Neural Information Processing Systems (NeurIPS)*, 2017. 3

[55] S. Thrun and T. M. Mitchell. Lifelong robot learning. *Robotics and Autonomous Systems*, 15 (1-2):25–46, 1995. 3

[56] T. Tieleman and G. Hinton. Divide the gradient by a running average of its recent magnitude. coursera: Neural networks for machine learning. *Technical Report.*, 2017. 15

[57] K. Weiss, T. M. Khoshgoftaar, and D. Wang. A survey of transfer learning. *Journal of Big data*, 3(1):9, 2016. 2

[58] D. Yarats, R. Fergus, A. Lazaric, and L. Pinto. Reinforcement learning with prototypical representations. In *International Conference on Machine Learning (ICML)*, 2021. 3