Modeling Transitivity and Cyclicity in Directed Graphs via Binary Code Box Embeddings

Abstract

Modeling directed graphs in continuous space is a fundamental requirement for performing machine learning on graph-structured data. Geometric embedding models (e.g., hyperbolic, cone, and box embeddings) excel at this task, exhibiting useful inductive biases for directed graphs. However, modeling directed graphs that both contain cycles and have transitive structure, two properties common in real-world settings, is challenging. Box embeddings, which can be thought of as representing the graph as an intersection over some learned subgraphs, have a natural inductive bias toward modeling transitive edges, but (as we prove) cannot model cycles. To this end, we propose *binary code box embeddings*, where a learned binary code selects a subset of graphs for intersection. We explore several variants, including global binary codes (amounting to a union over intersections) and per-vertex binary codes (allowing greater flexibility) as well as methods of regularization. Theoretical and empirical results show that the proposed models not only preserve a useful inductive bias of transitivity but also have sufficient representational capacity to model arbitrary graphs, including graphs with cycles.

1 Introduction

Many real-world networks, such as social media interactions, paper citations, web links, and ontology, are naturally represented as directed graphs [14, 6]. Two common properties of these graphs are transitivity and cyclicity. A *cycle* in a directed graph is a directed path starting from a node and traversing back to itself. For example, "organic matter" → "worm" → "fish" → "cat" → "organic matter" is a food cycle. *Asymmetric transitivity* is the property that if there exists a multi-hop directed path from u to v, then edge (u, v) is likely to exist. For example, If "cat is mammal" and "mammal is animal" are true, "cat is animal" is true [1].

In the age of deep learning, it is necessary to determine a way to capture the salient information from a graph in a continuous space. To this end, various graph embedding methods have been proposed. Some work, such as DeepWalk [17] and Node2vec [8], maps each vertex to a vector in Euclidean space. These methods perform a low-rank factorization of the adjacency matrix or the graph Laplacian [18] and are designed to model un-directed graphs. In order to capture edge asymmetry in directed graphs, it is common for each vertex to have two separate representations - one for source, and one for target - either unconstrained or related via projection functions. It has been proven that using a dot product or distance-based energy function, separate source and target vectors can encode any graph [1], including graphs with cycles. When the source and target

---

[1]In this paper, "transitivity" always refers to the asymmetric version.

representations live in separate spaces, however, relationships which result from following directed paths (e.g., transitivity) are harder to encode. For example, given edge (i, j) and (j, k), a vector model can learn to make $|s_i - t_j|_2 \approx 0$ and $|s_j - t_k|_2 \approx 0$, where s_i, s_j are source vectors and t_j, t_k are target vectors. However, the condition $|s_i - o_k|_2 \approx 0$ which would represent the transitive edge (i, k) has no encouragement to hold, as source and target spaces are entirely disconnected.

Transitivity cannot be trivially injected via symbolic rules, e.g., adding all transitive edges to a directed graph. This is because most real world edge types are not strictly transitive: The degree of transitivity is "soft", and may vary for different sets of nodes in the graph. Some work, such as HOPE [15] and APP [29], attempts to capture transitivity by factorizing high-order proximity signals instead of the graph Laplacian. This branch of work is limited by the imperfection of high-order proximity scores (for example, these scores do not model cycles well). ATP [25] resolves by breaking cycles in the graph, accepting a loss of graph information.

Region-based embeddings such as box embeddings [28, 11, 3] and hyperbolic entailment cones [13, 7, 21, 9] have a natural bias toward modeling transitivity. These region-based embeddings can capture the transitivity in a directed graph without relying on high-order proximity scores, using only the original adjacency matrix as supervision. Previous work [2] proved that box embeddings can model any directed acyclic graph (DAG). A natural question, therefore, is whether box embeddings can capture graphs with cycles. As we will show in Section 2, this is not the case.

In this work, we propose *binary code box embeddings*, a generalization of box embeddings to represent arbitrary directed graphs. Our intuition is that a given directed graph can be regarded as a union of multiple sub-graphs, where each sub-graph is acyclic, and therefore can be represented using boxes. We introduce the concept of a "binary code" which selects these sub-graphs.

Our contributions lie in three folds:

- We propose global (GBC-Box) and per-vertex (VBC-Box) binary code box models, generalizing box embeddings to represent arbitrary directed graphs.

- We theoretically analyze the limitations of existing box embeddings when modeling cycles, and prove that both binary code box models can model any directed graph.

- We evaluate our model on graph reconstruction and link prediction tasks with various synthetic graphs and real world graphs, and observe that our proposed methods perform the best in almost all scenarios, especially when a graph has strong cyclicity and transitivity.

2 Background

Given a simple[2] directed graph G with vertices and edges $(\mathcal{V}, \mathcal{E})$, we seek to represent the vertices using some mapping $\phi : \mathcal{V} \to \mathbb{R}^d$, and an energy function $\mathrm{E} : \mathcal{V} \times \mathcal{V} \to \mathbb{R}_+$ providing a score (based on ϕ and, perhaps, some hyperparameters $\boldsymbol{\lambda}$) which is interpreted as the negative log probability of edge existence, $\mathrm{E}(u, v; \phi, \boldsymbol{\lambda}) = -\log P((u, v) \in \mathcal{E})$. We can view these probabilities as a weighted graph, however in practice it is often necessary to make a hard decision on edge existence, which is done by choosing a (global) threshold T and binarizing the output. We denote the energy function for a particular model M with a subscript, i.e. E_{M}, and say that M is capable of modeling a graph $G = (\mathcal{V}, \mathcal{E})$ if there is some ϕ, $\boldsymbol{\lambda}$, and T such that $E = \{(u, v) \mid \mathrm{E}(u, v; \phi, \boldsymbol{\lambda}) < T\}$.

2.1 Boxicity

Let $\mathbf{I}$ be the set of closed and bounded intervals in $\mathbb{R}$. An *interval graph* is an undirected graph $G = (\mathcal{V}, \mathcal{E})$ such that there exists a mapping $\varphi : \mathcal{V} \to \mathbf{I}$ for which

$$\{u, v\} \in \mathcal{E} \iff \varphi(u) \cap \varphi(v) \neq \emptyset.$$

---

[2]A *simple* directed graph is one without multiple edges or self-loops, i.e. the adjacency matrix contains only 0s and 1s, with 0s on the diagonal. We remove self-loops from the learned representations.

More generally, we can consider $\mathbf{B}^d$, the set of d-dimensional "boxes", which are Cartesian products of intervals,

$$\prod_{i=1}^{d} [x_i^-, x_i^+] = [x_1^-, x_1^+] \times \cdots \times [x_d^-, x_d^+] \subseteq \mathbb{R}^d. \tag{1}$$

where x_i^- and x_i^+ are min and max coordinates in dimension i. As defined by Roberts [20], the *boxicity* of an undirected graph G is the smallest dimension d such that there exists a mapping $\phi : \mathcal{V} \to \mathbf{B}^d$ for which $\{u, v\} \in \mathcal{E}$ if and only if $\phi(u) \cap \phi(v) \neq \emptyset$. Equivalently, the boxicity is the minimal number of interval graphs whose intersection is G.

2.2 Box Embeddings

Vilnis et al. [28] provide a way of using boxes to represent directed graphs by defining an asymmetric energy function based on box volumes. There are a number of box embedding variants, all of which preserve not only the geometric representation of boxes from boxicity but also the related conceptual idea of graph intersection by using an energy function of the form

$$\mathrm{E}(u, v; \phi, \boldsymbol{\lambda}) = -\log \prod_{i=1}^{d} F(\phi(u)_i, \phi(v)_i; \boldsymbol{\lambda}), \tag{2}$$

where $\phi(u)_i$ are the parameters associated with node u in dimension i and $F(\phi(u)_i, \phi(v)_i; \boldsymbol{\lambda}) \in [0, 1]$ is the per-dimension score representing the probability of edge existence. The model originally defined in Vilnis et al. [28] represented each node using a box, as in (1). The per-dimension parameters are the endpoints of an interval, $\phi(u)_i = [\phi(u)_i^-, \phi(u)_i^+]$, and the score function is defined as

$$F_{\mathrm{Box}}([x^-, x^+], [y^-, y^+]) = \frac{|[x^-, x^+] \cap [y^-, y^+]|}{|[y^-, y^+]|} = \frac{\max(\min(x^+, y^+) - \max(x^-, y^-), 0)}{\max(y^+ - y^-, 0)}.$$

This encourages the box for a given node to contain the boxes for it's children. Boxes which are disjoint or contained in one another can present problems for training, however. Dasgupta et al. [3] addressed this by modeling the endpoints of intervals using Gumbel random variables. The per-dimension score can be written as[3]

$$F_{\mathrm{G\text{-}Box}}((x^-, x^+), (y^-, y^+); (\tau, \nu)) = \frac{\mathrm{LSE}_\nu\left(-\mathrm{LSE}_\tau(-x^+, -y^+) - \mathrm{LSE}_\tau(x^-, y^-), 0\right)}{\mathrm{LSE}_\nu(y^+ - y^-, 0)}, \tag{3}$$

where LSE_t denotes the following continuous extension of LogSumExp with temperature $t \geq 0$:

$$\mathrm{LSE}_t(\mathbf{x}) = \begin{cases} t \log(\sum_i e^{x_i/t}) & \text{if } t > 0, \\ \max(\mathbf{x}) & \text{if } t = 0. \end{cases} \tag{4}$$

In practice, the temperatures τ and ν are tuned separately as global hyperparameters, however when they are equal the parameters x^-, y^- (resp. x^+, y^+) can be interpreted as the mean of the GumbelMax (resp. GumbelMin) random variables with scale $\nu = \tau$, and $F_{\mathrm{G\text{-}Box}}$ approximates a ratio of expected box volumes. Note that for any $(x^-, x^+), (y^-, y^+) \in \mathbb{R}^2$, $F_{\mathrm{G\text{-}Box}}$ is continuous with respect to $\tau, \nu \in \mathbb{R}_{\geq 0}$, and $F_{\mathrm{G\text{-}Box}}((x^-, x^+), (y^-, y^+); 0, 0) = F_{\mathrm{Box}}([x^-, x^+], [y^-, y^+])$.

Boratko et al. [2] takes this one step further, using a mapping which learns 4 parameters per dimension: $\phi(u)_i = (\phi(u)_i^-, \phi(u)_i^+, \phi(u)_{i,\tau}, \phi(u)_{i,\nu})$. The per-dimension score function is then defined as

$$F_{\mathrm{T\text{-}Box}}((x^-, x^+, x_\tau, x_\nu), (y^-, y^+, y_\tau, y_\nu)) = F_{\mathrm{G\text{-}Box}}((x^-, x^+), (y^-, y^+); (\tfrac{x_\tau + y_\tau}{2}, \tfrac{x_\nu + y_\nu}{2})). \tag{5}$$

3 Existing Representational Capacity and Limitations

3.1 Representational Capacity

We would like to know each model's representational capacity (the set of graphs capable of being modeled) as well as how this may change depending on hyperparameter settings. It was proven in

---

[3]In Dasgupta et al. [4] they interpret $\phi(u)_i^{\pm}$ as the "location" parameters of the distribution, resulting in a slightly different form of the score function, however as we show in Appendix A our score (3) leads to an equivalent model.

106 Boratko et al. [2] that BOX can model any DAG, and of course since T-BOX is equivalent to BOX
107 when $\phi(u)_{i,\tau} = \phi(u)_{i,\nu} = 0$ this also holds for T-BOX. In fact, more can be said:

108 **Theorem 1.** *Given a threshold T and temperature hyperparameters τ, ν, there exists a threshold T'*
109 *and a bijection φ on the space of parameterizations $\{\mathcal{V} \to \mathbb{R}^{2d}\}$ such that*

$$\mathrm{E}_{\text{G-BOX}}(u, v; \varphi(\phi), \tau, \nu) < T' \quad \Longleftrightarrow \quad \mathrm{E}_{\text{BOX}}(u, v) < T.$$

110 In other words, for any given temperature hyperparameters, G-BOX can represent any graph repre-
111 sentable by BOX. For the proof, see Appendix B. Proposition 3 in Boratko et al. [2] states that any
112 DAG can be modeled by BOX in $\mathcal{O}((\Delta + 2) \log |\mathcal{V}|)$ dimensions with $\mathcal{O}(D(\Delta + 2) \log^2 |\mathcal{V}|)$ bits of
113 precision per box, where $D \leq |\mathcal{V}|$ is the depth of G and Δ is the maximum degree. Combining this
114 with Theorem 1 we have the following:

115 **Corollary 2.** *Let G be any DAG. Given any $\tau, \nu \in \mathbb{R}_{\geq 0}$, there exists a mapping $\phi : \mathcal{V} \to \mathbb{R}^{2d}$*
116 *and a threshold $T > 0$ such that $\mathrm{E}_{\text{G-BOX}}(u, v; \phi, (\tau, \nu)) < T$ if and only if $(u, v) \in \mathcal{E}$, where*
117 *$d = \mathcal{O}((\Delta + 2) \log |\mathcal{V}|)$, and Δ is the maximum degree in G.*

118 In other words, for any setting of temperature hyperparamters, G-BOX can model any DAG.

3.2 Limitation on Modeling Cycles

120 In this section, we point out that G-BOX cannot model any graph containing a (directed) *chordless*
121 *cycle*, which is a cycle such that no two vertices are connected by an edge which does not belong to
122 the cycle. Furthermore, we show that while G-BOX can model certain graphs with cycles, it may be
123 rather sensitive to the perturbation of the parameters.

124 **Theorem 3.** *If E is such that $\mathrm{E}(u, v) - \mathrm{E}(v, u) = g(u) - g(v)$ for some function $g : \mathcal{V} \to \mathbb{R}$ then it*
125 *cannot model any graph containing a chordless cycle with more than 2 nodes.*

126 *Proof.* Suppose the vertices $1, 2, ..., N$ comprise a chordless cycle, the edges of which are $D =$
127 $\{(1, 2), (2, 3), ..., (N - 1, N), (N, 1)\}$. Suppose further that we can model the graph containing this
128 cycle using energy E and threshold T. In particular, we have $\mathrm{E}(u, v) < T$ and $\mathrm{E}(v, u) \geq T$ for
129 $(u, v) \in D$. This implies that $g(u) - g(v) = \mathrm{E}(u, v) - \mathrm{E}(v, u) < 0$, and thus $g(u) < g(v)$ for each
130 $(u, v) \in D$. Hence $g(1) < g(2) < \cdots < g(N) < g(1)$, which is a contradiction. $\qquad\square$

131 **Corollary 4.** G-BOX *cannot model any graph containing a chordless cycle on more than 2 nodes.*

132 *Proof.* Theorem 3 applies to $E_{\text{G-BOX}}$ with $g(u) = -\log \prod_{i=1}^{d} \mathrm{LSE}_\nu(\phi(u)_i^+ - \phi(u)_i^-, 0)$. $\qquad\square$

133 It is possible to avoid the contradiction in Theorem 3 by the introduction of one reverse edge, and in
134 this case we observe that it is theoretically possible for G-BOX to represent a graph.

135 **Proposition 1.** *If G is a graph which is the union of a chordless cycle and one reverse edge,* G-BOX
136 *can model G in 2 dimensions.*

137 The proof of this statement is contained in Appendix C, where we also prove that, while it is possible
138 to represent such a graph, it is highly sensitive to perturbation of the parameters in a way which is
139 dependent on the length of the cycle, and therefore may be challenging to learn.

4 Method

141 In this section, we will introduce the binary code box embedding concept, which includes a family
142 of models whose shared feature is the use of learned binary codes to select subsets of dimensions.
143 Two we will focus on in particular include GBC-BOX, which uses "global" binary code vectors,
144 and VBC-BOX, which uses per-vertex binary code vectors. The following topics will be covered:
145 the motivation for binary codes, the definition of GBC-BOX and VBC-BOX, their representational
146 capacity to model arbitrary directed graphs, our learning objectives and regularization, the models'
147 inductive biases and strengths, and some discussion about their limitations and alternative variants.

4.1 Motivation

The idea of BC-Box is to allow more flexibility than simply taking an intersection over interval graphs, as captured by boxicity (see Section 2.1). Recall, in the undirected case, the boxicity of a graph $G = (\mathcal{V}, \mathcal{E})$ was equivalent to the smallest number d such that for some set of interval graphs $S = \{G_i = (\mathcal{V}, \mathcal{E}_i)\}_{i=1}^d$, we have $\mathcal{E} = \cap_{i=1}^d \mathcal{E}_i$, i.e.

$$\{u, v\} \in \mathcal{E} \quad \Longleftrightarrow \quad \forall F : (\mathcal{V}, F) \in S, \quad \{u, v\} \in F.$$

There are various ways to increase the flexibility of this representation. For example, we could consider allowing a union over intersections by specifying k subsets of S, $\{S_i\}_{i=1}^k$, for which $\mathcal{E} = \cup_{i=1}^k \cap_{(\mathcal{V}, F) \in S_k} F$, i.e.

$$\{u, v\} \in \mathcal{E} \quad \Longleftrightarrow \quad \exists S_i : \forall F : (\mathcal{V}, F) \in S_i, \quad \{u, v\} \in F. \tag{6}$$

To allow for even greater flexibility, we could allow each vertex to select a subset of graphs to intersect. Formally, we allow the specification of a function $\psi : \mathcal{V} \to 2^S$ which assigns a subset of interval graphs to each vertex, for which

$$\{u, v\} \in \mathcal{E} \quad \Longleftrightarrow \quad \forall F : (\mathcal{V}, F) \in \psi(u) \cap \psi(v), \quad \{u, v\} \in F. \tag{7}$$

For the undirected case the advantage is minimal, as any undirected graph can be represented as an intersection of interval graphs. For directed graphs, however, this is not the case, and (as we prove in Section 4.3) this generalization allows for any directed graph to be represented.

4.2 Definition

In order to capture the idea of a union over intersection specified in (6) we consider learning k "binary code" vectors $\mathbf{b}_j \in [0, 1]^d$. Each binary vector corresponds to a selection of which dimensions to include - if the i^{th} component is 0 the scores for edges in this dimension should be ignored, and if it is 1 they should be included. For convenience, we will represent these as the columns of a $d \times k$ matrix $B \in [0, 1]^{d \times k}$. The energy function in this case is

$$\mathrm{E_{GBC\text{-}Box}}(u, v; (\phi, B), (\tau, \nu, k)) := \min_{j \in \{1, \ldots, k\}} \left(-\log \prod_{i=1}^d F_{\mathrm{G\text{-}Box}}(\phi(u)_i, \phi(v)_i; (\tau, \nu))^{B_{i,j}} \right) \tag{8}$$

In order to capture the notion of per-vertex subset selection in (7), we learn 3 parameters per dimension, which we denote as $\phi(u)_i = (\phi(u)_i^-, \phi(u)_i^+, \phi(u)_i^\diamond) \in \mathbb{R} \times \mathbb{R} \times [0, 1]$. The binary code $\phi(u)_i^\diamond$ indicates whether this dimension should be taken into account when calculating the probability of edge existence for edges involving this node - if it is 0, the dimension should be ignored, and if it is 1 it may be included. We incorporate this at the level of the per-dimension score function as follows:

$$F_{\mathrm{VBC\text{-}Box}}((x^-, x^+, x^\diamond), (y^-, y^+, y^\diamond); \tau, \nu) := F_{\mathrm{G\text{-}Box}}((x^-, x^+), (y^-, y^+); \tau, \nu)^{x^\diamond \cdot y^\diamond}. \tag{9}$$

Using the product in the exponent is a relaxation of the intersection $\psi(u) \cap \psi(v)$ from (7). When computing the probability of an edge (u, v), the binary codes can learn to ignore certain dimensions by making $\phi(u)_i^\diamond$ or $\phi(v)_i^\diamond$ equal to 0.

In the following, we point out two perspectives which provide further intuition behind these models:

Generalization: If the binary codes are all 1, both models revert to G-Box. As we will show in Section 4.3, when some binary codes are less than 1 these models can represent more complex graphs.

Projection: If $B_{i,j} \in \{0, 1\}$ we can think of this defining a set of projections $\{P_j\}_{j=1}^k$ where P_j projects the boxes parameterized by ϕ into the $\sum_{i=1}^d B_{i,j}$ dimensional subspace where $B_{i,j} = 1$. Similarly, for VBC-Box, if $\phi(u)_i^\diamond \in \{0, 1\}$ we can think of this determining the dimensions $D_u := \{i : \phi(u)_i^\diamond = 1\}$ which the box will be projected in. Given an edge (u, v), we project into dimensions $D_u \cap D_v$ before determining the edge existence.

 ### 4.3 Representational Capacity

185 The energy functions for GBC-Box and VBC-Box were constructed such that Theorem 3 would
186 not apply, thus making it possible that they may be capable of representing some graphs with cycles.
187 In this section, we prove that both can model *any* directed graph.

188 **Theorem 5.** *Given a directed graph $G = (\mathcal{V}, \mathcal{E})$ and any $\tau, \nu \geq 0$ and $k \geq 2$, there exists a threshold*
189 $T > 0$, *parameters $\phi : \mathcal{V} \to \mathbb{R}^{2d}$, and binary codes $B \in [0, 1]^{d \times k}$ for which*

$$\mathrm{E}_{\text{GBC-Box}}(u, v; (\phi, B), (\tau, \nu)) < T \iff (u, v) \in \mathcal{E}.$$

190 *Proof.* Given a directed graph $G = (\mathcal{V}, \mathcal{E})$, let $(<, \mathcal{V})$ be an arbitrary strict total order on the vertices.
191 Then define subgraphs $D_1 = (\mathcal{V}, \mathcal{E}_1)$ and $D_2 = (\mathcal{V}, \mathcal{E}_2)$ where $\mathcal{E}_1 = \{(u, v) \mid u < v\} \cap \mathcal{E}$ and
192 $\mathcal{E}_2 = \{(u, v) \mid u > v\} \cap \mathcal{E}$. Observe that D_1 and D_2 are directed acyclic graphs, and thus Corollary
193 2 implies that for $j \in \{1, 2\}$ there exists a threshold T_j, dimension $d_j = \mathcal{O}((\Delta + 2) \log |\mathcal{V}|)$, and
194 mapping $\phi_j : \mathcal{V} \to \mathbb{R}^{2d_j}$ such that $\mathrm{E}_{\text{G-Box}}(u, v; \phi, (\tau, \nu)) < T_j \iff (u, v) \in \mathcal{E}_j$. Let
195 $d = d_1 + d_2$, $T = \min(T_1, T_2)$, and define $\phi : V \to \mathbb{R}^{2d}$ and $B \in [0, 1]^{d \times k}$ as follows:

$$\forall i \in \{1, \dots, d_1\}, \quad \phi(u)_i^{\pm} = \phi_1(u)_i^{\pm}, \quad B_{i,1} = \tfrac{T}{T_1}, \quad B_{i,2} = 0,$$
$$\forall i \in \{d_1 + 1, \dots, d_1 + d_2\}, \quad \phi(u)_i^{\pm} = \phi_2(u)_i^{\pm}, \quad B_{i,1} = 0, \quad B_{i,2} = \tfrac{T}{T_2}.$$

196 Then we have $\mathrm{E}_{\text{GBC-Box}}(u, v; (\phi, B), (\tau, \nu)) = \min_{j \in \{1,2\}} \frac{T}{T_j} \mathrm{E}_{\text{G-Box}}(u, v; \phi_j, (\tau, \nu))$ which com-
197 pletes the proof with $k = 2$, and therefore implies the result for all $k > 2$. □

198 While motivated by a similar idea, note that VBC-Box is not a generalization of GBC-Box, and
199 thus an independent proof of representational capacity is required.

200 **Theorem 6.** *Given a directed graph $G = (\mathcal{V}, \mathcal{E})$ and any $\tau, \nu \geq 0$, there exists a threshold $T > 0$ and*
201 *parameters $\phi : \mathcal{V} \to \mathbb{R}^{2d} \times [0, 1]^d$ for which $\mathrm{E}_{\text{VBC-Box}}(u, v; \phi, (\tau, \nu)) < T$ if and only if $(u, v) \in \mathcal{E}$.*

202 *Proof.* Given a graph $G = (\mathcal{V}, \mathcal{E})$ let $H = \{\{u, v\} \mid u, v \in \mathcal{V}, u \neq v\}$. We will construct a VBC-
203 Box model in $d = |H|$ dimensions. For convenience, index the dimensions using $h \in H$. Then
204 let $\phi(u)_h^{\diamond} = 1$ if $u \in h$, and 0 otherwise. This means when evaluating the edge (u, v) or (v, u) we
205 simply need to compare in the 1-d space obtained by projecting the boxes to dimension $h = \{u, v\}$,
206 and furthermore that this dimension will not be used when considering any other edges. Any directed
207 graph on 2 nodes can be embedded using boxes in 1-dimension (observable by direct construction),
208 which completes the proof. □

209 While Theorem 5 and Theorem 6 are helpful in establishing that, unlike all prior box embedding
210 models and many other geometric embeddings, GBC-Box and VBC-Box are capable of modeling
211 any directed graph, the implied dimensionality bounds are far from optimal. In general, both models
212 tend to require fewer dimensions than alternatives, which we analyze theoretically in Appendix D
213 and observe empirically in Section 5.

4.4 Learning

215 We fit geometric embeddings by optimizing a binary cross entropy objective. Given some edges in a
216 training set $\mathcal{T}$, the loss is defined as

$$L_{BCE}(\phi; \boldsymbol{\lambda}) = \sum_{(u,v) \in \mathcal{T}} \left[\mathrm{E}(u, v; \phi, \boldsymbol{\lambda}) - \sum_{(u',v') \in N(u,v)} \log \left(1 - e^{-\mathrm{E}(u',v';\phi,\boldsymbol{\lambda})} \right) \right] \quad (10)$$

217 where $N(u, v)$ is the set of negative samples for each positive edge (u, v) within one batch. We
218 sample minibatches of positive edges in $\mathcal{T}$, and for each positive edge we sample 32 edges not in
219 $\mathcal{T}$ by randomly corrupting either the source or target node. We also use a self-adversarial negative
220 weight, as described in [26].

4.5 Limitations and Regularization

There are a few limitations of Binary Code Box Embeddings: 1) **Transitivity and Flexibility** In order to model cycles with separate sub-spaces, the inductive bias of asymmetric transitivity might be weakened. 2) **Inefficiency of Parameterization** For VBC-BOX, the number of parameters is increased by 50% compared with a G-BOX model in equal dimension. In addition, during inference, a large portion of box co-ordinates are "dead" when binary codes are near zero. Here, we introduce a regularization method and a tunable binary code size to resolve above concerns.

Regularization We can regularize the sparsity of binary codes to penalize dimension drop-off using the lasso with a regularization weight w_r, leading to a loss function $L = L_{BCE} + w_r * \|1 - B\|_{\ell^1}$.
Restricted Binary Code Size We can constrain the number of trainable binary codes to the last d_{bin} dimensions, setting the first $d - d_{\text{bin}}$ dimensions to 1. Both w_r and d_{bin} can provide a handle on mitigating issues mentioned above. One can increase w_r or decrease d_{bin} to preserve more transitivity and make full use of the model's parameters.

5 Experiments

5.1 Graph Reconstruction

While GBC-BOX and VBC-BOX can provably model any directed graph, the extent to which they can be trained to do so via gradient descent is another matter. In this section, we compare the reconstruction performance of various geometric embedding methods on a number of synthetic graphs, including simple directed cycles, trees and scale-free networks.

Baselines We compare our model with different baselines, including: *Vector**: We implement a vector baseline where each node is parameterized by a source and target vector, and the energy function is measured by $\mathrm{E}(u, v) = -\log \sigma(\phi(u)_{\text{source}} \cdot \phi(v)_{\text{target}})$. * indicates it uses source and target vectors. *Lorentzian*: It has been shown that hyperbolic space can embed undirected trees with arbitrarily low distortion [22], therefore we also compare with the baseline of squared Lorentzian distance on the hyperboloid [10, 2]. *Hyperbolic Entailment Cones* [7] model vertices as cones in hyperbolic space, combining the bias of hyperbolic space to represent tree-like graphs with the transitivity bias of region-based representations. We also compare with G-BOX and T-BOX, as defined in Section 2.2. We use Bayesian hyperparameter tuning based on the optimal F1 score for reconstruction.

Capacity over Cycles We evaluate each model's capacity to represent cycles, where simple directed cycles are generated with an increasing number of vertices ($|\mathcal{V}| = 2^2, 2^4, 2^8, 2^{12}$). In addition, we analyze the effect of adding one reverse edge to the cycle, where standard box embedding can model it (though high precision is required). Results are shown in Table 1. For a fair comparison, all methods use 12 parameters per vertex [4]. VBC-BOX shows the best reconstruction performance. Most other geometric baselines cannot model cycles. Surprisingly, VBC-BOX even outperforms the *Vector* baseline when $|\mathcal{V}| = 2^{12}$, indicating our model's high expressivity and surprising ease of training. Results also show that, in concordance with Proposition 1, G-BOX can model a cycle containing a reverse edge when $|\mathcal{V}|$ is small. We also see that T-BOX can model certain cycles when $|\mathcal{V}|$ is small, which is not surprising as Theorem 3 does not apply to T-BOX.

Capacity over Trees It is known that Box space can naturally capture asymmetric transitivity, and hyperbolic space is suitable for un-directed trees. In this experiment, we evaluate whether BC-Box maintains the inductive bias of Box Embeddings. Therefore, we generated four balanced (out-)trees, each has 2^{13} vertices and the number of branches are choosing from [2, 3, 5, 10]. And we also generated another four graphs with full transitive closures. We compare each methods with 12, 24 and 48 parameters per vertex. All results are average performances over four graphs. The results are shown in Table 2. As expected, G-BOX performs the best on transitively closed trees, while Lorentzian distance embedding performs well on balanced trees. It is shown that, GBC-BOX performs equally

---

[4]12 is the least common multiple of 2, 3, 4 which are the minimum number of parameters per node for G-BOX, t-box and VBC-BOX

Table 1: Reconstruction performance (F1 score) on directed cycles. All embeddings use 12 parameters per vertex. Different columns show results as we increase the number of vertices in the cycle.

Methods	Simple cycle				+ One bidirectional edge			
$\|\mathcal{V}\| =$	2^2	2^4	2^8	2^{12}	2^2	2^4	2^8	2^{12}
Vector*	**1.0**	**1.0**	**1.0**	0.676	**1.0**	**1.0**	**1.0**	0.666
Lorentzian	0.857	0.75	0.679	0.671	**1.0**	0.839	0.693	0.665
Hyperbolic Entailment Cones	0.75	0.667	0.662	0.635	0.75	0.692	0.654	0.645
G-Box	0.857	0.762	0.695	0.648	**1.0**	0.914	0.689	0.630
t-Box	**1.0**	**1.0**	0.996	0.685	**1.0**	**1.0**	0.992	0.659
GBC-Box	**1.0**	**1.0**	0.992	0.957	**1.0**	**1.0**	0.993	0.967
VBC-Box ($d_{bin} = d$)	**1.0**	**1.0**	**1.0**	**0.973**	**1.0**	**1.0**	**1.0**	**0.978**

well as G-Box on transitively closed trees, while the performance of VBC-Box is slightly lower. In contrast, the latter performs similarly or better than former in the transitive reduction trees. This suggests that more transitive bias is preserved in GBC-Box, while per vertex binary codes provide more representational flexibility. In addition, we get similar observation as [2], where Binary Code Boxes and t-Box outperform Lorentzian model on balanced trees when dimension size is increased, while performances of other geometric-based embeddings saturate on larger dimension sizes.

Table 2: Average reconstruction performance (F1 score) on balanced trees with $\|\mathcal{V}\| = 2^{13}$ and branching factors of $2, 3, 5, 10$ using $12, 24,$ and 48 parameters per vertex.

Methods	Balanced tree			w. transitive closures		
# Parameters / vertex =	12	24	48	12	24	48
Vector*	0.453	0.992	**1.0**	0.863	0.999	**1.0**
Lorentzian	**0.929**	0.935	0.951	0.975	0.979	0.995
Hyperbolic Entailment Cones	0.828	0.834	0.838	0.977	0.982	0.987
G-Box	0.832	0.830	0.842	**1.0**	**1.0**	**1.0**
t-Box	0.800	0.957	**1.0**	0.952	0.997	**1.0**
GBC-Box	0.901	0.961	0.983	**1.0**	**1.0**	**1.0**
VBC-Box ($d_{bin} = d$)	0.866	**0.994**	**1.0**	0.987	0.999	**1.0**

Capacity over Random Graphs Finally, we conduct experiments on scale-free-network, a simulation to real world graphs, where the edge distribution follows preferential attachment. In order to analyze how the cyclicity of graphs affects models' performances, we randomly sampled nearly three-thousand graphs using a wide range of parameters used for graph generation. Then we split the generated graphs into five bins by our proposed measure *cyclicity*: The proportion of vertices in a given graph involved in at least one cycle. In order to analyze models' effectiveness of modeling cycles instead of the density of graphs, we randomly sample 5 graphs from each bin where the average degree is in the range between 3 and 4. Results are shown in Figure 1. From the chart, we can see that our proposed model out-performs standard G-Box in all scenarios. And there exists significant gap when cyclicity is high. It also clearly shows that per vertex binary codes provide more representational capacity overall while global binary codes is less expressive in modeling cyclic graphs.

Figure 1: Reconstruction performance on Scale-free networks with $\|\mathcal{V}\| = 2^{13}$. We plot the F1 scores for G-Box, GBC-Box and VBC-Box using 24, 48, 96 parameters per vertex.

5.2 Link Prediction

We apply Binary Code Box on link prediction tasks to evaluate model's generalization ability. We employ following real world graphs: Google hyperlink network, Epinions trust network, CORA citation network, Twitter network, and DREAM5 gene regulatory networks. For more data statistics, see Appendix E. During training, all hyper-parameters are tuned via 10% cross-validation and then the test set results are averaged over 10 models of different random seeds, which trained on the full training set with the best hyper-parameters found during corss validation. We also tune w_r for all BC-Box models on the link prediction task.

In Table 3, we follow [30] and compare with several baselines including vector based baselines such as DeepWalk [17], LINE [27], node2vec [8], HOPE [15], APP [29], DGGAN [30] and our implementation of vector-based model with source and target parameters, and region based baselines such as G-BOX [3] and t-Box [2]. Models are evaluated using the Area Under ROC Curve (AUC). For fair comparison, we following [30] and use 128 parameters per vertex for all our models. Results show that our Binary Code Box models out-performs other baselines in most cases. And there is an clear trend that VBC-BOX performs the best when graphs are highly cyclic (on the left side of the table), then VBC-BOX with less binary code dimensions and GBC-BOX model start to perform better when graphs are less cyclic. In the case where a graph is mostly acyclic (on the right side of the table), G-BOX performs equally well. We can see that box geometry is superior than vector inner-product models in all scenario, even if graphs are less transitive, or has a lot of cycles, showing the strength of box geometry in modeling directed graphs. In addition, we also compared with another recent work from Sim et al. [23] over DREAM5 datasets, where we observe that Box embedding-based model out-performs their baselines significantly in most cases (On *In Silico* dataset, our model has an average precision of 68.8%, out-performs their best result 61.0%). Detailed results are in Appendix F.

Table 3: **Link prediction on real-world graphs** We use AUC as evaluation metric. Vector-based methods (upper), and box embedding variants (bottom). We evaluated over two negative sampling strategies for testing, *unif.*: uniformly sampled negatives; *corr.*: randomly corrupting source or target node in each positive edge in the test set. All methods use 128 parameters per vertex. Bold numbers perform the best, and underscored numbers perform the best in all non-box models

Methods	Google		Epinions		CORA		Twitter	
Cyclicity =	0.96		0.88		0.23		0.01	
Transitivity =	0.40		0.09		0.22		0.01	
	unif.	corr.	unif.	corr.	unif.	corr.	unif.	corr.
DeepWalk 2014	83.6	-	76.6	-	84.9	-	50.4	-
LINE-1 2015	89.7	-	78.8	-	84.7	-	53.1	-
node2vec 2016	84.3	-	89.7	-	85.3	-	50.6	-
HOPE* 2016	87.5	-	79.6	-	77.6	-	98.0	-
APP* 2017	92.1	-	70.5	-	76.6	-	71.6	-
DGGAN 2021	92.3	-	96.1	-	85.1	-	99.7	-
Vector(Ours)*	94.0	94.2	93.0	88.9	78.9	76.7	99.8	84.1
G-BOX	99.2	98.2	95.1	90.0	93.9	89.6	99.8	**86.3**
GBC-BOX	99.0	98.3	96.8	**92.7**	92.7	**90.3**	99.9	86.2
VBC-BOX ($0 < d_{bin} < d$)	99.3	98.3	97.6	92.2	**94.1**	89.7	99.9	86.1
VBC-BOX ($d_{bin} = d$)	**99.5**	**98.6**	**98.0**	92.4	93.2	88.8	99.8	85.7

6 Conclusion

In this paper, we introduced binary code box embeddings, a generalized box embedding method to model directed graphs. We provide both theoretical and empirical results showing the capacity of our model for modeling directed graphs. We demonstrated that this model can maintain a useful bias of transitivity while also modeling graphs with cycles.

References

[1] Robi Bhattacharjee and Sanjoy Dasgupta. What relations are reliably embeddable in euclidean space? *Conference on Algorithmic Learning Theory (ALT)*, 2020.

[2] Michael Boratko, Dongxu Zhang, Nicholas Monath, Luke Vilnis, Kenneth Clarkson, and Andrew McCallum. Capacity and bias of learned geometric embeddings for directed graphs. *Advances in Neural Information Processing Systems*, 34, 2021.

[3] Shib Sankar Dasgupta, Michael Boratko, Dongxu Zhang, Luke Vilnis, Xiang Lorraine Li, and Andrew McCallum. Improving local identifiability in probabilistic box embeddings. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[4] Shib Sankar Dasgupta, Xiang Lorraine Li, Michael Boratko, Dongxu Zhang, and Andrew McCallum. Box-to-box transformations for modeling joint hierarchies. In *Proceedings of the 6th Workshop on Representation Learning for NLP (RepL4NLP-2021)*, pages 277–288, 2021.

[5] Munmun De Choudhury, Yu-Ru Lin, Hari Sundaram, Kasim Selcuk Candan, Lexing Xie, and Aisling Kelliher. How does the data sampling strategy impact the discovery of information diffusion in social media? In *Fourth international AAAI conference on weblogs and social media*, 2010.

[6] Leo Egghe and Ronald Rousseau. *Introduction to informetrics: Quantitative methods in library, documentation and information science*. Elsevier Science Publishers, 1990.

[7] Octavian-Eugen Ganea, Gary Bécigneul, and Thomas Hofmann. Hyperbolic entailment cones for learning hierarchical embeddings. *arXiv preprint arXiv:1804.01882*, 2018.

[8] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 855–864, 2016.

[9] Albert Gu, Frederic Sala, Beliz Gunel, and Christopher Ré. Learning mixed-curvature representations in product spaces. *International Conference on Learning Representations (ICLR)*, 2019.

[10] Marc Law, Renjie Liao, Jake Snell, and Richard Zemel. Lorentzian distance learning for hyperbolic representations. *International Conference on Machine Learning (ICML)*, 2019.

[11] Xiang Li, Luke Vilnis, Dongxu Zhang, Michael Boratko, and Andrew McCallum. Smoothing the geometry of probabilistic box embeddings. *International Conference on Learning Representations (ICLR)*, 2019.

[12] Daniel Marbach, James C Costello, Robert Küffner, Nicole M Vega, Robert J Prill, Diogo M Camacho, Kyle R Allison, Manolis Kellis, James J Collins, and Gustavo Stolovitzky. Wisdom of crowds for robust gene network inference. *Nature methods*, 9(8):796–804, 2012.

[13] Maximillian Nickel and Douwe Kiela. Learning continuous hierarchies in the lorentz model of hyperbolic geometry. *International Conference on Machine Learning (ICML)*, 2018.

[14] Evelien Otte and Ronald Rousseau. Social network analysis: a powerful strategy, also for the information sciences. *Journal of information Science*, 28(6):441–453, 2002.

[15] Mingdong Ou, Peng Cui, Jian Pei, Ziwei Zhang, and Wenwu Zhu. Asymmetric transitivity preserving graph embedding. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 1105–1114, 2016.

[16] Gergely Palla, Illés J Farkas, Péter Pollner, Imre Derényi, and Tamás Vicsek. Directed network modules. *New journal of physics*, 9(6):186, 2007.

[17] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 701–710, 2014.

[18] Jiezhong Qiu, Yuxiao Dong, Hao Ma, Jian Li, Kuansan Wang, and Jie Tang. Network embedding as matrix factorization: Unifying deepwalk, line, pte, and node2vec. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining*, pages 459–467, 2018.

[19] Matthew Richardson, Rakesh Agrawal, and Pedro Domingos. Trust management for the semantic web. In *International semantic Web conference*, pages 351–368. Springer, 2003.

[20] Fred S Roberts. On the boxicity and cubicity of a graph. *Recent progress in combinatorics*, 1969.

[21] Frederic Sala, Chris De Sa, Albert Gu, and Christopher Re. Representation tradeoffs for hyperbolic embeddings. *International Conference on Machine Learning (ICML)*, 2018.

[22] Rik Sarkar. Low distortion delaunay embedding of trees in hyperbolic plane. *International Symposium on Graph Drawing*, pages 355–366, 2011.

[23] Aaron Sim, Maciej L Wiatrak, Angus Brayne, Páidí Creed, and Saee Paliwal. Directed graph embeddings in pseudo-riemannian manifolds. In *International Conference on Machine Learning*, pages 9681–9690. PMLR, 2021.

[24] Lovro Šubelj and Marko Bajec. Model of complex networks based on citation dynamics. In *Proceedings of the 22nd international conference on World Wide Web*, pages 527–530, 2013.

[25] Jiankai Sun, Bortik Bandyopadhyay, Armin Bashizade, Jiongqian Liang, P Sadayappan, and Srinivasan Parthasarathy. Atp: Directed graph embedding with asymmetric transitivity preservation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 265–272, 2019.

[26] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. *International Conference on Learning Representations (ICLR)*, 2019.

[27] Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *Proceedings of the 24th international conference on world wide web*, pages 1067–1077, 2015.

[28] Luke Vilnis, Xiang Li, Shikhar Murty, and Andrew McCallum. Probabilistic embedding of knowledge graphs with box lattice measures. *Association for Computational Linguistics (ACL)*, 2018.

[29] Chang Zhou, Yuqiong Liu, Xiaofei Liu, Zhongyi Liu, and Jun Gao. Scalable graph embedding for asymmetric proximity. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

[30] Shijie Zhu, Jianxin Li, Hao Peng, Senzhang Wang, and Lifang He. Adversarial directed graph embedding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 4741–4748, 2021.