# ChunkLLM: A Lightweight Pluggable Framework for Accelerating LLMs Inference

## Abstract

Transformer-based large models suffer from severe computational inefficiency due to the quadratic complexity of self-attention with respect to input tokens. Recently, block selection and compression methods have been proposed to alleviate this problem, but they either compromise semantic completeness or are inefficient in both training and inference. To address these challenges, we propose ChunkLLM, a lightweight and pluggable framework. Its core consists of two novel components: the QK Adapter (comprising Q- and K-Adapters) and the Chunk Adapter. The QK Adapter is integrated into each Transformer layer. It performs dual functions: compressing features and acquiring chunk attention. The Chunk Adapter is placed at the bottommost layer of the model. It identifies chunk boundaries by leveraging contextual information. Notably, we design an attention distillation method to train the QK Adapter, which enhances the recall rate of key chunks. During inference, chunk selection is triggered only when the current token is identified as a chunk boundary, thereby accelerating the model. Experimental evaluations show that ChunkLLM achieves comparable performance on short-text benchmarks, while retaining 99.49% of the performance on long-context benchmarks with only 52.10% of key-value cache. Moreover, it is up to 4.48× faster than the vanilla Transformer when processing 120K-long texts.

## 1 Introduction

Transformer-based large models (Vaswani et al., 2017) have demonstrated exceptional performance across a diverse range of tasks, including natural language processing (Srivastava et al., 2025; Zhang et al., 2024) and computer vision (Jiang et al., 2025). However, they have also faced significant challenges in terms of computational efficiency, particularly when scaling to larger structures and large context inputs. A core issue of efficiency limitations lies in the self-attention module, whose computational complexity is a quadratic relationship with respect to the number of input tokens. Such deficiencies in computational efficiency exert a profound impact on both the training complexity and inference latency of large models.

Efficiency optimization of Transformer has emerged as a pivotal research domain, with efforts predominantly converging into three methodological paradigms. **Linear attention**, such as Mamba (Dao and Gu, 2024), RWKV (Peng et al., 2023b, 2024), and RetNet (Sun et al., 2023), seek to approximate and substitute the traditional softmax-based self-attention mechanism. However, the fundamental architectural disparities between linear attention and conventional attention mechanisms introduce non-trivial challenges: adapting pre-existing Transformer models to integrate linear attention often incurs prohibitive conversion costs(Mercat et al., 2024; Wang et al., 2024; Bick et al., 2024), while alternative strategies necessitate end-to-end training of entirely new model from scratch(Li et al., 2025). Another optimization paradigm is **Sparse attention**, which leverages predefined structural constraints, such as sink-based attention mechanisms (Xiao et al., 2024) or sliding window attention mechanisms (Beltagy et al., 2020a), to exploit this sparsity. While these methods may yield certain effects, they often rely heavily on specific tasks, which can limit the overall generalization ability of the model. Dynamic sparse attention mechanisms (Tang et al., 2024; Jiang et al., 2024; Liu et al., 2024) filter out subsets of tokens during the inference phase. Although such methods can reduce the computational load of long sequences, they fail to significantly lower the high training costs of long-context models, making it difficult for large language models to efficiently scale to context-processing tasks with million-level token sizes. **Chunk Selective attention**, a special type of sparse attention, can be primarily cat-

egorized into two paradigms: fixed chunk (Lu et al., 2025; Yuan et al., 2025; Wang et al., 2025) and separators-based dynamic chunk (Chen et al., 2024). Both approaches partition the input into discrete chunks: the former conducts partitioning with a fixed length, which gives rise to semantic incompleteness; the latter utilizes separators for partitioning, yet ambiguities often emerge. For example, periods frequently occur in numerical values or abbreviations. Furthermore, during the inference phase, these methods necessitate chunk selection for each generated token, incurring additional computational overhead. It is thus evident that existing efficient approaches still exhibit inherent limitations.

To address the aforementioned challenges, We propose ChunkLLM, which can be directly constructed by integrating two lightweight and trainable modules into existing LLMs: **QK Adapter** and **Chunk Adapter**. The Chunk Adapter connects to the output of the bottommost Transformer layer and used for identify if a token is the last token of a chunk. The QK Adapter is in parallel with Q and K matrix at each Transformer layer. It maps full attention scores to chunk attention scores, and trained by a distillation approach.

The QK Adapter fulfills feature compression and the generation of chunk attention scores. To train the QK Adapter, we propose an attention distillation approach designed to enhance the recall rate of key chunks. During training, LLM parameters are kept frozen, with the Kullback–Leibler (KL) divergence between chunk attention scores and full attention scores serving as a guidance signal for optimization. The Chunk Adapter determines whether a token corresponds to a chunk boundary by leveraging contextual semantic information. During the inference phase, we exploit the Intra-Chunk Attention Consistency (ICAC) pattern such that chunk selection is only updated when the current token is identified as a chunk boundary, which substantially enhances inference efficiency. Furthermore, ChunkLLM can achieve inference performance comparable to that of models optimized for 120K context lengths, despite being trained solely on 4K context lengths, thereby substantially reducing the training overhead associated with 120K context scaling. Experimental results validate that ChunkLLM yields a 4.48× speedup relative to the vanilla Transformer when processing 120K long texts.

Our contributions are summarized as follows:

- We introduce ChunkLLM, which integrates two lightweight and pluggable components — the QK Adapter and the Chunk Adapter— into existing LLMs. It only requires fine-tuning these components based on the original model architecture.

- We propose an attention distillation-based training approach for the QK Adapter, which leverages KL divergence to align chunk attention with full attention, thereby enhancing the recall rate of key chunks. Furthermore, we introduce a novel ICAC pattern, which yields notable improvements in inference efficiency for long-context scenarios.

- Experimental evaluations show that, compared to the vanilla Transformer, ChunkLLM maintains 99.49% of the performance on long-context benchmarks while using only 52.10% of the key-value cache (KVcache). This reduction in memory footprint contributes to a substantial speedup, reaching up to 4.48× on 120K-long texts.

## 2 Method

The framework of ChunkLLM is shown in Figure 1. ChunkLLM can be built on any existing transformer-based LLMs. Two extra lightweight and pluggable modules are designed to support chunk-related capability. One is Chunk Adapter, which is used to identify chunk boundaries. The other is the Q Adapter and K Adapter, which is tailored for efficient feature compression and chunk selection. This section elaborates on the details of the two modules.

### 2.1 Chunk Adapter

In existing research on chunk-sparse attention, most methods adopt fixed-size chunking. However, this approach fails to account for the semantic structure of the sequence, leading to context fragmentation and incomplete retrieval of key information. To address this issue, we employ a sentence segmentation tool to preprocess the data and train a semantically aware Chunk Adapter.

The Chunk Adapter is a one-layer forward neural network (FNN) classifier for chunk boundary prediction. Its input is the output of the first layer of the LLM, and the output is if or not the token is a chunk boundary, as depicted in the Figure 1.

For an input $X = \{x_1, x_2, ..., x_{n-1}, x_n\}$ with $n$ tokens and their corresponding labels $Y =$

Figure 1: The framework of ChunkLLM.

$\{y_1, y_2, ..., y_{n-1}, y_n\}$, $y_i \in \{0, 1\}$, where 1 indicates that the token $x_i$ is a chunk boundary, 0 indicates that it does not, $\mathbf{H}_i^{l_1}$ be the output of $x_i$ at first layer. The FNN based Chunk Adapter is given as in equation 1

$$\hat{y}_i = \begin{cases} 1, & \text{Sigmoid}(\text{FFN}(\mathbf{H}_i^{l_1})) > \alpha, \\ 0, & otherwise \end{cases} \quad (1)$$

For training the chunk adapter, we employ the binary cross-entropy loss (BCE) (equation 2) as the objective function. Detailed information on the training dataset will be given in the experiment part.

$$\mathcal{L}_{CBP} = -\frac{1}{n}\sum_{i=1}^n [y_i \cdot log(\hat{y}_i) + (1-y_i) \cdot log(1-\hat{y}_i)] \quad (2)$$

## 2.2 QK Adapter

At each layer of the LLM, we incorporate a Q-Adapter and a K-Adapter which used to compress the attention and select the chunks.

For each layer, let $\mathbf{Q}$ and $\mathbf{K}$ be the attention matrix respectively, $c$ be the chunk number of the input, $Index\_c = \{i_1, i_2, ...i_c\}$ is the index set of chunk boundary tokens. Let $\hat{\mathbf{K}}$ be the K matrix of these tokens. We then calculate chunk attention scores as follows:

$$\mathbf{A}^s = Softmax(\frac{Mul(\bar{\mathbf{Q}}, \bar{\mathbf{K}}^T)}{\sqrt{d_k}}) \quad (3)$$
$$\bar{\mathbf{Q}} = FFN_Q(\mathbf{Q}), \bar{\mathbf{K}} = FFN_K(\hat{\mathbf{K}})$$

where $FFN_Q$ and $FFN_K$ is proposed Q-Adapter and K-Adapter, respectively, $\bar{\mathbf{Q}} \in \mathbb{R}^{n \times d_k}, \bar{\mathbf{K}} \in \mathbb{R}^{c \times d_k}$, $d$ is the dimension of the model, and $d_k$ is the dimension of head. $d_k \ll d$.

**Attention Distillation** We propose an attention distillation strategy to train the Q-Adapter and K-Adapter. Where, we treat $\mathbf{A}^s$ as student attention, and a type of aggregation of original attention $\mathbf{A}^t$ which is given in follow as teacher attention. The objective is to align the student's chunk attention with that of the teacher, improving the recall performance for key chunks. As shown in Figure 1.

For the sake of descriptive simplicity, we use a single head as an illustrative example to show how to aggregate original attention. The calculation procedure is detailed as follows:

$$\mathbf{A}^t = Aggregate(\mathbf{A})$$
$$\mathbf{A} = Softmax(\frac{Mul(\mathbf{Q}, \mathbf{K}^T)}{\sqrt{d_k}}) \qquad \mathbf{A} \in \mathbb{R}^{n \times n} \quad (4)$$

where $\mathbf{Q} \in \mathbb{R}^{n \times d_k}$ and $\mathbf{K} \in \mathbb{R}^{n \times d_k}$ are the matrices of query and key for one attention layer. For brevity, the mask operation is omitted from the description.

$Aggregate$ denotes the operation of summing the token scores within a single chunk. Specifically, for the matrix $\mathbf{A}$, the attention scores of tokens within each chunk are accumulated along the column direction, representing the attention scores of tokens to the chunk. For multi-head attention, we compute the average along the head dimension, yielding matrix $\mathbf{A}^t$.

We employ the Kullback-Leibler (KL) divergence as the loss function for attention distillation to guide the student model $\mathbf{A}^s$ in approximating the teacher model's attention scores $\mathbf{A}^t$:

$$\mathcal{L}_{AD}^N = KL(\mathbf{A}^t || \mathbf{A}^s) \quad (5)$$

We average the KL divergence losses across the N layers to obtain the final attention distillation loss:

$$\mathcal{L}_{AD} = \frac{1}{N}\sum_i^N \mathcal{L}_{AD}^i \quad (6)$$

During the training phase, the parameters of the backbone network are frozen, with only the Chunk Adapter and QK Adapter undergoing training, thereby achieving efficient training.

Figure 2: The decoding process of ChunkLLM.

Figure 3: Attention visualization of chunk selection during the inference phase. The test case is from the LongBench summarization task.

## 2.3 Inference

We use sparse attention in the decoding process during the inference phase. The decoding process of ChunkLLM is depicted in Figure 2, encompassing two primary steps: chunk boundary prediction and chunk selection.

**Chunk Boundary Prediction** During inference, the Chunk Adapter performs binary classification on each input token to identify the positions of chunk boundary tokens, which are then used for Chunk Selection.

**Chunk Selection** In ChunkLLM, two separate KV-caches are maintained, which we refer to as the Cold KV-cache and the Hot KV-cache. The former stores the KV vectors of all tokens and is kept in either GPU memory or CPU memory. The latter stores the KV vectors of the chunks retrieved during the chunk selection stage and is actually used in the attention computation. In this stage, given an input token, the corresponding q, k, v vectors are computed. The k and v vectors are stored in the Cold KV-cache. Then, referring to equation 3, $\mathbf{A}^s$ is computed, and the chunks corresponding to the top-k scores are selected. The k and v vectors of these chunks are loaded into the Hot KV-cache, where they are used together with the q vector to compute the actual attention scores, producing the predicted token.

**ICAC** We find a phenomenon during the model inference, as illustrated in Figure 3. The chunks attended to by tokens within a generated chunk exhibit substantial consistency, whereas chunk updates predominantly occur at chunk boundaries. We name this phenomenon the "**I**ntra-**C**hunk **A**ttention **C**onsistency (ICAC)".

ICAC makes it possible to save computational cost in chunk selection. Specifically, the update of the Cold KV-cache by Chunk Selection is only required when the Chunk Adapter identifies a new chunk boundary token; at all other times, the Cold KV-cache can be reused.

**Vote** In our experiments, we observed that not all layers of large language models exhibit sparse attention characteristics, and applying sparse attention distillation to these layers fails to achieve the expected results. We illustrate this phenomenon in Figure 11. One solution is to fall back to full attention implementation. However, we found that, considering the results across all layers, the retrieved chunks are highly consistent with the key chunks. Therefore, we propose addressing this issue by aggregating the retrieval results from all layers, counting votes to select the top-k chunks with the highest votes as the shared chunks for all layers.

## 3 Experiments and Results

### 3.1 Experimental Settings

#### 3.1.1 Model and Baselines

Two representative open-source models, Qwen2.5-7B (Team, 2024) and Llama3.1-8B (Dubey et al., 2024), are chosen as the target models for evaluation. We select StreamingLLM (Xiao et al., 2024), SepLLM (Chen et al., 2024) and SnapKV (Li et al., 2024) as the baselines to benchmark the proposed method. Detailed settings of the experimental parameters and training datasets are provided in Appendix A.1.

#### 3.1.2 Benchmarks

**Long Context Benchmarks** We select two long-context evaluation datasets, LongBench (Bai et al., 2024) and Needle In A Haystack (NIAH) (Kamradt, 2023), to assess the model's long-context ability. For detailed data and description, see Appendix A.2.

**Short Context Benchmarks** The selection of the evaluation datasets is primarily centered on

| Methods | SDQA | | | MDQA | | | Summary | | Few-shot | | | Synthetic | | Code | | Avg | KV |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | NQA | Qasper | MFQA | HQA | Musi | 2WQA | GR | QMS | SAM | TQA | TREC | PC | PR-en | LCC | RB-P | | |
| Qwen2.5-7B | 33.76 | 51.40 | 57.17 | 56.76 | 29.40 | 38.09 | 31.57 | 24.40 | 46.73 | 92.50 | 72.00 | 2.00 | 66.50 | 62.86 | 53.53 | 47.91 | 100.00 |
| ChunkLLM | 31.09 | 50.52 | **56.95** | 55.61 | **29.41** | **38.27** | **31.25** | 23.16 | 46.53 | 92.50 | 72.50 | **3.00** | **68.00** | 62.72 | **53.50** | **47.67** | 52.10 |
| SepLLM | 26.43 | 50.18 | 50.29 | 47.25 | 22.83 | 36.34 | 28.31 | 21.14 | 46.71 | 91.50 | 71.50 | 1.50 | 65.50 | **62.88** | 52.84 | 45.14 | 51.85 |
| StrmLLM | 28.88 | 50.37 | 50.47 | 51.60 | 24.55 | 37.76 | 30.36 | 22.27 | **46.84** | 91.50 | 72.00 | 2.50 | 67.50 | 62.68 | 53.07 | 46.16 | 67.75 |
| SnapKV | **31.68** | **50.56** | 56.26 | **56.11** | 28.19 | 37.64 | 28.95 | **24.51** | 46.44 | 92.50 | 72.00 | 1.50 | 66.00 | 62.36 | 53.47 | 47.21 | 51.62 |
| Llama3.1-8B | 40.88 | 51.72 | 58.47 | 52.68 | 35.80 | 42.52 | 30.64 | 24.44 | 47.10 | 92.83 | 73.00 | 0.50 | 39.00 | 68.56 | 67.48 | 48.37 | 100.00 |
| ChunkLLM | 39.14 | 49.93 | 53.45 | 52.29 | 34.40 | **42.98** | **31.05** | 23.89 | **47.20** | **93.08** | 72.50 | **0.50** | 38.50 | 68.31 | 66.99 | **47.62** | 53.85 |
| SepLLM | 36.23 | **51.16** | 51.81 | 47.70 | 27.83 | 40.85 | 27.12 | 21.84 | 46.89 | 92.83 | 72.00 | 0.50 | 37.50 | 68.50 | 66.54 | 45.95 | 53.08 |
| StrmLLM | 35.94 | 50.96 | **54.13** | 50.54 | 30.95 | 41.83 | 27.50 | 23.06 | 46.23 | 92.83 | **73.00** | 0.50 | **39.00** | 68.43 | **67.00** | 46.80 | 68.68 |
| SnapKV | **40.17** | 51.16 | 55.73 | **52.83** | **35.52** | 42.78 | 28.21 | **24.31** | 45.60 | 92.88 | 72.00 | 0.50 | 32.66 | **68.64** | 66.86 | 47.32 | 53.75 |

Table 1: Experimental results on LongBench.

the model's performance in three key dimensions: **General Knowledge**, which evaluates the model's breadth of knowledge coverage and the accuracy of its knowledge, MMLU (Hendrycks et al., 2021) (5-shot), SciQ (Welbl et al., 2017) (5-shot), Open-BookQA (Mihaylov et al., 2018) (25-shot); **Question Answering**, which evaluates the model's capabilities in question understanding and information matching, CommonsenseQA (Talmor et al., 2019) (5-shot), Social IQA (Sap et al., 2019) (15-shot), PIQA (Bisk et al., 2020) (25-shot); and **Reasoning** which evaluates the model's capabilities in logical abstraction and complex decision-making, HellaSwag (Zellers et al., 2019) (10-shot), Wino-Grande (Sakaguchi et al., 2020) (25-shot), ARC-c/ARC-e (Clark et al., 2018) (25-shot).

### 3.2 Main Results

### 3.2.1 Results on LongBench

We set the top-k ratio to 45% and the number of local chunks to 15 for ChunkLLM. The experimental results on the LongBench using Qwen2.5-7B and Llama3.1-8B are presented in Table 1. (The sensitivity experiments of hyperparameters top-k rate and local chunks are elaborated upon in Appendix A.3 and A.4, respectively.) Here, "StrmLLM" represents StreamingLLM (Xiao et al., 2024).

We take Qwen2.5-7B as an example for analysis, and the same conclusion holds for Llama3.1-8B. The following observations can be made: (1) In terms of overall average performance, ChunkLLM attains the optimal performance when compared to SepLLM, StreamingLLM and SnapKV, with respective improvements of 2.51, 1.07 and 0.46 (47.67 v.s. 45.14 v.s. 46.16 v.s. 47.21). In contrast to the short-text benchmark in Subsection 3.2.4, ChunkLLM demonstrates a remarkable improvement in long-context evaluation, which validates the advantage of ChunkLLM in retrieving key chunk information during long-context reasoning. (2) Notably, in the MDQA task, ChunkLLM

yields a substantial improvement over SepLLM. We argue that the core challenge of MDQA lies in the dispersion of critical information across distinct positions within the context, which places high demands on the model's context comprehension capability. SepLLM leverages separators as chunk features, which is plagued by constrained representational capacity and the problem of chunk semantic incompleteness. By contrast, ChunkLLM enriches the representational capacity of chunks via attention distillation, which enhances the recall rates of critical chunks. This, in turn, effectively boosts the model's long-context understanding capability. (3) Given a comparable level of KV cache usage, ChunkLLM attains 99.49% of the vanilla model's performance, relative to SepLLM, StreamingLLM and SnapKV, findings that further substantiate the superiority of ChunkLLM in long-context scenarios.

### 3.2.2 Results on NIAH

We set the top-k to 256 and the number of local chunks to 16 for ChunkLLM. As depicted in Figure 4, ChunkLLM outperforms SepLLM across all scenarios in the 64K-context NIAH evaluation conducted on Qwen2.5-7B and Llama3.1-8B, achieving superior performance. Notably, in scenarios where the context length exceeds 12K, SepLLM exhibits near-total loss of retrieval capability (visualized in red), whereas ChunkLLM retains performance comparable to the vanilla model. This discrepancy is primarily attributed to ChunkLLM's attention distillation mechanism, which strengthens the feature representational capacity of chunks. Consequently, during chunk selection, the model effectively identifies critical chunks with higher query relevance, leading to improved inference performance. Additionally, ChunkLLM exhibits a reduced KV-Cache utilization rate relative to SepLLM, which further corroborates the effectiveness of key chunk retrieval. We also conduct experi-

Figure 4: Needle-in-a-Haystack retrieval accuracy across context positions with 64k context length. The last column represents the KV-cache utilization rate.

Figure 5: Comparison of inference time per 10k tokens in the generation process on PG19 test set.

ments with StreamingLLM, as shown in Appendix A.5.

### 3.2.3 Inference Efficiency

We conduct runtime evaluations of Vanilla and ChunkLLM for 120K-token generation tasks on the PG19(Rae et al., 2019) test set, with metrics recorded every 10K tokens. We set the top-k to 256 and the number of local chunks to 16 for ChunkLLM. As shown in Figure 5, as the number of generated tokens increases, Vanilla's inference time rises linearly, while ChunkLLM maintains persistent stability in time consumption. In the 110K–120K token generation phase, ChunkLLM outperforms Vanilla by speedups of 3.84× and 4.48×, which corroborates the efficacy of the proposed ICAC mechanism. During ChunkLLM's inference phase, chunk updates occur exclusively at chunk boundaries, minimizing the updates frequency and thereby boosting inference efficiency. The inference time of all sub-processes can be found in Appendix A.6. We also conduct supplementary experiments using the FineWeb-Edu dataset, from which 1000 test corpora of 4k length are sampled. For the task of chunk boundary pre-

| Length | Methods | PPL | Total Time(s) |
|---|---|---|---|
| 120K | Qwen2.5-7B | 14.41 | 10,684.31 |
| | ChunkLLM | 16.23 | 4,782.62 |
| | Llama3.1-8B | 11.93 | 14,906.19 |
| | ChunkLLM | 12.89 | 5,963.83 |

Table 2: The perplexity and running time comparison on the PG19 test set.

diction, we evaluate its performance using three key metrics: precision, recall, and F1-score. The calculated results are 98.31, 95.54, and 96.91, respectively. Such promising performance indicators serve to verify the reliability and effectiveness of our chunk boundary prediction task.

We conduct experiments where these models generated 120K tokens, evaluating both total inference time and average perplexity (ppl) on the PG19 test set, and results are summarized in Table 2. Compared to the vanilla model, ChunkLLM yields a slight enhancement in ppl alongside a significant decrease in total inference time. The underlying reason is that while the vanilla model maintains semantic integrity, it incurs linearly increasing inference time as generated token count rises. Conversely, ChunkLLM reduces computational burden and speeds up inference by leveraging its chunk

| Methods | General Knowledge | | | Question Answering | | | Reasoning | | | | Avg | KV |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | MMLU | SciQ | OQA | CQA | SIOA | PIQA | Heag | WG | ARC-c | ARC-e | | |
| Qwen2.5-7B | 74.25 | 97.00 | 52.80 | 84.52 | 58.44 | 81.72 | 80.24 | 77.27 | 63.82 | 87.21 | 75.73 | 100.00 |
| ChunkLLM | 72.51 | 96.60 | **52.40** | **84.68** | 58.34 | **81.77** | 80.08 | **76.87** | **63.65** | **87.21** | 75.41 | 45.47 |
| SepLLM | 73.07 | **96.70** | 52.20 | 84.19 | 58.25 | 81.41 | 80.10 | 76.48 | 62.94 | 86.11 | 75.15 | 50.20 |
| StrmLLM | 73.31 | 96.60 | 52.00 | 84.28 | 58.19 | 81.39 | 79.76 | 76.64 | 62.79 | 86.36 | 75.13 | 45.14 |
| SnapKV | **74.05** | 96.60 | 52.40 | 84.03 | **58.40** | 81.61 | **80.18** | 76.71 | 63.28 | 87.16 | **75.44** | 45.57 |
| Llama3.1-8B | 65.30 | 97.60 | 48.00 | 74.28 | 54.04 | 83.19 | 81.76 | 80.03 | 57.85 | 84.55 | 72.66 | 100.00 |
| ChunkLLM | 64.78 | 97.30 | **48.40** | **74.45** | **54.76** | 82.75 | **81.84** | 79.01 | 57.68 | 84.55 | **72.55** | 45.04 |
| SepLLM | 64.32 | **97.40** | 47.40 | 74.10 | 54.25 | **83.03** | 81.68 | 79.01 | **57.93** | 84.09 | 72.32 | 50.32 |
| StrmLLM | 61.19 | 97.20 | 48.00 | 73.79 | 53.94 | 81.56 | 80.14 | 78.22 | 56.91 | 83.59 | 72.45 | 45.30 |
| SnapKV | 62.57 | 97.70 | 47.20 | 74.37 | 54.09 | 82.75 | 81.66 | **79.72** | 57.34 | **84.80** | 72.49 | 45.72 |

Table 3: Experimental results on short context benchmarks.

| Methods | SDQA | | | MDQA | | | Summary | | Few-shot | | | Synthetic | | Code | | Avg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | NQA | Qasper | MFQA | HQA | Musi | 2WQA | GR | QMS | SAM | TQA | TREC | PC | PR-en | LCC | RB-P | |
| Qwen2.5-7B | 33.76 | 51.40 | 57.17 | 56.76 | 29.40 | 38.09 | 31.57 | 24.40 | 46.73 | 92.50 | 72.00 | 2.00 | 66.50 | 62.86 | 53.53 | 47.91 |
| ChunkLLM | 31.09 | 50.52 | **56.95** | **55.61** | **29.41** | 38.27 | 31.25 | 23.16 | 46.53 | **92.50** | **72.50** | **3.00** | **68.00** | 62.72 | 53.50 | 47.67 |
| w/o vote | 30.78 | 45.00 | 51.53 | 54.96 | 28.00 | 38.17 | 30.82 | 23.49 | 46.58 | 90.50 | 70.00 | 2.50 | 67.50 | 62.54 | 52.78 | 46.34 |
| w/o ICAC | **31.36** | **50.94** | 56.84 | 55.61 | 28.50 | **38.59** | **31.86** | **23.93** | **46.66** | 92.50 | 72.50 | 2.50 | 67.50 | **63.16** | **53.88** | **47.76** |

Table 4: Ablation Study on LongBench, w/o vote: remove vote mechanism, w/o ICAC: remove ICAC pattern.

Figure 6: Inference efficiency of ICAC on PG19 test set.

### 3.2.4 Results on Short Text

The experimental results for short texts are presented in Table 3. The following conclusions can be drawn: (1) ChunkLLM performs comparably to or better than StreamingLLM, SepLLM, and SnapKV in terms of overall average metrics across both Qwen2.5-7B and Llama3.1-8B, achieving 99.57% and 99.84% of the Vanilla model's performance, respectively. Notably, ChunkLLM attains optimal performance across 5 out of the 10 evaluation tasks, validating its efficacy in short-text task scenarios. (2) We perform statistical analyses on the average utilization rate of the KV cache. In comparison with SepLLM, ChunkLLM achieves superior performance while consuming a lower volume of KV cache (45.47% v.s. 50.20%). Specifically, on the Llama3.1-8B model, ChunkLLM not only exhibits the minimal KV cache usage but also outperforms both SepLLM and StreamingLLM in terms of performance metrics. This finding further validates the precision of ChunkLLM in chunk recall, achieving a balanced trade-off between performance and memory consumption.

selection and ICAC mechanisms.

### 3.3 Ablation Study

#### 3.3.1 Effectiveness of Vote and ICAC

We validate the proposed vote mechanism and ICAC pattern based on the Qwen2.5-7B using the LongBench, with experimental results shown in Table 4. Removal of the vote mechanism leads to a 1.33 drop in overall performance (47.67 v.s. 46.34), which confirms the mechanism's efficacy, as it integrates inter-layer differences in chunk selection and minimizes interference arising from such discrepancies. We also conduct a visual investigation into the recall performance of top-k chunks across different layers, with comprehensive experimental results provided in Appendix A.8. Conversely, removing ICAC results in a marginal 0.09 improvement in overall performance. This slight gain is attributed to the increased frequency of chunk selection updates during the inference phase. Frequent chunk selection, however, poses a limitation of low inference efficiency. As shown in Figure 6, after ICAC is removed, the inference latency is 2.12 times higher than that of ChunkLLM in the 110K–120K token generation stage. Conversely, incorporating ICAC enables the model to maintain near-lossless performance alongside improved inference efficiency, which provides additional validation of ICAC's success. Appendix A.7 shows a case study of the ICAC.

#### 3.3.2 Analysis of Fixed Chunks and Semantic Chunks

We conduct an experimental analysis of the fixed chunk method (FixLLM) on the NIAH task. To ensure consistent KV cache utilization and facilitate a

Figure 7: Visualization of fixed chunks and semantic chunks in NIAH test.

fair comparison, FixLLM is configured with a top-k of 384 and a local chunks of 24, while ChunkLLM is set to a top-k of 256 and a local chunks of 16. The experimental results are illustrated in Figure 7. As observed, under conditions of approximately consistent KV cache utilization, FixLLM exhibits an 8.23 reduction (87.78 v.s. 79.55) in accuracy relative to ChunkLLM on the 64K NIAH task. This discrepancy stems from the semantic incompleteness of fixed chunks, which in turn compromises chunk selection during the inference phase. In contrast, ChunkLLM leverages contextual semantic information to identify chunk boundaries, preserving the semantic integrity of chunks.

## 4 Related Work

**KV Cache Compression** Recent research has primarily focused on overcoming the limitations of Large Language Models (LLMs) in processing massive contextual inputs. SnapKV (Li et al., 2024) improves efficiency through KV cache compression, using attention scores to select and cluster important positional information; H2O (Zhang et al., 2023) implements a dynamic token retention policy that balances recent information and historically important information to optimize memory occupancy; StreamingLLM (Xiao et al., 2024) enables LLMs to handle sequences of infinite length without fine-tuning by retaining attention sinks and local tokens; PyramidInfer (Yang et al., 2024) and PyramidKV (Cai et al., 2024) optimize performance by adjusting the KV cache capacity across different layers. However, most methods in this category cannot be applied to the training phase. MoBA (Lu et al., 2025) proposes an innovative mixed block attention mechanism. ESA (Wang et al., 2025) reduces computational costs by selecting tokens most critical to the current generation for attention calculation.

**Sparse Attention** The sparse attention mechanism constructs sparse attention matrices by confining attention to predefined patterns, such as local

windows or fixed-stride block patterns. Beltagy et al. (2020b) combined dilated local window attention with task-specific global attention. NSA (Yuan et al., 2025) combines coarse-grained token compression and fine-grained token selection. SepLLM (Chen et al., 2024) finds that the segment information between separators can be effectively compressed into the separators themselves without causing significant information loss.

**Knowledge Distillation** Knowledge Distillation (Hinton et al., 2015), as a widely used model compression technique, aims to train a student model under the guidance of a teacher model (Rusu et al., 2016; Sanh et al., 2019; Gou et al., 2020). For text generation tasks, the standard KD method approximates the minimization of the forward Kullback-Leibler Divergence (forward KLD) between the generation distributions of the student and teacher models (Kim and Rush, 2016; Taori et al., 2023; Chiang et al., 2023; Peng et al., 2023a; Sanh et al., 2019).

## 5 Conclusion

We introduce ChunkLLM, a lightweight and pluggable framework, only necessitates fine-tuning lightweight components, QK Adapter and Chunk Adapter, on the basis of the original model architecture. And then we propose an attention distillation-based training approach for the QK Adapter, which leverages KL divergence to drive chunk attention toward approximating full attention, effectively enhancing the recall rate of key chunks. Furthermore, we introduce a novel "Intra-chunk Attention Consistency Pattern," which yields notable improvements in inference efficiency for long-context scenarios. Experimental results show that ChunkLLM attains a maximum speedup of 4.48× in comparison to the vanilla Transformer in the processing of 120K long texts.

## Limitations

ChunkLLM primarily focuses on plain text tasks but is limited in handling complex types of textual tasks, such as tables or JSON-formatted data, which is not researcher-friendly. In the future, we plan to incorporate table and JSON-formatted data into the training data to specifically enhance the model's performance in these areas.

## References

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024. Longbench: A bilingual, multi-task benchmark for long context understanding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 3119–3137. Association for Computational Linguistics.

Iz Beltagy, Matthew E Peters, and Arman Cohan. 2020a. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. 2020b. Longformer: The long-document transformer. *CoRR*, abs/2004.05150.

Aviv Bick, Kevin Li, Eric Xing, J Zico Kolter, and Albert Gu. 2024. Transformers to ssms: Distilling quadratic knowledge to subquadratic models. *Advances in Neural Information Processing Systems*, 37:31788–31812.

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, and 1 others. 2020. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 7432–7439.

Zefan Cai, Yichi Zhang, Bofei Gao, Yuliang Liu, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Baobao Chang, Junjie Hu, and Wen Xiao. 2024. Pyramidkv: Dynamic KV cache compression based on pyramidal information funneling. *CoRR*, abs/2406.02069.

Guoxuan Chen, Han Shi, Jiawei Li, Yihang Gao, Xiaozhe Ren, Yimeng Chen, Xin Jiang, Zhenguo Li, Weiyang Liu, and Chao Huang. 2024. Sepllm: Accelerate large language models by compressing one segment into one separator. *CoRR*, abs/2412.12094.

Wei-Lin Chiang, Zhuohan Li, Ziqing Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, and 1 others. 2023. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. *See https://vicuna. lmsys. org (accessed 14 April 2023)*, 2(3):6.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*.

Tri Dao and Albert Gu. 2024. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality. *arXiv preprint arXiv:2405.21060*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Jianping Gou, Baosheng Yu, Stephen John Maybank, and Dacheng Tao. 2020. Knowledge distillation: A survey. *CoRR*, abs/2006.05525.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. 2015. Distilling the knowledge in a neural network. *CoRR*, abs/1503.02531.

Huiqiang Jiang, Yucheng Li, Chengruidong Zhang, Qianhui Wu, Xufang Luo, Surin Ahn, Zhenhua Han, Amir H Abdi, Dongsheng Li, Chin-Yew Lin, and 1 others. 2024. Minference 1.0: Accelerating prefilling for long-context llms via dynamic sparse attention. *Advances in Neural Information Processing Systems*, 37:52481–52515.

Yiwen Jiang, Deval Mehta, Siyuan Yan, Yaling Shen, Zimu Wang, and Zongyuan Ge. 2025. Wise: Weak-supervision-guided step-by-step explanations for multimodal llms in image classification. *arXiv preprint arXiv:2509.17740*.

G. Kamradt. 2023. Llmtest needleinahaystack.

Yoon Kim and Alexander M Rush. 2016. Sequence-level knowledge distillation. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pages 1317–1327.

Aonian Li, Bangwei Gong, Bo Yang, Boji Shan, Chang Liu, Cheng Zhu, Chunhao Zhang, Congchao Guo, Da Chen, Dong Li, and 1 others. 2025. Minimax-01: Scaling foundation models with lightning attention. *arXiv preprint arXiv:2501.08313*.

Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. 2024. Snapkv: LLM knows what you are looking for before generation. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

Di Liu, Meng Chen, Baotong Lu, Huiqiang Jiang, Zhenhua Han, Qianxi Zhang, Qi Chen, Chengruidong Zhang, Bailu Ding, Kai Zhang, and 1 others. 2024. Retrievalattention: Accelerating long-context llm inference via vector retrieval. *arXiv preprint arXiv:2409.10516*.

Anton Lozhkov, Loubna Ben Allal, Leandro von Werra, and Thomas Wolf. 2024. Fineweb-edu: the finest collection of educational content.

Enzhe Lu, Zhejun Jiang, Jingyuan Liu, Yulun Du, Tao Jiang, Chao Hong, Shaowei Liu, Weiran He, Enming Yuan, Yuzhi Wang, Zhiqi Huang, Huan Yuan, Suting Xu, Xinran Xu, Guokun Lai, Yanru Chen, Huabin Zheng, Junjie Yan, Jianlin Su, and 6 others. 2025. Moba: Mixture of block attention for long-context llms. *CoRR*, abs/2502.13189.

Jean Mercat, Igor Vasiljevic, Sedrick Keh, Kushal Arora, Achal Dave, Adrien Gaidon, and Thomas Kollar. 2024. Linearizing large language models. *arXiv preprint arXiv:2405.06640*.

Meta. 2024. Llama 3 model card.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a suit of armor conduct electricity? A new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pages 2381–2391. Association for Computational Linguistics.

Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. 2023a. Instruction tuning with gpt-4. *arXiv preprint arXiv:2304.03277*.

Bo Peng, Eric Alcaide, Quentin Anthony, Alon Albalak, Samuel Arcadinho, Stella Biderman, Huanqi Cao, Xin Cheng, Michael Chung, Matteo Grella, and 1 others. 2023b. Rwkv: Reinventing rnns for the transformer era. *arXiv preprint arXiv:2305.13048*.

Bo Peng, Daniel Goldstein, Quentin Anthony, Alon Albalak, Eric Alcaide, Stella Biderman, Eugene Cheah, Xingjian Du, Teddy Ferdinan, Haowen Hou, and 1 others. 2024. Eagle and finch: Rwkv with matrix-valued states and dynamic recurrence. *arXiv preprint arXiv:2404.05892*.

Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, and Timothy P Lillicrap. 2019. Compressive transformers for long-range sequence modelling. *arXiv preprint arXiv:1911.05507*.

Andrei A. Rusu, Sergio Gomez Colmenarejo, Çaglar Gülçehre, Guillaume Desjardins, James Kirkpatrick, Razvan Pascanu, Volodymyr Mnih, Koray Kavukcuoglu, and Raia Hadsell. 2016. Policy distillation. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*.

Nipun Sadvilkar and Mark Neumann. 2020. PySBD: Pragmatic sentence boundary disambiguation. In *Proceedings of Second Workshop for NLP Open Source Software (NLP-OSS)*, pages 110–114, Online. Association for Computational Linguistics.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. 2020. Winogrande: An adversarial winograd schema challenge at scale. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 8732–8740. AAAI Press.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of BERT: smaller, faster, cheaper and lighter. *CoRR*, abs/1910.01108.

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan Le Bras, and Yejin Choi. 2019. Social iqa: Commonsense reasoning about social interactions. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, pages 4462–4472. Association for Computational Linguistics.

Saurabh Srivastava, Sweta Pati, and Ziyu Yao. 2025. Instruction-tuning llms for event extraction with annotation guidelines. *arXiv preprint arXiv:2502.16377*.

Yutao Sun, Li Dong, Shaohan Huang, Shuming Ma, Yuqing Xia, Jilong Xue, Jianyong Wang, and Furu Wei. 2023. Retentive network: A successor to transformer for large language models. *arXiv preprint arXiv:2307.08621*.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. 2019. Commonsenseqa: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pages 4149–4158. Association for Computational Linguistics.

Jiaming Tang, Yilong Zhao, Kan Zhu, Guangxuan Xiao, Baris Kasikci, and Song Han. 2024. Quest: Query-aware sparsity for efficient long-context llm inference. *arXiv preprint arXiv:2406.10774*.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. 2023. Stanford alpaca: An instruction-following llama model.

Qwen Team. 2024. Qwen2.5: A party of foundation models.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems*, 30.

Haoyu Wang, Tong Teng, Tianyu Guo, An Xiao, Duyu Tang, Hanting Chen, and Yunhe Wang. 2025. Unshackling context length: An efficient selective attention approach through query-key compression. *CoRR*, abs/2502.14477.

Junxiong Wang, Daniele Paliotta, Avner May, Alexander Rush, and Tri Dao. 2024. The mamba in the llama: Distilling and accelerating hybrid models. *Advances in Neural Information Processing Systems*, 37:62432–62457.

Johannes Welbl, Nelson F. Liu, and Matt Gardner. 2017. Crowdsourcing multiple choice science questions. In *Proceedings of the 3rd Workshop on Noisy User-generated Text, NUT@EMNLP 2017, Copenhagen, Denmark, September 7, 2017*, pages 94–106. Association for Computational Linguistics.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. 2024. Efficient streaming language models with attention sinks. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Dongjie Yang, Xiaodong Han, Yan Gao, Yao Hu, Shilin Zhang, and Hai Zhao. 2024. Pyramidinfer: Pyramid KV cache compression for high-throughput LLM inference. In *Findings of the Association for Computational Linguistics, ACL 2024, Bangkok, Thailand and virtual meeting, August 11-16, 2024*, pages 3258–3270. Association for Computational Linguistics.

Jingyang Yuan, Huazuo Gao, Damai Dai, Junyu Luo, Liang Zhao, Zhengyan Zhang, Zhenda Xie, Yuxing Wei, Lean Wang, Zhiping Xiao, Yuqing Wang, Chong Ruan, Ming Zhang, Wenfeng Liang, and Wangding Zeng. 2025. Native sparse attention: Hardware-aligned and natively trainable sparse attention. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 23078–23097. Association for Computational Linguistics.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. Hellaswag: Can a machine really finish your sentence? In *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- August 2, 2019, Volume 1: Long Papers*, pages 4791–4800. Association for Computational Linguistics.

Xiaobin Zhang, Liangjun Zang, Qianwen Liu, Shuchong Wei, and Songlin Hu. 2024. Event temporal relation extraction based on retrieval-augmented on llms. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE.

Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, Zhao Song, Yuandong Tian, Christopher Ré, Clark W. Barrett, Zhangyang Wang, and Beidi Chen. 2023. H2O: heavy-hitter oracle for efficient generative inference of large language models. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

# A Appendix

## A.1 Parameter Setting and Training Datasets

The Qwen2.5-7B and Llama3.1-8B models are trained with identical configurations. A cosine annealing strategy is adopted, with a maximum learning rate of 3e-5 and a warm-up period of 500 steps. Additionally, we use Adam optimizer with parameters beta1 = 0.9 and beta2 = 0.99. For the Qwen2.5-7B and Llama3.1-8B, the dimensions of the QK Adapter and Chunk Adapter are set to 3584 and 4096, respectively. The total number of additional parameters is 14.7M and 21M, respectively. $\alpha$ is set to 0.5 for chunk boundary prediction task. The training dataset comprised approximately 6B tokens, and the training process are conducted on 32 H200 GPUs for around 11,300 steps. We set training epoch is 1, and the attention distillation stage consum 11 hours, while the chunk boundary training stage took 1.5 hours.

For a fair comparison on long-context benchmarks, we set the initial cache capacity to 4, the local cache capacity to 4000, separator cache capacity to 4000 and the maximum cache capacity to 8192 for SepLLM (Chen et al., 2024). For StreamingLLM (Xiao et al., 2024), we configure the initial cache capacity as 4 and the local cache capacity as 8188. For SnapKV (Li et al., 2024), we set the cache capacity to 4096, the window size 32 and a max pooling operation with a kernel size of 7.

For short context benchmarks, we set the initial cache capacity to 4, the local cache capacity to 256, and the maximum cache capacity to infinity for SepLLM (Chen et al., 2024). For StreamingLLM (Xiao et al., 2024), we configure the initial cache capacity as 4 and the local cache capacity as 256.

The FineWeb-Edu dataset (Lozhkov et al., 2024) is employed as the training corpus in this study. Developed by the HuggingFaceFW team, this dataset undergoes filtering via an educational quality classifier, which constructed based on annotations generated by Llama3-70B-Instruct (Meta, 2024).

For preprocessing the training data, the pySBD tool (Sadvilkar and Neumann, 2020), a rule-based sentence boundary detection module that works out-of-the-box, is utilized to annotate the end positions of chunks in sequences, serving as foundational input for training the chunk boundary prediction module.

## A.2 Long Context Benchmarks

The average text length for most tasks ranges from 5k to 15k tokens in LongBench. For NIAH, the benchmark constructs prompts for LLMs by randomly inserting key information into long texts.

Table 5 presents the task name, abbreviations, evaluation methodologies, average lengths, and descriptive details of each subtask on LongBench.

## A.3 Top-K Sensitivity

We set the local chunks to 15 and conduct experiments on LongBench to evaluate the hyperparameter top-k rate. The results are presented in Table 6. Taking backbone Qwen2.5-7B as an example, the overall performance shows an upward trend as the top-k rate increases. This improvement is attributed to the introduction of more retrieved information, which enhances semantic richness. When the top-k rate is set to 45% (ChunkLLM 47.67 v.s. Qwen2.5-7B 47.91) , the overall performance reaches 99.49% of the vanilla model's performance, demonstrating the effectiveness of our selected top-k rate. This observed pattern also holds for Llama3.1-8B.

## A.4 Local Chunks Sensitivity

We also perform the hyperparameter experiment for local chunks on LongBench With the top-k rate fixed at 45%. The experimental results are presented in Table 7. Taking backbone Qwen2.5-7B as an example, the model's overall performance improves as local chunks increase. This is because the number of local chunks directly affects the quality of the retrieved top-k chunks. More local chunks provide richer semantics, leading to the retrieval of more relevant chunks. This observed pattern also holds for Llama3.1-8B.

## A.5 Compare with StreamingLLM on NIAH

As depicted in Figure 8, ChunkLLM outperforms StreamingLLM across all scenarios in the 64K-context NIAH evaluation conducted on Qwen2.5-7B and Llama3.1-8B with lower KV-cache usage, achieving superior performance. SteamingLLM leverages initial tokens and local tokens as its core token selection strategy. However, this design inherently limits its ability to effectively capture critical information situated in the middle segment of the input sequence, thereby resulting in a notable deficiency in long-context retrieval performance.

| Task | Subtask | Abbreviation | Evaluation | Avg Len | Description |
|------|---------|--------------|------------|---------|-------------|
| SDQA | NarrativeQA | NQA | Recall | 18,409 | Answer questions based on stories or scripts, including understanding of important elements such as characters, plots, themes, etc. |
| | Qasper | Qasper | Recall | 3,619 | Answer questions based on a NLP research paper, questions proposed and answered by NLP practitioners. |
| | MultiFieldQA-en | MFQA | Recall | 4,559 | Answer English questions based on a long article, which comes from a relatively diverse field. |
| MDQA | HotpotQA | HQA | Recall | 9,151 | Answer related questions based on multiple given documents. |
| | Musique | Musi | Recall | 11,214 | Answer related questions based on multiple given documents. |
| | 2WikiMultihopQA | 2WQA | Recall | 4,887 | Answer related questions based on multiple given documents. |
| Summary | GovReport | GR | Rouge-L | 8,734 | A summarization task that requires summarizing government work reports. |
| | QMSum | QMS | Rouge-L | 10,614 | A summarization task that requires summarizing meeting records based on user queries. |
| Few-shot | SAMSum | SAM | Rouge-L | 6,258 | A dialogue summarization task, providing several few-shot examples. |
| | TriviaQA | TQA | F1 | 8209 | Single document question answering task, providing several few-shot examples. |
| | TREC | TREC | Accuracy | 5,177 | A classification task that requires categorizing questions, includes 50 categories in total. |
| Synthetic | PassageCount | PC | Accuracy | 11,141 | Determine the total number of different paragraphs in a given repetitive article. |
| | PassageRetrieval-en | PR-en | Accuracy | 9,289 | Given 30 English Wikipedia paragraphs, determine which paragraph the given summary corresponds to. |
| Code | LCC | LCC | Edit Sim | 1,235 | Given a long piece of code, predict the next line of code. |
| | RepoBench-P | RB-P | Edit Sim | 4,206 | Given code in multiple files within a GitHub repository (including cross-file dependencies), predict the next line of code. |

Table 5: Task description on LongBench. SDQA: single-document question answering, MDQA: multi-document question answering.

### A.6 Inference Time of All Sub-processes

We measure the per-token total average time and chunk attention mechanism time for ChunkLLM with varying input lengths on PG19 test set during decoding, using Qwen2.5-7B and Llama3.1-8B backbones. (Times are averaged over 1000 generated tokens.) As shown in Figure 9(a), at an input length of 120K tokens, the chunk attention mechanism contributes only about 5.47% (2.04 v.s. 37.29) and 5.25% (2.35 v.s. 44.76) to the total time, respectively. This result demonstrates its low overhead.

In particular, we further analyze the time consumption of individual sub-processes within the chunk attention mechanism, which consists of four parts: model forward, KV cache update, chunk retrieval (Index chunk), and chunk boundary prediction (Predict chunk). The respective time costs and their proportions are illustrated in Figure 9(b) and (c).

It is evident that the model forward pass consumes around 80% of the time, whereas chunk retrieval(Index Chunk) and boundary prediction(Predict chunk) require a negligible 7% and 1%, respectively. The minimal cost of these auxiliary operations validates the high inference efficiency of ChunkLLM.

### A.7 Case Study

To illustrate the reasoning process, we randomly sample three examples from the passkey retrieval, Qasper and MultiFieldQA-en tasks in LongBench, with its visualization results presented in Figure 10. As observed in the figure, during the generation phase, the chunks attended to by tokens within the same chunk demonstrate remarkably high consistency, corresponding to the highlighted bands in the visualization, whereas shifts in attention occur exclusively at chunk boundaries. This empirical observation validates the effectiveness of the proposed ICAC pattern.

### A.8 Top-k Chunks Cross All Layers

Figure 11 presents the recall performance of top-k chunks across all layers based on Qwen2.5-7B. A consistent pattern emerges: the chunk recall rate in the lower layers (Layers 0–6) is relatively low, which we attribute to insufficient semantic representation. In contrast, the middle layers (Layers 7–20) demonstrate a notably higher chunk recall rate. Specifically, when top-k is set to 15, the recall rate of these middle layers exceeds 80%. This phenomenon, we contend, stems from the richer

| Methods | SDQA | | | MDQA | | | Summary | | Few-shot | | | Synthetic | | Code | | Avg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | NQA | Qasper | MFQA | HQA | Musi | 2WQA | GR | QMS | SAM | TQA | TREC | PC | PR-en | LCC | RB-P | |
| Qwen2.5-7B | 33.76 | 51.40 | 57.17 | 56.76 | 29.40 | 38.09 | 31.57 | 24.40 | 46.73 | 92.50 | 72.00 | 2.00 | 66.50 | 62.86 | 53.53 | 47.91 |
| ChunkLLM | 31.09 | 50.52 | 56.95 | 55.61 | 29.41 | 38.27 | 31.25 | 23.16 | 46.53 | 92.50 | 72.50 | 3.00 | 68.00 | 62.72 | 53.50 | 47.67 |
| Top-k rate 90 | 33.50 | 51.71 | 57.55 | 56.59 | 29.55 | 38.09 | 31.46 | 24.28 | 46.62 | 92.50 | 72.00 | 2.00 | 67.50 | 62.65 | 53.59 | 47.97 |
| Top-k rate 80 | 33.37 | 52.22 | 57.53 | 55.09 | 29.65 | 38.09 | 31.71 | 24.41 | 46.91 | 92.50 | 72.00 | 2.00 | 67.00 | 62.65 | 53.42 | 47.90 |
| Top-k rate 70 | 32.27 | 52.31 | 57.63 | 55.09 | 30.01 | 38.43 | 31 59 | 23.89 | 46.97 | 92.50 | 72.00 | 2.50 | 65.50 | 62.64 | 53.74 | 47.80 |
| Top-k rate 60 | 31.04 | 52.41 | 57.71 | 54.84 | 29.56 | 38.52 | 31.24 | 23.09 | 46.92 | 92.50 | 72.50 | 2.50 | 67.00 | 62.74 | 53.96 | 47.77 |
| Top-k rate 50 | 30.40 | 50.76 | 58.64 | 54.78 | 29.41 | 37.67 | 31.70 | 22.97 | 46.86 | 92.50 | 72.50 | 3.00 | 67.50 | 62.80 | 53.58 | 47.68 |
| Top-k rate 40 | 30.96 | 50.30 | 55.63 | 54.68 | 29.44 | 37.12 | 31.39 | 22.63 | 46.65 | 91.50 | 72.50 | 2.50 | 69.00 | 62.73 | 53.48 | 47.37 |
| Top-k rate 30 | 30.21 | 48.70 | 54.08 | 54.65 | 29.37 | 37.27 | 31.35 | 22.40 | 46.79 | 91.50 | 72.50 | 2.50 | 67.00 | 62.66 | 53.25 | 46.95 |
| Top-k rate 20 | 31.05 | 45.67 | 51.71 | 53.97 | 28.06 | 37.62 | 30.49 | 21.52 | 46.21 | 88.67 | 72.50 | 2.50 | 65.50 | 59.54 | 51.53 | 45.77 |
| Top-k rate 10 | 30.74 | 41.09 | 48.42 | 53.80 | 26.17 | 36.07 | 29.52 | 21.19 | 45.64 | 84.92 | 72.00 | 1.50 | 64.00 | 57.20 | 49.14 | 44.09 |
| Llama3.1-8B | 40.88 | 51.72 | 58.47 | 52.68 | 35.80 | 42.52 | 30.64 | 24.44 | 47.10 | 92.83 | 73.00 | 0.50 | 39.00 | 68.56 | 67.48 | 48.37 |
| ChunkLLM | 39.14 | 49.93 | 53.45 | 52.29 | 34.40 | 42.98 | 31.05 | 23.89 | 47.20 | 93.08 | 72.50 | 0.50 | 38.50 | 68.31 | 66.99 | 47.62 |
| Top-k rate 90 | 40.90 | 51.60 | 58.39 | 52.88 | 35.85 | 42.52 | 30.90 | 24.35 | 47.13 | 93.08 | 73.00 | 0.50 | 39.00 | 68.55 | 67.49 | 48.41 |
| Top-k rate 80 | 40.91 | 51.92 | 57.57 | 52.33 | 35.77 | 42.85 | 31.30 | 24.45 | 47.19 | 92.83 | 73.00 | 0.50 | 39.00 | 68.55 | 67.57 | 48.38 |
| Top-k rate 70 | 39.59 | 52.51 | 57.28 | 52.08 | 35.72 | 42.85 | 31.71 | 24.30 | 47.22 | 92.83 | 73.00 | 0.50 | 38.00 | 68.35 | 67.41 | 48.22 |
| Top-k rate 60 | 40.18 | 51.18 | 55.26 | 51.71 | 35.78 | 42.85 | 31.82 | 23.72 | 46.44 | 93.08 | 73.00 | 0.50 | 39.00 | 68.32 | 67.51 | 47.99 |
| Top-k rate 50 | 40.33 | 50.92 | 54.81 | 52.44 | 34.74 | 42.18 | 30.73 | 23.73 | 47.21 | 92.83 | 73.00 | 0.50 | 38.50 | 68.30 | 67.40 | 47.84 |
| Top-k rate 40 | 37.88 | 48.12 | 53.21 | 52.58 | 33.71 | 41.98 | 30.00 | 23.92 | 47.25 | 93.08 | 73.00 | 0.50 | 37.50 | 68.24 | 67.12 | 47.21 |
| Top-k rate 30 | 37.85 | 46.58 | 53.23 | 51.83 | 31.69 | 41.32 | 29.64 | 23.11 | 47.00 | 93.08 | 72.50 | 0.50 | 36.00 | 68.13 | 66.87 | 46.62 |
| Top-k rate 20 | 37.16 | 44.96 | 52.19 | 51.32 | 29.96 | 40.68 | 26.49 | 22.94 | 46.14 | 92.83 | 72.50 | 0.50 | 35.50 | 67.15 | 66.10 | 45.76 |
| Top-k rate 10 | 35.58 | 41.25 | 49.72 | 50.38 | 29.50 | 38.02 | 20.94 | 22.39 | 44.89 | 93.08 | 70.00 | 0.50 | 34.50 | 66.17 | 64.45 | 44.09 |

Table 6: Top-K sensitivity on LongBench.

| Methods | SDQA | | | MDQA | | | Summary | | Few-shot | | | Synthetic | | Code | | Avg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | NQA | Qasper | MFQA | HQA | Musi | 2WQA | GR | QMS | SAM | TQA | TREC | PC | PR-en | LCC | RB-P | |
| Qwen2.5-7B | 33.76 | 51.40 | 57.17 | 56.76 | 29.40 | 38.09 | 31.57 | 24.40 | 46.73 | 92.50 | 72.00 | 2.00 | 66.50 | 62.86 | 53.53 | 47.91 |
| ChunkLLM | 31.09 | 50.52 | 56.95 | 55.61 | 29.41 | 38.27 | 31.25 | 23.16 | 46.53 | 92.50 | 72.50 | 3.00 | 68.00 | 62.72 | 53.50 | 47.67 |
| Local-n 30 | 31.63 | 51.03 | 57.48 | 55.78 | 29.10 | 38.68 | 31.91 | 22.85 | 46.86 | 92.00 | 72.50 | 2.50 | 69.00 | 62.64 | 53.63 | 47.84 |
| Local-n 25 | 31.52 | 50.88 | 57.74 | 54.98 | 29.69 | 38.68 | 31.66 | 23.01 | 47.00 | 91.50 | 72.50 | 2.50 | 69.00 | 62.69 | 53.67 | 47.80 |
| Local-n 20 | 31.30 | 50.67 | 57.06 | 54.78 | 29.66 | 38.77 | 31.66 | 23.08 | 46.86 | 92.00 | 72.50 | 2.50 | 68.00 | 62.68 | 53.46 | 47.67 |
| Local-n 10 | 30.44 | 51.16 | 57.35 | 54.68 | 29.66 | 38.27 | 31.51 | 22.91 | 46.39 | 91.50 | 72.50 | 3.00 | 68.00 | 62.72 | 53.48 | 47.57 |
| Local-n 5 | 29.71 | 50.23 | 56.22 | 54.44 | 29.36 | 37.77 | 31.51 | 22.99 | 46.13 | 91.50 | 72.50 | 2.50 | 68.00 | 62.40 | 52.70 | 47.17 |
| Local-n 0 | 29.74 | 49.01 | 55.16 | 54.28 | 29.16 | 37.77 | 31.74 | 23.16 | 46.35 | 91.50 | 72.50 | 2.50 | 68.00 | 35.01 | 44.20 | 44.67 |
| Llama3.1-8B | 40.88 | 51.72 | 58.47 | 52.68 | 35.80 | 42.52 | 30.64 | 24.44 | 47.10 | 92.83 | 73.00 | 0.50 | 39.00 | 68.56 | 67.48 | 48.37 |
| ChunkLLM | 39.14 | 49.93 | 53.45 | 52.29 | 34.40 | 42.98 | 31.05 | 23.89 | 47.20 | 93.08 | 72.50 | 0.50 | 38.50 | 68.31 | 66.99 | 47.62 |
| Local-n 30 | 39.44 | 50.53 | 54.97 | 52.53 | 34.97 | 42.58 | 31.02 | 24.07 | 46.97 | 93.08 | 73.00 | 0.50 | 39.00 | 68.49 | 67.27 | 47.89 |
| Local-n 25 | 39.63 | 50.39 | 54.24 | 52.53 | 34.72 | 42.43 | 31.17 | 23.96 | 46.87 | 93.08 | 73.00 | 0.50 | 38.50 | 68.47 | 67.16 | 47.78 |
| Local-n 20 | 39.33 | 49.98 | 53.71 | 52.38 | 34.50 | 42.75 | 30.98 | 23.77 | 47.05 | 93.08 | 72.50 | 0.50 | 38.50 | 68.48 | 67.12 | 47.64 |
| Local-n 10 | 39.06 | 48.71 | 52.67 | 51.58 | 34.35 | 42.48 | 30.79 | 24.16 | 46.87 | 92.83 | 72.50 | 0.50 | 37.50 | 68.15 | 66.69 | 47.26 |
| Local-n 5 | 39.02 | 48.66 | 52.67 | 51.54 | 34.24 | 42.48 | 30.30 | 24.14 | 46.58 | 93.08 | 72.50 | 0.50 | 37.00 | 67.22 | 66.61 | 47.10 |
| Local-n 0 | 38.91 | 48.39 | 52.03 | 51.58 | 34.24 | 42.02 | 30.41 | 23.77 | 45.99 | 93.08 | 72.50 | 0.50 | 37.00 | 36.57 | 55.18 | 44.14 |

Table 7: Local chunks sensitivity on LongBench.

semantic representations inherent in the middle layers, coupled with the fact that our proposed attention distillation strategy effectively enhances the model's chunk selection capability. Conversely, the chunk recall rate in the highest layers (Layers 21–27) exhibits a downward trend; we attribute this to the functional role of the highest layers, which are primarily dedicated to facilitating the model's output generation. Notably, the chunk voting mechanism can effectively mitigate discrepancies between cross-layer chunks, and thereby enables the achievement of optimal performance.

Figure 8: Compare with StreamingLLM on Needle-in-a-Haystack. The last column represents the KV-cache utilization rate.

(a) Total time and time consumed by the chunk attention mechanism during inference.

(b) Cost time of each sub-process in chunk attention mechanism.

(c) Time proportion of each sub-process in chunk attention mechanism.

Figure 9: Inference time of all sub-processes.

(a) The sample is derived from the passkey retrieval task.

(b) The sample is derived from the Qasper task in LongBench.

(c) The sample is derived from the MultiFieldQA-en task in LongBench.

Figure 10: Case study of ICAC.

(a) Qwen2.5-7B with 4K input length.

(b) ChunkLLM with 4K input length.

(c) ChunkLLM with 32K input length.

Figure 11: Top-k chunks aross all layers.