Neural Structure Mapping For Learning Abstract Visual Analogies

Abstract

Building conceptual abstractions from sensory information and then reasoning about them is central to human intelligence. Abstract reasoning both relies on, and is facilitated by, our ability to make analogies about concepts from known domains to novel domains. Structure Mapping Theory of human analogical reasoning posits that analogical mappings rely on (higher-order) relations and not on the sensory content of the domain. This enables humans to reason systematically about novel domains, a problem with which machine learning (ML) models tend to struggle. We introduce a two-stage neural framework, which we call Neural Structure Mapping (NSM), to learn visual analogies from Raven's Progressive Matrices, an abstract visual reasoning test of fluid intelligence. Our framework uses (1) a multi-task visual relationship encoder to extract constituent concepts from raw visual input in the source domain, and (2) a neural module net-based analogy inference engine to reason compositionally about the inferred relation in the target domain. Our NSM approach (a) isolates the relational structure from the source domain with high accuracy, and (b) successfully utilizes this structure for analogical reasoning in the target domain.

1   Introduction

The ability to form abstractions of 'concepts' from information and then reason about them is central to human intelligence (Lake et al., 2015). Over the last decade, deep learning (DL) models that learn visual abstractions from raw images show strong validation performance on curated test datasets for image recognition (Krizhevsky et al., 2012), object detection (Ren et al., 2015), and scene classification (Zhou et al., 2017). However, unlike humans, DL models struggle with isolating these abstractions and systematically applying them to out of distribution test scenarios (Greff et al., 2020). One important way in which humans both build and reason about abstractions is through analogies (Mitchell, 2021). Structure Mapping Theory (SMT) of human analogical reasoning posits that perceptual information can be broken down into a domain consisting of objects and attributes, and structural relations between the attributes in the domain (Gentner, 1983). Consequently, SMT defines an analogy as a mapping between the structural relations across two domains, with no mapping of the attributes.

For example, to draw an analogy between the solar system and an atom, we can map the relational structure (`Planet` *revolves around* `Sun` $\implies$ `Electron` *revolves around* `Nucleus`, `Sun` *more massive than* `Planets` $\implies$ `Nucleus` *more massive than* `Electrons`). However, the domain attributes, such as the `Sun` being *yellow* or *hot* are not mapped to the `Nucleus` in drawing an analogy. This idea behind structure mapping was utilized by Hill et al. (2019) as a prior in training ML models for learning analogies. They first constructed a dataset on learning abstract visual analogies from Raven's progressive matrices (RPMs) (Raven, 2000). The RPM task is made up of two rows of five context

Submitted to 3rd Workshop on Shared Visual Representations in Human and Machine Intelligence (SVRHM 2021) of the Neural Information Processing Systems (NeurIPS) conference.

Figure 1: Neural Structure Mapping overview. Inset: An Abstract Visual Analogy Problem. Left (yellow box): Visual Relationship Encoder to extract the object, attribute and relationship from the first row of panels. Right (green box): Analogy Inference Engine that uses the relationship label to configure a neural module net for matching the correct candidate to the second row of panels.

panels, and four possible candidates to complete the analogy. The learner must understand the higher-order relation constituted by the first row of panels, and then choose the candidate satisfying the same relation with the the bottom row (shown inset in Figure 1). Hill et al. (2019) carefully curated the candidates presented during training to maximize differences in structural relations while being perceptually plausible. It was found that incorporating structural differences to maximize the importance of structure mapping during learning enabled DL models to learn visual analogies more accurately.

However, it is not always feasible to construct datasets that exploit the structure mapping prior. This would involve knowing combinatorially large possible relational structures beforehand and curating data to maximize learning these structures, which scales poorly with an increase in possible relational structures. To address this issue, we propose a two-stage Neural Structure Mapping (NSM) framework to learn abstract visual analogies (Figure 1). Our first-stage involves a visual relationship encoder that takes as input the visual context from the source domain and predicts the component visual concepts: `objects`, `attributes` and `relationship` in a multi-task manner. We then use the derived relation to dynamically build an analogy inference engine. Similar to structure mapping in humans, our engine utilizes only the relation from the source domain to pick the candidate panel that best fits the analogy. We incorporate compositional reasoning into our approach by using a neural module network (Andreas et al., 2016; Johnson et al., 2017b) as our engine. Our modular neural engine dynamically adapt its structure to align (Xu et al., 2020) with the structural `relationship`, thus explicitly incorporating the structure mapping process in our NSM model.

2 Problem Setup

Each abstract visual analogy task (Hill et al., 2019) consists of five context panels P_{con}^{1-5}, and four candidate panels P_{can}^{1-4}. The context panels are arranged in a matrix with two rows of three columns each, with the final panel in the second row missing. The first row of panels P_{con}^{1-3} express a semantically related triplet $\mathcal{R} = \{o, a, r\}$, that is composed of two lower-order perceptual visual concepts: `object` o and `attribute` a, and one higher-order semantic visual concept: `relationship` r. The objective is to choose a candidate $c \in \bigcup_{i=1}^{4} \{P_{\text{can}}^i\}$ that, upon substitution in place of the missing panel, represents the same `relationship` as the first row of panels.

Further details regarding the `objects` and `attributes`, which together constitute the domain d of a triplet, are provided in Appendix B. The authors also present several systematic generalization test splits of the dataset (Appendix B) which share the idea that understanding an analogy involves identifying the higher-order visual relation from the source domain and applying it to a different target domain.

The `relationship` ($r \in \{$`progression, AND, OR, XOR`$\}$) defines the semantics across a row of panels and is the core abstraction of analogical reasoning. It can be of classified into two types: Unary and Binary. The Unary relation, `progression`, is composed of a function applied to a single

panel to produce the next panel in a row. On the other hand, the Binary relations, (AND, OR, XOR), are composed of a function applied to the first two panels in a row to generate the final panel. Hill et al. (2019) hypothesized that introducing a prior on the learning process that requires the learner to correctly identify the `relationship` would align with how humans learn structure for analogical mapping. They designed this prior by carefully controlling the candidate panels P_{can}^{1-4} presented during model training (Figure 4) to consist of candidates that are all semantically possible to complete the visual analogy (called Learning Analogies By Contrasting (LABC)). Each candidate satisfies one possible `relationship` with the target domain panels but only the correct panel satisfies the `relationship` from the source domain panels. It was found that LABC training significantly improved the ability to learn analogies in DL models compared to training with merely perceptually possible candidates (Normal training). In fact, even a mixed training regime consisting of both LABC and Normal problems showed significant improvement on the Normal training regime.

3 Method

In our work, we take a complimentary approach to Hill et al. (2019) for learning abstract visual analogies in RPMs. Instead of depending on explicitly labeled candidates for mapping relational structure, we build a model that dynamically configures its structure based on the relational structure extracted from the source domain. Internally, our approach is made up of two different neural networks that correspond to the two separate tasks in our pipeline. We provide detailed discussion on each of these networks in our pipeline next (for implementation details of the networks please refer to Appendix G).

Visual Relationship Encoder   The Visual Relationship Encoder, $\mathcal{R}_{\text{pred}} = \phi(P_{\text{con}}^{1-3})$, segregates the abstract relationship triplet in the source domain panels into its constituent `object`, `attribute`, and `relationship` (corresponding to the structure extraction phase in SMT). The encoder ϕ is made up of a multi-task neural network. We use a convolutional neural network (CNN) C_ϕ to first extract a visual feature vector $vis_\phi^i = C_\phi(P_{\text{con}}^i)$ for each context panel. The extracted visual features are then sequentially fed into a long short term memory network (LSTM) R_ϕ to generate visual sequence features seq_ϕ of the source domain. The hidden layer vector after the third sequence panel is taken as the encoded features of the source domain $seq_\phi = R_\phi(vis^{1-3})$. The source domain feature vector seq_ϕ is then passed to a fully connected layer $l_\phi^{\text{shared}} = FC_\phi^{\text{shared}}(seq_\phi)$ that is shared between all three visual components. The shared linear feature vector l_ϕ^{shared} is then passed through three different fully connected layers $l_\phi^{\text{task}} = FC_\phi^{\text{task}}(l_\phi^{\text{shared}})$ for each task $t \in \{$`object`, `attribute`, `relation`$\}$ classification. Finally, each l_ϕ^{task} is passed through a fully connected layer $out_\phi^{\text{task}} = FC_\phi^{\text{out}^{\text{task}}}(l_\phi^{\text{task}})$ of sizes 2, 5, and 4 for the object, attribute, and relation prediction tasks respectively. A Softmax over the outputs out_ϕ^{task} yields a probability distribution over the possible $\{o, a, r\}$ values that constitute the triplet $\mathcal{R}$.

(a) Unary Relation   (b) Binary Relation

Figure 2: Types of `relationship` and corresponding Analogy Inference Engine layout. Only correct candidate panel shown. See Section 3 for details

Analogy Inference Engine The Analogy Inference Engine, $c = \pi(P_{con}^{4-5}, P_{can}^{1-4}, r)$, maps the source relationship r extracted by the Visual Relationship Encoder to the target domain P_{con}^{4-5} to identify the correct candidate c that completes the visual analogy. This step of our NSM model corresponds to the structure mapping phase in SMT, in which humans apply relations extracted from the source domain to a new domain to reason about concepts in the target domain. To generalize systematically to new domains and attribute values, we utilize a modular approach (Andreas et al., 2016) to build our analogy inference engine. Similar to Johnson et al. (2017b), we utilize modules with a generic architecture in order to enable computational reasoning and parameter reuse. The layout of the module network is chosen adaptively from two possible layouts based on the source domain relation at inference time. Each layout first processes the individual panels through the Stem module to extract visual features, followed by the Unary module. In the first layout, the Unary module outputs for the target domain panels P_{con}^{4-5} are combined using a Binary module, and the outputs for the second panel P_{con}^{5} and each candidate panel P_{can}^{1-4} are combined using another Binary module (Figure 2a). The outputs of both the Binary modules are then fed into the Classifier module. In the second layout, the Unary module outputs for the target domain panels P_{con}^{4-5} are similarly combined using a Binary module. However, the output of this Binary module and the Unary candidate output is directly fed into the Classifier module (Figure 2b). We provide further discussion on our neural modules and their layouts in Appendix C.

4 Experiments and Results

Visual Relationship Encoder Results We test the relationship prediction accuracy of our encoder across all five generalization splits, with each possible set of analogy candidates (Contrasting, Normal, Mixed). Our relationship encoder was able to isolate the component relationship from the source domain with a high degree of accuracy (min: 82.4%, max: 86.04%) across all generalization splits and all three types of candidates (Figure 5). Furthermore, since the encoder utilizes only the source domain information in determining the relation, we observe no drop between training and test accuracy across all generalization splits.

By identifying the visual relationship in the source domain, the output of the visual relationship encoder is able to determine the layout for the subsequent analogy inference engine. Since the inference engine chooses between only two possible layouts, a baseline that always chooses the majority class layout would lead to a correct choice in 75% of problems. Hence, our encoder must achieve a high degree of accuracy in identifying the correct layout to beat this baseline. Our encoder is indeed able to identify the layout matching the reasoning problem with near perfect accuracy (min: 98.42%, max: 99.9%). The full results for layout prediction across all generalization splits and training regimes are in Table 7 in Appendix F.

Analogy Inference Engine Results

Does the modular analogy inference engine generalize systematically?

We hypothesize that choosing a modular engine for analogy inference enables compositional reasoning about novel domain values (objects and attributes). In Table 1 we compare the generalization performance of our engine on the Novel Attribute Value: Extrapolation and Novel Domain: Line

Model	Test Accuracy % (Contrasting/Normal)					
	Novel Domain (Line Type)			Novel Attribute Value (Extrapolation)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
CNN-LSTM (Hill et al., 2019)	76/50	45/57	75/54	62/45	43/44	56/39
ResNet	25.01/24.95	41.8/46.96	25.01/24.95	**78.97**/55.2	48.5/49.55	62.59/52.73
ResNet-Parallel	79.35/**66.51**	52.43/**76.7**	79.67/**75.9**	61.97/57.23	54.86/56.69	65.71/57.17
WReN	73.71/57.49	53.42/62.64	61.1/49.93	74.25/**61.36**	61.23/**61.4**	**70.57/63.31**
NSM (ours)	78.14/59.55	70.64/64.31	78.53/64.1	65.24/57.14	62.33/58.08	58.4/50.98
NSM (full context)	**79.75**/59.55	**76.18**/62.43	**80.57**/65.74	73.36/59.94	**66.75**/59.84	63.47/52.92

Table 1: Candidate prediction test accuracy comparison for Novel Domain and Novel Attribute values. Our approach achieves the best generalization accuracy for the most number of possible train/test candidate scenarios across all models (4/12), and is within $< 1\%$ of the best generalization performance for half of all scenarios (6/12). Higher accuracy == Better systematic generalization.

(a) Novel Attribute Value: Extrapolation

(b) Novel Domain: Line Type

Figure 3: Systematic generalization test performance with Normal training candidates which lack the structure mapping prior at training time.

Type test splits of the analogy dataset. Our approach achieves the highest test accuracy across all three training candidate regimes in the Novel Domain setting when tested with contrasting candidates. Furthermore, our approach yields high test accuracy (highest or within $< 1\%$) for the Contrasting and Normal training candidate regimes in the Novel Attribute Value setting. Thus, our NSM approach is better at systematic generalization to novel visual domains than monolithic neural networks. For completeness, we provide the results for both our evaluation setups across all training and test regimes in Tables 8 and 9 in Appendix F.2

Does our model learn the structure mapping prior?

We specifically evaluate the Normal training scenario where the candidates presented to the learner are drawn randomly and lack the structure mapping prior explicitly present when training with Contrasting. Since our NSM model explicitly captures and maps the structure of the visual analogy, thus making up for the lack of the structural prior in the candidates, we anticipate that the test performance of our model trained with normal candidates would outperform other baselines. We visualize the generalization performance of this training scenario for the Novel Domain Value: Extrapolation and Novel Domain: Line Type generalization splits in Figure 3. We observe that our model outperforms other networks when averaged across both types of candidates during testing, demonstrating that it learns the structure mapping prior better than other models.

How important is structure mapping in drawing the correct analogy?

We verify the importance of explicitly mapping structure on the performance of our NSM approach by comparing our results when the visual relationship encoder infers the correct `relationship` versus when it does not. We find that the test error rate is consistently lower by a factor of 2 when the mapping is correct versus when it is incorrect. Thus, the performance of our NSM model relies strongly on the ability of our encoder to infer the correct structural `relationship`.

Structure mapping	Test (Contrasting) % Error Rate			Test (Normal) % Error Rate			Test (Mixed) % Error Rate		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Correct	**9.9**	**10.61**	**7.48**	**22.38**	**11.44**	**10.35**	**16.14**	**11.01**	**8.93**
Incorrect	21.53	20.86	17.48	47.32	21.35	19.64	34.41	21.1	18.56

Table 2: Comparing candidate prediction error rate with correct/incorrect `relationship` extraction on the Novel Domain Transfer split.

5   Conclusions and Future Work

In this work, we introduce a two-stage neural framework for learning abstract visual analogies based on the Structure Mapping Theory of human analogy making. Our approach is able to generalize systematically to novel target domains, compensate for the lack of a structure mapping prior in candidate selection, and successfully exploit the process of extracting and mapping the relationship structure. In future work, we plan to investigate search-based (e.g. Neural Architecture Search) as well as differentiable (e.g. attention-based) methods for generating the layouts of our Analogy Inference Engine. Furthermore, we would like explore approaches that combine our structure mapping framework into existing methods for reasoning about Raven's Progressive Matrices beyond analogy making.

References

Jacob Andreas, Marcus Rohrbach, Trevor Darrell, and Dan Klein. Neural module networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 39–48. IEEE, 2016.

Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron Courville. Systematic generalization: What is required and can it be learned? In *International Conference on Learning Representations*, 2018.

David Barrett, Felix Hill, Adam Santoro, Ari Morcos, and Timothy Lillicrap. Measuring abstract reasoning in neural networks. In *International Conference on Machine Learning*, pp. 511–520. PMLR, 2018.

David J Chalmers, Robert M French, and Douglas R Hofstadter. High-level perception, representation, and analogy: A critique of artificial intelligence methodology. *Journal of Experimental & Theoretical Artificial Intelligence*, 4(3):185–211, 1992.

Kezhen Chen, Irina Rabkina, Matthew D McLure, and Kenneth D Forbus. Human-like sketch object recognition via analogical learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 1336–1343, 2019.

Brian Falkenhainer, Kenneth D Forbus, and Dedre Gentner. *The structure-mapping engine*, volume 1275. Department of Computer Science, University of Illinois at Urbana-Champaign, 1986.

Jerry A Fodor. *The language of thought*, volume 5. Harvard university press, 1975.

Jerry A Fodor and Zenon W Pylyshyn. Connectionism and cognitive architecture: A critical analysis. *Cognition*, 28(1-2):3–71, 1988.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

Dedre Gentner. Structure-mapping: A theoretical framework for analogy. *Cognitive science*, 7(2): 155–170, 1983.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the binding problem in artificial neural networks. *arXiv preprint arXiv:2012.05208*, 2020.

Felix Hill, Adam Santoro, David Barrett, Ari Morcos, and Timothy Lillicrap. Learning to make analogies by contrasting abstract relational structure. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=SylLYsCcFm.

Douglas R Hofstadter and Melanie Mitchell. The copycat project: A model of mental fluidity and analogy-making. 1994.

N Ichien, Q Liu, S Fu, KJ Holyoak, AL Yuille, and H Lu. Visual analogy: Deep learning versus compositional models. In *Proceedings of the 43rd Annual Meeting of the Cognitive Science Society*, 2021.

Justin Johnson, Ranjay Krishna, Michael Stark, Li-Jia Li, David Shamma, Michael Bernstein, and Li Fei-Fei. Image retrieval using scene graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3668–3678, 2015.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2901–2910, 2017a.

Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Judy Hoffman, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Inferring and executing programs for visual reasoning. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2989–2998, 2017b.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd Int. Conf. on Learning Representations (ICLR)*, 2015.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.

Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *International Conference on Machine Learning*, pp. 2873–2882. PMLR, 2018.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

João Loula, Marco Baroni, and Brenden Lake. Rearranging the familiar: Testing compositional generalization in recurrent networks. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 108–114, 2018.

Andrew Lovett and Kenneth Forbus. Modeling visual problem solving as analogical reasoning. *Psychological review*, 124(1):60, 2017.

Gary F Marcus. *The algebraic mind: Integrating connectionism and cognitive science*. MIT press, 2019.

Melanie Mitchell. *Analogy-making as perception: A computer model*. 1993.

Melanie Mitchell. Abstraction and analogy-making in artificial intelligence. *arXiv preprint arXiv:2102.10717*, 2021.

Niv Pekar, Yaniv Benny, and Lior Wolf. Generating correct answers for progressive matrices intelligence tests. *Advances in Neural Information Processing Systems*, 33, 2020.

John Raven. The raven's progressive matrices: change and stability over culture and time. *Cognitive psychology*, 41(1):1–48, 2000.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 91–99, 2015.

Adam Santoro, David Raposo, David G Barrett, Mateusz Malinowski, Razvan Pascanu, Peter Battaglia, and Timothy Lillicrap. A simple neural network module for relational reasoning. *Advances in Neural Information Processing Systems*, 30, 2017.

Steven Spratley, Krista Ehinger, and Tim Miller. A closer look at generalisation in raven. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXVII 16*, pp. 601–616. Springer, 2020.

Damien Teney, Peng Wang, Jiewei Cao, Lingqiao Liu, Chunhua Shen, and Anton van den Hengel. V-prom: A benchmark for visual reasoning using visual progressive matrices. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 12071–12078, 2020.

Duo Wang, Mateja Jamnik, and Pietro Lio. Abstract diagrammatic reasoning with multiplex graph networks. *arXiv preprint arXiv:2006.11197*, 2020.

Taylor Webb, Zachary Dulberg, Steven Frankland, Alexander Petrov, Randall O'Reilly, and Jonathan Cohen. Learning representations that support extrapolation. In *International Conference on Machine Learning*, pp. 10136–10146. PMLR, 2020.

Keyulu Xu, Jingling Li, Mozhi Zhang, Simon S. Du, Ken ichi Kawarabayashi, and Stefanie Jegelka. What can neural networks reason about? In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rJxbJeHFPS.

Licheng Yu, Zhe Lin, Xiaohui Shen, Jimei Yang, Xin Lu, Mohit Bansal, and Tamara L. Berg. Mattnet: Modular attention network for referring expression comprehension. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

269 Chi Zhang, Feng Gao, Baoxiong Jia, Yixin Zhu, and Song-Chun Zhu. Raven: A dataset for relational
270 and analogical visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and
271 Pattern Recognition*, pp. 5317–5327, 2019.

272 Kecheng Zheng, Zheng-Jun Zha, and Wei Wei. Abstract reasoning with distracting features. *Advances
273 in Neural Information Processing Systems*, 32:5842–5853, 2019.

274 Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10
275 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine
276 Intelligence*, 2017.

A   Related Work

Learning Analogies   Gentner (1983)'s SMT defines an analogy as a *comparison in which relational predicates, but few or no object attributes, can be mapped from base to target* domains. Symbolic models based on SMT (Falkenhainer et al., 1986), including those designed for RPMs (Lovett & Forbus, 2017), rely on first extracting a rule based representation of the domains from the perceptual input. Other cognitive analogy models based on Active Symbol theory (Hofstadter & Mitchell, 1994; Mitchell, 1993) or High-Level Perception theory (Chalmers et al., 1992) do not separate the structure extraction and mapping process, nor rely on mapping the structure syntax across domains. Our approach is not directly related to these models. Hill et al. (2019) introduced the dataset for learning analogies from RPMs and utilized several neural network architectures to directly learn from visual data. Their key contribution was to introduce the SMT prior into the dataset during candidate selection. Webb et al. (2020) introduced Temporal Context Normalization to explicitly learn visual features that can support extrapolation, and tested it on the Visual Analogy Extrapolation Challenge (VAEC) dataset. Both of these approaches are complementary to ours. Other DL approaches most similar to ours are the Part-Composition Model (Ichien et al., 2021) and Chen et al. (2019)'s approach. However, unlike our model, these models rely on availability of very structured intermediate representations like semantic segmentation maps, and do not use the extracted structural representations to explicitly configure the reasoning model.

Abstract Reasoning   Hill et al. (2019)'s dataset (released publicly for commercial use under Apache License 2.0) is directly derived from the Procedurally Generated Matrices (PGM) dataset introduced by Barrett et al. (2018) to test the ability of neural networks to perform abstract reasoning on RPM problems. RPM tests are an important measure of fluid intelligence in humans (Raven, 2000), and the PGM dataset provided a sufficiently large sample size for training neural networks on this problem. Following this work, two new RPM datasets were also released: RAVEN (Zhang et al., 2019), which utilized additional rules and structured rule annotations, and V-PROM (Teney et al., 2020), which utilized real images. DL approaches to RPM tasks can be roughly categorized into three types. The first is relation learning approaches, such as WReN (Barrett et al., 2018), which models all pairwise relationships between the matrix panels using relation networks (Santoro et al., 2017), and MXGNet (Wang et al., 2020), which learns row-based node embeddings and then performs a graph classification on the resulting candidate graphs. Second is rule learning approaches, such as DRT (Zhang et al., 2019), that learns a structured Stochastic Image Grammar of the abstract rules, and LEN (Zheng et al., 2019) that utilizes a logic embedding network along with a curriculum to learn with increasingly distracting features. Third is object-centric learning, such as Rel-AIR (Spratley et al., 2020), that obtains object embeddings generated via Attend-Infer-Repeat for each panel, and Pekar et al. (2020)'s method that utilizes both Variational AutoEncoders and an adversarial loss for candidate generation. Our model can be broadly fit into rule learning by way of the encoder, followed by relation learning via the analogy inference engine. However, our general approach towards explicitly extracting structure and mapping it is complimentary to these ideas and can be used in conjunction with several of them.

Systematic Generalization   Systematic generalization refers to the ability to generalize to novel concepts (out of distribution data) by understanding them as compositions of known concepts (Bahdanau et al., 2018). It is underpinned by three important characteristics: (1) systematicity, the ability to generalize to semantically related concepts; (2) productivity, the ability to iteratively apply compounding to generalize from constituent concepts to their recurrence; and (3) localism, the ability to iteratively apply reductionism to generalize from repeated constituent concepts to the singular. The ability to generalize systematically has been previously explored in human cognition (Fodor & Pylyshyn, 1988), natural language processing models (Lake & Baroni, 2018), and language-grounded computer vision models (Bahdanau et al., 2018). It has its origins in human cognition and was formalized by Fodor (1975) under the 'Language of Thought' hypothesis. Cognitive scientists have expressed reservations about the ability of connectionist models to generalize systematicitally (Fodor & Pylyshyn, 1988; Marcus, 2019). Investigation of neural language models showed that systematic generalization still poses a challenge for DL (Lake & Baroni, 2018; Loula et al., 2018). A key reason deep neural networks lack systematicity is due to their propensity towards 'shortcut learning' (Geirhos et al., 2020). This suggests that DL models rely on exploiting a few number of predictive features instead of considering all possible information about the data while drawing conclusions. Consequently, this leads to poor generalization when the key predictive features are changed, even

though the central evidence remains the same. For example, DL approaches to solving RPM problems were discovered to rely on evaluating the mode across all candidates in the RAVEN dataset and a significant drop in generalization performance was observed when the models were tested without the shortcut on the RAVEN-Fair dataset (Spratley et al., 2020). On the other hand, neural module networks (Andreas et al., 2016; Johnson et al., 2017b) generalized well systematically when their layout aligned well with specific language-grounded reasoning problems (Bahdanau et al., 2018). Hence, we utilize a modular approach in building our analogy inference engine, which in turn utilizes the `relationship` structure inferred by our encoder to automatically align itself to the problem. This is a form of conditional computation.

B   Problem Setup: Additional Details

The object (o $\in$ {line, shape}) and attribute (a $\in$ {quantity,colour,type,size,position}) together constitute the visual domain d of the triplet $\mathcal{R}$. Each possible attribute can take ten values $v(a) \in \{1, 2, ..., 9, 10\}$ (normalized). The domain of the first row of panels P_{con}^{1-3} defines the source domain d_{source} of the analogy, and the domain of the second row of panels $\{P_{con}^{4-5}, c\}$ defines the target domain d_{target}. The dataset consists of seven unique possible domains such that $d \in$ {shape quantity, shape colour, shape type, shape size, shape position, line type, line colour}. To test the systematic generalization in learning visual analogies, the dataset has five different generalization splits that require the ability to recognize the `relationship` across both novel domain d and attribute a values:

- **Novel Domain Transfer:** The training set consists of 42 ordered pairs of d_{source} and d_{target} while the remaining 7 (7*7 - 42) pairs are present only in the test set i.e.
  $d_{source}^{train} \times d_{target}^{train} \cap d_{source}^{test} \times d_{target}^{test} = \varnothing$.

- **Novel Domain Type** (line type **and** shape color)**:** The training set does not contain any problems with the held-out domain i.e. $d^{train} \notin$ {line type} or $d^{train} \notin$ {shape colour}, while each problem in the test set involves the held-out domain.

- **Novel Domain Values (Interpolation and Extrapolation):** The training and test sets are made of two mutually exclusive sets of attribute values. For the extrapolation split, $v(a)^{train} \in \{1, 2, 3, 4, 5\}$ while $v(a)^{test} \in \{6, 7, 8, 9, 10\}$. For interpolation, $v(a)^{train} \in \{2, 4, 6, 8, 10\}$ while $v(a)^{test} \in \{1, 3, 5, 7, 9\}$.

(a) Contrasting   (b) Normal

Figure 4: Two different types of candidates for the same target domain. (a) Contrasting candidates, each of which satisfies a relationship structure and highlights the Structure Mapping prior during candidate selection. (b) Normal candidates, which are merely perceptually similar to the context.

C   Neural Module Network Details

Our engine is made up of four different types of neural modules:

- The `Stem` module performs a series of convolution operations with stride=2. It takes the original grayscale images of size $1 \times 160 \times 160$ as input and returns a visual feature map of size $8 \times 9 \times$

410   9 ($C \times H \times W$). Each of P_{con}^{4-5} and P_{can}^{1-4} panels is first passed through the `Stem` module to extract
411   visual features before being processed by the rest of the engine.

412   • The `Unary` module is a residual block with two 3×3 convolution layers. It receives one feature
413   map ($C \times H \times W$) as input, and returns one feature map of ($C \times H \times W$) as output.

414   • The `Binary` module receives two feature maps, concatenates them along the channel dimension,
415   and uses a 1×1 convolution to project them to C dimensions. It then passes the combined feature
416   maps through a residual block, and returns one feature map of ($C \times H \times W$) as output.

417   • The `Classifier` module also receives two feature maps, and projects them to C dimensions. It
418   then flattens the feature maps and passes them through two fully connected layers to generate a
419   probability distribution over the relations.

420 The generic architecture of our modules allows for a combinatorially large number of possible
421 architectural layouts of our inference engine. Previous work in language-grounded reasoning tasks
422 like VQA (Johnson et al., 2017b) or referring expression comprehension (Yu et al., 2018) uses a
423 semantic parse tree generated from natural language to generate layouts for neural module networks.
424 Since our inference engine $\pi(r)$ relies only on the relationship label from the source domain, it lacks
425 the rich compositional structure available in language-grounded reasoning to arrange the modular
426 network layout. However, generating the proper layout for neural module networks is fundamental to
427 their ability to generalize systematically (Bahdanau et al., 2018).

428 As discussed in Section 3, we dynamically chose between two layouts of our neural module network
429 based on the `relationship` type. Our rationale behind choosing these layouts comes from the
430 knowledge of the possible `relationships` our engine has to reason about. Each layout aligns
431 algorithmically (Xu et al., 2020) with a reasoning algorithm for identifying the relationship across
432 three panels. The first layout models Algorithm 1 to identify a Unary relationship like `progression`
433 (not to be confused with a `Unary` module) between panels 1, 2 and 3. The second layout models
434 Algorithm 2 to identify a Binary relationship (`OR, AND, XOR`) across panels 1 and 2 in the last panel.

Algorithm 1 To Identify Unary Relation

Require: Panels P_1, P_2, P_3
 1: $D_1 \leftarrow$ *extractObjectsAndAttributes*(P_1)
 2: $D_2 \leftarrow$ *extractObjectsAndAttributes*(P_2)
 3: $D_3 \leftarrow$ *extractObjectsAndAttributes*(P_3)
 4: $R_{12} \leftarrow$ *artihmeticOperation*(D_1, D_2)
 5: $R_{23} \leftarrow$ *artihmeticOperation*(D_2, D_3)
 6: Result $\leftarrow$ *isConsistent*(R_{12}, R_{23})
 7: **return** Result

Algorithm 2 To Identify Binary Relation

Require: Panels P_1, P_2, P_3
 1: $D_1 \leftarrow$ *extractObjectsAndAttributes*(P_1)
 2: $D_2 \leftarrow$ *extractObjectsAndAttributes*(P_2)
 3: $D_3 \leftarrow$ *extractObjectsAndAttributes*(P_3)
 4: $R_{12} \leftarrow$ *binaryOperation*(D_1, D_2)
 5: Result $\leftarrow$ *isConsistent*(R_{12}, D_3)
 6: **return** Result

---

436 We do not explicitly train our modules to correspond to any individual functional form. Instead, we
437 expect the module instantiations to learn the corresponding function in the reasoning step simply
438 by learning from the classification loss. For example, in the reasoning algorithms above, a `Unary`
439 module can learn *extractObjectsAndAttributes()*, `Binary` module can learn *artihmeticOperation()*
440 and *binaryOperation()*, and `Classifier` module can learn *isConsistent()* functions. This enables
441 the modules to share parameters across relation functions (such as two different instantiations of
442 *binaryOperation()* for `AND` and `OR`), as well as across objects and attributes. This also enables us to
443 utilize general purpose modules which could potentially be arranged in several possible combinations
444 depending on the reasoning problem, and can be easily extended beyond the abstract visual analogy
445 setting of only four `relationships` to large number of possible `relationships` in real-world
446 datasets like Scene Graph (Johnson et al., 2015) and CLEVR (Johnson et al., 2017a).

447 **Do algorithmically aligned engine layouts learn corresponding relations better?**

448 We chose two possible layouts for our modular engine based on their alignment with algorithms for
449 identifying a Unary or Binary relation across three panels in RPM problems. We expect Layout-A
450 (Figure 2a) to better align with Unary (`progression`) problems and Layout-B (Figure 2b) to better
451 align with Binary (`AND, OR, XOR`) problems. In order to verify this empirically we train each layout
452 individually with similar training hyperparameters as the full engine. We control the overall validation
453 accuracy to select trained models which perform similarly across the full dataset. Next, we compare

Modular Layout	Training Accuracy			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Layout A	**88.47**/94.66	**91.81**/91.3	91.72/**93.91**	**87.63**/94.21	**89.74/90.89**	91.51/**95.19**	**79.54/76.32**	**90.76**/90.6	91.47/**92.03**	**83.53/85.3**	**90.26**/90.74	91.49/**93.61**
Layout B	86.44/95	90.79/**92.4**	**92.85**/93.54	85.35/**94.28**	77.6/90.28	**91.96**/94.73	74.83/75.05	89.5/**91.43**	**92.83**/91.86	80.01/84.7	83.64/**90.85**	**92.4**/93.3

Table 3: Comparison of the analogy inference engine layouts on corresponding (unary/binary) `relationship` types

the test accuracy for Unary and Binary relations for the trained Layout-A and Layout-B models in Table 3.

In practice, we found significant stochasticity in the performance between Unary and Binary relation types across both layouts. From the observed results, we cannot conclusively say that our layouts necessarily align better with one or the other relationship problem. One possible explanation for this could be that there can be alternate algorithms for evaluating the same relation, which align algorithmically with these layouts. This is similar to Xu et al. (2020)'s observation that a neural network which would have not aligned with the Bellman-Ford algorithm was found to align well with a different algorithm for the same dynamic programming problem.

Does having an adaptive engine enable better analogy inference?

We use an adaptive modular engine for analogy inference which chooses between two possible module net layouts at inference time. This enables our engine to compositionally reason about the underlying relation. We expect our adaptive setup to outperform a static layout since the engine can then chose to use a better fit layout according to the mapped `relationship` structure. To verify our hypothesis, we compare our input-adaptive engine to a fixed engine. We chose each candidate layout described in Section 3 as a possible inference engine. We call these fixed models Engine-A and Engine-B, and train them similar to our full model. We then compare the test accuracy performance of our full model, which we label Engine-Full, against the test accuracy fixed models.

Inference Engine	Training Accuracy %			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Engine-A	93.39	91.41	93.46	92.88	90.66	94.44	77.00	90.63	91.91	84.94	90.65	93.18
Engine-B	93.24	92.07	93.40	92.47	87.70	94.16	75.01	91.02	92.06	83.74	89.36	93.11
Engine-Full	93.12	91.04	93.32	91.07	90.40	93.30	74.57	88.92	90.02	82.81	89.66	91.65

Table 4: Comparison of fixed analogy inference engines versus the full adaptive engine

Empirically, we found that the adaptive engine was not able to outperform the fixed engines, contrary to our expectation. We believe there are two main reasons for this: (1) Our individual engines are not sufficiently differentiated in their performance on their respective reasoning tasks (as shown in Table 3), so there is not a significant performance gain in choosing one over the other, and (2) the number of possible reasoning scenarios is quite limited in the abstract visual analogy problem, and hence the adaptive engine is not able to benefit from learning a large number of mixture of experts.

D Multi-task versus Multi-label Visual Relationship Encoder

In our two-step structure mapping approach, we treat the structure extraction problem as a multi-task learning problem where the `relationship`, `object`, `attribute` prediction are treated as separate learning tasks. We could have alternatively treated the structure extraction problem as a multi-label classification problem and instead predicted the full triplet $\mathcal{R} = \{o, a, r\}$ from our model. A multi-label problem could in principle learn from added network interactions between the final classification layer weights for the domain components.

In order to draw a comparison between both these learning approaches, we trained a multi-label visual relationship encoder which predicts the triplet $\mathcal{R} = \{o, a, r\}$ as its output. We replaced the $l_\phi^{\text{task}} = FC_\phi^{\text{task}}(l_\phi^{\text{shared}})$ layers in out multi-task encoder with a $l_\phi^{\text{shared}_2} = FC_\phi^{\text{shared}_2}(l_\phi^{\text{shared}})$ layer, and the final classifiers $out_\phi^{\text{task}} = FC_\phi^{\text{out}^{\text{task}}}(l_\phi^{\text{task}})$ of sizes 2, 5, and 4, with one classifier $out_\phi = FC_\phi^{\text{out}}(l_\phi^{\text{shared}_2})$ of size 11 (2+5+4). For training, we used exactly the same procedure as the multi-task encoder (described in Section E.1).

We compared the performance of these models by evaluating there test accuracy across three different generalization splits: Novel Domain Transfer, Novel Domain: Line Type, and Novel Attribute Value:

Encoder	Extrapolation % Accuracy				Novel Domain Transfer % Accuracy				Novel Domain (line type) % Accuracy			
	Training	Test (Contrasting)	Test (Normal)	Test (Mixed)	Training	Test (Contrasting)	Test (Normal)	Test (Mixed)	Training	Test (Contrasting)	Test (Normal)	Test (Mixed)
Multi-task	86.23	84.78	84.75	84.76	86.96	82.52	82.75	82.64	86.16	84.93	84.58	84.75
Multi-label	86.11	84.84	84.98	84.91	85.31	84.13	84.38	84.25	85.80	85.16	85.15	85.16

Table 5: Comparison of `relationship` prediction accuracy of a multi-task versus a multi-label visual relationship encoder

Extrapolation. Since our encoder is not trained with the candidate panels, we restrict ourselves to one training regime (Contrasting) for this comparison. Our observations are reported below in Table 5.

We found the performance of the two types of relationship encoders to be quite similar in terms of the test accuracy for predicting the `relationship` from the source domain panels. In fact, the multi-label encoder was slightly better than the multi-task encoder across all generalization splits. Despite this, we still went ahead with using the multi-task encoder in our two-step approach since the multi-task learning network scales much better with the number of objects, attributes, and relationships in the perceptual domain.

E Experimental Setup

E.1 Visual Relationship Encoder

Training The Visual Relationship Encoder ϕ is trained using the source domain context panels P_{con}^{1-3} and the visual relationship labels $\mathcal{R} = \{o, a, r\}$. The cross-entropy loss for each task is obtained using the multi-task network's predictions and triplet labels. The total encoder loss is calculated as a weighted sum of the individual losses for object, attribute, and relation prediction:

$$\mathcal{L}_{\text{encoder}} = \alpha * \mathcal{L}_{\text{object}} + \beta * \mathcal{L}_{\text{attribute}} + \gamma * \mathcal{L}_{\text{relationship}} \tag{1}$$

Empirically, we found that the values of $\alpha = 0.5, \beta = 0.5, \gamma = 2.0$ led to higher validation accuracy. The model was trained for 100 epochs using the Adam optimizer (Kingma & Ba, 2015) with a learning rate of $1e-4$. The training was performed on a local cluster with 10 Nvidia GTX2080Ti GPUs. For each generalization split, the model was trained with contrasting, normal, as well as mixed candidates. The model with the best validation accuracy was chosen for testing (the validation set consisted of a similar set of analogy candidates as the training set).

E.2 Analogy Inference Engine

Training The Analogy Inference Engine π is trained using the target domain context panels P_{con}^{4-5}, the candidate panels P_{can}^{1-4}, the ground truth candidate label, and the ground truth visual relationship label r. The engine was trained for 100 epochs using the Adam optimizer with a learning rate of $1e^{-4}$. The training was performed on a local cluster with 10 Nvidia GTX2080Ti GPUs. Similar to the first stage, the engine was also trained with contrasting, normal, as well as mixed candidates. The model with the highest validation accuracy was chosen for testing (validation set consisted of a similar set of analogy candidates as the training set).

Testing For testing, we rely on the relationship label r_{pred} predicted by our encoder instead of ground truth r. Each candidate panel is fed parallely to the engine to generate its predictions for all four relations. In order to generate the candidate selection, we subset the probability of `relationship` r (r_{pred} during inference) for all candidates, and select the candidate with the highest corresponding probability.

While all baselines (see below) are trained with the full set of context panels P_{con}^{1-5}, our Analogy Inference Engine only utilizes the target domain panels P_{con}^{4-5} for context. Hence, we also provide the results of a full context model which utilizes all context panels P_{con}^{1-5}. For this purpose, we leverage our encoder which is trained with the remaining context panels $P_{\text{con}}^{1} - P_{\text{con}}^{3}$. We use it to first extract the `relationship` r from the source domain as discussed in Section 3. In addition, we also generate candidate probabilities from the encoder during inference, by considering each candidate in parallel followed by a Softmax over the probability of r across all candidates. The candidate probabilities of the full context NSM model are calculated as a 1:1 ensemble between the probabilities from both the inference engine and the encoder.

535 **Baselines**   We compare the candidate selection accuracy of our analogy inference engine with
536 each model utilized by Hill et al. (2019). These baselines include a CNN-LSTM model, a standard
537 ResNet50 (with 9 input channels for 9 panels), a parallel ResNet50 (with 6 channels and each
538 candidate fed in parallel), and a Wide Relation Network. Each baseline is trained for 100 epochs using
539 the Adam optimizer with a learning rate of $1e^{-4}$, with contrasting, normal, and mixed candidates.

F   Supplementary Results

F.1   Visual Relationship Encoder

Figure 5: Relationship prediction test accuracy of our Visual Relationship Encoder. Results are first grouped (L-R) by test candidate regimes (contrasting, normal, and mixed candidates) and then sub-grouped (L-R) by training candidate regimes.

GENERALIZATION SPLIT	Training Accuracy %			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Extrapolation	86.23	86.44	86.75	84.78	84.84	85.86	84.75	84.92	86.06	84.76	84.88	85.96
Interpolation	86.34	86.54	86.56	84.71	84.86	85.57	84.67	85.01	85.81	84.69	84.93	85.69
Novel Domain Transfer	86.96	86.66	86.30	82.52	82.40	83.18	82.75	83.02	83.88	82.64	82.71	83.53
Novel Domain (shape color)	86.68	86.48	86.27	85.16	84.91	85.55	85.00	84.98	85.62	85.08	84.95	85.58
Novel Domain (line type)	86.16	86.23	86.30	84.93	85.07	85.46	84.58	84.70	85.46	84.75	84.88	85.46

Table 6: Relationship prediction accuracy of our visual relationship encoder

GENERALIZATION SPLIT	Training Accuracy %			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Extrapolation	98.27	99.87	99.32	66.89	61.77	59.61	58.23	57.97	52.12	62.56	59.87	55.87
Interpolation	98.44	99.94	99.33	95.17	82.69	95.45	70.82	95.67	94.62	82.69	89.35	95.02
Novel Domain Transfer	98.72	97.11	97.86	90.93	90.34	93.35	74.49	88.89	89.95	82.70	89.63	91.66
Novel Domain (shape color)	96.63	98.23	98.39	78.80	76.41	83.51	60.71	66.74	70.81	69.76	71.58	77.15
Novel Domain (line type)	96.26	96.43	96.78	79.84	72.29	79.98	61.58	65.27	65.25	70.71	68.79	72.61

Table 7: Engine layout prediction accuracy of our visual relationship encoder

F.2   Analogy Inference Engine

GENERALIZATION SPLIT	Training Accuracy %			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Extrapolation	97.31	99.58	99.08	65.24	62.33	58.40	57.14	58.08	50.98	61.19	60.20	54.69
Interpolation	97.47	99.78	98.90	93.46	82.15	94.55	69.81	95.11	94.29	81.33	88.80	94.29
Novel Domain Transfer	97.31	95.70	96.44	87.96	87.48	90.81	73.07	86.78	87.94	80.50	87.13	89.38
Novel Domain (shape color)	95.82	97.61	97.75	77.79	75.64	82.69	58.72	66.27	70.26	68.25	70.96	76.47
Novel Domain (line type)	94.90	95.40	95.38	78.14	70.64	78.53	60.23	64.31	64.10	69.18	67.48	71.32

Table 8: Candidate prediction accuracy of our two-step model

GENERALIZATION SPLIT	Training Accuracy %			Test Accuracy % (Contrasting)			Test Accuracy % (Normal)			Test Accuracy % (Mixed)		
	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed	Contrasting	Normal	Mixed
Extrapolation	96.96	99.41	98.52	73.56	66.75	63.47	59.94	59.84	52.92	66.65	63.29	58.19
Interpolation	97.18	99.68	98.73	93.11	85.40	94.95	70.88	94.86	93.89	81.71	90.25	94.41
Novel Domain Transfer	90.81	88.75	91.25	88.57	88.61	91.40	73.02	86.80	88.15	80.80	87.71	89.78
Novel Domain (shape color)	95.26	96.91	97.23	78.43	79.50	83.15	58.08	66.18	69.66	68.25	72.83	76.40
Novel Domain (line type)	94.15	94.58	94.84	79.75	76.18	80.57	59.55	62.43	65.74	69.65	69.30	73.15

Table 9: Candidate prediction accuracy of our full-context ensemble

G   Implementation Details

G.1   Visual Relationship Encoder

Index	Layer	Output Size
1	Panel Image Input	1 x 160 x 160
2	Conv(3 x 3, 1→ 8, stride 2)	8 x 79 x 79
3	BatchNorm	8 x 79 x 79
4	ReLU	8 x 79 x 79
5	Conv(3 x 3, 8→ 8, stride 2)	8 x 39 x 39
6	BatchNorm	8 x 39 x 39
7	ReLU	8 x 39 x 39
8	Conv(3 x 3, 8→ 8, stride 2)	8 x 19 x 19
10	BatchNorm	8 x 19 x 19
12	ReLU	8 x 19 x 19
13	Conv(3 x 3, 8→ 8, stride 2)	8 x 9 x 9
14	BatchNorm	8 x 9 x 9
15	ReLU	8 x 9 x 9
16	FC(8*9*9 → 128)	128
17	BatchNorm	128
15	ReLU	128

Table 10: Encoder CNN architecture

Index	Layer	Output Size
1	Encoder-CNN Output (3 panels)	3 x 128
2	LSTM (hidden dim = 128, sequence length = 3)	output = 3 x 128 final hidden state = 128 final cell state = 128

Table 11: Encoder LSTM architecture

Index	Layer	Output Size
1	Encoder-LSTM final hidden state	128
3	FC(128 → 128)	128
7	ReLU	128
4	$FC_{task}(128 \rightarrow 64)$	64
7	ReLU	64
5	$FC_{classifier_{task}}(64 \rightarrow |Task|)$	$|Task|$

Table 12: Encoder Multi-Task classifier architecture. $|Task|$ = 2, 5, 4 for object, attribute, and relationship classifiers respectively

G.2   Analogy Inference Engine

Index	Layer	Output Size
1	Panel Image Input	1 x 160 x 160
2	Conv(3 x 3, 1→ 8, stride 2)	8 x 79 x 79
3	BatchNorm	8 x 79 x 79
4	ReLU	8 x 79 x 79
5	Conv(3 x 3, 8→ 8, stride 2)	8 x 39 x 39
6	BatchNorm	8 x 39 x 39
7	ReLU	8 x 39 x 39
8	Conv(3 x 3, 8→ 8, stride 2)	8 x 19 x 19
10	BatchNorm	8 x 19 x 19
12	ReLU	8 x 19 x 19
13	Conv(3 x 3, 8→ 8, stride 2)	8 x 9 x 9
14	BatchNorm	8 x 9 x 9
15	ReLU	8 x 9 x 9

Table 13: Stem module architecture

Index	Layer	Output Size
1	Previous Module Output	8 x 9 x 9
2	Conv(3 x 3, 8→ 8)	8 x 9 x 9
3	ReLU	8 x 9 x 9
4	Conv(3 x 3, 8→ 8)	8 x 9 x 9
5	Residual: Add (1) and (4)	8 x 9 x 9
6	ReLU	8 x 9 x 9

Table 14: Unary module architecture

Index	Layer	Output Size
1	Previous Module Output	8 x 9 x 9
2	Previous Module Output	8 x 9 x 9
3	Concatenate (1) and (2)	16 x 9 x 9
4	Conv(1 x 1, 16→ 8)	8 x 9 x 9
5	ReLU	8 x 9 x 9
6	Conv(3 x 3, 8→ 8)	8 x 9 x 9
7	ReLU	8 x 9 x 9
8	Conv(3 x 3, 8→ 8)	8 x 9 x 9
9	Residual: Add (5) and (8)	8 x 9 x 9
10	ReLU	8 x 9 x 9

Table 15: Binary module architecture

Index	Layer	Output Size
1	Previous Module Output	8 x 9 x 9
2	Previous Module Output	8 x 9 x 9
3	Concatenate (1) and (2)	16 x 9 x 9
4	Conv(1 x 1, 16 → 8)	8 x 9 x 9
5	ReLU	8 x 9 x 9
6	FC(8*9*9 → 256)	256
7	ReLU	256
8	FC(256 → $|r|$)	$|r|$
9	Softmax($|c|$ x $|r|$ → $|c|$) (over subset of (8) along index r_{pred} for all $|c|$ candidates)	$|c|$

Table 16: Classifier module architecture. $|r|$ = 4. $|c|$ = 4.