# ElasticMVS: Learning elastic part representation for self-supervised multi-view stereopsis

## Abstract

Self-supervised multi-view stereopsis (MVS) attracts increasing attention for learning dense surface predictions from only a set of images without onerous ground-truth 3D training data for supervision. However, existing methods highly rely on the local photometric consistency, which fail to identify accurately dense correspondence in broad textureless or reflectant areas. In this paper, we show that geometric correlations such as surface connectedness and occlusion boundaries parsed from images could serve as a reliable guidance for pixel-wise multi-view correspondences. With this insight, we present a novel elastic part representation, which encodes physically-connected part segmentations with elastically-varying scales, shapes and boundaries. Meanwhile, a self-supervised MVS framework namely ElasticMVS is proposed to learn the representation and estimate per-view depth following a part-aware propagation and evaluation scheme. Specifically, the pixel-wise part representation is trained by a contrastive learning-based strategy, which increases the representation compactness in geometrically concentrated areas and contrasts otherwise. ElasticMVS iteratively optimizes a part-level consistency loss and a surface smoothness loss, based on a set of depth hypotheses propagated from the geometrically concentrated parts. Extensive evaluations convey the superiority of ElasticMVS in the reconstruction completeness and accuracy, as well as the efficiency and scalability. Particularly, for the challenging large-scale reconstruction benchmark, ElasticMVS demonstrates significant performance gain over both the supervised and self-supervised approaches.

## 1 Introduction

Given a set of images with known camera parameters, multi-view stereopsis (MVS) aims to reconstruct the dense and accurate geometry of the scene. Existing learning-based approaches (Yao et al., 2018), typically being cast as an end-to-end depth regression task, outperform the traditional geometry-based ones (Schönberger et al., 2016). However, their generalization ability in open environments is severely hindered by the availability of the onerous laser-scanned 3D training data. Self-supervised MVS (Khot et al., 2019; Dai et al., 2019) lifts such limitation by leveraging the multi-view photometric consistency in place of the supervisory signals. Unfortunately, the pixel-level photometric regularization is susceptible to textureless patterns and illumination variations, leading to incomplete and inaccurate reconstructions, especially in outdoor environments.

In this paper, we tackle the above challenges with a novel image parsing paradigm. Instead of treating images as projections of 3D scenes, we show that the inherent geometric correlations, such as surface connectedness, smoothness and boundaries, could be inferred from images and serve as a reliable guidance for pixel-wise multi-view correspondence estimation. The mainstream solutions of feature-based regularizations introduce either hand-crafted structures such as lines and

Figure 1: An overview of ElasticMVS, a self-supervised MVS framework to learn the representation and estimate per-view depth. The elastic part representation of each image is trained by a contrastive learning-based strategy, which increases the representation compactness in geometrically concentrated areas and contrasts otherwise. Benefiting from the elastic part representation, the inherent geometric correlations are effectively exploited by a patchmatch-based strategy.

planes from superpixels (Romanoni and Matteucci, 2019; Bódis-Szomorú et al., 2014; Micusík and Kosecka, 2010), or semantic features pre-trained from limited geometric-unrelated labels (Xu et al., 2021; Hung et al., 2019). Different from those, we aim to build the correlation between the latent space of the representation and the scene space of the surface in a self-supervised way. With this insight, we present a novel elastic part representation which encodes physically-connected part segmentations with elastically-varying scales, shapes and boundaries. Unlike the traditional segmentation networks with a fixed number of labels, our pixel-wise part representation directly reflects the surface correlation, i.e., the more similar the two representations are, the higher probability they belong to the same physical surface part. Meanwhile, a self-supervised MVS framework namely ElasticMVS is proposed to learn the representation and estimate per-view depth iteratively following a part-aware propagation and evaluation scheme.

Benefiting from the elastic part representation, the inherent geometric correlations are effectively exploited by a patchmatch-based propagation strategy (Galliani et al., 2015). Specifically, in each iteration, depth is estimated by selecting the best depth hypotheses propagated only from the geo-metrically concentrated part. Besides, the pixel-level photometric consistency loss is enhanced by the constraints of feature-level correspondence and surface smoothness, which provide part-aware matching cues to guide a more robust depth prediction in textureless and reflectant areas. To train the elastic part representation, a contrastive learning-based strategy is implemented by increasing the representation compactness in geometrically concentrated areas and contrasts otherwise. Without the ground-truth 3D information, these geometrically concentrated areas are identified by the depth map generated from the initialized ElasticMVS without the part representation, which owns the same workflow as the traditional geometry-based stereopsis (Schönberger et al., 2016). A noise-robust training loss is implemented to get rid of undesirable identifications.

Experiments on 'DTU' and 'Tanks and Temples (T&T)' datasets demonstrate that the proposed ElasticMVS significantly outperforms all state-of-the-art self-supervised learning-based methods. Remarkably, in the challenging large-scale reconstruction benchmark (T&T advanced), ElasticMVS shows dramatic performance improvements w.r.t. both the supervised and self-supervised approaches. Besides, the systematic evaluations indicate that our elastic part representation is superior in modeling elastically-varied parts, while being robust and lightweight in training and inference.

## 2 Related work

### 2.1 Multi-view Stereopsis (MVS)

The major works in multi-view stereopsis focus on the view-wise depth map estimation (Tola et al., 2012; Furukawa and Ponce, 2010) and then fuse together to form the point cloud(Zach, 2008; Goesele

et al., 2007). Among these methods, patchmatch-based depth optimization methods(Galliani et al., 2015; Schönberger et al., 2016; Xu and Tao, 2019), initialized from the randomly sampled depth hypotheses, show great run-time and memory efficiency in depth map estimation. Some learning-based methods (Wang et al., 2021a; Lee et al., 2021) introduce an iterative coarse-to-fine optimization in an end-to-end trainable architecture to improve each of the core steps in patchmatch. However, these algorithms suffer from incomplete and noisy depth predictions in textureless and reflectant areas.

Currently, learning methods based on 3D cost volume regularization demonstrate state-of-the-art results in several benchmarks. These methods optimizes the 3D geometry by 3D CNN, unprojecting from 2D images or features into the 3D volume (Ji et al., 2017, 2020; Kendall et al., 2017; Yao et al., 2018; Kar et al., 2017; Yao et al., 2019; Yi et al., 2019; Chen et al., 2019; Gu et al., 2019; Cheng et al., 2020). However, these supervised methods crucially rely on ground-truth 3D data, which are hard to generalize in wild open environments. To realize self-supervised MVS without the onerous ground-truth 3D training data, (Dai et al., 2019; Huang et al., 2021; Khot et al., 2019; Zhang et al., 2021; Xu et al., 2021; Liu et al., 2019; Niemeyer et al., 2020) replace the supervision signal with the unsupervised rendering loss or cross-view feature consistency loss. However, reprojection under multiple views is highly sensitive to environmental illumination, which is hard to generalize in highly variable scenarios.

## 2.2  Part Representation

Recently, learning representations from the image in a self-supervised training strategy has gained growing popularity in 2D vision tasks, which use contrastive learning (Wu et al., 2018; Chen et al., 2020b,a; Caron et al., 2020) to deal with the lack of ground-truth labels. They use InfoNCE (Van den Oord et al., 2018) to generate a unique embedding for each picture in a batch. Wang et al. (2021b) further leverages a dense projection head to generalize such embedding from image-level to patch-level, which is more suitable for performing dense prediction tasks sucn as semantic segmentations. Hung et al. (2019); Wang et al. (2020) assigns the equivariance constraint and the semantic consistency regularization on the learned part response representation (Zhou et al., 2016) to predict part segmentations that are consistent across different instances or camera poses. Xu et al. (2021) incorporates learned semantic features into multi-view stereopsis pipeline to boost the reconstruction ability. However, previous works only concentrate on generating semantic features and using it forward to perform down-stream tasks. Instead, we utilize the rough depth map as supervision to the semantic learning process, which forms a natural integration of photometric and geometric information to provide elastic part representations.

## 3  Method

We estimate the depth maps of a given reference image $x$ and the corresponding $M$ unstructured source images with known camera calibrations. The final point cloud reconstruction is obtained by fusing all of them. The key ingredient of our framework is a novel *elastic part representation*, which encodes sufficient geometric details to predict a piecewise-smooth depth map. We first formally define our part-aware representation in Sec. 3.1. Based upon the learned representation, we introduce two improvements on depth hypotheses propagation and evaluation for part-aware patchmatch in Sec. 3.2. We present the self-supervised training scheme in Sec. 3.3 and implementation details in Sec. 3.4.

## 3.1  Elastic Part Representation

Suppose that $(\tilde{d}, \tilde{n}) \in \mathbb{R}^{H \times W \times 4}$ are the underlying depth and normal map of the image $x$, we first define the geometry-aware part segmentation $S_p$ related to each pixel location $p \in \mathbb{R}^2$, which is geometrically concentrated inside: $S_p \triangleq \{q \in \mathbb{R}^2 | \Gamma\{(\tilde{d}_p, \tilde{n}_p); (\tilde{d}_q, \tilde{n}_q)\} \leq \epsilon\}$, where $\Gamma\{(\tilde{d}_p, \tilde{n}_p); (\tilde{d}_q, \tilde{n}_q)\} \triangleq |([q, \tilde{d}_q] - [p, \tilde{d}_p]) \cdot \tilde{n}_p|$ is the 3D point-to-plane distance (Tateno et al., 2015) between two pixels.

Equipped with the part segmentation $S_p$ for each pixel $p$, we propose to learn a per-pixel elastic part representation $z_p \in \mathbb{R}^D$ for each $p \in \mathbb{R}^2$, such that $z_p$ is compact in the geometric concentrated part $S_p$ and contrast otherwise. Specifically, we use the Soft-Nearest Neighbor Loss (Salakhutdinov and

Figure 2: Detailed architecture of part-aware patchmatch. Given the pixel-wise elastic part representation from the ConvNet, depth hypotheses are sampled from high confidence regions which own similar features. The optimal depth values in each iteration are chosen based on the combination of a part-aware correspondence and a part smoothness cost.

Hinton, 2007) to formulate such:

$$L_p = -\sum_p \log \frac{\sum_{p^+ \in S_p} \exp\left(\langle z_p, z_{p^+}\rangle/\tau\right)}{\sum_{q \neq p} \exp\left(\langle z_p, z_q\rangle/\tau\right)}, \tag{1}$$

where $z_{p^*} \in z$ is a feature on pixel local $p^*$, $\langle \cdot, \cdot \rangle$ is the dot product, and $\tau$ is the temperature.

Finally, we use a ConvNet, $F_\Theta(\cdot)$, to model the generation of the elastic part representation, i.e., for the reference image $x \in \mathbb{R}^{H \times W \times 3}$, $F_\Theta(x) \in \mathbb{R}^{H \times W \times D}$ denotes the collection of per-pixel elastic part representations.

## 3.2 Part-aware Matching

We build our part-aware matching module on top of the seminal work of patchmatch (Galliani et al., 2015). In particular, we incorporate our elastic part representation and propose the following two novel improvements: 1. Propagation: we propagate hypotheses to neighbors with our learned elastic part representation; 2. Evaluation: we evaluate and choose the best hypotheses based on photometric consistency, feature-level correspondence, and geometrically smoothness. The resulting module is differentiable, and the architecture of part-aware patchmatch is illustrated in Fig. 2.

**Propagation.** The key idea of the part-aware propagation is to gather hypotheses from the nearby pixels of the same physical surface part. As illustrated in Fig. 3, instead of propagating hypotheses naively from a static set of neighbors (Galliani et al., 2015), our depth hypotheses are sampled from the nearby pixels which own similar features of the learned elastic part representation.

Since the depth value is unreliable in textureless and highly reflectant areas, a confidence map $c \in [0, 1]^{H \times W}$ is generated to pick the reliable candidates from noise, which is a combination of the photometric consistency and the geometric consistency (Schönberger et al., 2016). Please refer to the supplementary material for a more detailed explanation. For each pixel $p$ in the depth map to be updated, $K_p$ patch hypotheses are propagated from the propagation candidates $\mathcal{T}_p$, which is a set of nearby pixels $q$ whose feature $z_q$ is close to the feature $z_p$ with high confidence $c_q$:

$$\mathcal{T}_p = \left\{ q \in R^2 \middle| \|z_p - z_q\| \leq \eta, c_q \geq \xi \right\}. \tag{2}$$

According to the property of elastic part representation in Eq. 1, the generated depth hypotheses from $\mathcal{T}_p$ would stay close to the underlying surface.

**Evaluation.** Beyond the photometric consistency loss, we propose two novel losses for hypothesis evaluation – Part-aware correspondence loss and Part smoothness loss.

*Part-aware correspondence loss* evaluates the feature similarity of the elastic part representation between the reference view and the warped source views. Given in homogeneous coordinates and depth hypothesis $d$, we obtain the warped source feature $z_{p_i(d)}^{[i]}$ of the $i$-th source view via differentiable

(a) Standard propagation       (b) Part-aware propagation

Figure 3: Visualization of all sampled locations for propagation (blue points) during 3 iterations of patchmatch given six pixels (red points).

bilinear interpolation. Therefore, given the features $z_p^{[0]}, z_{p_i(d)}^{[i]}$ of the elastic part representation in the reference and source view respectively, the part-aware correspondence at depth $d_p$ and normal direction $n_p$ is given by:

$$M_s(d_p, n_p | x, z) = \left[ \sum_i \langle z_p^{[0]}, z_{p_i(d)}^{[i]} \rangle + \alpha_s \cdot \rho(d_p, n_p | x, x^{[i]}) \right], \qquad (3)$$

where $\rho(\cdot)$ is the NCC value (Galliani et al., 2015) implemented in the traditional patchmatch algorithm.

*Part smoothness loss* aims to augment the local patchmatch evaluation with a non-local piecewise smoothness term corresponding to the same physical surface part. Inspired by the work of Locally Optimal Projection (LOP) (Lipman et al., 2007) for surface reconstruction from point clouds, the part smoothness loss is formulated using an L1 median loss, which is robust to the outliers and gives a piecewise second-order surface approximation in each surface part (Lipman et al., 2007).

More specifically, the depth map $d \in \mathbb{R}^{H \times W \times 1}$ is firstly transferred to the point set $e \in \mathbb{R}^{H \times W \times 3}$ in the scene space given the camera matrix $\mathbf{M}$: $e = \{e_{p^*} \in \mathbb{R}^3 | [e_{p^*}^\top, 1]^\top = \mathbf{M}^{-1}[p^{*\top}, d_{p^*}, 1]^\top \}$. Then we define our part smoothness loss as the sum of the Euclidean distance to the points from propagation candidates in $\mathcal{T}_p$ (Eq. 2):

$$M_g(d_p, n_p \mid z) = \sum_{q \in T_p} \omega_q \, \|e_p - e_q\|, \qquad (4)$$

where $\omega_q = \exp\{-c_p - \alpha_n \langle n_p, n_q \rangle\}$ is a weight correlated with the confidence $c_q$ and the normal similarity.

Putting all the components together, as illustrated in Fig. 2, the depth map initialization consists of $K_p$ random values within the depth range of interest. For subsequent iterations, $K_p$ hypotheses are propagated based on the depth values of the former one. To deliver a more diverse set of hypotheses than just using propagation, another $K_r$ hypotheses are sampled by adding a small random perturbation to the previous estimation. In each iteration, the optimal depth and normal are chosen as: $(d_p^{\text{opt}}, n_p^{\text{opt}}) = \underset{d_p^*, n_p^*}{\arg\min} \{M_s(d_p^*, n_p^* | x, z) + \alpha_g \cdot M_g(d_p^*, n_p^* \mid z)\}$. Empirically, 5 iterations are sufficient to obtain an accurate piecewise smoothness depth map.

### 3.3 Network Training

The elastic part representation $z$, as described in Sec. 3.1, is compact in the area of a smooth surface part. We now describe how to train the ConvNet $F_\Theta(x)$ using the self-supervised contrastive learning strategy without knowing the ground-truth depth and normal information.

The core of contrastive learning is to construct a set of positive and negative samples, in which the representation in the positive samples stay close to each other while the negative ones are far apart. Before training, a depth map $d$ and a normal map $n$ of each reference image $x$ are generated by the initialized ElasticMVS without the part representation, which is similar to the traditional patchmatch-based algorithm, e.g., Gipuma (Galliani et al., 2015).

For each pixel $p$ with high confidence ($c_p \geq \xi$), we construct a set of pixel candidates $\hat{\mathcal{S}}_p$ for positive samples, in which each of them is geometrically concentrated to $p$ with high confidence:

$$\hat{\mathcal{S}}_p = \{q \in \mathbb{R}^2 | \Gamma\{(d_p, n_p); (d_q, n_q)\} \leq \epsilon, c_q \geq \xi\}. \tag{5}$$

Therefore, the dense contrastive loss for self-supervised training is defined as:

$$L_c = -\sum_p \mathbf{1}_{[c_p \geq \xi]} \log \frac{\sum_{p^+ \in \hat{\mathcal{S}}_p} \exp\left(\langle z_p, z_{p^+}\rangle/\tau\right)}{\sum_{q \neq p} \exp\left(\langle z_p, z_q\rangle/\tau\right)}. \tag{6}$$

This loss function encourages representation compactness in parts with close surface distance and separation otherwise, i.e., the distance in the representation space naturally reflects the distance in the 3D scene space. Due to the memory limitation, it is impossible to densely sample all positive and negative samples from the whole image in Eq. 6. Therefore, we randomly select $N_c$ points from all samples in $\hat{S}_p$, using a probability distribution inversely proportional to the distance away from $p$.

To obtain spatially concentrated representation, we utilize a spatial concentration loss that encourages all the pixel embeddings to become isotropically isolated:

$$L_s = \sum_p \left\| \sum_{q \in \hat{\mathcal{S}}_p} \exp\left(\beta \cdot \langle z_p, z_q\rangle\right) \cdot q - p \right\|. \tag{7}$$

which prompts the weighted average of the sampled neighboring points $q$ to be close to the point $p$. Therefore, the pixel locations far away from the sampled point will be given low weights, leading to a spatially concentrated representation.

### 3.4 Implementation Details

The elastic part representation is trained with a Feature Pyramid Network , which shares the same structure as in PatchmatchNet (Wang et al., 2021a). To train the network, we use the SGD (Bottou, 2010) with an initial learning rate of $1.0 \times 10^{-4}$. The threshold $\epsilon$ for defining $S_p$ is set to $0.5$ in the DTU dataset and $0.01$ in the T&T dataset. We fix the temperature number $\tau = 0.5$ and the confidence threshold $\xi = 0.7$ during training and propagation. We sample $N_c = 8$ points for each pixel. During the propagation, we select $K_p = 8$ hypotheses for propagation and $K_r = 4$ for perturbation. We choose $\eta = 0.1$ in Eq. 2 to find nearby pixels. During the reconstruction stage, we set respectively $\alpha_s = 0.1$ and $\alpha_g = 0.5$ in Eq. 3 and 4. All the training and reconstruction are conducted on a single NVIDIA GTX 3090 graphics card.

## 4 Experiment

### 4.1 Benchmarks

**DTU dataset (Aanæs et al., 2016)** is an MVS dataset consisting of different indoor objects scanned at 49 camera positions under 7 different lighting conditions. We use the original image size ($1600 \times 1200$) as input and follow the same evaluation protocol as (Aanæs et al., 2016) to compute the accuracy and the completeness of the final reconstructions. The overall distance metric is defined as the mean of the two metrics.

Quantitative results with three types of reconstruction methods are shown in Table 1, including geometry-based, supervised and self-supervised MVS methods. Our method outperforms all the self-supervised

Table 1: Evaluation of reconstruction quality by measuring the distance metric (lower is better) on the DTU dataset (Aanæs et al., 2016).

| Method | Acc.(mm) | Comp.(mm) | Overall(mm) |
|---|---|---|---|
| Furu (Furukawa and Ponce, 2010) | 0.613 | 0.941 | 0.777 |
| Tola (Tola et al., 2012) | 0.342 | 1.190 | 0.766 |
| Gipuma (Galliani et al., 2015) | **0.283** | 0.873 | 0.578 |
| COLMAP (Schönberger et al., 2016) | 0.400 | **0.664** | **0.532** |
| MVSNet (Yao et al., 2018) | 0.396 | 0.527 | 0.462 |
| SurfaceNet+ (Ji et al., 2020) | 0.385 | 0.448 | 0.416 |
| Point-MVSNet (Chen et al., 2019) | 0.342 | 0.441 | 0.376 |
| CasMVSNet (Gu et al., 2019) | **0.325** | 0.385 | 0.355 |
| UCS-Net (Cheng et al., 2020) | 0.338 | 0.349 | **0.344** |
| PVA-MVSNet (Yi et al., 2019) | 0.379 | 0.336 | 0.357 |
| D$^2$HC-RMVSNet (Yan et al., 2020) | 0.395 | 0.378 | 0.386 |
| PatchmatchNet (Wang et al., 2021a) | 0.427 | **0.277** | 0.352 |
| Consistency (Khot et al., 2019) | 0.881 | 1.073 | 0.977 |
| SurRF (Zhang et al., 2021) | 0.388 | 0.390 | 0.389 |
| MVS$^2$ (Dai et al., 2019) | 0.760 | 0.515 | 0.637 |
| M$^3$VSNet (Huang et al., 2021) | 0.636 | 0.531 | 0.583 |
| JDACS (Xu et al., 2021) | 0.398 | **0.318** | 0.358 |
| **ElasticMVS (ours)** | **0.374** | 0.325 | **0.349** |

Figure 4: Point cloud visualization in the T&T intermediate and advanced benchmarks, compared with three types of reconstruction methods: supervised methods (a)(b) (Wang et al., 2021a; Gu et al., 2019), self-supervised methods (d)(e) (Huang et al., 2021; Xu et al., 2021), and one traditional geometry-based method (c) (Schönberger et al., 2016).

methods including SurRF (Zhang et al., 2021) and JDACS (Xu et al., 2021) in *accuracy* and *overall* distance metrics, and achieves the second-best performance in *completeness*. It is remarkable that ElasticMVS is competitive compared to state-of-the-art supervised methods, e.g., our overall distance metric is the second best among *all* methods.

**Tanks and Temples** (Knapitsch et al., 2017) dataset contains two benchmarks (*intermediate* and *advanced*) on outdoor real-world scenes with complex geometry. We use the original image size (1920 × 1080) as the input. We evaluate the results with F-score (Knapitsch et al., 2017), the higher value of which indicates the better reconstruction. We summarize the quantitative results in Table 2. On the *intermediate* benchmark, ElasticMVS achieves state-of-the-art performance among all supervised and self-supervised MVS methods. Especially, our method outperforms all the self-supervised MVS methods by a significant margin. On the more challenging *T&T advanced* benchmark, which contains large-scale real-world scenes with more than 300 camera views for each scene, ElasticMVS even compares favourably with the supervised methods. The tremendous performance improvement in this benchmark demonstrates the effectiveness and robustness of the proposed ElasticMVS w.r.t complex categories and geometries.

Table 2: Quantitative evaluation (F-score, higher is better) of state-of-the-art learning-based methods on two benchmarks of the Tanks and Temples (T&T) dataset (Knapitsch et al., 2017).

| Method | Intermediate | Advanced |
|---|---|---|
| MVSNet (Yao et al., 2018) | 43.48 | - |
| CasMVSNet (Gu et al., 2019) | **56.84** | 31.12 |
| UCSNet (Cheng et al., 2020) | 54.83 | - |
| PVAMVSNet (Yi et al., 2019) | 54.46 | - |
| SurfaceNet+ (Ji et al., 2020) | 49.38 | - |
| R-MVSNet (Yao et al., 2019) | 50.55 | 29.55 |
| Point-MVSNet (Chen et al., 2019) | 48.27 | - |
| PatchmatchNet (Wang et al., 2021a) | 53.15 | **32.31** |
| Patchmatch-RL (Lee et al., 2021) | 51.81 | 31.78 |
| MVS$^2$ (Dai et al., 2019) | 37.21 | - |
| M$^3$VSNet (Huang et al., 2021) | 37.67 | - |
| SurRF (Zhang et al., 2021) | 54.36 | - |
| JDACS (Xu et al., 2021) | 45.48 | - |
| **ElasticMVS (ours)** | **57.88** | **37.81** |

We also compare our reconstructions with various baselines qualitatively in Fig. 4. ElasticMVS produces much more complete predictions compared with COLMAP (Schönberger et al., 2016), while generating much less noise than existing self-supervised methods (M3VSNet (Huang et al., 2021) and JDACS (Xu et al., 2021)). Besides, we achieve even surpassing performances upon

| (a) w/o PR | (b) w/o PC | (c) w/o PS | (d) Ours | (e) Ground Truth |

Figure 5: Reconstruction results of ablation study on part-aware patchmatch, without part representation (w/o PR), part-aware correspondence (w/o PC) and part smoothness (w/o PS) relatively.

state-of-the-art supervised methods (CasMVSNet (Gu et al., 2019) and PatchmatchNet (Wang et al., 2021a)).

## 4.2 Ablation Study

In this section, we provide detailed ablation study and analysis of the key components of ElasticMVS, including the part-aware patchmatch and the elastic part representation.

**Part-aware patchmatch.** To investigate the effects of the key components in the part-aware patchmatch during inference, we conduct a comparison with respect to the part-aware propagation and evaluation described in Sec. 3.2. Our part-aware patchmatch is compared with three variants: 1. Propagation without elastic Part Representation (w/o PR), which employs fixed sampled locations for propagation similar to Gipuma (Galliani et al., 2015); 2. Evaluation without Part-aware Correspondence (w/o PC), which only employs the photometric consistency in Eq. 3; 3. Evaluation without Part Smoothness loss (w/o PS) in Eq. 4, which simply employs an L1-median loss from all neighborhoods, similar to the LOP (Lipman et al., 2007) for point cloud de-noising.

Table 3: Ablation study of part-aware patchmatch, without the help of part representation (w/o PR), part-aware Correspondenc (w/o PC) and part smoothness (w/o PS)

| Methods | DTU | T&T |
|---------|-----|-----|
| w/o PR | 0.455 | 40.05 |
| w/o PC | 0.430 | 43.82 |
| w/o PS | 0.411 | 39.58 |
| Ours | **0.349** | **57.88** |

As shown in Table 3, our part-aware propagation and evaluation modules both play important roles in boosting the overall performance across different datasets. Qualitative results are shown in Fig. 5. Implementations without the elastic part representation (a) and the part-aware correspondence (b) fail to recover the dense surface in textureless regions. Although applying a naive surface de-noising and completion method (c) helps to fill in some of the holes in textureless areas, it still suffers from low accuracy and noisy predictions due to the lack of part awareness. Overall, the strong geometric coherence revealed by the learned elastic sampling strategy helps ElasticMVS gather more accurate and complete depth maps in both small complex surfaces and large flattened areas.

**Training loss of elastic part representation.** Now we study how different training losses described in Sec. 3.3 affect the performance of the representation and further the depth map predictions. Our elastic part representation is compared with two variants, which are trained without confidence map (w/o Con.) in Eq. 6 and without spatial concentration loss (w/o Spa.) in Eq. 7.

Table 4: Ablation study of the representation concerning the training loss without the help of confidence map (w/o Con.) and spatial concentration (w/o Spa.).

| Methods | Contrastive loss | Depth error(mm) |
|---------|-----------------|-----------------|
| w/o Con. | 2.52 | 3.55 |
| w/o Spa. | 2.34 | 3.01 |
| Ours | **2.28** | **2.52** |

We test on the DTU dataset. We first measure the compactness of the learned part representation as described in Eq. 1 using the ground truth depth map. We also compare the predicted depth map error using these representations, which is evaluated by the L1 distance from the predicted depth map to the ground-truth. As shown in Table 4, our elastic part representation is the most compact one (with lowest contrastive loss).

Visualizations of the representation are demonstrated in Fig. 6, shown by a heat map of the representation distance $\|z_q - z_p\|$ from a pixel location $p$ to all other pixels $q$ in the whole image.

As expected, our elastic part representation successfully recognizes the part on the same physical surface, resulting in proper surface boundary identifications with elastically-varying scales and shapes. Contrastingly, the representation trained without the confidence map (w/o Con.) fails to identify a complete surface part due to the noisy training samples. Meanwhile, the representations trained without spatial concentration loss (w/o Spa.) suffer from outliers far from the surface part, demonstrating the effectiveness of spatial regularization.

(a) w/o Con.  (b) w/o Spa.  (c) Ours

Figure 6: Visualization of the elastic part representation for two pixels (black). Con. denotes confidence map, and Spa. denotes spatial concentration loss.

### 4.3 Discussion

**Memory.** In Table 5, we compare the GPU memory consumption and the run-time during inference with two memory-efficient learning-based methods. We choose scan 9 and a fixed reference view downsampled to the scale of $640 \times 800$ in the DTU dataset in this study. As shown in Table 5, ElasticMVS is more memory-efficient compared with two learning-based MVS backbones. Notice that the memory and running time are adaptively changed with the hypothesis number and the iteration number, since propagation with more hypotheses will converge with fewer iterations, but take a larger memory consumption. Overall, the experiment demonstrates the superiority memory efficiency of ElasticMVS.

**Limitation and Future work.** It takes a long time in ElasticMVS to calculate the patch similarity for each pixel, since the total computational complexity to evaluate the photo consistency from $M$ source images of size $H \times W$ with $K$ hypotheses is $O(M \times H \times W \times K \times l^2)$, where $l$ is the patch size. Empirically, $l = 11$, which is impossible to give a forward and backward pass from a single graphics card at

Table 5: Memory and running time comparison with two learning-based MVS backbones.

| Methods | No. of stages | GPU Mem. (MB) | Run-time (s) |
|---|---|---|---|
| CasMVSNet (Gu et al., 2019) | 3 | 3489 | 0.12 |
| PatchmatchNet (Wang et al., 2021a) | 5 | 4439 | **0.08** |
| ElasticMVS (8 hypotheses) | 5 | **2679** | 0.48 |
| ElasticMVS (16 hypotheses) | 3 | 5785 | 0.37 |

once. As shown in Table 5, the running time of ElasticMVS is not competitive compared with the cost-volume-based methods. One solution is to replace the $l \times l$ patch with the learned feature in Patchmatch. However, the accuracy of the learned photometric consistency in self-supervised stereopsis is still far from the traditional one. In future work, we plan to design a lightweight network architecture to represent not only the part correlation but also the pixel-wise wrapped image patches, jointly learned from a self-supervised learning-based strategy, which can meet the demand for more challenging tasks such as real-time MVS and dynamic MVS.

## 5 Conclusion

In this paper, we present a novel elastic part representation that encodes physically connected part segmentations with elastically-varying scales, shapes and boundaries. We build the correlation between the embedding space and the scene space to represent the surface connectedness and boundaries behind the image. A self-supervised MVS framework, ElasticMVS, is proposed to learn the representation and estimate per-view depth following a part-aware patchmatch-based algorithm. Benefiting from the inherent geometric correlations learned from the huge amount of images, ElasticMVS delivers state-of-the-art performance in both reconstruction completeness and accuracy, and extraordinary generalization ability in the challenging large-scale scenes.

# References

Henrik Aanæs, Rasmus Ramsbøl Jensen, George Vogiatzis, Engin Tola, and Anders Bjorholm Dahl. 2016. Large-Scale Data for Multiple-View Stereopsis. *International Journal of Computer Vision* (2016), 1–16.

András Bódis-Szomorú, Hayko Riemenschneider, and Luc Van Gool. 2014. Fast, Approximate Piecewise-Planar Modeling Based on Sparse Structure-from-Motion and Superpixels. *2014 IEEE Conference on Computer Vision and Pattern Recognition* (2014), 469–476.

Léon Bottou. 2010. Large-Scale Machine Learning with Stochastic Gradient Descent. In *COMPSTAT*.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. 2020. Unsupervised learning of visual features by contrasting cluster assignments. *Advances in Neural Information Processing Systems* 33 (2020), 9912–9924.

Rui Chen, Songfang Han, Jing Xu, and Hao Su. 2019. Point-Based Multi-View Stereo Network. In *IEEE Conference on Computer Vision and Pattern Recognition*.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. 2020b. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*. PMLR, 1597–1607.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. 2020a. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297* (2020).

Shuo Cheng, Zexiang Xu, Shilin Zhu, Zhuwen Li, Li Erran Li, Ravi Ramamoorthi, and Hao Su. 2020. Deep stereo using adaptive thin volume representation with uncertainty awareness. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 2524–2534.

Yuchao Dai, Zhidong Zhu, Zhibo Rao, and Bo Li. 2019. Mvs2: Deep unsupervised multi-view stereo with multi-view symmetry. In *2019 International Conference on 3D Vision (3DV)*. IEEE, 1–8.

Yasutaka Furukawa and Jean Ponce. 2010. Accurate, dense, and robust multiview stereopsis. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 32, 8 (2010), 1362–1376.

Silvano Galliani, Katrin Lasinger, and Konrad Schindler. 2015. Massively parallel multiview stereopsis by surface normal diffusion. In *IEEE International Conference on Computer Vision*. 873–881.

Michael Goesele, Noah Snavely, Brian Curless, Hugues Hoppe, and Steven Seitz. 2007. Multi-View Stereo for Community Photo Collections. 1–8. https://doi.org/10.1109/ICCV.2007.4408933

Xiaodong Gu, Zhiwen Fan, Siyu Zhu, Zuozhuo Dai, Feitong Tan, and Ping Tan. 2019. Cascade Cost Volume for High-Resolution Multi-View Stereo and Stereo Matching. *arXiv preprint arXiv:1912.06378* (2019).

Baichuan Huang, Can Huang, Yijia He, Jingbin Liu, and Xiao Liu. 2021. M3VSNet: Unsupervised Multi-metric Multi-view Stereo Network. *ArXiv* abs/2005.00363 (2021).

Wei-Chih Hung, Varun Jampani, Sifei Liu, Pavlo Molchanov, Ming-Hsuan Yang, and Jan Kautz. 2019. Scops: Self-supervised co-part segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 869–878.

Mengqi Ji, Juergen Gall, Haitian Zheng, Yebin Liu, and Lu Fang. 2017. SurfaceNet: An End-to-End 3D Neural Network for Multiview Stereopsis. *2017 IEEE International Conference on Computer Vision (ICCV)* (2017), 2326–2334.

Mengqi Ji, Jinzhi Zhang, Qionghai Dai, and Lu Fang. 2020. SurfaceNet+: An End-to-end 3D Neural Network for Very Sparse Multi-view Stereopsis. *IEEE Transactions on Pattern Analysis and Machine Intelligence* (2020).

Abhishek Kar, Christian Häne, and Jitendra Malik. 2017. Learning a Multi-View Stereo Machine.

Alex Kendall, Hayk Martirosyan, Saumitro Dasgupta, Peter Henry, Ryan Kennedy, Abraham Bachrach, and Adam Bry. 2017. End-to-End Learning of Geometry and Context for Deep Stereo Regression. *CoRR* abs/1703.04309 (2017).

Tejas Khot, Shubham Agrawal, Shubham Tulsiani, Christoph Mertz, Simon Lucey, and Martial Hebert. 2019. Learning unsupervised multi-view stereopsis via robust photometric consistency. *arXiv preprint arXiv:1905.02706* (2019).

Arno Knapitsch, Jaesik Park, Qian-Yi Zhou, and Vladlen Koltun. 2017. Tanks and temples: Benchmarking large-scale scene reconstruction. *ACM Transactions on Graphics (ToG)* 36, 4 (2017), 1–13.

Jae Yong Lee, Joseph DeGol, Chuhang Zou, and Derek Hoiem. 2021. PatchMatch-RL: Deep MVS with Pixelwise Depth, Normal, and Visibility. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)* (2021), 6138–6147.

Yaron Lipman, Daniel Cohen-Or, David Levin, and Hillel Tal-Ezer. 2007. Parameterization-free projection for geometry reconstruction. In *SIGGRAPH 2007*.

Shichen Liu, Shunsuke Saito, Weikai Chen, and Hao Li. 2019. Learning to infer implicit surfaces without 3d supervision. In *Advances in Neural Information Processing Systems*. 8295–8306.

Branislav Micusík and Jana Kosecka. 2010. Multi-view Superpixel Stereo in Urban Environments. *International Journal of Computer Vision* 89 (2010), 106–119.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. 2020. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 3504–3515.

Andrea Romanoni and Matteo Matteucci. 2019. TAPA-MVS: Textureless-Aware PAtchMatch Multi-View Stereo. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)* (2019), 10412–10421.

Ruslan Salakhutdinov and Geoff Hinton. 2007. Learning a nonlinear embedding by preserving class neighbourhood structure. In *Artificial Intelligence and Statistics*. PMLR, 412–419.

Johannes L Schönberger, Enliang Zheng, Jan-Michael Frahm, and Marc Pollefeys. 2016. Pixelwise view selection for unstructured multi-view stereo. In *European Conference on Computer Vision*. Springer, 501–518.

Keisuke Tateno, Federico Tombari, and Nassir Navab. 2015. Real-time and scalable incremental segmentation on dense SLAM. *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)* (2015), 4465–4472.

Engin Tola, Christoph Strecha, and Pascal Fua. 2012. Efficient large-scale multi-view stereo for ultra high-resolution image sets. *Machine Vision and Applications* (2012), 1–18.

Aaron Van den Oord, Yazhe Li, and Oriol Vinyals. 2018. Representation learning with contrastive predictive coding. *arXiv e-prints* (2018), arXiv–1807.

Fangjinhua Wang, Silvano Galliani, Christoph Vogel, Pablo Speciale, and Marc Pollefeys. 2021a. Patchmatchnet: Learned multi-view patchmatch stereo. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 14194–14203.

Xinlong Wang, Rufeng Zhang, Chunhua Shen, Tao Kong, and Lei Li. 2021b. Dense contrastive learning for self-supervised visual pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 3024–3033.

Yude Wang, Jie Zhang, Meina Kan, Shiguang Shan, and Xilin Chen. 2020. Self-supervised equivariant attention mechanism for weakly supervised semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 12275–12284.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. 2018. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. 3733–3742.

Hongbin Xu, Zhipeng Zhou, Yu Qiao, Wenxiong Kang, and Qiuxia Wu. 2021. Self-supervised Multi-view Stereo via Effective Co-Segmentation and Data-Augmentation. *ArXiv* abs/2104.05374 (2021).

Qingshan Xu and Wenbing Tao. 2019. Multi-scale geometric consistency guided multi-view stereo. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. 5483–5492.

Jianfeng Yan, Zizhuang Wei, Hongwei Yi, Mingyu Ding, Runze Zhang, Yisong Chen, Guoping Wang, and Yu-Wing Tai. 2020. Dense Hybrid Recurrent Multi-view Stereo Net with Dynamic Consistency Checking. In *European Conference on Computer Vision*. Springer, 674–689.

Yao Yao, Zixin Luo, Shiwei Li, Tian Fang, and Long Quan. 2018. MVSnet: Depth inference for unstructured multi-view stereo. In *Proceedings of the European Conference on Computer Vision (ECCV)*. 767–783.

443 Yao Yao, Zixin Luo, Shiwei Li, Tianwei Shen, Tian Fang, and Long Quan. 2019. Recurrent mvsnet for high-
444   resolution multi-view stereo depth inference. In *Proceedings of the IEEE Conference on Computer Vision and*
445   *Pattern Recognition*. 5525–5534.

446 Hongwei Yi, Zizhuang Wei, Mingyu Ding, Runze Zhang, Yisong Chen, Guoping Wang, and Yu-Wing Tai.
447   2019. Pyramid Multi-view Stereo Net with Self-adaptive View Aggregation. *arxiv preprint arXiv:1912.03001*
448   (2019).

449 Christopher Zach. 2008. Fast and High Quality Fusion of Depth Maps. (01 2008).

450 Jinzhi Zhang, Mengqi Ji, Guangyu Wang, Xue Zhiwei, Shengjin Wang, and Lu Fang. 2021. SurRF: Unsupervised
451   Multi-view Stereopsis by Learning Surface Radiance Field. *IEEE Transactions on Pattern Analysis and*
452   *Machine Intelligence* (2021).

453 Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. 2016. Learning deep features
454   for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern*
455   *recognition*. 2921–2929.