Graph Generation via Temporal-Aware Biased Walks

Abstract

Some real networks keep a fixed structure (e.g., roads, sensors and their connections) while node or edge signals evolve over time. Existing graph generators either model topology changes (i.e., edge additions/deletions) or focus only on static graph properties (such as degree distributions or motifs), without considering how temporal signals shape the generated structure. By approaching the problem from an unconventional perspective, we introduce temporally attributed graphs, named TANGEM, that integrate a temporal similarity matrix into biased random walks, thereby coupling signals with structure to generate graphs that highlight patterns reflecting how nodes co-activate over time. We evaluate TANGEM using an approach that separates structural fidelity (clustering, spectral metrics) from downstream temporal consistency, allowing us to clearly isolate the impact of the topology generator itself. In time series benchmarks, TANGEM consistently outperforms strong baselines in structural metrics while remaining lightweight, learning from a single graph. These results show that adding temporal bias to structural sampling produces more realistic graphs and establishes TANGEM as a basis for future models that further integrate evolving signals and structure.

1 Introduction

Graphs provide a powerful abstraction for representing relational information across diverse domains, including social networks (Leskovec & Mcauley, 2012), biological and molecular structures (Stark et al., 2005), recommender systems, and infrastructure networks such as roads, power grids, and computer systems (Li et al., 2018; Olug et al., 2024). Generative models of graphs, which learn underlying graph distributions from data, are also increasingly important for protein design, drug discovery (Liu et al., 2019), and various networked systems, such as the Internet of Things (De et al., 2022), as well as data augmentation approaches (Bas et al., 2024).

In many of these settings, networks are not only structured but also timeful: nodes and edges may appear or disappear, and their attributes often fluctuate (Rozemberczki et al., 2021).While several recent graph generation studies (e.g., TagGen (Zhou et al., 2020), TIGGER (Gupta et al., 2022), DAMNETS (Clarkson et al., 2022)) tackle the case where the graph topology itself evolves, which is an important and timely contribution, far less attention has been given to the complementary, and practically critical regime where the network topology remains fixed but the node or edge signals change substantially over time. For example, the road infrastructure of a city is largely fixed, yet traffic intensities evolve dynamically; citation networks maintain a stable core of authors and affiliations, but citation frequencies shift over time; sensor networks retain their physical layout, yet the measurements vary continuously; these are only a few such cases.

We argue that even with a fixed topology, temporal dynamics should shape the generated connectivity patterns (e.g., which motifs recur or which spectral modes are emphasized) because time shapes how nodes co-activate. However, existing approaches typically fall into three separate tracks: methods that emphasize topological evolution through edge additions and deletions (Zhou et al., 2020; Gupta et al., 2022; Clarkson et al., 2022); generation models that focus solely on structural graph patterns without temporal context (Bojchevski et al., 2018; Simonovsky & Komodakis, 2018; You et al., 2018b; Shi et al., 2020); and forecasting approaches that predict node signals on a fixed graph but do not allow temporal dynamics to inform the structural patterns of the generated graphs (Islam et al., 2024; Yu et al., 2018; Li et al., 2018).

To address this gap, we propose TANGEM (Temporally Attributed Network GEneration Model), inspired by "tandem", *two components working together*. TANGEM bridges *signal* and *structure* through a temporal-aware biased random walk. We learn a pairwise similarity matrix ρ from historical node signals and inject it as a time-aware bias into a second-order walk, which is modeled autoregressively with a transformer. This design allows temporal co-activation to steer which motifs and spectral modes are emphasized during graph generation, an aspect overlooked by the current literature. To our knowledge, TANGEM is the first generator of temporally attributed graphs with a fixed topology that explicitly couples temporal signals with walk sampling. Our main contributions and findings are: i) a learned similarity matrix ρ computed from historical signals and injected as a time-aware bias into an autoregressive, transformer-based random walk, explicitly coupling temporal co-activation with structural sampling; (ii) empirical gains on temporally attributed benchmarks in structural fidelity, particularly clustering coefficients and spectral distributions, showing that temporal bias in structural sampling better captures recurring interaction patterns; and (iii) ablation studies and clear evaluation, separating structural fidelity (e.g., clustering and spectral MMD) from downstream temporal consistency [1].

2 Related Works

Deep graph generators. Modern deep graph generators mitigate limits in the probabilistic graph generators (e.g., Erdős–Rényi, Barabási–Albert, (Erdös & Rényi, 1959; Albert & Barabási, 2002) and stochastic block models (Holland et al., 1983; Mandjes et al., 2019)) by learning from examples. These models can be broadly categorized into three frameworks: generative adversarial networks (GANs) (Bojchevski et al., 2018), variational auto-encoders (VAEs) (Simonovsky & Komodakis, 2018), and autoregressive models (You et al., 2018b). There are also other methods that leverage reinforcement learning (You et al., 2018a) and flow-based learning (Shi et al., 2020) approaches, mainly for molecular graph generation. Concurrently, there is rapid progress on diffusion and score-based graph generators. Score models tackle the isomorphism issue by operating on set-valued states or exchangeable representations (Niu et al., 2020; Jo et al., 2022). Diffusion-style methods (discrete denoising or continuous-time variants) such as DiGress (Vignac et al., 2023), discrete-state continuous-time diffusion (Xu et al., 2024), CoMeTh (Xu et al., 2024), and DeFoG (QIN et al., 2025) achieve high-fidelity topology and attribute generation, especially in molecular settings (i.e., relatively small graphs), but they still optimize static fidelity (and often require large graph corpora and multi-step sampling). These approaches, however, focus almost exclusively on topology, optimizing adjacency-level fidelity (or delta matrices (Clarkson et al., 2022)) and typically ignore temporal node/edge signals that co-evolve with structure.

Temporal graph learning. A parallel line of work deals with temporal graph learning rather than graph generation, focusing on predicting signals that evolve on a fixed or slowly changing network. Models such as T-GCN (Zhao et al., 2019) and ST-GCN/DCRNN (Yu et al., 2018; Li et al., 2018) combine graph convolution with recurrent or diffusion mechanisms to forecast traffic and other time-series data at network nodes. More recent efforts such as DyGCL (Islam et al., 2024) extend this idea to event prediction by learning dynamic graph representations with contrastive objectives. Although these approaches show how temporal information can improve forecasting on graphs, they are not designed to generate graphs. Nevertheless, they reveal two well-established directions in graph learning that highlight the bidirectional dependency between structure and signals: (1) structure to signals, where topology aids forecasting (Yu et al., 2018; Li et al., 2018); and (2) signals to structure, where temporal co-variation informs graph inference (Dong et al., 2016; Thanou et al., 2016). Together, these studies underscore the need for models that jointly capture structure and temporal dynamics, serving as a direct motivation for the approach we develop in this paper.

Dynamic graph generation with evolving topologies. Another parallel line of work focuses on generating dynamic graphs by modeling how the topology evolves over time. Temporal interaction models like TagGen and TIGGER create timestamped edges using temporal random walks and discriminators or inductive embeddings, explicitly adding and deleting edges over time (Zhou et al., 2020; Gupta et al., 2022). DAMNETS predicts edge additions, removals, or persistence between snapshots using a learned delta matrix

---

[1]For completeness, we *transfer corresponding node features* to the generated topology and then apply autoregressive updates (GCN+RNN), confirming that the observed structural gains arise from the proposed topology module rather than from the forecasting side. This routine component is *not* a technical contribution and is detailed in the Appendix A.9

(Clarkson et al., 2022). Motif-oriented approaches such as DyMOND replicate evolving motif patterns but still treat edge activity as the main signal and generally ignore node or edge attributes (Zeno et al., 2021). These works mainly assume or prioritize structural changes and tend to overlook temporal node features as primary modeling targets.

In contrast, TANGEM (i) jointly models structure and signals rather than treating time as an add-on; (ii) differs from dynamic graph generators (e.g., TagGen, TIGGER, DAMNETS) by not modeling edge additions or deletions but instead focusing on signal–structure coupling within a fixed topology graph generation setting; and (iii) complements deep graph generators by providing a lightweight, history-conditioned mechanism, learned from a single graph.

3 Methodology

In this section, we first define a temporally attributed graph and then describe our method.

Definition 1 (Temporally-Attributed Graph) *A temporally-attributed graph $\mathcal{G}$ is defined as $\mathcal{G} = (\mathbf{G}, \mathbf{X})$, where $\mathbf{G} = (V, E)$ represents the underlying graph topology with node set V and edge set E, and $\mathbf{X} \in \mathbb{R}^{|V| \times T \times F}$ is the tensor of temporal node features, with T denoting the number of discrete time steps and F the number of features per node per timestamps. This formulation captures the evolution of node attributes over time, preserving the structural relationships encoded in $\mathbf{G}$.*

Prior research has demonstrated the effectiveness of biased random walks in capturing graph topology. Specifically, Bojchevski et al. (2018) highlighted that increasing the number and length of these walks improves the ability of the generative model to learn graph representations. However, scale-free networks, such as social networks and citation networks, pose unique challenges, as their number of edges grows faster than their number of nodes due to the preferential attachment mechanism Barabási et al. (2002); Lattanzi & Sivakumar (2009). Consequently, the number of walks required for effective representation increases superlinearly with graph size and even quadratically for certain types of scale-free networks Barabási et al. (2002)zz, resulting in significant computational inefficiencies. Additionally, sampling an excessive number of uniform random walks raises the risk of the generative model overfitting by memorizing the local patterns of the input graph rather than generating meaningful synthetic variations. These challenges underscore the need for strategically designed walks with an ultimate focus on generation, rather than simply increasing the quantity of uniform random walks. To address this, we re-design the biased random walk proposed in Node2Vec Grover & Leskovec (2016) with emphasis on structural exploration and with an additional bias obtained via the temporal node attributes, which leverages the principle of homophily. The ultimate motivation is to capture as many connections as possible (i.e., low repetitions of nodes during walk) while not sacrificing the coherence of local structures and the meaningful community organization of the network.

Temporal Aware Biased Random Walk. To incorporate the temporal (i.e., dynamic) attributes of nodes into a graph's structure, we must make foundational assumptions about how these features are distributed throughout the graph. The principle of spatial smoothness assumes that the features of nodes that are connected and structurally close in a graph (e.g., being in the same community) are more alike than those of disconnected nodes Dong et al. (2016). When we consider features that evolve over time, we extend this assumption to state that the temporal correlation of features is stronger between these same structurally closer nodes. This means a node's feature trajectory is more likely to mirror that of its neighbors within its own community than that of its neighbors in other communities, as their shared environment and interactions lead to more similar and coordinated changes over time.

Under this assumption, we introduce a temporal bias into the random walk process. In the proposed temporal-aware biased random walk method, the walk is guided not only by structural connectivity (i.e., Node2Vec Grover & Leskovec (2016)) but also by a preference to move to nodes whose temporal features are similar to the current node's features. This encourages the random walk to stay within temporally coherent regions of the graph, thereby capturing both the graph topology and temporal dynamics simultaneously. We apply this by defining a pairwise similarity matrix $\mathbf{S} \in \mathbb{R}^{|V| \times |V|}$, where s_{ij} measures the temporal alignment between vertices with indices i and j. This matrix captures the interactions between temporal features from the temporal features of node matrix $\mathbf{X} \in \mathbb{R}^{|V| \times T \times F}$. The similarity is defined by a metric f as in Eq. 1.

Figure 1: Overview of TANGEM. We first compute a $|V| \times |V|$ temporal correlation matrix from the node attributes, which captures how nodes relate to each other across time. This matrix, together with a structural bias that encourages exploratory behavior, guides the walk process used to sample node sequences. The sampled walks are then used as input to a decoder-only transformer, which is trained to model node sequences. During inference, we begin from an initial node (either chosen randomly or specified) and generate a walk autoregressively until the maximum sequence length is reached. The resulting node sequence is finally converted back into a graph structure, using consecutiveness information.

$$S_{ij} = f(x_i, x_j) \tag{1}$$

In previous work, node signals $\mathbf{X}$ are used to *infer* an unknown graph structure by estimating an adjacency matrix $\mathbf{A}$ or a Laplacian $\mathbf{L}$ through constrained optimization (e.g., (Kalofolias, 2016; Thanou et al., 2016)). In contrast, our setting assumes a known, fixed topology $\mathbf{G} = (V, E)$ and does *not* attempt to reconstruct $\mathbf{A}$ or $\mathbf{L}$. Instead, we compute a pairwise temporal similarity matrix $\mathbf{S} \in \mathbb{R}^{|V| \times |V|}$, where each entry $S_{ij} = f(x_i, x_j)$ measures the alignment between the temporal node features $x_i, x_j \in \mathbb{R}^{T \times F}$. This similarity matrix $\mathbf{S}$ directly encodes temporal interactions among vertices and is used as a bias in our random-walk–based graph generation framework, without requiring explicit topology reconstruction.

The traditional second-order random walk is characterized by two parameters, p (return parameter) and q (in-out parameter), to guide the walk. Given a walker just traversed an edge between node k and node u, defining the π_{uv} as unnormalized transition probability between node u and node v, we get the Eq. 2 for unweighted graphs:

$$\pi_{uv} = \alpha_{pq}(k, v) \tag{2}$$

where the search bias α is defined as

$$\alpha_{pq}(k, v) = \begin{cases} \frac{1}{p} & \text{if } \delta_{kv} = 0 \\ 1 & \text{if } \delta_{kv} = 1 \\ \frac{1}{q} & \text{if } \delta_{kv} = 2 \end{cases} \tag{3}$$

The δ_{kv} in Eq. 3 is the shortest path between node k and node v, and is defined as Eq. 4.

Figure 2: The illustration compares three types of walks. In a uniform random walk, the walker moves randomly at each step but often remains in the same neighborhood due to frequent backtracking. A biased walk with exploratory behavior ($q \ll 1$) instead prioritizes moving away from the current neighborhood, reducing redundancy and encouraging exploration of the graph structure. A temporal-aware biased walk balances these two behaviors by always moving for exploration while giving priority to nodes with strong temporal correlation (represented by similar colors).

$$\delta_{kv} = \begin{cases} 0 & \text{if } k = v \\ 1 & \text{if } (k, v) \in E \\ 2 & \text{if } (k, v) \notin E \end{cases} \tag{4}$$

According to our observations, encouraging the depth-first approximation with lower q values improves the learning of graph topology, particularly for generation purposes. It is admissible because the lower values of q reduce the frequency of edge repetitions during the walk, which is desired for the generative model to capture more information on connectivity structure of the graph. Considering this, we update the Eq. 3 by eliminating the parameter p (fixing it as 1), and adding a temporal bias function $\rho(u, v)$ where the u and v are source and target nodes, respectively. With lower values of parameter q, this formulation benefits to sampling explorative walks, while still taking into account the locality information, thanks to the temporal bias function ρ. Finally, we obtain Eq. 5.

$$\alpha_q(k, v, u) = \begin{cases} \frac{1}{q}\rho(u, v) & \text{if } \delta_{kv} = 2 \\ 1 & \text{otherwise} \end{cases} \tag{5}$$

The $\rho(u, v)$ is simply a lookup function as Eq. 6.

$$\rho(u, v) = S_{uv} \tag{6}$$

Then, to consider the two-hop neighbors, $\rho(u, v)$ can be updated as Eq. 7.

$$\rho(u, v) = S_{uv} + \lambda \frac{\sum_{x \in \mathcal{N}(v) \setminus (\mathcal{N}(u) \cup \{u\})} S_{ux}}{|\mathcal{N}(v) \setminus \mathcal{N}(u)| - 1} \tag{7}$$

Here, $\mathcal{N}(.)$ is the set of neighbors of the given node, and the λ is a hyperparameter to control the influence of second-hop neighbors (i.e., neighbors of v, that are not directly connected to u). The set $|\mathcal{N}(v) \setminus \mathcal{N}(u)|$ refers to the size of the set difference between the set of neighbors of vertex v and the set of neighbors of the vertex u in a graph.

For intuition, Fig. 2 illustrates how temporal features are incorporated into the walk sampling procedure. Suppose the walker is at v_3; the exploratory bias reduces the chance of visiting v_1 or v_5' (Eq. 3), but does not distinguish between v_4 and v_4'; here, the temporal bias favors v_4, which lies in a temporally coherent region. Conversely, when the walker is at v_4, the exploratory bias discourages revisiting v_5', which is already connected to the previous node v_3, and instead encourages moving forward to v_5, which promotes exploration.

Autoregressive Generation via Sequence Modelling. We treat the generation of the graph structure as a sequence generation task, where the sequence refers to a series of nodes. Compared to sampling the graph in a single step, sequential representation is often desirable, as it allows for autoregressive modeling of the graph, enabling the capture of complex joint probability of nodes and connections via recurrent learning architectures such as RNNs and transformer-based models You et al. (2018b); Bojchevski et al. (2018); Liao et al. (2019). In contrast, sampling the adjacency matrix (or an equivalent) in a single step suffers from scalability issues, as the adjacency matrix size grows quadratically with the number of vertices Tavakoli et al. (2017). For these two reasons, we use a transformer model to learn the underlying marginal distribution of the joint distribution of the graph (the same form given in Eq. 8) by leveraging temporal-aware biased random walks sampled from the graph. In other words, we take into account all tokens generated so far, not just the current state, when computing the next-step probability.

At the inference time (i.e., generating synthetic graphs), we start with an initial token and generate a sequence of nodes conditioned on the previous tokens, following the approach used in sequence models, similar to language models. The joint probability of generating a sequence can be decomposed as in Eq. 8, where the v_1 is the starting token (i.e., first node), and $\mathbf{s}_{<m}$ is the sequence generated so far. Here, $P(\mathbf{s})$ denotes the overall probability of generating the full node sequence. The term $P(v_1)$ represents the probability of generating the initial node (or starting token). Each subsequent term $P(v_m \mid \mathbf{s}_{<m})$ corresponds to the probability of generating the m-th node v_m, conditioned on the previously generated sequence $\mathbf{s}_{<m} = \{v_1, \ldots, v_{m-1}\}$

$$P(\mathbf{s}) = P(v_1) \prod_{m=2}^{M} P(v_m \mid \mathbf{s}_{<m}) \tag{8}$$

We use the terms *sequence* and *walk* interchangeably, with the hyperparameter M denoting both the sequence length and number of generated tokens. Unlike methods that rely on aggregating multiple short walks to form an adjacency matrix Bojchevski et al. (2018); Zhou et al. (2020), we instead generate a small number of long walks, k. This design choice is motivated by the ability of the transformer model to capture long-range dependencies within sequences. The resulting sequence directly encodes graph connectivity, uniquely determining the graph structure. Notably, if one sequence of length M is used, the generated graph contains at most M unique nodes, and exactly M only for a path graph, since repeated vertices in the sequence reduce the effective node count.

4 Experiments

We evaluate TANGEM on synthetic and real-world datasets, benchmarking structural fidelity (degree, clustering, spectral, motif, orbit) against strong baselines.

To provide a rigorous analysis of the model's capabilities and practical utility, our experiments are guided by the following three research questions:

- **RQ1:** How do variations in walk-sampling strategies affect the quality of graphs?

- **RQ2:** How does feature-guidance interact with homophilic graphs, where connectivity and feature similarity are correlated?

- **RQ3:** How does feature-guidance interact with heterophilic graphs, where connectivity and feature similarity are independent?

4.1 Datasets

We evaluate TANGEM on both synthetic and real-world temporal datasets with varying sizes and properties (e.g., grid-like, path-like, community).

IBB dataset. The IBB graph datasets consist of real-world road traffic data collected in Istanbul (Olug et al., 2024). To evaluate our model across varying scales, we utilize three distinct graph configurations: two

Figure 3: Comparison between original and generated graphs with different sizes.

district-level subsets and one comprehensive global network. The two regional datasets, IBB1 and IBB2, represent specific districts of Istanbul and consist of $|N| = 256$ and $|N| = 294$ nodes, respectively. To assess the scalability of our approach, we further incorporate a city-wide global network comprising $|N| = 2,451$ nodes and $|E| = 3,667$ edges. In each graph, vertices represent specific geographic locations, and the associated temporal attributes correspond to traffic density values recorded at those locations.

PEMS dataset. The PEMS-04 traffic dataset (Chen et al., 2001) was collected in a major metropolitan area in California. The original dynamic graph has a size of $|N| = 307$. For our experiments, we focus on the largest connected component, which consists of $|N| = 237$ nodes.

CiteSeer dataset. The CiteSeer (CS) network (Sen et al., 2008) is a widely used benchmark dataset where documents are represented as nodes and citation relationships as edges. Following (Bojchevski et al., 2018), we used the largest connected component, which has a size of $|N| = 2120$. To generate synthetic temporal node features and introduce dynamicity, we used a heat diffusion process (see the Appendix A.6 for details).

4.2 Baseline Models

We benchmarked TANGEM against both classical and modern graph generators. As traditional baselines we used the Erdős–Rényi (E–R) model (Erdos & Renyi, 1959), which forms edges with a fixed probability, and the Barabási–Albert (B–A) model (Barabási et al., 2002), which reproduces scale-free networks via preferential attachment. For deep learning baselines we included GraphVAE (Simonovsky & Komodakis, 2018), a variational autoencoder for latent-variable graph reconstruction; GraphRNN (You et al., 2018b), which sequentially generates nodes and edges with an RNN; GRAN Liao et al. (2019), which combines block-wise autoregression and self-attention; NetGAN Bojchevski et al. (2018), which uses random walks and adversarial training to learn graph distributions; and DiGress Vignac et al. (2023), a diffusion-based model that denoises to produce high-quality, diverse graphs. NetGAN is the only baseline able to learn from a single input graph, like our approach, whereas the others require multiple graphs. To ensure compatibility of our single-graph datasets (IBB1, IBB2, and Pems04) with these methods, we created augmented versions by adding and removing random edges.

Table 1: Comparison of TANGEM to other generative models across different datasets and metrics (lower values are better). TANGEM-Plain is trained on uniform random walks, while TANGEM is trained on biased and temporal-aware walks formulated in Eq. 5. Bold numbers correspond to the best performance, while underlined entries are the second-best performance.

	IBB1					IBB2				
	Degree	Clustering	Spectral	Orbit	Motif	Degree	Clustering	Spectral	Orbit	Motif
E-R Generator	0.1464	0.0508	0.0862	0.1887	0.9817	0.1809	0.3898	0.0640	0.7971	1.2489
B-A Generator	0.4117	0.0001	0.2769	1.2684	1.5436	0.3033	1.4708	0.1262	1.2303	1.3013
GraphVAE	0.2952	1.2321	0.1592	1.3620	1.2369	0.3138	1.2748	0.1085	1.3574	1.2164
NetGAN	0.1316	0.0780	0.1037	0.1693	1.0169	0.2803	0.8705	0.0800	1.4898	1.7207
GraphRNN	0.0165	0.0527	0.0988	0.0057	0.2143	0.2243	0.1295	0.1266	0.3793	1.5659
GRAN	0.0153	0.0412	0.1180	0.0160	0.5055	**0.0358**	0.5573	0.0509	0.0259	0.5599
DiGress	0.0355	0.0071	0.1108	0.0073	0.0239	0.1417	0.0467	0.0655	0.0913	**0.0987**
TANGEM-Plain	0.0155	0.0030	0.1201	0.0104	0.1518	0.0601	0.0022	0.0721	**0.0214**	0.5993
TANGEM	**0.0038**	**0.0004**	**0.0548**	**0.0001**	**0.0155**	0.0449	**0.0007**	**0.0464**	0.0397	0.7055

	Pems04					CiteSeer				
	Degree	Clustering	Spectral	Orbit	Motif	Degree	Clustering	Spectral	Orbit	Motif
E-R Generator	0.1324	1.8028	0.1321	0.2152	1.2456	0.0805	1.9977	0.0705	1.9939	1.9534
B-A Generator	0.3191	1.8998	0.3617	1.1361	1.4508	0.0823	1.9881	0.0439	1.2782	1.3310
GraphVAE	0.2260	1.2625	0.1827	1.3945	1.2705	-	-	OOM	-	-
NetGAN	0.1213	1.3081	0.1656	0.0226	0.3007	0.0051	**0.1371**	0.0245	1.3514	1.1846
GraphRNN	0.0417	0.4823	0.1522	0.0036	0.0259	-	-	OOM	-	-
GRAN	0.0110	0.7434	0.1191	0.0133	0.1415	0.0131	1.7133	0.0245	1.3703	1.3763
DiGress	0.1383	1.0884	0.1570	0.4537	1.4593	-	-	OOM	-	-
TANGEM-Plain	0.0407	0.3515	0.1410	0.0650	0.7994	**0.0008**	0.1515	0.0085	1.6221	1.6530
TANGEM	**0.0012**	**0.2694**	**0.0637**	**0.0004**	**0.0048**	0.0024	0.6963	**0.0079**	**0.0799**	**0.0112**

4.3 Evaluation Metrics

Following prior work You et al. (2018b); Liao et al. (2019), we assess TANGEM by comparing generated and original graphs using Maximum Mean Discrepancy (MMD) Gretton et al. (2012) over key structural properties: degree distribution, clustering coefficient, spectral characteristics, motif count, and orbit count. These metrics respectively capture connection frequencies, community structure, global connectivity via Laplacian eigenvalues, prevalence of recurring subgraphs, and roles of nodes within motifs. For each property, we compute MMD with a Gaussian kernel to measure the divergence between the distributions of the original and generated graphs, ensuring a robust evaluation of both local and global structural features. We additionally conduct a visual inspection to qualitatively assess structural resemblance.

4.4 Experimental Results

Table 1 presents a comparison of different graph generation models, including two variants of TANGEM. TANGEM-Plain represents a simpler version of TANGEM, where the transformer is trained on uniform random walks instead of temporal-aware biased walks. Still, TANGEM-Plain remains competitive with the baselines. TANGEM, on the other hand, shows strong performance against all baselines across every structural metric. On the IBB1 and Pems04 datasets, which are path-like, TANGEM surpasses all other methods in almost all metrics. This suggests that TANGEM is particularly effective at modeling path-like graphs (see also Fig. 3). However, some caution is needed, since such paths could be memorized by the model due to the explorative nature of the walks, which can nearly cover long paths. To investigate this, we generated graphs of different sizes and visualized them, as shown in Fig. 3. For the IBB2 dataset, no method clearly outperforms the others, though TANGEM remains competitive. On CiteSeer, NetGAN is the only comparable deep generative model, and TANGEM surpasses it on all metrics except clustering.

Following previous works (You et al., 2018b; Liao et al., 2019; Vignac et al., 2023), we further evaluate the performance of TANGEM via visual inspection. Fig. 3 visualizes the graphs generated by TANGEM and

baselines, highlighting that TANGEM can capture and synthesize the real-world graphs with characteristics like path, grid, and community. For the CiteSeer graph, it can be clearly seen that the community structures and sparsity are well-preserved. Notably, TANGEM generates relatively large graphs within a highly acceptable training and inference time, whereas all deep graph generators but NetGAN fail to scale. As seen in the figure, although the NetGAN-generated CiteSeer graph weakly reflects community structure, it fails to represent the overall characteristics of the original graph.

4.5 RQ1: Parameter Analysis

In that section, we assess the effect of structural and feature-based bias sources on the graph generation performance. Structural bias is controlled by the parameters p and q, which enable an adjustable walk strategy between Breadth-First Search (BFS) and Depth-First Search (DFS) behaviors. We conducted our experiments on the IBB graph, which comprises 2,451 nodes and 3,667 edges. The experimental results, illustrated in Fig. 4, demonstrate that increasing p from 0.1 to 2 yields improvements across all metrics, regardless of the value of q. This trend supports our hypothesis on the role of exploratory behavior. Regarding q, we observe that for nearly all values of p, an increase in q leads to higher MMD scores, further validating our initial hypothesis. In this setting, we aimed to isolate structural bias from temporal bias and did not utilize feature bias.

Figure 4: Analysis of structural bias parameters p and q (scores are normalized).

	Method	Degree ($\downarrow$)	Clust. ($\downarrow$)	Orbit ($\downarrow$)
Pems04	Base	1.85 ± 0.11	35.21 ± 7.52	8.56 ± 0.95
	Pearson	$\underline{1.84 \pm 0.15}$	$\mathbf{27.36 \pm 6.09}$	9.03 ± 0.78
	Cross-Corr	1.93 ± 0.42	31.54 ± 9.85	$\underline{8.41 \pm 2.36}$
	DTW	$\mathbf{1.83 \pm 0.15}$	$\underline{33.81 \pm 4.69}$	$\mathbf{7.28 \pm 1.17}$
IBB	Base	0.74 ± 0.05	0.02 ± 0.01	12.18 ± 1.96
	Pearson	$\underline{0.73 \pm 0.02}$	$\underline{0.01 \pm 0.00}$	$\underline{11.54 \pm 1.41}$
	Cross-Corr	0.79 ± 0.04	0.02 ± 0.00	12.10 ± 0.71
	DTW	$\mathbf{0.69 \pm 0.05}$	$\mathbf{0.01 \pm 0.00}$	$\mathbf{10.22 \pm 0.60}$
CiteSeer	Base	$\mathbf{0.10 \pm 0.01}$	13.03 ± 1.04	6.94 ± 0.50
	Cosine	$\mathbf{0.10 \pm 0.01}$	$\underline{12.50 \pm 0.61}$	$\mathbf{5.44 \pm 1.37}$
	Cross-Corr	0.11 ± 0.01	19.00 ± 6.76	7.59 ± 5.43
	DTW	0.12 ± 0.02	14.79 ± 2.89	7.48 ± 1.93

Table 2: Analysis of feature bias functions ($\times 10^{-2}$).

To evaluate the impact of feature-guided bias, we compared the performance of Pearson Correlation, Cross-correlation, and Dynamic Time Warping (DTW) across two spatio-temporal traffic datasets (Pems04 and IBB) and one static graph dataset (CiteSeer). Our results indicate that for spatio-temporal graphs, DTW consistently outperforms other methods, while Pearson Correlation also notably surpasses the Base version, where no feature-guided bias is applied. This trend continues in the IBB dataset, where DTW maintains the highest performance, and the success of Pearson Correlation further suggests that even when the specific time-series nature of the data is not fully leveraged, applying a simple statistical bias can significantly enhance generation performance. Finally, in the static context of CiteSeer, Pearson Correlation proves to be the most effective measure, confirming that feature-guided bias is beneficial across diverse graphs.

4.6 RQ2: Applicability on Homophilic Networks

While the homophily assumption describes the overall behavior of various real-world networks (e.g., social and citation graphs), noisy (i.e., non-homophilic) edges naturally arise. In this context, our feature-guided walks should prioritize nodes with high feature alignment in addition to structural proximity. This approach

Table 3: Mean Purity and Coverage: Standard vs. Biased and the resulting Percentage Change

| | | q values | | | | | | | |
| | | 0.1 | | 0.5 | | 1.0 | | 2.0 | |
p value	Method	Pur. (↑)	Cov. (↑)	Pur. (↑)	Cov. (↑)	Pur. (↑)	Cov. (↑)	Pur. (↑)	Cov. (↑)
	Standard	0.673	11.35	0.719	7.78	0.712	6.18	0.753	4.84
p = 0.1	Biased	0.673	11.03	0.733	7.57	0.722	5.82	0.755	4.71
	Change	**+0.00%**	**-2.82%**	**+1.95%**	**-2.70%**	**+1.40%**	**-5.83%**	**+0.27%**	**-2.69%**
	Standard	0.600	14.28	0.641	11.93	0.671	10.17	0.690	8.61
p = 0.5	Biased	0.609	14.21	0.660	11.43	0.660	9.91	0.693	8.38
	Change	**+1.50%**	**-0.49%**	**+2.96%**	**-4.19%**	**-1.64%**	**-2.56%**	**+0.43%**	**-2.67%**
	Standard	0.611	15.26	0.632	13.07	0.665	11.67	0.662	10.13
p = 1.0	Biased	0.638	14.74	0.637	12.96	0.688	11.22	0.672	9.82
	Change	**+4.42%**	**-3.41%**	**+0.79%**	**-0.84%**	**+3.46%**	**-3.86%**	**+1.51%**	**-3.06%**
	Standard	0.592	15.50	0.593	14.38	0.624	12.87	0.632	11.50
p = 2.0	Biased	0.608	15.74	0.624	14.19	0.619	13.15	0.657	11.16
	Change	**+2.70%**	**+1.55%**	**+5.25%**	**-1.32%**	**-0.80%**	**+2.17%**	**+3.95%**	**-2.95%**

ideally functions as a local adaptive filter that de-emphasizes noisy edges while strengthening local clusters.

To validate this claim, we conducted an experimental analysis using the CiteSeer dataset. Specifically, we sampled walks using pure structural information and compared them against walks incorporating feature guidance. We assessed two key metrics: label purity and node coverage. Label purity measures the semantic consistency of a walk, calculated as the percentage of nodes sharing the same label as the starting node. Node coverage measures exploration capability, defined as the number of distinct nodes visited during a walk. A predictable trade-off is that feature guidance can induce highly localized behavior, where the walker tends to oscillate within a narrow neighborhood. While this increases label purity, it may hinder the exploration necessary for high-quality generation (see Fig. 4). We posit that the feature-guided mechanism is beneficial if the gain in label purity does not significantly harm node coverage. This balance ensures semantic consistency without sacrificing the structural diversity required for effective node representations.

The results of this experiment are summarized in Table 3, covering various combinations of the hyperparameters p and q. For each configuration, 100 walks of length 20 were generated across three independent trials for consistency. We utilized the largest connected component of CiteSeer and applied cosine similarity to the 3,703-dimensional bag-of-words node features. The dataset contains a total of six labels.

Before comparing the methods, several general patterns emerge. For BFS-like configurations such as $(p, q) = (0.1, 2.0)$, the walk exhibits significantly restricted exploration. This results in low Coverage (averaging 4–5 unique nodes), though Purity remains relatively high ($\tilde{0}.75$). This aligns with the theoretical role of a low p value, which encourages the walker to stay near the source node. Conversely, configurations favoring DFS-like exploration, such as $(p, q) = (2.0, 0.1)$, yield substantially higher Coverage (averaging 15 unique nodes). However, this expanded exploration typically comes at the cost of Purity, which drops to approximately 0.6 as the walker becomes more likely to cross class boundaries.

When comparing purely structural walks to our feature-guided approach, performance gains become evident when $p \geq 1$. At $p = 1$, the increase in Purity begins to outweigh the marginal reduction in Coverage, particularly for lower values of q. A notable example is the configuration $(p, q) = (1.0, 0.1)$, where Purity increases by 4.42% while Coverage decreases by only 3.41%. The advantages of the feature-guided mechanism are most pronounced at higher values of p, such as $p = 2$. This setting promotes high structural exploration, which is then refined by feature similarity to ensure that even far-reaching walks remain semantically consistent. This is best exemplified at $(p, q) = (2.0, 0.5)$, where Purity significantly improved by 5.25% while Coverage dropped by only 1.32%. Finally, the $(p, q) = (2.0, 0.1)$ configuration presents a particularly interesting case, as both Purity and Coverage improved simultaneously. This can be explained by the synergy between DFS-like behavior and feature guidance; the mechanism may guide the walker toward high-degree nodes of that community. Ultimately, this allows the walker to explore more distant parts of the graph (increasing Coverage) while remaining within the correct semantic manifold (increasing Purity).

(a) SBM graph   (b) Resulting embeddings

Condition	NMI ($\uparrow$)	ARI ($\uparrow$)	Silh. ($\uparrow$)
Pure Structure	0.634	0.674	0.030
Random	0.606	0.656	0.027
Homophily	**0.952**	**0.966**	**0.085**
Heterophily	0.150	0.146	0.014

Table 4: Clustering results by structure-feature correlation (Bold: Homophily; Underline: Heterophily).

Figure 6: Analysis of structural and feature-based biases.

4.7 RQ3: Applicability on Heterophilic Networks

In this section, we examine the behavior of feature-guided walks within heterophilic graphs. For this purpose, we construct a synthetic graph using a Stochastic Block Model (SBM) with four distinct communities. To analyze varying node-feature interactions, we generate homophilic, heterophilic, and random features over this structure. Structural and distance-based weights are kept equal; for each variant, node embeddings are generated using Node2Vec with walk parameters $(p, q) = (1.0, 0.1)$, biased toward transitions to nodes with lower Cosine distance. We evaluate the results using K-Means clustering. Performance is measured against ground-truth communities using Normalized Mutual Information (NMI), Adjusted Rand Index (ARI), and Silhouette scores.

For the homophilic case, features are assigned based on a node's community membership. For heterophily, we apply graph coloring to each community separately; this ensures that connected nodes within the same community possess dissimilar features, while nodes in different communities may share similarities. Finally, we use a Gaussian distribution to assign random features to nodes, independent of any structural information.

The results presented in Table 4 indicate that in heterophilic settings, all evaluation metrics drop significantly compared to the topology-only (pure structure), homophilic, and random cases. This suggests that features misaligned with the graph structure force the random walks to take steps that conflict with the underlying topology. Notably, the homophilic scenario yields the highest Silhouette, NMI, and ARI scores. These findings are visually approved by the t-SNE plots in Fig. 5b: while clusters are distinguishable in the structural embeddings, they become increasingly blurred in the random case and almost indistinguishable in the heterophilic case. In contrast, the homophilic variant produces the most clearly defined clusters.

This experiment demonstrates that the proposed feature-guided biased random walk is effective when the graph homophily is leveraged. Consequently, while the current distance-based metrics (e.g., cosine, Euclidean, DTW) are optimized for homophilic structures, their performance in high-heterophily settings suggests a dependency on feature-topological alignment. We have identified the integration of learnable distance metrics as a key direction for future work to extend the method's robustness to heterophilic graphs.

4.8 RQ4: Scalability

This section evaluates the computational efficiency of TANGEM against DiGress, which is a primary diffusion-based baseline model. While DiGress is effective for large datasets with small-to-medium graphs (e.g., Wu et al. (2018)), it faces significant scalability issues on larger graphs due to an $O(n^2)$ space complexity. Its iterative sampling process further scales linearly with the number of diffusion steps (T), resulting in an overall time complexity of $O(T \cdot n^2)$. Conversely, in TANGEM, each generation step requires a linear cost of $O(n)$ per step. Since k sequences, each consisting of M tokens, are independently parallelizable, the

Table 5: Scalability Comparison of DiGress and TANGEM

N	TANGEM	DiGress $(T = 100)$	DiGress $(T = 500)$
50	0.10s / 18.0 MB	0.44s / 41.7 MB	2.20s / 41.7 MB
100	0.21s / 19.0 MB	0.48s / 86.7 MB	2.39s / 86.7 MB
200	0.43s / 19.0 MB	0.88s / 269.4 MB	4.43s / 269.4 MB
400	0.86s / 25.0 MB	3.30s / 972.8 MB	16.48s / 972.8 MB
800	1.72s / 28.0 MB	12.42s / 3.8 GB	62.12s / 3.8 GB
1600	3.44s / 36.0 MB	48.61s / 15.3 GB	TIMEOUT
3200	6.82s / 69.0 MB	OOM / TIMEOUT	OOM / TIMEOUT

Figure 7: Generation parameters

time complexity remains $O(M \cdot n)$, while total computational work scales as $O(M \cdot \mathbf{k} \cdot n)$. Unlike diffusion methods, the space complexity remains $O(n)$ as no adjacency matrix is involved.

The total number of tokens generated $(M \cdot \mathbf{k})$ bounds the number of nodes in the resulting graph by $\min(M \cdot \mathbf{k}, n)$. In practise, due to the repeated node visits and cross-sequence overlap, the graph size is expected to be lower than $(M \cdot \mathbf{k})$. Fig. 7 shows the change in graph size as a function of M and $\mathbf{k}$. These two hyperparameters enable flexible control over the generation size, which is particularly useful for large graph generation where a single long sequence may be insufficient.

Table 5 presents the time and space analysis for generating a single SBM graph with different numbers of nodes and a fixed edge density $(|E| \approx 5 \times |N|)$ using DiGress and TANGEM. The results indicate that while DiGress generates graphs with several hundred nodes within reasonable limits, it quickly starts to explode due to its quadratic complexity in both dimensions. For instance, generating a 400-node graph requires 1 GB of memory. On the other hand, TANGEM exhibits significantly better scalability, maintaining manageable time and space requirements as the graph size increases.

Limitations. While TANGEM introduces a new framework for generating attributed graphs with a fixed topology, it currently relies on several simplifying assumptions. First, it assumes that the set of nodes and the underlying edge skeleton are known in advance and remain stable across snapshots. This choice is well-suited to domains such as transportation or sensor networks, but limits direct applicability to settings where nodes and edges emerge frequently, such as social networks. An extension toward dynamic graphs, where edges or nodes may appear or disappear over time, is to train on the union of all edges observed across time and to learn a time-dependent edge-presence function. For example, during generation, walks could still be sampled on this union graph, while a neural head $g(u, v, t)$ would output a time-dependent edge-survival probability (e.g., Bernoulli) conditioned on temporal similarity $\rho(u, v)$, recency, and walk context, retrofitting edge addition and deletion without redesigning the core architecture. Second, TANGEM currently leverages a distance-based similarity signal to guide walk sampling. Although this bias improves structural fidelity in homophilic signals, it may be less effective in non-homophilic graphs where connected nodes display dissimilar patterns. Addressing these constraints opens several research avenues.

5 Conclusion

We presented TANGEM, a generator for temporally attributed graphs with a fixed topology. By injecting a learned temporal similarity into a transformer-based biased random walk, TANGEM directly couples signals and structure so that recurring co-activation patterns guide which motifs and spectral modes the generated graphs emphasize. Across benchmarks, it consistently improves structural metrics over strong static baselines. To keep this study focused and provide clear ablations, we have intentionally left extensions to dynamic graphs and non-homophilic settings for future work. Nonetheless, we believe TANGEM establishes a solid foundation for temporally attributed graph generation in fixed-topology regimes and serves as a stepping stone toward future models that also incorporate evolving nodes and edges.

Reproducibility Statement

The main paper specifies the problem setting and evaluation separation (Sec. 3: the definition of the temporally-attributed graph and fixed-topology regime; Sec. 4: structural vs. downstream metrics) and defines all metrics (clustering, spectral MMD) and baselines. The Appendix details the topology generator (temporal-similarity construction, transformer walk model, and hyperparameters), ablations, and the routine feature-sampling setup used only for analysis. Our anonymous code repository (link in Supplementary) includes: implementation of TANGEM's topology module, exact training/evaluation scripts for each dataset, configuration files with all hyperparameters, random seeds, and run commands; data preprocessing pipelines for time-series benchmarks (including splits and normalization); and scripts to compute all reported metrics and figures. We also release preprocessed datasets, instructions for environment setup (including requirements and container specifications), and notes on hardware/runtime in the public repository.

References

Réka Albert and Albert-László Barabási. Statistical mechanics of complex networks. *Reviews of Modern Physics*, 74(1):47–97, January 2002. ISSN 1539-0756. doi: 10.1103/revmodphys.74.47. URL http://dx.doi.org/10.1103/RevModPhys.74.47.

A.L Barabási, H Jeong, Z Néda, E Ravasz, A Schubert, and T Vicsek. Evolution of the social network of scientific collaborations. *Physica A: Statistical Mechanics and its Applications*, 311(3):590–614, 2002. ISSN 0378-4371. doi: https://doi.org/10.1016/S0378-4371(02)00736-7. URL https://www.sciencedirect.com/science/article/pii/S0378437102007367.

Sumeyye Bas, Kiymet Kaya, Resul Tugay, and Sule Gunduz Oguducu. Data augmentation in graph neural networks: The role of generated synthetic graphs, 2024. URL https://arxiv.org/abs/2407.14765.

Aleksandar Bojchevski, Oleksandr Shchur, Daniel Zügner, and Stephan Günnemann. Netgan: Generating graphs via random walks, 2018. URL https://arxiv.org/abs/1803.00816.

Chao Chen, Karl F. Petty, Alexander Skabardonis, Pravin Pratap Varaiya, and Zhanfeng Jia. Freeway performance measurement system: Mining loop detector data. *Transportation Research Record*, 1748:102 – 96, 2001. URL https://api.semanticscholar.org/CorpusID:108891582.

Jase Clarkson, Mihai Cucuringu, Andrew Elliott, and Gesine Reinert. Damnets: A deep autoregressive model for generating markovian network time series. In *Learning on Graphs Conference*, pp. 23–1. PMLR, 2022.

Suparna De, Maria Bermudez-Edo, Honghui Xu, and Zhipeng Cai. Deep generative models in the industrial internet of things: A survey. *IEEE Transactions on Industrial Informatics*, 18(9):5728–5737, 2022. doi: 10.1109/TII.2022.3155656.

Xiaowen Dong, Dorina Thanou, Pascal Frossard, and Pierre Vandergheynst. Learning laplacian matrix in smooth graph signal representations, 2016. URL https://arxiv.org/abs/1406.7842.

P Erdös and A Rényi. On random graphs i. *Publicationes Mathematicae Debrecen*, 6:290–297, 1959.

Paul Erdos and Alfred Renyi. On random graphs i. *Publicationes Mathematicae*, 6:290–297, 1959.

Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13(25):723–773, 2012. URL http://jmlr.org/papers/v13/gretton12a.html.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks, 2016. URL https://arxiv.org/abs/1607.00653.

Shengnan Guo, Youfang Lin, Ning Feng, Chao Song, and Huaiyu Wan. Attention based spatial-temporal graph convolutional networks for traffic flow forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):922–929, Jul. 2019. doi: 10.1609/aaai.v33i01.3301922. URL https://ojs.aaai.org/index.php/AAAI/article/view/3881.

Shubham Gupta, Sahil Manchanda, Srikanta Bedathur, and Sayan Ranu. Tigger: Scalable generative modelling for temporal interaction graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 6819–6828, 2022.

Paul W. Holland, Kathryn Blackmond Laskey, and Samuel Leinhardt. Stochastic blockmodels: First steps. *Social Networks*, 5(2):109–137, 1983. ISSN 0378-8733. doi: https://doi.org/10.1016/0378-8733(83)90021-7. URL https://www.sciencedirect.com/science/article/pii/0378873383900217.

Muhammed Ifte Khairul Islam, Khaled Mohammed Saifuddin, Tanvir Hossain, and Esra Akbas. Dygcl: Dynamic graph contrastive learning for event prediction. *arXiv preprint arXiv:2404.15612*, 2024.

Jaehyeong Jo, Seul Lee, and Sung Ju Hwang. Score-based generative modeling of graphs via the system of stochastic differential equations. In *International Conference on Machine Learning*, 2022. URL https://api.semanticscholar.org/CorpusID:246634850.

Vassilis Kalofolias. How to learn a graph from smooth signals, 2016. URL https://arxiv.org/abs/1601.02513.

Silvio Lattanzi and D. Sivakumar. Affiliation networks. In *Proceedings of the Forty-First Annual ACM Symposium on Theory of Computing*, STOC '09, pp. 427–434, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585062. doi: 10.1145/1536414.1536474. URL https://doi.org/10.1145/1536414.1536474.

Jure Leskovec and Julian Mcauley. Learning to discover social circles in ego networks. In F. Pereira, C.J. Burges, L. Bottou, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012. URL https://proceedings.neurips.cc/paper_files/paper/2012/file/7a614fd06c325499f1680b9896beedeb-Paper.pdf.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting, 2018. URL https://arxiv.org/abs/1707.01926.

Renjie Liao, Yujia Li, Yang Song, Shenlong Wang, Will Hamilton, David K Duvenaud, Raquel Urtasun, and Richard Zemel. Efficient graph generation with graph recurrent attention networks. *Advances in neural information processing systems*, 32, 2019.

Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander L. Gaunt. Constrained graph variational autoencoders for molecule design, 2019. URL https://arxiv.org/abs/1805.09076.

Michel Mandjes, Nicos Starreveld, René Bekker, and Peter Spreij. Dynamic erdős-rényi graphs. *Computing and Software Science: State of the Art and Perspectives*, pp. 123–140, 2019.

Chenhao Niu, Yang Song, Jiaming Song, Shengjia Zhao, Aditya Grover, and Stefano Ermon. Permutation invariant graph generation via score-based generative modeling. In Silvia Chiappa and Roberto Calandra (eds.), *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pp. 4474–4484. PMLR, 26–28 Aug 2020.

Eren Olug, Kiymet Kaya, Resul Tugay, and Sule Gunduz Oguducu. Ibb traffic graph data: Benchmarking and road traffic prediction model, 2024. URL https://arxiv.org/abs/2408.01016.

Yiming QIN, Manuel Madeira, Dorina Thanou, and Pascal Frossard. Defog: Discrete flow matching for graph generation. In *Forty-second International Conference on Machine Learning*, 2025.

Benedek Rozemberczki, Paul Scherer, Yixuan He, George Panagopoulos, Alexander Riedel, Maria Astefanoaei, Oliver Kiss, Ferenc Beres, Guzmán López, Nicolas Collignon, and Rik Sarkar. Pytorch geometric temporal: Spatiotemporal signal processing with neural machine learning models. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, CIKM '21, pp. 4564–4573, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450384469. doi: 10.1145/3459637.3482014. URL https://doi.org/10.1145/3459637.3482014.

Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Gallagher, and Tina Eliassi-Rad. Collective classification in network data. *AI Mag.*, 29(3):93–106, September 2008. ISSN 0738-4602. doi: 10.1609/aimag.v29i3.2157. URL https://doi.org/10.1609/aimag.v29i3.2157.

Chence Shi, Minkai Xu, Zhaocheng Zhu, Weinan Zhang, Ming Zhang, and Jian Tang. Graphaf: a flow-based autoregressive model for molecular graph generation, 2020. URL https://arxiv.org/abs/2001.09382.

Martin Simonovsky and Nikos Komodakis. Graphvae: Towards generation of small graphs using variational autoencoders, 2018. URL https://arxiv.org/abs/1802.03480.

Chris Stark, Bobby-Joe Breitkreutz, Teresa Reguly, Lorrie Boucher, Ashton Breitkreutz, and Mike Tyers. Biogrid: a general repository for interaction datasets. *Nucleic Acids Research*, 34:D535 – D539, 2005. URL https://api.semanticscholar.org/CorpusID:2838900.

Sahar Tavakoli, Alireza Hajibagheri, and Gita Reese Sukthankar. Learning social graph topologies using generative adversarial neural networks. In *Proceedings of the International Conference on Social Computing, Behavioral-Cultural Modeling and Prediction (SBP-BRiMS)*, 2017. URL https://api.semanticscholar.org/CorpusID:34723828.

Dorina Thanou, Xiaowen Dong, Daniel Kressner, and Pascal Frossard. Learning heat diffusion graphs, 2016. URL https://arxiv.org/abs/1611.01456.

Clement Vignac, Igor Krawczuk, Antoine Siraudin, Bohan Wang, Volkan Cevher, and Pascal Frossard. Digress: Discrete denoising diffusion for graph generation, 2023. URL https://arxiv.org/abs/2209.14734.

Zhenqin Wu, Bharath Ramsundar, Evan N. Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S. Pappu, Karl Leswing, and Vijay Pande. Moleculenet: A benchmark for molecular machine learning, 2018. URL https://arxiv.org/abs/1703.00564.

Zhe Xu, Ruizhong Qiu, Yuzhong Chen, Huiyuan Chen, Xiran Fan, Menghai Pan, Zhichen Zeng, Mahashweta Das, and Hanghang Tong. Discrete-state continuous-time diffusion for graph generation. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Jiaxuan You, Bowen Liu, Zhitao Ying, Vijay Pande, and Jure Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. *Advances in neural information processing systems*, 31, 2018a.

Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton, and Jure Leskovec. Graphrnn: Generating realistic graphs with deep auto-regressive models. In *International conference on machine learning*, pp. 5708–5717. PMLR, 2018b.

Bing Yu, Haoteng Yin, and Zhanxing Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence*, IJCAI-2018, pp. 3634–3640. International Joint Conferences on Artificial Intelligence Organization, July 2018. doi: 10.24963/ijcai.2018/505. URL http://dx.doi.org/10.24963/ijcai.2018/505.

Giselle Zeno, Timothy La Fond, and Jennifer Neville. Dymond: Dynamic motif-nodes network generative model. In *Proceedings of the Web Conference 2021*, pp. 718–729, 2021.

Ling Zhao, Yujiao Song, Chao Zhang, Yu Liu, Pu Wang, Tao Lin, Min Deng, and Haifeng Li. T-gcn: A temporal graph convolutional network for traffic prediction. *IEEE transactions on intelligent transportation systems*, 21(9):3848–3858, 2019.

Dawei Zhou, Lecheng Zheng, Jiawei Han, and Jingrui He. A data-driven graph generative model for temporal interaction networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 401–411, 2020.

A Appendix

A.1 Implementation Details of TANGEM

The TANGEM employs a transformer that processes sampled walks, treating graphs as sequences of tokens. The model uses learnable token and positional embeddings of size 64, with a context window defined by the block size. The architecture consists of 4 Transformer layers, each with 4 self-attention heads and a feed-forward network, connected through residual links and layer normalization. A dropout rate of 0.5 is applied. The final linear layer projects hidden states to the vocabulary space, and the model is trained with cross-entropy loss. During inference, the model generates graph sequences autoregressively by sampling from the predicted token distribution.

The AdamW optimizer is used for minibatch training, and each minibatch contains 128 tokenized walks. Depending on the input graph, walk length may differ (usually around 30-50). The default learning rate is set as 0.001, and the maximum number of epochs is set as 10,000; early stopping is applied.

A.2 Running Time of TANGEM

Training is conducted on a Google Colab L4 accelerator. The training time for CiteSeer is around 10 to 20 minutes, and the inference time for generating one CiteSeer graph is around 2 minutes.

During the generation of small graphs $|V| <$ 1000, generation can be achieved in one long sequence. However, for larger graphs, multiple sequences can be sampled independently and then composed into a single graph. For CiteSeer ($|V| = 2120$) generation, we composed 3 independent sequences, each initialized from a randomly selected token.

A.3 Experimental Setup

We evaluated deep graph generation baselines using their official implementations and default settings: GraphRNN, GRAN, NetGAN, and DiGress. Since NetGAN relies on an older version of TensorFlow (1.x), we ran it locally, while the other models were executed in Google Colab notebooks for convenience. To provide training inputs for GraphRNN, GRAN, and DiGress, which require multiple graphs, we applied simple data augmentation (e.g., edge dropping) to generate additional graphs from the original one. For evaluation, each method generated 10 graphs, and we measured their similarity to the original graph using the MMD distance. The same evaluation procedure was applied consistently across all baselines.

A.4 Notation Table

A.5 Similarity Matrix

We utilize a pairwise similarity matrix $S \in \mathbb{R}^{|V| \times |V|}$ to integrate temporal node features, capturing their relationships and integrating this information into the walk sampling process as shown in Fig. 8. This allows the walks to reflect the more localized behavior of the nodes while maintaining exploration across the graph.

A.6 Heat Diffusion on Graphs

In order to evaluate the performance of our temporal-aware biased random walk method on synthetic and benchmark static graphs (i.e., community and Citeseer), we generated synthetic node features from the heat diffusion process. An example of generated temporal node features has shown in Fig. 9.

The graph Laplacian matrix is used in modeling the heat diffusion process throughout a graph. The fundamental equation governing heat diffusion is given by

$$\frac{d\mathbf{h}}{dt} = -L\mathbf{h} \tag{9}$$

Table 6: Notation summary.

Symbol	Description
$G = (V, E)$	Underlying graph topology with node set V and edge set E.
$X \in \mathbb{R}^{|V| \times T \times F}$	Tensor of temporal node features; T time steps, F features per node per time step.
$x_i \in \mathbb{R}^{T \times F}$	Temporal feature vector of node i.
$S \in \mathbb{R}^{|V| \times |V|}$	Pairwise temporal similarity matrix computed from node features.
$S_{ij} = f(x_i, x_j)$	Similarity between node i and node j defined by metric f.
$f(\cdot, \cdot)$	Similarity metric (e.g., cosine similarity, correlation, RBF kernel).
$\rho(u, v) = S_{uv}$	Temporal bias lookup function for nodes u and v; extended in Eq. (7) to include second-hop neighbors.
A	Adjacency matrix of the graph.
$L = D - A$	Unnormalized Laplacian matrix; D is diagonal degree matrix.
p	Return parameter of Node2Vec-style second-order random walk.
q	In–out (exploration) parameter of Node2Vec-style second-order random walk.
δ_{kv}	Shortest-path distance between nodes k and v (0, 1, or 2 for direct neighbors).
$\alpha_{pq}(k, v)$	Search bias (Node2Vec) for moving from node u to v after visiting k.
$\alpha_q(k, v, u)$	Modified search bias with temporal bias $\rho(u, v)$ (Eq. 5).
$s = \{v_1, \ldots, v_M\}$	A node sequence (walk) of length M.
$\mathbf{k}$	Number of sequences to sample during generation
$P(s)$	Joint probability of generating sequence s (Eq. 8).
M	Sequence length / maximum number of tokens to generate.
$N(v)$	Set of neighbors of node v.
λ	Hyperparameter controlling influence of second-hop neighbors in $\rho(u, v)$.

Figure 8: Similarity Matrix (S): similarity matrix using temporal node features across graph snapshots. Each entry reflects the similarity between nodes based on their temporal feature evolution over time.

where h is a vector representing the heat value at each node, and t represents the time. The unnormalized Laplacian matrix L is defined as

$$L = D - A \tag{10}$$

where A is the adjacency matrix of the graph and D is diagonal degree matrix defined as

$$D_{ii} = \sum_j A_{ij} \tag{11}$$

The solution of Eq. 9 is given by

$$\mathbf{h}(t) = e^{-tL}\mathbf{h}(0) \tag{12}$$

where e^{-tL} is knows as the heat kernel, and the h_0 is the vector of initial heat values associated with nodes.

| (a) t_1 | (b) t_2 | (c) t_3 | (d) t_4 |

Figure 9: Example of heat diffusion on graphs: Red color represents high temperature at nodes.

A.7 More Visual Examples by TANGEM

We provide additional visual examples generated by TANGEM, showcasing its ability to capture complex patterns and temporal dynamics in graph structures, as seen in Table 7

A.8 Assessing Different Walk Sampling Strategies

We compare four walkers: uniform Random Walk (RW), temporal-aware Random Walk (RW+), Biased Random Walk (BRW, Node2Vec-style with $q = 0.01$), and Temporal-Aware Biased Random Walk (BRW+, combining BRW and temporal similarity), and values are given in Table 8. Lower values indicate better alignment to the target graph for each structural signature (Degree, Clustering, Spectral, Orbit, Motif). Bold marks the best per column. All walkers share identical decoder, walk lengths, and stitching procedures; only the transition kernel changes (uniform vs. biased vs. temporal-weighted). We report means over fixed seeds; code, seeds, and per-run logs are provided in the Supplement. The following points provide additional observations and takeaways that complement the main text.

- Exploration helps almost universally. Comparing BRW to RW improves 19/20 cells across datasets (the only exception is Clustering on CiteSeer). A low q discourages backtracking and covers the graph more evenly, improving degree/spectral/orbit/motif statistics that rely on broader coverage.

- Temporal awareness is beneficial but dataset-dependent. Relative to BRW, BRW+ wins 9/20 cells:
  - **IBB1 (community structure):** BRW+ improves 4/5 metrics; temporal similarity reinforces homophily, aiding Clustering, Orbit, and Motif. A slight drop on Spectral suggests over-emphasis on tightly similar regions can shift global eigenvalue mass.
  - **IBB2 (grid-like regularity):** BRW outperforms BRW+ on all metrics; a regular lattice has weak assortative signal, so temporal bias misaligns with the underlying regular structure, hurting degree/clustering/spectral fidelity.
  - **Pems04 (traffic sensors):** BRW+ excels on Spectral, Orbit, and Motif, while BRW keeps a tiny edge on Degree. Here temporal co-activation is meaningful, so injecting similarity improves higher-order patterns.

Table 7: Original graph names are shown on the left. Each row has the original graph and four generated graphs by TANGEM.

- **CiteSeer (citation network):** BRW+ improves Orbit and Motif (role/motif statistics), but BRW remains better on Degree and Spectral, and uniform RW best preserves Clustering. Exploration can reduce triangle closure locally, explaining the clustering dip.

- Adopting an explorative bias(low q) as the default is sensible, as it consistently improves structural fidelity.

- Applying temporal bias is beneficial when temporal signals align with structural homophily or co-activation (e.g., traffic or community graphs), but it should be reduced or avoided on highly regular or weakly assortative graphs (e.g., grids).

- Different signatures react differently. Clustering looks at how many triangles (three nodes all connected) are formed locally. This favors simple random walks that stay close to the starting point, because they are more likely to see and preserve those local triangles. Orbit, Motif, and Spectral metrics look at larger patterns and the graph's overall shape. These benefit from walks that explore more widely (biased walks with low q) and, when it makes sense, use temporal information to steer the walk toward nodes that behave similarly over time.

A.9 Evaluating Downstream Node Sampling on Generated Topologies

Additionally, we used generated Pems04 graphs from TANGEM and GRAN (the one of the strongest baseline), and mapped the traffic features from the original dataset. Then, we trained an attention-based spatial-

Table 8: Comparison of random walk (RW), temporal aware random walk (RW+), biased random walk (BRW), and temporal aware biased random walk (BRW+).

	IBB1					**IBB2**				
	Degree	Clustering	Spectral	Orbit	Motif	Degree	Clustering	Spectral	Orbit	Motif
Random Walk (RW)	0.0115	0.0030	0.1201	0.0104	0.1518	0.0661	0.0028	0.0685	0.0592	0.9392
T-A Random Walk (RW+)	0.0045	0.0064	0.1142	0.0005	0.1071	0.0961	0.0003	0.0809	0.0481	0.9003
Biased Random Walk (BRW)	0.0062	0.0006	**0.0530**	0.0006	0.0391	**0.0347**	**0.0001**	**0.0428**	**0.0351**	**0.5875**
T-A Biased Random Walk (BRW+)	**0.0038**	**0.0004**	0.0548	**0.0001**	**0.0155**	0.0449	0.0007	0.0464	0.0397	0.7055

	Pems04					**CiteSeer**				
	Degree	Clustering	Spectral	Orbit	Motif	Degree	Clustering	Spectral	Orbit	Motif
Random Walk (RW)	0.0402	0.3515	0.1411	0.0653	0.7994	0.0008	**0.1515**	0.0085	1.6221	1.6534
T-A Random Walk (RW+)	0.0256	**0.1875**	0.1375	0.0025	0.0774	**0.0005**	0.1909	0.0076	0.5686	0.0819
Biased Random Walk (BRW)	**0.0008**	0.2517	0.0697	0.0012	0.0145	0.0015	0.5612	**0.0048**	0.4595	0.0426
T-A Biased Random Walk (BRW+)	0.0012	0.2694	**0.0637**	**0.0004**	**0.0048**	0.0024	0.6963	0.0079	**0.0799**	**0.0112**

(a) Traffic forecasting on TANGEM-generated graph. Predicted vs. ground truth.

(b) Traffic forecasting on GRAN-generated graph. Predicted vs. ground truth.

temporal graph convolutional network Guo et al. (2019) to learn the traffic patterns and predict 5 days of traffic data. The results for TANGEM and GRAN are visualized in Fig. 10a and Fig. 10b. This ablation study aims to test whether a generated topology supports realistic temporal behavior when real signals are placed on it. We took graphs generated by TANGEM and by GRAN; then, we mapped the original PEMS04 traffic signals onto each generated graph; then, we trained the same Attention-Based Spatial-Temporal GCN Guo et al. (2019) to forecast 5 days of traffic. PEMS is a fixed-topology domain, directly take from real road network. If the generated structure reflects real temporal co-activation (who tends to rise/fall together), a standard predictor should forecast more accurately on that structure. Here, in 10a, forecasts on TANGEM graphs track the ground truth more closely than forecasts on GRAN graphs, as seen in Fig. 10b. Because the predictor and signals are held constant across methods, the performance gap is attributable to the generated topology, i.e., the structure TANGEM produces provides a better substrate for temporal propagation and aggregation. This experiment shows that such signal-guided structure is not just cosmetically closer in static metrics; it also improves downstream temporal