Latent Hierarchical Causal Structure Discovery with Rank Constraints

Abstract

Most causal discovery procedures assume that there are no latent confounders in the system, which is often violated in real-world problems. In this paper, we consider a challenging scenario for causal structure identification, where some variables are latent and they form a hierarchical graph structure to generate the measured variables; the children of latent variables may still be latent and only leaf nodes are measured, and moreover, there can be multiple paths between every pair of variables (i.e., it is beyond tree structure). We propose an estimation procedure that can efficiently locate latent variables, determine their cardinalities, and identify the latent hierarchical structure, by leveraging rank deficiency constraints over the measured variables. We show that the proposed algorithm can find the correct Markov equivalence class of the whole graph asymptotically under proper restrictions on the graph structure.

1 Introduction

In many cases, the common assumption in causal discovery algorithms–no latent confounders–may not hold. For example, in complex systems, it is usually hard to enumerate and measure all task-related variables, so there may exist latent variables that influence multiple measured variables, the ignorance of which may introduce spurious correlations among measured variables. Much effort has been made to handle the confounding problem in causal structure learning. One research line considers the causal structure over measured variables, including FCI and its variants [Spirtes et al., 2000, Pearl, 2000, Colombo et al., 2012, Akbari et al., 2021], matrix decomposition-based approaches [Chandrasekaran et al., 2011, 2012, Frot et al., 2019], and over-complete ICA-based ones [Hoyer et al., 2008, Salehkaleybar et al., 2020].

Another line focuses on identifying the causal structure among latent variables, including Tetrad condition-based approaches [Silva et al., 2006, Kummerfeld and Ramsey, 2016], high-order moments-based ones [Shimizu et al., 2009, Xie et al., 2020, Adams et al., 2021], copula model-based approach [Cui et al., 2018], and mixture oracles-based approach [Kivva et al., 2021]. Moreover, regarding the scenario of latent hierarchical structures, previous work along this line assumes a tree structure [Pearl, 1988, Zhang, 2004, Choi et al., 2011, Drton et al., 2017], where there is one and only one undirected path between every pair of variables. This assumption is rather restrictive and the structure in real-world problems could be more complex–beyond a tree.

In this paper, we consider a more challenging scenario where latent causal variables form a hierarchical graph structure to generate measured variables—the children of latent variables may still be latent and only the leaf nodes are measured, and moreover, there can be multiple paths between every pair of variables (see the example hierarchical graphs in Figure 1). We aim to find out identifiability conditions of the hierarchical structure that are as mild as possible, and meanwhile, develop an efficient algorithm with theoretical guarantees to answer the following questions. (1) How can we locate latent parents for both measured and latent variables, as well as determining the cardinality of

Pa:	Parents
PCh:	Pure children
PDe:	Pure descendants
Gp:	Grandparents
Sib:	Siblings
$\mathcal{M}$:	Measured pure descendants

Table 1: Graphical notations.

Figure 1: Example hierarchical graphs that our method can handle, where X_i are measured variables and L_i are latent variables.

the latent parents, by only providing the leaf nodes? (2) How can we identify the causal relationships among latent variables and that from latent variables to measured variables?

Interestingly, we can answer these questions by properly making use of rank deficiency constraints; finding and leveraging rank properties in specific ways enable us to identify the Markov equivalence class of the whole graph, under appropriate conditions. Our contribution is mainly two-fold:

- We propose a structure identification algorithm that can efficiently locate latent variables (including their cardinalities) and identify the latent hierarchical structure, by leveraging the rank deficiency.
- We show that the proposed algorithm can find the correct graph asymptotically under mild restrictions of the graph structure. Roughly speaking, we show that it is sufficient to have $k + 1$ pure children (which can be latent), as well as another $k + 1$ neighbors, to identify the latent variable set with size k (see the detailed conditions in Definition 4 and Condition 1).

It is worth mentioning that rank constraints have been used in previous methods [Silva et al., 2006, Kummerfeld and Ramsey, 2016], but they assume that each latent variable has three measured ones as children and each measured variable has only one latent parent. There are also other methods for latent structure learning; for instance, Anandkumar et al. [2013], which uses matrix decomposition, needs $3k$ measured children, and the GIN-based method [Xie et al., 2020], which makes use of high-order statistics, needs $2k$ measured children. However, all those developments require that every latent variable should have measured variables as children.

The paper is organized as follows. In Section 2, we give formal definitions of the latent hierarchical causal model under investigation and give conditions that are essential to the identifiability of the graph structure. In Section 3, we propose an efficient algorithm that makes use of rank-deficiency constraints to identify the latent hierarchical structure. Moreover, we show theoretically in Section 4 that the proposed algorithm outputs the correct Markov equivalence class of the whole graph asymptotically. In Section 5, we empirically validate the proposed approach on synthetic data. A complete version of experimental settings and results, as well as more details on the related work, identifiability conditions, algorithms, and theoretical results, are given in Appendix. Notations for graphical representations that are used in the paper are provided in Table 1.

2 Latent Hierarchical Causal Model

In this paper, we focus on latent hierarchical causal model with graph structure $\mathcal{G}$, where both measured variables $\mathbf{X}_\mathcal{G} = \{X_1, \cdots, X_m\}$ and latent variables $\mathbf{L}_\mathcal{G} = \{L_1, \cdots, L_n\}$ are generated by their latent parents in a directed acyclic graph (DAG) with linear relationships:

$$X_i = \sum_{L_j \in Pa(X_i)} b_{ij} L_j + \varepsilon_{X_i}, L_j = \sum_{L_k \in Pa(L_j)} c_{jk} L_k + \varepsilon_{L_j}, \tag{1}$$

where b_{ij} and c_{jk} are the causal strength from L_j to X_i and from L_k to L_j, respectively, and ε_{X_i} and ε_{L_j} are noise terms that are independent of each other. Without loss of generality, we assume that all variables $\mathbf{X}_\mathcal{G}$ and $\mathbf{L}_\mathcal{G}$ have zero mean.

Below, we first give the general definition of a linear latent hierarchical graphical model in Definition 1. Then we give more detailed conditions on the graph structure (Definitions 2-4) that are essential to formalize the identifiability condition of the latent hierarchical structure.

Definition 1 (Linear Latent Hierarchical (L^2H) Model). *A graphical model, with its graph $\mathcal{G} = (\mathbf{V}_\mathcal{G}, \mathbf{E}_\mathcal{G})$, is a linear latent hierarchical model if:*

1. *$\mathbf{V}_\mathcal{G} = \mathbf{X}_\mathcal{G} \bigcup \mathbf{L}_\mathcal{G}$, where $\mathbf{X}_\mathcal{G}$ is the set of measured variables and $\mathbf{L}_\mathcal{G}$ is the set of latent variables,*
2. *there is at least one undirected path between every pair of variables, and*
3. *each variable in $\mathbf{X}_\mathcal{G}$ and $\mathbf{L}_\mathcal{G}$ are generated by the structural equation models in Eq. 1.*

Generally, without further constraints, the causal structure of the L^{2}H model is hard to be identified. It has been shown that if the underlying graph structure satisfies a tree [Pearl, 1988], then the structure is identifiable. However, this structural constraint may be too strong to hold in many real-world problems. In this paper, we give sufficient conditions that are much milder than previous ones, as well as an efficient search algorithm, for the identifiability of the causal structure.

We now give the corresponding definitions, including *pure children*, *pure descendants*, and *effective cardinality*, that will be used in the identifiability condition, together with illustrative examples.

Definition 2 (Pure Children). *Variables* $\mathbf{V}$ *are pure children of a set of latent variables* $\mathbf{L}$ *in a graph* $\mathcal{G}$, *if* $Pa_{\mathcal{G}}(\mathbf{V}) = \mathbf{L}$ *and* $\mathbf{V} \cap \mathbf{L} = \emptyset$. *That is,* $\mathbf{V}$ *have no other parents than* $\mathbf{L}$. *We denote the pure children of* $\mathbf{L}$ *by* $PCh_{\mathcal{G}}(\mathbf{L})$.

Accordingly, *Pure Descendants* of a set of latent variables $\mathbf{L}$ are defined as all recursive pure children of $\mathbf{L}$ (including $PCh_{\mathcal{G}}(\mathbf{L}), PCh_{\mathcal{G}}(PCh_{\mathcal{G}}(\mathbf{L}))$, etc.), denoted by $PDe_{\mathcal{G}}(\mathbf{L})$. Furthermore, measured variables that are pure descendent of $\mathbf{L}$ are called *Measured Pure Descendants*, denoted by $\mathcal{M}_{\mathcal{G}}(\mathbf{L})$.

Example 1. *In Figure 1(a), the pure children of* $\{L_2, L_3\}$ *are* $\{L_6, \cdots, L_{10}\}$, *its pure descendants are* $\{L_6, \cdots, L_{10}, X_1, \cdots, X_{11}\}$, *and its measured pure descendants are* $\{X_1, \cdots, X_{11}\}$.

Definition 3 (Effective Cardinality). *For a set of latent variables* $\mathbf{L}$, *denote by* $\mathbf{C}$ *the largest subset of* $PCh_{\mathcal{G}}(\mathbf{L})$ *such that there is no subset* $\mathbf{C}' \subseteq \mathbf{C}$ *satisfying* $|\mathbf{C}'| > |Pa_{\mathcal{G}}(\mathbf{C}')|$ *and* $|Pa_{\mathcal{G}}(\mathbf{C}')| < |\mathbf{L}|$. *Then, the effective cardinality of* $\mathbf{L}$*'s pure children is* $|\mathbf{C}|$.

In the case when $\mathbf{L}$ and its pure children are fully connected, the effective cardinality is just the cardinality of the pure children of $\mathbf{L}$. However, for Figure 1(a), the effective cardinality of the pure children of $\{L_7, L_8\}$ is 3, because here the largest subset that satisfies the condition is $\{X_5, X_6, X_7\}$.

We further define *latent atomic cover* that constraints the number of pure children and the number of neighbour set of latent variables, which are essential for the structural identifiability.

Definition 4 (Latent Atomic Cover). *Let* $\mathbf{L} = \{L_1, ..., L_k\}$ *be a set of latent variables in graph* $\mathcal{G}$, *with* $|\mathbf{L}| = k$. *We say that* $\mathbf{L}$ *is a latent atomic cover if the following conditions are met:*

1. there exists a subset of pure children $\mathbf{C}' \subseteq PCh_{\mathcal{G}}(\mathbf{L})$ *with effective cardinality* $\geq k + 1$;

2. there exists a neighbour set $\mathbf{B}$ *to* $\mathbf{L}$ *s.t.* $\mathbf{B} \bigcap \mathbf{C}' = \emptyset$ *and* $|\mathbf{B}| = k + 1$;

3. there does not exist a partition of $\mathbf{L} = \mathbf{L}_1 \cup \mathbf{L}_2$, *so that both* $\mathbf{L}_1, \mathbf{L}_2$ *satisfy conditions 1 and 2 and* $\{PCh_{\mathcal{G}}(\mathbf{L}_1) \cup PCh_{\mathcal{G}}(\mathbf{L}_2)\} \backslash \mathbf{L} = PCh_{\mathcal{G}}(\mathbf{L})$.

Example 2. *In Figure 1(a),* $\mathbf{L} = \{L_2, L_3\}$ *is a latent atomic cover with* $k = 2$, *because (1) there exists a subset of pure children* $\mathbf{C}' = \{L_6, L_7, L_8\}$ *with effective cardinality* $3 = k + 1$, *(2) there exists a neighbor set* $\mathbf{B} = \{L_1, L_9, L_{10}\}$, *s.t.* $\mathbf{B} \cap \mathbf{C}' = \emptyset$ *and* $|\mathbf{B}| = 3 = k + 1$, *and (3) neither* $\{L_2\}$ *or* $\{L_3\}$ *satisfies the above two conditions.*

We now give the conditions for structural identifiability from measured variables $\mathbf{X}_{\mathcal{G}}$ alone, including those on the structural constraints (Condition 1) and rank faithfulness assumption (Condition 2).

Condition 1 (Irreducible Linear Latent Hierarchical (IL^{2}H) Graph). *An L^{2}H graph* $\mathcal{G}$ *is an IL^{2}H graph if*

1. every latent variable $L \in \mathbf{L}$ *in* $\mathcal{G}$ *belongs to at least one latent atomic cover,*

2. for any pair of latent atomic covers $(\mathbf{L}_A, \mathbf{L}_B)$, *if* $PDe_{\mathcal{G}}(\mathbf{L}_A) \bigcap PDe_{\mathcal{G}}(\mathbf{L}_B) \neq \emptyset$, *then either (a)* $\mathbf{L}_A \subset \mathbf{L}_B$ *or (b)* $\mathbf{L}_A \subset PDe_{\mathcal{G}}(\mathbf{L}_B)$ *or (c)* $\mathbf{L}_B \subset \mathbf{L}_A$ *or (d)* $\mathbf{L}_B \subset PDe_{\mathcal{G}}(\mathbf{L}_A)$, *and*

3. for any three latent atomic covers $\mathbf{L}_A, \mathbf{L}_B, \mathbf{L}_C$, *if the causal structure satisfies* $\mathbf{L}_A \rightarrow \mathbf{L}_B \rightarrow \mathbf{L}_C$ *or* $\mathbf{L}_A \leftarrow \mathbf{L}_B \rightarrow \mathbf{L}_C$, *and* $|\mathbf{L}_B| = k$, *then* $\mathbf{L}_B$ *has* $2k$ *neighbors, except for* $\mathbf{L}_A, \mathbf{L}_C$ *and the parents in the v structure where* $\mathbf{L}_B$ *is a collider.*

Next, we give the faithfulness assumption, which holds for generic covariance matrices consistent with $\mathcal{G}$ [Spirtes, 2013].

Condition 2 (Rank Faithfulness). *A probability distribution P is rank faithful to a DAG* $\mathcal{G}$ *if every rank constraint on a sub-covariance matrix that holds in P is entailed by every linear structural model with respect to* $\mathcal{G}$.

We will show in section 4 that if the underlying latent hierarchical graph satisfies an IL^{2}H graph and the rank faithfulness holds, then the location and cardinality of latent variables, and the causal structure among latent atomic covers and that from latent atomic covers to measured variables, are identifiable with appropriate search procedures. Below, let us first present the identification procedure.

3 Structure Identification with Rank-Deficiency Constraints

We propose an identification algorithm (Algorithm 1) to identify the structure of IL^{2}H graphs, by leveraging rank-deficiency constraints of measured variables. In particular, the algorithm includes three phases: finding causal clusters and assigning latent atomic covers in a greedy manner ("*findCausalClusters*"), refining incorrect clusters and covers due to the greedy search ("*refineClusters*"), and refining edges and finding v structures ("*refineEdges*").

Algorithm 1: Latent Hierarchical Causal Structure Discovery

Input : Date from a set of measured variables $\mathbf{X}_\mathcal{G}$
Output: Markov equivalence class $\mathcal{G}'$

1 $\mathcal{G}' = $ findCausalClusters $(\mathbf{X}_\mathcal{G})$;   // find clusters and assign latent covers greedily
2 $\mathcal{G}' = $ refineClusters $(\mathcal{G}')$;   // refine incorrect clusters and covers from greedy search
3 $\mathcal{G}' = $ refineEdges $(\mathcal{G}')$;   // refine some edges and find v structures

---

Before describing the identification algorithm, we first give a theorem that relates the graphical structure of an IL^{2}H graph to the rank constraints over the covariance matrix of measured variables.

Theorem 1 (Graphical Implication of Rank Constraints in IL^{2}H Graphs). *Suppose $\mathcal{G}$ satisfies an IL^{2}H graph. Under the rank faithfulness assumption, the cross-covariance matrix $\Sigma_{\mathbf{X}_A,\mathbf{X}_B}$ over measured variables $\mathbf{X}_A$ and $\mathbf{X}_B$ in $\mathcal{G}$ (with $|\mathbf{X}_A|, |\mathbf{X}_B| > r$) has rank r, if and only if there exists a subset of latent variables $\mathbf{L}$ with $|\mathbf{L}| = r$ such that $\mathbf{L}$ d-separates $\mathbf{X}_A$ from $\mathbf{X}_B$, and there is no $\mathbf{L}'$ with $|\mathbf{L}'| < |\mathbf{L}|$ that d-separates $\mathbf{X}_A$ from $\mathbf{X}_B$. That is,*

$$rank(\Sigma_{\mathbf{X}_A,\mathbf{X}_B}) = min\{|\mathbf{L}| : \mathbf{L} \text{ d-separates } \mathbf{X}_A \text{ from } \mathbf{X}_B\}.$$

For instance, in Figure 1(a), $rank(\Sigma_{\{X_1,X_2\},\{X_3,X_4\}}) = 1$, because L_6 d-separates $\{X_1, X_2\}$ from $\{X_3, X_4\}$ with $|L_6| = 1$. We further show that for any subset of latent variables in an IL^{2}H graph, we can use the measured variables as surrogates to estimate the rank, as indicated in the following theorem.

Theorem 2 (Measurement as a surrogate). *Suppose $\mathcal{G}$ is an IL^{2}H graph. Denote by $\mathbf{A}, \mathbf{B} \subseteq \mathbf{V}_\mathcal{G}$ two subsets of variables in $\mathcal{G}$, with $\mathbf{A} \cap \mathbf{B} = \emptyset$. Furthermore, denote by $\mathbf{X}_A$ the set of measured variables that are d-separated by $\mathbf{A}$ from all other measures, and by $\mathbf{X}_B$ the set of measured variables that are d-separated by $\mathbf{B}$ from all other measures. Then $\mathtt{rank}(\Sigma_{\mathbf{A},\mathbf{B}}) = \mathtt{rank}(\Sigma_{\mathbf{X}_A,\mathbf{X}_B})$.*

A special case when Theorem 2 holds is that $\mathbf{X}_A$ and $\mathbf{X}_B$ are the measured pure descendants of $\mathbf{A}$ and $\mathbf{B}$, respectively. Note that Theorem 1 is a special case of Theorem 2.8 in Sullivant et al. [2010] when applied to IL^{2}H graphs. Different from the setting in Sullivant et al. [2010] where access to the full covariance matrix $\Sigma_{\mathbf{V}_\mathcal{G},\mathbf{V}_\mathcal{G}}$ is assumed, we only have access to the covariance matrix $\Sigma_{\mathbf{X}_\mathcal{G},\mathbf{X}_\mathcal{G}}$ over the measured variables $\mathbf{X}_\mathcal{G}$, which we will use to infer the causal structure over the entire graph $\mathcal{G}$. For this reason, although we can infer the number of latent variables that d-separate any two sets of measured variables $\mathbf{X}_A, \mathbf{X}_B$, we cannot directly know the exact location of these variables in the graph. Fortunately, the structure constraints of the IL^{2}H graph and Theorem 2 will allow us to reconstruct the graph with certain search procedures, as shown below.

3.1 Phase I: Finding Causal Clusters

We start to discover clusters in a recursive and greedy manner, by performing rank-deficiency tests over measured variables. We denote by $\mathcal{S}$ a set of active variables that is under investigation; $\mathcal{S}$ is set to $\mathbf{X}_\mathcal{G}$ initially and will be updated to include latent atomic covers when rank deficiency is discovered. Below, we first give the definition about set size and the definition of *atomic rank-deficiency set*, which will be used in Rule 1 and Algorithm 2.

Definition 5 (Set Size). *Suppose $\mathcal{S}$ is a set. We denote by $|\mathcal{S}|$ the cardinality of $\mathcal{S}$; that is, $|\mathcal{S}|$ is the number of elements S_i in $\mathcal{S}$, for $S_i \in \mathcal{S}$. We denote by $\|\mathcal{S}\|$ the number of variables in $\mathcal{S}$, where $\|\mathcal{S}\| = |\bigcup_i S_i|$, for $S_i \in \mathcal{S}$.*

For example, suppose $\mathcal{S} = \{\{L_1\}, \{L_6\}, \{L_7, L_8\}, \{L_9, L_{10}\}\}$. Then $|\mathcal{S}| = 4$ and $\|\mathcal{S}\| = 6$.

Definition 6 (Atomic Rank-Deficiency Set). *Given a graph $\mathcal{G}'$. Denote by $\mathcal{S} \subseteq V_{\mathcal{G}'}$ an active set of variables that is under investigation. Let $\mathbf{A} \subset \mathcal{S}$ and $\mathbf{B} = \mathcal{S} \backslash \mathbf{A}$. Denote by $\mathbf{X}_A = \mathcal{M}_{\mathcal{G}'}(\mathbf{A})$ and $\mathbf{X}_B = \mathcal{M}_{\mathcal{G}'}(\mathbf{B})$ the measured pure descendants of $\mathbf{A}$ and $\mathbf{B}$, respectively. If (1) $\Sigma_{\mathbf{A},\mathbf{B}}$ is rank deficient, i.e., $\mathtt{rank}(\Sigma_{\mathbf{A},\mathbf{B}}) < min\{\|\mathbf{A}\|, \|\mathbf{B}\|\}$), and (2) no proper subset of $\mathbf{A}$ is rank deficient, then $\mathbf{A}$ is called an atomic rank-deficient set, and $\Sigma_{\mathbf{A},\mathbf{B}}$ can be estimated by $\Sigma_{\mathbf{X}_A,\mathbf{X}_B}$.*

For example, in Figure 1(a), suppose now we have the measured variables $\mathbf{X}_{\mathcal{G}}$ under investigation, so the active variable set $\mathcal{S} = \mathbf{X}_{\mathcal{G}}$. $\mathbf{A} = \{X_1, X_2\} \subset \mathcal{S}$ forms an atomic rank-deficiency set because the cross-covariance matrix of $\mathbf{X}_A$ against all other measures has rank 1 (i.e., rank deficient). According to Theorem 1, the rank deficiency occurs because the latent parent L_6 of $\{X_1, X_2\}$ d-separates them from all other measures. This naturally leads to the following rule that assigns a latent atomic cover over the rank-deficiency set:

Rule 1: If $\mathbf{A}$ is a rank-deficiency set with $\text{rank}(\Sigma_{\mathbf{X}_A, \mathbf{X}_B}) = k$, then assign a latent atomic cover $\mathbf{L}$ of size k as the parent of every variable $A_i \in \mathbf{A}$.

Later in Phase II, we will show that Rule 1 may not correctly identify the latent atomic cover in some cases, and, accordingly, we will further provide an efficient revision procedure in Phase II. At the current phase, we use Rule 1, together with certain search procedures, to identify the clusters and latent atomic covers. The detailed search procedure of Phase I is given in Algorithm 2 (*findCausalClusters*), which tests for rank deficiency recursively to discover clusters of variables and their latent atomic clusters. The set of active variables $\mathcal{S}$ is set to $\mathbf{X}_{\mathcal{G}}$ initially (line 1) and will be updated as the search goes on (line 13). We start to identify the latent atomic cover with size $k = 1$ (line 1). We consider any subset of the latent atomic covers in $\mathcal{S}$ and replace them with their pure children, resulting in $\tilde{\mathcal{S}}$ (line 4). Then we draw a subset of variables $\mathbf{A} \subset \tilde{\mathcal{S}}$ with cardinality at least $k + 1$ and conduct a rank deficiency test of $\mathbf{A}$ against $\mathcal{S} \backslash \mathbf{A}$ by estimating the rank of $\text{rank}(\Sigma_{\mathbf{X}_A, \mathbf{X}_B})$ (lines 6-7). Note that here $\mathbf{X}_A$ and $\mathbf{X}_B$ are the measured pure descendants of $\mathbf{A}$ and $\mathbf{B}$, respectively, in the currently learned graph. This step is repeated until all subsets are tested (lines 5-9). If rank deficiency is found, we merge the overlapping groups into a cluster and add latent covers over the cluster (lines 10-13). We further reset $k = 1$ and resume the search (line 14). Otherwise, if no latent cover is found, we increment $k = k + 1$ (line 16). This procedure is repeated until no more clusters are found. Finally, we connect the elements in $\mathcal{S}$ into a chain structure (line 18). Figure 2 illustrates an example procedure of finding new clusters by applying *findCausalClusters* to the measured variables $\mathbf{X}_{\mathcal{G}}$ generated from the structure in Figure 1(a).

Algorithm 2: Phase I: findCausalClusters

Input : Data from a set of measured variables $\mathbf{X}_{\mathcal{G}}$
Output : Graph $\mathcal{G}'$

1 Active set $\mathcal{S} \leftarrow \mathbf{X}_{\mathcal{G}}$; $k \leftarrow 1$;
2 **repeat**
3   **repeat**
4   draw a set of latent atomic covers $\tilde{\mathbf{L}} \subset \mathcal{S}$;   let $\tilde{\mathcal{S}} = (\mathcal{S} \backslash \tilde{\mathbf{L}}) \cup (\cup_{L_i \in \tilde{\mathbf{L}}} PCh(L_i))$;
5   **repeat**
6   draw a set of test variables $\mathbf{A} \subset \tilde{\mathcal{S}}$, with $\|\mathbf{A}\| \geq k + 1$, and let $\mathbf{B} \leftarrow \tilde{\mathcal{S}} \backslash \mathbf{A}$;
7          $k' \leftarrow \text{rank}(\Sigma_{\mathbf{X}_A, \mathbf{X}_B})$ estimated by rank deficiency test;
8   **if** $k' < k + 1$ **then** rank deficiency found and keep track of this set $\mathbf{A}$;
9   **until** *all subsets $\mathbf{A}$ exhausted*;
10   **if** *any groups with rank deficiency are found* **then**
11   merge overlapping clusters & identify lowest rank k' found;
12   **foreach** *discovered cluster of variables $\mathbf{A}$ with rank k'* **do**
13   create latent cover $\mathbf{L}$ with cardinality k' as parents of $\mathbf{A}$; $\mathcal{S} = (\mathcal{S} \backslash \mathbf{A}) \cup \mathbf{L}$;
14          $k = 1$; **break**;
15   **until** *all subsets $\tilde{\mathbf{L}}$ exhausted*;
16   **if** *no group with rank deficiency is found* **then** $k = k + 1$;
17 **until** *no more clusters are found*;
18 for all $S_i \in \mathcal{S}$, connect them into a chain structure;
19 **return** $\mathcal{G}'$

Figure 2: An illustration of Algorithm 2 that discovers new clusters in sequence (marked with gray circle) by applying *findCausalClusters* to the measured variables $\mathbf{X}_{\mathcal{G}}$ generated from the structure in Figure 1(a). See more detailed explanations in Section G in Appendix.

(a) $k = 1$, $\mathcal{S} = \{X_1, \cdots, X_{16}\}$.

(b) $k = 2$, $\mathcal{S} = \{\{L_6\}, \{L_7\}, X_6, \cdots, X_{16}\}$.

(c) $k = 1$, $\mathcal{S} = \{\{L_4, L_5\}, \{L_6\}, \{L_7, L_8\}, \{L_9, L_{10}\}\}$.

(d) $k = 2$, $\mathcal{S} = \{\{L_1\}, \{L_7, L_8\}, \{L_6\}, \{L_9, L_{10}\}\}$.

(e) Connect $\{L_2, L_3\}$ and $\{L_7, L_8\}$.

3.2 Phase II: Refining Clusters

As we have mentioned above, the naive assignment of causal clusters in Algorithm 2 (*findCausalClusters*) may not be correct in some cases. In this section, we provide a precise characterization of the cases where *findCausalClusters* incorrectly clusters variables and, accordingly, propose an efficient algorithm to correct such cases.

Take Figure 3(a) as an example to illustrate the issue. By applying *findCausalClusters* to the measured variables $\mathbf{X}_{\mathcal{G}}$, at $k = 2$, we discovered that $\{X_9, X_{10}, X_{11}\}$ form a cluster and then set a 2-latent atomic cover $\{L'_1, L'_2\}$ over it (Figure 3(b)). This is not correct, because X_9, X_{10}, X_{11} actually belong to three different 1-latent atomic covers, L_1, L_2, L_3, respectively. The incorrect clustering and covering are because when discovering the rank-deficiency set $\{X_9, X_{10}, X_{11}\}$, the latent covers $\{L_4, L_5\}, \{L_6, L_7\}$ have not been identified yet. If $\{L_4, L_5\}$ had already been discovered, we would correctly find that $\{X_9, L_4, L_5\}$ form a 1-latent atomic cover, and the algorithm would proceed correctly thereafter. More generally, *findCausalClusters* may set incorrect cluster for the rank-deficiency set $\{X_9, X_{10}, X_{11}\}$, in the case when their parents L_1, L_2, L_3 split the graph into two or more disconnected graphs. This result is formally stated in the following definition and theorem.

Definition 7 (Bond Set). *Consider a set of measured variables $\mathbf{X} \subseteq \mathbf{X}_{\mathcal{G}}$, and a minimal set of latent variables $\mathbf{L} \subseteq \mathbf{L}_{\mathcal{G}}$ that d-separate $\mathbf{X}$ from all other measures $\mathbf{X}' \coloneqq \mathbf{X}_{\mathcal{G}} \backslash \mathbf{X}$. We say that $\mathbf{X}$ is a bond set if $\mathbf{L}$ also d-separates some partition $\mathbf{X}_A \subset \mathbf{X}', \mathbf{X}_B \subset \mathbf{X}'$ from one another.*

From the previous example, we have seen that with the existence of bond sets, *findCausalClusters* may end up with incorrect clusters and covers. The following theorem shows that the presence of bond sets is the only reason of incorrect clusters and covers with *findCausalClusters*.

Theorem 3 (Correct Cluster Condition). *Suppose $\mathcal{G}$ is an IL^2H graph with measured variables $\mathbf{X}_{\mathcal{G}}$. Consider the output $\mathcal{G}'$ from applying findCausalClusters over $\mathbf{X}_{\mathcal{G}}$. If none of the clusters in $\mathcal{G}'$ is the bond set in $\mathcal{G}$, then all latent atomic covers have been correctly identified.*

However, without access to the true graph $\mathcal{G}$, we are not able to identify which clusters formed from *findCausalClusters* are bond sets. Fortunately, the following properties of the clusters formed over bond sets provide a way to remove bond sets in our discovered graph even without such knowledge, so that the clusters and latent covers can be correctly identified.

Theorem 4 (Correcting Clusters). *Denote by $\mathcal{G}'$ the output from findCausalClusters and by $\mathcal{G}$ the true graph. For a latent atomic cover $\mathbf{L}'$ in $\mathcal{G}'$, if the measured pure descendants of $\mathbf{L}'$, $\mathcal{M}_{\mathcal{G}'}(\mathbf{L}')$, is a bond set in the true graph $\mathcal{G}$, then there exists a set of siblings $\mathbf{S}$ of $\mathbf{L}'$ in $\mathcal{G}'$ and a set of children $\mathbf{C}$ of $\mathbf{L}'$, such that $\mathcal{M}_{\mathcal{G}'}(\mathbf{S} \cup \mathbf{C})$ forms a cluster that is not a bond set in $\mathcal{G}$.*

The above theorem shows that whenever forming a bond set, the siblings of the latent cover are the key to correct the incorrect clusters and covers. Specifically, we will remove such a cover and use its children to form new clusters with the siblings (see details in Algorithm 3), and Theorem 4 guarantees that these new clusters will not contain bond sets, and thus, providing correct clusters.

Example 3. *In Figure 3(b), the formed cluster $\{X_9, X_{10}, X_{11}\}$ is the bond set in the true graph in Figure 3(a), and the cover $\{L'_1, L'_2\}$ is not correct. Observe that L'_7, L'_8 are siblings of $\{L'_1, L'_2\}$, and if we were to remove $\{L'_1, L'_2\}$ (and its parent $\{L'_9, L'_{10}\}$) and consider its children, we would find that L'_7 forms a size 1 cluster with X_{10}, and the cluster is over measures $\{X_5, X_6, X_7, X_8, X_{10}, X_{11}\}$ which is not a bond set.*

(a) Original Graph   (b) Output from findCausalClusters

Figure 3: An example where findCausalClusters fails.

Furthermore, with Theorem 4, we give the following rule for correcting the clusters and covers.

Rule 2: For each discovered latent atomic cover $\mathbf{L}$, let $\mathbf{V} = Gp_{\mathcal{G}'}(\mathbf{L}) \bigcup Sib_{\mathcal{G}'}(\mathbf{L}) \bigcup Ch_{\mathcal{G}'}(\mathbf{L})$ and apply *findCausalClusters* to $\mathbf{V}$ to refine the clusters.

Before introducing the detailed refining algorithm *refineClusters* based on Rule 2, we first introduce an operator *makeRoot* that will be used in the algorithm, which will not change the rank deficiency constraints.

Definition 8 (*makeRoot*). *Give a graph $\mathcal{G}'$ and a latent atomic cover $\mathbf{L}$ in $\mathcal{G}'$. A makeRoot operator of $\mathbf{L}$, denoted by makeRoot($\mathbf{L}$), reorients all outgoing edges of $\mathbf{L}$ to $\mathbf{L}$, such that $\mathbf{L}$ is a root variable.*

246 Algorithm 3 introduces the procedure of refining clusters based on Rule 2. Starting with the output
247 $\mathcal{G}'$ from *findCausalClusters*, we proceed in a breadth-first search from the root variable (lines 1-3, 5).
248 Because the root is trivially not over a bond set, Theorem 4 guarantees that for each child of the root,
249 we will form new clusters that are not over bond sets. For each cover $\mathbf{L}$, if it has only one child, we
250 will recursively consider the children of its child instead, since if $\mathbf{L}$ is over a bond set then its single
251 child will also be. We add the first set of children into the search set $\mathbf{V}$ (line 4). We construct the
252 search set (line 6) and remove the covers we are refining (lines 7-8). Finally, we make $\mathbf{L}$ the root
253 (line 8) and conduct the search (line 9). The algorithm ends after refining every latent cover in $\mathcal{G}'$.
254 With this refining procedure, we will derive the correct latent covers for the graph in Figure 3(a).

Algorithm 3: Phase II: refineClusters

Input : Output graph $\mathcal{G}'$ from Phase I
Output : Refined graph $\mathcal{G}'$

refineClusters ($\mathcal{G}'$):
1 Let Q be an empty queue; Q.enqueue($PCh_{\mathcal{G}'}(Root(\mathcal{G}'))$);
2 **repeat**
3    $\mathbf{L} \leftarrow Q$.dequeue();
4   **while** $Ch_{\mathcal{G}'}(\mathbf{L})$ *is a single atomic cover* **do** remove $Ch_{\mathcal{G}'}(\mathbf{L})$ and add $Ch_{\mathcal{G}'}(Ch_{\mathcal{G}'}(\mathbf{L}))$ as children of $\mathbf{L}$;
5   **for** *each atomic cover* $C \in Ch_{\mathcal{G}'}(\mathbf{L})$ **do** Q.enqueue($\mathbf{C}$) ;
6    $\mathbf{V} \leftarrow Gp_{\mathcal{G}'}(\mathbf{L}) \bigcup Sib_{\mathcal{G}'}(\mathbf{L}) \bigcup Ch_{\mathcal{G}'}(\mathbf{L})$;   // variables for finding new clusters
7    $\mathbf{R} \leftarrow \mathbf{L} \bigcup Pa_{\mathcal{G}}(\mathbf{L})$;   // atomic covers to be removed
8    $\mathcal{G}' \leftarrow$ makeRoot$_{\mathcal{G}'}(\mathbf{L})$; remove $\mathbf{R}$ and all adjoining edges from $\mathcal{G}'$;
9    $\mathcal{G}'' \leftarrow$ findCausalClusters($\mathbf{V}$); update $\mathcal{G}'$ with new clusters from $\mathcal{G}''$; // find new clusters
10 **until** *Q is empty*;
11 **return** $\mathcal{G}'$

3.3 Phase III: Refining Edges

256 With *findCausalClusters* and *refineClusters*, the output $\mathcal{G}'$ correctly identifies the latent variables.
257 Moreover, $\mathcal{G}'$ correctly identifies the following d-separation: for every $\mathbf{L} \in \mathbf{L}_{\mathcal{G}'}$, its parents $Pa_{\mathcal{G}'}(\mathbf{L})$
258 d-separates $\mathbf{L}$ and its descendants from the ancestors of $Pa_{\mathcal{G}'}(\mathbf{L})$, and thus, there cannot be any edges
259 from each $\mathbf{L}$ to any of its ancestors beyond its own parents. However, $\mathcal{G}'$ may still have incorrect
260 edges *locally*. Specifically, each time we create an atomic cover $\mathbf{L}$ in *findCausalClusters*, the implicit
261 assumption is that each of its children is conditionally independent of the other children given the
262 parents $\mathbf{L}$. However, this assumption is not necessarily true, as (i) the children of $\mathbf{L}$ may be directly
263 connected to one another and (ii) $\mathbf{L}$ may only be directly connected to a subset of its children. In
264 other words, previous steps did not consider condition independence relationships across clusters.
265 Hence, we need a further step to correct edges over each $\mathbf{L}$ and its children.

266 For example, consider the true graph in Figure 4(a), which ends up with the graph in Figure 4(b) with
267 the first two phases. However, note that the first two phases did not consider the d-separation between
268 L'_2 and L'_3, and thus the edges among L'_1, L'_2, L'_3, L'_4 may not be correct, including the v structure. In
269 particular, in the true graph, L_1 d-separates L_2 from L_3, while $\{L_1, L_4\}$ does not d-separate L_2 from
270 L_3, but these d-separations are not reflected in the discovered $\mathcal{G}'$ in the first two phases. Thus, we
271 need to refine the edges. To this end, we first set L'_1, L'_2, L'_3 and L'_2, L'_3, L'_4 to be fully connected, and
272 consider testing $\mathcal{A} = \{L'_2, X_1\}$ against $\mathcal{B} = \{L'_3, X_2\}$, where we partition the children of L'_1 into two
273 sets and put them in $\mathcal{A}$ and $\mathcal{B}$, respectively. By doing so, we force L'_1 in $\mathcal{G}'$ to be in the separating set.
274 Since $\text{rank}(\Sigma_{\mathcal{A},\mathcal{B}}) = 1$, it implies that no other variable is in the separating set, and therefore we can
275 conclude that L'_1 d-separates L'_2 from L'_3. This principle is captured in the following lemma.

276 **Lemma 5** (Cross-Cover Test)**.** *Given a set of variables $\mathcal{S}$, consider two latent atomic covers $\mathbf{L}_A, \mathbf{L}_B \in$*
277 *$\mathcal{S}$, and a potential separating set $\mathbf{C} = \{\mathbf{L}_{C_i}\} \subseteq \mathcal{S} \backslash \{\mathbf{L}_A, \mathbf{L}_B\}$. For each $\mathbf{L}_{C_i}$, consider $\mathbf{C}_i^A, \mathbf{C}_i^B \subseteq$*
278 *$PCh(\mathbf{L}_{C_i})$ with $\mathbf{C}_i^A, \mathbf{C}_i^B \neq \emptyset$ and $\mathbf{C}_i^A \cap \mathbf{C}_i^B = \emptyset$, and denote the cardinality $k_i^A := min(|\mathbf{L}_{C_i}|, |\mathbf{C}_i^A|)$,*
279 *$k_i^B := min(|\mathbf{L}_{C_i}|, |\mathbf{C}_i^B|)$, respectively. Then there is no edge between $\mathbf{L}_A$ and $\mathbf{L}_B$ if and only if there exists*
280 *a separating set $\mathbf{C}$ such that $\text{rank}(\Sigma_{\mathcal{A},\mathcal{B}}) < min(|\mathbf{L}_A| + \sum_i k_i^A, |\mathbf{L}_B| + \sum_i k_i^B)$, where $\mathcal{A} = \{\mathbf{L}_A, \mathbf{C}_1^A, \mathbf{C}_2^A, ...\}$*
281 *and $\mathcal{B} = \{\mathbf{L}_B, \mathbf{C}_1^B, \mathbf{C}_2^B, ...\}$. In this case, we say that $\mathbf{C}$ satisfies the cross-cover test of $\mathbf{L}_A$ against $\mathbf{L}_B$.*

282 Note that in order to find rank deficiency when performing the cross-cover test, $\mathbf{L}_{C_i}$ needs to satisfy
283 the third condition in Condition 1. Based on Lemma 5, we use the following rule to refine the edges.

284   **Rule 3:** For a pair of latent covers $(\mathbf{L}_A, \mathbf{L}_B)$, let $\mathcal{A} \leftarrow \{\mathbf{L}_A, \mathbf{C}_1^A, \mathbf{C}_2^A, ...\}$ and $\mathcal{B} \leftarrow \{\mathbf{L}_B, \mathbf{C}_1^B, \mathbf{C}_2^B, ...\}$.
285   If there exists such $\mathcal{A}, \mathcal{B}$ such that $\text{rank}_{\mathcal{G}'}(\Sigma_{\mathcal{A},\mathcal{B}})$ is rank deficient, then remove all edges
286   between $\mathbf{L}_A, \mathbf{L}_B$ in $\mathcal{G}'$.

287 Furthermore, with Rule 3, Algorithm 4a (*crossCoverTest*) in Appendix gives the procedure of refining
288 the edges over a set of latent variables, which helps to correct the causal skeleton. Furthermore, we are
289 going to identify the v structures among latent atomic covers. In the output $\mathcal{G}'$ from phase II, for any
290 $\mathbf{L}'$ with a child $\mathbf{C}'_i$ and parent $\mathbf{P}'$, it is not possible to have a collider $\mathbf{C}'_i \to \mathbf{L}' \leftarrow \mathbf{P}'$ in the ground-truth
291 graph, because in this case the cluster would not have been rank deficient. Therefore, the only v
292 structures in the graph are amongst the variables in $\mathbf{L}' \cup PCh_{\mathcal{G}'}(\mathbf{L}')$, and similar to *crossCoverTest*,
293 we only need to test for v structures locally.

294 Continue to consider the example in Figure 4. The edge between L'_2 and L'_3 is missing because the rank
295 over $\{L'_2, X_1\}$ and $\{L'_3, X_2\}$ is 1, implying that L'_1 d-separates L'_2 from L'_3, as is done in *crossCoverTest*.
296 Now, since $L'_2 - L'_4 - L'_3$ forms an unshielded triplet, we want to test if a collider exists at L'_4. We find
297 that the rank over $\mathcal{A} = \{L'_2, L'_4, X_1\}$ and $\mathcal{B} = \{L'_3, X_2\}$ is $2 > 1$, and the rank over $\mathcal{A} = \{L'_2, X_1\}$ and
298 $\mathcal{B} = \{L'_3, L'_4, X_2\}$ is $2 > 1$, so $L'_2 \to L'_4 \leftarrow L'_3$. For general cases, the rule for finding v structures are
299 formulated in the following lemma and Algorithm 4b (*findColliders*) in Appendix.

300 **Lemma 6** (V-Structure Test). *For any unshielded triangle $\mathbf{L}_A - \mathbf{L}_C - \mathbf{L}_B$, let $\mathcal{A}, \mathcal{B}$ be the set of*
301 *variables in Lemma 5 such that $\Sigma_{\mathcal{A},\mathcal{B}}$ was rank deficient. Let $k = \mathrm{rank}(\Sigma_{\mathcal{A},\mathcal{B}})$, $k_1 = \mathrm{rank}(\Sigma_{\mathcal{A}\cup\mathbf{L}_C,\mathcal{B}})$,*
302 *and $k_2 = \mathrm{rank}(\Sigma_{\mathcal{A},\mathcal{B}\cup\mathbf{L}_C})$. Then, $\mathbf{L}_A \to \mathbf{L}_B \leftarrow \mathbf{L}_C$ if and only if $k < \min(k_1, k_2)$.*

303 As mentioned above, we only need to perform cross-cover test and v-structure test locally in the
304 estimated graph $\mathcal{G}'$. Algorithm 4 (*refineEdges*) combines the search procedure of the two components
305 together with the output $\mathcal{G}'$ from *refineClusters* as the input. Specifically, for each latent cover $\mathbf{L}'$ in
306 $\mathcal{G}'$, we only need to consider testing for edges amongst $\mathbf{L}'$ and its children $\mathbf{C} = Ch_{\mathcal{G}'}(\mathbf{L}')$. Thus, we
307 perform a depth-first traversal of the output graph $\mathcal{G}'$ starting from $Root(\mathcal{G}')$ (lines 1-3), and apply the
308 cross-cover test at each $\mathbf{L}$ to refine the skeleton of $\mathcal{G}'$ (lines 4-7, 11) and the collider test to identify the
309 v structures (lines 10, 11). After determining v-structures, we can find more directions by applying
310 Meek's rule (line 12), analogous to that in the PC algorithm [Spirtes et al., 2000].

Algorithm 4: Phase III: refineEdges

Input : Learned graph $\mathcal{G}'$ from phase II
Output : Markov equivalence class $\mathcal{G}'$
refineEdges ($\mathcal{G}'$):
1 **foreach** *latent atomic cover* $\mathbf{L}'$ *in* $\mathcal{G}'$ **do**
2   **if** $\mathbf{L}'$ *does not have latent children* **then return** $\mathcal{G}'$;
3   **foreach** *latent child* $\mathbf{C}_i$ *of* $\mathbf{L}'$ **do** $\mathcal{G}' \leftarrow$ refineEdges($\mathcal{G}', \mathbf{C}_i$) ;
4   **if** $\mathbf{C} := PCh_{\mathcal{G}'}(\mathbf{L}')$ *is a single latent cover* **then** $\mathcal{S} \leftarrow \mathbf{L}' \cup \mathbf{C} \cup PCh_{\mathcal{G}'}(\mathbf{C})$;
5   **else** $\mathcal{S} \leftarrow \mathbf{L}' \cup \mathbf{C}$;
6     $\mathcal{G}'' \leftarrow$ makeRoot$_{\mathcal{G}'}(\mathbf{L}')$ and remove all edges amongst $\mathcal{S}$ in $\mathcal{G}''$;   // temp graph
7   Edgeset $\mathcal{E} \leftarrow$ crossCoverTest($\mathcal{S}, \mathcal{G}''$);
8   **if** *no conditional independencies found* **then return** $\mathcal{G}'$;
9   **else**
10   Collider set $C \leftarrow$ findColliders($\mathcal{S}, \mathcal{E}, \mathcal{G}''$);
11   in $\mathcal{G}'$, remove all edges amongst $\mathcal{S}$ and use $\mathcal{E}, C$ to connect variables in $\mathcal{S}$;
12   apply Meek's rule to $\mathcal{G}'$;
13 convert $\mathcal{G}'$ to its Markov equivalence class;
14 **return** $\mathcal{G}'$

(a) an IL²H graph with v structure.   (b) Possible Output from Phase II.   (c) Output from phase III.

Figure 4: Illustrations for refineEdges.

4   Theoretical Results

312 In this section, we show the correctness of the algorithms proposed in Section 3. In particular, by
313 making use of the rank constraints of only the measured variables, the proposed algorithms output
314 the correct Markov equivalence class of the IL²H graph asymptotically, under the *minimal-graph*
315 *operator* and *skeleton operator*, with their definitions given below.

316 **Definition 9** (Minimal-Graph Operator). *Suppose $\mathcal{G}$ is an IL²H graph. For every latent atomic cover*
317 $\mathbf{L}$ *in $\mathcal{G}$, merge $\mathbf{L}$ to its parents $\mathbf{P}$ if the following conditions hold: (1) $\mathbf{L}$ is the pure children of $\mathbf{P}$, (2)*

318 |**L**| = |**P**|, *and (3) the pure children of* **L** *form one latent atomic cover, or the siblings of* **L** *form one*
319 *latent atomic cover. We call such operator the minimal-graph operator and denote it by* $O_{min}(\mathcal{G})$.

320 **Definition 10** (Skeleton Operator). *Suppose* $\mathcal{G}$ *is an* IL^2H *graph. A skeleton operator of* $\mathcal{G}$, *denoted by*
321 $O_s(\mathcal{G})$ *is defined as follows: for any latent atomic cover* **L**, *draw an edge from* $l_j \in$ **L** *to* $c_k \in PCh_{\mathcal{G}}(\mathbf{L}_i)$,
322 *if* l_j *and* c_k *are not directly connected in* $\mathcal{G}$.

323 Note that the minimal-graph operator and the skeleton operator will not change the rank. These
324 operators have ready been achieved in Algorithm 1, so the output of the algorithm is the rank-
325 equivalent graph with the minimal number of latent atomic covers. For instance, for the graph in
326 Figure 1(a), after applying the operators, the following edges will be added: $L_3 \rightarrow L_6$ and $L_3 \rightarrow L_{10}$.
327 More details and corresponding examples are given in Section B in Appendix.

328 We next proceed to show that phases I-III will output a graph $\mathcal{G}'$ such that $O_{min}(O_s(\mathcal{G}'))$ will be in the
329 same Markov equivalence class as $O_{min}(O_s(\mathcal{G}))$, denoted by $\mathcal{G}' \approx \mathcal{G}$. We have already shown earlier in
330 Theorem 3 that *findCausalClusters* gives correct latent covers when there is no bond set. Furthermore,
331 Theorem 4 shows that even in the presence of bond sets, Phase II *refineClusters* is able to refine
332 clusters into the one without bond sets. Therefore, Phase I-II can correctly identify the latent atomic
333 covers of $O_{min}(\mathcal{G})$, and with only the first two conditions in Condition 1 (see the theorem in Appendix).
334 Moreover, Phase III *refineEdges* further guarantees correct skeletons and v structures. Therefore, the
335 following theorem shows that Algorithm 1, which includes Phases I-III, can asymptotically identify
336 the Markov equivalence class, up to the skeleton operator and the minimal-graph operator.

337 **Theorem 7.** *Suppose* $\mathcal{G}$ *is an R-2H graph with measured variables* $\mathbf{X}_{\mathcal{G}}$. *Algorithm 1, including*
338 *Phases I-III, over* $\mathbf{X}_{\mathcal{G}}$ *can asymptotically identify the Markov equivalence class of* $O_{min}(O_s(\mathcal{G}))$.

5 Experimental Results

340 We applied the proposed algorithm to synthetic data to learn the latent hierarchical causal graph.
341 Specifically, we considered different types of latent graphs and different sample sizes. The causal
342 strength was generated uniformly from $[-5, -0.5] \cup [0.5, 5]$, and the noise term was randomly chosen
343 from a normal distribution with noise variance uniformly sampled from $[1, 5]$. To the best of our
344 knowledge, this is the first algorithm that can identify such general latent hierarchical structures, so to
345 fairly compare with other methods, besides general IL^2H graphs, we also considered tree structures
346 and measurement models. We compared the proposed method with tree-based method–Chow-Liu
347 Recursive Grouping (CLRG) [Choi et al., 2011], as well as measurement-model-based methods,
348 including FOFC [Kummerfeld and Ramsey, 2016] and GIN [Xie et al., 2020].

349 Table 2 gives the estimation results evaluated on three types of latent graphs: IL^2H graphs, tree
350 structures, and measurement models. The performance is measured by the percentage of correctly
351 identified causal clusters over only measured variables. Our method gives the best results on all types
352 of graphs, indicating that it can handle not only the tree-based and measurement-based structures,
353 but also the latent hierarchical structure. The CLRG algorithm does not perform well on tree-based
354 structure because the metric is rather strict–even a single misclustered variable outputs an error.
355 Complete experimental settings and more results, including performance measured by other metrics
356 and the case when the noise terms are uniformly distributed, are given in Section D in Appendix.

Table 2: Performance (mean (standard deviation)) on learning different types of latent graphs.

Sample size	IL^2H				Tree				Measurement model			
	Ours	CLRG	FOFC	GIN	Ours	CLRG	FOFC	GIN	Ours	CLRG	FOFC	GIN
2k	0.70 (0.22)	0	0.12	0.35	0.89 (0.12)	0	0.38	0.13	0.92 (0.08)	0	0.38	0.3
5k	0.83 (0.15)	0	0.17	0.40	1.0 (0.00)	0	0.75	0.23	1.0 (0.00)	0	0.65	0.7
10k	0.86 (0.13)	0	0.29	0.44	1.0 (0.00)	0.13	0.87	0.50	1.0 (0.00)	0	1.0	0.7

6 Conclusions and Future Work

358 In this paper, we formulated a specific type of latent hierarchical causal model and proposed a method
359 to identify its graph by making use of rank deficiency constraints. Theoretically, we show that the
360 proposed algorithm can find the correct Markov equivalence class of the whole graph asymptotically
361 under mild restrictions of the graph structure. For more general graphs, only using the second-order
362 statistics may result in rank equivalence class that contains multiple DAGs, so how to further leverage
363 high-order statistics to distinguish between causal graphs within the equivalence class will be our
364 future work. Other future research directions include allowing nonlinear causal relationships and
365 allowing measured variables to cause latent variables (existing techniques, e.g., Adams et al. [2021],
366 Squires et al. [2022], may help to mitigate this issue).

References

Peter Spirtes, Clark N Glymour, and Richard Scheines. *Causation, Prediction, and Search*. MIT press, 2000.

Judea Pearl. *Causality: Models, Reasoning, and Inference*. Cambridge University Press, New York, NY, USA, 2000. ISBN 0-521-77362-8.

Diego Colombo, Marloes H Maathuis, Markus Kalisch, and Thomas S Richardson. Learning high-dimensional directed acyclic graphs with latent and selection variables. *The Annals of Statistics*, pages 294–321, 2012.

Sina Akbari, Ehsan Mokhtarian, AmirEmad Ghassami, and Negar Kiyavash. Recursive causal structure learning in the presence of latent variables and selection bias. In *Advances in Neural Information Processing Systems*, volume 34, pages 10119–10130, 2021.

V. Chandrasekaran, S. Sanghavi, P. A. Parrilo, and A. S. Willsky. Rank-sparsity incoherence for matrix decomposition. *SIAM Journal on Optimization*, 21(2):572–596, 2011.

V. Chandrasekaran, P. A. Parrilo, and A. S. Willsky. Latent variable graphical model selection via convex optimization. *Annals of Statistics*, 40(4):1935–1967, 2012.

Benjamin Frot, Preetam Nandy, and Marloes H Maathuis. Robust causal structure learning with some hidden variables. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 81 (3):459–487, 2019.

Patrik O Hoyer, Shohei Shimizu, Antti J Kerminen, and Markus Palviainen. Estimation of causal effects using linear non-gaussian causal models with hidden variables. *International Journal of Approximate Reasoning*, 49(2):362–378, 2008.

Saber Salehkaleybar, AmirEmad Ghassami, Negar Kiyavash, and Kun Zhang. Learning linear non-gaussian causal models in the presence of latent variables. *Journal of Machine Learning Research*, 21(39):1–24, 2020.

Ricardo Silva, Richard Scheine, Clark Glymour, and Peter Spirtes. Learning the structure of linear latent variable models. *Journal of Machine Learning Research*, 7(Feb):191–246, 2006.

Erich Kummerfeld and Joseph Ramsey. Causal clustering for 1-factor measurement models. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1655–1664. ACM, 2016.

Shohei Shimizu, Patrik O Hoyer, and Aapo Hyvärinen. Estimation of linear non-gaussian acyclic models for latent factors. *Neurocomputing*, 72(7-9):2024–2027, 2009.

Feng Xie, Ruichu Cai, Biwei Huang, Clark Glymour, Zhifeng Hao, and Kun Zhang. Generalized independent noise condition for estimating latent variable causal graphs. In *Advances in Neural Information Processing Systems*, pages 14891–14902, 2020.

Jeffrey Adams, Niels Hansen, and Kun Zhang. Identification of partially observed linear causal models: Graphical conditions for the non-gaussian and heterogeneous cases. *Advances in Neural Information Processing Systems*, 34, 2021.

Ruifei Cui, Perry Groot, Moritz Schauer, and Tom Heskes. Learning the causal structure of copula models with latent variables. In *UAI*, pages 188–197. AUAI Press, 2018.

Bohdan Kivva, Goutham Rajendran, Pradeep Ravikumar, and Bryon Aragam. Learning latent causal graphs via mixture oracles. *Advances in Neural Information Processing Systems*, 34, 2021.

Judea Pearl. *Probabilistic Reasoning in Intelligent Systems: Networks of Plausible Inference*. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 1988. ISBN 1558604790.

Nevin L Zhang. Hierarchical latent class models for cluster analysis. *The Journal of Machine Learning Research*, 5:697–723, 2004.

Myung Jin Choi, Vincent Y.F. Tan, Animashree Anandkumar, and Alan S. Willsky. Learning latent tree graphical models. *Journal of Machine Learning Research*, 12(49):1771–1812, 2011. URL http://jmlr.org/papers/v12/choi11b.html.

Mathias Drton, Shaowei Lin, Luca Weihs, and Piotr Zwiernik. Marginal likelihood and model selection for gaussian latent tree and forest models. *Bernoulli*, 23(2):1202–1232, 2017.

Animashree Anandkumar, Daniel Hsu, Adel Javanmard, and Sham Kakade. Learning linear bayesian networks with latent variables. In *International Conference on Machine Learning*, pages 249–257, 2013.

Peter Spirtes. Calculation of entailed rank constraints in partially non-linear and cyclic models. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pages 606–615. AUAI Press, 2013.

Seth Sullivant, Kelli Talaska, and Jan Draisma. Trek separation for Gaussian graphical models. *The Annals of Statistics*, 38(3):1665 – 1685, 2010. doi: 10.1214/09-AOS760. URL https://doi.org/10.1214/09-AOS760.

C. Squires, A. Yun, E. Nichani, R. Agrawal, and C. Uhler. Causal structure discovery between clusters of nodes induced by latent factors. In *CLeaR*, 2022.