Distributed Influence-Augmented Local Simulators for Parallel MARL in Large Networked Systems

Abstract

Due to its high sample complexity, simulation is, as of today, critical for the successful application of reinforcement learning. Many real-world problems, however, exhibit overly complex dynamics, which makes their full-scale simulation computationally slow. In this paper, we show how to decompose large networked systems of many agents into multiple local components such that we can build separate simulators that run independently and in parallel. To monitor the influence that the different local components exert on one another, each of these simulators is equipped with a learned model that is periodically trained on real trajectories. Our empirical results reveal that distributing the simulation among different processes not only makes it possible to train large multi-agent systems in just a few hours but also helps mitigate the negative effects of simultaneous learning.

1 Introduction

Imagine we have to train a team of agents in controlling the traffic lights of a very large city, so large that we simply cannot control all traffic lights using a single policy. The first step would be to split the problem into multiple sub-regions. A natural division would be to assign one traffic light to each agent. Then, since the agents act locally, we would limit their observations to contain only local information. This partial observability could affect their optimal policies but would also make each individual decision-making problem more manageable (McCallum, 1995; Dearden and Boutilier, 1997). Moreover, we may also want to reward agents only for what occurs in their local neighborhood such that we reduce the variance of the returns (Spooner et al., 2021) and facilitate credit assignment (Castellini et al., 2020). Finally, we could train all agents together on a big traffic simulator that reproduces the global dynamics. However, if the city is truly large, it could take weeks or even months to optimize their policies. That is assuming training actually converges.

One may argue that, since the agents' observations and rewards are local, we could as well train them on separate simulators that model only the local transition dynamics (i.e. cars moving within each of the sub-regions; van der Pol and Oliehoek 2016). This approach might work if the agents' local transitions are isolated from the rest of the system (Becker et al., 2003), but would probably break when the local regions are coupled. This is because the local simulators would fail to account for the fact that the agents' local regions belong in a larger system and depend on one another.

A solution is to model the influence the global system exerts on each of the local regions. Fortunately, this does not necessarily imply modelling the entire system, or else we would just use the global simulator. In many scenarios, such as in the traffic problem, even though the local regions may be affected by many external variables (e.g.traffic densities in other parts of the city), they are only directly influenced by a small subset of them (e.g. road segments that connect the intersections with the rest of the city). This subset of variables are known as the influence sources. The theoretical framework of Influence-Based Abstraction (Oliehoek et al., 2021) shows that by monitoring the

posterior distribution of the influence sources given the action local state history (ALSH) one can simulate realistic trajectories that match those produced by the global simulator. The resulting simulator, known as the influence-augmented local simulator (IALS), has been proven effective in single agent scenarios when combined with planning (He et al., 2020) and reinforcement learning (RL) algorithms (Suau et al., 2022).

In this paper we extend the IBA framework to multi-agent domains. We show how to decompose large networked systems, such as the previous traffic example, into multiple sub-regions so that we can replace the GS by a distributed network of IALSs that can run independently and in parallel. There is one important caveat to this. The IBA framework assumes there is only a single agent learning at a time. This assumption is needed to make the influence distributions stationary. This implies that in our case, since we want the agents to learn simultaneously, previously computed influence distributions would no longer be valid after the agents update their policies. The naive solution would be to recompute new influence distributions every time any of the agents updates its policy. However, we argue that this is not only impractical, since recomputing the distributions is not without costs, but also undesirable. The theoretical results in Section 4.1 demonstrate that multiple (similar) joint policies may induce the same influence distributions, and that even when they vary a little, they can still elicit the same optimal policies. Further, our insights in Section 4.3 hint that what seems to be a problem at first, may in fact be an advantage, since in many situations, maintaining the previous influence distributions implies that the local transitions, although biased, remain stationary.

Contributions The main contributions of this paper are: (1) adapting IBA to multi-agent reinforcement learning (MARL), and demonstrating that simultaneous learning is possible without incurring major computational costs, (2) showing that by distributing the simulation among different processes we can parallelize training and scale up to systems with many agents, (3) revealing that the non-stationarity issues inherent to MARL are partly mitigated as a result of this training scheme.

2 Related Work

A few prior works have investigated the computational benefits of factorizing large systems into independent local regions (Nair et al., 2005; Varakantham et al., 2007; Kumar et al., 2011; Witwicki and Durfee, 2011). Unfortunately, since local regions are often coupled to one another, such factorizations are not always appropriate. Nonetheless, in many cases, the interactions between regions occur through a limited number of variables. Using this property, the theoretical work by Oliehoek et al. (2021) on influence-based abstraction (IBA) describes how to build influence-augmented local simulators (IALS) of local-POMDPs, which model only the variables in the environment that are directly relevant to the agent while monitoring the response of the rest of the system with the influence predictor. The problem is that the exact computation of the conditional influence distribution is intractable and we can only try to estimate it from data. Congeduti et al. (2021) provide theoretical bounds on the value loss when planning with approximate influence predictors. The work by He et al. (2020) has empirically demonstrated the advantage of this approach to improve the efficiency of online planning in two discrete toy problems. Suau et al. (2022) scale the method to high-dimensional problems by integrating the IBA framework with single-agent RL showing that the IALS can train policies much faster than the GS. In this paper, we extend the IBA solution to MARL and explain how to build a network of independent IALS such that we can train agents in parallel.

One of the consequences of training agents on independent simulators is that the non-stationarity issues arising from having the agents learn simultaneously are partly mitigated. There is a sizeable body of literature that concentrates on this issue (Hernandez-Leal et al., 2017), we include a review of these works in Appendix B for completeness. However, we note that the main purpose of this paper is to scale MARL up to systems with many agents. Hence, we are not concerned here with comparing our method with those that exclusively target non-stationarity, especially given that, for scalability reasons, these cannot be applied to the high-dimensional problems we consider here.

3 Preliminaries

The type of problems we describe in the introduction can be formulated as factored partially observable stochastic games (Hansen et al., 2004), which are defined as follows.

Definition 1 (fPOSG). A factored partially observable stochastic game (fPOSG) is a tuple $\langle N, S, F, A, T, \{R_i\}, \Omega, \{O_i\}\rangle$ where $N = \{1, ..., n\}$ is the set of n agents, S is the set state variables $S = \{S^1, ..., S^k\}$, such that every state $s^t \in \times_{j=1}^k S^j$ is a k-dimensional vector $s^t = \langle s^{1,t}, ..., s^{k,t}\rangle$, $A = \times_{i\in N} A_i$ is the set of joint actions $a^t = \langle a_1^t, ..., a_n^t\rangle$, with A_i being the set of actions for agent i, T is the transition function, with $T(s^{t+1}|s^t, a^t)$, $R_i(s^t, a_i^t)$ is the immediate reward for agent i, $\Omega = \times_{i\in N}\Omega_i$ is the set of joint observations $o_i^t = \langle o_1^t, ..., o_n^t\rangle$, with Ω_i being the set of observations for agent i, and O_i is the observation function for agent i, $O_i(o_i^t|s^t)$.

Solving the fPOSG implies finding the policy π_i for each agent i that maximizes the expected return G^t; as defined in Sutton and Barto (1998). However, agents receive only partial observations o_i of the true state s, which are not necessarily Markovian. Therefore, optimal policies are in general history-dependent in a POSG. Hence, we define the agents' policies $\pi_i(a_i^t|h_i^t)$ as mappings from action-observation histories (AOH), $h_i^t = \langle o_i^1, a_i^1, ..., a_i^{t-1}, o_i^t\rangle$, to probability distributions over actions, such that agent i's optimal policy π_i^* is the one that for every AOH h_i^t selects the action with the highest Q-value $Q^{\pi_i^*}(h_i^t, a_i^t) = \mathbb{E}[G^t \mid h_i^t, a_i^t, \pi_i^*]$.

Given the structural assumptions we made in the introduction about the agents' only being able to observe and be rewarded for what occurs in their local neighborhood, we can narrow down the problem formulation and work with a specific class of fPOSGs called local-form fPOSGs (Oliehoek et al., 2021), which better encompass the problems we consider here.

Definition 2 (Local-form fPOSG). A Local-form fPOSG is a fPOSG where O_i and R_i depend only on a subset of m state variables $X_i = \{X_i^1, ..., X_i^m\} \subseteq S$, with $m \leq k$ (number of state variables), and agent i's local states $x_i \in \times_{j=1}^m X_i^j$ being vectors $x_i^t = \langle x_i^{1,t}, ..., x_i^{k,t}\rangle$, such that $O_i(o_i^t|s^t) = \dot{O}_i(o_i^t|x_i^t)$ and $R_i(s^t, a_i^t) = \dot{R}_i(x_i^t, a_i^t)$, where $\dot{O}_i$ and $\dot{R}_i$ are the local observation and reward functions for agent i.

3.1 Influence-Based Abstraction

We now describe the IBA framework (Oliehoek et al., 2021) which intends to simplify the local-form fPOSG formulation by exploiting its structural properties. The framework assumes that there is a single agent i learning at a time while all other agents' polices π_{-i} are fixed. Hence, from the perspective of agent i the problem reduces to a POMDP (Kaelbling et al., 1996) where states are pairs $\langle s^t, h_{-i}^t\rangle$, with h_{-i}^t being the AOHs of all agents but agent i (Nair et al., 2003). Finding a solution to the Local-form fPOSG can be approached by sequentially iterating over all agents, possibly multiple times, and solving their respective POMDPs.

Looking at the definition of Local-form fPOSG, one can argue that, when solving for agent i, sampling actions from the policies of all the other agents $\pi_{-i}(a_{-i}^t|h_{-i}^t)$ and simulating the transitions $T(s^{t+1}|s^t, a^t)$ of the full set of state variables is unnecessary, and while doing so is possible in small problems, it might become computationally intractable in large domains with many agents. Instead, we can define a new transition function $\bar{T}_i$ that models only agent i's local state variables x_i, $\bar{T}_i(x_{i,t+1}|x_i^t, a_i^t)$. The problem is that x_i^{t+1} may still depend on the other agents actions a_{-i}^t and the non-local state variables $S \setminus X_i$, which means that $\bar{T}_i$ is not well defined. Fortunately, in many problems, only a fraction of the non-local state variables will *directly influence* agent i's local region.

The diagram on the left of Figure 1 is a Dynamic Bayesian Network (DBN) (Pearl, 1988; Boutilier et al., 1999) describing a particular instance of the transition dynamics for a generic agent i in a local-fPOSG. Agent i's local region, corresponds to the variables that lie within the red box, $x_i \in X_i = \{X_i^1, X_i^2\}$. The diagram also shows the non-local variables, known as influence sources $u_i \in U_i \subseteq S \setminus X_i$, that influence the local region directly. The three dots on the top indicate that there can be, potentially many, other non-local variables in S affecting the local variables X_i. These are denoted by $y_i \in Y_i \subseteq S \setminus X_i \cup U_i$. The diagram also shows that agent j can affect agent i's local region through its actions $a_j \in A_j$. However, both Y_i and A_j can only influence X_i via U_i. Hence, given u_i^t, x_i^{t+1} is conditionally independent of y_i^t and a_j^t, therefore $P(x_i^{t+1}|x_i^t, u_i^t, y_i^t, a_j^t) = P(x_i^{t+1}|x_i^t, u_i^t)$.

The above implies that by inferring the value of the influence source u_i^t, we can monitor the influence of the other agents and the non-local state variables and thus compute the local state transitions. This can be done by keeping track of the action-local-state history (ALSH) $l_i^t = \langle x_i^1, a_i^1 ..., a_i^{t-1}, x_i^t\rangle$.

Figure 1: **Left:** A Dynamic Bayesian Network showing agent i's transition dynamics in a local-form fPOSG prototype. **Right:** A conceptual diagram of the IALS.

Definition 3 (IALM). An influence-augmented local Model (IALM) for agent i is a tuple $\langle X_i, U_i, A_i, \dot{T}_i, \dot{R}_i, \Omega_i, \dot{O}_i, I_i \rangle$, with local states $x_i \in \times_{j \in |X_i|} X_i^j$, influence sources $u_i \in \times_{j \in |U_i|} U_i^j$, local transition function $\dot{T}_i(x_i^{t+1}|x_i^t, u_i^t, a_i^t)$, local observation function $\dot{O}_i(o_i^{t+1}|x_i^{t+1})$, local reward function $\dot{R}_i(x_i^t, a_i^t)$, and influence distribution $I_i(u_i^t|l_i^t)$.

Using the IALM we can compute agent i's local transitions as

$$P(x_i^{t+1}|l_i^t, a_i^t) = \sum_{u^t} \dot{T}_i(x_i^{t+1}|x_i^t, u_i^t, a_i^t) I_i(u_i^t|l_i^t). \tag{1}$$

Note that, as opposed to the Local-form fPOSG, the transition function $\dot{T}_i$ in the IALM is defined purely in terms of the local state variables and the influence sources. Moreover, since u_t *d-separates* (Bishop, 2006) x_t from y_t, we only need to maintain a belief over u_i^t, $I_i(u_i^t|l_i^t)$, rather than over the full set of of state variables s^t and other agents' histories h_{-i}^t, $P(s^t, h_{-i}^t|l_i^t)$. All in all, this translates into a much more compact, yet *exact* representation of the problem (Oliehoek et al., 2021), which should be computationally much lighter than the original Local-form fPOSG.

3.2 Influence-Augmented Local Simulators

Here we briefly describe how the IALM formulation can be used in practice to build IALS (Suau et al., 2022), which consist of a *local simulator* and an *approximate influence predictor*.

Local simulator (LS): The LS is an abstracted version of the environment that only models a small portion of it. As opposed to a global simulator (GS), which should closely reproduce the dynamics of every state variable, the LS focuses on characterizing the transitions of those variables X_i that agent i directly interacts with, $\dot{T}_i(x_i^{t+1}|x_i^t, u_i^t, a_i^t)$.

Approximate influence predictor (AIP): The AIP monitors the interactions between agent i's local region X_i, the external variables Y_i, and the other agents' actions A_{-i}, by estimating $I_i(u_i^t|l_i^t)$. Since, due to combinatorial explosion, computing the exact probability $I_i(u_i^t|l_i^t)$ is generally intractable (Oliehoek et al., 2021), a neural network is used instead to approximate the influence distribution. Thus, we write $\hat{I}_{\theta_i}$ to denote agent i's AIP, where θ_i are the network parameters. Due to the sequential nature of the problem, rather than feeding the full past ALSH every time we make a prediction, a recurrent neural network (RNN) (Hochreiter and Schmidhuber, 1997; Cho et al., 2014) is used such that local states can be processesed one at a time while the ALSH is embedded in the RNN's internal memory. The AIP $\hat{I}_{\theta_i}$ is trained on a dataset D_i of N samples of the form (l_i^t, u_i^t) collected from the GS. Since role of the AIP is to estimate the conditional probability of the influence sources u_i^t given the past ALSH, we can formulate the task as a classification problem and optimize the network using the expected cross-entropy loss (Bishop, 2006).

4 Distributed Influence-Augmented Local Simulators

As mentioned in the previous section, local-form fPOSGs are solved iteratively in the IBA framework. This means that only a single agent can update its policy at a time. Here, we relax this assumption

and discuss the advantages and disadvantages of simultaneous learning. Proofs for all the theoretical results in this section can be found in Appendix A.

4.1 Enabling Parallelization

The main reason to disallow simultaneous learn-
ing is that changes in the other agents' poli-
cies can affect agent i's influence distribution
$I_i(u_i^t|l_i^t)$, which may become non-stationary.
This renders previously computed influences
useless because they no longer capture the true
response of the global system.

Figure 2: A conceptual diagram of the DIALS

This restriction, however, prevents IBA from
unlocking its full potential. The fact that each
agent's IALS is independent of the others means
that the computations can be distributed among
different processes that can run in parallel. Hence, putting aside the non-stationarity issue, and
assuming no overhead costs in spawning an increasing number of processes, the total runtime of
the method would stay constant if the dimensionality of the global system grew, either because the
number of non-local variables or the number of agents increased. This is in contrast to having agents
learn simultaneously in the same GS, in which case larger environments imply longer runtimes.
Moreover, since each IALS simulates only a portion of the environment the total amount of memory
space needed would be split among the different processors. Hence, we could run the simulation on
multiple machines with small memory rather than one big machine with very large memory.

In principle, one could prevent the AIPs from becoming stale by simply updating all $\{\hat{I}_{\theta_i}(u_i^t|l_i^t)\}_{i \in N}$
every time any of the other agents changes its policy. However, this creates a difficult moving target
problem, and makes the whole method very inefficient since, especially in deep RL, policies are
updated very frequently. Fortunately, as we argue in the following, in many cases, paying the extra
cost of retraining the AIPs is neither necessary nor desirable.

4.1.1 Multiple joint policies may induce the same influence distribution

In the following, we show that multiple joint policies may often map onto the same influence
distribution $I_i(u_i^t|l_i^t) \in \Psi_i$ for agent $i \in N$.

Lemma 1. *Let $\Pi = \times_{i \in N} \Pi_i$ be the product space of joint policies with Π_i being the set of polices
for agent i. Moreover, let $\Psi = \times_{i \in N} \Psi_i$ be the product space of joint influences, with Ψ_i being the
set of influence distributions for agent i. Every joint policy $\pi \in \Pi$ induces exactly one influence
distribution $I_i(u_i^t|l_i^t) \in \Psi_i$ for every agent $i \in N$.*

Proposition 1. *The space of joint policies $\Pi = \times_{i \in N} \Pi_i$ is necessarily greater than or equal to the
space of joint influences $\Psi = \times_{i \in N} \Psi_i$, $|\Pi| \geq |\Psi|$. Moreover, there exist local-form fPOSGs for
which the inequality is strict.*

The advantages of this result were shown empirically by Witwicki and Durfee (2010), who demon-
strated that planning times can be reduced by searching the space of joint influences rather than the
space of joint policies, which is often much larger. In fact, in the extreme case of local transition
independence (Becker et al., 2003),[1] we have that for all joint policies π there is a single $\{I_i\}_{i \in N}$

Corollary 1. *Let agent i's influence sources u_i^t be independent of the other agents' actions a_{-i}.
Then, for any joint policy $\pi \in \Pi$, there is a unique influence distribution $I_i^* \in \Psi_i$ for every agent
$i \in N$ and $|\Pi| \gg |\Psi| = 1$.*

The result above implies that, in this particular case, we would only need to train the AIPs once at the
beginning. Although we do not expect the situation in Corollary 1 to be the norm, we do believe that
in many scenarios, such as in the two environments we explore here, we would not need to retrain the
AIPs very often because similar joint policies will influence the local regions in very similar, if not in
the same, ways. Furthermore, the next result shows that even when this is not the case, an outdated I_i
computed from an old joint policy might still produce the same optimal policy for agent i.

---

[1]As opposed to IBA, Becker et al. (2003) assume agents are tied by a shared global reward.

4.1.2 Multiple influence distributions may induce the same optimal policy

We use the simulation lemma (Kearns and Singh, 2002) to prove that if two influence distributions are similar enough they will induce the same optimal policy.

Lemma 2. *Let M_i^1 and M_i^2 be two IALMS differing only on their influence distributions $I_i^1(u_i^t|l_i^t)$ and $I_i^2(u_i^t|l_i^t)$. Let $Q_{M_i^1}^{\pi_i}$ and $Q_{M_i^2}^{\pi_i}$ be the value functions induced by M_i^1 and M_i^2 for the same π_i. If I_i^1 and I_i^2 satisfy*

$$\sum_{l_i^t, u_i^t} P(l_i^t|h_i^t)\left|I_i^1(u_i^t|l_i^t) - I_i^2(u_i^t|l_i^t)\right| \leq \xi, \text{ then } \left|Q_{M_i^1}^{\pi_i}(h_i^t, a_i^t) - Q_{M_i^2}^{\pi_i}(h_i^t, a_i^t)\right| \leq \bar{R}\frac{(H-t)(H-t+1)}{2}\xi \tag{2}$$

for all π_i, h_i^t, and a_i^t, where H is the horizon and $\bar{R} = ||R||_\infty$

Intuitively, Lemma 2 shows that the difference in value between M_i^1 an M_i^2 is upper-bounded by the maximum difference between I_i^1 and I_i^2 times a constant. Actually, if the *action-gap* (Farahmand, 2011) (i.e. value difference between the best and the second best action) in one of the IALMs is larger than twice the difference between the $Q_{M_1}^{\pi_i}$ and $Q_{M_2}^{\pi_i}$ the IALMs share the same optimal policy.

Theorem 1. *Let M_i^1 and M_i^2 be two IALMS differing only on their influence distributions $I_i^1(u_i^t|l_i^t)$ and $I_i^2(u_i^t|l_i^t)$. M_i^1 and M_i^2 induce the same optimal policy π^* if, for some Δ,*

$$Q_{M_i^1}^{\pi_i^*}(h_i^t, \bar{a}_i^t) - Q_{M_i^1}^{\pi_i^*}(h_i^t, \hat{a}_i^t) > 2\Delta \quad \forall h_i^t, \hat{a}_i^t \neq \bar{a}_i^t \text{ with } \left|Q_{M_i^1}^{\pi_i}(h_i^t, a_i^t) - Q_{M_i^2}^{\pi_i}(h_i^t, a_i^t)\right| \leq \Delta \quad \forall h_i^t, a_i^t, \pi_i, \tag{3}$$

where $\bar{a}_i^t = \arg\max_{a_i^t} Q_{M_i^1}^{\pi_i^*}(h_i^t, a_i^t)$

Hence, combining Lemma 2 and Theorem 1, Δ can be chosen as $\bar{R}\frac{(H-t)(H-t+1)}{2}\xi$, which means the closer the distributions I_i^1 and I_i^2 are, the more likely they are to elicit the same optimal policy.

4.2 Algorithm

After the analysis above, we are now ready to present our method, which we call Distributed Influence-Augmented Local Simulators (DIALS). Algorithm 1 describes how we can train multi-agent systems with DIALS. As mentioned earlier, the key advantage in using DIALS is that simulations can be distributed among different processes, and thus training can be fully parallelized. This enables MARL to scale to very large systems with many learning agents. Moreover, following from our theoretical results, AIP training, which can also be done in parallel, is performed only every certain number of timesteps. The hyperparameter F in Algorithm 1 controls the AIPs' training frequency.

Algorithm 1 MARL with DIALS

1: Initialize policies $\{\pi_i\}_{i \in N}$ and AIPs $\{\hat{I}_{\theta_i}\}_{i \in N}$
2: **repeat**
3:     Collect datasets $\{D_i\}_{i \in N}$ from GS   ▷ See Algorithm 2 in Appendix C
4:     **in parallel, for** $i \in N$ **do**
5:         Train AIP $\hat{I}_{\theta_i}$ on dataset D_i ▷ See Section 3.2
6:     **end for**
7:     **in parallel, for** $i \in N$ **do**
8:         **for** F steps **do**   ▷ F is the AIPs' training frequency
9:             Simulate trajectories with IALS $\langle \dot{T}_i, \dot{R}_i, \dot{O}_i, \hat{I}_{\theta_i} \rangle$ ▷ See Algorithm 3 in Appendix C
10:             Train policy π_i ▷ Using any standard RL method
11:         **end for**
12:     **end for**
13: **until** end of training

4.3 Mitigating the negative effects of simultaneous learning

The results in the previous section showed that the AIPs may not need to be retrained every single time policies are updated, as the influence distributions may often stay the same or vary only a little. Yet, we now argue that, even when changes in the joint policy do affect the influence distributions $I_i(u_i^t|l_i^t)$ significantly, it may be advantageous not to retrain the AIPs.

First, we have already mentioned that when all agents learn simultaneously in the same simulator the transition dynamics often look non-stationary from the perspective of each individual agent. This may result in sudden performance drops caused by oscillations in the value targets (Claus and Boutilier, 1998). In contrast, when using independent IALS to train our agents, the transition dynamics remain stationary unless we update the AIPs. Hence, by not updating the AIPs too frequently, we get a biased but otherwise more consistent learning signal that the agents can rely on to improve their policies.

Second, we posit that the poor empirical convergence of many Deep MARL methods is also because stochastic gradient descent updates often result in policies that perform worse than the previous ones. Thus, when learning together, agents may try to adapt to other agents' poor performing polices. These policies, however, are likely to be temporary as they are just a result of the inherent stochasticity of the learning process. Similarly, in many environments, agents shall take exploratory actions before they can improve there policies, which may also negatively impact cooperation if they learn simultaneously (Zhang et al., 2009, 2010). In our case, we can again benefit from the fact that the AIPs need to be purposely retrained, and do so only when the policies of the other agents have improved sufficiently.

Even though, further theoretical analysis would be needed to be more conclusive about the benefits of using independent simulators, the observations above give reasons to believe that what we initially described as a problem may in fact be an advantage. This view is also supported by our experiments.

5 Experiments

The goal of the experiments is to: (1) test whether we can reduce training times by replacing GS with DIALS, (2) investigate how the method scales to large environments with many learning agents, (3) evaluate the convergence benefits of using separate simulators to train agents rather than a single GS, and (4) study the effect of the AIPs' training frequency F on the agents' learning performance.

5.1 Experimental setup

Agents are trained independently with PPO (Schulman et al., 2017)[2] on (1) the global simulator (GS), (2) distributed influence-augmented local simulators (DIALS) with AIPs trained periodically on datasets collected from the GS using the most recent joint policy, (3) DIALS with untrained AIPs (untrained-DIALS). To measure the agent's performance, training is interleaved with periodic evaluations on the GS. The results are averaged over 10 random seeds on all except on the largest scenarios (10×10) for which, due to computational limitations we could only run 5 seeds. We report the mean return of all learning agents. We also compare the simulators in terms of total runtime. For DIALS this includes: the agents' training time, the AIPs' training time, and the time for data collection.

5.2 Environments

Traffic control The first domain we consider is a multi-agent variant of the traffic control benchmark proposed by Vinitsky et al. (2018). In this scenario agents are requested to manage the lights of a big traffic network. Each agent controls a single traffic light and can only observe cars when they are inside the intersection's local neighborhood. Their goal is to maximize the average speed of cars within their respective intersections. To demonstrate the scalability of the method we evaluate DIALS on four different variants of the traffic network with $4, 25, 49$, and even 100 intersections (agents). A screenshot of the traffic network with 25 intersections is shown in Appendix E. The GS and LS are built using Flow (MIT License) (Wu et al., 2017) and SUMO (Eclipse Public License Version 2) (Lopez et al., 2018). The GS simulates the entire traffic network while each LS models only the local neighborhood of each intersection $i \in N$ (Figure 6 in Appendix E). We use the same LS for every agent-intersection but since, depending on where they are located, they are influenced differently by the rest of the traffic network, we have separate AIPs, $\{I_{\theta_i}\}_{i \in N}$, for each them. These are feedforward neural networks with the same architecture but different weights θ_i, trained periodically with frequency F on datasets $\{D_i\}_{i \in N}$ collected from the GS. The influence sources u_t^i are binary variables indicating whether or not a car will be entering from each the four incoming lanes.

---

[2]The vanilla PPO algorithm with decentralized value functions (independent PPO; IPPO) has been shown to perform exceptionally well on several multi-agent environments (de Witt et al., 2020; Yu et al., 2021).

(a) Traffic   (b) Warehouse

Figure 3: **First (a) and (b):** Learning curves with the three simulators on the 4-intersection traffic and 4-robot warehouse environments. **Second (a) and (b):** Final average return of agents trained for 4M timesteps. **Third (a) and (b):** Total runtime of training for 4M timesteps, y-axis is in $\log_2$ scale.

Warehouse Commissioning The second domain we consider is a warehouse commissioning task (Suau et al., 2022). A team of robots (blue) need to fetch the items (yellow) that appear with probability 0.02 on the shelves (dashed black lines) of the warehouse (see Figure 5 in Appendix E). Each robot has been designated a 5×5 square region and can only collect the items that appear on the shelves at the edges. The regions overlap so that each of the 4 item shelves in a robot's region is shared with one of its 4 neighbors. The robots receive as observations a bitmap encoding their own location and a set of 12 binary variables that indicate whether or not a given item needs to be collected. The robots, however, cannot see the location of the other robots even though all of them are directly or indirectly influencing each other through their actions. We built four variants of the warehouse with 4, 25, 49, and 100 robots (agents). A screenshot of the warehouse with 25 robots is shown in Appendix E. The GS simulates the entire warehouse while the LS models only a 5×5 square region (Figure 6 in Appendix E). We use the same LS for every robot (agent) but since, depending on where they are located they are influenced differently by the rest of the robots, we have separate AIPs, $\{\hat{I}_{\theta_i}\}_{i \in N}$, for each of them. These are GRUs (Cho et al., 2014) with the same architecture but different weights θ_i, which we train periodically with frequency F on datasets $\{D_i\}_{i \in N}$ collected from the GS. Robot i's influence sources u_i^t encode the location of the four neighbor robots. If its AIP $\hat{I}_{\theta_i}$ predicts that any of the neighbor robots is at one of the 12 cells within its region, and there is an active item on that cell, that item is removed and robot i can no longer collect it.

5.3 Results

GS vs. DIALS The two plots on the left of Figures 3a and 3b show the average return as a function of the number of timesteps obtained with GS, DIALS, and untrained-DIALS on the 4-agent traffic and warehouse environments. Shaded areas indicate the standard error of the mean. Agents are trained for 4M timesteps on all three simulators. The results reveal that, while agents trained on DIALS seem to converge steadily towards similar high-performing policies, agents trained with the GS often get stuck in local minima, hence the poor mean episodic reward and large standard error obtained with the GS relative to that of the DIALS. In contrast, the low performance of agents trained with the untrained-DIALS indicates that estimating the influences correctly is important for learning good policies. It is worth noting that the gap between the GS and the DIALS is larger in Figure 3b than in Figure 3a. We posit that this is because, in the warehouse domain, agents are more strongly coupled. The learning curves for the other scenarios are provided in Appendix D together with further discussion on these results.[3]

Scalability The benefits of parallelization are more apparent when moving to larger environments. The two bar plots in Figures 3a and 3b depict the final average return and the total run time of training 4, 25, 49 and 100 agents on the two tasks for 4M timesteps. The plots show that DIALS scales far better than the GS to larger problem sizes, while also yielding better performing policies. For example, training **100 agents** on the traffic network takes less than **6 hours** with the DIALS, whereas training them with the GS would take more than **10 days**. This is a **speedup factor of 40**. In fact, since the maximum execution time allowed by our computer cluster is 1 week, the results reported

---

[3]A video showing how agents trained with DIALS perform on the traffic control task is provided at
https://www.dropbox.com/sh/tk5oxoe82qjy0b9/AAD6HMqpXXUys8dyH6ndifMWa?dl=0

| | (a) Traffic 25 agents | (b) Warehouse 25 agents |

Figure 4: **Left (a) and (b):** Learning curves for different values of F on the 25-agent versions of the two environments. **Right (a) and (b):** CE loss as a function of runtime averaged over the 25 AIPs.

for the GS in the scenarios of size 10×10 do not correspond to 4M timesteps but the equivalent of 1 week of training. We would also like to point out that, disregarding the overhead costs associated with multiprocessing, the DIALS runtime should remain constant independently of the problem size. However, to update the AIPs, new samples are collected form the GS, which does increase the runtime. This explains the gap between DIALS and untrained-DIALS. That said, the number of samples needed to update the AIPs (80K for traffic and 10K for warehouse) is significantly lower than the samples needed to train the agents (4M), which is why the runtime difference between GS and DIALS is so large. A table with a breakdown of the runtimes is given in Appendix F.

AIPs' training frequency Our first results have already demonstrated that isolating the agents in separate simulators and not updating the AIPs too frequently can be beneficial for convergence. We now further investigate this phenomenon by evaluating the agents' learning performance for different values of the hyperparameter F. The two plots on the left of Figures 4a and 4b show the learning curves for agents trained on DIALS where F is set to 100K, 500K, 1M, and 4M timesteps. In the traffic domain, the gap between the green and the purple curve (Figure 4a) suggests that it is important to retrain the AIPs at least every 1M timesteps, such that agents become aware of changes in the other agents' policies. In contrast, in the warehouse domain (Figure 4b), we see that training the AIPs only once at the beginning (DIALS $F = 4M$) seems sufficient. In fact, updating the AIPs too frequently (DIALS $F = 100K$) is detrimental to the agents' performance. This is consistent with our hypothesis in Section 4.3. The plots on the right show the average cross-entropy (CE) loss of the AIPs evaluated on trajectories sampled from the GS. As explained in Section 4 since all agents learn simultaneously, the influence distributions $\{I(u_i^t | l_i^t)\}_{i \in N}$ are non-stationary. For this reason, we see that the CE loss changes as the policies of the other agents are updated. We can also see how the CE loss decreases when the AIPs are retrained, which happens more or less frequently depending on the hyperparameter F. Note that the CE not only measures the distance between the two probability distributions but also the absolute entropy. In the warehouse domain, the neighbor robots' locations become more predictable (lower entropy) as their policies improve. This explains why in the first plot from the right the CE loss decreases even though the AIPs are not updated. Also in the same plot, even though by the end of training DIALS $F = 4M$ is highly inaccurate, as evidenced by the gap between the purple and the other curves, it is still good enough to train policies that match the performance of those trained with DIALS $F = 500K$ and $F = 1M$. This is in line with our results in Section 4. The same plots for the rest of scenarios are provided in Appendix D.

6 Conclusion

This paper has offered a practical solution that allows training large networked systems with many agents in just a few hours. We showed how to decompose these systems into multiple sub-regions such that we could build distributed influence-augmented local simulators (DIALS). The key advantage of DIALS is that simulations can be distributed among different processes, and thus training can be fully parallelized. To account for the interactions between the different sub-regions, the simulators are equipped with approximate influence predictors (AIPs), which are trained periodically on real trajectories sampled from a global simulator (GS). We demonstrated that, although with DIALS agents learn simultaneously, training the AIPs very frequently is neither necessary nor desirable. Our results reveal that DIALS not only enables MARL to scale up but also mitigates the non-stationarity issues of simultaneous learning. Future work could analyse this phenomenon from a theoretical perspective, or study how to retrain the AIPs without having to run the GS to generate new samples.

References

Becker, R., Zilberstein, S., Lesser, V., and Goldman, C. V. (2003). Transition-independent decentralized Markov decision processes. In *Proc. of the International Conference on Autonomous Agents and Multiagent Systems*, pages 41–48.

Bishop, C. M. (2006). *Pattern Recognition and Machine Learning*. Springer.

Boutilier, C., Dean, T., and Hanks, S. (1999). Decision-theoretic planning: Structural assumptions and computational leverage. *Journal of Artificial Intelligence Research*, 11:1–94.

Castellini, J., Devlin, S., Oliehoek, F. A., and Savani, R. (2020). Difference rewards policy gradients. *arXiv preprint arXiv:2012.11258*.

Cho, K., van Merrienboer, B., Gulcehre, C., Bougares, F., Schwenk, H., and Bengio, Y. (2014). Learning phrase representations using rnn encoder-decoder for statistical machine translation. In *Conference on Empirical Methods in Natural Language Processing (EMNLP 2014)*.

Claus, C. and Boutilier, C. (1998). The dynamics of reinforcement learning in cooperative multiagent systems. In *Proc. of the National Conference on Artificial Intelligence*, pages 746–752.

Congeduti, E., Mey, A., and Oliehoek, F. A. (2021). Loss bounds for approximate influence-based abstraction. In *Proceedings of the Twentieth International Conference on Autonomous Agents and MultiAgent Systems*.

de Witt, C. S., Gupta, T., Makoviichuk, D., Makoviychuk, V., Torr, P. H., Sun, M., and Whiteson, S. (2020). Is independent learning all you need in the starcraft multi-agent challenge? *arXiv preprint arXiv:2011.09533*.

Dearden, R. and Boutilier, C. (1997). Abstraction and approximate decision-theoretic planning. *Artificial Intelligence*, 89(1-2):219–283.

Farahmand, A.-m. (2011). Action-gap phenomenon in reinforcement learning. *Advances in Neural Information Processing Systems*, 24.

Foerster, J., Chen, R. Y., Al-Shedivat, M., Whiteson, S., Abbeel, P., and Mordatch, I. (2018a). Learning with opponent-learning awareness. In *Proceedings of the Seventeenth International Conference on Autonomous Agents and MultiAgent Systems*.

Foerster, J., Farquhar, G., Afouras, T., Nardelli, N., and Whiteson, S. (2018b). Counterfactual multi-agent policy gradients. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence*.

Hansen, E. A., Bernstein, D. S., and Zilberstein, S. (2004). Dynamic programming for partially observable stochastic games. In *Proc. of the National Conference on Artificial Intelligence*, pages 709–715.

He, J., Suau, M., and Oliehoek, F. (2020). Influence-augmented online planning for complex environments. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M. F., and Lin, H., editors, *Advances in Neural Information Processing Systems*, volume 33, pages 4392–4402. Curran Associates, Inc.

Hernandez-Leal, P., Kaisers, M., Baarslag, T., and de Cote, E. M. (2017). A survey of learning in multiagent environments: Dealing with non-stationarity. *arXiv preprint arXiv:1707.09183*.

Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8):1735–1780.

Kaelbling, L. P., Littman, M., and Moore, A. (1996). Reinforcement learning: A survey. *Journal of AI Research*, 4:237–285.

Kearns, M. and Singh, S. (2002). Near-optimal reinforcement learning in polynomial time. *Machine learning*, 49(2):209–232.

Konda, V. and Tsitsiklis, J. (1999). Actor-critic algorithms. *Advances in neural information processing systems*, 12.

Kumar, A., Zilberstein, S., and Toussaint, M. (2011). Scalable multiagent planning using probabilistic inference. In *Proc. of the International Joint Conference on Artificial Intelligence*, pages 2140–2146.

Laurent, G. J., Matignon, L., Fort-Piat, L., et al. (2011). The world of independent learners is not markovian. *International Journal of Knowledge-based and Intelligent Engineering Systems*, 15(1):55–64.

Li, W., Wang, X., Jin, B., Sheng, J., and Zha, H. (2021). Dealing with non-stationarity in marl via trust-region decomposition. In *International Conference on Learning Representations*.

Lopez, P. A., Behrisch, M., Bieker-Walz, L., Erdmann, J., Flötteröd, Y.-P., Hilbrich, R., Lücken, L., Rummel, J., Wagner, P., and Wießner, E. (2018). Microscopic traffic simulation using sumo. In *The 21st IEEE International Conference on Intelligent Transportation Systems*. IEEE.

Lowe, R., Wu, Y., Tamar, A., Harb, J., Abbeel, P., and Mordatch, I. (2017). Multi-agent actor-critic for mixed cooperative-competitive environments. *Neural Information Processing Systems (NIPS)*.

Lyu, X., Xiao, Y., Daley, B., and Amato, C. (2021). Contrasting centralized and decentralized critics in multi-agent reinforcement learning. *Proceedings of the Twentieth International Conference on Autonomous Agents and MultiAgent Systems*.

McCallum, A. K. (1995). *Reinforcement Learning with Selective Perception and Hidden State*. PhD thesis, University of Rochester.

Nair, R., Tambe, M., Yokoo, M., Pynadath, D. V., and Marsella, S. (2003). Taming decentralized POMDPs: Towards efficient policy computation for multiagent settings. In *Proc. of the International Joint Conference on Artificial Intelligence*, pages 705–711.

Nair, R., Varakantham, P., Tambe, M., and Yokoo, M. (2005). Networked distributed POMDPs: A synthesis of distributed constraint optimization and POMDPs. In *Proc. of the National Conference on Artificial Intelligence*, pages 133–139.

van der Pol, E. and Oliehoek, F. A. (2016). Coordinated deep reinforcement learners for traffic light control. NIPS'16 Workshop on Learning, Inference and Control of Multi-Agent Systems.

Oliehoek, F., Witwicki, S., and Kaelbling, L. (2021). A sufficient statistic for influence in structured multiagent environments. *Journal of Artificial Intelligence Research*, 70:789–870.

Oliehoek, F. A. and Amato, C. (2016). *A Concise Introduction to Decentralized POMDPs*. Springer Briefs in Intelligent Systems. Springer.

Pearl, J. (1988). *Probabilistic Reasoning In Intelligent Systems: Networks of Plausible Inference*. Morgan Kaufmann.

Rabinowitz, N., Perbet, F., Song, F., Zhang, C., Eslami, S. A., and Botvinick, M. (2018). Machine theory of mind. In *International conference on machine learning*, pages 4218–4227. PMLR.

Raileanu, R., Denton, E., Szlam, A., and Fergus, R. (2018). Modeling others using oneself in multi-agent reinforcement learning. In *International conference on machine learning*, pages 4257–4266. PMLR.

Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. (2017). Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Spooner, T., Vadori, N., and Ganesh, S. (2021). Factored policy gradients: Leveraging structure for efficient learning in MOMDPs. *Advances in Neural Information Processing Systems*, 34.

Suau, M., He, J., Spaan, M. T., and Oliehoek, F. A. (2022). Influence-augmented local simulators: A scalable solution for fast Deep RL in large networked systems. *arXiv preprint arXiv:2202.01534*.

Sutton, R. S. and Barto, A. G. (1998). *Reinforcement Learning: An Introduction*. The MIT Press.

Tan, M. (1993). Multi-agent reinforcement learning: Independent vs. cooperative agents. In *Proceedings of the tenth international conference on machine learning*, pages 330–337.

Varakantham, P., Marecki, J., Yabu, Y., Tambe, M., and Yokoo, M. (2007). Letting loose a SPIDER on a network of POMDPs: Generating quality guaranteed policies. In *Proc. of the International Conference on Autonomous Agents and Multiagent Systems*.

Vinitsky, E., Kreidieh, A., Le Flem, L., Kheterpal, N., Jang, K., Wu, C., Wu, F., Liaw, R., Liang, E., and Bayen, A. M. (2018). Benchmarks for reinforcement learning in mixed-autonomy traffic. In *Conference on robot learning*, pages 399–409. PMLR.

Witwicki, S. J. and Durfee, E. H. (2010). Influence-based policy abstraction for weakly-coupled Dec-POMDPs. In *Proc. of the International Conference on Automated Planning and Scheduling*, pages 185–192.

Witwicki, S. J. and Durfee, E. H. (2011). Towards a unifying characterization for quantifying weak coupling in Dec-POMDPs. In *Proceedings of the Tenth International Conference on Autonomous Agents and Multiagent Systems*, pages 29–36, Taipei, Taiwan.

Wu, C., Kreidieh, A., Parvate, K., Vinitsky, E., and Bayen, A. M. (2017). Flow: A modular learning framework for autonomy in traffic. *arXiv preprint arXiv:1710.05465*.

Yu, C., Velu, A., Vinitsky, E., Wang, Y., Bayen, A., and Wu, Y. (2021). The surprising effectiveness of ppo in cooperative, multi-agent games. *arXiv preprint arXiv:2103.01955*.

Zhang, C., Abdallah, S., and Lesser, V. (2009). Integrating organizational control into multi-agent learning. In *Proceedings of The 8th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 757–764.

Zhang, C., Lesser, V. R., and Abdallah, S. (2010). Self-organization for coordinating decentralized reinforcement learning. In *AAMAS*, volume 10, pages 739–746.