REINFORCEMENT LEARNING WITH LATENT FLOW

ABSTRACT

Temporal information is essential to learning effective policies with Reinforcement Learning (RL). However, current state-of-the-art RL algorithms either assume that such information is given as part of the state space or, when learning from pixels, use the simple heuristic of frame-stacking to implicitly capture temporal information present in the image observations. This heuristic is in contrast to the current paradigm in video classification architectures, which utilize explicit encodings of temporal information through methods such as optical flow and two-stream architectures to achieve state-of-the-art performance. Inspired by leading video classification architectures, we introduce the **F**low of **La**tents for **Re**inforcement Learning (*Flare*), a network architecture for RL that explicitly encodes temporal information through latent vector differences. We show that Flare (i) recovers optimal performance in state-based RL without explicit access to the state velocity, solely with positional state information, (ii) achieves state-of-the-art performance on pixel-based continuous control tasks within the DeepMind control benchmark suite, and (iii) is the most sample efficient model-free pixel-based RL algorithm on challenging environments in the DeepMind control suite such as quadruped walk, hopper hop, finger turn hard, pendulum swing, and walker run, outperforming the prior model-free state-of-the-art by $\mathbf{1.9}\times$ and $\mathbf{1.5}\times$ on the 500k and 1M step benchmarks, respectively.

1 INTRODUCTION

Reinforcement learning (RL) (Sutton & Barto, 1998) holds the promise of enabling artificial agents to solve a diverse set of tasks in uncertain and unstructured environments. Recent developments in RL with deep neural networks have led to tremendous advances in autonomous decision making. Notable examples include classical board games (Silver et al., 2016; 2017), video games (Mnih et al., 2015; Berner et al., 2019; Vinyals et al., 2019), and continuous control (Schulman et al., 2017; Lillicrap et al., 2016; Rajeswaran et al., 2018). A large body of research has focused on the case where an RL agent is equipped with a compact state representation. Such compact state representations are typically available in simulation (Todorov et al., 2012; Tassa et al., 2018) or in laboratories equipped with elaborate motion capture systems (OpenAI et al., 2018; Zhu et al., 2019; Lowrey et al., 2018). However, state representations are seldom available in unstructured real-world settings like the home. For RL agents to be truly autonomous and widely applicable, sample efficiency and the ability to act using raw sensory observations like pixels is crucial. Motivated by this understanding, we study the problem of efficient and effective deep RL from pixels.

A number of recent works have made progress towards closing the sample-efficiency and performance gap between deep RL from states and pixels (Laskin et al., 2020b;a; Hafner et al., 2019a; Kostrikov et al., 2020). An important component in this endeavor has been the extraction of high quality visual features during the RL process. Laskin et al. (2020a) and Stooke et al. (2020) have shown that features learned either explicitly with auxiliary losses (reconstruction or contrastive losses) or implicitly (through data augmentation) are sufficiently informative to recover the agent's pose information. While existing methods can encode positional information from images, there has been little attention devoted to extracting temporal information from a stream of images. As a result, existing deep RL methods from pixels struggle to learn effective policies on more challenging continuous control environments that deal with partial observability, sparse rewards, or those that require precise manipulation.

Current approaches in deep RL for learning temporal features are largely heuristic in nature. A commonly employed approach is to stack the most recent frames as inputs to a convolutional neural network (CNN). This can be viewed as a form of early fusion (Karpathy et al., 2014), where information from the recent time window is combined immediately at the pixel level for input to the CNN. In contrast, modern video recognition systems use alternate architectures that employ optical flow and late fusion (Simonyan & Zisserman, 2014), where frames are processed individually with CNN layers before fusion and downstream processing. Such a late fusion approach is typically beneficial due to better performance, fewer parameters, and the ability to use multi-modal data (Jain et al., 2019; Chebotar et al., 2017). However, it is not straightforward how to port such architectures to RL. Comput-

Figure 1: **F**low of **La**tents for **Re**inforcement Learning (*Flare*) architecture. Input frames are first encoded individually by the same encoder. The resulting latent vectors are then concatenated with their latent differences before being passed to the downstream RL algorithm.

ing optical flow in real-time for action selection can be computationally infeasible in applications with fast control loops like robotics. In our experiments, we also find that a naive late fusion architecture minus the optical flow yields poor results in RL settings (see Section 6.3). This observation is consistent with recent findings in related domains like visual navigation (Walsman et al., 2019).

To overcome the above challenges, we develop **F**low of **La**tents for **Re**inforcement Learning (*Flare*), a new architecture for deep RL from pixels (Figure 1). Flare can be interpreted as a *structured late fusion* architecture. Flare processes each frame individually to compute latent vectors, similar to a standard late fusion approach (see Figure 1). Subsequently, temporal differences between the latent feature vectors are computed and fused along with the latent vectors by concatenation for downstream processing. By incorporating this structure of temporal difference in latent feature space, we provide the learning agent with appropriate inductive bias. In experiments, we show that Flare (i) recovers optimal performance in state-based RL without explicit access to the state velocity, solely with positional state information, (ii) achieves state-of-the-art performance compared to model-free methods on several challenging pixel-based continuous control tasks within the DeepMind control benchmark suite, namely Quadruped Walk, Hopper Hop, Finger Turn-hard, Pendulum Swingup, and Walker Run, and (iii) is the most sample efficient model-free pixel-based RL algorithm across these tasks, outperforming the prior model-free state-of-the-art RAD by **1.9×** and **1.5×** on the 500k and 1M environment step benchmarks, respectively.

2 RELATED WORK

Pixel-Based RL The ability of an agent to autonomously learn control policies from visual inputs can greatly expand the applicability of deep RL (Dosovitskiy et al., 2017; Savva et al., 2019). Prior works have used CNNs to extend RL algorithms like PPO (Schulman et al., 2017), SAC (Haarnoja et al., 2018), and Rainbow (Hessel et al., 2017) to pixel-based tasks. Such direct extensions have typically required substantially larger number of environment interactions when compared to the state-based environments. In order to improve sample efficiency, recent efforts have studied the use of auxiliary tasks and loss functions (Yarats et al., 2019; Laskin et al., 2020b; Schwarzer et al., 2020), data augmentation (Laskin et al., 2020a; Kostrikov et al., 2020), and latent space dynamics modeling (Hafner et al., 2019b;a). Despite these advances, there is still a large gap between the learning efficiency in state-based and pixel-based environments in a number of challenging benchmark tasks. Our goal in this work is to identify where and how to improve pixel-based performance on this set of challenging control environments.

Neural Network Architectures in RL The work of Mnih et al. (2015) combined Q-learning with CNNs to achieve human level performance in Atari games. In this work, Mnih et al. (2015) concatenate the most recent 4 frames and use a convolutional neural network to output the Q values. In 2016, Mnih et al. (2016) proposed to use a shared CNN among frames to extract visual features and aggregate the temporal information with LSTM. The same architectures have been adopted by most

works till date (Laskin et al., 2020b; Schwarzer et al., 2020; Kostrikov et al., 2020; Laskin et al., 2020a). The development of new architectures to better capture temporal information in a stream of images has received little attention in deep RL, and our work aims to fill this void. Perhaps closest to our motivation is the work of Amiranashvili et al. (2018) who explicitly use optical flow as an extra input to the RL policy. However, this approach requires additional information and supervision signal to train the flow estimator, which could be unavailable or inaccurate in practice. In contrast, our approach is a simple modification to existing deep RL architectures and does not require any additional auxiliary tasks or supervision signals.

Two-Stream Video Classification In video classification tasks, such as activity recognition (Soomro et al., 2012), there are a large body of works on how to utilize temporal information (Donahue et al., 2015; Ji et al., 2012; Tran et al., 2015; Carreira & Zisserman, 2017; Wang et al., 2018; Feichtenhofer et al., 2019). Of particular relevance is the two-stream architecture of Simonyan & Zisserman (2014), where one CNN stream takes the usual RGB frames, while the other the optical flow computed from the RGB values. The features from both streams are then late-fused to predict the activity class. Simonyan & Zisserman (2014) found that the two-stream architecture yielded a significant performance gain compared to the single RGB stream counterpart, indicating the explicit temporal information carried by the flow plays an essential role in video understanding. Instead of directly computing the optical flow, we propose to capture the motion information in latent space to avoid computational overheads and potential flow approximation errors. Our approach also could focus on domain-specific motions that might be overlooked in a generic optical flow representation.

3 BACKGROUND

Soft Actor Critic (SAC) (Haarnoja et al., 2018) is an off-policy actor-critic RL algorithm for continuous control with an entropy maximization term augmented to its score function to encourage exploration. SAC learns a policy network $\pi_\psi(a_t|\mathbf{o}_t)$ and critic networks $Q_{\phi_1}(\mathbf{o}_t, a_t)$ and $Q_{\phi_2}(\mathbf{o}_t, a_t)$ to estimate state-action values. The critic $Q_{\phi_i}(\mathbf{o}_t, a_t)$ is optimized to minimize the (soft) Bellman residual error:

$$\mathcal{L}_Q(\phi_i) = \mathbb{E}_{\tau \sim \mathcal{B}} \left[\left(Q_{\phi_i}(\mathbf{o}_t, a_t) - (r_t + \gamma V(\mathbf{o}_{t+1})) \right)^2 \right], \tag{1}$$

where r is the reward, γ the discount factor, $\tau = (\mathbf{o}_t, a_t, \mathbf{o}_{t+1}, r_t)$ is a transition sampled from replay buffer $\mathcal{B}$, and $V(\mathbf{o}_{t+1})$ is the (soft) target value estimated by:

$$V(\mathbf{o}_{t+1}) = \left(\min_i Q_{\bar{\phi}_i}(\mathbf{o}_{t+1}, a_{t+1}) - \alpha \log \pi_\psi(a_{t+1}|\mathbf{o}_{t+1}) \right), \tag{2}$$

where α is the entropy maximization coefficient. For stability, in eq. 2, $Q_{\bar{\phi}_i}$ is the exponential moving average of Q_{ϕ_i}'s over training iterations. The policy π_ψ is trained to maximize the expected return estimated by Q together with the entropy term

$$L_\pi(\psi) = -\mathbb{E}_{a_t \sim \pi} \left[\min_i Q_{\phi_i}(\mathbf{o}_t, a_t) - \alpha \log \pi_\psi(a_t|\mathbf{o}_t) \right], \tag{3}$$

where α is also a learnable parameter.

Reinforcement Learning with Augmented Data (RAD) (Laskin et al., 2020a) is a recently proposed training technique. In short, RAD pre-processes raw pixel observations by applying random data augmentations, such as random translation and cropping, for RL training. As simple as it is, RAD has taken many existing RL algorithms, including SAC, to the next level. For example, on many DMControl (Tassa et al., 2018) benchmarks, while vanilla pixel-based SAC performs poorly, RAD-SAC—i.e. applying data augmentation to pixel-based SAC—achieves state-of-the-art results both in sample efficiency and final performance. In this work, we refer RAD to RAD-SAC and the augmentation used is random translation.

4 MOTIVATION

We motivate our method by investigating the importance of temporal information in state-based RL. Our investigation utilizes five diverse environments from the DMControl (Tassa et al., 2018) suite. The full state for these environments includes both the agent's pose information, such as the joints' positions and angles, as well as temporal information, such as the joints' translational and

Figure 2: We motivate Flare by investigating whether temporal information is essential to learning effective policies from the proprioceptive states. We run three variants of SAC: (i) SAC with the full state as input, containing both pose and temporal information, i.e. full-state SAC (blue); (ii) SAC with only pose information as input, i.e. position-only SAC (green); (iii) SAC with pose information and velocity approximations through pose offsets as input, i.e. Flare applied to the state space (orange). While full-state SAC efficiently learns the optimal policy, position-only SAC recovers suboptimal policies and fails learning at all in some cases. However, through the fusion of approximated velocities, Flare is able to recover the optimal policy nearly as efficiently as the full state SAC in most cases. Results are averaged over 3 seeds with standard deviation.

Figure 3: To ensure that the improved performance comes from the temporal approximation and not access to consecutive states, we compare Flare, which fuses positional information with positional differences, to a variant of SAC that only receives consecutive positional states as input (Stack SAC). Stack SAC is different from positional-only SAC in Figure 2. Position-only SAC receives (s_t) as input while Stack SAC receives (s_t, s_{t-1}) as input. Flare receives (s_t, δ_t) where $\delta_t = s_t - s_{t-1}$ as input. We find that despite having implicit access to temporal information between consecutive states Stack SAC performs significantly worse than Flare on most environments, motivating the benefit of explicit fusion of temporal information. Results are averaged over three seeds.

angular velocities. We train two variants with SAC – one variant where the agent receives the full state as input (full-state SAC), and the other with the temporal information masked out, i.e. the agent only receives the pose information as its input (position-only SAC). The resulting learning curves are in Figure 2. While the full-state SAC learns the optimal policy quickly, the position-only SAC learns much sub-optimal policies, which often fail entirely. It is therefore clearly shown that effective policies cannot be learned from positional information alone, and that temporal information is crucial for efficient learning.

While full-state SAC can receive velocity information from internal sensors in simulation, in the more general case such as learning from pixels, such information is often not readily available. For this reason, we investigate whether we can explicitly approximate temporal information as the difference between two consecutive states. If the input is the positional state, then this positional difference roughly approximates the agent's velocity. Given poses s_t^p, s_{t-1}^p at time $t, t-1$, we compute the positional offset $\delta_t = s_t - s_{t-1}$, and provide the fused vector (s_t, δ_t) to the SAC agent. This procedure precisely describes the state-based version of Flare. Results shown in Figure 2 demonstrate that state-based Flare significantly outperforms the position-only SAC. Furthermore, state-based Flare achieves optimal asymptotic performance, and its learning efficiency is comparable to full-state SAC in most environments. Given that the position-only SAC (which utilizes s_t alone) has only partial information compared to Flare that utilizes (s_t, δ_t), we also investigate a variant where we provide consecutive positions (s_t, s_{t-1}) to the SAC agent. We call this variant stack-SAC, since it is identical to the frame-stack heuristic used in pixel-based RL. Results in Figure 3 show that Flare still significantly outperforms the stack-SAC. It suggests that the well-structured inductive bias in the form of temporal-position fusion is essential for efficient learning.

(a) Frame stacking heuristic   (b) Individual frame encoding   (c) Flow of Latents for RL (Flare)

Figure 4: **F**low of **La**tents for **Re**inforcement Learning (*Flare*). In panel (a) we show the architecture for the frame stacking heuristic, in (b) we show an alternative to the frame stacking hueristic by encoding each image individually, and in (c) we show the Flare architecture which encodes images individually, computes the feature differences, and fuses the differences together with the latents.

Our findings from the state experiments in Figure 2 and Figure 3 suggest that (i) temporal information is crucial to learning effective policies in RL and (ii) approximating temporal information in the absence of sensors that provide explicit measurements is sufficient in most cases. When learning from pixels, it is common to assume the absence of specialized sensors for reading out temporal information. We therefore hypothesize that explicit fusion of temporal information approximated directly from pixel-level inputs can improve the efficiency of learning control policies.

5 Reinforcement Learning with Latent Flow

To date, the most common way of pre-processing pixel-based input to convey temporal information for RL algorithms has been by stacking frames. This heuristic, introduced by Mnih et al. (2015), has been largely untouched since its inception and is used in most state-of-the-art RL architectures. However, our observations from the experiments run on proprioceptive state input in Section 4 suggest an alternative to the frame stacking heuristic through the explicit inclusion of temporal information as part of the input. To learn effective control policies from pixels, we seek a general approach to explicitly incorporate temporal information that can be coupled to any base RL algorithm with minimal modification. To this end, we propose the **F**low of **La**tents for **Re**inforcement Learning (*Flare*) architecture. Our proposed method calculates differences between the latent encodings of individual frames and fuses the feature differences and latent embeddings before passing them as input to the base RL algorithm, as shown in Figure 4. For the base RL algorithm we use RAD-SAC (Laskin et al., 2020a), a state-of-the-art model-free off-policy RL method, though any RL algorithm can be used in principle.

5.1 Latent Flow

In computer vision, the most common approach to explicitly inject temporal information of a video sequence is to compute dense optical flow between consecutive frames (Simonyan & Zisserman, 2014). Then the RGB and the optical flow inputs are individually fed into two streams of encoders and the features from both streams are fused in the later stage of the network. However, two-stream architectures with optical flow are not directly applicable to RL. The main issue is that the computation of optical flow is slow: during inference, it is often prohibitively expensive to compute in real-time for applications with fast control loops like robotics; during training, optical flow calculation adds significant overhead to the wallclock training time in online learning settings like RL. While video architectures can utilize a memory bank, such that optical flow need only be pre-computed once for the entire dataset, RL training is done dynamically and on the fly, and computing optical flow at each step is therefore costly.

To address this challenge and motivated by experiments in Section 4, we propose an alternative architecture that is similar in spirit to the two-stream networks for video classification. Rather than

| Quadruped Walk | Hopper Hop | Pendulum Swingup | Walker Run | Finger Turn Hard |

Figure 5: We choose the following environments for our main experiments – (i) quadruped walk, which requires coordination of multiple joints, (ii) hopper hop, which requires hopping while maintaining balance, (iii) pendulum swingup, an environment with sparse rewards, (iv) walker run, which requires the agent to maintain balance at high speeds, and (v) finger turn hard, which requires precise manipulation of a rotating object. These environments are deemed challenging because prior state-of-the-art model-free pixel-based methods (Laskin et al., 2020b; Kostrikov et al., 2020; Laskin et al., 2020a) either fail to reach the asymptotic performance of state SAC or learn less efficiently.

Task	Flare (500K)	RAD (500K)	Flare (1M)	RAD (1M)
Quadruped Walk	**296** $\pm$ 139	206 $\pm$ 112	**488** $\pm$ 221	322 $\pm$ 229
Pendulum Swingup	**242** $\pm$ 152	79 $\pm$ 73	**809** $\pm$ 31	520 $\pm$ 321
Hopper Hop	**90** $\pm$ 55	40 $\pm$ 41	**217** $\pm$ 59	211 $\pm$ 27
Finger Turn hard	**282** $\pm$ 67	137 $\pm$ 98	**661** $\pm$ 315	249 $\pm$ 98
Walker Run	426 $\pm$ 33	**547** $\pm$ 48	556 $\pm$ 93	**628** $\pm$ 39

Table 1: Evaluation on 5 benchmark tasks around 500K and 1M environment steps. We evaluate over 5 seeds, each of 10 trajectories and show the mean $\pm$ standard deviation across runs.

computing optical flow directly, we approximate temporal information in the latent space. Instead of encoding a stack of frames at once, we use a frame-wise CNN to encode each individual frame. Then we compute the differences between the latent encodings of consecutive frames, which we refer to as *latent flow*. Finally, the latent features and the latent flow are fused together through concatenation before getting passed to the downstream RL algorithm. We call the proposed architecture as **Fl**ow of **La**tents for **Re**inforcement Learning (*Flare*).

Algorithm 1: Pixel-based Flare Inference

Given π_ψ, f_{CNN};
for *each environment step t* **do**
  $z_j = f_{CNN}(o_j), j = t - k, .., t$;
  $\delta_j = z_j - z_{j-1}, j = t - k + 1, .., t$;
  $\mathbf{z}_t = (z_{t-k+1}, \cdots, z_t, \delta_{t-k+1}, \cdots, \delta_t)$;
  $a_t \sim \pi_\psi(a_t | \mathbf{z}_t)$;
  $o_{t+1} \sim p(a_{t+1} | a_t, \mathbf{o}_t = (o_t, o_{t-1} .. o_{t-k}))$;
end

While Flare is a broadly applicable technique, for clarity of exposition, we select RAD as the base algorithm to elaborate the execution of Flare. We also use RAD later on in our experiments as the comparative baseline (Section 6). The RAD architecture, shown in Figure 4a, stacks multiple data augmented frames observed in the pixel space and encodes them altogether through an CNN. This can be viewed as a form of early fusion (Karpathy et al., 2014). Another preprocessing option is to encode each frame individually through a shared frame-wise encoder and perform late fusion of the resulting latent features, as shown in Figure 4b. However, we find that simply concatenating the latent features results in inferior performance when compared to the frame stacking heuristic, which we further elaborate in Section 6.3. We conjecture that pixel-level frame stacking benefits from leveraging both the CNN and the fully connected layers to process temporal information, whereas latent-level stacking does not propagate temporal information back through the CNN encoder. Based on this conjecture, we explicitly compute the latent flow $\delta_t = z_t - z_{t-1}$ while detaching the z_{t-1} gradients when computing δ_t. We fuse the latent flow δ_t with the latent embedding z_t, and pass the fused input to the actor and critic networks as shown in Figure 4c. We provide pseudocode that illustrates how to do inference with Flare in Algorithm 1; during training, the encodings of latent features and latent flow are done in the same except with augmented observations.

6 EXPERIMENTS

We first introduce the 5 core challenging continuous control tasks from DMControl suite (Tassa et al., 2018) that are experiments focus on. Next we present the main experimental results, where we

Figure 6: We compare the performance of Flare to RAD, a state-of-the-art algorithm and the base algorithm used in Flare, on five challenging environments. Pendulum Swingup are trained over 1.5e6 and the rest 2.5e6. We see that Flare substantially outperforms RAD on a majority (3 out of the 5) of environments, while being competitive in the remaining. While not closing the gap between pixel and state-based performance entirely, Flare is closer to state-based performance than prior methods, and is the state-of-the-art pixel-based model-free algorithm on most of these challenging environments. Results are averaged over 5 random seeds with standard deviation (shaded regions).

Figure 7: We perform three ablation studies. (a) *pixel flow ablation*: we compare Flare to a variant where the differences are computed directly in pixel space (pixel flow) and find that latent flow is more stable and achieves better performance. (b) *Latent stack ablation*: in this experiment, we fuse the latent vectors without the temporal approximation. We find that this method performs significantly worse than Flare, and on quadruped fails entirely, suggesting that fusing explicit temporal information is crucial. (c) *Frames count ablation*: We test whether adding more frames increases performance for Flare. We find that including additional input frames either does not change or degrades performance.

show that Flare achieves substantial performance gains over the base algorithm RAD (Laskin et al., 2020a). Finally, we conduct a series of ablation studies to stress test the design choices of the Flare architecture.

6.1 DMCONTROL AND EVALUATION METRICS

The DeepMind Control Suite (DMControl) (Tassa et al., 2018), based on MuJoCo (Todorov et al., 2012), is a commonly used benchmark for continuous control from pixels. Prior works such as DrQ (Kostrikov et al., 2020) and RAD (Laskin et al., 2020a) have made substantial progress on this benchmark and closed the gap between state-based and pixel-based efficiency on the simpler environments in the suite, such as Reacher Easy, Ball-in-cup Catch, Finger Spin, Walker Walk, Cheetah Run, Cartpole Swingup. However, current pixel-based RL algorithms struggle to learn optimal policies efficiently in more challenging environments that feature partial observability, sparse rewards, or precise manipulation. In this work, we study more challenging tasks from the suite to better showcase the efficacy of our proposed method. The 5 environments, listed in Figure 5, include Walker Run (requires maintaining balance with speed), Quadruped Walk (partially observable

agent morphology), Hopper Hop (locomotion with sparse rewards), Finger Turn-hard (precise manipulation), and Pendulum Swingup (torque control with sparse rewards). For evaluation, we benchmark performance at 500K and 1M *environment steps* and compare against RAD.

6.2 MAIN RESULTS

Our main experimental results on the five DMControl tasks are presented in Figure 6 and Table 1 (top). We find that Flare outperforms RAD in terms of both final performance and sample efficiency, while being competitive in the remaining environments. Specifically, Flare attains similar asymptotic performance to state-based RL on Pendulum Swingup, Hopper Hop, and Finger Turn-hard. For quadruped walk, a particularly challenging environment due to its large action space and partial observability, Flare learns much more efficiently than RAD and achieves a higher final score. Moreover, Flare outperforms RAD in terms of sample efficiency on all of the core tasks except for walker run shown visualized in Figure 6. The 500k and 1M environment step evaluations in Table 1 show that, on average, Flare achieves **1.9**× and **1.5**× higher scores than RAD at the 500k step and the 1M step benchmarks, respectively.

Though our investigation primarily focuses on these 5 challenging environments, we also show in Appendix A.2 that Flare matches the state-of-the-art on the 6 simpler environments.

6.3 ABLATION STUDIES

We ablate a number of components of the Flare architecture on the Quadruped Walk and Pendulum Swingup environments to stress test the Flare architecture. The results shown in Figure 7 aim to answer the following questions:

Q1: *Do we need latent flow or is computing pixel differences sufficient?* While Flare proposes a late fusion of latent differences with the latent embeddings, a simpler approach is an early fusion of pixel differences with the pixel input, which we call pixel flow. We compare Flare to pixel flow in Figure 7 (left) and find that, while pixel flow outperforms RAD, it is significantly less efficient and less stable than Flare, particularly on Quadruped Walk. This ablation suggests that late fusion temporal information after encoding the image is preferable to early fusion.

Q2: *Are the gains coming from latent flow or individual frame-wise encoding?* Next, we address the potential concern that the performance gain of Flare stems from the frame-wise ConvNet architectural modification instead of the fusion of latent flow. Concretely, we follow the exact architecture and training as Flare, but instead of concatenating the latent flow, we concatenate each frame's latent after the convolution encoders directly as described in Figure 4 (b). This ablation is similar in spirit to the state-based experiments in Figure 3. The learning curves in Figure 7 (center) show that individual frame-wise encoding is not the source of increased performance. While on par with RAD on Pendulum Swingup, on Quadruped Walk frame-wise encoding performs worse. Flare's improved performance over RAD is therefore most likely a result of the explicit fusion of latent flow.

Q3: *How does the input frame count affect performance?* Lastly, we compare stacking 2, 3, and 5 frames in Flare in Figure 7 (right). We find that changing the number of stacked frames does not significantly impact the locomotion task, quadruped walk, but Pendulum Swingup tends to be more sensitive to this hyperparameter. Interestingly, the optimal number of frames for Pendulum Swingup is 2, and more frames can in fact degrade Flare's performance, indicating that the immediate position and velocity information is the most critical to learn effective policies on this task. We hypothesize that Flare trains more slowly with increased frame count on Pendulum Swingup due to the presence of unnecessary information that the actor and critic networks need to learn to ignore.

7 CONCLUSION

We propose Flare, an architecture for RL that explicitly encode temporal information by computing flow in the latent space. In experiments, we show that in the state space, Flare can recover the optimal performance with only state positions and no access to the state velocities. In the pixel space, Flare improves upon the state-of-the-art model-free RAD in terms of both sample efficiency and performance on 4 out of 5 challenging continuous control tasks from DMControl and matches RAD on all the simpler 6 classic tasks. We would like to integrate Flare with model-based RL in the future.

REFERENCES

Artemij Amiranashvili, Alexey Dosovitskiy, Vladlen Koltun, and Thomas Brox. Motion perception in reinforcement learning with dynamic objects. In *Conference on Robot Learning*, pp. 156–168. PMLR, 2018.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemyslaw Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Joao Carreira and Andrew Zisserman. Quo vadis, action recognition? a new model and the kinetics dataset. In *proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6299–6308, 2017.

Yevgen Chebotar, Mrinal Kalakrishnan, Ali Yahya, Adrian Li, S. Schaal, and S. Levine. Path integral guided policy search. *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3381–3388, 2017.

Jeffrey Donahue, Lisa Anne Hendricks, Sergio Guadarrama, Marcus Rohrbach, Subhashini Venugopalan, Kate Saenko, and Trevor Darrell. Long-term recurrent convolutional networks for visual recognition and description. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2625–2634, 2015.

Alexey Dosovitskiy, German Ros, Felipe Codevilla, Antonio Lopez, and Vladlen Koltun. Carla: An open urban driving simulator. *arXiv preprint arXiv:1711.03938*, 2017.

Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE international conference on computer vision*, pp. 6202–6211, 2019.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019a.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pp. 2555–2565. PMLR, 2019b.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. *arXiv preprint arXiv:1710.02298*, 2017.

Divye Jain, Andrew Li, Shivam Singhal, Aravind Rajeswaran, Vikash Kumar, and Emanuel Todorov. Learning Deep Visuomotor Policies for Dexterous Hand Manipulation. In *International Conference on Robotics and Automation (ICRA)*, 2019.

Shuiwang Ji, Wei Xu, Ming Yang, and Kai Yu. 3d convolutional neural networks for human action recognition. *IEEE transactions on pattern analysis and machine intelligence*, 35(1):221–231, 2012.

A. Karpathy, G. Toderici, S. Shetty, T. Leung, R. Sukthankar, and L. Fei-Fei. Large-scale video classification with convolutional neural networks. In *2014 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1725–1732, 2014.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *arXiv preprint arXiv:2004.14990*, 2020a.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. *Proceedings of the 37th International Conference on Machine Learning, Vienna, Austria, PMLR 119*, 2020b. arXiv:2004.04136.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *ICLR*, 2016.

Kendall Lowrey, Svetoslav Kolev, Jeremy Dao, Aravind Rajeswaran, and Emanuel Todorov. Reinforcement learning for non-prehensile manipulation: Transfer from simulation to physical system. In *IEEE SIMPAR*, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

OpenAI, Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafał Józefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, Szymon Sidor, Josh Tobin, Peter Welinder, Lilian Weng, and Wojciech Zaremba. Learning dexterous in-hand manipulation. *CoRR*, abs/1808.00177, 2018.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, et al. Habitat: A platform for embodied ai research. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 9339–9347, 2019.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with momentum predictive representations. *arXiv preprint arXiv:2007.05929*, 2020.

David Silver, Aja Huang, Christopher J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *Nature*, 529:484–503, 2016. URL http://www.nature.com/nature/journal/v529/n7587/full/nature16961.html.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 10 2017. doi: 10.1038/nature24270.

Karen Simonyan and Andrew Zisserman. Two-stream convolutional networks for action recognition in videos. In *Advances in neural information processing systems*, pp. 568–576, 2014.

Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012.

Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning, 2020.

Richard Sutton and Andrew Barto. *Reinforcement Learning: An Introduction*. MIT Press, 1998.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.

Du Tran, Lubomir Bourdev, Rob Fergus, Lorenzo Torresani, and Manohar Paluri. Learning spatiotemporal features with 3d convolutional networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 4489–4497, 2015.

Oriol Vinyals, Igor Babuschkin, Wojciech M. Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H. Choi, Richard Powell, Timo Ewalds, Petko Georgiev, Junhyuk Oh, Dan Horgan, Manuel Kroiss, Ivo Danihelka, Aja Huang, Laurent Sifre, Trevor Cai, John P. Agapiou, Max Jaderberg, Alexander S. Vezhnevets, Rémi Leblond, Tobias Pohlen, Valentin Dalibard, David Budden, Yury Sulsky, James Molloy, Tom L. Paine, Caglar Gulcehre, Ziyu Wang, Tobias Pfaff, Yuhuai Wu, Roman Ring, Dani Yogatama, Dario Wünsch, Katrina McKinney, Oliver Smith, Tom Schaul, Timothy Lillicrap, Koray Kavukcuoglu, Demis Hassabis, Chris Apps, and David Silver. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782): 350–354, 2019. doi: 10.1038/s41586-019-1724-z. URL https://doi.org/10.1038/s41586-019-1724-z.

Aaron Walsman, Yonatan Bisk, Saadia Gabriel, Dipendra Misra, Yoav Artzi, Yejin Choi, and Dieter Fox. Early Fusion for Goal Directed Robotic Vision. In *International Conference on Intelligent Robots and Systems (IROS)*, 2019.

Xiaolong Wang, Ross Girshick, Abhinav Gupta, and Kaiming He. Non-local neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7794–7803, 2018.

Denis Yarats, Amy Zhang, Ilya Kostrikov, Brandon Amos, Joelle Pineau, and Rob Fergus. Improving sample efficiency in model-free reinforcement learning from images. *arXiv preprint arXiv:1910.01741*, 2019.

H. Zhu, A. Gupta, A. Rajeswaran, S. Levine, and V. Kumar. Dexterous manipulation with deep reinforcement learning: Efficient, general, and low-cost. *2019 International Conference on Robotics and Automation (ICRA)*, pp. 3651–3657, 2019.

A APPENDIX

A.1 INTERPRETING FLARE FROM A TWO-STREAM PROSPECTIVE

Let f_{CNN} and o'_t be the pixel encoder and the augmented observation in Flare. Then, $z_t = f_{\text{CNN}}(o'_t)$ denotes the latent encoding for a frame at time t. By computing the latent flow $\delta_t = z_t - z_{t-1}$, Flare essentially approximates $\frac{\partial z_t}{\partial t}$ via backward finite difference. Then following chain rule, we have

$$\frac{\partial z}{\partial t} = \frac{\partial z}{\partial o'} \cdot \frac{\partial o'}{\partial t} = \frac{f_{\text{CNN}}(o')}{\partial o'} \cdot \text{dense optical flow}$$

indicating that Flare eventually uses dense optical flow by propagating it through the derivative of the trained encoder. While the two-stream architecture trains a spatial stream CNN from RGB channels and a temporal stream from optical flow separately, Flare can be interpreted as training one spatial stream encoder from the RL objective and approximate the temporal stream encoder with its derivative.

A.2 SOLVED DMCONTROL ENVIRONMENTS

We show in Figure 8 that Flare matches the model-free state-of-the-art on the six most commonly benchmarked DMControl environments in Laskin et al. (2020a); Kostrikov et al. (2020); Hafner et al. (2019a). These environments are considered simple because the state-of-the-art pixel-based SAC variants are as efficient as state-based SAC, suggesting that the pixel-based SAC performance is effectively saturated. For this reason, we benchmark against more challenging environments in the main text.

Figure 8: Pixel-based RAD and Flare on classic environments: We compare Flare to RAD on six classic environment that can already be solved by RAD. Flare matches the performance with RAD on all of them.

A.3 IMPLEMENTATION DETAILS FOR PIXEL-BASED EXPERIMENTS

Hyperparameter	Value
Augmentation	Random Translate
Observation size	$(100, 100)$
Augmented size	$(108, 108)$
Replay buffer size	100000
Initial steps	10000
Training environment steps	$1.5e6$ pendulum swingup
	$2.5e6$ others
Batch size	128
Stacked frames	2 pendulum swingup
	3 others
Action repeat	2 walker run, hopper hop
	4 others
Camera id	2 quadruped, walk
	0 others
Evaluation episode length	10
Hidden units (MLP)	1024
Number of layers (MLP)	2
Optimizer	Adam
$(\beta_1, \beta_2) \rightarrow (f_{CNN}, \pi_\psi, Q_\phi)$	$(.9, .999)$
$(\beta_1, \beta_2) \rightarrow (\alpha)$	$(.5, .999)$
Learning Rate (π_ψ, Q_ϕ)	$2e-4$
Learning Rate (f_{CNN})	$1e-3$
Learning Rate (α)	$1e-4$
Critic target update frequency	2
Critic EMA τ	0.01
Encoder EMA τ	0.05
Convolutional layers	4
Number of CNN filters	32
Latent dimension	64
Non-linearity	ReLU
Discount γ	0.99
Initial Temperature	0.1

A.4 IMPLEMENTATION DETAILS FOR STATE-BASED MOTIVATION EXPERIMENTS

Hyperparameter	Value
Replay buffer size	2000000
Initial steps	5000
Batch size	1024
Stacked frames	4 Flare, Stack SAC;
	1 otherwise
Action repeat	1
Evaluation episode length	10
Hidden units	1024
Number of layers	2
Optimizer	Adam
$(\beta_1, \beta_2) \rightarrow (f_{CNN}, \pi_\psi, Q_\phi)$	$(.9, .999)$
$(\beta_1, \beta_2) \rightarrow (\alpha)$	$(.9, .999)$
Learning Rate (π_ψ, Q_ϕ)	$1e-4$
Learning Rate (α)	$1e-4$
Critic target update frequency	2
Critic EMA τ	0.01
Non-linearity	ReLU
Discount γ	0.99
Initial Temperature	0.1