ARC-Encoder: learning compressed text representations for large language models

Abstract

Recent techniques such as retrieval-augmented generation or chain-of-thought reasoning have led to longer contexts and increased inference costs. Context compression techniques can reduce these costs, but the most effective approaches require fine-tuning the target model or even modifying its architecture. This can degrade its general abilities when not used for this specific purpose. Here we explore an alternative approach: an encoder that compresses the context into continuous representations which replace token embeddings in decoder LLMs. First, we perform a study of training strategies and architecture choices for the encoder. Our findings led to the design of an Adaptable text Representations Compressor, named ARC-Encoder, which outputs x-times fewer continuous representations (typically $x \in \{4, 8\}$) than text tokens. We evaluate ARC-Encoder across a variety of LLM usage scenarios, ranging from in-context learning to context window extension, on both instruct and base decoders. Results show that ARC-Encoder achieves strong performance on several benchmarks and tasks while improving computational efficiency at inference. Finally, we demonstrate that our models can be adapted to multiple decoders simultaneously, allowing a single encoder to generalize across different decoder LLMs. This makes ARC-Encoder a flexible and efficient solution for portable encoders that can support multiple LLMs with only small MLPs.

1 Introduction

As their use expands, LLMs are required to process increasingly long contexts to incorporate detailed user prompts or external knowledge retrieved from large corpora as in retrieval-augmented generation (RAG) systems (Lewis et al., 2021). However, this implies a *large computational cost* at inference due to the quadratic complexity of Transformer attention mechanisms (Tay et al., 2022). Furthermore, using longer contexts can dilute interesting information leading to poor downstream results or can even reach the *context window limit* of the LLM, which damages the model capacities.

To address this issue, context compression is a promising solution. It reduces input length while preserving the semantics necessary for accurate generation (Liu et al., 2025). Techniques fall into two main categories: *hard compression*, which prunes, summarizes or deletes tokens (Jiang et al., 2023b), offering interpretability and model-agnosticism but limited compression; and *soft compression*, which encodes context into dense vectors, e.g. memory tokens and gist tokens (Mu et al., 2024; Ge et al., 2024). While achieving higher compression, soft methods often require training specialized encoders and even adapting the decoder itself to be able to process these compressed representations (Louis et al., 2025a; Tang et al., 2025).

Our work aims at leveraging LLMs' compression ability in cases where documents should be processed on the fly. Most importantly, we constrain ourselves not to modify the decoder so that the method remains plug-and-play while maintaining flexibility between compression and accuracy on downstream tasks. In this paper, we introduce an Adaptable text Representations Compressor ("ARC-Encoder") that produces *pooled tokens*, optimized to be directly consumable by a decoder in the same way as standard input tokens (injected after the embedding matrix). By preserving the few-shot abilities of models (Brown et al., 2020), we ensure compatibility with the standard question-answering (QA) evaluation set-up, such as 5-shot evaluation using exact match (EM). We achieve nearly the same accuracy as a decoder operating on full text, even at a $4\times$

pooling factor while using an encoder adaptable to several decoders by means of a small MLP which has less than 1% of the encoder parameters. Our approach achieves strong results among models that do not fine-tune the decoder while generalizing well to various tasks and domains. We further adapt it to context extension applications and show that it works in a zero-shot setting using instruct models as decoders.

Here is a summary of our main contributions:

- We introduce ARC-Encoder, a method to compute compressed text representations that replace the raw text input in LLMs. Our approach reduces the input sequence length, *without requiring any modification to the decoder model*. ARC-Encoder preserves strong performance across various benchmarks and scenarios, including in-context learning (ICL).

- We show that a single encoder can be trained to work with multiple decoders, requiring less than 1% new parameters per LLM. ARC-Encoder can be adapted to new decoders with minimal adjustment.

- ARC-Encoder can be trained to extend a decoder context size, by compressing chunks of a large document in parallel, showing competitive results on long-context benchmarks.

- Finally, we show that both pretraining and fine-tuning are key to the success of our approach. We also find that the compressed representations of Wikipedia require memory on the same order as that needed to store the raw text, allowing to precompute representations.

2 Related work

Encoder-Decoder architectures. Text auto-encoders have long been studied to improve transformers on specific downstream tasks. They process the input into dense embeddings to reduce processing cost while preserving or improving model accuracy. For instance, Atlas (Izacard et al., 2022) retrieves and encodes multiple relevant passages before decoding with a focus on knowledge intensive tasks. RAVEN (Huang et al., 2024) uses a similar retrieval-augmented encoder-decoder structure improving in-context learning abilities while using less compute. More recently, Zhang et al. (2025) propose an asymmetric architecture, closer to ours, where a smaller encoder aims at improving the decoder generation through cross-attention under similar inference budget. As in our work, they experimented with combination of different-sized models.

Context Compression. Context compression reduces the number of tokens processed by a model to improve the efficiency of inference. There are two main approaches. *Hard compression* methods, such as LLMLingua (Jiang et al., 2023b), operate directly in the text space by removing tokens from prompts. It aims at reducing their length while preserving the performance of the model. In contrast, we perform *soft compression* which involves learning continuous compressed representations. This line of work began with gist tokens (Mu et al., 2024), which summarize task instructions into a few tokens by modifying the attention matrix to force generated tokens to only attend to gist tokens. Similarly, in summary vectors or memory tokens (Chevalier et al., 2023; Ge et al., 2024), learnable vectors which come from an encoder are prepended to the input sequence. These vectors serve as condensed representations of the full sequence when passed through the decoder. These methods typically rely on a pretraining phase to align the encoder's output with the decoder's hidden states, followed by fine-tuning of both encoder and decoder to fully leverage the compressed representations (Louis et al., 2025a;b). Recently, more similarly to our pooling method, Tang et al. (2025) explore using merged tokens to replace memory ones. They perform several training stages on the encoder, but also on the decoder in contrast to our work. Fine-tuning the decoder often degrades performance on standard tokens compared to our method which enables to use compressed tokens as well as standard ones. Other approaches explore the use of pre-computed text embeddings as memory tokens, reaching higher pooling factors (up to ×150) with xRAG (Cheng et al., 2024) but performing poorly on certain benchmarks and lacking compression flexibility. All these context compression methods rely on the intrinsic compression capacity of LLMs. Indeed, Kuratov et al. (2025) has proven that an LLM decoder can be used to directly compress a text passage of roughly 1568 tokens into just one 4096-dimensional vector. More recently, Eyuboglu et al. (2025) leveraged this property to produce sets of compressed KV-caches for frequently used long documents. Recently, alternative methods use vision encoders (Xing et al., 2025) to produce compressed textual representations from text rendered as image.

Long Context. Recent work on long-context language modeling combines fine-tuning with extended positional encoding strategies. Together AI (2023) fine-tunes Llama2 7B to handle 32k-token inputs using position interpolation (Chen et al., 2023). Zhang et al. (2024) extends context length by inserting activation "anchors" into the hidden states of the model, requiring modification and fine-tuning of the target LLM itself to compress. In contrast, Yen et al. (2024) introduce a lightweight encoder that processes long inputs in parallel and passes compressed representations to a decoder via learned cross-attention, allowing efficient long-sequence handling. Similar works such as Han et al. (2024) rely on additional chunking strategy in addition of the encoder to also compress information. Our work follows the idea of Yen et al. (2024) while producing fewer tokens and keeping the decoder untouched.

3 Method

3.1 Architecture

The overall architecture that we consider comprises a text *encoder* and an *MLP projector*, together forming a trainable ARC-Encoder, followed by the frozen target *decoder*. The encoder is based on an LLM transformer, from which we remove the output head and the causal mask as usually done for sentence embedders (Lee et al., 2025). We add a pooling mechanism that reduces the number of elements in the sequence from n to $\frac{n}{x}$ with x the pooling factor (PF). The MLP projector is a 2-layer MLP without activation, mapping the encoder output to the embedding dimension of the decoder through a dimensional bottleneck. The decoder remains unchanged, as opposed to the encoder and MLP that are trained. The compressed continuous representations from the ARC-Encoder are used instead of the token embeddings in the decoder.

3.2 Pooling method

Most context compression works use learned or memory tokens as compressed representations. This makes it harder to effectively compress sequences of various lengths, as the number of output representations is fixed. Instead, we pool hidden state vectors directly, leading to a fixed pooling factor, independent of the input sequence length (Suganthan et al., 2025).

We performed an empirical study on how and where to pool tokens to obtain compressed continuous representations. As illustrated in Fig. 1, pooling is performed in the self-attention module. We average consecutive queries to reach the targeted pooling factor, while keys and values remain unchanged. For a PF of 2 for example (denoting the encoder as 'ARC$_2$-Encoder'), we group the tokens of the sequence two-by-two. We merge their queries in the last self-attention module, by averaging their continuous hidden states. Then, these pooled queries attend the non-compressed keys and values, mimicking a standard self-attention, but with two-times fewer queries, resulting in a pooling factor of two. We explored inserting the pooling mechanism earlier in the encoder, but this lead to poorer performance. This follows the intuition that the information should be as processed as possible before pooling (Tang et al., 2025).

Figure 1: **Pooling in ARC$_2$-Encoder**. In the last SA, queries are merged by pairs of successive tokens.

3.3 Training

Base pretraining. Memory tokens (Ge et al., 2024) show the importance of the reconstruction task when training the model to create easily decompressible continuous representations. However, pure reconstruction is easier than compressing contexts for downstream tasks. In fact, with proper training, our auto-encoder architecture achieves near-perfect reconstruction at a × pooling factor on relatively short sequences (up to

a) reconstruction   b) continuation

Figure 2: **ARC2-Encoder pretraining tasks**. The encoder, special tokens and the MLP are trained through two alternating tasks: a) Reconstruction: compressed tokens are given to the decoder which is teacher-forced to replicate the full text tokens; b) Continuation: a subpart of the tokens in the sequence are compressed and the decoder is teacher-forced to continue starting from the partially compressed sequence.

around 128 tokens). Unfortunately, these compressed representations cannot be well exploited by the decoder on downstream tasks, as the model tends to regurgitate the entire context, instead of extracting pertinent information from it. Thus, we consider a second pretraining task, continuation, which is better aligned with inference-time behavior. It consists in replacing subsequences of natural text by their compressed representations, and to teacher-force the continuation immediately following compressed segments. We alternate between these two pretraining tasks as summarized in Fig. 2, and use the standard cross-entropy loss. Additionally, we append special learned tokens `<Cont>` and `<Rec>` after each compressed sequence. The two special tokens are crucial to specify the task during pretraining and enable good downstream results.

Fine-Tuning. After pretraining, our ARC-Encoder can be flexibly adapted to a range of specific tasks. In particular, it can be used to condition a frozen decoder on task-specific inputs, allowing task specialization without modifying the decoder itself. To preserve the decoder's few-shot capabilities, we optionally include a small number of in-context examples in the continuation objective–interleaving compressed documents, full-text queries and answers–following a structured prompt template described in Appendix C. To compute the loss, we mask all tokens except the ones that continue the last compressed sequence, corresponding to the final answer in a few-shot setting. This design encourages generalization and preserves ICL possibilities at inference time with every document being compressed. Furthermore, we demonstrate that zero-shot abilities of instruct decoders can also be preserved; it simply requires to use a different pretraining and fine-tuning template. Once pretrained, ARC-Encoder can be fine-tuned to master in-context learning, long context understanding, or other downstream tasks. The pooling factor between the two training stages can be changed. It leads to improved models when pretraining with a higher factor than for fine-tuning, see Appendix A.2. We remind that only the encoder is fine-tuned, and that the decoder is unchanged.

Multi-Decoder Training. To improve the generality of our method, we design a compressor capable of generating token representations that can be used by multiple decoders without any modification. It is a nontrivial challenge due to inherent discrepancies between the hidden-state spaces of different decoder architectures. To overcome this, we employ a shared encoder but we specialize a projector layer (the MLP in Fig. 2) and the special tokens. This set of learned parameters accounts for less than 1% of the encoder's weights, enabling decoder-specific adaptation with minimal overhead. We find that training with an alternating objective provides the most stable and effective results. At each training step we sample a decoder uniformly and update only its associated projector as well as the shared encoder. This strategy ensures balanced exposure across decoders while maintaining the generalization capacity of the shared encoder.

4 Experiments

In this section, we first describe the main settings used for our experiments. Second, we evaluate our method on various downstream tasks that use contexts, such as question answering with retrieved documents or reading comprehension. The contexts for these tasks tend to be short, ranging from 30 to 1,500 tokens. Thus, we also evaluate ARC-Encoders for long-context understanding applications. Finally, we report the results of our ablation study on training and architecture as well as an analysis of the memory used to encode Wikipedia with continuous representations from ARC-Encoder.

4.1 Experimental setting

Models. We perform experiments using different decoders: Llama3.1 8B (Grattafiori et al., 2024), Mistral 7B (Jiang et al., 2023a), both base models, and Llama2 7B Chat (Touvron et al., 2023). We design our ARC-Encoder with Llama3.2 3B as the backbone: we remove its last two layers and no causal mask is applied. The MLP consists of two layers: the first projects the 3072-dimensional vectors from the encoder to 2048 dimensions, and the second projects these vectors to 4096-dimensional hidden states, matching the decoder dimension. During inference, we append the special `<Cont>` token after every sequence of compressed tokens.

Training & Datasets. By default, we decide to train all layers of the encoder, including the embedding matrix, using AdamW optimizer (Loshchilov & Hutter, 2019). For pretraining, we use data from Common Crawl that has been filtered and processed using dactory[1]. ARC-Encoder is pretrained on approximately 2.6B tokens. For fine-tuning, we use two different mixes of synthetic and supervised datasets: one for standard context compression benchmarks using base models as decoders and another for long-context benchmarks using an instruct decoder. See the following sections and Appendix C.3 for more details.

4.2 Context compression

Benchmarks. We evaluate our method on question answering, translation, and summarization tasks. For question answering, we use HotpotQA (Yang et al., 2018, HQA) with the *distractor* setting, Natural Questions (Kwiatkowski et al., 2019, NQ), TriviaQA (Joshi et al., 2017, TQA) and SQuAD (Rajpurkar et al., 2016). Top-5 passages are retrieved using NV-Embed v2 (Lee et al., 2025) from Atlas (Izacard et al., 2022) Wikipedia chunks, simulating a RAG setup. We report exact match (EM) as the main metric, where EM = 1 if the normalized predicted and reference answers exactly match. For translation, we evaluate on FLORES (Goyal et al., 2021) averaging BLEU scores across four directions: English to Danish, French, German, and Spanish. Summarization performance is evaluated on CNN-DailyMail using ROUGE-L, which aligns well with human judgments for summarization abilities according to Zhang et al. (2023). All models are evaluated via 5-shot with compressed contexts. The reported pooling factor reflects the per-context ratio of original tokens (using the decoder tokenizer) to compressed tokens. See Appendix D.2 for evaluation details.

Setting & Baselines. Unlike prior works in the context compression literature that often report zero-shot accuracy with instruct decoders—potentially inflating performance when models simply replicate the context—our use of EM aims at better capturing real-world LLM usage by rewarding answers following the few-shot format patterns. We believe it better measures the encoder abilities to produce useful representations, from which the decoder can extract information. Thus, we focus on base model decoders for context compression evaluations. We first set two baselines that reflect the decoder intrinsic abilities. In the first one, denoted *closed-book*, the decoder relies only on its parametric knowledge and in the second one, called *open-book*, the decoder has access to uncompressed documents in its context.

For meaningful comparisons, we select a diverse set of strong baselines that capture different approaches to context compression. These include: i) LLMLingua2 (Pan et al., 2024), which performs hard compression; ii) ICAE (Ge et al., 2024), a soft compression approach using memory tokens; iii) xRAG (Cheng et al., 2024), which relies on pre-computed embeddings for retrieval-augmented generation; iv) PISCO (Louis et al., 2025a), which fine-tunes both the encoder and decoder and states that pretraining is not necessary. We re-implemented the last three baselines using our decoder, fine-tuning dataset, and interleaved fine-tuning task

---

[1] https://github.com/kyutai-labs/dactory

Table 1: **Main comparison of ARC-Encoder and other models**. 'PF' (pooling factor): the token reduction factor (e.g., 4×) for fixed-ratio methods or the number of compressed tokens used, e.g. ∼ 16, when this number is fixed as this yields benchmark-dependent ratios; 'Param.': number of parameters of the encoder; 'Avg. length': mean number of tokens per context document. The superscript on ARC-Encoder indicates if the model is specifically trained for one decoder (^{M} for Mistral or ^{L} for Llama) or both simultaneously ($^\otimes$). † marks modified re-implementations, see details in Appendix D.1. Best context compression results are in **bold**, second best are underlined.

	Methods	PF	Param.	NQ	TQA	HQA	SQuAD	FLORES	CNN	Avg.
	Avg. length			155	152	1479	185	30	956	
Mistral 7B decoder	*closed-book*	∞		29.1	62.4	22.8	17.1			
	open-book	1×		39.9	70.5	48.3	77.7	31.3	27.2	49.2
	ICAE-like†	∼ 32	7.2B	36.5	66.7	24.3	58.8	28.3	15.8	38.4
	xRAG-like†	∼ 1	7.1B	30.7	65.2	21.5	23.9	0.9	14.6	26.1
	LLMLingua2	1.9×	0.6B	38.8	69.0	43.7	59.2	12.6	24.9	41.4
	PISCO-like†	∼ 32	7.2B	34.7	68.5	24.9	38.2	33.6	19.2	36.5
		4×	—	36.6	69.2	29.4	48.1	**34.5**	19.3	39.5
	ARC$_4$-Encoder$^\otimes$	4×	3.0B	38.2	**70.4**	40.8	69.2	29.5	**25.6**	45.6
	ARC$_4$-Encoder^M	4×	—	**39.0**	68.9	**45.1**	**71.1**	31.0	23.8	**46.5**
	ARC$_8$-Encoder^M	8×	—	38.4	67.9	40.8	62.0	28.3	22.9	43.4
	Avg. length			135	133	1285	164	27	855	
Llama3.1 8B decoder	*closed-book*	∞		25.4	60.6	21.6	15.3			
	open-book	1×		38.6	67.1	47.1	72.2	32.8	26.5	47.4
	ICAE-like†	∼ 32	7.6B	38.4	67.3	20.5	61.6	31.3	17.3	39.4
	xRAG-like†	∼ 1	7.1B	28.0	62.1	21.7	22.3	3.4	12.7	25.0
	LLMLingua2	2.0×	0.6B	36.1	66.3	45.2	58.8	13.6	23.8	40.6
	PISCO-like†	∼ 32	7.6B	35.1	69.4	30.6	40.5	35.2	19.7	38.4
		4×	—	37.9	70.5	37.0	57.2	**36.5**	20.7	43.3
	ARC$_4$-Encoder$^\otimes$	4×	3.0B	39.6	**70.8**	43.6	71.8	32.8	**26.1**	47.5
	ARC$_4$-Encoder^L	4×	—	**39.7**	70.1	**46.9**	**74.0**	33.7	23.7	**48.0**
	ARC$_8$-Encoder^L	8×	—	38.9	69.0	42.8	66.0	30.6	22.8	45.0

format to ensure a consistent few-shot evaluation setup while preserving each method's core design. This allows direct comparisons with a common evaluation protocol; See Appendix D.1 for implementation details.

We fine-tune models on a mix of synthetic translation data and supervised datasets (QA, summarization, paraphrasing, and reading comprehension), explicitly excluding the training sets of our evaluation benchmarks. This setup better highlights our method's generalization ability (using the train sets of benchmarks strongly improves results, sometimes outperforming the *open-book* results as shown in Tab. 6 of the Appendix). Since each data sample is drawn from one of the sub-datasets, fine-tuning involves stochasticity; unless otherwise specified, we fix the random seed to 0. For our final ARC-Encoder we follow the best pretraining / fine-tuning pooling factor pairs as shown in Fig. 6. This leads to ARC$_4$-Encoder using the same pretrained encoder as ARC$_8$-Encoder, only with its fine-tuning performed at a pooling factor of 4.

Results. In Tab. 1, we report our main results on context compression using the best checkpoints of ARC-Encoder. First, we observe that our models outperform the *closed-book* baseline, showing that frozen decoders can extract useful information for downstream tasks from the compressed tokens. We also note that ARC-Encoder tends to outperform the baselines more on tasks where the decoder cannot rely on its own parametric memory, such as reading comprehension (SQuAD) or summarization (CNN). Furthermore, we observe that both specialized and shared ARC-Encoder perform better when paired with the Llama3.1 8B decoder, likely because it belongs to the same model family as our encoder backbone based on Llama3.2 3B. Finally, ARC$_4$-Encoder nearly matches the *open-book* baseline without altering the decoder and while achieving ×1.8 gains of prefilling FLOPs, as profiled in § 4.5, larger pooling factors in Appendix A.5.1.

Please note that for certain baselines, our results differ from the ones reported in previous work. This is due to the different setting that we consider in this paper: 1) using exact match as the metric, 2) excluding the training sets of the benchmarks from the fine-tuning data and 3) using base models instead of instruct ones.

Encoder adaptation to multi-decoder. Through multiple experiments, we found that a single encoder can be trained to be used by multiple decoders. More specifically, during both pretraining and fine-tuning, we use a joint learning setup where at each training step, we sample which decoder to use among the two targets. To improve performance, we introduce a separate MLP projector for each decoder. This allows lightweight specialization of compressed representations, adding only 15M parameters per decoder. We report results in Tab. 1, showing that in average, the common encoder, ARC-Encoder$^\otimes$, loses less than 1.0 point compared to its specialized counterparts. More encoder-decoder pairings are tested in Appendix A.3.

Adaptation to new decoders. Once our ARC-Encoder has been trained for a decoder, we can adapt it to new decoders with minimal adjustments. Indeed, we solely learn a new MLP projector and special tokens to feed a third decoder, OLMo-7B (Groeneveld et al., 2024), while keeping the encoder frozen. Fine-tuning leads to better results than the *closed-book* baseline by only training 15M parameters. However, the score gap with the *open-book* setting remains relatively larger than when training with the alternating decoder objective as shown in Tab. 1 with Llama and Mistral models. Interestingly, on benchmarks where the decoder was limited by its context window, such as HotpotQA, using ARC$_4$-Encoder outperforms the *open-book* setup.

Figure 3: Extending an ARC-Encoder to a new decoder.

Table 2: **Adaptation to a new decoder**. Due to OLMo 7B 2048-token context window, we truncate documents for *open-book* baseline to 400 tokens. Per decoder specific parameters are reported.

	Methods	PF	Param.	**NQ**	**TQA**	**HQA**	**SQuAD**	**FLORES**	**CNN**	**Avg.**
OLMo-7B	*closed-book*	∞		19.5	48.3	17.8	11.2			
	open-book	$1\times$		35.3	64.8	22.9	67.9	22.2	24.2	39.6
	ARC$_4$-Encoder^M	$4\times$	15M	31.5	62.5	26.5	46.4	17.2	19.1	33.9
	ARC$_4$-Encoder$^\otimes$	$4\times$	$-$	33.1	63.1	25.0	44.6	17.1	18.9	33.6

4.3 Long Context

In this section, we adapt our fine-tuning method to handle longer contexts, testing our architecture on long-context understanding tasks. We pretrain and fine-tune an ARC$_8$-Encoder paired with an instruct decoder Llama2 7B Chat (Touvron et al., 2023). During fine-tuning, we encode fixed-size chunks of long documents in parallel and feed them to the decoder by concatenating the compressed tokens of each chunk. For fine-tuning, we synthesize a QA and summarization dataset based on concatenated Wikipedia chunks, PG-19 books (Rae et al., 2019) and ArXiv papers from RedPajama (Weber et al., 2024) using Gemma3-27B (Team et al., 2025). Then, we divide each context in up to 32 chunks of 1024 tokens. Similarly at inference, contexts are truncated to 32k tokens and then ARC$_8$-Encoder processes chunks in parallel. In this setting, we remove the special tokens, as instruction prompts play a similar role, see Appendix C for technical details.

Benchmarks & Models. For long-context understanding, we report F1 score on NarrativeQA and QASPER and report Rouge-L on GovReport and QM-Sum validation sets from the ZeroSCROLLS benchmark (Shaham et al., 2023), a suite of zero-shot long-context understanding tasks. Specifically, we adopt the task formats and instructions as used in Yen et al. (2024)[2]. On these benchmarks, we compare our model to Llama2 7B Chat, which is constrained by a context window of 4096 tokens, as well as to open-source models specifically designed to extend its limited context window. These include Llama2-32k Instruct (Together AI, 2023), which relies on positional interpolation combined with fine-tuning, and CEPED (Yen et al., 2024),

---

[2]https://github.com/princeton-nlp/CEPE

which employs a lightweight encoder to process chunks of input in parallel, feeding their representations into a decoder through learned cross-attention layers.

Table 3: **Long-context evaluation on long-context benchmarks**. The token count includes all tokens fed to the decoder. CEPED uses 2k decoder tokens plus encoder-side tokens.

Models	Max. Tokens	NQA	Qspr	GvRp	QM-Sum
Llama2 Chat	4k	16.1	17.2	15.7	19.8
+ CEPED	2k + 30k	20.5	19.7	12.7	19.7
Llama2-32k Instruct	32k	14.2	16.4	17.8	17.6
ARC_8-Encoder + Llama2 Chat	4k (32k//8)	27.5	28.3	14.1	19.1

Results. In Tab. 3, we show that feeding compressed tokens from ARC_8-Encoder to Llama2 Chat improves long-context QA performance. It allows the model to process up to 8× more input than its original context window. This also shows that the decoder can interpret the compressed tokens without any parameter modification. Thus, a small model's context window can be extended simply by training an external compressing encoder. On some tasks, our approach even outperforms methods that expand Llama2's context window through new learned internal modules or full-model fine-tuning. This advantage may stem partly from our synthesized fine-tuning dataset, which matches the answer-length distributions of evaluation benchmarks, as other models do not fine-tune specifically on these tasks. In Appendix A.7, we show that ARC-Encoder achieves strong and more consistent fine-grained retrieval performance across varying context lengths than other tested models. Crucially, our approach is unique in leaving the decoder unchanged, ensuring consistent behavior across standard tasks while significantly enhancing long-context understanding. While we demonstrate this capability by extending Llama2, we leave scaling to longer contexts (e.g., 128k tokens) for future work, as such an expansion would necessitate specialized datasets and substantial computational budgets.

4.4 Compression Ablations

In this section, we discuss key design choices of our method. We compare context compression results using the same evaluation setting as in Tab. 1, mostly showing the average score on all these benchmarks. Unless stated otherwise, models are pretrained and then fine-tuned using a pooling factor of 8 with the Mistral 7B decoder. To reduce the computation costs of these ablations we pretrained on approximately 2B tokens only, roughly 75% of the tokens used for models in Tab. 1. Additional details are provided in Appendix C.1.

Training objective. In contrast to Louis et al. (2025a), we show that pretraining is essential for our approach. While fine-tuning is also crucial, it cannot provide competitive results on downstream tasks on its own. Long pretraining is essential for aligning ARC-Encoder outputs with the decoder's hidden state space. For example, after 20k pretraining steps, we observe an improvement of approximately +16 points on the average score, while after 80k steps, the improvement reaches +19 points, compared to directly fine-tuning without pretraining. Without fine-tuning the decoder fails to use the compressed context leading to large performance drop in translations, reading comprehension and summarization.

Table 4: Impact of pretraining reconstruction ratio.

% Rec.	Avg.
0%	39.8
20%	**41.6**
50%	41.5
100%	37.5

Beyond pretraining length, the choice of pretraining tasks also proves critical: Tab. 4 shows that omitting reconstruction or using too little continuation leads to substantial performance drops. In practice, early training updates mainly reduce the reconstruction loss, suggesting that the encoder and MLP first learn to produce correctly aligned compressed representations with the embedding space of the decoder, after which the continuation objective encourages representations that the LLM can use effectively for downstream generation. We also tried adding context distillation as in Cheng et al. (2024) during fine-tuning but it did not improve results while adding a large computational overhead.

Table 5: **Ablations on encoder design**. *Default setting* corresponds to ARC_8-$Encoder^M$ with only 60k pretraining steps. Results are averaged over 3 seeds, with standard deviations shown in indices.

	Param.	**NQ**	**TQA**	**HQA**	**SQuAD**	**FLORES**	**CNN**	**Avg.**
Default setting	3.0B	$36.9_{\pm0.2}$	$67.2_{\pm0.3}$	$39.9_{\pm0.4}$	$58.3_{\pm2.0}$	$27.4_{\pm0.3}$	$20.1_{\pm0.1}$	$41.7_{\pm0.4}$
How to truncate the encoder?								
Truncate 0 layer	3.2B	$38.8_{\pm0.3}$	$67.7_{\pm0.3}$	$39.4_{\pm0.9}$	$61.6_{\pm0.8}$	$26.9_{\pm0.2}$	$20.3_{\pm0.1}$	$42.4_{\pm0.3}$
Truncate 4 layers	2.8B	$37.6_{\pm0.3}$	$67.5_{\pm0.3}$	$39.1_{\pm0.6}$	$60.1_{\pm1.3}$	$25.0_{\pm0.6}$	$20.4_{\pm0.3}$	$41.6_{\pm0.3}$
Truncate 21 layers	1.1B	$37.0_{\pm0.3}$	$67.3_{\pm0.1}$	$32.5_{\pm0.2}$	$52.1_{\pm0.5}$	$23.5_{\pm0.2}$	$19.2_{\pm0.3}$	$38.6_{\pm0.1}$
How to pool?								
by 2 every last layers	3.0B	$38.2_{\pm0.6}$	$68.4_{\pm0.4}$	$40.0_{\pm0.2}$	$61.1_{\pm0.6}$	$26.7_{\pm0.3}$	$20.1_{\pm0.1}$	$42.4_{\pm0.2}$
by 2 every two layers	–	$38.3_{\pm0.2}$	$68.1_{\pm0.6}$	$38.9_{\pm0.4}$	$61.1_{\pm1.3}$	$26.4_{\pm0.2}$	$20.0_{\pm0.2}$	$42.1_{\pm0.3}$
How to modify the encoder?								
w LoRA (all, rank= 128)	–	$38.8_{\pm0.4}$	$67.0_{\pm0.5}$	$37.0_{\pm0.2}$	$57.7_{\pm1.4}$	$27.0_{\pm0.1}$	$19.1_{\pm0.5}$	$41.1_{\pm0.4}$
w causality	–	$38.7_{\pm0.3}$	$67.9_{\pm0.6}$	$37.4_{\pm0.3}$	$57.3_{\pm1.1}$	$27.0_{\pm0.3}$	$19.4_{\pm0.1}$	$41.3_{\pm0.2}$

Encoder Architecture. This ablation explores design choices for reducing encoder size or boosting performance. Thanks to strong results in multi-decoder and long-context applications, we keep the default setting architecture in Tab. 1 for consistency reasons, though other designs may excel in other use cases. Tab. 5 shows the trade-off between encoder parameters and performance when truncating layers of the LLM backbone. We observe the same trade-off when using LoRA instead of full fine-tuning. We maintained full fine-tuning as our default setting to minimize the number of hyperparameters.Alternative pooling schedules also look promising: pooling every two tokens in the last layers performs better than our default at the same pooling factor, suggesting pooling strategies could be adapted to the target pooling factor. Adding special learned tokens is particularly useful to help encoder generalize to new decoders. We chose to remove causality from our standard configuration because it limits the exploration of non-causal pooling strategies and results in slightly worse performance on reading comprehension tasks without providing significant benefits.

Pooling. The pooling operation should merge information from continuous representations while still producing vectors interpretable by the decoder. We experiment with memory tokens, the standard approach in the field. This method performs poorly as sequence length increases (see Tab. 8 in appendix), since the effective compression becomes higher. We also tested k-means clustering, but this merging of potentially distant tokens proved harmful especially in translation tasks. It assumes in addition a non-causal training of the encoder, failing completely without it. The most effective poolings instead use contiguous tokens, either by averaging them as in Fig. 1, or by selecting the last token of each segment. Since averaging proved more robust in the multi-decoder setting, we choose it as our default method. While we explored dynamic merging strategies to achieve a specific average pooling factor, these initial attempts yielded variable results, suggesting that further refinement of the merging logic is required.

4.5 Profiling

By compressing context we aim at speeding up inference as well as reducing the computations. In practice, we evaluate these benefits using Torch Profiler[3] measuring CUDA execution time (s) and tera FLOPs (TFLOPS) for the compression, prefilling and decoding stages with various prompt context lengths and various numbers of tokens to generate. All experiments use Mistral 7B decoder and are run in float32 on one NVIDIA H100 GPU with a batch size of 1. We force the decoder to continue its context prompt, compressed or not, and generate $n \in \{1, 100\}$ tokens. As shown in Fig. 4, generation is less costly in terms of compute when using compressed tokens by ARC-Encoder. The compute cost of compression is amortized during the prefilling phase since the decoder has fewer tokens to process. In terms of memory, the compressed representations

---

[3]https://docs.pytorch.org/tutorials/recipes/recipes/profiler_recipe.html

(a) Number of TFLOPs

(b) CUDA time (s)

Figure 4: **Measured computational costs**. (a) TFLOPs and (b) CUDA time in seconds for the continuation of a book (PG19) for various prompt lengths and numbers of tokens to generate on one NVIDIA H100.

could be pre-computed on another GPU as shown in § 4.6. It would use 6GB of memory in bfloat16 for our standard model but could be reduced by training smaller ARC-Encoder as experimented in Appendix A.8.

4.6 Memory Analysis

When compressing contexts on the fly, ARC$_4$-Encoder already leads to a 1.8× speed-up compared to using the natural text. In the case where contexts are potentially used multiple times, such as in RAG systems, even greater speed-ups could be achieved by *pre-computing* the compressed representations and storing them. This option is only viable if the size of compressed representations is roughly the same as the original text. Here, we explore the following tradeoffs to reduce the size of compressed representations: 1) changing the pooling factor, 2) reducing the dimension of the MLP bottleneck and 3) quantizing the representations using product quantization (Jégou et al., 2011, PQ), by increasing the dimension of the sub-quantizers while keeping the number of centroids fixed. We report results in Fig. 5, showing that by combining these different methods (bottleneck dimension varies within curves of the same color, and markers indicate the pooling factor), encoding English Wikipedia with ARC-Encoder requires 80 GiB with minimal impact on performance, or 20 GiB while still improving the closed book baseline significantly. For comparison, the raw text of English Wikipedia requires approximately 24 GiB, thus making ARC-Encoder suitable for pre-computing compressed representations.

Figure 5: Compression results with varying MLP dimensional bottlenecks and number of bits per dimension (B/d).

---
[3]https://github.com/facebookresearch/faiss/wiki

5   Conclusion

We introduce ARC-Encoder, a novel method to compute compressed text representations that can replace the raw text input in large language models. By reducing the context length, our method leads to faster prefilling and decoding stages, while leaving the target LLM unchanged. We show that a single encoder can be trained to work with multiple decoders, or even extended to new decoders with minimal adaptation. This opens the way towards *universal compressed representations*. These representations can be used for various tasks (e.g., QA, summarization, translation...) and generalize well to new domains. We show that pretraining and fine-tuning are both critical for the success of our approach. In terms of architecture, pooling in the attention mechanism leads to strong results, while allowing a constant pooling factor for different sequence sizes, as opposed to memory tokens. Finally, using an MLP between the encoder and decoder allows our approach to compress representations further and learn a single encoder for multiple decoders.

References

Max Bartolo, Alastair Roberts, Johannes Welbl, Sebastian Riedel, and Pontus Stenetorp. Beat the ai: Investigating adversarial human annotation for reading comprehension. *Transactions of the Association for Computational Linguistics*, 8:662–678, December 2020. ISSN 2307-387X. doi: 10.1162/tacl_a_00338. URL http://dx.doi.org/10.1162/tacl_a_00338.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020. URL https://arxiv.org/abs/2005.14165.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation, 2023. URL https://arxiv.org/abs/2306.15595.

Yulong Chen, Yang Liu, Liang Chen, and Yue Zhang. DialogSum: A real-life scenario dialogue summarization dataset. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 5062–5074, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.findings-acl.449. URL https://aclanthology.org/2021.findings-acl.449/.

Xin Cheng, Xun Wang, Xingxing Zhang, Tao Ge, Si-Qing Chen, Furu Wei, Huishuai Zhang, and Dongyan Zhao. xrag: Extreme context compression for retrieval-augmented generation with one token, 2024. URL https://arxiv.org/abs/2405.13792.

Alexis Chevalier, Alexander Wettig, Anirudh Ajith, and Danqi Chen. Adapting language models to compress contexts, 2023. URL https://arxiv.org/abs/2305.14788.

Nachshon Cohen, Oren Kalinsky, Yftah Ziser, and Alessandro Moschitti. WikiSum: Coherent summarization dataset for efficient human-evaluation. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pp. 212–219, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-short.28. URL https://aclanthology.org/2021.acl-short.28/.

Qingxiu Dong, Xiaojun Wan, and Yue Cao. ParaSCI: A large scientific paraphrase dataset for longer paraphrase generation. In Paola Merlo, Jorg Tiedemann, and Reut Tsarfaty (eds.), *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 424–434, Online, April 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.eacl-main. 33. URL https://aclanthology.org/2021.eacl-main.33/.

Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs, 2019. URL https://arxiv.org/abs/1903.00161.

Sabri Eyuboglu, Ryan Ehrlich, Simran Arora, Neel Guha, Dylan Zinsley, Emily Liu, Will Tennien, Atri Rudra, James Zou, Azalia Mirhoseini, and Christopher Re. Cartridges: Lightweight and general-purpose long context representations via self-study, 2025. URL https://arxiv.org/abs/2506.06266.

Tao Ge, Jing Hu, Lei Wang, Xun Wang, Si-Qing Chen, and Furu Wei. In-context autoencoder for context compression in a large language model, 2024. URL https://arxiv.org/abs/2307.06945.

gkamradt. Llmtest needle in a haystack — pressure testing llms. https://github.com/gkamradt/LLMTest_NeedleInAHaystack, 2023. Accessed: 2025-11-26.

Bogdan Gliwa, Iwona Mochol, Maciej Biesek, and Aleksander Wawer. SAMSum corpus: A human-annotated dialogue dataset for abstractive summarization. In Lu Wang, Jackie Chi Kit Cheung, Giuseppe Carenini, and Fei Liu (eds.), *Proceedings of the 2nd Workshop on New Frontiers in Summarization*, pp. 70–79, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-5409. URL https://aclanthology.org/D19-5409/.

Naman Goyal, Cynthia Gao, Vishrav Chaudhary, Peng-Jen Chen, Guillaume Wenzek, Da Ju, Sanjana Krishnan, Marc'Aurelio Ranzato, Francisco Guzman, and Angela Fan. The flores-101 evaluation benchmark for low-resource and multilingual machine translation, 2021. URL https://arxiv.org/abs/2106.03193.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, and Daniel Song et al. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Dirk Groeneveld, Iz Beltagy, Pete Walsh, Akshita Bhagia, Rodney Kinney, Oyvind Tafjord, Ananya Harsh Jha, Hamish Ivison, Ian Magnusson, Yizhong Wang, Shane Arora, David Atkinson, Russell Authur, Khyathi Chandu, Arman Cohan, Jennifer Dumas, Yanai Elazar, Yuling Gu, Jack Hessel, Tushar Khot, William Merrill, Jacob Morrison, Niklas Muennighoff, Aakanksha Naik, Crystal Nam, Matthew E. Peters, Valentina Pyatkin, Abhilasha Ravichander, Dustin Schwenk, Saurabh Shah, Will Smith, Nishant Subramani, Mitchell Wortsman, Pradeep Dasigi, Nathan Lambert, Kyle Richardson, Jesse Dodge, Kyle Lo, Luca Soldaini, Noah A. Smith, and Hannaneh Hajishirzi. Olmo: Accelerating the science of language models. *Preprint*, 2024.

Wei Han, Pan Zhou, Soujanya Poria, and Shuicheng Yan. Two are better than one: Context window extension with multi-grained self-injection, 2024. URL https://arxiv.org/abs/2410.19318.

Jie Huang, Wei Ping, Peng Xu, Mohammad Shoeybi, Kevin Chen-Chuan Chang, and Bryan Catanzaro. Raven: In-context learning with retrieval-augmented encoder-decoder language models, 2024. URL https://arxiv.org/abs/2308.07922.

Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. Atlas: Few-shot learning with retrieval augmented language models, 2022. URL https://arxiv.org/abs/2208.03299.

Hervé Jégou, Matthijs Douze, and Cordelia Schmid. Product Quantization for Nearest Neighbor Search. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(1):117–128, January 2011. doi: 10.1109/TPAMI.2010.57. URL https://inria.hal.science/inria-00514462.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b, 2023a. URL https://arxiv.org/abs/2310.06825.

Huiqiang Jiang, Qianhui Wu, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Llmlingua: Compressing prompts for accelerated inference of large language models, 2023b. URL https://arxiv.org/abs/2310.05736.

Kelvin Jiang, Dekun Wu, and Hui Jiang. FreebaseQA: A new factoid QA data set matching trivia-style question-answer pairs with Freebase. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 318–323, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1028. URL https://aclanthology.org/N19-1028/.

Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William W. Cohen, and Xinghua Lu. Pubmedqa: A dataset for biomedical research question answering, 2019. URL https://arxiv.org/abs/1909.06146.

Matt Gardner Johannes Welbl, Nelson F. Liu. Crowdsourcing multiple choice science questions. 2017.

Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1601–1611, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1147. URL https://aclanthology.org/P17-1147/.

Anastasia Krithara, Anastasios Nentidis, Konstantinos Bougiatiotis, and Georgios Paliouras. Bioasq-qa: A manually curated corpus for biomedical question answering. *Scientific Data*, 10, 03 2023. doi: 10.1038/s41597-023-02068-4.

Yuri Kuratov, Mikhail Arkhipov, Aydar Bulatov, and Mikhail Burtsev. Cramming 1568 tokens into a single vector and back again: Exploring the limits of embedding space capacity, 2025. URL https://arxiv.org/abs/2502.13063.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Matthew Kelcey, Jacob Devlin, Kenton Lee, Kristina N. Toutanova, Llion Jones, Ming-Wei Chang, Andrew Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: a benchmark for question answering research. *Transactions of the Association of Computational Linguistics*, 2019.

Chankyu Lee, Rajarshi Roy, Mengyao Xu, Jonathan Raiman, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. Nv-embed: Improved techniques for training llms as generalist embedding models, 2025. URL https://arxiv.org/abs/2405.17428.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021. URL https://arxiv.org/abs/2005.11401.

Xuyang Liu, Zichen Wen, Shaobo Wang, Junjie Chen, Zhishan Tao, Yubo Wang, Xiangqi Jin, Chang Zou, Yiyu Wang, Chenfei Liao, Xu Zheng, Honggang Chen, Weijia Li, Xuming Hu, Conghui He, and Linfeng Zhang. Shifting ai efficiency from model-centric to data-centric compression, 2025. URL https://arxiv.org/abs/2505.19147.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization, 2019. URL https://arxiv.org/abs/1711.05101.

Maxime Louis, Hervé Déjean, and Stéphane Clinchant. Pisco: Pretty simple compression for retrieval-augmented generation, 2025a. URL https://arxiv.org/abs/2501.16075.

Maxime Louis, Thibault Formal, Hervé Dejean, and Stéphane Clinchant. Oscar: Online soft compression and reranking, 2025b. URL https://arxiv.org/abs/2504.07109.

Jesse Mu, Xiang Lisa Li, and Noah Goodman. Learning to compress prompts with gist tokens, 2024. URL https://arxiv.org/abs/2304.08467.

Tri Nguyen, Mir Rosenberg, Xia Song, Jianfeng Gao, Saurabh Tiwary, Rangan Majumder, and Li Deng. MS MARCO: A human generated machine reading comprehension dataset. *CoRR*, abs/1611.09268, 2016. URL http://arxiv.org/abs/1611.09268.

Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang, Menglin Xia, Xufang Luo, Jue Zhang, Qingwei Lin, Victor Rühle, Yuqing Yang, Chin-Yew Lin, H. Vicky Zhao, Lili Qiu, and Dongmei Zhang. Llmlingua-2: Data distillation for efficient and faithful task-agnostic prompt compression, 2024. URL https://arxiv.org/abs/2403.12968.

Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Maillard, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. Kilt: a benchmark for knowledge intensive language tasks, 2021. URL https://arxiv.org/abs/2009.02252.

Jack W Rae, Anna Potapenko, Siddhant M Jayakumar, Chloe Hillier, and Timothy P Lillicrap. Compressive transformers for long-range sequence modelling. *arXiv preprint*, 2019. URL https://arxiv.org/abs/1911.05507.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text, 2016. URL https://arxiv.org/abs/1606.05250.

Uri Shaham, Maor Ivgi, Avia Efrat, Jonathan Berant, and Omer Levy. Zeroscrolls: A zero-shot benchmark for long text understanding, 2023. URL https://arxiv.org/abs/2305.14196.

Ivan Stelmakh, Yi Luan, Bhuwan Dhingra, and Ming-Wei Chang. Asqa: Factoid questions meet long-form answers, 2023. URL https://arxiv.org/abs/2204.06092.

Paul Suganthan, Fedor Moiseev, Le Yan, Junru Wu, Jianmo Ni, Jay Han, Imed Zitouni, Enrique Alfonseca, Xuanhui Wang, and Zhe Dong. Adapting decoder-based language models for diverse encoder downstream tasks, 2025. URL https://arxiv.org/abs/2503.02656.

Jiwei Tang, Zhicheng Zhang, Shunlong Wu, Jingheng Ye, Lichen Bai, Zitai Wang, Tingwei Lu, Jiaqi Chen, Lin Hai, Hai-Tao Zheng, and Hong-Gee Kim. Gmsa: Enhancing context compression via group merging and layer semantic alignment, 2025. URL https://arxiv.org/abs/2505.12215.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey, 2022. URL https://arxiv.org/abs/2009.06732.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, and Gaël Liu et al. Gemma 3 technical report, 2025. URL https://arxiv.org/abs/2503.19786.

Together AI. Llama-2-7B-32K-Instruct — and fine-tuning for Llama-2 models with Together API. https://www.together.ai/blog/llama-2-7b-32k-instruct, August 2023. Accessed: 2025-07-17.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy

Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023. URL https://arxiv.org/abs/2307.09288.

Maurice Weber, Daniel Y. Fu, Quentin Anthony, Yonatan Oren, Shane Adams, Anton Alexandrov, Xiaozhong Lyu, Huu Nguyen, Xiaozhe Yao, Virginia Adams, Ben Athiwaratkun, Rahul Chalamala, Kezhen Chen, Max Ryabinin, Tri Dao, Percy Liang, Christopher Ré, Irina Rish, and Ce Zhang. Redpajama: an open dataset for training large language models. *NeurIPS Datasets and Benchmarks Track*, 2024.

Ling Xing, Alex Jinpeng Wang, Rui Yan, Xiangbo Shu, and Jinhui Tang. Vision-centric token compression in large language model, 2025. URL https://arxiv.org/abs/2502.00791.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering, 2018. URL https://arxiv.org/abs/1809.09600.

Howard Yen, Tianyu Gao, and Danqi Chen. Long-context language modeling with parallel context encoding, 2024. URL https://arxiv.org/abs/2402.16617.

Biao Zhang, Fedor Moiseev, Joshua Ainslie, Paul Suganthan, Min Ma, Surya Bhupatiraju, Fede Lebron, Orhan Firat, Armand Joulin, and Zhe Dong. Encoder-decoder gemma: Improving the quality-efficiency trade-off via adaptation, 2025. URL https://arxiv.org/abs/2504.06225.

Peitian Zhang, Zheng Liu, Shitao Xiao, Ninglu Shao, Qiwei Ye, and Zhicheng Dou. Long context compression with activation beacon, 2024. URL https://arxiv.org/abs/2401.03462.

Tianyi Zhang, Faisal Ladhak, Esin Durmus, Percy Liang, Kathleen McKeown, and Tatsunori B. Hashimoto. Benchmarking large language models for news summarization, 2023. URL https://arxiv.org/abs/2301.13848.

A   Further experiments

A.1   Context Compression with benchmark train sets

To demonstrate the generalization ability of ARC-Encoder, we deliberately avoid fine-tuning on the training sets of evaluation benchmarks. However, we believe that this could be an interesting use case for users who wish to specialize ARC-Encoder in a given domain. In Tab. 6, we report results from models fine-tuned on our dataset augmented with the HotpotQA and SQuAD training sets. These results show that, even without altering decoders, ARC-Encoders can specialize effectively on specific benchmarks. They outperform the *open-book* baseline while maintaining efficiency gains and without harming performance on other tasks.

Table 6: **Performance when adding HotpotQA and SQuAD train sets to the fine-tuning dataset.** 'PF': the token reduction factor (e.g., 4× for fixed-ratio methods or the number of compressed tokens used, e.g. ~ 16, when this number is fixed; 'Param.': number of parameters of the encoder; The superscript on ARC-Encoder indicates if the model is specifically trained for one decoder (^{M} for Mistral or ^{L} for Llama) or both simultaneously ($^\otimes$). Best context compression results are in **bold**, second best are underlined.

	Method	PF	Param.	**NQ**	**TQA**	**HQA**	**SQuAD**	**FLORES**	**CNN**	**Avg.**
Mistral 7B	*closed-book*	∞		29.1	62.4	22.8	17.1			
	open-book	1×		39.9	70.5	48.3	77.7	31.3	27.2	49.2
	ARC$_4$-Encoder$^\otimes$	4×	3.0B	38.3	**68.9**	60.5	77.0	29.9	**26.0**	50.1
	ARC$_4$-Encoder^M	4×	–	38.4	67.9	**60.7**	**81.1**	30.9	22.7	**50.3**
	ARC$_8$-Encoder^M	8×	–	**39.0**	67.0	57.5	74.8	28.0	20.8	47.9
Llama3.1 8B	*closed-book*	∞		25.4	60.6	21.6	15.3			
	open-book	1×		38.6	67.1	47.1	72.2	32.8	26.5	47.4
	ARC$_4$-Encoder$^\otimes$	4×	3.0B	38.5	**69.7**	61.9	78.6	**33.2**	**26.0**	51.3
	ARC$_4$-Encoder^L	4×	–	**40.7**	68.5	**62.1**	**82.3**	**33.2**	22.2	**51.5**
	ARC$_8$-Encoder^L	8×	–	38.6	67.6	59.1	76.0	30.1	21.7	48.9

A.2   Pooling factor generalization

Fig. 6 demonstrates that ARC-Encoder pretrained at a certain pooling factor can still be fine-tuned at another, sometimes even improving results on downstream tasks. This transfer works best as we use a smaller pooling factor than the one previously pretrained on. Notably, pretraining at 8× seems to be particularly effective since we can then outperform any other pair on pooling factors of 4× and 8×. In contrast, models do not generalize well when fine-tuned to higher pooling factors. This capability greatly benefits the method since it enables to reach better results at various pooling factors while pretraining fewer models. We train our best ARC$_4$-Encoder and ARC$_8$-Encoder from models pretrained using a pooling factor of 8. When pooling too much performance degrades sharply as with a pooling factor of 32 where the model has an averaged score of 33.1.

Figure 6: Score for various pooling factors between pretraining and fine-tuning.

A.3   Encoder-Decoder pairs

Following the same recipe as described in Section 3, we can design ARC-Encoder / decoder pairs based on other backbone models. Tab. 7 shows that Llama3.1 8B can also serve as an encoder backbone, displaying higher affinity with Llama decoders, similar to Llama3.2 3B. Adding the MLP projector is crucial to adapt to different decoders in the multi-decoder case as well as in the specific decoder one. Our experiments further reveal that the hidden state spaces of Llama3.1 8B and Mistral 7B are not fully disentangled: a

single encoder can feed both decoders with the same compressed representations while outperforming the closed-book baseline. We attribute this compatibility to their similar architectures and training pipelines.

Table 7: **Different backbones for an ARC$_4$-Encoder paired with different decoders**. The score is the average of the metrics in the Tab. 1. For underlined modules, the weights are the same for the two decoders; they are decoder-specific otherwise.

	Encoder				
Decoder	L8B	L3B + MLP	L8B	L8B + MLP	L3B + MLP
Llama3.1 8B	46.0	47.2	32.4	46.2	45.5
Mistral 7B	44.8	45.1	32.8	41.8	43.2

A.4 Pooling methods

Table 8: **Different pooling methods**. Scores are averaged over 3 fine-tunings with different seeds.

	Pooling method	PF	NQ	TQA	HQA	SQuAD	FLORES	CNN	Avg.
Mistral 7B	Average queries	×4	$36.9_{\pm0.2}$	$67.2_{\pm0.3}$	$39.9_{\pm0.4}$	$58.3_{\pm2.0}$	$27.4_{\pm0.3}$	$20.1_{\pm0.1}$	$41.7_{\pm0.4}$
	Last queries	−	$37.6_{\pm0.3}$	$68.1_{\pm0.3}$	$39.7_{\pm0.4}$	$59.8_{\pm1.0}$	$27.3_{\pm0.2}$	$19.7_{\pm0.2}$	$42.1_{\pm0.3}$
	Kmeans merged queries	−	$37.1_{\pm0.6}$	$65.8_{\pm0.2}$	$38.4_{\pm0.2}$	$52.3_{\pm0.2}$	$18.6_{\pm0.3}$	$19.4_{\pm0.6}$	$38.6_{\pm0.1}$
	Memory tokens	∼ 32	$36.8_{\pm0.6}$	$66.8_{\pm0.9}$	$28.9_{\pm0.4}$	$49.8_{\pm1.2}$	$31.0_{\pm0.3}$	$17.0_{\pm0.2}$	$38.4_{\pm0.1}$

A.5 Further baselines evaluations

A.5.1 ICAE further comparisons

ICAE-style context compression relies on learned tokens (memory tokens) appended at the end of the context to compress. It produces for each encoded sequence a fixed number of compressed representations corresponding to the output of these memory tokens. In contrast, our method requires no additional learned tokens: the encoder directly pools context tokens, yielding a variable number of compressed representations that scales with input length. It enables consistent results across sequence lengths. Additionally, ICAE encoders mirror the architecture of their target decoder, while ARC-Encoders are trained starting from any decoder-only LLM (typically Llama 3.2 3B) with removed layers and bidirectional attention, making them noticeably smaller and more versatile. ICAE-like model in Tab. 1 represents an ICAE context compression architecture under the same setting as our models training and evaluation. However, direct comparison is imperfect because ICAE's pooling factor is not fixed: e.g. 32 memory tokens always produce 32 outputs, whereas ARC4-Encoder produces outputs 4x shorter than the input. To clarify this we have also trained and evaluated ICAE architectures on fixed-size chunks as described in Section 3.3.3 of the ICAE paper (Ge et al., 2024), so that they operate with a fixed pooling factor. We show downstream results of these models in Tab. 10 as well as the ICAE-like architecture with varying pooling factors across benchmarks. The downstream results show that our method outperforms ICAE-like models at matched pooling factors while requiring less than twice the encoding compute. For some benchmarks we still outperform ICAE-like models using ARC-Encoders with higher pooling factors.

A.5.2 Generalization on out-of-domain professional datasets

To assess the generalization ability of our fine-tuned models on strictly out-of-domain benchmarks, we evaluate the above models on BioASQ (Krithara et al., 2023) and PubMedQA (Jin et al., 2019). These two QA datasets focus on biological and biomedical question-answering. Both domains do not appear the fine-tuning datasets enabling to test out-of-domain generalization. It further highlights the strengths of the following models in specialized professional domains. Since all compressor models we compare against, except

Table 9: **Further baselines evaluations.** Same setting and specifics as in Tab. 1

	Methods	PF	Param.	NQ	TQA	HQA	SQuAD	FLORES	CNN	Avg.
Mistral 7B decoder	*closed-book*	∞		29.1	62.4	22.8	17.1			
	open-book	$1\times$		39.9	70.5	48.3	77.7	31.3	27.2	49.2
	ICAE-like[†]	~ 32	7.2B	36.5	66.7	24.3	58.8	28.3	15.8	38.4
	xRAG-like[†]	~ 1	7.1B	30.7	65.2	21.5	23.9	0.9	14.6	26.1
		~ 8	–	28.7	62.4	21.8	24.2	9.0	10.7	26.1
	LLMLingua2	$1.9\times$	0.6B	38.8	69.0	43.7	59.2	12.6	24.9	41.4
		$3.6\times$	–	35.2	66.6	36.0	42.0	4.3	22.1	34.4
	PISCO-like[†]	~ 32	7.2B	34.7	68.5	24.9	38.2	33.6	19.2	36.5
		$4\times$	–	36.6	69.2	29.4	48.1	**34.5**	19.3	39.5
	ARC$_4$-Encoder$^\otimes$	$4\times$	3.0B	38.2	**70.4**	40.8	69.2	29.5	**25.6**	45.6
	ARC$_4$-Encoder^M	$4\times$	–	**39.0**	68.9	**45.1**	**71.1**	31.0	23.8	**46.5**
	ARC$_8$-Encoder^M	$8\times$	–	38.4	67.9	40.8	62.0	28.3	22.9	43.4
Llama3.1 8B decoder	*closed-book*	∞		25.4	60.6	21.6	15.3			
	open-book	$1\times$		38.6	67.1	47.1	72.2	32.8	26.5	47.4
	ICAE-like[†]	~ 32	7.6B	38.4	67.3	20.5	61.6	31.3	17.3	39.4
	xRAG-like[†]	~ 1	7.1B	28.0	62.1	21.7	22.3	3.4	12.7	25.0
		~ 8	–	26.6	61.1	21.9	22.3	6.4	12.6	25.2
	LLMLingua2	$2.0\times$	0.6B	36.1	66.3	45.2	58.8	13.6	23.8	40.6
		$3.9\times$	–	34.2	66.1	37.2	41.9	3.2	21.3	34.0
	PISCO-like[†]	~ 32	7.6B	35.1	69.4	30.6	40.5	35.2	19.7	38.4
		$4\times$	–	37.9	70.5	37.0	57.2	**36.5**	20.7	43.3
	ARC$_4$-Encoder$^\otimes$	$4\times$	3.0B	39.6	**70.8**	43.6	71.8	32.8	**26.1**	47.5
	ARC$_4$-Encoder^L	$4\times$	–	**39.7**	70.1	**46.9**	**74.0**	33.7	23.7	**48.0**
	ARC$_8$-Encoder^L	$8\times$	–	38.9	69.0	42.8	66.0	30.6	22.8	45.0

Table 10: **Further baselines evaluations.** Same setting and specifics as in Tab. 1 with Mistral 7B decoder. Average pooling factors for each benchmark are indicated as subscripts of the reported scores. These variations occur when the number of memory tokens is fixed, and ICAE-like models are not trained or evaluated on fixed-size chunks, resulting in a pooling factor that depends on the context length.

Methods	PF	NQ	TQA	HQA	SQuAD	FLORES	CNN	Avg.
closed-book	∞	29.1	62.4	22.8	17.1			
open-book	$1\times$	39.9	70.5	48.3	77.7	31.3	27.2	49.2
ICAE-like[†]	~ 32	$36.5_{(5\times)}$	$66.7_{(5\times)}$	$24.3_{(46\times)}$	$58.8_{(6\times)}$	$28.3_{(1\times)}$	$15.8_{(32\times)}$	38.4
	$4\times$	36.4	66.7	23.8	60.5.	28.7	18.6	39.1
	~ 16	$35.7_{(10\times)}$	$66.7_{(9\times)}$	$26.0_{(92\times)}$	$51.0_{(12\times)}$	$26.9_{(2\times)}$	$14.3_{(64\times)}$	20.6
	$8\times$	34.8	66.6	8.9	53.0	26.7	17.5	34.6
	~ 8	$34.9_{(19\times)}$	$65.3_{(19\times)}$	$25.3_{(185\times)}$	$28.9_{(23\times)}$	$18.5_{(4\times)}$	$17.7_{(128\times)}$	18.1
	$16\times$	33.7	65.6	0.1	31.1	19.0	14.7	27.4
ARC$_2$-Encoder^M	$2\times$	**41.7**	**69.3**	**48.3**	**76.7**	30.4	18.9	**47.6**
ARC$_4$-Encoder^M	$4\times$	39.0	68.9	45.1	71.1	**31.0**	23.8	46.5
ARC$_8$-Encoder^M	$8\times$	38.4	67.9	40.8	62.0	28.3	22.9	43.4
ARC$_{16}$-Encoder^M	$16\times$	35.4	67.1	31.8	45.1	22.7	20.3	37.1
ARC$_{32}$-Encoder^M	$32\times$	34.6	65.8	28.8	34.8	17.0	17.8	33.1

for LLMLingua2, were fine-tuned on the same dataset, they are expected to struggle with the out-of-domain nature of the provided contexts. In shown in Tab. 11, our ARC-Encoder achieves the best performance even with a pooling factor of 8, reaching results close to the upper-bound *open-book* setting. These findings demonstrate the strong real-world applicability and robustness of our approach.

Table 11: **Out-of-domain evaluations.** Same setting and specifics as in Tab. 1. Evaluated using F1 score.

	Methods	PF	Param.	**PubMedQA**	**BioASQ**
Mistral 7B decoder	*closed-book*	∞		58.7	63.6
	open-book	$1\times$		84.4	77.5
	ICAE-like[†]	~ 32	7.2B	63.6	57.7
	LLMLingua2	$1.9\times$	0.6B	74.4	73.4
		$3.6\times$	–	66.4	69.7
	PISCO-like[†]	~ 32	7.2B	62.4	60.5
		$4\times$	–	62.0	66.0
	$ARC_4\text{-Encoder}^{\otimes}$	$4\times$	3.0B	73.9	72.0
	$ARC_4\text{-Encoder}^{M}$	$4\times$	–	76.6	**75.6**
	$ARC_8\text{-Encoder}^{M}$	$8\times$	–	**76.7**	74.9
Llama3.1 8B decoder	*closed-book*	∞		52.5	56.3
	open-book	$1\times$		84.0	77.2
	ICAE-like[†]	~ 32	7.6B	75.0	70.9
	LLMLingua2	$2.0\times$	0.6B	73.4	75.1
		$4.0\times$	–	62.7	70.9
	PISCO-like[†]	~ 32	7.6B	62.9	67.8
		$4\times$	–	68.4	71.8
	$ARC_4\text{-Encoder}^{\otimes}$	$4\times$	3.0B	**81.1**	76.3
	$ARC_4\text{-Encoder}^{L}$	$4\times$	–	**81.1**	**77.1**
	$ARC_8\text{-Encoder}^{L}$	$8\times$	–	80.2	75.5

A.6 Context length performance scaling

(a) On QASPER (F1) (b) On QMSUM (Rouge-L)

Figure 7: **Performance scaling with context length**. On two benchmarks (a) QASPER and (b) QMSUM evaluation of our long-context ARC-Encoder paired with Llama2 7B Chat on subsets of the test dataset with similar context sizes.

In Fig. 7, we show how performance scales with the context length in the long-context setting. We address this by splitting QMSUM and QASPER into bins containing approximately the same number of samples. Each bin groups examples whose contexts fall within a specific token-length range. We see that independently of the task (question answering for QASPER and summarization for QMSUM), ARC-Encoder performance

remains largely consistent across different token-length ranges. We attribute this context length robustness to our fine-tuning which contains samples of varying lengths.

A.7 Needle-in-Haystack analysis

Our method performs lossy context compression and our evaluation shows that this loss does not prevent the target LLM from extracting semantic information from the compressed representations for downstream tasks. To further explore this information loss, we evaluate fine-grained retrieval using the Needle-in-Haystack(gkamradt, 2023) (NIAH) benchmark in Fig. 8. In the following plots, we test ARC-Encoder (pooling factor 8) with Llama2 7B Chat in a long-context setting and compare it to other long-context-capable models, none of which were trained for this task. ARC-Encoder (bottom right) enables Llama2 7B Chat to retrieve precise information beyond its 4096-token window, and retrieval appears more consistent across varying context lengths and depths. Our model's top score is 7 because it outputs "Eat a sandwich and sit in Dolores Park on a sunny day" instead of the exact needle given to the LLM as a judge "The best thing to do in San Francisco is eat a sandwich and sit in Dolores Park on a sunny day." This demonstrates that ARC-Encoder enables fine-grained retrieval, but the model does not format the retrieved answer correctly.

Figure 8: **Needle in the Haystack evaluation.** We test various models as in Tab. 3: Llama2 Chat (upper left), Llama2 32K fine-tuned for long-context (upper right), Llama2 with CEPED (bottom left) and our ARC_8-Encoder (bottom right).

A.8 On targeting a smaller LLM

An ARC-Encoder with 3B parameters does not offer efficiency gains when paired with smaller LLMs. However, our encoder ablations show that we can truncate more layers from the backbone or even switch to a different backbone to reduce its size. We therefore train two additional ARC-Encoder variants: one using Llama 3.2 3B truncated by 14 layers (1.8B parameters) and one using Llama 3.2 1B truncated by 2 layers (1.1B parameters). When combined with a 3B LLM (Llama 3.2 3B), both variants achieve strong performance as shown in Tab. 12, remaining close to the open-book setting, while also delivering computational benefits even at this scale, see Fig. 9 and Fig. 10. Our method should be adapted depending on the targeted LLM to preserve an effective performance–efficiency trade-off.

Table 12: **Smaller encoders paired with a smaller LLM.** Same setting and specifics as in Tab. 1 with Llama3.2 3B. We either use Llama3.2 3B with half of its layers truncated (1.8B parameters for the ARC-Encoder) or Llama3.1 1B truncated of 2 layers (1.1B parameters) as the backbone for an ARC-Encoder.

Methods	PF	Param.	**NQ**	**TQA**	**HQA**	**SQuAD**	**FLORES**	**CNN**	**Avg.**
closed-book	∞		19.1	50.1	17.4	11.6			
open-book	$1\times$		34.4	65.5	43.2	71.4	29.3	26.0	45.0.
ARC_4-$Encoder^L$	$4\times$	1.8B	37.13	66.3	40.3	65.0	28.8	21.0	43.1
ARC_8-$Encoder^L$	$8\times$	—	34.6	65.5	35.6	55.8	24.7	21.8	39.7
ARC_4-$Encoder^L$	$4\times$	1.1B	34.9	65.9	37.9	63.4	27.6	20.8	41.8
ARC_8-$Encoder^L$	$8\times$	—	33.0	64.4	33.2	52.4	23.0	20.5	37.8

(a) Number of TFLOPs

(b) CUDA time (s)

Figure 9: **Measured computational costs for Llama 3.2 3B using ARC-Encoders with 1.8B parameters**. (a) Number of TFLOPs and (b) CUDA time in seconds for the continuation of a book from PG19 for various prompt lengths and numbers of tokens to generate on one NVIDIA H100.

(a) Number of TFLOPs

(b) CUDA time (s)

Figure 10: **Measured computational costs for Llama 3.2 3B using ARC-Encoders with 1.1B parameters**. (a) Number of TFLOPs and (b) CUDA time in seconds for the continuation of a book from PG19 for various prompt lengths and numbers of tokens to generate on one NVIDIA H100.

B   Theoretical generation FLOPs

Let us denote s the number of tokens of the prompt sequence, d the hidden dimension of the model, n_{layers} its number of layers, v the vocabulary size and N the overall number of parameters of the decoder. We assume for simplicity that the decoder uses multi-head attention and that the hidden dimension is the same everywhere in the model. The theoretical complexity of prefilling steps, measured in floating point operations (FLOPs) and neglecting norms, is:

- **Multi-head attention:**

$$\textbf{Q, K, V projections} = 3 \times s \times d^2$$
$$\textbf{Attention scores} = s^2 \times d$$
$$\times \textbf{V} = s^2 \times d$$
$$\textbf{Final projection} = s \times d^2 (\text{depends})$$
$$\textbf{Overall} = 4s \times d^2 + 2s^2 \times d$$

- **Feedforward network** $\propto s \times d^2$

- **Output projection** $\propto s \times d \times v$.

In the case where $d \gg s$, as the number of parameters per layer is proportional to d^2, we have $d \propto \sqrt{\frac{N}{n_{\text{layers}}}}$, which leads to:

$$\textbf{Total prefill FLOPs} \propto sN \quad \text{if } \sqrt{N} \gg s. \tag{1}$$

Hence, using $\frac{s}{x}$ tokens for prefilling instead of s leads to a relative FLOPs of $\frac{1}{x}$.

At the opposite, when processing very large prompts, i.e, $d \ll s$, the computational complexity reads:

$$\textbf{Total prefill FLOPs} \propto s^2\sqrt{N}. \tag{2}$$

If we use an ARC-Encoder, with a pooling factor of x, which has $n = p \times N$ parameters ($p < 1$) wih p the relative size of the encoder vs. decoder, then the number of FLOPs to compress the prompt can be approximated to:

$$\begin{cases} \propto sN \times (p + \frac{1}{x}) & \text{if } d \gg s, \\ \propto s^2\sqrt{N}(\sqrt{p} + \frac{1}{x^2}) & \text{if } d \ll s. \end{cases} \tag{3}$$

For instance, it is approximately $1.5\times$ smaller for ARC_4-Encoder and $1.9\times$ smaller for ARC_8-Encoder in the setting of the main table.

C   Training details

C.1   Default setting

Trainings are performed on $8\times$H100 NVIDIA GPUs using PyTorch's FSDP framework[4]. The ablations follow the parameters and architectural choices from our best ARC_8-Encoder encoders 1, namely:

- **Encoder**: Llama3.2 3B truncated of the 2 last layers with every layer trained using a non-causal attention mask. When using Llama3.1 8B as encoder we truncate the 8 last layers.

- **Pooling**: by averaging queries in the last transformer block of the encoder with a pooling factor of 8.

- **MLP projector**: 2 learned matrices without activation function, with dimensions sequence $3072 \rightarrow 2048 \rightarrow 4096$ if the encoder is Llama3.2 3B, $4096 \rightarrow 2048 \rightarrow 4096$ otherwise.

---

[4]https://docs.pytorch.org/docs/stable/fsdp.html

- **Training**:

  - Special tokens are added depending on the task.
  - 20% reconstruction for pretraining during 60k steps with approximately 2B tokens seen by the encoder and maximum 256 tokens compressed and 256 tokens to continue or reconstruct.

- During the continuation task, maximum 256 text tokens are prefixed to the compressed sequence to better align with the final few-shot evaluation.

- **Fine-tuning**:

  - `<Cont>` token is appended after each compressed sequence.
  - Compressed representations are used as context and all the samples follow the format below (C.3) with more or less in-context examples as described in Tab. 15.
  - Fine-tuning is performed with the same pooling factor as for the pretraining, unless stated otherwise.

Remarks. Inserting text tokens before the compressed sequence in the continuation task introduces a significant compute overhead during pretraining. Yet, after fine-tuning with interleaved few-shot samples, it offers no gains in the specific-decoder setting. Standard continuation can substitute for the "interleaved" one in pretraining, as long as fine-tuning later interleaves compressed and normal tokens. For consistency, we keep interleaved continuation in reported results since it helps ARC-Encoder generalize better in the multi-decoder setting.

C.2   Hyperparameters

Table 13: Pretraining hyperparameters.

Hyperparameters	Pretraining settings
optimizer	AdamW
max lr encoder	1×10^{-5}
max lr special tokens	1×10^{-5}
max lr rate MLP	5×10^{-5}
lr scheduler type	1 cycle policy
init lr	1×10^{-20}
final lr	1×10^{-10}
warmup steps	1000
weight decay	0.1
batch size	16
gradient accumulation steps	None
GPUs	8
max tokens compressed at once	256
prefix text tokens	≤ 256
max norm (gradient clipping)	1.0
mixed precision	Yes
number of steps	60k for ablations
	80k for multi-decoder
	80k for ARC-Encoder (long context or not)
MLP init.	Kaiming Unif. leaky-ReLU slope of $\sqrt{5}$
Special tokens init.	Ones

Multi-Decoder specificities. To add OLMo 7B to the existing multi-decoder ARC$_4$-Encoder, we fine-tune the MLP using 8k steps with 100 warmup steps and a maximum learning rate for the MLP of 10^{-4}.

Table 14: Fine-tuning hyperparameters. Not listed hyperparameters are identical to pretraining ones.

Hyperparameters	Context Compression	Long Context
max lr encoder	2×10^{-6}	–
max lr special tokens	2×10^{-6} (3×10^{-5} for multi-decoder)	NA
max lr rate MLP	3×10^{-5}	–
final lr	1×10^{-8}	–
warmup steps	50	1000
weight decay	5×10^{-2}	–
n. steps	4k (8k for multi-decoder)	8k
batch size	8	2
gradient accumulation steps	None	4
max tokens compressed at once	2048	1024
interleaved examples	$\leq$ # in-context examples (M)	NA
	$= M$ for Tabs. 1, 2, 6 and 9	NA
contexts chunked to	No	1024 tokens
max contexts in parallel	1	31

C.3 Context Compression fine-tuning

To generate synthetic fine-tuning data, we use the vLLM[5] library for fast, efficient single-GPU inference. Gemma 3 27B (Team et al., 2025) is then prompted to generate translations of Atlas Wikipedia passages (up to 3 concatenated passages) in various languages that we split into two categories:

1) Spanish, French, German and Danish;

2) Hindi, Russian, Swahili, Arabic, Turkish, Japanese, Finnish and Chinese (simplified).

We mix these generated translation datasets with supervised QA, summarization and reading comprehension datasets. For QA datasets, we retrieve the top-5 passages using NV-Embed (Lee et al., 2025), based on Wikipedia sequences[6] from KILT framework (Petroni et al., 2021). To improve information retrieval in large compressed contexts, we concatenate retrieved passages when possible and compress them jointly. The number of concatenated passages is randomly sampled between 1 and the maximum number of retrieved passages. This is particularly beneficial for HotpotQA and CNN, with minimal impact on other evaluation benchmarks. For MS MARCO (Nguyen et al., 2016) we removed the samples without answers (*no answer*). The complete list of the subsets that make up our final fine-tuning dataset is reported in Tab. 15, along with the proportions according to which these subsets are sampled from.

---

[5]https://docs.vllm.ai
[6]https://huggingface.co/datasets/dmrau/kilt-128

Subsets	Proportion	# in-context examples	Max. concat. passages
Synth. translations			
Group 1 translations	6%	5	
Group 2 translations	4%	5	
QA with retrieved context			
AdversarialQA (Bartolo et al., 2020)	8%	5	4
FreebaseQA (Jiang et al., 2019)	27%	5	4
ASQA (Stelmakh et al., 2023)	1%	5	4
MS MARCO (Nguyen et al., 2016)	9%	5	4
SciQ (Johannes Welbl, 2017)	3%	5	4
Reading comprehension			
DROP (Dua et al., 2019)	20%	5	
ParaSCI (Dong et al., 2021)	12%	5	
Summarization			
DialogSum (Chen et al., 2021)	2.5%	3	
SAMSum (Gliwa et al., 2019)	2.5%	4	
WikiSum (Cohen et al., 2021)	5%	5	

Table 15: Fine-tuning dataset for context compression

Few-shot compressed fine-tuning template

Document: `<TOKENS_COMPRESSED>`
Question: `<QUESTION>`
Answer: `<ANSWER>`

Document: `<TOKENS_COMPRESSED>`
Question: `<QUESTION>`
Answer: `<ANSWER>`
⋮
Document: `<TOKENS_COMPRESSED>`
Question: `<QUESTION>`
Answer: `<ANSWER>`   (*the loss is computed only on the last answer*)

C.4 Long Context

C.4.1 Pretraining

To pretrain ARC-Encoder when paired with an instruct decoder model, we continue to alternate between continuation and reconstruction tasks. We format each of the pretraining samples using the following template C.4.1.

Pretraining templates with Llama2 Chat decoder

Template:
`` [INST] Prefix+`<TOKENS_COMPRESSED>`+Instruction [/INST] Suffix ``
Reconstruction:

- Prefix = `"Text:\n\n"`

- Instruction = `"\n Replicate the input text."`

- Suffix = `"Replicated text:\n"`

Continuation:

- Prefix = `"Text:\n\n"`

- Instruction = `"\n Continue the previous text."`

- Suffix = `"Text continuation:\n..."`

C.4.2 Fine-tuning

For this part, we synthesized QA, summarization and paraphrasing examples using the same procedure as in Appendix C.3.

QA generation. We split books from PG-19 (Rae et al., 2019) and arXiv papers from RedPajama (Weber et al., 2024) into paragraphs, randomly selecting 5 consecutive paragraphs. We then prompted Gemma3-27B to generate questions and gold answers using instructions such as:

- *As a human instructor assessing students' comprehension of a scientific article, you craft a concise question that ideally requires a short phrase or sentence to answer. If the article lacks the necessary information, the answer should be 'unanswerable'. For yes/no questions, reply with 'yes', 'no', or 'unanswerable'. Then, supply the gold answer.*

- *You are given a story from a book. Your task is to create a question that can be answered in a short phrase or sentence. Then, provide the gold answer.*

The final context in the dataset is the entire book or paper. Additionally, we generate QA examples from Wikipedia by selecting one chunk from the Atlas Wikipedia dataset and appending up to 20 chunks from the same source before prompting the model.

Summarization generation. Using the same datasets, we split the texts into 10 groups of passages. Gemma3 27B is prompted to summarize each subsection; then, based on these summaries, it is prompted again to produce a higher-level summary, with prompt variations controlling the target length. For Atlas Wikipedia, we directly ask the model to produce a short summary from 10 consecutive chunks. In both QA and summarization tasks, we truncate contexts longer than 500k characters and discard those shorter than 1k characters.

Paraphrase. To mimic the questions asked in QM-Sum benchmarks, we prompt Gemma3 to reformulate passages of the text. For all tasks, we truncate contexts longer than 500k characters and discard those shorter than 1k characters.

Contexts	# samples	Mean Ctx	Median Ctx	Mean answer
Summarization				
From Atlas	64000	6833	5593	714
From PG-19 books	64000	55048	34915	635
From ArXiv papers	40000	10896	4875	834
Paraphrase				
From PG-19 books	80000	31854	29272	665
From ArXiv papers	64000	5625	4260	617
QA				
From Atlas	80000	8065	8325	43
From PG-19 books	80000	317179	322942	69
From ArXiv papers	40000	54526	43386	49

Table 16: **Fine-tuning dataset statistics for long-context understanding**. We report different statistics on the length in characters of the contexts ('Ctx') and the answers for each subset of fine-tuning samples.

All samples are inserted in an instruction prompt depending on their task and context dataset using the same template as in C.4.1 with adapted *Prefix*, *Instruction* and *Suffix*.

D Evaluation details

D.1 Baselines implementation

LLMLingua2 (Pan et al., 2024): We used the open-source model *microsoft/llmlingua-2-xlm-roberta-large-meetingbank* following the instructions from LLMLingua.

xRAG (Cheng et al., 2024): We use the official codebase from xRAG and extend it to support Llama3.1 8B as a decoder. Due to architectural similarities between Mistral 7B and Llama3.1 8B, only minor modifications are required. We first pretrain the MLP projector by closely following the instructions and data from the repository and the original paper, adapting it to base models by removing all chat templates. Next, we modify the fine-tuning dataset pre-processing to interleave compressed context in an ICL-style format, aligned with our fine-tuning template (see C.3), which closely matches the evaluation setup. To ensure consistency and avoid variability due to dataset size or quality, we use our own dataset for fine-tuning. We observe in Tabs. 1 and 9 that xRAG performs poorly on translations tasks (FLORES). After further investigations, we believe that compressing the full sequence into one vector leads to a loss of information that causes partial-only translations or hallucinations, as illustrated below.

ICAE (Ge et al., 2024): For this re-implementation, we use our own codebase. We follow the hyperparameters and design choices described in the original paper, including the use of special tokens and alternating pretraining tasks. We set the language modeling task ratio to 0.5 and pretrain the encoder on our evaluated decoders (Llama3.1 8B and Mistral 7B) with our crawl dataset for 100k steps (which is half the number of steps reported in the paper, but the training curve had already converged). Additionally, we adapt the fine-tuning template to match our evaluation format (see Appendix C.3). To avoid redundancy with our ablation studies on pooling methods with memory tokens, we retain the fine-tuning dataset from Ge et al. (2024) (PwC), which was specifically synthesized for this purpose. However, due to the poor generalization on our evaluation benchmarks, we present ICAE-like models fine-tuned on our own dataset.

PISCO (Louis et al., 2025a): As with ICAE, we re-implemented PISCO using our own codebase, following the hyperparameters and design choices outlined in the original paper (e.g., LoRA applied to both encoder and decoder, encoder architecture, use of memory tokens). Since the official code is not publicly available, we referred to Ge et al. (2024) for implementation details not specified in the paper, such as the use of special tokens. To ensure consistency and avoid variability from dataset quality, we use our custom fine-tuning dataset but increased the number of fine-tuning steps to 8000 to reach near 500k samples which

matches the number of training samples used in the PISCO paper. Furthermore, our custom dataset consists in PISCO fine-tuning dataset without the train sets of the evaluation datasets, with extra summarization datasets and synthesized translations data. While sequence-level distillation is key to avoiding reliance on gold labels, early experiments with silver labels showed that using gold labels enables a fairer comparison. Additionally, we train variants that process fixed-length input chunks of size 128 tokens, enabling a fixed pooling factor and aligning the setup more closely with that of Louis et al. (2025a).

---

xRAG with Mistral 7B failures to translate English texts

To French:

- `Ground-truth:` "Cette page est accessible facilement à partir d'une seule adresse Web, ce qui la rend facile à mémoriser et à écrire pour les étudiants qui ne savent pas utiliser un clavier et qui ont des problèmes d'orthographe."

- `xRAG generation:` "Avec un seul nom de domaine, il est facile pour les utilisateurs d'accéder à l'information, ce qui est un avantage pour les étudiants."

To Spanish:

- `Ground-truth:` "Son superiores a los servidores proxy por varios motivos: redirigen todo el tráfico de Internet y no únicamente los http."

- `xRAG generation:` "Estos son más eficientes que los proxy, ya que no requieren que el usuario realice cambios en sus configuraciones de red."

To German:

- `Ground-truth:` "Vergessen Sie nicht die Extrakosten für weitere Visa, Abfluggebühren, Transportmittel an Land etc. für all die Orte außerhalb von Afrika mit einzuberechnen."

- `xRAG generation:` "Das ist zwar teurer als die Flüge, aber das Geld ist es wert, weil man damit nicht nur das Flugzeug spart, sondern auch die Kosten für die Übernachtung, die Verpflegung und die Reiseversicherung."

D.2 Evaluation datasets

Context Compression. We evaluate our pipeline on question answering (QA) and reading comprehension tasks using the following benchmarks: HotpotQA (Yang et al., 2018) (*distractor* setting on the dev set, 7400 samples) , Natural Questions (Kwiatkowski et al., 2019) (NQ open dev set, 3605 samples), TriviaQA (Joshi et al., 2017) (unfiltered nocontext validation set, 11308 samples), SQuAD (Rajpurkar et al., 2016) (10565 samples). When ground-truth context is not provided, we retrieve the top-5 passages using NV-Embed (Lee et al., 2025), based on Wikipedia sequences from the Atlas framework (Izacard et al., 2022), effectively simulating a RAG setup. The number of retrieved passages used for evaluation is specified for each benchmark. We report Exact Match (EM) as our primary evaluation metric, where answers are normalized and EM = 1 if all characters match exactly. We demonstrate summarization capabilities on the CNN-DailyMail dataset (a subset of 1000 samples of the dev set), evaluating performance with the Rouge-L metric, as Zhang et al. (2023) noted that strong Rouge-L scores in this context are closely aligned with high human approval.

For translation tasks, we evaluate on the FLORES benchmark (Goyal et al., 2021) (992 samples), using BLEU scores computed with SacreBLEU[7]. BLEU scores are averaged over four translation directions: English to Danish, French, German, and Spanish. Models are prompted in a 5-shot setting using the following template, using compressed contexts for each example. Examples are sampled from the validation set and are fixed among all models. The reported pooling factor reflects the average per-context compression of tokens, not the ratio over the full prompt (including the textual prompt). It consists in dividing the number of tokens of

---

[7]https://github.com/mjpost/sacrebleu

the full document using the decoder tokenizer by the number of compressed tokens or the number of tokens of the compressed document in the hard compression case.

Evaluation QA template

- **n examples for n-shot evaluation:**
  Document: `<TOKENS_COMPRESSED>`
  Question: `<QUESTION>`
  Answer: `<ANSWER>`

  Document: `<TOKENS_COMPRESSED>`
  Question: `<QUESTION>`
  Answer: `<ANSWER>`
  ⋮

- **the final question**
  Document: `<TOKENS_COMPRESSED>`
  Question: `<QUESTION>`
  Answer:

Evaluation translation template

- **n examples for n-shot evaluation:**
  Document: `<TOKENS_COMPRESSED>`
  Question: Translate the previous document into `<LANGUAGE>`.
  Answer: `<ANSWER>`
  ⋮

- **the final question**
  Document: `<TOKENS_COMPRESSED>`
  Question: Translate the previous document into `<LANGUAGE>`.
  Answer:

Long Context. For long-context understanding, we report results on NarrativeQA (NQA), QASPER (Qspr), GovReport (GvRp), and QM-Sum validation datasets from ZeroSCROLLS (Shaham et al., 2023) benchmark, a suite of zero-shot long-context understanding tasks that emphasize instruction-following capabilities. We evaluate on the full validation dataset which consists in respectively 3461, 1726, 973 and 272 samples. Specifically, we adopt the task formats and instructions as used in Yen et al. (2024)[8].

---

[8]https://github.com/princeton-nlp/CEPE