Mosaicking to Distill:
Knowledge Distillation from Out-of-Domain Data

Gongfan Fang[1,3]**, Yifan Bao**[1]**, Jie Song**[1]**, Xinchao Wang**[2]**, Donglin Xie**[1]
Chengchao Shen[3]**, Mingli Song**[1,3*]
[1]Zhejiang University, [2]National University of Singapore, [3]Central South University
[3]Alibaba-Zhejiang University Joint Institute of Frontier Technologies
{fgf,yifanbao,sjie,donglinxie,brooksong}@zju.edu.cn
xinchao@nus.edu.sg, scc.cs@csu.edu.cn

Abstract

Knowledge distillation (KD) aims to craft a compact student model that imitates the behavior of a pre-trained teacher in a target domain. Prior KD approaches, despite their gratifying results, have largely relied on the premise that *in-domain* data is available to carry out the knowledge transfer. Such an assumption, unfortunately, in many cases violates the practical setting, since the original training data or even the data domain is often unreachable due to privacy or copyright reasons. In this paper, we attempt to tackle an ambitious task, termed as *out-of-domain* knowledge distillation (OOD-KD), which allows us to conduct KD using only OOD data that can be readily obtained at a very low cost. Admittedly, OOD-KD is by nature a highly challenging task due to the agnostic domain gap. To this end, we introduce a handy yet surprisingly efficacious approach, dubbed as *MosaicKD*. The key insight behind MosaicKD lies in that, samples from various domains share common local patterns, even though their global semantic may vary significantly; these shared local patterns, in turn, can be re-assembled analogous to mosaic tiling, to approximate the in-domain data and to further alleviating the domain discrepancy. In MosaicKD, this is achieved through a four-player min-max game, in which a generator, a discriminator, a student network, are collectively trained in an adversarial manner, partially under the guidance of a pre-trained teacher. We validate MosaicKD over classification and semantic segmentation tasks across various benchmarks, and demonstrate that it yields results much superior to the state-of-the-art counterparts on OOD data. Our code is available at https://github.com/zju-vipa/MosaicKD.

1 Introduction

Knowledge distillation (KD) has emerged as a popular paradigm for model compression and knowledge transfer, attracting attention from various research communities [18, 42, 48, 15]. The goal of KD is to train a lightweight model, known as the student, by imitating a pre-trained but more cumbersome model, known as the teacher, so that the student masters the expertise of the teacher. In recent years, KD has demonstrated encouraging results over various machine learning applications, including but not limited to computer vision [6, 30], data mining [2], and natural language processing [47, 21]

Nevertheless, the conventional setup for KD has largely relied on the premise that, data from at least the same domain, if not the original training data, is available to train the student. This seemingly-mind assumption, paradoxically, imposes a major constraint for conventional KD approaches: in many cases, the training data and even their domain for a pre-trained network are agnostic, due to for example confidential or copyright reasons. Hence, the in-domain prerequisite significantly limits the

35th Conference on Neural Information Processing Systems (NeurIPS 2021).

applicable scenarios of KD, and precludes taking advantage of the sheer number of publicly-available pre-trained models, many of which with unknown training domain [26, 40], to carry out massive knowledge transfer.

In this paper, we aim at the ambitious goal of conducting KD using only *out-of-domain* (OOD) data, which, in turn, enables us to greatly relax the conventional prerequisite and thereby largely strengthens applicability of KD. Unarguably, OOD-KD is by nature a highly challenging task, since the domain discrepancy will inevitably impose a major obstacle towards the proper functioning of the pre-trained teacher. In fact, if we are to conduct naive KD on the raw OOD data, the resulting student model, as will be demonstrated in our experiments, fails to provide any performance guarantee on the target domain. This phenomenon signifies the limited generalization capability learned from OOD data, which is unsurprising.

To this end, we propose a novel assembling-by-dismantling approach, termed as MosaicKD, that allows us to take advantage of OOD data to conduct KD. Our motivation stems from the fact that, even though data from different domains exhibit divergent global distributions, their local distributions, such as patches in images, may however resemble each other. This observation further inspires us to leverage the local patterns, shared by the OOD and target-domain data, to resolve the domain shift problem in OOD-KD. As such, the core idea of MosaicKD is to synthesize in-domain data, of which the local patterns imitate those from real-world OOD data, while the global distribution, assembled from local ones, is expected to fool the pre-trained teacher. As shown in Figure 1, the shared local patterns are extracted from OOD data and re-assembled into in-domain data. Intuitively, this process is analogous to mosaic tiling, where tesserae are utilized to compose the whole art piece.

Specifically, in MosaicKD, we frame OOD-KD problem as a novel four-player min-max game involving a generator, a discriminator, a student, and a teacher, among which the former three are to be learned while the last one is pre-trained and hence fixed. The generator, as those in prior GANs, takes as input a random noise vector and learns to mosaic synthetic in-domain samples with locally-authentic and globally-legitimate distributions, under the supervisions back-propagated from the other three players. The discriminator, on the other hand, learns

Figure 1: Natural images share common local patterns. In MosaicKD, these local patterns are first dissembled from OOD data and then assembled to synthesize in-domain data, making OOD-KD feasible.

to distinguish local patches extracted from the real-world OOD data and from the synthetic samples. The entire synthetic images are fed to both the pre-trained teacher and the to-be-trained student, based on which the teacher provides category knowledge for data synthesis and the student mimics the behavior of the teacher so as to carry out KD. The four players collaboratively reinforce one another in an adversarial fashion, and collectively accomplish the student training.

In short, our contribution is the first dedicated attempt towards OOD-KD, a highly practical yet largely overlooked problem, achieved through a novel scheme that mosaics in-domain data. The synthetic samples, generated via a four-player min-max game, enjoy realistic local structures and sensible global semantics, laying the ground for a dependable knowledge distillation from the pre-trained teacher. We conduct experiments over classification and semantic segmentation tasks across various benchmarks, and demonstrate that MosaicKD yields truly encouraging results much superior to those derived by its state-of-the-art competitors on OOD data.

2 Related Work

Knowledge distillation. Knowledge Distillation aims to craft a lightweight student model from cumbersome teachers [18], by either transferring network outputs [4, 18] or intermediate representations [42, 39]. In the literature, knowledge distillation and its variants largely rely on the premise that original training data is available during distillation, which is vulnerable in real-world applications due to privacy or copyright reasons [34, 59, 45, 58, 46, 22, 44]. Recently, data-free knowledge

distillation [31, 34, 10, 62, 60] has attracted attention from various research communities, which trains student model only with synthetic data. However, due to the difficulty in data synthesis without real-world samples, data-free KD usually leads to a degraded student on complicated tasks [62, 5]. Another solution to relax the conventional prerequisite on training data is to use some OOD samples. Unfortunately, it is found that naive knowledge distillation on OOD usually fails to learn a comparable student model from teachers [33, 28].

Domain adaptation and generalization. Most learning algorithms strongly rely on the premise that the source data for training and the target data for testing are independent and identically distributed [51], ignoring the OOD problem that is frequently encountered in real-world applications. In the literature, the OOD problem is usually addressed by domain generalization (DG) or adaptation (DA) [3, 65]. Adaptation is a popular technique for aligning the source and target domain [43, 11, 49], which typically requires the target domain to be accessible during training. In recent years, Domain adaptation has been extended to open-set settings where the label space of training and testing data are different [38]. In comparison, domain generalization is related to the topic of adaptation, but does not requires the information from target domain [3], which trains a model on the source domain only once and directly applied the model on the target domain [29, 12, 52, 16]. Despite the success of DA and DG in supervised learning, OOD problem is still under-studied in the context of knowledge distillation, where domain information can be extracted from an already trained teacher model.

Generative adversarial networks (GAN). Generative adversarial network is initially introduced by Goodfellow *et al.* for image generation [13], where a generator is trained to fool a discriminator in an adversarial min-max game. In recent years, several works have been proposed to improve the performance of GANs, from the perspective of image quality [23, 24], data diversity [32, 57], and training stability [1]. Besides, Some explorations have been taken to make GAN training more efficient with limited data through transfer learning [53] or augmentation [63]. In this work, we study data synthesis in OOD settings, where the original training data is unavailable and conventional GAN technique can not be diretly applied.

3 Out-of-Domain Knowledge Distillation

Without loss of generality, we study OOD problem in the context of image classification task. The domain underlying a dataset is defined as a triplet $\mathcal{D} = \{\mathcal{X}, \mathcal{Y}, P_{\mathcal{X} \times \mathcal{Y}}\}$, consisting of the input space $\mathcal{X} \subset \mathbb{R}^{c \times h \times w}$, the label space $\mathcal{Y} = \{1, 2, ..., K\}$ and the joint distribution $P_{\mathcal{X} \times \mathcal{Y}}$ over $\mathcal{X} \times \mathcal{Y}$. Given a teacher model $T(x; \theta_t)$ that is directly trained on domain $\mathcal{D}$ to learn a function mapping $T : \mathcal{X} \rightarrow \mathcal{Y}$, vanilla KD trains a student model to imitate teacher's behaviour, by directly minimizing the empirical risk on the original training domain $\mathcal{D}$ as follows:

$$\theta_s^* = \arg\min_{\theta_s} \mathbb{E}_{(x,y) \sim P_{\mathcal{X} \times \mathcal{Y}}} \left[\ell_{\mathrm{KL}}(T(x; \theta_t) \| S(x; \theta_s)) + \ell_{\mathrm{CE}}(S(x; \theta_s), y) \right], \quad (1)$$

where ℓ_{KL} and ℓ_{CE} refers to the KL divergence and the cross entropy loss. However, when the original training domain $\mathcal{D}$ is unavailable and replaced by another domain $\mathcal{D}' = \{\mathcal{X}', \mathcal{Y}', P_{\mathcal{X} \times \mathcal{Y}}\}$, Equation 1 would be problematic due to the domain gap. To tackle this problem, we focus on the out-of-domain problem in knowledge distillation, described as follows:

Problem Definition (OOD-KD). Given a teacher model $T(x; \theta_t)$ obtained from training domain $\mathcal{D} = \{\mathcal{X}, \mathcal{Y}, P_{\mathcal{X} \times \mathcal{Y}}\}$, the goal of OOD-KD is to craft a comparable student model $S(x; \theta_s)$ only leveraging out-of-domain data from $\mathcal{D}' = \{\mathcal{X}', \mathcal{Y}', P_{\mathcal{X}' \times \mathcal{Y}'}\}$, where $\mathcal{X}' \neq \mathcal{X}$ and $\mathcal{Y}' \neq \mathcal{Y}$.

In OOD-KD, due to the domain divergence between OOD data and original training data, some important patterns may be the missing if the OOD data is directly used for training, which causes the difficulty of transferring comprehensive knowledge from teachers to students. In this work, we propose a novel assembling-by-dismantling approach to eliminate the domain divergence between the OOD set and the unavailable training set, so as to make KD feasible on out-of-domain data.

4 Proposed Method

In the absence of original training data X, directly minimizing the risk on an OOD set X' would be problematic due to the diverged data domain. To address this problem, we introduce a generative method for OOD-KD problem, dubbed as MosaicKD, where a generator $G(z; \theta_g)$ is introduced to construct a new distribution P_G for training. Specifically, MosaicKD is developed upon the

distributionally robust optimization (DRO) framework [41]. Given a pre-defined distance metric $d(\cdot, \cdot)$ for distributions, the basic form of DRO framework can be represented as the following:

$$\min_S \max_G \left\{ \mathbb{E}_{x \sim P_G} \left[\ell_{\text{KL}}(T(G(z)) \| S(G(z))) \right] : d(P_G, P_{X'}) \leq \epsilon \right\} \tag{2}$$

where ℓ_{KL} refers to the KL divergence for student learning, $d(P_G, P_{X'})$ refers the distribution distance between the generated samples and OOD data. The hyper-parameter ϵ specifies the radius of searching space, which is a ball space centered at $P_{X'}$. According to this definition, DRO framework aims to find the worst-case distribution for optimization, which establishes an upper bound for all distributions covered by the ball searching space. Ideally, if the target distribution P_X of original training data exactly lies in the searching space, its empirical risk can effectively be optimized by the DRO framework. However, we would like to argue that this premise may be problematic in OOD settings, where $\mathcal{X} \neq \mathcal{X}'$ and $\mathcal{Y} \neq \mathcal{Y}'$. Note that if two distribution p_{X_1} and p_{X_2} are close in the input space under certain metric $d(\cdot; \cdot)$, their label space $\mathcal{Y}_1$ and $\mathcal{Y}_2$ should be also similar [50]. Thus, all distributions within the small ϵ ball space, centered at $P_{X'}$ are likely to share the same label space, i.e., $\mathcal{X} \approx \mathcal{X}'$ and $\mathcal{Y} \approx \mathcal{Y}'$, which obviously conflicts with the OOD setting. Therefore, the target domain of original training data might not be covered by the search space. A remedy for this issue is to use a sufficiently large radius ϵ. Unfortunately, it will only lead to intractable searching space, flooded with meaningless distributions to target tasks. The above problems indicate that the conventional DRO framework may inapplicable for OOD-KD.

4.1 Mosaicking to Distill

As mentioned above, the searching space built upon OOD data is insufficient for establishing an reliable upper bound for optimization. To address this problem, MosaicKD introduces a new way to construct the searching space based on local patches. Our motivation stems from that patterns of natural images are often organized hierarchically, where high-level patterns are assembled from low-level ones. In OOD-KD, although the domain of original training data X and OOD data X' are diverged, their local patterns may still resemble each other. For example, the patterns of "fur" can be shared by different animal species from varied domains. Based on this observation, the proposed approach, MosaicKD, adopts an assembling-by-dismantling strategy, which re-organizes shared local patches to synthesize in-domain data.

Patch Learning. The first step towards MosaicKD is to extract local patterns from OOD data X' and estimate the patch distribution. Given an OOD dataset $X' = \{x'_1, x'_2, ..., x'_N; x'_i \in \mathbb{R}^{H \times W \times 3}\}$, we can obtain patches through $L \times L$ cropping, which produces a patch dataset $C = \{c_1, c_2, ..., c_M; c_i \in \mathbb{R}^{L \times L \times 3}\}$. Naturally, different patch sizes can lead to varied semantics. For example, when $L = W = H$, each patch covers a full image, revealing the global semantic like category. When we decrease the patch size to $L = 1$, then each patch only contains color information. Small size P can lead to more general patterns shared by different domains than large P. Besides, increasing patch size introduces more complicated structural information to each patch, which will make the patch distribution closer to the original distribution of full images. MosaicKD models these local information as a generative problem, where a generator $G(z; \theta_g)$ is trained to approximate the patch distribution by fooling a discriminator network $D(x; \theta_d)$. Note that our final goal is to synthesize full images, we let the generator $G(x; \theta_g)$ synthesize images in the full resolution and obtain the generated patches by random cropping, which will lead to the generated patch distribution $P_{V(G)}$. Let $C(\cdot)$ refers to the cropping operation, the objective of patch learning can be formulated as follows:

$$\min_G \max_D \mathcal{L}_{local}(G, D) = \mathbb{E}_{x' \sim P_{X'}} \left[\log D(C(x')) \right] + \mathbb{E}_{z \sim P_z} \left[\log(1 - D(C(G(z)))) \right] \tag{3}$$

where $P_{X'}$ refers to the patch distribution of OOD data and P_z refers to the prior distribution of the latent variable z. $C(x')$ and $C(G(z))$ refers cropped patches from OOD data and generated data. The main difference between Eqn. (3) and the objectives in vanilla GANs [13] lies in the patch-level discrimination, where MosaicKD only restricts local patterns to be authentic. In this min-max optimization, we leave the global structure of generated samples unstructured. As mentioned before, global semantic can be assembled from local ones to reveal various semantic, MosaicKD leverage these patches to synthesize in-domain data by aligning their label space.

Label Space Aligning. As no inter-patch restriction is introduced in Eqn. (3), the generator may only produce images with meaningless global semantic, although their local patterns are plausible. In this step, we turn to the teacher model for more information as the guidance for in-domain data synthesis,

Figure 2: The framework of MosaicKD. We leverage the local patterns of OOD data and the category knowledge of teacher to synthesize locally-authentic and globally-legitimate samples for KD.

which can be achieved by label space aligning. In KD, the teacher model is trained on the original training data X, whose output is a conditional probability $T(x; \theta_t) = p(y|x, \theta_t)$. The response on position y corresponds to the probability that x belongs to y-th category. To obtain task-related information, a naive method is to maximize the confidence of teacher predictions, i.e., minimizing the entropy term $H(p(y|x, \theta_t))$. However, prior works have shown that a naive category probability maximization may only lead to "rubbish samples" [14] without too much visual information for humans. Results from [19] also show that this operation only produces so-called non-robust features. In this work, we propose a regularized objective to align label space as follows:

$$\min_G \mathcal{L}_{align}(G, D, T) = \mathbb{E}_{z \sim P_z} \left[\log(1 - D(C(G(z)))) + H\left[p(y|G(z), \theta_t)\right] \right] \quad (4)$$

where the first term refers to the discrimination loss in Equation 3, which regularizes the local patterns to be authentic. The first term refers to the entropy loss to maximize the teacher's confidence, which works on full images to assemble local patterns. This objective will be simultaneously optimized with Equation (3) so as to avoid unrealistic patterns [14].

DRO in MosaicKD. In previous sections, Equation 3 regularizes the local patterns to be authentic and Equation 4 aligns the label space of synthetic data to that of training data. They collaboratively construct a new searching space for DRO framework:

$$\min_S \max_G \mathcal{L}_{DRO}(G, D, S, T) = \{\mathbb{E}_{z \sim p_z(z)} \left[\ell_{KL}(T(G(z)) \| S(G(z)))\right] : \mathcal{R}(G, D, T)) \leq \epsilon\} \quad (5)$$

where $\mathcal{R}(G, D, T)$ is a regularization term derived from Equation 3 and 4. Note that optimizing a generative adversarial networks as Equation 3 is equivalent to minimizing the Jensen–Shannon divergence of two patch distribution, i.e., $\ell_{JSD}(P_{X'}^{patch}, P_G^{patch})$, the regularization term can be formalized as:

$$\mathcal{R}(G, D, T) = \ell_{JSD}(P_{X'}^{patch}, P_G^{patch}) + \mathbb{E}_{z \sim P_z} \left[H(p(y|G(z), \theta_t))\right] \quad (6)$$

This regularization force the generator to leverage local patterns from OOD data for data synthesis. And the searching space is defined as all possible assembling schemes of local patterns. Different to the conventional DRO on full images, MosaicKD can deploy a small radius for optimization, where the target domain can be covered by the searching space. We relax the regularization in Equation 5 to obtain an tractable objective for optimization as follows:

$$\min_S \max_G \mathcal{L}_{DRO}(G, D, S, T) = \mathbb{E}_{x \sim P_z} \left[\ell_{KL}(T(G(z)) \| S(G(z)))\right] - \lambda \mathcal{R}(G, D, T)) \quad (7)$$

4.2 Optimization

Patch Discriminator. For training efficiency, the discriminator in equation 3 can be implemented with as Patch GAN [20] with carefully designed receptive fields and patch overlap. Specifically, we stack several convolutional layers to build a fully convolutional network, whose output is a score map instead of a single true-or-fake scalar. Each score unit accepts a $L \times L$ local patches for discrimination. We apply an additional stride downsampling with step size s on the score map to control the overlap between patches. A large step size s will lead to more independent patches for training, further reducing the structure restrictions of different patches.

Full Algorithm. The full algorithm of MosaicKD is summarized in Alg. 1, where a generator $G(z; \theta_g)$, a discriminator $D(x; \theta_d)$, and a student $S(x; \theta_s)$ are optimized collectively with a fixed teacher model $T(x; \theta_t)$, under the guidance of $\mathcal{L}_{local}$, $\mathcal{L}_{align}$ and $\mathcal{L}_{DRO}$.

Algorithm 1 MosaicKD for out-of-domain knowledge distillation
***
Input: Pretrained teacher $T(x; \theta_t)$, student $S(x; \theta_s)$ and out-of-domain data X'.
Output: An optimized student $S(x; \theta_s)$
***
1: Initialize a generator $G(z; \theta_g)$ and a discriminator $D(z; \theta_d)$
2: **repeat**
3:     ▷ Patch Discrimination
4:     Sample a mini-batch of OOD data x' from X' and synthetic data x from $G(z)$;
5:     update discriminator to distinguish fake patches from real ones using $\mathcal{L}_{local}$ from Eqn. 3;
6:     ▷ Generation
7:     Sample a mini-batch of generated data x from $G(z)$;
8:     Update generator G to:
9:         (a) fool the discriminator D using $\mathcal{L}_{local}$ from Eqn. 3;
10:        (b) align label space with teacher T using $\mathcal{L}_{align}$ from Eqn. 4;
11:        (c) fool the student S using $\mathcal{L}_{DRO}$ from Eqn. 7;
12:     ▷ Knowledge Distillation
13:     **for** j steps **do**:
14:        Sample generated samples from $G(z)$;
15:        Update student through knowledge distillation using $\mathcal{L}_{DRO}$ from Eqn. 7
16:     **end for**
17: **until** converge
***

5 Experiments

5.1 Settings

Datasets. The proposed method is evaluated on two mainstream vision tasks, *i.e.*, image classification and semantic segmentation. Four datasets are adopted in our experiments for training teacher models, including CIFAR-100 [27], CUB-200 [54], Stanford Dogs [25] and NYUv2 [35]. For OOD-KD, we substitute original training data with OOD data, including CIFAR-10 [27], Places365 [64], ImageNet [9] and SVHN [37].

Evaluation metrics. For image classification, accuracy and Frechet Inception Distance (FID) are used to evaluate different methods. FID indicates the divergence of two datasets, which was originally used to assess the synthesis quality of GANs [17]:

$$FID = \|\mu_1 - \mu_2\|_2^2 + tr\left(\Sigma_1 + \Sigma_2 - 2\left(\Sigma_1\Sigma_2\right)^{1/2}\right) \tag{8}$$

where (μ_1, Σ_1) and (μ_2, Σ_2) are the mean and covariance statistics of generated and original samples. For semantic segmentation, we use mean Intersection of Unions (mIoU) as the metric. Please refer to the supplementary materials for more details about datasets, training protocol, and metrics.

5.2 Results of Knowledge Distillation

CIFAR-100. Table 1 reports the results with teachers pre-trained on CIFAR-100. Here we use CIFAR-10, ImageNet, Places365 and SVHN as OOD data to evaluate MosaicKD for OOD-KD. We compare the proposed MosaicKD to various baselines, including some data-free KD methods (DAFL [7], ZSKT [34], DeepInv. [62], DFQ [8]) and OOD-KD methods naively adapted from state-of-the-art KD methods (BKD [18], Balanced [36], FitNet [42], RKD [39], CRD [48]) and SSKD [55].

From the results, we can see that despite the mismatched distributions, naively adapted OOD-KD methods still learn some useful but incomplete knowledge (*i.e.*, yielding significantly superior performance to random guessing) from OOD data, which indicates the existence of shared features. Further, some exploration was taken from the perspective of category balance and representation transfer. First, we balance the OOD data by re-sampling the scarce categories according to the teacher's prediction. However, results show that naively balancing the OOD data may not help students learn correct class information because most samples in OOD data are just outliers. In the context of OOD settings, a naive balance operation may lead to over-fitting on outliers, which may degrade the student performance on the test set. As mentioned before, OOD data and original data

Method	Data	resnet-34 resnet-18	vgg-11 resnet-18	wrn40-2 wrn16-1	wrn40-2 wrn40-1	wrn40-2 wrn16-2	Average
Teacher	CIFAR-100 (Original Data)	78.05	71.32	75.83	75.83	75.83	75.37
Student		77.10	77.10	65.31	72.19	73.56	73.05
KD [18]		77.87	75.07	64.06	68.58	70.79	72.27
DAFL [7]	Data-Free	74.47	54.16	20.88	42.83	43.70	47.20
ZSKT [34]		67.74	54.31	36.66	53.60	54.59	53.38
DeepInv. [62]		61.32	54.13	53.77	61.33	61.34	58.38
DFQ [8]		77.01	66.21	51.27	54.43	64.79	62.74
KD [18]	CIFAR-10 (OOD Data)	73.55	68.04	47.47	61.17	63.48	62.74
Balanced [36]		68.54	64.14	50.50	56.50	57.33	59.40
FitNet [42]		70.14	67.52	50.31	60.17	60.60	63.15
RKD [39]		67.45	63.06	45.37	53.29	57.10	57.25
CRD [48]		71.23	66.48	47.00	59.59	61.37	61.13
SSKD [55]		73.81	68.72	49.57	60.71	64.61	63.48
Ours		**77.01**	**71.56**	**61.01**	**69.14**	**69.41**	**69.55**
KD [18]	ImageNet† (OOD Subset)	50.89	50.52	36.54	36.87	41.69	43.30
Balanced [36]		41.74	47.04	31.61	29.57	35.65	37.12
FitNet [42]		60.15	58.23	42.63	44.21	48.53	50.75
RKD [39]		40.26	35.80	31.15	24.95	34.48	33.32
Ours		**75.81**	**68.94**	**59.32**	**66.61**	**67.36**	**67.60**
KD [18]	Places365† (OOD Subset)	43.49	46.24	33.28	31.39	36.37	38.15
Balanced [36]		28.16	38.85	23.22	21.54	28.62	28.08
FitNet [42]		54.08	54.15	36.33	44.21	38.74	45.50
RKD [48]		30.25	33.06	28.07	21.12	21.12	26.72
Ours		**74.70**	**68.55**	**56.70**	**65.34**	**65.89**	**66.23**
KD [18]	SVHN (OOD Data)	31.55	34.00	19.77	23.07	24.75	26.63
Balanced [36]		26.93	29.34	16.18	18.96	21.50	22.58
FitNet [42]		33.69	36.22	20.02	23.72	25.41	27.81
RKD [39]		26.83	27.31	18.09	22.55	24.29	23.81
Ours		**47.18**	**37.63**	**31.87**	**45.84**	**44.40**	**41.38**

Table 1: Test accuracy (%) of student networks trained with the following settings: conventional KD with original training data, data-free KD with synthetic data, and OOD-KD with OOD data. †: As Places365 and ImageNet contain some in-domain samples, we craft OOD subsets with low teacher confidence (high entropy) from the original dataset, so as to match our OOD setting.

Method	Data	FLOPs	mIoU
Teacher	NYUv2	41G	0.519
Student		5.54G	0.375
ZSKT	Data-Free	5.54G	0.364
DAFL		5.54G	0.105
KD	ImageNet	5.54G	0.406
Ours		5.54G	**0.454**

Table 2: Mean Intersection over Union (mIoU) of student models on NYUv2 data set.

Method	CUB-200	Stanford Dogs
Teacher	49.41	56.65
Student	41.44	48.61
KD	11.07	10.24
Balanced	4.56	6.42
FitNet	18.12	19.13
Ours	**26.11**	**28.02**

Table 3: Test accuracy of student networks on fine-grained datasets.

may share some patterns on which the student can capture task-related information. Therefore, we apply three KD methods for representation transfer, i.e., FitNet, RKD and CRD. Compared with RKD that transfers instance relation, we found that response-based methods like fitnet can transfer more helpful information in OOD-KD, where the student directly imitates the teacher's intermediate outputs in shallow and deep layers. As low-level features are usually more general, transferring them sometimes can be helpful for OOD-KD. CRD is a powerful KD method for conventional settings but may be inappropriate for OOD-KD because it works on the high-level representation from the penultimate layer, which is considered to be less transferable on OOD data.

Instead of directly leveraging these OOD data, our method handles the OOD-KD problem as a generative problem. In MosaicKD, we leverage local patterns of OOD data for data synthesis, where some task-related patterns will be "assembled" from shared local patches. Results show that these re-assembled data can effectively transfer knowledge from teachers to students. In Table 1, we also extend our method to more OOD data from various domains. We found that the performance of

Figure 3: Statistical information of OOD data and out generated data. Category percentage (the first y-axis) and FID score (the second y-axis) to original data (CIFAR-100) is reported.

Patch size		1	2	4	8	18	22	32
CIFAR-10	Acc.	52.22	55.58	58.94	61.01	**61.03**	58.94	51.34
	FID	2.43	4.47	8.78	16.82	22.81	26.07	28.30
Places365	Acc.	46.44	45.90	50.67	**56.70**	53.99	53.44	40.29
	FID	12.32	14.77	21.32	30.09	35.54	38.64	41.41
SVHN	Acc.	19.83	21.86	**32.09**	31.87	21.05	22.08	20.54
	FID	93.39	146.76	145.64	143.72	148.33	147.25	148.94

Table 4: Test accuracy (%) of students obtained with different patch sizes. The Patch FID score between OOD data and original data is also reported. Results show that our approach requires smaller patch sizes to handle severe domain discrepancies.

MosaicKD is relative to the degree of domain divergence between OOD data and original data. For example, ImageNet is an object recognition dataset while Places365 is a scene classification dataset. Results show that MosaicKD can achieve better performance on ImageNet than Places365. The training curves of MosaicKD and other baseline methods are illustrated in Figure 5.

Fine-grained Classification. To further study the effectiveness of our approach, we conduct knowledge distillation on fine-grained datasets as shown in Table 3, using Places365 as OOD data. OOD-KD on fine-grained data is a challenging problem, because different categories is visually similar. Results show that our method achieves superior performance compared to baselines methods.

Semantic Segmentation. Semantic segmentation can also be viewed as a classification task, where the network is trained to predict the category of each pixel. We apply our method to the NYUv2 dataset, following the protocol in [10]. The teacher network is a deeplab v3 network with resnet-50 backbone. The student is a freshly initialized deeplabv3-MobileNetv2 model. Our method can effectively improve the knowledge transfer on OOD data and achieve superior performance, even compared to vanilla KD settings.

5.3 Quantitative Analysis

Data balance and FID. Figure 3 provides some statistical information of OOD data and generated samples, including the category balance predicted by teachers and the per-class FID scores. The category is ranked according to category percentage. Note that the original CIFAR-10 dataset only contains 10 categories, which is limited compared with the 100 categories. As illustrated in Figure 3 (a), a lot of CIFAR-100 categories are missing in CIFAR-10. Besides, the large FID between OOD data and original training data also indicates that, although some samples are categorized to a specific class by the teacher, they may still belong to outliers from different domains. By contrast, our method successfully balances different CIFAR-100 categories and alleviates the domain gap (lower class FID), especially for unbalanced categories.

The influence of patch size. Patch size plays an essential role in our method, which determines the flexibility of data synthesis. The optimal patch size actually depends on the divergence between OOD data and in-domain data. For OOD data with large domain discrepancy, small patches are usually required due to the limited local similarity. As shown in Table 4, we evaluate our method with different patch sizes and report the test accuracy and patch FID. According to the student performance, we find that for OOD data like CIFAR-10 and Places365, we can use a large patch size (e.g., 18) for student learning. However, for SVHN dataset, a smaller patch size would be more appropriate, as SVHN severely diverges from CIFAR-100.

Teacher prediction : apple
True category: car

Teacher prediction : tree
True categories: car, deer, frog

Teacher prediction : apple
True category: apple

Teacher prediction : tree
True category: tree

(a) W/O Patch Learning   (b) Patch Learning (Ours)

Figure 4: Visualization of synthetic data with and without patch learning. GANs without patch learning will be trapped by OOD data and fails to present correct semantic for different categories (highlighted in blue). In our method, the semantic can be correctly aligned with target domain.

Method	wrn40-2 wrn16-1	wrn40-2 wrn40-1	wrn40-2 wrn16-2
ours	**61.01**	**69.14**	**69.41**
w/o patch	51.34	56.23	57.23
w/o disc.	44.05	58.11	59.73
w/o adv.	55.11	67.57	68.25

Table 5: Test accuracy (%) of students in different ablation settings.

Figure 5: Training efficiency of our method compared with DFQ and vanilla KD.

Ablation study. In this section, we conduct ablation to understand the role of patch learning further. We consider the following settings: (a) MosaicKD (b) mosaicKD without patch learning (c) mosaicKD without discrimination (d) mosaicKD wihout adversarial training. Results are reported in Table 5. We find that in some cases, discrimination on full images without patch learning may lead to worse results than MosaicKD without any discrimination. Figure 4 visualizes the synthetic data with or without patch learning. Results show that the generator without patch learning is trapped by the label space of OOD data, failing to synthesize in-domain categories like trees and apples. In contrast, our method can produce desired objects for knowledge distillation.

6 Discussion

Relation to unlabeled knowledge distillation. In the literature of knowledge distillation, a slice of works also use unlabeled data for student learning. However, they either make an i.i.d. assumption about unlabeled data and original training [61], or assume that there are sufficient in-domain samples inside unlabeled set [56]. In this work, we allow the unlabeled set to be fully OOD, which is more challenging than existing unlabeled settings.

Relation to data-free knowledge distillation. The commonality between the data-free distillation algorithm and our algorithm is that we both solve the distillation problem through data synthesis. However, data-free KD only leverages some simple priors such as category probabilities [7] and Gaussian distributions [62] from the teacher model for data synthesis, which ignores the structural details in natural images. By contrast, we resolve the data synthesis problem in an assembling-by-dismantling manner, where natural patterns can be utilized to improve synthesis quality.

7 Conclusion

In this work, we propose a novel approach, termed as MosaicKD, that enables us to take advantage of only the OOD data for KD. MosaicKD follows a assembling-by-dismantling scheme where a synthetic sample is generated by locally resembling the real-world OOD data while globally fooling the pre-trained teacher. This is technically achieved through a handy yet effective four-player min-max game, in which a generator, a discriminator, and a student network are learned in the presence of a pre-trained teacher. We validate MosaicKD over classification and semantic segmentation tasks across various benchmarks, and showcase that it yields results significantly superior to the state-of-the-art techniques on OOD data.

8 Acknowledgements and Disclosure of Funding

This work is supported by National Natural Science Foundation of China (U20B206661976186), Key Research and Development Program of Zhejiang Province (2020C01023), the Major Scientific Research Project of Zhejiang Lab (No. 2019KD0AC01), the Fundamental Research Funds for the Central Universities, Alibaba-Zhejiang University Joint Research Institute of Frontier Technologies, Start-Up Grant from National University of Singapore (R-263-000-E95-133), and MOE AcRF TIER 1 FRC Research Grant (R-263-000-F14-114).

References

[1] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

[2] Siddhartha Arora, Mitesh M Khapra, and Harish G Ramaswamy. On knowledge distillation from complex networks for response prediction. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 3813–3822, 2019.

[3] Gilles Blanchard, Gyemin Lee, and Clayton Scott. Generalizing from several related classification tasks to a new unlabeled sample. *Advances in neural information processing systems*, 24:2178–2186, 2011.

[4] Cristian Buciluǎ, Rich Caruana, and Alexandru Niculescu-Mizil. Model compression. In *Proceedings of the 12th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 535–541, 2006.

[5] Akshay Chawla, Hongxu Yin, Pavlo Molchanov, and Jose Alvarez. Data-free knowledge distillation for object detection. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3289–3298, 2021.

[6] Guobin Chen, Wongun Choi, Xiang Yu, Tony Han, and Manmohan Chandraker. Learning efficient object detection models with knowledge distillation. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 742–751, 2017.

[7] Hanting Chen, Yunhe Wang, Chang Xu, Zhaohui Yang, Chuanjian Liu, Boxin Shi, Chunjing Xu, Chao Xu, and Qi Tian. Data-free learning of student networks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3514–3522, 2019.

[8] Yoojin Choi, Jihwan Choi, Mostafa El-Khamy, and Jungwon Lee. Data-free network quantization with adversarial knowledge distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pages 710–711, 2020.

[9] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[10] Gongfan Fang, Jie Song, Chengchao Shen, Xinchao Wang, Da Chen, and Mingli Song. Data-free adversarial distillation. *arXiv preprint arXiv:1912.11006*, 2019.

[11] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pages 1180–1189. PMLR, 2015.

[12] Muhammad Ghifary, W Bastiaan Kleijn, Mengjie Zhang, and David Balduzzi. Domain generalization for object recognition with multi-task autoencoders. In *Proceedings of the IEEE international conference on computer vision*, pages 2551–2559, 2015.

[13] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.

[14] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

[15] Jianping Gou, Baosheng Yu, Stephen John Maybank, and Dacheng Tao. Knowledge distillation: A survey. *arXiv preprint arXiv:2006.05525*, 2020.

[16] Tianyu Guo, Chang Xu, Boxin Shi, Chao Xu, and Dacheng Tao. Learning from bad data via generation. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

[17] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *arXiv preprint arXiv:1706.08500*, 2017.

[18] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[19] Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. *arXiv preprint arXiv:1905.02175*, 2019.

[20] Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1125–1134, 2017.

[21] Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling bert for natural language understanding. *arXiv preprint arXiv:1909.10351*, 2019.

[22] Yongcheng Jing, Yiding Yang, Xinchao Wang, Mingli Song, and Dacheng Tao. Amalgamating knowledge from heterogeneous graph neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2021.

[23] Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

[24] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4401–4410, 2019.

[25] Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Li Fei-Fei. Novel dataset for fine-grained image categorization. In *First Workshop on Fine-Grained Visual Categorization, IEEE Conference on Computer Vision and Pattern Recognition*, Colorado Springs, CO, June 2011.

[26] Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. *arXiv preprint arXiv:1912.11370*, 6(2):8, 2019.

[27] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. *technical report*, 2009.

[28] Mandar Kulkarni, Kalpesh Patil, and Shirish Karande. Knowledge distillation using unlabeled mismatched images. *arXiv preprint arXiv:1703.07131*, 2017.

[29] Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5400–5409, 2018.

[30] Muyang Li, Ji Lin, Yaoyao Ding, Zhijian Liu, Jun-Yan Zhu, and Song Han. Gan compression: Efficient architectures for interactive conditional gans. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5284–5294, 2020.

[31] Raphael Gontijo Lopes, Stefano Fenu, and Thad Starner. Data-free knowledge distillation for deep neural networks. *arXiv preprint arXiv:1710.07535*, 2017.

[32] Qi Mao, Hsin-Ying Lee, Hung-Yu Tseng, Siwei Ma, and Ming-Hsuan Yang. Mode seeking generative adversarial networks for diverse image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1429–1437, 2019.

[33] Gaurav Menghani and Sujith Ravi. Learning from a teacher using unlabeled data. *arXiv preprint arXiv:1911.05275*, 2019.

[34] Paul Micaelli and Amos Storkey. Zero-shot knowledge transfer via adversarial belief matching. *arXiv preprint arXiv:1905.09768*, 2019.

[35] Pushmeet Kohli Nathan Silberman, Derek Hoiem and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *ECCV*, 2012.

[36] Gaurav Kumar Nayak, Konda Reddy Mopuri, and Anirban Chakraborty. Effectiveness of arbitrary transfer sets for data-free knowledge distillation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1430–1438, 2021.

[37] Yuval Netzer, T. Wang, A. Coates, A. Bissacco, B. Wu, and A. Ng. Reading digits in natural images with unsupervised feature learning. 2011.

[38] Pau Panareda Busto and Juergen Gall. Open set domain adaptation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 754–763, 2017.

[39] Wonpyo Park, Dongju Kim, Yan Lu, and Minsu Cho. Relational knowledge distillation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3967–3976, 2019.

[40] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

[41] Hamed Rahimian and Sanjay Mehrotra. Distributionally robust optimization: A review. *arXiv preprint arXiv:1908.05659*, 2019.

[42] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

[43] Kuniaki Saito, Kohei Watanabe, Yoshitaka Ushiku, and Tatsuya Harada. Maximum classifier discrepancy for unsupervised domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3723–3732, 2018.

[44] Chengchao Shen, Xinchao Wang, Jie Song, Li Sun, and Mingli Song. Amalgamating knowledge towards comprehensive classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019.

[45] Chengchao Shen, Xinchao Wang, Youtan Yin, Jie Song, Sihui Luo, and Mingli Song. Progressive network grafting for few-shot knowledge distillation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

[46] Chengchao Shen, Mengqi Xue, Xinchao Wang, Jie Song, Li Sun, and Mingli Song. Customizing student networks from heterogeneous teachers via adaptive knowledge amalgamation. In *Proceedings of the IEEE International Conference on Computer Vision*, 2019.

[47] Siqi Sun, Yu Cheng, Zhe Gan, and Jingjing Liu. Patient knowledge distillation for bert model compression. *arXiv preprint arXiv:1908.09355*, 2019.

[48] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. *arXiv preprint arXiv:1910.10699*, 2019.

[49] Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7167–7176, 2017.

[50] Jesper E Van Engelen and Holger H Hoos. A survey on semi-supervised learning. *Machine Learning*, 109(2):373–440, 2020.

[51] Vladimir Vapnik. Principles of risk minimization for learning theory. In *Advances in neural information processing systems*, pages 831–838, 1992.

[52] Riccardo Volpi, Hongseok Namkoong, Ozan Sener, John Duchi, Vittorio Murino, and Silvio Savarese. Generalizing to unseen domains via adversarial data augmentation. *arXiv preprint arXiv:1805.12018*, 2018.

[53] Yaxing Wang, Chenshen Wu, Luis Herranz, Joost van de Weijer, Abel Gonzalez-Garcia, and Bogdan Raducanu. Transferring gans: generating images from limited data. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 218–234, 2018.

[54] P. Welinder, S. Branson, T. Mita, C. Wah, F. Schroff, S. Belongie, and P. Perona. Caltech-UCSD Birds 200. Technical Report CNS-TR-2010-001, California Institute of Technology, 2010.

[55] Guodong Xu, Ziwei Liu, Xiaoxiao Li, and Chen Change Loy. Knowledge distillation meets self-supervision. In *European Conference on Computer Vision*, pages 588–604. Springer, 2020.

[56] Yixing Xu, Yunhe Wang, Hanting Chen, Kai Han, XU Chunjing, Dacheng Tao, and Chang Xu. Positive-unlabeled compression on the cloud. In *Advances in Neural Information Processing Systems*, pages 2561–2570, 2019.

[57] Dingdong Yang, Seunghoon Hong, Yunseok Jang, Tianchen Zhao, and Honglak Lee. Diversity-sensitive conditional generative adversarial networks. *arXiv preprint arXiv:1901.09024*, 2019.

[58] Yiding Yang, Zunlei Feng, Mingli Song, and Xinchao Wang. Factorizable graph convolutional networks. In *Conference on Neural Information Processing Systems*, 2020.

[59] Yiding Yang, Jiayan Qiu, Mingli Song, Dacheng Tao, and Xinchao Wang. Distilling knowledge from graph convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

[60] Jingwen Ye, Yixin Ji, Xinchao Wang, Xin Gao, and Mingli Song. Data-free knowledge amalgamation via group-stack dual-gan. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

[61] Jingwen Ye, Yixin Ji, Xinchao Wang, Kairi Ou, Dapeng Tao, and Mingli Song. Student becoming the master: Knowledge amalgamation for joint scene parsing, depth estimation, and more. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019.

[62] Hongxu Yin, Pavlo Molchanov, Zhizhong Li, Jose M Alvarez, Arun Mallya, Derek Hoiem, Niraj K Jha, and Jan Kautz. Dreaming to distill: Data-free knowledge transfer via deepinversion. *arXiv preprint arXiv:1912.08795*, 2019.

[63] Shengyu Zhao, Zhijian Liu, Ji Lin, Jun-Yan Zhu, and Song Han. Differentiable augmentation for data-efficient gan training. *arXiv preprint arXiv:2006.10738*, 2020.

[64] Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

[65] Kaiyang Zhou, Ziwei Liu, Yu Qiao, Tao Xiang, and Chen Change Loy. Domain generalization: A survey. *arXiv preprint arXiv:2103.02503*, 2021.