Text-to-Image Diffusion Models are Zero-Shot Classifiers

Abstract

Text-to-image diffusion models have demonstrated remarkable generative capabilities, suggesting they learn informative representations of image-text data. However, their abilities are not fully understood and they have not been thoroughly explored on downstream tasks. We investigate diffusion models by proposing a method for evaluating them as zero-shot classifiers. The key idea is using a diffusion model's ability to denoise a noised image given a textual description of a label as a proxy for that label's likelihood. We apply our method to Imagen, using it to probe fine-grain aspects of Imagen's knowledge and comparing it with CLIP's zero-shot abilities. Imagen performs competitively with CLIP on a wide range of zero-shot image classification datasets. Additionally, it is more robust than CLIP and can successfully perform attribute binding while CLIP does not. Although generative pre-training is common in NLP, visual foundation models often use other methods such as contrastive learning. Based on our findings, we argue that generative pre-training should be explored as a compelling alternative for visual and vision-language problems.

1 Introduction

Generative text-to-image models based on denoising diffusion problablistic models (Ho et al., 2020) such as Imagen (Saharia et al., 2022a), Dalle-2 (Ramesh et al., 2022), and Stable Diffusion (Rombach et al., 2022) have demonstrated excellent abilities in generating high-resolution images and generalizing to diverse text prompts. Their strong performance suggests that they learn effective representations of image-text data. However, their ability to transfer to downstream discriminative tasks and how they compare to other pre-trained image models has not been explored thoroughly.

We investigate these questions by transferring the Imagen diffusion model to discriminative tasks. Specifically, we propose a method for using text-to-image diffusion models as zero-shot image classifiers. While Burgert et al. (2022) have explored using Stable Diffusion for zero-shot referring segmentation and Bar et al. (2022) have explored using inpainting models for few-shot pixel-level tasks, to our knowledge zero-shot classification with diffusion models has not been studied previously.

Our method essentially runs Imagen as a generative classifier (Ng & Jordan, 2001), using a re-weighted version of Imagen's variational lower bound to score images since diffusion models do not produce exact likelihoods. First, our method makes a text prompt for each class (e.g. "a photo of a cat."). Then it scores input the image conditioned on each text prompt, measuring how helpful each prompt is for denoising the image averaged over different noise levels. The class corresponding to the prompt with the best score is predicted. This classification procedure requires denoising with Imagen many times for every class (with different noise levels), so it is computationally expensive. To make it usable in practice, we present improvements that increase the method's sample efficiency by up to 1000x, such as pruning away obviously-incorrect classes early.

We compare Imagen against CLIP[1] (Radford et al., 2021), a widely used model for zero-shot image-text tasks trained with contrastive learning. First, we demonstrate that Imagen has strong zero-shot classification accuracies (competitive with CLIP) on several diverse vision datasets. Next, we show that Imagen performs robustly and achieves SOTA results ($>$50% error reduction over CLIP) on images with texture-shape conflicting cues (Geirhos et al., 2018) that have shown to

---

[1]We use the largest public CLIP model

confound pre-trained convolutional supervised models. An important use of our classification method is in quantitatively studying fine-grained aspects of what diffusion models know (as opposed to qualitatively examining model generations). We showcase this by studying attribute binding in Imagen, and find that, unlike CLIP, it can successfully bind attributes in some settings. Together, our study of Imagen suggests that text-to-image diffusion models learn powerful representations that can effectively be used for tasks beyond image generation.

2 ZERO-SHOT CLASSIFICATION USING IMAGEN

We seek to demonstrate the knowledge transfer capabilities of text-to-image diffusion models using the setting of zero-shot classification.

Imagen as a Generative Classifier We begin with a dataset, $\{(\boldsymbol{x}^1, y^1), \ldots, (\boldsymbol{x}^n, y^n)\} \subseteq \mathbb{R}^{d_1 \times d_2} \times [\mathsf{y}_K]$ of n images where each image belongs to one of K classes $[\mathsf{y}_K] := \{\mathsf{y}_1, \mathsf{y}_2, \cdots, \mathsf{y}_K\}$. Given an image $\boldsymbol{x}$, our goal is to predict the most likely class assignment

$$\tilde{y} = \arg\max_{\mathsf{y}_k} p(y = \mathsf{y}_k | \boldsymbol{x}) = \arg\max_{\mathsf{y}_k} p(\boldsymbol{x} | y = \mathsf{y}_k) \cdot p(y = \mathsf{y}_k) = \arg\max_{\mathsf{y}_k} \log p(\boldsymbol{x} | y = \mathsf{y}_k).$$

where we assume a uniform prior $p(y_i = \mathsf{y}_k) = \frac{1}{k}$ that can be dropped from the $\arg\max$.[2] A generative classifier (Ng & Jordan, 2001) uses a conditional generative model with parameters θ to estimate the likelihood as $p_\theta(\boldsymbol{x} | y = \mathsf{y}_k)$.

Imagen is conditioned on text prompts rather than class labels. Thus we convert each label, y_k, to text using a mapping T with a dataset-specific template (e.g. $\mathsf{y}_k \to$ `A photo of a` y_k). Furthermore, diffusion models do not produce exact log-likelihoods (i.e. we cannot compute $\log p_\theta(\boldsymbol{x} | y = \mathsf{y}_k)$ directly). Our key idea for a solution is to use the diffusion model's variational lower bound (VLB) as a proxy. In particular, we use $\mathcal{L}_{\text{Diffusion}}$, the portion of the VLB corresponding to denoising images, as Imagen is not trained with the other loss terms. See Appendix A for more detailed background on diffusion models and their training. The predicted class is:

$$\tilde{y} = \arg\max_{\mathsf{y}_k} \log p_\theta(\boldsymbol{x} | y = \mathsf{y}_k) \approx \arg\min_{\mathsf{y}_k} \mathcal{L}_{\text{Diffusion}}(\boldsymbol{x}, \mathsf{y}_k)$$

$$= \arg\min_{\mathsf{y}_k \in [\mathsf{y}_K]} \mathbb{E}_{\epsilon, t} \Big[\boldsymbol{w}_t \| \boldsymbol{x} - \tilde{\boldsymbol{x}}_{\boldsymbol{\theta}} \big(\boldsymbol{x}_t, \boldsymbol{c}_{\boldsymbol{\phi}}(\text{T}(\mathsf{y}_k)), t \big) \|_2^2 \Big] \tag{1}$$

Estimating the Expectation: We approximate the expectation in Equation (1) using a Monte-Carlo estimatation. At each step, we sample a $t \sim \mathcal{U}([0, 1])$ and then $\boldsymbol{x}_t$ according to the forward diffusion process (Equation (2)): $\boldsymbol{x}_t \sim q(\boldsymbol{x}_t | \boldsymbol{x}_0)$. Next, we denoise this noisy image using Imagen (i.e. we use Imagen to predict $\boldsymbol{x}$ from $\boldsymbol{x}_t$), obtaining $\hat{\boldsymbol{x}} = \tilde{\boldsymbol{x}}_{\boldsymbol{\theta}} \big(\boldsymbol{x}_t, \boldsymbol{c}_{\boldsymbol{\phi}}(\text{T}(\mathsf{y}_k)), t \big)$. We predict the class with the lowest average weighted squared error $\boldsymbol{w}_t \| \boldsymbol{x} - \hat{\boldsymbol{x}} \|_2^2$ across steps.

The choice of weighting function, $\boldsymbol{w}_t$, is crucial to the overall performance of the classification algorithm. Here, we chose $\boldsymbol{w}_t := \exp(-7t)$ which we found to work well across many datasets and use it in our experiments. Furthermore, the algorithm presented here is computationally expensive because $\mathcal{L}_{\text{Diffusion}}$ has a fairly high variance. We propose efficiency techniques that reduce the compute cost of computing argmin over classes in Appendix B.

3 EMPIRICAL ANALYSIS AND RESULTS

Here we evaluate Imagen as a zero-shot classifier on a variety of tasks. We compare with CLIP (Radford et al., 2021), which is widely used as a zero-shot classifier. Our main aim is to study the strengths and weaknesses of image-text representation learning via generative training as in Imagen and contrastive training as used for CLIP. See Appendix C for details on the experimental setup.

3.1 IMAGE CLASSIFICATION

We first evaluate the performance of Imagen on 13 datasets from Radford et al. (2021) as reported in Table 1. We use the prompt templates and class labels used by Radford et al. (2021), which renames

---

[2]We can't use a learned prior in the zero-shot setting.

Dataset	Imagen	CLIP
CIFAR10	**96.6**	94.7
CIFAR100	**84.3**	68.6
STL10	**99.6**	99.6
MNIST	**79.2**	74.3
DTD	**37.3**	36.0
Patch Camelyon	**60.3**	58.0
SVHN	**62.7**	21.50
EuroSAT	**60.3**	58.04
Imagenet	62.7	61.3 / 64.0
Stanford Cars	23.0	13.0 / 31.8
Caltech101	68.9	70.2 / 84.1
Oxford Pets	66.5	76.0 / 89.9
Food 101	68.4	83.9 / 93.3

Table 1: Percentage accuracies for zero-shot image classification. For CLIP where two numbers are reported, the accuracy correspond to two settings: downsizing the images to 64x64 and then resizing the images up to 224x224, and resizing directly to 224x224.

Task	Imagen	CLIP
Recognition (Color)	**96**	**94**
Recognition (Shape)	**85**	**98**
Binding (Color|Shape)	**70**	49
Binding (Size|Shape)	49	50
Binding (Shape|Color)	**66**	50
Pair Binding (Color)	**100**	47
Pair Binding (Size)	**99**	52
Spatial	**62**	49

Table 2: Percentage accuracy for models on zero-shot synthetic-data tasks investigating attribute binding. Bold results are better than chance. CLIP is unable to bind attributes, while Imagen can in some settings.

some classes that confuse models (e.g. "crane → "crane bird"" in Imagenet) (OpenAI, 2021b). We use the first prompt from the list, except for Imagenet, where we use "A bad photo of a *label* " since this is a good prompt for both Imagen and CLIP (OpenAI, 2021a).

Since we use the low-resolution Imagen model, we obtain results using CLIP under two settings for a fair comparison. In the first setting, we resize all the images to 64×64 which serves as the base low-resolution dataset. Imagen uses this dataset directly. CLIP requires 224×224 resolution inputs, so we bicubic-upsample the images to this size. In the second setting, we directly resize to 224×224 resolution without first going to 64x64, to obtain the best results possible using CLIP where it can take advantage of its higher input resolution compared to Imagen. The first eight datasets are all originally of resolution 64×64 or less. On these, Imagen outperforms CLIP on classification accuracy under the same evaluation setting (i.e. the models are conditioned on the same text prompts, etc). Imagen significantly outperforms CLIP on e.g. SVHN, which requires recognizing text in an image, reinforcing the qualitative observation that Imagen is good at generating images containing text (Saharia et al., 2022b). The next five datasets use higher-resolution images. For some of these, taking advantage of CLIP's higher input resolution substantially improves results. It may be possible to get similar benefits from Imagen by incorporating scores from its superresolution models, which we leave for future work to explore.

3.2 ROBUSTNESS

We next study the robustness of text-to-image diffusion models like Imagen by evaluating it on the cue conflict dataset from Geirhos et al. (2018). The dataset consists of Imagenet images altered to have a shape-texture conflict. While (for example) changing an image of a cat so it has a texture similar to elephant skin doesn't confuse humans, it could cause a model to classify the image as an elephant. We use the same setting for classification here as in Appendix C.1. Imagen achieves 82.88 % accuracy compared to 51.56% by CLIP and 79% top-5 accuracy by a supervised trained ResNet50. We provide more details in Appendix C.2.

3.3 EVALUATING ATTRIBUTE BINDING ON SYNTHETIC DATA

We next test attribute binding in Imagen and CLIP on synthetic datasets. Attribute binding is a key piece of compositional reasoning: to understand novel combinations of concepts, one must bind the concepts together and treat them as a whole. While other work has examined attribute binding in text-to-image models by qualitatively examining model generations (Nichol et al., 2021; Yu et al., 2022), our Imagen classifier offers a way of studying the question quantitatively.

Dataset Construction: We use a setup similar to Lewis et al. (2022), where images are generated based on the CLEVR (Johnson et al., 2017) dataset. CLEVR images contain various object (cubes, cylinders, and spheres) with various attributes (different sizes, colors, and materials). We use a modified version of the CLEVR rendering script that generates images containing two objects of different shapes. From these images, we construct four binary classification tasks as shown below:

Recognition tasks determine if the model can identify basic image features by scoring an attribute in the image against one not present. e.g.: A sphere. vs. A cylinder.

Single-object binding tasks test if the model binds a given attribute to the correct object. e.g.: A yellow sphere. vs. A gray sphere.

Pair binding tasks are easier binding tasks where information about both objects is provided. e.g.: A small sphere and a large cube. vs. A large sphere and a small cube.

Spatial tasks test if the model is capable of binding objects and their positions in the image. e.g.: On the left is a yellow sphere. vs. On the right is a yellow sphere.

Recognition Results: Results are shown in Table 2. Both Imagen and CLIP are able to accurately identify shapes and colors that occur in the image. Imagen is slightly worse at shape identification; we find most of these are due to it mixing up "cylinder" and "cube" when the objects are small.

Binding Results: CLIP performs no better than random chance for the attribute binding tasks, showing it is unable to map attributes to objects on this data. In contrast, Imagen performs excellently at the pair tasks, and better than chance on two of the three single tasks. Part of Imagen's advantage might be in its text encoder, the pre-trained T5 (Raffel et al., 2020) model. Saharia et al. (2022b) find that instead using CLIP's text encoder for Imagen decreased its performance on generations involving specific colors or spatial positions. Similarly, Ramesh et al. (2022) find that DALLE-2, which uses a CLIP text encoder, is worse at attribute binding than GLIDE, which uses representations from a jointly-trained transformer processing the text. However, a perhaps more significant advantage of Imagen over CLIP is its use of cross attention to allow interaction between textual and visual features.

One mistake we observed frequently in Color|Shape is Imagen preferring the color of the larger object in the image; e.g. scoring "A gray sphere" over "A yellow sphere" in Figure **??**. We hypothesize that it is helpful for denoising at high noise levels when the text conditioning provides the color for a large region of the image, even when the color is associated with the wrong shape. In the pair task, the full color information for both objects is always provided, which avoids this issue.

Spatial Positioning Results: Previous work has qualitatively found that large image generation models sometimes struggle with spatial positioning (Yu et al., 2022). We find this to be mostly true for Imagen, which performs poorly at associating objects with their position. CLIP performs even worse, performing no better than random chance. We found it prefers the caption with "right" in it over "left" 85% of the time, with it mostly ignoring the rest of the description.

4 CONCLUSION

While previous fine-grained analysis of diffusion models usually studies generated images qualitatively, our framework provides a new way of quantitatively studying them through evaluation on controlled classification tasks. We find Imagen is an effective and robust image classifier and is capable of performing attribute binding (while CLIP can't).

We hope our findings will inspire future work in using diffusion models for tasks other than generation. One direction is fine-tuning diffusion models on downstream tasks, e.g. evaluating Imagen as a classifier after further supervised training on the dataset. Our main comparison against CLIP is not direct in that the model architectures and parameter counts are different. As models become larger, a key question is how do the scaling laws (Hestness et al., 2017; Kaplan et al., 2020) of contrastive vs generative pre-training compare, which we leave for future work.

Ultimately, our method does not produce a very practical classifier, as it requires substantial compute when scoring many classes. Instead, we see the main value of this work is in revealing more about the abilities of large pre-trained diffusion models: our results suggest that generative pre-training may be a useful alternative to contrastive pre-training for text-image self-supervised learning.

REFERENCES

Amir Bar, Yossi Gandelsman, Trevor Darrell, Amir Globerson, and Alexei A Efros. Visual prompting via image inpainting. *arXiv preprint arXiv:2209.00647*, 2022.

Ryan Burgert, Kanchana Ranasinghe, Xiang Li, and Michael S Ryoo. Peekaboo: Text to Image Diffusion Models are Zero-Shot Segmentors. *arXiv preprint arXiv:2211.13224*, 2022.

Morris H DeGroot and Stephen E Fienberg. The comparison and evaluation of forecasters. *Journal of the Royal Statistical Society: Series D (The Statistician)*, 32(1-2):12–22, 1983.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. ImageNet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. *arXiv preprint arXiv:1811.12231*, 2018.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International conference on machine learning*, pp. 1321–1330. PMLR, 2017.

Joel Hestness, Sharan Narang, Newsha Ardalani, Gregory Diamos, Heewoo Jun, Hassan Kianinejad, Md Patwary, Mostofa Ali, Yang Yang, and Yanqi Zhou. Deep learning scaling is predictable, empirically. *arXiv preprint arXiv:1712.00409*, 2017.

Jonathan Ho and Tim Salimans. Classifier-free Diffusion Guidance. *arXiv preprint arXiv:2207.12598*, 2022.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Jonathan Ho, William Chan, Chitwan Saharia, Jay Whang, Ruiqi Gao, Alexey Gritsenko, Diederik P Kingma, Ben Poole, Mohammad Norouzi, David J Fleet, et al. Imagen video: High definition video generation with diffusion models. *arXiv preprint arXiv:2210.02303*, 2022a.

Jonathan Ho, Tim Salimans, Alexey Gritsenko, William Chan, Mohammad Norouzi, and David J Fleet. Video diffusion models. *arXiv preprint arXiv:2204.03458*, 2022b.

Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2901–2910, 2017.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Diederik Kingma, Tim Salimans, Ben Poole, and Jonathan Ho. Variational diffusion models. *Advances in neural information processing systems*, 34:21696–21707, 2021.

Diederik P Kingma and Max Welling. Auto-encoding Variational Bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Martha Lewis, Qinan Yu, Jack Merullo, and Ellie Pavlick. Does clip bind concepts? probing compositionality in large image models. *arXiv preprint arXiv:2212.10537*, 2022.

Andrew Ng and Michael Jordan. On discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes. *Advances in neural information processing systems*, 14, 2001.

Alex Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob McGrew, Ilya Sutskever, and Mark Chen. Glide: Towards photorealistic image generation and editing with text-guided diffusion models. In *International Conference on Machine Learning*, 2021.

Weili Nie, Brandon Guo, Yujia Huang, Chaowei Xiao, Arash Vahdat, and Anima Anandkumar. Diffusion Models for Adversarial Purification. *arXiv preprint arXiv:2205.07460*, 2022.

OpenAI. Prompt Engineering for Imagenet. *Github*, 2021a.

OpenAI. Prompts for Datasets. *Github*, 2021b.

John Platt et al. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. *Advances in large margin classifiers*, 10(3):61–74, 1999.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Chitwan Saharia, William Chan, Huiwen Chang, Chris Lee, Jonathan Ho, Tim Salimans, David Fleet, and Mohammad Norouzi. Palette: Image-to-image diffusion models. In *ACM SIGGRAPH 2022 Conference Proceedings*, pp. 1–10, 2022a.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S Sara Mahdavi, Rapha Gontijo Lopes, et al. Photorealistic Text-to-Image Diffusion Models with Deep Language Understanding. *arXiv preprint arXiv:2205.11487*, 2022b.

Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. Laion-400m: Open dataset of clip-filtered 400 million image-text pairs. *arXiv preprint arXiv:2111.02114*, 2021.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pp. 2256–2265. PMLR, 2015.

Yang Song and Stefano Ermon. Improved techniques for training score-based generative models. *Advances in neural information processing systems*, 33:12438–12448, 2020.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*, 2020.

Jiahui Yu, Yuanzhong Xu, Jing Yu Koh, Thang Luong, Gunjan Baid, Zirui Wang, Vijay Vasudevan, Alexander Ku, Yinfei Yang, Burcu Karagol Ayan, et al. Scaling autoregressive models for content-rich text-to-image generation. *arXiv preprint arXiv:2206.10789*, 2022.