BAYESIAN FEW-SHOT CLASSIFICATION WITH ONE-VS-EACH PÓLYA-GAMMA AUGMENTED GAUSSIAN PROCESSES

ABSTRACT

Few-shot classification (FSC), the task of adapting a classifier to unseen classes given a small labeled dataset, is an important step on the path toward human-like machine learning. Bayesian methods are well-suited to tackling the fundamental issue of overfitting in the few-shot scenario because they allow practitioners to specify prior beliefs and update those beliefs in light of observed data. Contemporary approaches to Bayesian few-shot classification maintain a posterior distribution over model parameters, which is slow and requires storage that scales with model size. Instead, we propose a Gaussian process classifier based on a novel combination of Pólya-gamma augmentation and the one-vs-each softmax approximation (Titsias, 2016) that allows us to efficiently marginalize over functions rather than model parameters. We demonstrate improved accuracy and uncertainty quantification on both standard few-shot classification benchmarks and few-shot domain transfer tasks.

1 INTRODUCTION

Few-shot classification (FSC) is a rapidly growing area of machine learning that seeks to build classifiers able to adapt to novel classes given only a few labeled examples. It is an important step towards machine learning systems that can successfully handle challenging situations such as personalization, rare classes, and time-varying distribution shift. The shortage of labeled data in FSC leads to uncertainty over the parameters of the model, known as *model uncertainty* or *epistemic uncertainty*. If model uncertainty is not handled properly in the few-shot setting, there is a significant risk of overfitting. In addition, FSC is increasingly being used for risk-averse applications such as medical diagnosis (Prabhu, 2019) and human-computer interfaces (Wang et al., 2019) where it is important for a few-shot classifier to know when it is uncertain.

Bayesian methods maintain a distribution over model parameters and thus provide a natural framework for capturing this inherent model uncertainty. In a Bayesian approach, a prior distribution is first placed over the parameters of a model. After data is observed, the posterior distribution over parameters is computed using Bayesian inference. This elegant treatment of model uncertainty has led to a surge of interest in Bayesian approaches to FSC that infer a posterior distribution over the weights of a neural network (Finn et al., 2018; Yoon et al., 2018; Ravi & Beatson, 2019).

Although conceptually appealing, there are several practical obstacles to applying Bayesian inference directly to the weights of a neural network. Bayesian neural networks (BNNs) are expensive from both a computational and memory perspective. Moreover, specifying meaningful priors in parameter space is known to be difficult due to the complex relationship between weights and network outputs (Sun et al., 2019). Gaussian processes (GPs) instead maintain a distribution over *functions* rather than model parameters. The prior is directly specified by a mean and covariance function, which may be parameterized by deep neural networks. When used with Gaussian likelihoods, GPs admit closed form expressions for the posterior and predictive distributions. They exchange the computational drawbacks of BNNs for cubic scaling with the number of examples. In FSC, where the number of examples is small, this is often an acceptable trade-off.

When applying GPs to classification with a softmax likelihood, the non-conjugacy of the GP prior renders posterior inference intractable. Many approximate inference methods have been proposed

to circumvent this, including variational inference and expectation propagation. In this paper we investigate a particularly promising class of approaches that augments the GP model with a set of auxiliary random variables, such that when the auxiliary variables are marginalized out the original model is recovered (Albert & Chib, 1993; Girolami & Rogers, 2006; Linderman et al., 2015). Such augmentation-based approaches typically admit efficient Gibbs-sampling procedures for generating posterior samples which when combined with Fisher's identity (Douc et al., 2014) can be used to optimize the parameters of the mean and covariance functions.

In particular, augmentation with Pólya-gamma random variables (Polson et al., 2013) makes inference tractable in logistic models. Naively, this is useful for handling binary classification, but in this paper we show how to extend this augmentation to classification with multiple classes by using the one-vs-each softmax approximation (Titsias, 2016), which can be expressed as a product of logistic sigmoids.

In this work, we make several contributions:

- We propose a novel GP classification method that combines the one-vs-each softmax approximation (Titsias, 2016) with Pólya-gamma augmentation for tractable inference.

- We demonstrate competitive classification accuracy of our method on standard FSC benchmarks and challenging domain transfer settings.

- We propose several new benchmarks for uncertainty quantification in FSC, including calibration, robustness to input noise, and out-of-episode detection.

- We demonstrate improved uncertainty quantification of our method on the proposed benchmarks relative to standard few-shot baselines.

2   RELATED WORK

Our work is related to both GP classification methods for handling non-conjugacy of classification likelihoods and Bayesian approaches to FSC. We summarize the most relevant work here.

2.1   GP CLASSIFICATION

Non-augmentation approaches. There are several classes of approaches for applying Gaussian processes to classification. The most straightforward method, known as least squares classification (Rifkin & Klautau, 2004; Williams & Rasmussen, 2006) treats class labels as real-valued observations with a Gaussian likelihood. Laplace's approximation constructs a Gaussian approximate posterior centered at the posterior mode. Variational approaches (Titsias, 2009) maximize a lower bound on the log marginal likelihood. In expectation propagation (Minka, 2001; Kim & Ghahramani, 2006), local Gaussian approximations to the likelihood are fitted iteratively until convergence.

Augmentation approaches. Augmentation-based approaches introduce auxiliary random variables such that the original model is recovered when marginalized out. Girolami & Rogers (2006) propose a Gaussian augmentation for multinomial probit regression. Linderman et al. (2015) utilize Pólya-gamma augmentation (Polson et al., 2013) and a stick-breaking construction to decompose a multinomial distribution into a product of binomials. Galy-Fajou et al. (2019) proposes a logistic-softmax likelihood for classification and uses Gamma and Poisson augmentation in addition to Pólya-gamma augmentation in order to perform inference.

2.2   FEW-SHOT CLASSIFICATION

Meta-learning. A common approach to FSC is meta-learning, which seek to learn how to update neural network parameters. The Meta-learner LSTM (Ravi & Larochelle, 2017) learns a meta-level LSTM to recurrently output a new set of parameters for the base learner. MAML (Finn et al., 2017) learns deep neural networks to perform well on the task-specific loss after one or a few steps of gradient descent on the support set by directly backpropagating through the gradient descent procedure itself. LEO (Rusu et al., 2018) performs meta-learning in a learned low-dimensional latent space from which the parameters of a classifier are generated.

Metric learning. Metric learning approaches learn distances such that input examples can be meaningfully compared. Siamese Networks (Koch et al., 2015) learn a shared embedding network along with a distance layer for computing the probability that two examples belong to the same class. Matching Networks (Vinyals et al., 2016) uses a nonparametric classification in the form of attention over nearby examples, which can be interpreted as a form of soft k-nearest neighbors in the embedding space. Prototypical Networks (Snell et al., 2017) make predictions based on distances to nearest class centroids. Relation Networks (Sung et al., 2018) instead learn a more complex neural network distance function on top of the embedding layer.

Bayesian Few-shot Classification. More recently, Bayesian FSC approaches that attempt to infer a posterior over task-specfic parameters have appeared. Grant et al. (2018) reinterprets MAML as an approximate empirical Bayes algorithm and propose LLAMA, which optimizes the Laplace approximation to the marginal likelihood. Bayesian MAML (Yoon et al., 2018) instead uses Stein Variational Gradient Descent (SVGD) (Liu & Wang, 2016) to approximate the posterior distribution over model parameters. VERSA (Gordon et al., 2019) uses amortized inference networks to obtain an approximate posterior distribution over task-specific parameters. ABML (Ravi & Beatson, 2019) uses a few steps of Bayes by Backprop (Blundell et al., 2015) on the support set to produce an approximate posterior over network parameters.

GPs for Few-shot Learning. There have been relatively few works applying GPs to few-shot learning. Tossou et al. (2019) consider Gaussian processes in the context of few-shot regression with Gaussian likelihoods. GPNet (Patacchiola et al., 2019) use Gaussian processes with least squares classification to perform few-shot classification and learn covariance functions parameterized by deep neural networks. More recently, Titsias et al. (2020) applies GPs to meta-learning with the variational information bottleneck.

3 BACKGROUND

In this section we review Pólya-gamma augmentation for binary classification and the one-vs-each approximation before introducing our method in Section 4.

3.1 PÓLYA-GAMMA AUGMENTATION

Suppose we have a vector of logits $\boldsymbol{\psi} \in \mathbb{R}^N$ with corresponding binary labels $\mathbf{y} \in \{0, 1\}^N$. The logistic likelihood is

$$p(\mathbf{y}|\boldsymbol{\psi}) = \prod_{i=1}^{N} \sigma(\psi_i)^{y_i}(1 - \sigma(\psi_i))^{1-y_i} = \prod_{i=1}^{N} \frac{(e^{\psi_i})^{y_i}}{1 + e^{\psi_i}}, \tag{1}$$

where $\sigma(\cdot)$ is the logistic sigmoid function. Let the prior over $\boldsymbol{\psi}$ be Gaussian: $p(\boldsymbol{\psi}) = \mathcal{N}(\boldsymbol{\psi}|\boldsymbol{\mu}, \boldsymbol{\Sigma})$. In Bayesian inference, we are interested in the posterior $p(\boldsymbol{\psi}|\mathbf{y}) \propto p(\mathbf{y}|\boldsymbol{\psi})p(\boldsymbol{\psi})$ but the form of (1) does not admit analytic computation due to non-conjugacy. The main idea of Pólya-gamma augmentation is to introduce auxiliary random variables $\boldsymbol{\omega}$ to the likelihood such that the original model is recovered when $\boldsymbol{\omega}$ is marginalized out: $p(\mathbf{y}|\boldsymbol{\psi}) = \int p(\boldsymbol{\omega})p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega}) \, d\boldsymbol{\omega}$. Conditioned on $\boldsymbol{\omega} \sim \mathrm{PG}(b, c)$, the likelihood is proportional to a diagonal Gaussian (see Section A for a full derivation):

$$p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega}) \propto \prod_{i=1}^{N} e^{-\omega_i \psi_i^2/2} e^{\kappa_i \psi_i} \propto \mathcal{N}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} \,|\, \boldsymbol{\psi}, \boldsymbol{\Omega}^{-1}), \tag{2}$$

where $\kappa_i = y_i - 1/2$ and $\boldsymbol{\Omega} = \mathrm{diag}(\boldsymbol{\omega})$. The conditional distribution over $\boldsymbol{\psi}$ given $\mathbf{y}$ and $\boldsymbol{\omega}$ is now tractable:

$$p(\boldsymbol{\psi}|\mathbf{y}, \boldsymbol{\omega}) \propto p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega})p(\boldsymbol{\psi}) \propto \mathcal{N}(\boldsymbol{\psi}|\tilde{\boldsymbol{\Sigma}}(\boldsymbol{\Sigma}^{-1}\boldsymbol{\mu} + \boldsymbol{\kappa}), \tilde{\boldsymbol{\Sigma}}), \tag{3}$$

where $\tilde{\boldsymbol{\Sigma}} = (\boldsymbol{\Sigma}^{-1} + \boldsymbol{\Omega})^{-1}$. The conditional distribution of $\boldsymbol{\omega}$ given $\boldsymbol{\psi}$ and $\mathbf{y}$ can also be easily computed:

$$p(\omega_i|y_i, \psi_i) \propto \mathrm{PG}(\omega_i|1, 0)e^{-\omega_i \psi_i^2/2} \propto \mathrm{PG}(\omega_i|1, \psi_i), \tag{4}$$

where the last expression follows from the exponential tilting property of Pólya-gamma random variables. This suggest a Gibbs sampling procedure in which iterates $\boldsymbol{\omega}^{(t)} \sim p(\boldsymbol{\omega}|\mathbf{y}, \boldsymbol{\psi}^{(t-1)})$ and

$\psi^{(t)} \sim p(\psi | \mathbf{X}, \mathbf{y}, \omega^{(t)})$ are drawn sequentially until the Markov chain reaches its stationary distribution, which is the joint posterior $p(\psi, \omega | \mathbf{y})$. Fortunately, efficient samplers for the Pólya-gamma distribution have been developed (Windle et al., 2014) to facilitate this.

3.2 One-vs-Each Approximation to Softmax

The one-vs-each (OVE) approximation (Titsias, 2016) was formulated as a lower bound to the softmax likelihood in order to handle classification over a large number of output classes, where computation of the normalizing constant is prohibitive. We use the OVE approximation not to deal with extreme classification, but rather due to its compatibility with Pólya-gamma augmentation, as we shall soon see. The one-vs-each approximation can be derived by first rewriting the softmax likelihood as follows:

$$p^{\text{SM}}(y = c \,|\, \mathbf{f}) \triangleq \frac{e^{f_c}}{\sum_{c'} e^{f_{c'}}} = \frac{1}{1 + \sum_{c' \neq c} e^{-(f_c - f_{c'})}}, \tag{5}$$

where $\mathbf{f} \triangleq (f_1, \dots, f_C)^\top$ are the logits. Since $\prod_i (1 + \alpha_i) \geq (1 + \sum_i \alpha_i)$ for $\alpha_i \geq 0$, the softmax likelihood (5) can be bounded as follows:

$$p^{\text{SM}}(y = c \,|\, \mathbf{f}) \geq \prod_{c' \neq c} \frac{1}{1 + e^{-(f_c - f_{c'})}} = \prod_{c' \neq c} \sigma(f_c - f_{c'}), \tag{6}$$

which is the OVE lower bound. This expression avoids the normalizing constant and factorizes into a product of pairwise sigmoids.

4 One-vs-Each Pólya-Gamma GPs

We now introduce our method for GP-based Bayesian few-shot classification, which utilizes a novel combination of Pólya-gamma augmentation and the one-vs-each (OVE) approximation.

4.1 OVE as a Likelihood Function

Suppose we have access to examples $\mathbf{X} \in \mathbb{R}^{N \times D}$ with corresponding one-hot labels $\mathbf{Y} \in \{0, 1\}^{N \times C}$, where C is the number of classes. We consider the logits jointly as a single vector $\mathbf{f} \triangleq (f_1^1, \dots, f_N^1, f_1^2, \dots, f_N^2, \dots, f_1^C, \dots, f_N^C)^\top$ and place an independent GP prior on the logits for each class: $\mathbf{f}^c(\mathbf{x}) \sim \mathcal{GP}(m(\mathbf{x}), k(\mathbf{x}, \mathbf{x}'))$. Therefore we have $p(\mathbf{f} | \mathbf{X}) = \mathcal{N}(\mathbf{f} | \boldsymbol{\mu}, \mathbf{K})$, where $\mu_i^c = m(\mathbf{x}_i)$ and $\mathbf{K}$ is block diagonal with $K_{ij}^c = k(\mathbf{x}_i, \mathbf{x}_j)$ for each block $\mathbf{K}^c$.

The Pólya-gamma integral identity used to derive (2) does not have a multi-class analogue and thus a direct application of the augmentation scheme to the softmax likelihood is nontrivial. Instead, we propose to directly replace the softmax with an OVE-based likelihood function, which is the same as (6):

$$p^{\text{OVE}}(y_i = c \,|\, \mathbf{f}_i) \triangleq \prod_{c' \neq c} \sigma(f_i^c - f_i^{c'}). \tag{7}$$

We use this likelihood not to handle extreme classification as Titsias (2016), but instead due to its close relationship with the softmax likelihood while maintaining tractable inference with Pólya-gamma augmentation. Compared to other choices of likelihoods used by previous approaches, there are several reasons to prefer OVE. Compared to the Gaussian augmentation approach of Girolami & Rogers (2006), Pólya-gamma augmentation has the benefit of fast mixing and moreover a single value of ω can capture much of the marginal distribution over function values[1]. The stick-breaking construction of Linderman et al. (2015) induces a dependence on the ordering of classes, which leads to undesirable asymmetry. Finally, the logistic-softmax likelihood of Galy-Fajou et al. (2019) requires three augmentations and careful learning of the mean function to avoid *a priori* underconfidence (see Section J for more details).

---

[1]See in particular Appendix C of (Linderman et al., 2015) for a detailed explanation of this phenomenon.

4.2 POSTERIOR INFERENCE VIA GIBBS SAMPLING

Define the matrix $\mathbf{A} \triangleq \text{OVE-MATRIX}(\mathbf{Y})$ to be a $CN \times CN$ sparse block matrix with C row partitions and C column partitions. Each block $\mathbf{A}_{cc'}$ is a diagonal $N \times N$ matrix defined as follows:

$$\mathbf{A}_{cc'} \triangleq \text{diag}(\mathbf{Y}_{\cdot c'}) - \mathbb{1}[c = c']\mathbf{I}_n, \tag{8}$$

where $\mathbf{Y}_{\cdot c'}$ denotes the c'th column of $\mathbf{Y}$. Now the binary logit vector $\boldsymbol{\psi} \triangleq \mathbf{Af} \in \mathbb{R}^{CN}$ will have entries equal to $f_i^{y_i} - f_i^c$ for each unique combination of c and i, of which there are CN in total. The OVE likelihood can now be written as $p^{\text{OVE}}(\mathbf{Y}|\boldsymbol{\psi}) = 2^N \prod_{j=1}^{NC} \sigma(\psi_j)$, where the 2^N term arises from the N cases in which $\psi_j = 0$ due to comparing the ground truth logit with itself.

Analogous to (2), the likelihood of $\boldsymbol{\psi}$ conditioned on $\boldsymbol{\omega}$ is proportional to a diagonal Gaussian:

$$p(\mathbf{Y}|\boldsymbol{\psi}, \boldsymbol{\omega}) \propto \prod_{j=1}^{NC} e^{-\omega_j \psi_j^2/2} e^{\kappa_j \psi_j} \propto \mathcal{N}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa}|\boldsymbol{\psi}, \boldsymbol{\Omega}^{-1}), \tag{9}$$

where $\kappa_j = 1/2$ and $\boldsymbol{\Omega} = \text{diag}(\boldsymbol{\omega})$. By exploiting the fact that $\boldsymbol{\psi} = \mathbf{Af}$, we can express the likelihood in terms of $\mathbf{f}$ and write down the conditional posterior as follows:

$$p(\mathbf{f}|\mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}) \propto \mathcal{N}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa}|\mathbf{Af}, \boldsymbol{\Omega}^{-1})\mathcal{N}(\mathbf{f}|\boldsymbol{\mu}, \mathbf{K}) \propto \mathcal{N}(\mathbf{f}|\tilde{\boldsymbol{\Sigma}}(\mathbf{K}^{-1}\boldsymbol{\mu} + \mathbf{A}^\top\boldsymbol{\kappa}), \tilde{\boldsymbol{\Sigma}}), \tag{10}$$

where $\tilde{\boldsymbol{\Sigma}} = (\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}$, which is an expression remarkably similar to (3). Analogous to (4), the conditional distribution over $\boldsymbol{\omega}$ given $\mathbf{f}$ and the data becomes $p(\boldsymbol{\omega}|\mathbf{y}, \mathbf{f}) = \text{PG}(\boldsymbol{\omega}|\mathbf{1}, \mathbf{Af})$.

The primary computational bottleneck of posterior inference lies in sampling $\mathbf{f}$ from (10). Since $\tilde{\boldsymbol{\Sigma}}$ is a $CN \times CN$ matrix, a naive implementation has complexity $\mathcal{O}(C^3 N^3)$. By utilizing the matrix inversion lemma and conditional Gaussian sampling techniques (Doucet, 2010), this can be brought down to $\mathcal{O}(CN^3)$ (See Appendix E for details).

4.3 LEARNING COVARIANCE HYPERPARAMETERS FOR FEW-SHOT CLASSIFICATION

We now describe how we apply OVE Pólya-gamma augmented GPs to few-shot classification. We assume the standard episodic few-shot setup in which one observes a labeled support set $\mathcal{S} = (\mathbf{X}, \mathbf{Y})$. Predictions must then be made for a query example $(\mathbf{x}_*, \mathbf{y}_*)$. We consider a zero-mean GP prior over the class logits $\mathbf{f}^c(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, k_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{x}'))$, where $\boldsymbol{\theta}$ are learnable parameters of our covariance function. These could include traditional hyperparameters such as lengthscales or the weights of a deep neural network as in deep kernel learning (Wilson et al., 2016).

We consider two objectives for learning hyperparameters of the covariance function: the marginal likelihood (ML) $p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X})$ and the predictive likelihood (PL) $p_{\boldsymbol{\theta}}(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y})$. Marginal likelihood measures the likelihood of the hyperparameters given the observed data and is intuitively appealing from a Bayesian perspective. On the other hand, many standard FSC methods optimize for predictive likelihood on the query set (Vinyals et al., 2016; Finn et al., 2017; Snell et al., 2017). Both objectives marginalize over latent functions, thereby making full use of our Bayesian formulation.

The details of these objectives and how we compute gradients can be found in Section B. Our learning algorithm for both marginal and predictive likelihood may be found in Section C. Details of computing the posterior predictive distribution $p(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega})$ may be found in Section D. Finally, details of our chosen "cosine" kernel may be found in Section G.

5 EXPERIMENTS

We compare classification accuracy and uncertainty quantification to representative baselines for several major approaches to FSC: fine-tuning, metric learning, gradient-based meta-learning, Bayesian neural network and GP-based classifiers. An overview of the baselines we used can be found in Section F.2. One of our aims is to compare methods based on uncertainty quantification. We therefore developed new benchmark evaluations and tasks: few-shot calibration, robustness, and out-of-episode detection. In order to empirically compare methods, we could not simply borrow the accuracy results from other papers, but instead needed to train each of these baselines ourselves. For all baselines except Bayesian MAML, ABML, and Logistic Softmax GP, we ran the code from

(Patacchiola et al., 2019) and verified that the accuracies matched closely to those reported by (Patacchiola et al., 2019). Additional experimental details may be found in Section F. Code for our experiments may be found in the supplementary materials.

5.1 Classification on Few-shot Benchmarks

As mentioned above, we follow the training and evaluation protocol of Patacchiola et al. (2019) for this section. We train both 1-shot and 5-shot versions of our model in four different settings: Caltech-UCSD Birds (CUB) (Wah et al., 2011), mini-Imagenet with the split proposed by Ravi & Larochelle (2017), as well as two cross-domain transfer tasks: training on mini-ImageNet and testing on CUB, and from Omniglot (Lake et al., 2011) to EMNIST (Cohen et al., 2017). We employ the commonly-used Conv4 architecture with 64 channels (Vinyals et al., 2016) for all experiments. Further experimental details and comparisons across methods can be found in the appendix. Classification results are shown in Table 1 and 2. We find that our proposed Pólya-Gamma OVE GPs yield strong classification results.

Table 1: Average accuracy and standard deviation (percentage) on 5-way FSC. Baseline results (through GPNet + Linear) are from Patacchiola et al. (2019). Evaluation is performed on 3,000 randomly generated test episodes. Standard deviation for our approach is computed by averaging over 5 batches of 600 episodes with different random seeds. The best results are highlighted in bold.

	CUB		mini-ImageNet	
Method	**1-shot**	**5-shot**	**1-shot**	**5-shot**
Feature Transfer	46.19 ± 0.64	68.40 ± 0.79	39.51 ± 0.23	60.51 ± 0.55
Baseline++	61.75 ± 0.95	78.51 ± 0.59	47.15 ± 0.49	66.18 ± 0.18
MatchingNet	60.19 ± 1.02	75.11 ± 0.35	48.25 ± 0.65	62.71 ± 0.44
ProtoNet	52.52 ± 1.90	75.93 ± 0.46	44.19 ± 1.30	64.07 ± 0.65
RelationNet	62.52 ± 0.34	78.22 ± 0.07	48.76 ± 0.17	64.20 ± 0.28
MAML	56.11 ± 0.69	74.84 ± 0.62	45.39 ± 0.49	61.58 ± 0.53
GPNet + Linear	60.23 ± 0.76	74.74 ± 0.22	48.44 ± 0.36	62.88 ± 0.46
Bayesian MAML	55.93 ± 0.71	72.87 ± 0.26	44.46 ± 0.30	62.60 ± 0.25
Bayesian MAML (Chaser)	53.93 ± 0.72	71.16 ± 0.32	43.74 ± 0.46	59.23 ± 0.34
ABML	49.57 ± 0.42	68.94 ± 0.16	37.65 ± 0.22	56.08 ± 0.29
LSM GP + Cosine (ML)	60.23 ± 0.54	74.58 ± 0.25	46.75 ± 0.20	59.93 ± 0.31
LSM GP + Cosine (PL)	60.07 ± 0.29	78.14 ± 0.07	47.05 ± 0.20	66.01 ± 0.25
OVE PG GP + Cosine (ML) [ours]	$\mathbf{63.98 \pm 0.43}$	77.44 ± 0.18	$\mathbf{50.02 \pm 0.35}$	64.58 ± 0.31
OVE PG GP + Cosine (PL) [ours]	60.11 ± 0.26	$\mathbf{79.07 \pm 0.05}$	48.00 ± 0.24	$\mathbf{67.14 \pm 0.23}$

5.2 Uncertainty Quantification through Calibration

We next turn to uncertainty quantification, an important concern for few-shot classifiers. When used in safety-critical applications such as medical diagnosis, it is important for a machine learning system to defer when there is not enough evidence to make a decision. Even in non-critical applications, precise uncertainty quantification helps practitioners in the few-shot setting determine when a class has an adequate amount of labeled data or when more labels are required, and can facilitate active learning.

We chose several commonly used metrics for calibration. Expected calibration error (ECE) (Guo et al., 2017) measures the expected binned difference between confidence and accuracy. Maximum calibration error (MCE) is similar to ECE but measures maximum difference instead of expected difference. Brier score (BRI) (Brier, 1950) is a proper scoring rule computed as the squared error between the output probabilities and the one-hot label. For a recent perspective on metrics for uncertainty evaluation, please refer to Ovadia et al. (2019). The results for representative approaches on 5-shot, 5-way CUB can be found in Figure 1. Our OVE PG GPs are the best calibrated overall across the metrics.

Table 2: Average accuracy and standard deviation (percentage) on 5-way cross-domain FSC, with the same experimental setup as in Table 1. Baseline results (through GPNet + Linear) are from (Patacchiola et al., 2019).

Method	Omniglot→EMNIST		mini-ImageNet→CUB	
	1-shot	5-shot	1-shot	5-shot
Feature Transfer	64.22 ± 1.24	86.10 ± 0.84	32.77 ± 0.35	50.34 ± 0.27
Baseline++	56.84 ± 0.91	80.01 ± 0.92	39.19 ± 0.12	$\mathbf{57.31 \pm 0.11}$
MatchingNet	75.01 ± 2.09	87.41 ± 1.79	36.98 ± 0.06	50.72 ± 0.36
ProtoNet	72.04 ± 0.82	87.22 ± 1.01	33.27 ± 1.09	52.16 ± 0.17
RelationNet	75.62 ± 1.00	87.84 ± 0.27	37.13 ± 0.20	51.76 ± 1.48
MAML	72.68 ± 1.85	83.54 ± 1.79	34.01 ± 1.25	48.83 ± 0.62
GPNet + Linear	75.97 ± 0.70	$\mathbf{89.51 \pm 0.44}$	38.72 ± 0.42	54.20 ± 0.37
Bayesian MAML	63.94 ± 0.47	65.26 ± 0.30	33.52 ± 0.36	51.35 ± 0.16
Bayesian MAML (Chaser)	55.04 ± 0.34	54.19 ± 0.32	36.22 ± 0.50	51.53 ± 0.43
ABML	76.37 ± 0.29	87.96 ± 0.28	29.35 ± 0.26	45.74 ± 0.33
LSM GP + Cosine (ML)	62.91 ± 0.49	83.80 ± 0.13	36.41 ± 0.18	50.33 ± 0.13
LSM GP + Cosine (PL)	70.70 ± 0.36	86.59 ± 0.15	36.73 ± 0.26	56.70 ± 0.31
OVE PG GP + Cosine (ML) [ours]	68.43 ± 0.67	86.22 ± 0.20	$\mathbf{39.66 \pm 0.18}$	55.71 ± 0.31
OVE PG GP + Cosine (PL) [ours]	$\mathbf{77.00 \pm 0.50}$	87.52 ± 0.19	37.49 ± 0.11	57.23 ± 0.31

Figure 1: Reliability diagrams, expected calibration error (ECE), maximum calibration error (MCE), and Brier Score (BRI) for 5-shot 5-way tasks on CUB (additional calibration results can be found in the Section H). Metrics are computed on 3,000 random tasks from the test set.

5.3 ROBUSTNESS TO INPUT NOISE

Input examples for novel classes in FSC may have been collected under conditions that do not match those observed at training time. For example, labeled support images in a medical diagnosis application may come from a different hospital than the training set. To mimic a simplified version of this scenario, we investigate robustness to input noise. We used the Imagecorruptions package (Michaelis et al., 2019) to apply Gaussian noise, impulse noise, and defocus blur to both the support set and query sets of episodes at test time and evaluated both accuracy and calibration. We used corruption severity of 5 (severe) and evaluated across 1,000 randomly generated tasks on the three datasets involving natural images. The results are shown in Figure 2. We find that in general Bayesian approaches tend to be robust due to their ability to marginalize over hypotheses consistent with the support labels. Our approach is one of the top performing methods across all settings.

5.4 OUT-OF-EPISODE DETECTION

Finally, we measure performance on out-of-episode detection, another application in which uncertainty quantification is important. In this experiment, we used 5-way, 5-shot support sets at test time but incorporated out-of-episode examples into the query set. Each episode had 150 query examples: 15 from each of 5 randomly chosen in-episode classes and 15 from each of 5 randomly chosen out-of-episode classes. We then computed the AUROC of binary outlier detection using the negative of

Figure 2: Accuracy (↑) and Brier Score (↓) when corrupting both support and query with noise on 5-way 5-shot tasks. Quantitative results may be found in Section I.

the maximum logit as the score. Intuitively, if none of the support classes assign a high logit to the example, it can be classified as an outlier. The results are shown in Figure 3. Our approach generally performs the best across the datasets.

Figure 3: Average AUROC (↑) for out-of-episode detection. The AUC is computed separately for each episode and averaged across 1,000 episodes. Bars indicate a 95% bootstrapped conf. interval.

6 DISCUSSION

In our experiments, we observed that the fine-tuning approaches are strong baselines in terms of accuracy (Baseline++ in particular), but do not produce reliable estimates of uncertainty. Methods relying on Gaussian likelihoods (RelationNet and GPNet) tend to also exhibit poor uncertainty quantification. We hypothesize this is due to the ill-suited nature of applying Gaussian likelihoods to the fundamentally discrete task of classification. Optimizing for predictive cross-entropy generally improves classification accuracy and to some extent can remedy calibration issues of marginal likelihood-based methods. The OVE likelihood is better suited to classification than the Logistic Softmax likelihood, as can be seen by comparing the accuracy and calibration results of the ML versions of these models. Overall, our proposed OVE PG GP demonstrates strong performance across a wide range of scenarios.

7 CONCLUSION

In this work, we have proposed a Bayesian few-shot classification approach based on Gaussian processes. Our method replaces the ordinary softmax likelihood with a one-vs-each likelihood and applies Pólya-Gamma augmentation to perform inference. This allows us to model class logits directly as function values and efficiently marginalize over uncertainty in each few-shot episode. Modeling functions directly enables our approach to avoid the dependence on model size that posterior inference in weight-space based models inherently have. Our approach compares favorably to baseline FSC methods under a variety of dataset and shot configurations, including dataset transfer. We also demonstrate strong uncertainty quantification, robustness to input noise, and out-of-episode detection. We believe that Bayesian modeling in genereal and GPs in particular are powerful tools for handling uncertainty and hope that our work will lead to broader adoption of efficient Bayesian inference in the few-shot scenario.

REFERENCES

James H Albert and Siddhartha Chib. Bayesian analysis of binary and polychotomous response data. *Journal of the American statistical Association*, 88(422):669–679, 1993.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *International Conference on Machine Learning*, 2015.

Glenn W Brier. Verification of forecasts expressed in terms of probability. *Monthly weather review*, 78(1):1–3, 1950.

Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Wang, and Jia-Bin Huang. A closer look at few-shot classification. In *International Conference on Learning Representations*, 2019.

Gregory Cohen, Saeed Afshar, Jonathan Tapson, and Andre Van Schaik. Emnist: Extending mnist to handwritten letters. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 2921–2926. IEEE, 2017.

Randal Douc, Eric Moulines, and David Stoffer. *Nonlinear time series: Theory, methods and applications with R examples*. CRC press, 2014.

A Doucet. A note on efficient conditional simulation of gaussian distributions. *Departments of Computer Science and Statistics, University of British Columbia*, 1020, 2010.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, 2017.

Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*, pp. 9516–9527, 2018.

Ronald A Fisher. The use of multiple measurements in taxonomic problems. *Annals of eugenics*, 7 (2):179–188, 1936.

Théo Galy-Fajou, Florian Wenzel, Christian Donner, and Manfred Opper. Multi-class gaussian process classification made conjugate: Efficient inference via data augmentation. In *Uncertainty in Artificial Intelligence*, 2019.

Mark Girolami and Simon Rogers. Variational bayesian multinomial probit regression with gaussian process priors. *Neural Computation*, 18(8):1790–1817, 2006.

Jonathan Gordon, John Bronskill, Matthias Bauer, Sebastian Nowozin, and Richard E Turner. Meta-learning probabilistic inference for prediction. In *International Conference on Learning Representations*, 2019.

Erin Grant, Chelsea Finn, Sergey Levine, Trevor Darrell, and Thomas Griffiths. Recasting gradient-based meta-learning as hierarchical bayes. *arXiv preprint arXiv:1801.08930*, 2018.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1321–1330. JMLR. org, 2017.

Nathan Hilliard, Lawrence Phillips, Scott Howland, Artëm Yankov, Courtney D Corley, and Nathan O Hodas. Few-shot learning with metric-agnostic conditional embeddings. *arXiv preprint arXiv:1802.04376*, 2018.

Yehuda Hoffman and Erez Ribak. Constrained realizations of gaussian fields-a simple algorithm. *The Astrophysical Journal*, 380:L5–L8, 1991.

Hyun-Chul Kim and Zoubin Ghahramani. Bayesian gaussian process classification with the em-ep algorithm. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(12):1948–1959, 2006.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Advances in neural information processing systems*, pp. 2575–2583, 2015.

Gregory Koch, Richard Zemel, and Ruslan Salakhutdinov. Siamese neural networks for one-shot image recognition. In *ICML deep learning workshop*, volume 2. Lille, 2015.

Brenden Lake, Ruslan Salakhutdinov, Jason Gross, and Joshua Tenenbaum. One shot learning of simple visual concepts. In *Proceedings of the annual meeting of the cognitive science society*, 2011.

Scott Linderman, Matthew J Johnson, and Ryan P Adams. Dependent multinomial models made easy: Stick-breaking with the pólya-gamma augmentation. In *Advances in Neural Information Processing Systems*, pp. 3456–3464, 2015.

Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose bayesian inference algorithm. In *Advances in neural information processing systems*, pp. 2378–2386, 2016.

Claudio Michaelis, Benjamin Mitzkus, Robert Geirhos, Evgenia Rusak, Oliver Bringmann, Alexander S. Ecker, Matthias Bethge, and Wieland Brendel. Benchmarking robustness in object detection: Autonomous driving when winter is coming. *arXiv preprint arXiv:1907.07484*, 2019.

Thomas Peter Minka. *A family of algorithms for approximate Bayesian inference*. PhD thesis, Massachusetts Institute of Technology, 2001.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, pp. 13969–13980, 2019.

Massimiliano Patacchiola, Jack Turner, Elliot J Crowley, Michael O'Boyle, and Amos Storkey. Deep kernel transfer in gaussian processes for few-shot learning. *arXiv preprint arXiv:1910.05199*, 2019.

Nicholas G Polson, James G Scott, and Jesse Windle. Bayesian inference for logistic models using pólya–gamma latent variables. *Journal of the American statistical Association*, 108(504):1339–1349, 2013.

Viraj Uday Prabhu. Few-shot learning for dermatological disease diagnosis. Master's thesis, Georgia Institute of Technology, 2019.

Sachin Ravi and Alex Beatson. Amortized bayesian meta-learning. In *International Conference on Learning Representations*, 2019.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2017.

Ryan Rifkin and Aldebaro Klautau. In defense of one-vs-all classification. *Journal of machine learning research*, 5(Jan):101–141, 2004.

Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. *arXiv preprint arXiv:1807.05960*, 2018.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, 2017.

Shengyang Sun, Guodong Zhang, Jiaxin Shi, and Roger Grosse. Functional variational bayesian neural networks. In *International Conference on Learning Representations*, 2019.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales. Learning to compare: Relation network for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *Artificial Intelligence and Statistics*, pp. 567–574, 2009.

Michalis K Titsias. One-vs-each approximation to softmax for scalable estimation of probabilities. In *Advances in Neural Information Processing Systems*, pp. 4161–4169, 2016.

Michalis K Titsias, Sotirios Nikoloutsopoulos, and Alexandre Galashov. Information theoretic meta learning with gaussian processes. *arXiv preprint arXiv:2009.03228*, 2020.

Prudencio Tossou, Basile Dura, Francois Laviolette, Mario Marchand, and Alexandre Lacoste. Adaptive deep kernel learning. *arXiv preprint arXiv:1905.12131*, 2019.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, 2016.

Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. computation & neural systems technical report. *California Institute of Technology*, 2011.

Kuan-Chieh Wang, Jixuan Wang, Khai Truong, and Richard Zemel. Customizable facial gesture recognition for improved assistive technology. In *ICLR AI for social good workshop*, 2019.

Yeming Wen, Paul Vicol, Jimmy Ba, Dustin Tran, and Roger Grosse. Flipout: Efficient pseudo-independent weight perturbations on mini-batches. In *International Conference on Representation Learning*, 2018.

Christopher KI Williams and Carl Edward Rasmussen. *Gaussian processes for machine learning*. MIT press Cambridge, MA, 2006.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial Intelligence and Statistics*, pp. 370–378, 2016.

Jesse Windle, Nicholas G Polson, and James G Scott. Sampling pólya-gamma random variates: alternate and approximate techniques. *arXiv preprint arXiv:1405.0506*, 2014.

Jaesik Yoon, Taesup Kim, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*, pp. 7332–7342, 2018.

A DERIVATION OF PÓLYA-GAMMA AUGMENTED LOGISTIC LIKELIHOOD

In this section, we show the derivation for the augmented logistic likelihood presented in Section 3.1. First, recall the logistic likelihood:

$$p(\mathbf{y}|\boldsymbol{\psi}) = \prod_{i=1}^{N} \sigma(\psi_i)^{y_i}(1 - \sigma(\psi_i))^{1-y_i} = \prod_{i=1}^{N} \frac{(e^{\psi_i})^{y_i}}{1 + e^{\psi_i}}, \tag{11}$$

where $\sigma(\cdot)$ is the logistic sigmoid function. We have a Gaussian prior $p(\boldsymbol{\psi}) = \mathcal{N}(\boldsymbol{\psi}|\boldsymbol{\mu}, \boldsymbol{\Sigma})$ and introduce Pólya-gamma auxiliary random variables $\boldsymbol{\omega}$ to the likelihood such that the original model is recovered when $\boldsymbol{\omega}$ is marginalized out: $p(\mathbf{y}|\boldsymbol{\psi}) = \int p(\boldsymbol{\omega})p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega}) \, d\boldsymbol{\omega}$.

The Pólya-gamma distribution $\omega \sim \text{PG}(b, c)$ can be written as an infinite convolution of gamma distributions:

$$\omega \overset{D}{=} \frac{1}{2\pi^2} \sum_{k=1}^{\infty} \frac{\text{Ga}(b, 1)}{(k - 1/2)^2 + c^2/(4\pi^2)}. \tag{12}$$

The following integral identity holds for $b > 0$:

$$\frac{(e^{\psi})^a}{(1 + e^{\psi})^b} = 2^{-b} e^{\kappa\psi} \int_0^{\infty} e^{-\omega\psi^2/2} p(\omega) \, d\omega, \tag{13}$$

where $\kappa = a - b/2$ and $\omega \sim \text{PG}(b, 0)$. Specifically, when $a = y$ and $b = 1$, we recover an individual term of the logistic likelihood (11):

$$p(y|\psi) = \frac{(e^{\psi})^y}{1 + e^{\psi}} = \frac{1}{2} e^{\kappa\psi} \int_0^{\infty} e^{-\omega\psi^2/2} p(\omega) \, d\omega, \tag{14}$$

where $\kappa = y - 1/2$ and $\omega \sim PG(1,0)$. Conditioned on ω, the batch likelihood is proportional to a diagonal Gaussian:

$$p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega}) \propto \prod_{i=1}^{N} e^{-\omega_i \psi_i^2/2} e^{\kappa_i \psi_i} \propto \mathcal{N}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} \,|\, \boldsymbol{\psi}, \boldsymbol{\Omega}^{-1}), \tag{15}$$

where $\kappa_i = y_i - 1/2$ and $\boldsymbol{\Omega} = \mathrm{diag}(\boldsymbol{\omega})$. The conditional distribution over $\boldsymbol{\psi}$ given $\mathbf{y}$ and $\boldsymbol{\omega}$ is now tractable:

$$p(\boldsymbol{\psi}|\mathbf{y}, \boldsymbol{\omega}) \propto p(\mathbf{y}|\boldsymbol{\psi}, \boldsymbol{\omega})p(\boldsymbol{\psi}) \propto \mathcal{N}(\boldsymbol{\psi}|\tilde{\boldsymbol{\Sigma}}(\boldsymbol{\Sigma}^{-1}\boldsymbol{\mu} + \boldsymbol{\kappa}), \tilde{\boldsymbol{\Sigma}}), \tag{16}$$

where $\tilde{\boldsymbol{\Sigma}} = (\boldsymbol{\Sigma}^{-1} + \boldsymbol{\Omega})^{-1}$.

B MARGINAL LIKELIHOOD AND PREDICTIVE LIKELIHOOD OBJECTIVES

Marginal Likelihood (ML). The log marginal likelihood can be written as follows:

$$\mathcal{L}^{\mathrm{ML}}(\boldsymbol{\theta}) \triangleq \log \int p(\boldsymbol{\omega})p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X}, \boldsymbol{\omega}) \, d\boldsymbol{\omega}, \tag{17}$$

where $p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X}, \boldsymbol{\omega}) = \int p(\mathbf{Y}|\mathbf{f}, \boldsymbol{\omega})p_{\boldsymbol{\theta}}(\mathbf{f}|\mathbf{X}) \, d\mathbf{f}$. The gradient of the log marginal likelihood can be estimated by posterior samples $\boldsymbol{\omega} \sim p_{\boldsymbol{\theta}}(\boldsymbol{\omega}|\mathbf{X}, \mathbf{Y})$. In practice, we use a stochastic training objective based on samples of $\boldsymbol{\omega}$ from Gibbs chains. We use Fisher's identity (Douc et al., 2014) to derive the following gradient estimator:

$$\nabla_{\boldsymbol{\theta}}\mathcal{L}^{\mathrm{ML}} = \int p_{\boldsymbol{\theta}}(\boldsymbol{\omega}|\mathbf{X}, \mathbf{Y})\nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X}, \boldsymbol{\omega}) \, d\boldsymbol{\omega} \approx \frac{1}{M}\sum_{m=1}^{M} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X}, \boldsymbol{\omega}^{(m)}), \tag{18}$$

where $\boldsymbol{\omega}^{(1)}, \ldots, \boldsymbol{\omega}^{(M)}$ are samples from the posterior Gibbs chain. As suggested by Patacchiola et al. (2019), who applied GPs to FSC via least-squares classification, we merge the support and query sets during learning to take full advantage of the available data within each episode.

Predictive Likelihood (PL). The expected log predictive likelihood for a query example $\mathbf{x}_*$ is:

$$\mathcal{L}^{\mathrm{PL}}(\boldsymbol{\theta}) \triangleq \log \int p(\boldsymbol{\omega})p_{\boldsymbol{\theta}}(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}) \, d\boldsymbol{\omega}. \tag{19}$$

We use an approximate gradient estimator again based on posterior samples of $\boldsymbol{\omega}$:

$$\nabla_{\boldsymbol{\theta}}\mathcal{L}^{\mathrm{PL}} \approx \int p_{\boldsymbol{\theta}}(\boldsymbol{\omega}|\mathbf{X}, \mathbf{Y})\nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}) \, d\boldsymbol{\omega} \approx \frac{1}{M}\sum_{m=1}^{M} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}^{(m)}). \tag{20}$$

We note that this is not an unbiased estimator of the gradient, but find it works well in practice.

C LEARNING ALGORITHM

Our learning algorithm for both marginal and predictive likelihood is summarized in Algorithm 1.

Algorithm 1 One-vs-Each Pólya-Gamma GP Learning

Input: Objective $\mathcal{L} \in \{\mathcal{L}^{\mathrm{ML}}, \mathcal{L}^{\mathrm{PL}}\}$, Task distribution $\mathcal{T}$, number of parallel Gibbs chains M, number of steps T, learning rate η.

Initialize hyperparameters $\boldsymbol{\theta}$ randomly.
repeat
    Sample $\mathcal{S} = (\mathbf{X}, \mathbf{Y}), \mathcal{Q} = (\mathbf{X}_*, \mathbf{Y}_*) \sim \mathcal{T}$
    if $\mathcal{L} = \mathcal{L}^{\mathrm{ML}}$ **then**
        $\mathbf{X} \leftarrow \mathbf{X} \cup \mathbf{X}_*, \mathbf{Y} \leftarrow \mathbf{Y} \cup \mathbf{Y}_*$
    end if
    $\mathbf{A} \leftarrow \text{OVE-MATRIX}(\mathbf{Y})$
    for $m = 1$ **to** M **do**
        $\boldsymbol{\omega}_0^{(m)} \sim PG(1, 0), \mathbf{f}_0^{(m)} \sim p_{\boldsymbol{\theta}}(\mathbf{f}|\mathbf{X})$
        for $t = 1$ **to** T **do**
            $\boldsymbol{\psi}_t^{(m)} \leftarrow \mathbf{A}\mathbf{f}_{t-1}^{(m)}$
            $\boldsymbol{\omega}_t^{(m)} \sim PG(1, \boldsymbol{\psi}_t^{(m)})$
            $\mathbf{f}_t^{(m)} \sim p_{\boldsymbol{\theta}}(\mathbf{f}|\mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}_t^{(m)})$
        end for
    end for
    if $\mathcal{L} = \mathcal{L}^{\mathrm{ML}}$ **then**
        $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \frac{\eta}{M} \sum_{m=1}^{M} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{Y}|\mathbf{X}, \boldsymbol{\omega}_T^{(m)})$
    else
        $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \frac{\eta}{M} \sum_{m=1}^{M} \sum_j \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{y}_{*j}|\mathbf{x}_{*j}, \mathcal{S}, \boldsymbol{\omega}_T^{(m)})$
    end if
until convergence

D   POSTERIOR PREDICTIVE DISTRIBUTION

The posterior predictive distribution for a query example $\mathbf{x}_*$ conditioned on $\boldsymbol{\omega}$ is:

$$p(\mathbf{y}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}) = \int p(\mathbf{y}_*|\mathbf{f}_*)p(\mathbf{f}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega})\, d\mathbf{f}_*, \tag{21}$$

where $\mathbf{f}_*$ are the query example's logits. The predictive distribution over $\mathbf{f}_*$ can be obtained by noting that $\boldsymbol{\psi}$ and the query logits are jointly Gaussian:

$$\begin{bmatrix} \boldsymbol{\psi} \\ \mathbf{f}_* \end{bmatrix} \sim \mathcal{N}\left(0, \begin{bmatrix} \mathbf{AKA}^\top + \boldsymbol{\Omega}^{-1} & \mathbf{AK}_* \\ (\mathbf{AK}_*)^\top & \mathbf{K}_{**} \end{bmatrix}\right), \tag{22}$$

where $\mathbf{K}_*$ is the $NC \times C$ block diagonal matrix with blocks $K_\theta(\mathbf{X}, \mathbf{x}_*)$ and $\mathbf{K}_{**}$ is the $C \times C$ diagonal matrix with diagonal entries $k_\theta(\mathbf{x}_*, \mathbf{x}_*)$. The predictive distribution becomes:

$$p(\mathbf{f}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega}) = \mathcal{N}(\mathbf{f}_*|\boldsymbol{\mu}_*, \boldsymbol{\Sigma}_*), \text{ where}$$
$$\boldsymbol{\mu}_* = (\mathbf{AK}_*)^\top(\mathbf{AKA}^\top + \boldsymbol{\Omega}^{-1})^{-1}\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} \text{ and} \tag{23}$$
$$\boldsymbol{\Sigma}_* = \mathbf{K}_{**} - (\mathbf{AK}_*)^\top(\mathbf{AKA}^\top + \boldsymbol{\Omega}^{-1})^{-1}\mathbf{AK}_*.$$

With $p(\mathbf{f}_*|\mathbf{x}_*, \mathbf{X}, \mathbf{Y}, \boldsymbol{\omega})$ in hand, the integral in equation (21) can easily be computed numerically for each class c by forming the corresponding OVE linear transformation matrix $\mathbf{A}^c$ and then performing 1D Gaussian-Hermite quadrature on each dimension of $\mathcal{N}(\boldsymbol{\psi}_*^c|\mathbf{A}^c\boldsymbol{\mu}^*, \mathbf{A}^c\boldsymbol{\Sigma}_*\mathbf{A}^{c\top})$.

E   EFFICIENT CONDITIONAL SAMPLING OF $\mathbf{f}$

The Gibbs conditional distribution over $\mathbf{f}$ is given by:

$$p(\mathbf{f}|\mathbf{X}, \mathbf{y}, \boldsymbol{\omega}) = \mathcal{N}(\mathbf{f}|\tilde{\boldsymbol{\Sigma}}(\mathbf{K}^{-1}\boldsymbol{\mu} + \mathbf{A}^\top\boldsymbol{\kappa}), \tilde{\boldsymbol{\Sigma}}), \tag{24}$$

where $\tilde{\boldsymbol{\Sigma}} = (\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}$. Naively sampling from this distribution requires $\mathcal{O}(C^3N^3)$ computation since $\tilde{\boldsymbol{\Sigma}}$ is a $CN \times CN$ matrix. Here we describe a method for sampling from this distribution that requires $\mathcal{O}(CN^3)$ computation instead.

First, we note that equation (24) can be interpreted as the conditional distribution $p(\mathbf{f}|\mathbf{z} = \boldsymbol{\Omega}^{-1}\boldsymbol{\kappa})$ resulting from the following marginal distribution $p(\mathbf{f})$ and conditional $p(\mathbf{z}|\mathbf{f})$:

$$p(\mathbf{f}) = \mathcal{N}(\mathbf{f}|\boldsymbol{\mu}, \mathbf{K}) \tag{25}$$

$$p(\mathbf{z}|\mathbf{f}) = \mathcal{N}(\mathbf{z}|\mathbf{Af}, \boldsymbol{\Omega}^{-1}), \tag{26}$$

where we have made implicit the dependence on $\mathbf{X}, \mathbf{Y}$, and $\boldsymbol{\omega}$ for brevity of notation. Equivalently, the distribution over $\mathbf{f}$ and $\mathbf{z}$ can be represented by the partitioned Gaussian

$$\begin{bmatrix} \mathbf{f} \\ \mathbf{z} \end{bmatrix} \sim \mathcal{N} \left(\begin{bmatrix} \boldsymbol{\mu} \\ \mathbf{A}\boldsymbol{\mu} \end{bmatrix}, \begin{bmatrix} \mathbf{K} & \mathbf{K}\mathbf{A}^\top \\ \mathbf{A}\mathbf{K} & \mathbf{A}\mathbf{K}\mathbf{A}^\top + \boldsymbol{\Omega}^{-1} \end{bmatrix} \right). \tag{27}$$

The conditional distribution $p(\mathbf{f}|\mathbf{z})$ is given as:

$$p(\mathbf{f}|\mathbf{z}) = \mathcal{N}(\mathbf{f}|\tilde{\boldsymbol{\Sigma}}(\mathbf{K}^{-1}\boldsymbol{\mu} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{z}), \tilde{\boldsymbol{\Sigma}}), \tag{28}$$

where $\tilde{\boldsymbol{\Sigma}} = (\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}$. Note that $p(\mathbf{f}|\mathbf{z} = \boldsymbol{\Omega}^{-1}\boldsymbol{\kappa})$ recovers our desired Gibbs conditional distribution from equation (24).

An efficient approach to conditional Gaussian sampling is due to Hoffman & Ribak (1991) and described in greater clarity by Doucet (2010). The procedure is as follows:

1. Sample $\mathbf{f}_0 \sim p(\mathbf{f})$ and $\mathbf{z}_0 \sim p(\mathbf{z}|\mathbf{f})$.
2. Return $\bar{\mathbf{f}} = \mathbf{f}_0 + \mathbf{K}\mathbf{A}^\top(\mathbf{A}\mathbf{K}\mathbf{A}^\top + \boldsymbol{\Omega}^{-1})^{-1}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} - \mathbf{z}_0)$ as the sample from $p(\mathbf{f}|\mathbf{z})$.

$\mathbf{K}$ is block diagonal and thus sampling from $p(\mathbf{f})$ requires $\mathcal{O}(CN^3)$ time. $\mathbf{Af}$ can be computed in $\mathcal{O}(CN)$ time, since each entry is the difference between $f_i^{y_i}$ and f_i^c for some i and c. Overall, step 1 requires $\mathcal{O}(CN^3)$ time.

We now show how to compute $\bar{\mathbf{f}}$ from step 2 in $\mathcal{O}(CN^3)$ time. We first expand $(\mathbf{A}\mathbf{K}\mathbf{A}^\top + \boldsymbol{\Omega}^{-1})^{-1}$:

$$(\mathbf{A}\mathbf{K}\mathbf{A}^\top + \boldsymbol{\Omega}^{-1})^{-1} = \boldsymbol{\Omega} - \boldsymbol{\Omega}\mathbf{A}(\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}\mathbf{A}^\top\boldsymbol{\Omega} \tag{29}$$

We substitute into the expression for $\bar{\mathbf{f}}$:

$$\bar{\mathbf{f}} = \mathbf{f}_0 + \mathbf{K}\mathbf{A}^\top(\boldsymbol{\Omega} - \boldsymbol{\Omega}\mathbf{A}(\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}\mathbf{A}^\top\boldsymbol{\Omega})(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} - \mathbf{z}_0) \tag{30}$$

$$= \mathbf{f}_0 + \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} - \mathbf{z}_0) - \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}(\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}\mathbf{A}^\top\boldsymbol{\Omega}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} - \mathbf{z}_0) \tag{31}$$

$$= \mathbf{f}_0 + \mathbf{K}\mathbf{v} - \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}(\mathbf{K}^{-1} + \mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A})^{-1}\mathbf{v}, \tag{32}$$

where we have defined $\mathbf{v} \triangleq \mathbf{A}^\top\boldsymbol{\Omega}(\boldsymbol{\Omega}^{-1}\boldsymbol{\kappa} - \mathbf{z}_0)$.

Now let $\mathbf{d} \triangleq (d_1^1, \ldots, d_N^1, d_1^2, \ldots, d_N^2, \ldots, d_1^C, \ldots, d_N^C)^\top$, where $d_i^c = Y_{ic}\sum_{c'}\omega_i^{c'}$. Define $\mathbf{Y}^\dagger$ to be the $CN \times N$ matrix produced by vertically stacking $\text{diag}(Y_{\cdot c})$, and let $\mathbf{W}^\dagger$ be the $CN \times N$ matrix produced by vertically stacking $\text{diag}((\omega_1^c, \ldots, \omega_N^c)^\top)$. $\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}$ may then be written as follows:

$$\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A} = \mathbf{D} - \mathbf{S}\mathbf{P}\mathbf{S}^\top, \text{ where} \tag{33}$$

$$\mathbf{D} = \boldsymbol{\Omega} + \text{diag}(\mathbf{d}), \tag{34}$$

$$\mathbf{S} = \begin{bmatrix} \mathbf{Y}^\dagger & \mathbf{W}^\dagger \end{bmatrix}, \tag{35}$$

$$\mathbf{P} = \begin{bmatrix} \mathbf{0}_N & \mathbf{I}_N \\ \mathbf{I}_N & \mathbf{0}_N \end{bmatrix}. \tag{36}$$

Substituting (33) into (32):

$$\bar{\mathbf{f}} = \mathbf{f}_0 + \mathbf{K}\mathbf{v} - \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}(\mathbf{K}^{-1} + \mathbf{D} - \mathbf{S}\mathbf{P}\mathbf{S}^\top)^{-1}\mathbf{v}. \tag{37}$$

Now we expand $(\mathbf{K}^{-1} + \mathbf{D} - \mathbf{S}\mathbf{P}\mathbf{S}^\top)^{-1}$:

$$(\mathbf{K}^{-1} + \mathbf{D} - \mathbf{S}\mathbf{P}\mathbf{S}^\top)^{-1} = \mathbf{E} - \mathbf{E}\mathbf{S}(\mathbf{S}^\top\mathbf{E}\mathbf{S} - \mathbf{P}^{-1})^{-1}\mathbf{S}^\top\mathbf{E}, \tag{38}$$

where $\mathbf{E} = (\mathbf{K}^{-1} + \mathbf{D})^{-1} = \mathbf{K}(\mathbf{K} + \mathbf{D}^{-1})^{-1}\mathbf{D}^{-1}$ is a block-diagonal matrix that can be computed in $\mathcal{O}(CN^3)$ time, since $\mathbf{D}$ is diagonal and $\mathbf{K}$ is block diagonal. Now, substituting (38) back into (37),

$$\bar{\mathbf{f}} = \mathbf{f}_0 + \mathbf{K}\mathbf{v} - \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}\mathbf{E}\mathbf{v} + \mathbf{K}\mathbf{A}^\top\boldsymbol{\Omega}\mathbf{A}\mathbf{E}\mathbf{S}(\mathbf{S}^\top\mathbf{E}\mathbf{S} - \mathbf{P}^{-1})^{-1}\mathbf{S}^\top\mathbf{E}\mathbf{v}. \tag{39}$$

Note that $(\mathbf{S}^\top\mathbf{E}\mathbf{S} - \mathbf{P}^{-1})^{-1}$ is a $2N \times 2N$ matrix and thus can be inverted in $\mathcal{O}(N^3)$ time. The overall complexity is therefore $\mathcal{O}(CN^3)$.

F EXPERIMENTAL DETAILS

Here we provide more details about our experimental setup for our classification experiments, which are based on the protocol of (Patacchiola et al., 2019).

F.1 DATASETS

We used the four dataset scenarios described below. The first three are the same used by Chen et al. (2019) and the final was proposed by Patacchiola et al. (2019).

- **CUB.** Caltech-UCSD Birds (CUB) (Wah et al., 2011) consists of 200 classes and 11,788 images. A split of 100 training, 50 validation, and 50 test classes was used (Hilliard et al., 2018; Chen et al., 2019).
- **mini-Imagenet.** The mini-Imagenet dataset (Vinyals et al., 2016) consists of 100 classes with 600 images per class. We used the split proposed by Ravi & Larochelle (2017), which has 64 classes for training, 16 for validation, and 20 for test.
- **mini-Imagenet→CUB.** This cross-domain transfer scenario takes the training split of mini-Imagenet and the validation & test splits of CUB.
- **Omniglot → EMNIST.** We use the same setup as proposed by Patacchiola et al. (2019). Omniglot (Lake et al., 2011) consists of 1,623 classes, each with 20 examples, and is augmented by rotations of 90 degrees to create 6,492 classes, of which 4,114 are used for training. The EMNIST dataset (Cohen et al., 2017), consisting of 62 classes, is split into 31 training and 31 test classes.

F.2 BASELINES

We compare to a variety of baselines, explained here in more detail.

- **Feature Transfer** (Chen et al., 2019) involves first training an off-line classifier on the training classes and then training a new classification layer on the episode.
- **Baseline++** (Chen et al., 2019) is similar to Feature Transfer except it uses a cosine distance module prior to the softmax during fine-tuning.
- **Matching Networks** (Vinyals et al., 2016) can be viewed as a soft form of k-nearest neighbors that computes attention and sums over the support examples to form a predictive distribution over classes.
- **Prototypical Networks** (Snell et al., 2017) computes class means (prototypes) and forms a predictive distribution based on Euclidean distance to the prototypes. It can be viewed as a Gaussian classifier operating in an embedding space.
- **MAML** (Finn et al., 2017) performs one or a few steps of gradient descent on the support set and then makes predictions on the query set, backpropagating through the gradient descent procedure. For this baseline, we simply quote the classification accuracy reported by (Patacchiola et al., 2019).
- **RelationNet** (Sung et al., 2018) rather than using a predefined distance metric as in Matching Networks or Prototypical Networks instead learns a deep distance metric as the output of a neural network that accepts as input the latent representation of both examples. It is trained to minimize squared error of output predictions.
- **GPNet** (Patacchiola et al., 2019) relies on least squares classification to maintain tractability of Gaussian process posterior inference. This is concurrent work to ours and so we compare to their results with a linear kernel (the latest version at the time the bulk of our experiments were performed). This work has since been renamed to GPShot.
- **Bayesian MAML** (Yoon et al., 2018) relies on Stein Variational Gradient Descent (SVGD) (Liu & Wang, 2016) to get an approximate posterior distribution in weight-space. We compare to both the non-chaser version, which optimizes cross-entropy of query predictions, and the chaser version, which optimizes mean squared error between the approximate posterior on the support set and the approximate posterior on the merged support & query set.

The non-chaser version is therefore related to predictive likelihood methods and the chaser version is more analogous to the marginal likelihood methods. For the non-chaser version, we used 20 particles and 1 step of adaptation at both train and test time. For the chaser version, we also used 20 particles. At train time, the chaser took 1 step and the leader 1 additional step. At test time, we used 5 steps of adaptation. Due to the slow performance of this method, we followed the advice of Yoon et al. (2018) and only performed adaptation on the final layer of weights, which may help explain the drop in performance relative to MAML. The authors only released Tensorflow code for regression, so we reimplemented this baseline in PyTorch.

- **Amortized Bayesian Meta-Learning (ABML)** (Ravi & Beatson, 2019) performs a few steps of Bayes-by-backprop (Blundell et al., 2015) in order to infer a fully-factorized approximate posterior over the weights. The authors did not release code and so we implemented our own version of ABML in PyTorch. We found the weighting on the inner and outer KL divergences to be important for achieving good performance. We took the negative log likelihood to be mean cross entropy and used an inner KL weight of 0.01 and an outer KL weight of 0.001, which values were arrived upon by doing a small amount of hyperparameter tuning on the Omniglot$\rightarrow$ EMNIST dataset. We used $\alpha = 1.0$ and $\beta = 0.01$ for the Gamma prior over the weights. We only applied ABML to the weights of the network; the biases were learned as point estimates. We used 4 steps of adaptation and took 5 samples when computing expectations (using any more than this did not fit into GPU memory). We used the local reparameterization trick (Kingma et al., 2015) and flipout (Wen et al., 2018) when computing expectations in order to reduce variance. In order to match the architecture used by Ravi & Beatson (2019), we trained this baseline with 32 filters throughout the classification network.

- **Logistic Softmax GP** (Galy-Fajou et al., 2019) is the multi-class Gaussian process classification method that relies on the logistic softmax likelihood. Galy-Fajou et al. (2019) did not consider few-shot, but we use the same objectives described in Section 3.3 of the main paper to adapt this method to FSC. In addition, we used the cosine kernel (see Section G for a description) that we found to work best with our OVE PG GPs. For this method, we found it important to learn a constant mean function (rather than a zero mean) in order to improve calibration. Please refer to Section J for a possible explanation why this is necessary.

F.3 TRAINING DETAILS

All methods employed the commonly-used Conv4 architecture (Vinyals et al., 2016) (see Table 3 for a detailed specification), except ABML which used 32 filters throughout. All of our experiments used the Adam (Kingma & Ba, 2014) optimizer with learning rate 10^{-3}. During training, all models used epochs consisting of 100 randomly sampled episodes. A single gradient descent step on the encoder network and relevant hyperparameters is made per episode. All 1-shot models are trained for 600 epochs and 5-shot models are trained for 400 epochs. Each episode contained 5 classes (5-way) and 16 query examples. At test time, 15 query examples are used for each episode. Early stopping was performed by monitoring accuracy on the validation set. The validation set was not used for retraining.

We train both marginal likelihood and predictive likelihood versions of our models. For Pólya-gamma sampling we use the PyPólyaGamma package[2]. During training, we use a single step of Gibbs (T=1). For evaluation, we run until $T = 50$. In both training and evaluation, we use $M = 20$ parallel Gibbs chains to reduce variance.

G EFFECT OF KERNEL CHOICE ON CLASSIFICATION ACCURACY

In this section, we examine the effect of kernel choice on classification accuracy for our proposed One-vs-Each Pólya-gamma OVE GPs.

---

[2] https://github.com/slinderman/pypolyagamma

Table 3: Specification of Conv4 architecture.

(a) Conv4 architecture for Omniglot→EMNIST dataset.

Output Size	Layers
$1 \times 28 \times 28$	Input image
$64 \times 14 \times 14$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 7 \times 7$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 3 \times 3$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 1 \times 1$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
64	`Flatten`

(b) Conv4 architecture for all other datasets.

Output Size	Layers
$3 \times 84 \times 84$	Input image
$64 \times 42 \times 42$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 21 \times 21$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 10 \times 10$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
$64 \times 5 \times 5$	`Conv2d` (3×3, stride 1, SAME)
`BatchNorm2d`
`ReLU`
`MaxPool2d` (2×2, stride 2, VALID)
1600	`Flatten`

Cosine Kernel. In the main paper, we showed results for the following kernel, which we refer to as the "cosine" kernel due to its resemblance to cosine similarity:

$$k^{\cos}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta}, \alpha) = \exp(\alpha) \frac{g_{\boldsymbol{\theta}}(\mathbf{x})^{\top} g_{\boldsymbol{\theta}}(\mathbf{x}')}{\|g_{\boldsymbol{\theta}}(\mathbf{x})\|\|g_{\boldsymbol{\theta}}(\mathbf{x}')\|}, \tag{40}$$

where $g_{\boldsymbol{\theta}}(\cdot)$ is a deep neural network that outputs a fixed-dimensional encoded representation of the input and α is the scalar log output scale. Both $\boldsymbol{\theta}$ and α are considered hyperparameters and learned simultaneously as shown in Algorithm 1. We found that this kernel works well for a range of datasets and shot settings. We note that the use of cosine similarity is reminiscent of the approach taken by Baseline++ method of (Chen et al., 2019), which computes the softmax over cosine similarity to class weights.

Here we consider three additional kernels: linear, RBF, and normalized RBF.

Linear Kernel. The linear kernel is defined as follows:

$$k^{\lin}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta}, \alpha) = \frac{1}{D} \exp(\alpha) g_{\boldsymbol{\theta}}(\mathbf{x})^{\top} g_{\boldsymbol{\theta}}(\mathbf{x}'), \tag{41}$$

where D is the output dimensionality of $g_{\boldsymbol{\theta}}(\mathbf{x})$. We apply this dimensionality scaling because the dot product between $g_{\boldsymbol{\theta}}(\mathbf{x})$ and $g_{\boldsymbol{\theta}}(\mathbf{x}')$ may be large depending on D.

RBF Kernel. The RBF (also known as squared exponential) kernel can be defined as follows:

$$k^{\rbf}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta}, \alpha, \ell) = \exp(\alpha) \exp\left(-\frac{1}{2D \exp(\ell)^2} \|g_{\boldsymbol{\theta}}(\mathbf{x}) - g_{\boldsymbol{\theta}}(\mathbf{x}')\|^2\right), \tag{42}$$

where ℓ is the log lengthscale parameter (as with α, we learn the ℓ alongside $\boldsymbol{\theta}$).

Normalized RBF Kernel. Finally, we consider a normalized RBF kernel similar in spirit to the cosine kernel:

$$k^{\text{rbf-norm}}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta}, \alpha, \ell) = \exp(\alpha) \exp\left(-\frac{1}{2 \exp(\ell)^2} \left\| \frac{g_{\boldsymbol{\theta}}(\mathbf{x})}{\|g_{\boldsymbol{\theta}}(\mathbf{x})\|} - \frac{g_{\boldsymbol{\theta}}(\mathbf{x}')}{\|g_{\boldsymbol{\theta}}(\mathbf{x}')\|} \right\|^2\right). \tag{43}$$

The results of our Pólya-gamma OVE GPs with different kernels can be found in Tables 4 and 5. In general, we find that the cosine kernel works best overall. We hypothesize that this is because they help the embedding network $g_{\boldsymbol{\theta}}(\cdot)$ to learn linearly separable representations. In contrast, the RBF-based kernels yields nonlinear decision boundaries with respect to the embedded representation and may not provide the embedding network with as strong of a learning signal. Further study of the benefits and drawbacks of linear vs. nonlinear kernels is an interesting area of future work.

Table 4: Classification accuracy for Pólya-Gamma OVE GPs (our method) using different kernels. Cosine is overall the best, followed closely by linear. RBF-based kernels perform worse, except for the Omniglot→EMNIST dataset. Evaluation is performed on 5 randomly generated sets of 600 test episodes. Standard deviation of the mean accuracy is also shown. ML = Marginal Likelihood, PL = Predictive Likelihood.

		CUB		mini-ImageNet	
Kernel	Objective	1-shot	5-shot	1-shot	5-shot
Cosine	ML	**63.98 ± 0.43**	77.44 ± 0.18	50.02 ± 0.35	64.58 ± 0.31
Linear	ML	62.48 ± 0.26	77.94 ± 0.21	**50.81 ± 0.30**	66.66 ± 0.45
RBF	ML	58.49 ± 0.40	75.50 ± 0.18	50.33 ± 0.26	64.62 ± 0.37
RBF (normalized)	ML	62.75 ± 0.32	78.71 ± 0.08	50.26 ± 0.31	64.84 ± 0.39
Cosine	PL	60.11 ± 0.26	**79.07 ± 0.05**	48.00 ± 0.24	**67.14 ± 0.23**
Linear	PL	60.44 ± 0.39	78.54 ± 0.19	47.29 ± 0.31	66.66 ± 0.36
RBF	PL	56.18 ± 0.69	77.96 ± 0.19	48.06 ± 0.28	66.66 ± 0.39
RBF (normalized)	PL	59.78 ± 0.34	78.42 ± 0.13	47.51 ± 0.20	66.42 ± 0.36

Table 5: Cross-domain classification accuracy for Pólya-Gamma OVE GPs (our method) using different kernels. The experimental setup is the same as Table 4.

Kernel	Objective	Omniglot→EMNIST		mini-ImageNet→CUB	
		1-shot	5-shot	1-shot	5-shot
Cosine	ML	68.43 ± 0.67	86.22 ± 0.20	$\mathbf{39.66 \pm 0.18}$	55.71 ± 0.31
Linear	ML	72.42 ± 0.49	88.27 ± 0.20	39.61 ± 0.19	55.07 ± 0.29
RBF	ML	$\mathbf{78.05 \pm 0.38}$	88.98 ± 0.16	36.99 ± 0.07	51.75 ± 0.27
RBF (normalized)	ML	75.51 ± 0.47	88.86 ± 0.16	38.42 ± 0.16	54.20 ± 0.13
Cosine	PL	77.00 ± 0.50	87.52 ± 0.19	37.49 ± 0.11	$\mathbf{57.23 \pm 0.31}$
Linear	PL	75.87 ± 0.43	88.77 ± 0.10	36.83 ± 0.27	56.46 ± 0.22
RBF	PL	74.62 ± 0.35	$\mathbf{89.87 \pm 0.13}$	35.06 ± 0.25	55.12 ± 0.21
RBF (normalized)	PL	76.01 ± 0.31	89.42 ± 0.16	37.50 ± 0.28	56.80 ± 0.39

H ADDITIONAL CALIBRATION RESULTS

In Figure 4, we include calibration results for mini-Imagenet and Omniglot→EMNIST. They follow similar trends to the results presented in Section 5.2.

Figure 4: Reliability diagrams, expected calibration error, maximum calibration error, and Brier scores for 5-shot 5-way tasks on mini-Imagenet, mini-Imagenet→CUB, and Omniglot→EMNIST. Metrics are computed on 3,000 random tasks from the test set.

I QUANTITATIVE ROBUSTNESS TO INPUT NOISE RESULTS

In this section we include quantitative results for the robustness to input noise results presented in Figure 2. Results for Gaussian noise are shown in Table 6, impulse noise in Table 7, and defocus blur in Table 8.

Table 6: Accuracy (%) and Brier Score when applying Gaussian noise corruption of severity 5 to both the support and query set of test-time episodes. Results were evaluated across 1,000 randomly generated 5-shot 5-way tasks.

Method	CUB		mini-ImageNet		mini-ImageNet→CUB	
	Acc. (↑)	Brier (↓)	Acc. (↑)	Brier (↓)	Acc. (↑)	Brier (↓)
Feature Transfer	30.45	0.775	22.58	0.799	22.75	0.799
Baseline++	22.60	0.798	23.82	0.797	24.13	0.797
MatchingNet	26.72	0.803	24.80	0.797	23.59	0.804
ProtoNet	32.28	0.778	29.97	0.781	32.30	0.779
RelationNet	25.23	0.799	23.69	0.800	20.00	0.800
GPNet + Linear	31.19	0.773	26.14	0.792	30.53	0.785
Bayesian MAML	22.79	0.905	20.52	0.963	20.46	0.949
Bayesian MAML (Chaser)	20.20	1.133	20.41	1.118	21.39	1.039
LSM GP + Cosine (ML)	27.92	0.787	22.43	0.798	22.36	0.799
LSM GP + Cosine (PL)	31.21	0.772	31.77	0.768	**34.74**	**0.754**
OVE PG GP + Cosine (ML) [ours]	32.27	0.774	29.99	0.776	29.97	0.784
OVE PG GP + Cosine (PL) [ours]	**33.01**	**0.771**	**33.29**	**0.760**	31.41	0.764

Table 7: Accuracy (%) and Brier Score when applying impulse noise corruption of severity 5 to both the support and query set of test-time episodes. Results were evaluated across 1,000 randomly generated 5-shot 5-way tasks.

Method	CUB		mini-ImageNet		mini-ImageNet→CUB	
	Acc. (↑)	Brier (↓)	Acc. (↑)	Brier (↓)	Acc. (↑)	Brier (↓)
Feature Transfer	30.20	0.776	23.54	0.798	22.87	0.799
Baseline++	28.05	0.790	23.72	0.798	25.58	0.795
MatchingNet	28.25	0.790	23.80	0.803	23.21	0.811
ProtoNet	32.12	0.774	28.81	0.783	32.70	0.775
RelationNet	25.23	0.799	23.13	0.800	20.00	0.800
GPNet + Linear	30.57	0.775	25.99	0.792	31.28	0.785
Bayesian MAML	22.76	0.903	20.50	0.970	20.56	0.950
Bayesian MAML (Chaser)	20.25	1.172	20.51	1.116	21.45	1.022
LSM GP + Cosine (ML)	28.18	0.787	21.82	0.799	23.64	0.797
LSM GP + Cosine (PL)	32.10	**0.769**	30.22	0.776	**35.09**	**0.751**
OVE PG GP + Cosine (ML) [ours]	31.41	0.778	29.66	0.778	30.28	0.783
OVE PG GP + Cosine (PL) [ours]	**33.36**	0.772	**33.23**	**0.761**	32.06	0.762

J COMPARISON OF LIKELIHOODS

In this section we seek to better understand the behaviors of the softmax, OVE, logistic softmax, and Gaussian likelihoods for classification. For convenience, we summarize the forms of these likelihoods below.

- **Softmax.** $p(y = c|\mathbf{f}) = \dfrac{\exp(f_c)}{\sum_{c'} \exp(f_{c'})}$

- **OVE.** $p(y = c|\mathbf{f}) = \prod_{c' \neq c} \sigma(f_c - f_{c'})$

- **Logistic Softmax.** $p(y = c|\mathbf{f}) = \dfrac{\sigma(f_c)}{\sum_{c'} \sigma(f_{c'})}$

Table 8: Accuracy (%) and Brier Score when applying defocus blur corruption of severity 5 to both the support and query set of test-time episodes. Results were evaluated across 1,000 randomly generated 5-shot 5-way tasks.

Method	CUB Acc. (↑)	Brier (↓)	mini-ImageNet Acc. (↑)	Brier (↓)	mini-ImageNet→CUB Acc. (↑)	Brier (↓)
Feature Transfer	38.03	0.734	33.06	0.791	33.47	0.792
Baseline++	42.55	0.710	35.89	0.761	39.88	0.740
MatchingNet	44.43	0.682	34.43	0.754	35.95	0.741
ProtoNet	46.78	**0.676**	36.92	0.737	41.45	0.714
RelationNet	40.81	0.759	30.11	0.790	25.69	0.794
GPNet + Linear	48.31	0.691	38.97	**0.735**	43.57	**0.712**
Bayesian MAML	42.65	0.697	30.63	0.808	37.32	0.736
Bayesian MAML (Chaser)	40.66	0.881	29.93	1.121	31.33	1.125
LSM GP + Cosine (ML)	45.37	0.706	34.10	0.769	39.66	0.753
LSM GP + Cosine (PL)	48.55	0.690	**39.46**	0.737	43.15	0.714
OVE PG GP + Cosine (ML) [ours]	46.46	0.701	37.65	0.775	43.48	0.723
OVE PG GP + Cosine (PL) [ours]	**49.44**	0.695	38.95	0.780	**43.66**	0.720

- **Gaussian.** $p(y = c|\mathbf{f}) = \prod_{c'} \mathcal{N}(2 \cdot \mathbb{1}[c' = c] - 1 | \mu = f_{c'}, \sigma^2 = 1)$

We sampled logits from $f \sim \mathcal{N}(0, 1)$ and plotted a histogram and kernel density estimate of the maximum output probability $\max_c p(y = c|\mathbf{f})$ for each of the likelihoods, where $C = 5$. Note that because we are interested in predictions here that all output probabilities are normalized to sum to 1 when computing confidences. The results are shown in Figure 5. Logistic softmax is *a priori* underconfident: it puts little probability mass on confidence above 0.4. This may be due to the use of the sigmoid function which squashes large values of f. Gaussian likelihood *a priori* is overconfident in that it puts a large amount of probability mass on confident outputs. OVE is slightly closer to softmax compared to Gaussian, yet still overconfident. Note that this is not a complete explanation, because GP hyperparameters such as the prior mean or Gaussian likelihood variance may be able to compensate for these imperfections to some degree. Indeed, we found it helpful to learn a constant mean for the logistic softmax likelihood, as mentioned in Section F.2.

Figure 5: Histogram and kernel density estimate of confidence for randomly generated function samples $f \sim \mathcal{N}(0, 1)$. Normalized output probabilities were computed for $C = 5$ and a histogram of $\max_c p(y = c|\mathbf{f})$ was computed for 50,000 randomly generated simulations.

K   LIKELIHOOD VISUALIZATION

In order to visualize the various likelihoods under consideration, we consider a trivial classification task with a single observed example. We assume that there are three classes ($C = 3$) and the single example belongs to the first class ($y = 1$). We place the following prior on $\mathbf{f} = (f_1, f_2, f_3)^\top$:

$$p(\mathbf{f}) = \mathcal{N}\left(\mathbf{f} \,\middle|\, \boldsymbol{\mu} = \left[\begin{array}{c} 0 \\ 0 \\ 0 \end{array}\right], \boldsymbol{\Sigma} = \left[\begin{array}{ccc} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{array}\right]\right). \tag{44}$$

In other words, the prior for f_1 and f_2 is a standard normal and f_3 is clamped at zero (for ease of visualization). We consider here the softmax, Gaussian, logistic softmax (LSM), and one-vs-each (OVE) likelihoods as defined in Table 9.

Table 9: Likelihoods used in Section K.

Likelihood	$L(\mathbf{f}|y = 1)$
Softmax	$\dfrac{e^{f_1}}{e^{f_1} + e^{f_2} + e^{f_3}}$
Gaussian	$\mathcal{N}(1 \,|\, \mu = f_1, \sigma^2 = 1)\,\mathcal{N}(-1 \,|\, \mu = f_2, \sigma^2 = 1)\,\mathcal{N}(-1 \,|\, \mu = f_3, \sigma^2 = 1)$
Logistic Softmax (LSM)	$\dfrac{\sigma(f_1)}{\sigma(f_1) + \sigma(f_2) + \sigma(f_3)}$
One-vs-Each (OVE)	$\sigma(f_1 - f_2)\sigma(f_1 - f_3)$

The posterior for a given likelihood can be computed as:

$$p(\mathbf{f}|y = 1) = \frac{L(\mathbf{f}|y = 1)p(\mathbf{f})}{\int L(\mathbf{f}'|y = 1)p(\mathbf{f}')\, d\mathbf{f}'} \tag{45}$$

The likelihoods as defined in Table 9 and corresponding posteriors are plotted in Figure 6 and Figure 7, respectively.

L   2D IRIS EXPERIMENTS

We also conducted experiments on a 2D version of the Iris dataset (Fisher, 1936), which contains 150 examples across 3 classes. The first two features of the dataset were retained (sepal length and width). We used a zero-mean GP prior and an RBF kernel $k(\mathbf{x}, \mathbf{x}') = \exp\left(-\dfrac{1}{2}d(\mathbf{x}, \mathbf{x}')\right)^2$, where $d(\cdot, \cdot)$ is Euclidean distance. We considered class-balanced training set sizes with 1, 2, 3, 4, 5, 10, 15, 20, 25, and 30 examples per class. For each training set size, we performed GP inference on 200 randomly generated train/test splits and compared the predictions across Gaussian, logistic softmax, and one-vs-each likelihoods.

Predictions at a test point $\mathbf{x}_*$ were made by applying the normalized likelihood to the posterior predictive mean $\bar{\mathbf{f}}_*$. The predictive probabilities for each likelihood is shown in Figure 8 for a randomly generated train/test split with 30 examples per class. Test predictive accuracy, Brier score, expected calibration error, and evidence lower bound (ELBO) results across various training set sizes are shown in Figure 9.

The ELBO is computed by treating each likelihood's posterior $q(\mathbf{f}|\mathbf{X}, \mathbf{Y})$ as an approximation to the softmax posterior $p(\mathbf{f}|\mathbf{X}, \mathbf{Y})$.

$$\begin{aligned} \text{ELBO}(q) &= \mathbb{E}_q[\log p(\mathbf{f}|\mathbf{X})] + \mathbb{E}_q[\log p(\mathbf{Y}|\mathbf{f})] - \mathbb{E}_q[\log q(\mathbf{f}|\mathbf{X}, \mathbf{Y})] \\ &= \log p(\mathbf{x}) - \text{KL}(q(\mathbf{f}|\mathbf{X}, \mathbf{Y})||p(\mathbf{f}|\mathbf{X}, \mathbf{Y})). \end{aligned}$$

Figure 6: Plot of $L(\mathbf{f}|y = 1)$, where f_3 is clamped to 0. Gaussian likelihood penalizes configurations far away from $(f_1, f_2) = (1, -1)$. Logistic softmax is much flatter compared to softmax and has visibly different contours. One-vs-Each is visually similar to the softmax but penalizes (f_1, f_2) near the origin slightly more.

Even though direct computation of the softmax posterior $p(\mathbf{f}|\mathbf{X}, \mathbf{y})$ is intractable, computing the ELBO is tractable. A larger ELBO indicates a lower the KL divergence to the softmax posterior.

One-vs-Each performs well for accuracy, Brier score, and ELBO across the training set sizes. Gaussian performs best on expected calibration error through 15 examples per class, beyond which one-vs-each is better.

(a) Softmax

(b) Gaussian

(c) Logistic Softmax

(d) Logistic Softmax

Figure 7: Plot of posterior $p(\mathbf{f}|y = 1)$, where f_3 is clamped to 0. The mode of each posterior distribution is similar, but each differs slightly in shape. Gaussian is more peaked about its mode, while logistic softmax is more spread out. One-vs-Each is similar to softmax, but is slightly more elliptical.

(a) Gaussian

(b) Logistic Softmax

(c) One-vs-Each

Figure 8: Training points (colored points) and maximum predictive probability for various likelihoods on the Iris dataset. The Gaussian likelihood produces more warped decision boundaries than the others. Logistic softmax tends to produce lower confidence predictions, while one-vs-each produces larger regions of greater confidence than the others.

(a) Accuracy

(b) Brier

(c) Expected Calibration Error (computed with 10 bins

(d) ELBO

Figure 9: Comparison across likelihoods in terms of test predictive accuracy, Brier score, expected calibration error, and ELBO. Results are averaged over 200 randomly generated splits for each training set size (1, 2, 3, 4, 5, 10, 15, 20, 25, and 30 examples per class). Error bars indicate 95% confidence intervals.