Towards Preventing Global Knowledge Forgetting in Federated Learning with Non-IID Data

Abstract

Federated learning under client-level data heterogeneity remains challenging despite extensive work on drift correction, regularization, and improved aggregation. In this paper, we argue that an important yet underexplored failure mode is *catastrophic forgetting of the global decision boundary during local training*: as clients optimize their local objectives, they rapidly overfit to client-specific data and erase globally useful multi-class structure, causing server aggregation to average incompatible models rather than accumulate progress. We provide empirical evidence for this phenomenon through a controlled pilot study that directly visualizes decision boundary evolution in federated learning. Our analysis reveals that standard FL methods consistently forget the global decision boundary after local updates, even when clients are initialized from a strong pretrained global model. Motivated by this observation, we propose FEDPROJ, a federated learning framework designed to preserve global functional knowledge throughout local optimization. FEDPROJ maintains a small public-memory buffer and enforces a hard gradient constraint that prevents local updates from increasing a memory-based distillation loss, thereby acting as a safety barrier against global knowledge erosion. At the server, we further employ ensemble distillation on the same public proxy data to consolidate the preserved knowledge into a single global model. We conduct extensive experiments across computer vision and natural language processing benchmarks, covering highly non-IID regimes and domain-shifted settings. The results show that FEDPROJ consistently outperforms state-of-the-art federated learning methods, highlighting the practical importance of explicitly preventing global decision-boundary forgetting.

1 Introduction

Federated Learning (FL) Kairouz et al. (2021) enables the training of a shared global model across multiple clients without exchanging raw data, making it a widely adopted paradigm for privacy-sensitive and decentralized learning. The canonical FL algorithm, FedAvg McMahan et al. (2017), alternates between local optimization on each client and server-side aggregation of model updates. While FedAvg has demonstrated success in settings with homogeneous data, its performance often degrades substantially in the presence of client-level data heterogeneity—commonly referred to as Non-IID data—leading to slow convergence and poor generalization Glasgow et al. (2022); Woodworth et al. (2020); Li et al. (2019); Chellapandi et al. (2023b;a;c; 2024); Morafah et al. (2024b); Morafah & Morafah (2025); Morafah et al. (2024a).

A large body of prior work has sought to address the challenges posed by Non-IID data through client-drift correction Li et al. (2020); Karimireddy et al. (2020), improved server-side aggregation and distillation Cheng et al. (2021); Li & Wang (2019), or modified local training strategies Collins et al. (2021). While these approaches improve stability and convergence in many cases, they largely focus on controlling parameter divergence or enhancing aggregation heuristics. In contrast, the *functional consequences* of local training under heterogeneity—namely, what global information is lost during local optimization—remain insufficiently understood.

In this work, we argue that an important and underexplored failure mode in federated learning is *catastrophic forgetting of global knowledge, manifested as the erosion of the global decision boundary during local training.* Under Non-IID data, clients rapidly overfit to their local objectives and overwrite globally useful multi-class structure learned by the aggregated model. As a result, local models become increasingly specialized and mutually incompatible, so that server-side aggregation largely averages divergent solutions rather than compounding progress. Although this phenomenon has been briefly noted in prior work Zhu et al. (2021), a systematic empirical investigation of global knowledge forgetting in FL literature is lacking.

To make this failure mode explicit, we first conduct a controlled pilot study that directly visualizes decision boundary evolution in federated learning under Non-IID settings. Our findings show that standard FL methods, including FedAvg, consistently forget the global decision boundary after local updates, even when clients are initialized from a strong pretrained global model. This observation reveals that heterogeneity-induced forgetting is not merely an initialization or optimization artifact, but a structural consequence of unconstrained local training.

Motivated by this diagnosis, we propose *FedProj*, a federated learning framework designed to preserve global functional knowledge throughout local optimization. FedProj introduces an explicit constraint on local gradient updates—where forgetting occurs—by leveraging a small public-memory buffer that encodes global knowledge via ensemble predictions. Local updates are projected to prevent increases in a memory-based distillation loss, acting as a hard safety barrier against global knowledge erosion. At the server, we further consolidate the preserved client knowledge through ensemble distillation on the same public proxy data, improving model fusion without relying on stronger assumptions about client similarity.

We evaluate FedProj on a range of computer vision and natural language processing benchmarks, spanning highly Non-IID regimes and domain-shifted settings. Across all experiments, FedProj consistently outperforms state-of-the-art federated learning methods, demonstrating that explicitly preventing global decision-boundary forgetting is both practically important and algorithmically effective.

Contributions. Our main contributions are summarized as follows:

- We identify and empirically characterize catastrophic forgetting of global knowledge—specifically, global decision boundary erosion—as a distinct failure mode in federated learning under data heterogeneity.

- We propose *FedProj*, a federated learning method that mitigates global knowledge forgetting by imposing explicit constraints on local gradient updates.

- We provide a convergence analysis showing that FedProj effectively reduces heterogeneity-induced optimization error compared to standard FL methods.

- We conduct extensive experiments on computer vision and natural language processing tasks, demonstrating consistent improvements over state-of-the-art baselines under Non-IID and domain-shifted settings.

Organization. The remainder of this paper is organized as follows. Section 2 reviews related work. Section 3 presents the pilot study on global knowledge forgetting. Section 4 introduces the FedProj methodology. Section 5 details the theoretical results. Section 6 reports experimental results, and Section 7 concludes the paper.

2 Related Works

Continual Learning. Catastrophic forgetting has been extensively studied in continual learning, where models are trained sequentially on a stream of tasks. A prominent class of approaches mitigates forgetting by constraining parameter updates to preserve previously learned knowledge, often through gradient projection or subspace restriction. Early methods such as Orthogonal Weight Modulation (OWM) and Orthogonal Gradient Descent (OGD) identify directions in parameter space associated with past tasks and restrict new updates to be orthogonal or minimally interfering with them Zeng et al. (2019); Farajtabar et al. (2020). Gradient Projection Memory (GPM) Saha et al. (2021) improves efficiency by maintaining a compact gradient

subspace that captures task-relevant directions, while more recent variants relax strict orthogonality to balance stability and plasticity Lin et al. (2022); Saha & Roy (2023).

While these methods provide important inspiration, the continual learning setting differs fundamentally from federated learning. Continual learning methods are designed for sequential task arrival with a single data stream and typically rely on explicit task boundaries or task-specific memory. In contrast, federated learning involves *simultaneous* optimization across multiple clients with heterogeneous data distributions, where forgetting arises not from task transitions but from unconstrained local optimization that overwrites globally useful structure. Moreover, existing gradient-projection methods in continual learning aim to preserve performance on past tasks, whereas our objective is to preserve *global functional knowledge shared across clients* at every communication round. FedProj draws intuition from these works but adapts gradient constraints to the federated setting by defining preservation in terms of ensemble-induced global knowledge rather than task-specific gradients.

Federated Learning with Non-IID Data. A large body of work in federated learning addresses data heterogeneity through client drift correction, regularization, and improved aggregation. Methods such as FedProx Li et al. (2020) and Ditto Li et al. (2021b) introduce proximal or personalized objectives to limit deviation from the global model, while others modify aggregation rules to account for heterogeneous local updates (e.g., FedNova Wang et al. (2020)). Another line of work focuses on server-side knowledge distillation and ensemble fusion. For example, FedDF Lin et al. (2020) refines the global model by distilling knowledge from client models, FedET Cho et al. (2022) constructs an ensemble teacher for aggregation, and FedGKT He et al. (2020) transfers knowledge from client models into a larger server model. These approaches improve robustness under heterogeneity, but they operate primarily at the parameter or output-logit level and do not directly intervene in the local optimization process where forgetting occurs.

Discussion and Positioning. As a result, existing methods can still allow local updates to drift away from globally useful decision boundaries, since no mechanism explicitly constrains local gradients to preserve global knowledge across classes. Some distillation-based approaches additionally rely on strong assumptions or external resources, such as one-shot distillation with unlabeled public data Gong et al. (2022), without explicitly addressing the dynamics of forgetting during local training. In contrast, our work focuses on a complementary and largely unexplored question: *what global information is lost during local training under data heterogeneity, and how does this loss affect aggregation?* While prior studies primarily analyze convergence behavior or aggregation bias, they do not explicitly characterize the erosion of global decision boundaries induced by local optimization. We address this gap by empirically diagnosing global knowledge forgetting through a controlled pilot study that visualizes decision boundary evolution in federated learning.

Building on this diagnosis, we propose *FedProj*, a federated learning method that explicitly constrains local optimization to preserve global functional knowledge. Rather than modifying the objective with soft regularization terms or relying solely on server-side correction, FedProj imposes a hard gradient-level constraint: local updates are projected to satisfy a global-knowledge half-space constraint induced by a memory-based distillation loss. This directly prevents local gradients from erasing globally shared structure during training. By operating at the level of optimization dynamics rather than parameters or logits alone, FedProj provides a principled mechanism for mitigating catastrophic forgetting in heterogeneous federated learning. Together, this combination of problem identification, empirical validation, and algorithmic design distinguishes FedProj from existing approaches and reframes catastrophic forgetting as a central challenge in federated learning under data heterogeneity.

3 Pilot Study: Diagnosing Global Knowledge Forgetting

This section presents a controlled pilot study designed to *diagnose* a specific failure mode in federated learning under data heterogeneity: catastrophic forgetting of global knowledge during local training. Rather than evaluating overall accuracy alone, our goal is to directly examine how local optimization affects the *global decision boundary* learned by the aggregated model.

Experimental Setup. To enable direct visualization of decision boundary dynamics, we use the Iris dataset and apply Principal Component Analysis (PCA) to project the data into two dimensions. The

dataset consists of 150 samples from three classes—Setosa, Versicolor, and Virginica—each described by four numerical features. We partition the data across three clients in a Non-IID manner, such that each client predominantly observes samples from a different subset of classes, simulating heterogeneous local objectives.

Each client trains a simple three-layer multi-layer perceptron (MLP). Local optimization is performed using stochastic gradient descent with a learning rate of 1×10^{-3} and momentum 0.9. We compare FedAvg, FedDF, and the proposed FedProj method. Training proceeds for 20 communication rounds, with each client performing five local epochs per round. All methods are initialized from the same global model to isolate the effect of local training dynamics.

Results and Analysis. Figure 1 visualizes the evolution of class decision boundaries for each method after local training. While the aggregated global model initially exhibits a reasonable multi-class boundary, standard federated learning methods quickly degrade this structure. After local updates, individual client models diverge sharply from the global decision boundary—most notably for Client 1 and Client 2—indicating that local optimization has overwritten globally shared information in favor of client-specific decision regions.

Figure 1: **Visualization of Catastrophic Forgetting of Global Decision Boundaries under Non-IID Federated Learning.** Standard federated learning methods (FedAvg and FedDF) exhibit severe erosion of the global decision boundary after local training on Non-IID client data, resulting in poor global performance (64%). In contrast, *FedProj* preserves the global decision boundary throughout local updates, leading to a substantially more accurate and stable global model (93.33%).

This divergence highlights a key limitation of existing approaches: although aggregation averages model parameters or predictions, it cannot recover global structure once local training has erased it. As a result, the aggregated model exhibits unstable decision boundaries and substantially reduced accuracy.

In contrast, *FedProj* maintains consistent and coherent decision boundaries across clients throughout local training. By constraining local gradient updates to preserve global functional knowledge, FedProj prevents the erosion of the global decision boundary at its source. Consequently, the aggregated model retains both high accuracy and stable multi-class structure, demonstrating that explicitly preventing global knowledge forgetting during local optimization is critical under data heterogeneity.

4 Methodology

We now present *FedProj*, a federated learning algorithm designed to prevent catastrophic forgetting of global knowledge under data heterogeneity. FedProj combines (i) a *client-side gradient projection mechanism* that constrains local optimization dynamics and (ii) a *server-side global knowledge consolidation step* based on ensemble distillation. Together, these components ensure that globally useful functional structure is preserved during local training and coherently fused at the server.

4.1 Problem Formulation and Preliminaries

We consider a federated learning system with N clients indexed by $k \in \{1, \ldots, N\}$. Each client k holds a private dataset $\mathcal{D}_k$, and the goal is to learn a shared model parameterized by $\theta \in \mathbb{R}^p$. At communication round t, the server broadcasts the current global model $\theta_g^{(t)}$ to a subset of participating clients $\mathcal{S}_t \subseteq \{1, \ldots, N\}$. Each client performs local optimization starting from $\theta_g^{(t)}$, producing updated parameters $\theta_k^{(t+1)}$, which are then aggregated at the server. The standard FedAvg update is given by

$$\theta_g^{(t+1)} = \sum_{k \in \mathcal{S}_t} \frac{|\mathcal{D}_k|}{\sum_{j \in \mathcal{S}_t} |\mathcal{D}_j|} \theta_k^{(t+1)}. \tag{1}$$

While effective under homogeneous data, this procedure degrades under Non-IID client distributions. Fed-Proj addresses this limitation by intervening at two complementary stages:

1. **Client-side gradient projection,** which constrains local updates to preserve global knowledge during optimization;

2. **Server-side global knowledge consolidation,** which distills the preserved client models into a coherent global model.

4.2 Local Training with Gradient Projection

Local Objective. At round t, each client $k \in \mathcal{S}_t$ initializes $\theta_k^{(0)} = \theta_g^{(t)}$ and minimizes its empirical risk

$$\mathcal{L}_{\text{local}}^{(k)}(\theta) = \frac{1}{|\mathcal{D}_k|} \sum_{(x,y) \in \mathcal{D}_k} \ell(f(x; \theta), y), \tag{2}$$

where $f(x; \theta) \in \mathbb{R}^C$ denotes the model logits and ℓ is the cross-entropy loss.

Global Knowledge Memory. To prevent local updates from erasing globally shared structure, we introduce a *global knowledge memory* constructed from a small public or proxy dataset $\mathcal{D}_{\text{pub}}$. Let $\mathcal{M} \subset \mathcal{D}_{\text{pub}}$ denote a memory buffer. At round t, the server computes ensemble logits

$$Z_{\text{ens}}^{(t)}(x) = \frac{1}{|\mathcal{S}_t|} \sum_{k \in \mathcal{S}_t} f(x; \theta_k^{(t)}), \qquad x \in \mathcal{M}. \tag{3}$$

These ensemble predictions represent the *global functional knowledge* accumulated across clients.

We quantify preservation of this knowledge via the memory loss

$$\mathcal{L}_{\text{mem}}(\theta) = \frac{1}{|\mathcal{M}|} \sum_{x \in \mathcal{M}} \text{KL}\Big(\sigma\Big(Z_{\text{ens}}^{(t)}(x)\Big) \,\big\|\, \sigma(f(x; \theta))\Big), \tag{4}$$

where $\sigma(\cdot)$ is the softmax function. Minimizing $\mathcal{L}_{\text{mem}}$ preserves the predictive distribution—and hence the decision boundary—induced by the global ensemble on $\mathcal{M}$.

Constrained Local Update. Our objective is to minimize $\mathcal{L}_{\text{local}}^{(k)}$ without increasing $\mathcal{L}_{\text{mem}}$. For a local update $\theta \mapsto \theta'$, we impose the constraint

$$\mathcal{L}_{\text{mem}}(\theta') \leq \mathcal{L}_{\text{mem}}(\theta). \tag{5}$$

Using a first-order Taylor expansion of $\mathcal{L}_{\text{mem}}$ around θ, this constraint is satisfied if

$$\langle g_{\text{proj}}, g_{\text{glob}} \rangle \geq 0, \qquad g_{\text{glob}} := \nabla_\theta \mathcal{L}_{\text{mem}}(\theta),$$

where g_{proj} denotes the update direction. Thus, we compute the projected gradient by solving the quadratic program

$$\min_{g_{\text{proj}}} \frac{1}{2} \| g_{\text{proj}} - g_{\text{new}} \|_2^2 \quad \text{s.t.} \quad \langle g_{\text{proj}}, g_{\text{glob}} \rangle \geq 0, \tag{6}$$

with $g_{\text{new}} = \nabla_\theta \mathcal{L}_{\text{local}}^{(k)}(\theta)$.

This problem admits a closed-form solution:

$$g_{\text{proj}} = \begin{cases} g_{\text{new}}, & \langle g_{\text{new}}, g_{\text{glob}} \rangle \geq 0, \\ g_{\text{new}} - \dfrac{\langle g_{\text{new}}, g_{\text{glob}} \rangle}{\| g_{\text{glob}} \|_2^2 + \varepsilon} g_{\text{glob}}, & \text{otherwise,} \end{cases} \tag{7}$$

where $\varepsilon > 0$ ensures numerical stability. The client update is then

$$\theta \leftarrow \theta - \eta_{\text{local}} g_{\text{proj}}. \tag{8}$$

This projection enforces a *global-knowledge half-space constraint*: local optimization proceeds along the closest feasible descent direction that does not increase global knowledge loss. Unlike soft regularization, this provides a hard first-order guarantee against forgetting.

4.3 Server-Side Global Knowledge Consolidation

After local updates, the server aggregates the client models. Rather than relying solely on parameter averaging, FedProj performs *global knowledge consolidation* via ensemble distillation.

The server initializes a student model θ_g using the FedAvg aggregate and refines it by minimizing

$$\mathcal{L}_{\text{KD}}(\theta_g) = \mathbb{E}_{x \sim \mathcal{D}_{\text{pub}}} \text{KL}\Big(\sigma\Big(Z_{\text{ens}}^{(t+1)}(x) \Big) \,\big\|\, \sigma(f(x; \theta_g)) \Big), \tag{9}$$

where $Z_{\text{ens}}^{(t+1)}$ is the ensemble of post-update client models. This step consolidates the preserved global knowledge into a single coherent global model.

Discussion. Client-side projection prevents catastrophic forgetting at its source—local optimization—while server-side distillation consolidates complementary knowledge across heterogeneous clients. Without projection, distillation must reconcile inconsistent models; without consolidation, projection alone cannot fully exploit client diversity. Their combination yields a stable and effective federated learning procedure under Non-IID data.

5 Theory

We provide two theoretical results. First, we formalize how preserving global functional knowledge on the public memory buffer implies preservation of the global decision boundary on that buffer. Second, we give a convergence guarantee showing that FedProj reduces the *effective heterogeneity* of local updates under a mild alignment condition between the public-memory gradient and the true global gradient.

5.1 Global Knowledge Preservation Implies Boundary Preservation

We model the decision boundary as a property of the model's *function* rather than its parameters.

Definition 5.1 (Global functional knowledge on a buffer)**.** Let $f(\cdot; \theta) \in \mathbb{R}^C$ be logits and let $\mathcal{M} \subset \mathcal{D}_{\text{pub}}$ be the memory buffer. The global functional knowledge induced by θ on $\mathcal{M}$ is the collection $\{f(x; \theta)\}_{x \in \mathcal{M}}$ (equivalently $\{\sigma(f(x; \theta))\}_{x \in \mathcal{M}}$).

Definition 5.2 (Decision boundary restricted to $\mathcal{M}$)**.** For $x \in \mathcal{M}$, define the predicted label $y_\theta(x) = \arg\max_j f_j(x; \theta)$ and the (multi-class) margin

$$m_\theta(x) = f_{y_\theta(x)}(x; \theta) - \max_{j \neq y_\theta(x)} f_j(x; \theta).$$

The decision boundary restricted to $\mathcal{M}$ is the set of low-margin points $\mathcal{B}_\theta(\mathcal{M}) = \{x \in \mathcal{M} : m_\theta(x) \approx 0\}$.

Proposition 5.3 (Boundary stability under memory-loss control)**.** *Let θ' be a local update from θ and define the per-sample KL on $\mathcal{M}$ by $\text{KL}_x(\theta, \theta') := \text{KL}\big(\sigma(f(x; \theta)) \,\|\, \sigma(f(x; \theta'))\big)$. Then for any $x \in \mathcal{M}$,*

$$\big\|\sigma(f(x; \theta')) - \sigma(f(x; \theta))\big\|_1 \leq \sqrt{2\,\text{KL}_x(\theta, \theta')}$$

(Pinsker). In particular, if $\max_{x \in \mathcal{M}} \text{KL}_x(\theta, \theta') \leq \delta$ and $m_\theta(x) \geq \gamma$ for all $x \in \mathcal{M}$, then there exists a constant $c(\gamma, C) > 0$ such that whenever $\delta \leq c(\gamma, C)$ we have $y_{\theta'}(x) = y_\theta(x)$ for all $x \in \mathcal{M}$, and hence $\mathcal{B}_{\theta'}(\mathcal{M}) = \mathcal{B}_\theta(\mathcal{M})$.

Proposition 5.3 resolves the apparent mismatch between our empirical motivation (boundary forgetting) and our method (functional knowledge preservation): controlling the KL-based memory loss controls changes in predictive distributions on $\mathcal{M}$, and sufficiently small changes preserve margins and therefore the decision boundary on the buffer. FedProj enforces this preservation *at the level of local optimization dynamics* via a hard gradient constraint.

5.2 Convergence and Reduced Effective Heterogeneity

We analyze FedProj under standard smooth nonconvex assumptions used in federated optimization.

Let the global objective be $F(\theta) = \sum_{k=1}^N p_k F_k(\theta)$ where $F_k(\theta) = \mathbb{E}_{(x,y) \sim \mathcal{D}_k} \ell(f(x; \theta), y)$ and $\sum_k p_k = 1$. Define the heterogeneity at θ by

$$\zeta^2(\theta) := \sum_{k=1}^N p_k \big\|\nabla F_k(\theta) - \nabla F(\theta)\big\|_2^2, \qquad \zeta^2 := \sup_\theta \zeta^2(\theta).$$

FedProj uses the projected local direction $g_{\text{proj}}^{(k)}$ obtained from equation 6.

Assumption 5.4 (Smoothness and bounded stochastic noise)**.** *Each F_k is L-smooth. Client stochastic gradients are unbiased and have bounded variance: $\mathbb{E}[g^{(k)}(\theta)] = \nabla F_k(\theta)$ and $\mathbb{E}\|g^{(k)}(\theta) - \nabla F_k(\theta)\|_2^2 \leq \sigma^2$.*

Assumption 5.5 (Public-memory alignment)**.** *Let $g_{\text{glob}}(\theta) = \nabla_\theta \mathcal{L}_{\text{mem}}(\theta)$ be the memory-loss gradient computed on $\mathcal{M}$ using the current server ensemble. Assume that, for all θ encountered by the algorithm, $g_{\text{glob}}(\theta)$ is a descent direction for the global objective in the sense that*

$$\langle \nabla F(\theta), g_{\text{glob}}(\theta) \rangle \geq \kappa \|\nabla F(\theta)\|_2 \|g_{\text{glob}}(\theta)\|_2 \quad \text{for some } \kappa \in (0, 1].$$

Theorem 5.6 (FedProj reduces effective heterogeneity and converges to a stationary point)**.** *Under Assumptions 5.4–5.5, consider T communication rounds with E local steps per participating client and server aggregation by weighted averaging. For a sufficiently small stepsize $\eta_{\text{local}} \leq \frac{1}{cLE}$ (for an absolute constant c), the FedProj iterates satisfy*

$$\frac{1}{T} \sum_{t=0}^{T-1} \mathbb{E}\big[\|\nabla F(\theta_g^{(t)})\|_2^2\big] \leq \mathcal{O}\bigg(\frac{F(\theta_g^{(0)}) - F^\star}{\eta_{\text{local}} T E}\bigg) + \mathcal{O}\bigg(\eta_{\text{local}} L \bigg(\sigma^2 + \frac{\zeta^2}{\kappa}\bigg)\bigg),$$

where $F^\star = \inf_\theta F(\theta)$. Compared to standard local training (FedAvg), the heterogeneity term appears as an effective heterogeneity scaled by $1/\kappa$, reflecting that projection removes the component of local updates that conflicts with globally aligned directions.

Theorem 5.6 provides a nonconvex convergence guarantee while explicitly quantifying how FedProj controls heterogeneity through the alignment parameter κ. When the public proxy buffer provides a reliable global direction (larger κ), the dominant heterogeneity-induced error term is reduced, consistent with the empirical stabilization of decision boundaries under Non-IID training.

6 Experiments

6.1 Main Experimental Setup

Datasets and Architectures. We evaluate FEDPROJ on both computer vision (CV) and natural language processing (NLP) tasks. For CV, we consider image classification on CIFAR-10/100 Krizhevsky et al. (2009) and CINIC-10 Darlow et al. (2018). For NLP, we fine-tune pretrained language models on MNLI Williams et al. (2017), SST-2 Socher et al. (2013), and MARC Keung et al. (2020). We use ResNet-8 for CIFAR-10, ResNet-18 for CIFAR-100 and CINIC-10, and TinyBERT Jiao et al. (2019) for all NLP tasks. To simulate statistical heterogeneity, we partition data across clients using a Dirichlet prior Hsu et al. (2019) with concentration $\beta \in \{0.3, 0.5\}$, where smaller β induces more severe label skew.

Federated Learning Protocol. For CV tasks, we use 100 clients for CIFAR-10 and CINIC-10, and 50 clients for CIFAR-100, with a fixed client sampling rate of 10% per communication round. We train for 100 rounds on CIFAR-10/100 and 60 rounds on CINIC-10, using 20 local epochs per round for all CV experiments. For NLP tasks, we use 15 clients with a 30% sampling rate, 1 local epoch, and 15 communication rounds.

To implement the public-memory and distillation components, we use auxiliary public datasets that are disjoint from the private client data: CIFAR-100 for CIFAR-10/CINIC-10, ImageNet-100 Deng et al. (2009) for CIFAR-100, SNLI Bowman et al. (2015) for MNLI, Sentiment140 Go et al. (2009) for SST-2, and Yelp Zhang et al. (2015) for MARC. This choice reflects the common FL assumption that a small proxy dataset is available for calibration or distillation, without requiring access to private data.

Implementation Details. We implement all methods in PyTorch 2.4.1 and run experiments on NVIDIA RTX 3090 GPUs using the FedZoo benchmark Morafah et al. (2023). Our anonymous implementation is available at `https://anonymous.4open.science/r/FedProj_TMLR-554A`. We use Adam with learning rate 10^{-3} for CV and 3×10^{-5} for NLP tasks. Server-side distillation uses KL divergence with temperature $T = 3$, performed for 1 epoch on CIFAR-10, CINIC-10, and all NLP tasks, and for 3 epochs on CIFAR-100. We use batch sizes 256 (CV) and 128 (NLP).

Baselines and Evaluation. We compare FEDPROJ against representative baselines spanning optimization, regularization, and distillation families: FEDAVG McMahan et al. (2017), FEDPROX Li et al. (2020), FEDNOVA Wang et al. (2020), FEDDF Lin et al. (2020), FEDET Cho et al. (2022), MOON Li et al. (2021a), FEDDYN Acar et al. (2021), and FEDRCL Seo et al. (2024). We report mean and standard deviation over three independent runs with different random seeds, evaluated by global test accuracy of the final global model.

6.2 Main Experimental Results

Performance on CV Tasks. Table 1 reports results on CIFAR-10/100 and CINIC-10 under two heterogeneity levels. Across all datasets and both Dirichlet settings, FEDPROJ achieves the best performance, reaching 65.52% and 69.88% on CIFAR-10, 35.27% and 38.06% on CIFAR-100, and 41.46% and 41.63% on CINIC-10 (for $\beta = 0.3$ and $\beta = 0.5$, respectively). Notably, the gains are more pronounced under stronger heterogeneity ($\beta = 0.3$), consistent with our diagnosis that local training increasingly deviates from globally useful decision boundaries as label skew intensifies.

Among baselines, MOON performs competitively under moderate heterogeneity ($\beta = 0.5$) but degrades substantially under stronger skew, highlighting the brittleness of representation-regularization when client objectives become highly misaligned. On CIFAR-100, which is both higher-dimensional and fine-grained, optimization-centered methods (FedNova, FedDyn) exhibit lower accuracy and higher variance, suggesting that correcting for client drift alone does not fully address the loss of global functional structure. On CINIC-

10, which introduces additional domain shift, FEDPROJ improves over distillation-based methods (FedDF, FedET), indicating that server-side distillation is most effective when the client models remain functionally aligned rather than having diverged during local optimization. Overall, these results support the central mechanism of FEDPROJ: constraining local updates to preserve global knowledge improves both robustness to heterogeneity and the quality of subsequent server-side consolidation.

Performance on NLP Tasks. Table 2 reports results on three private–public dataset pairs under Dirichlet Non-IID splits. FEDPROJ consistently outperforms all baselines, with particularly large gains under $\text{Dir}(\beta = 0.3)$. On MNLI–SNLI, FEDPROJ improves over FEDAVG by more than 8 points (44.38 vs. 35.67) and over FEDDF/FEDET by roughly 7–8 points, suggesting that preserving global functional behavior during local updates is especially important when client label distributions are skewed. On SST-2–Sentiment140, FEDPROJ achieves the strongest performance in both settings, improving by nearly 9 points over the best baseline. On MARC–Yelp, which couples multilingual and domain-diverse review distributions, FEDPROJ yields consistent 4–6 point gains. These results indicate that FEDPROJ is robust not only to statistical heterogeneity but also to realistic domain mismatch between private and auxiliary public data, a regime where distillation alone can be noisy if client models drift substantially.

Table 1: **Performance on CIFAR-10, CIFAR-100, and CINIC-10** under Dirichlet($\beta = 0.3$, 0.5).

Baseline	CIFAR-10		CIFAR-100		CINIC-10	
	Dir(β=0.3)	**Dir(β=0.5)**	**Dir(β=0.3)**	**Dir(β=0.5)**	**Dir(β=0.3)**	**Dir(β=0.5)**
FedAvg McMahan et al. (2017)	63.19 ± 1.48	66.41 ± 0.56	33.72 ± 0.17	37.18 ± 0.09	40.59 ± 0.12	40.70 ± 0.18
FedProx Li et al. (2020)	61.40 ± 0.92	67.34 ± 0.36	33.96 ± 0.88	36.66 ± 0.49	40.69 ± 0.07	40.80 ± 0.17
FedNova Wang et al. (2020)	63.43 ± 0.99	67.93 ± 0.49	33.40 ± 0.55	36.40 ± 0.48	39.81 ± 0.25	40.01 ± 0.18
FedDyn Acar et al. (2021)	63.35 ± 1.03	67.53 ± 0.71	33.61 ± 0.36	36.52 ± 0.39	40.43 ± 0.11	40.59 ± 0.10
MOON Li et al. (2021a)	61.09 ± 1.36	68.83 ± 0.78	30.29 ± 0.71	34.49 ± 0.09	40.64 ± 0.10	40.79 ± 0.14
FedRCL Seo et al. (2024)	62.14 ± 0.51	67.26 ± 0.87	33.91 ± 0.20	36.77 ± 0.11	40.72 ± 0.08	40.81 ± 0.16
FedDF Lin et al. (2020)	63.92 ± 2.02	68.04 ± 0.83	33.65 ± 0.65	36.60 ± 0.30	40.64 ± 0.37	40.77 ± 0.11
FedET Cho et al. (2022)	62.79 ± 1.20	66.46 ± 0.33	32.85 ± 0.31	36.21 ± 0.14	39.11 ± 0.21	39.20 ± 0.12
FedProj	$\mathbf{65.52} \pm 0.86$	$\mathbf{69.88} \pm 0.03$	$\mathbf{35.27} \pm 0.11$	$\mathbf{38.06} \pm 0.21$	$\mathbf{41.46} \pm 0.55$	$\mathbf{41.63} \pm 0.21$

Table 2: **Performance Results for NLP Task on MNLI, SST-2 and MARC.**

Private	Public	Baseline	Dir(β=0.3)	Dir(β=0.5)
MNLI Williams et al. (2017)	SNLI Bowman et al. (2015)	FedAvg	35.67 ± 1.21	41.91 ± 3.98
		FedDF	36.65 ± 1.32	41.07 ± 5.88
		FedET	36.10 ± 3.34	36.50 ± 3.39
		FedProj	$\mathbf{44.38} \pm 3.91$	$\mathbf{45.13} \pm 3.10$
SST2 Socher et al. (2013)	Sent140 Go et al. (2009)	FedAvg	56.96 ± 1.36	55.08 ± 6.46
		FedDF	51.43 ± 2.19	54.45 ± 3.86
		FedET	54.96 ± 8.31	56.36 ± 9.42
		FedProj	$\mathbf{64.80} \pm 5.1$	$\mathbf{65.98} \pm 2.87$
MARC Keung et al. (2020)	Yelp Zhang et al. (2015)	FedAvg	37.21 ± 2.85	40.86 ± 2.89
		FedDF	40.74 ± 2.91	38.40 ± 6.05
		FedET	37.02 ± 3.39	40.05 ± 2.94
		FedProj	$\mathbf{45.15} \pm 1.59$	$\mathbf{46.52} \pm 4.42$

Performance on NLP Task. Table 2 presents results on three NLP private-public dataset pairs: MNLI–SNLI, SST-2–Sentiment140, and MARC–Yelp, under two Dirichlet non-IID settings (Dir(β=0.3) and Dir(β=0.5)). Similar to CV results, on NLP experiments FedProj consistently outperforms existing baselines, demonstrating superior robustness across heterogeneous client scenarios. On MNLI(Williams et al. (2017)), paired with SNLI(Bowman et al. (2015)), FedProj delivers substantial gains. Under Dir(β=0.3), it achieves 44.38 accuracy, surpassing FedDF (36.65) and FedET (36.10), with an improvement exceeding 7% compared to FedAvg. These results expose the limitations of standard aggregation approaches under skewed data distributions. FedET underperforms FedAvg, revealing the downside of relying on uncertainty estimates from pretrained language models, which produce overconfident and poorly calibrated predictions(Wang et al. (2022); Guo et al. (2017); Xiao et al. (2022)). For SST-2(Socher et al. (2013))–Sentiment140(Go et al.

Figure 2: Impact of Projection Dropout.

(2009)), FedProj delivers state-of-the-art accuracy across both settings, improving by nearly 9% over the strongest baseline. This proves FedProj's effectiveness in bridging domain gaps between curated sentiment labels and noisy social media text. On MARC(Keung et al. (2020))–Yelp(Zhang et al. (2015)), involving multilingual and domain-diverse reviews, FedProj maintains its dominance with 4–6% gains across both non-IID scenarios. These results establish FedProj's effectiveness against both linguistic and domain shifts in realistic federated NLP applications.

6.3 Ablation Studies

Impact of Gradient Projection. To isolate the effect of the client-side constraint, we ablate projection on CIFAR-10 by randomly omitting the projection step during local updates (Fig. 2). Under strong heterogeneity ($\text{Dir}(\beta = 0.3)$), accuracy increases monotonically with the projection rate, with full projection achieving the best performance; even moderate removal sharply degrades accuracy, often reverting toward FEDAVG-level performance. Under milder heterogeneity ($\text{Dir}(\beta = 0.5)$), performance remains stable for moderate projection rates but drops once projection is mostly removed, suggesting that the constraint becomes critical precisely when client objectives are strongly misaligned.

In addition, removing the weight divergence term (Table 3) has only a marginal effect, whereas removing projection substantially degrades performance. Moreover, the consistent gains of FEDPROJ over FEDDF and FEDET—which also employ server-side distillation—further indicate that projection, rather than distillation alone, is the primary driver of improvement. Together, these ablations support the core claim of the paper: explicitly constraining local optimization to preserve global knowledge is essential for preventing catastrophic boundary erosion under heterogeneous federated learning.

7 Conclusion

In this work, we identify *catastrophic forgetting of global decision boundaries* as a distinct and practically important failure mode in federated learning under data heterogeneity. Through a controlled pilot study, we show that standard local training can rapidly overwrite globally useful functional structure, causing client models to drift toward locally optimal boundaries and undermining subsequent aggregation. Motivated by this diagnosis, we propose FEDPROJ, a federated learning framework that explicitly preserves global functional knowledge during local optimization and then consolidates it at the server. FEDPROJ combines: (i) a client-side *hard* gradient projection constraint induced by a memory-based distillation loss, which prevents local updates from increasing global-knowledge loss, and (ii) a server-side ensemble distillation step that consolidates client knowledge into a single global model using a small public proxy dataset. Across a range of CV and NLP benchmarks under realistic Non-IID and domain-shift settings, FEDPROJ consistently improves accuracy and robustness over strong baselines, highlighting the benefits of intervening directly on local optimization dynamics rather than relying solely on soft regularization or aggregation heuristics.

References

Durmus Alp Emre Acar, Yue Zhao, Ramon Matas Navarro, Matthew Mattina, Paul N Whatmough, and Venkatesh Saligrama. Federated learning based on dynamic regularization. *arXiv preprint arXiv:2111.04263*, 2021.

Samuel R Bowman, Gabor Angeli, Christopher Potts, and Christopher D Manning. A large annotated corpus for learning natural language inference. *arXiv preprint arXiv:1508.05326*, 2015.

Vishnu Pandi Chellapandi, Antesh Upadhyay, Abolfazl Hashemi, and Stanislaw H Żak. On the convergence of decentralized federated learning under imperfect information sharing. *IEEE Control Systems Letters*, 2023a.

Vishnu Pandi Chellapandi, Liangqi Yuan, Christopher G. Brinton, Stanislaw H Zak, and Ziran Wang. Federated learning for connected and automated vehicles: A survey of existing approaches and challenges. *IEEE Transactions on Intelligent Vehicles*, November 2023b.

Vishnu Pandi Chellapandi, Liangqi Yuan, Stanislaw H Zak, and Ziran Wang. A survey of federated learning for connected and automated vehicles. *arXiv preprint arXiv:2303.10677*, 2023c.

Vishnu Pandi Chellapandi, Antesh Upadhyay, Abolfazl Hashemi, and Stanislaw H Żak. Fednmut – federated noisy model update tracking convergence analysis. *arXiv preprint arXiv:2403.13247*, 2024.

Sijie Cheng, Jingwen Wu, Yanghua Xiao, and Yang Liu. Fedgems: Federated learning of larger server models via selective knowledge fusion. *arXiv preprint arXiv:2110.11027*, 2021.

Yae Jee Cho, Andre Manoel, Gauri Joshi, Robert Sim, and Dimitrios Dimitriadis. Heterogeneous ensemble knowledge transfer for training large models in federated learning. *arXiv preprint arXiv:2204.12703*, 2022.

Liam Collins, Hamed Hassani, Aryan Mokhtari, and Sanjay Shakkottai. Exploiting shared representations for personalized federated learning. In *International conference on machine learning*, pp. 2089–2099. PMLR, 2021.

Luke N Darlow, Elliot J Crowley, Antreas Antoniou, and Amos J Storkey. Cinic-10 is not imagenet or cifar-10. *arXiv preprint arXiv:1810.03505*, 2018.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Mehrdad Farajtabar, Navid Azizan, Alex Mott, and Ang Li. Orthogonal gradient descent for continual learning. In *International conference on artificial intelligence and statistics*, pp. 3762–3773. PMLR, 2020.

Margalit R Glasgow, Honglin Yuan, and Tengyu Ma. Sharp bounds for federated averaging (local sgd) and continuous perspective. In *International Conference on Artificial Intelligence and Statistics*, pp. 9050–9090. PMLR, 2022.

Alec Go, Richa Bhayani, and Lei Huang. Twitter sentiment classification using distant supervision. *CS224N project report, Stanford*, 1(12):2009, 2009.

Xuan Gong, Abhishek Sharma, Srikrishna Karanam, Ziyan Wu, Terrence Chen, David Doermann, and Arun Innanje. Preserving privacy in federated learning with ensemble cross-domain knowledge distillation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 11891–11899, 2022.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International conference on machine learning*, pp. 1321–1330. PMLR, 2017.

Chaoyang He, Murali Annavaram, and Salman Avestimehr. Group knowledge transfer: Federated learning of large cnns at the edge. *Advances in neural information processing systems*, 33:14068–14080, 2020.

Tzu-Ming Harry Hsu, Hang Qi, and Matthew Brown. Measuring the effects of non-identical data distribution for federated visual classification. *arXiv preprint arXiv:1909.06335*, 2019.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling bert for natural language understanding. *arXiv preprint arXiv:1909.10351*, 2019.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *Foundations and trends® in machine learning*, 14(1–2):1–210, 2021.

Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank Reddi, Sebastian Stich, and Ananda Theertha Suresh. Scaffold: Stochastic controlled averaging for federated learning. In *International conference on machine learning*, pp. 5132–5143. PMLR, 2020.

Phillip Keung, Yichao Lu, György Szarvas, and Noah A Smith. The multilingual amazon reviews corpus. *arXiv preprint arXiv:2010.02573*, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images.(2009), 2009.

Daliang Li and Junpu Wang. Fedmd: Heterogenous federated learning via model distillation. *arXiv preprint arXiv:1910.03581*, 2019.

Qinbin Li, Bingsheng He, and Dawn Song. Model-contrastive federated learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10713–10722, 2021a.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *Proceedings of Machine learning and systems*, 2:429–450, 2020.

Tian Li, Shengyuan Hu, Ahmad Beirami, and Virginia Smith. Ditto: Fair and robust federated learning through personalization. In *International conference on machine learning*, pp. 6357–6368. PMLR, 2021b.

Xiang Li, Kaixuan Huang, Wenhao Yang, Shusen Wang, and Zhihua Zhang. On the convergence of fedavg on non-iid data. *arXiv preprint arXiv:1907.02189*, 2019.

Sen Lin, Li Yang, Deliang Fan, and Junshan Zhang. Trgp: Trust region gradient projection for continual learning. *arXiv preprint arXiv:2202.02931*, 2022.

Tao Lin, Lingjing Kong, Sebastian U Stich, and Martin Jaggi. Ensemble distillation for robust model fusion in federated learning. *Advances in neural information processing systems*, 33:2351–2363, 2020.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Mahdi Morafah, Weijia Wang, and Bill Lin. A practical recipe for federated learning under statistical heterogeneity experimental design. *IEEE Transactions on Artificial Intelligence*, 5(4):1708–1717, 2023.

Mahdi Morafah, Hojin Chang, and Bill Lin. Large scale delocalized federated learning over a huge diversity of devices in emerging next-generation edge intelligence environments. In *Proceedings of the 43rd IEEE/ACM International Conference on Computer-Aided Design*, pp. 1–8, 2024a.

Mahdi Morafah, Matthias Reisser, Bill Lin, and Christos Louizos. Stable diffusion-based data augmentation for federated learning with non-iid data. *arXiv preprint arXiv:2405.07925*, 2024b.

Majid Morafah and Mahdi Morafah. Clustered federated learning: A review. *Federated Learning-A Systematic Review*, 2025.

Gobinda Saha and Kaushik Roy. Continual learning with scaled gradient projection. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pp. 9677–9685, 2023.

Gobinda Saha, Isha Garg, and Kaushik Roy. Gradient projection memory for continual learning. *arXiv preprint arXiv:2103.09762*, 2021.

Seonguk Seo, Jinkyu Kim, Geeho Kim, and Bohyung Han. Relaxed contrastive learning for federated learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12279–12288, 2024.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 conference on empirical methods in natural language processing*, pp. 1631–1642, 2013.

Jianyu Wang, Qinghua Liu, Hao Liang, Gauri Joshi, and H Vincent Poor. Tackling the objective inconsistency problem in heterogeneous federated optimization. *Advances in neural information processing systems*, 33: 7611–7623, 2020.

Yuxia Wang, Daniel Beck, Timothy Baldwin, and Karin Verspoor. Uncertainty estimation and reduction of pre-trained models for text regression. *Transactions of the Association for Computational Linguistics*, 10: 680–696, 2022.

Adina Williams, Nikita Nangia, and Samuel R Bowman. A broad-coverage challenge corpus for sentence understanding through inference. *arXiv preprint arXiv:1704.05426*, 2017.

Blake E Woodworth, Kumar Kshitij Patel, and Nati Srebro. Minibatch vs local sgd for heterogeneous distributed learning. *Advances in Neural Information Processing Systems*, 33:6281–6292, 2020.

Yuxin Xiao, Paul Pu Liang, Umang Bhatt, Willie Neiswanger, Ruslan Salakhutdinov, and Louis-Philippe Morency. Uncertainty quantification with pre-trained language models: A large-scale empirical analysis. *arXiv preprint arXiv:2210.04714*, 2022.

Guanxiong Zeng, Yang Chen, Bo Cui, and Shan Yu. Continual learning of context-dependent processing in neural networks. *Nature Machine Intelligence*, 1(8):364–372, 2019.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28, 2015.

Zhuangdi Zhu, Junyuan Hong, and Jiayu Zhou. Data-free knowledge distillation for heterogeneous federated learning. In *International conference on machine learning*, pp. 12878–12889. PMLR, 2021.

A   Additional Theory and Proofs

A.1   Proof of Boundary Stability Result

We first formalize the relationship between KL control and stability of the predicted label on the buffer.

Lemma A.1 (Pinsker bound for per-sample predictive shift). *For any x and any θ, θ', let $p = \sigma(f(x;\theta))$ and $q = \sigma(f(x;\theta'))$. Then*

$$\|p - q\|_1 \ \leq \ \sqrt{2\,\mathrm{KL}(p\|q)}.$$

Proof. This is Pinsker's inequality.   □

Lemma A.2 (Margin implies label stability under small logit perturbations). *Fix x and let $y = y_\theta(x) = \arg\max_j f_j(x;\theta)$. If $\max_j |f_j(x;\theta') - f_j(x;\theta)| \leq \gamma/2$ and $m_\theta(x) \geq \gamma$, then $y_{\theta'}(x) = y_\theta(x)$.*

Proof. For any $j \neq y$,

$$f_y(x;\theta') \ \geq \ f_y(x;\theta) - \gamma/2 \ \geq \ \max_{j \neq y} f_j(x;\theta) + \gamma - \gamma/2 \ \geq \ \max_{j \neq y} f_j(x;\theta'),$$

where the last inequality uses $f_j(x;\theta') \leq f_j(x;\theta) + \gamma/2$. Thus y remains the argmax under θ'.   □

Lemma A.3 (From KL shift to a bound on logit perturbations (sufficient condition)). *Let $p = \sigma(z)$ and $q = \sigma(z')$ be softmax distributions over C classes. If $\|p - q\|_1 \leq \epsilon$ and $\min_j p_j \geq \underline{p} > 0$, then $\|z - z'\|_\infty \leq \frac{2\epsilon}{\underline{p}}$ up to an additive constant shared across logits.*

Proof sketch. Softmax is invariant to additive shifts, so we compare logits modulo a constant. Using standard Lipschitz properties of the log-softmax mapping on the set $\{p : \min_j p_j \geq \underline{p}\}$ yields $\|\log p - \log q\|_\infty \leq \frac{\|p-q\|_\infty}{\underline{p}} \leq \frac{\|p-q\|_1}{\underline{p}}$, and then $\|z - z'\|_\infty$ is controlled by $\|\log p - \log q\|_\infty$.   □

Proof of Proposition 5.3. Lemma A.1 gives $\|\sigma(f(x;\theta')) - \sigma(f(x;\theta))\|_1 \leq \sqrt{2\,\mathrm{KL}_x(\theta,\theta')}$. Assuming $\mathrm{KL}_x(\theta,\theta') \leq \delta$ for all $x \in \mathcal{M}$ implies a uniform bound on the probability shift. Under a mild non-degeneracy condition on the predictive distribution (e.g., $\min_j \sigma(f(x;\theta))_j \geq \underline{p}$ on $\mathcal{M}$), Lemma A.3 converts this to a bound on the (shift-invariant) logit perturbation. Finally, if $m_\theta(x) \geq \gamma$ on $\mathcal{M}$ and the induced logit perturbation is at most $\gamma/2$, Lemma A.2 implies $y_{\theta'}(x) = y_\theta(x)$ for all $x \in \mathcal{M}$. Thus the restricted decision boundary $\mathcal{B}_\theta(\mathcal{M})$ is preserved.   □

A.2   Projection Properties: Feasibility and Minimal Intervention

Proposition A.4 (Feasibility and closed-form solution). *The solution to equation 6 is given by equation 7, and satisfies $\langle g_{\mathrm{proj}}, g_{\mathrm{glob}} \rangle \geq 0$.*

Proof. This is a one-constraint convex quadratic program. Applying KKT conditions yields: (i) if $\langle g_{\mathrm{new}}, g_{\mathrm{glob}} \rangle \geq 0$ then g_{new} is feasible and optimal; (ii) otherwise the optimum lies on the boundary $\langle g_{\mathrm{proj}}, g_{\mathrm{glob}} \rangle = 0$, and the orthogonal projection onto that boundary gives equation 7.   □

Proposition A.5 (Minimal intervention). *Among all feasible directions g satisfying $\langle g, g_{\mathrm{glob}} \rangle \geq 0$, the projected direction g_{proj} uniquely minimizes $\|g - g_{\mathrm{new}}\|_2$. Equivalently, FedProj alters the local gradient by the smallest possible amount needed to satisfy the global-knowledge constraint.*

Proof. This is immediate from the definition of the Euclidean projection onto a closed convex set (here, a half-space).   □

A.3 Convergence: Proof Outline for Theorem 5.6

We sketch the key steps and highlight where FedProj improves the heterogeneity term.

Lemma A.6 (One-step descent under smoothness). *If F is L-smooth, then for any update $\theta^+ = \theta - \eta v$,*

$$F(\theta^+) \leq F(\theta) - \eta \langle \nabla F(\theta), v \rangle + \frac{L\eta^2}{2} \|v\|_2^2.$$

Proof. Standard smoothness inequality. □

Lemma A.7 (Effective heterogeneity bound under alignment). *Assume $\langle \nabla F(\theta), g_{\text{glob}}(\theta) \rangle \geq \kappa \|\nabla F(\theta)\| \|g_{\text{glob}}(\theta)\|$. Then for the projected direction g_{proj} produced by equation 6, the component of the local gradient that conflicts with $\nabla F(\theta)$ is reduced so that*

$$\mathbb{E}\big[\|g_{\text{proj}} - \nabla F(\theta)\|_2^2\big] \leq \mathcal{O}\left(\sigma^2 + \frac{\zeta^2(\theta)}{\kappa}\right),$$

where the expectation is over client sampling and stochastic gradients.

Proof of Lemma A.7. Fix an iterate θ and suppress the explicit dependence on θ for readability. Let $C := \{g \in \mathbb{R}^p : \langle g, g_{\text{glob}} \rangle \geq 0\}$ be the closed half-space induced by the memory gradient g_{glob}. By construction, g_{proj} is the Euclidean projection of g_{new} onto C (Proposition A.4), i.e., $g_{\text{proj}} = \Pi_C(g_{\text{new}})$.

Assumption 5.5 states that

$$\langle \nabla F, g_{\text{glob}} \rangle \geq \kappa \|\nabla F\|_2 \|g_{\text{glob}}\|_2 > 0,$$

hence $\langle \nabla F, g_{\text{glob}} \rangle \geq 0$ and therefore $\nabla F \in C$.

A standard property of Euclidean projection onto a nonempty closed convex set C is: for any $u \in C$,

$$\|\Pi_C(a) - u\|_2^2 \leq \|a - u\|_2^2. \tag{10}$$

(Indeed, this follows from the Pythagorean inequality for projections onto convex sets.)

Applying equation 10 with $a = g_{\text{new}}$ and $u = \nabla F \in C$ yields

$$\|g_{\text{proj}} - \nabla F\|_2^2 = \|\Pi_C(g_{\text{new}}) - \nabla F\|_2^2 \leq \|g_{\text{new}} - \nabla F\|_2^2. \tag{11}$$

Taking expectation over the client sampling and the stochasticity of g_{new} gives

$$\mathbb{E}\|g_{\text{proj}} - \nabla F\|_2^2 \leq \mathbb{E}\|g_{\text{new}} - \nabla F\|_2^2. \tag{12}$$

Let k denote the sampled client (according to $\{p_k\}$), and let g_{new} be an unbiased stochastic gradient for F_k:

$$\mathbb{E}[g_{\text{new}} \mid k] = \nabla F_k, \qquad \mathbb{E}\|g_{\text{new}} - \nabla F_k\|_2^2 \leq \sigma^2.$$

Write the decomposition

$$g_{\text{new}} - \nabla F = (g_{\text{new}} - \nabla F_k) + (\nabla F_k - \nabla F).$$

Using $\|a + b\|_2^2 \leq 2\|a\|_2^2 + 2\|b\|_2^2$ and then taking expectations:

$$\mathbb{E}\|g_{\text{new}} - \nabla F\|_2^2 \leq 2\,\mathbb{E}\|g_{\text{new}} - \nabla F_k\|_2^2 + 2\,\mathbb{E}\|\nabla F_k - \nabla F\|_2^2$$

$$\leq 2\sigma^2 + 2\sum_{k=1}^{N} p_k \|\nabla F_k - \nabla F\|_2^2$$

$$= 2\sigma^2 + 2\zeta^2(\theta). \tag{13}$$

Combining equation 12 and equation 13 yields

$$\mathbb{E}\|g_{\text{proj}} - \nabla F\|_2^2 \leq 2\sigma^2 + 2\zeta^2(\theta).$$

Finally, since $\kappa \in (0, 1]$ implies $\zeta^2(\theta) \leq \zeta^2(\theta)/\kappa$, we also have the (looser but convenient) form

$$\mathbb{E}\|g_{\text{proj}} - \nabla F\|_2^2 \leq 2\sigma^2 + 2\frac{\zeta^2(\theta)}{\kappa},$$

which matches the scaling used in Theorem 5.6 up to constants. $\qquad\square$

Proof of Theorem 5.6. We analyze one communication round and then telescope over $t = 0, \ldots, T - 1$. For clarity, we present the argument for the case of one effective client update per round aggregated at the server; the extension to E local steps follows by standard arguments that bound the additional client-drift error by $\mathcal{O}(\eta_{\text{local}}^2 L^2 E^2)$ under L-smoothness, which is absorbed into the constants of the theorem when $\eta_{\text{local}} \leq 1/(cLE)$.

Since F is L-smooth, for any update $\theta^+ = \theta - \eta v$, Lemma A.6 yields

$$F(\theta^+) \leq F(\theta) - \eta \langle \nabla F(\theta), v \rangle + \frac{L\eta^2}{2} \|v\|_2^2. \tag{14}$$

At round t, let $\theta = \theta_g^{(t)}$ and let the server update be

$$\theta_g^{(t+1)} = \theta_g^{(t)} - \eta_{\text{local}} v_t,$$

where v_t is the (weighted) aggregate of client projected directions in that round. Taking $v = v_t$ and $\eta = \eta_{\text{local}}$ in equation 14 gives

$$F(\theta_g^{(t+1)}) \leq F(\theta_g^{(t)}) - \eta_{\text{local}} \langle \nabla F(\theta_g^{(t)}), v_t \rangle + \frac{L\eta_{\text{local}}^2}{2} \|v_t\|_2^2. \tag{15}$$

Under the standard FL sampling model (clients sampled according to p_k and aggregated with the same weights), and unbiased stochastic gradients on each client, the aggregated direction is unbiased for the global gradient:

$$\mathbb{E}[v_t \mid \theta_g^{(t)}] = \nabla F(\theta_g^{(t)}). \tag{16}$$

(Here the expectation is over client sampling and stochastic gradients; projection does not introduce bias in expectation for the global direction because it only modifies the local stochastic direction but the aggregate remains aligned in the descent analysis through the second-moment control below.)

Using equation 16,

$$\mathbb{E}\big[\langle \nabla F(\theta_g^{(t)}), v_t \rangle \mid \theta_g^{(t)}\big] = \|\nabla F(\theta_g^{(t)})\|_2^2.$$

We use the standard inequality $\|a\|_2^2 \leq 2\|a - b\|_2^2 + 2\|b\|_2^2$ with $b = \nabla F(\theta_g^{(t)})$:

$$\mathbb{E}\big[\|v_t\|_2^2 \mid \theta_g^{(t)}\big] \leq 2\,\mathbb{E}\big[\|v_t - \nabla F(\theta_g^{(t)})\|_2^2 \mid \theta_g^{(t)}\big] + 2\,\|\nabla F(\theta_g^{(t)})\|_2^2. \tag{17}$$

By Lemma A.7 (applied at $\theta = \theta_g^{(t)}$),

$$\mathbb{E}\big[\|v_t - \nabla F(\theta_g^{(t)})\|_2^2 \mid \theta_g^{(t)}\big] \leq C_1\left(\sigma^2 + \frac{\zeta^2}{\kappa}\right),$$

for an absolute constant $C_1 > 0$ (absorbing the factor of 2 from Lemma A.7 into C_1). Substituting into equation 17 yields

$$\mathbb{E}\big[\|v_t\|_2^2 \mid \theta_g^{(t)}\big] \leq 2C_1\left(\sigma^2 + \frac{\zeta^2}{\kappa}\right) + 2\|\nabla F(\theta_g^{(t)})\|_2^2. \tag{18}$$

Take conditional expectation of equation 15 given $\theta_g^{(t)}$ and apply the bounds above:

$$\begin{aligned}
\mathbb{E}\big[F(\theta_g^{(t+1)}) \mid \theta_g^{(t)}\big] &\leq F(\theta_g^{(t)}) - \eta_{\text{local}}\|\nabla F(\theta_g^{(t)})\|_2^2 + \frac{L\eta_{\text{local}}^2}{2}\mathbb{E}\big[\|v_t\|_2^2 \mid \theta_g^{(t)}\big] \\
&\leq F(\theta_g^{(t)}) - \eta_{\text{local}}\|\nabla F(\theta_g^{(t)})\|_2^2 + \frac{L\eta_{\text{local}}^2}{2}\left(2C_1\left(\sigma^2 + \frac{\zeta^2}{\kappa}\right) + 2\|\nabla F(\theta_g^{(t)})\|_2^2\right) \\
&= F(\theta_g^{(t)}) - \eta_{\text{local}}\left(1 - L\eta_{\text{local}}\right)\|\nabla F(\theta_g^{(t)})\|_2^2 + L\eta_{\text{local}}^2 C_1\left(\sigma^2 + \frac{\zeta^2}{\kappa}\right).
\end{aligned} \tag{19}$$

Choose η_{local} sufficiently small so that $1 - L\eta_{\text{local}} \geq \frac{1}{2}$ (e.g., $\eta_{\text{local}} \leq 1/(2L)$; the statement in the theorem uses $\eta_{\text{local}} \leq 1/(cLE)$ to also absorb local-step drift when $E > 1$). Then equation 19 gives

$$\mathbb{E}\big[F(\theta_g^{(t+1)})\big] \leq \mathbb{E}\big[F(\theta_g^{(t)})\big] - \frac{\eta_{\text{local}}}{2}\mathbb{E}\|\nabla F(\theta_g^{(t)})\|_2^2 + L\eta_{\text{local}}^2 C_1\Big(\sigma^2 + \frac{\zeta^2}{\kappa}\Big). \tag{20}$$

Summing equation 20 over $t = 0, \ldots, T-1$ telescopes the left-hand side:

$$\mathbb{E}\big[F(\theta_g^{(T)})\big] \leq F(\theta_g^{(0)}) - \frac{\eta_{\text{local}}}{2}\sum_{t=0}^{T-1}\mathbb{E}\|\nabla F(\theta_g^{(t)})\|_2^2 + T \cdot L\eta_{\text{local}}^2 C_1\Big(\sigma^2 + \frac{\zeta^2}{\kappa}\Big).$$

Using $F(\theta_g^{(T)}) \geq F^\star$ and rearranging yields

$$\frac{1}{T}\sum_{t=0}^{T-1}\mathbb{E}\|\nabla F(\theta_g^{(t)})\|_2^2 \leq \frac{2(F(\theta_g^{(0)}) - F^\star)}{\eta_{\text{local}}T} + 2L\eta_{\text{local}}C_1\Big(\sigma^2 + \frac{\zeta^2}{\kappa}\Big).$$

Finally, incorporating E local steps per round scales the effective progress term by E and introduces an additional client-drift contribution controlled by L-smoothness, which is absorbed by the stated stepsize restriction $\eta_{\text{local}} \leq 1/(cLE)$ and constant factors. This yields the theorem statement (up to absolute constants), completing the proof. $\qquad \square$

A.4 Proof for Gradient Projection in equation 5

We provide a detailed mathematical derivation of the gradient projection step used in FedProj.

Proof. Consider the optimization problem:

$$\min_{g_{\text{proj}}} \quad \frac{1}{2}\|g_{\text{new}} - g_{\text{proj}}\|_2^2, \quad \text{s.t.} \quad \langle g_{\text{proj}}, g_{\text{glob}}\rangle \geq 0. \tag{21}$$

We introduce the Lagrangian:

$$\mathcal{L}(g_{\text{proj}}, \lambda) = \frac{1}{2}\|g_{\text{new}} - g_{\text{proj}}\|_2^2 - \lambda\langle g_{\text{proj}}, g_{\text{glob}}\rangle,$$

with the Karush-Kuhn-Tucker (KKT) optimality conditions:

$$\frac{\partial \mathcal{L}}{\partial g_{\text{proj}}} = g_{\text{proj}} - g_{\text{new}} - \lambda g_{\text{glob}} = 0, \tag{22}$$

$$\lambda \geq 0, \tag{23}$$

$$\lambda\langle g_{\text{proj}}, g_{\text{glob}}\rangle = 0, \quad \langle g_{\text{proj}}, g_{\text{glob}}\rangle \geq 0. \tag{24}$$

From the first KKT condition, we have:

$$g_{\text{proj}} = g_{\text{new}} + \lambda g_{\text{glob}}. \tag{25}$$

To find λ, we consider two cases:

- **Case 1 ($\lambda = 0$):** If $\langle g_{\text{new}}, g_{\text{glob}}\rangle \geq 0$, then $g_{\text{proj}} = g_{\text{new}}$ directly satisfies the constraint, making it the optimal solution.

- **Case 2:** If $\langle g_{\text{new}}, g_{\text{glob}}\rangle < 0$, the constraint becomes active:

$$\langle g_{\text{proj}}, g_{\text{glob}}\rangle = 0.$$

Dataset	WD	$\text{Dir}(\beta{=}0.3)$	$\text{Dir}(\beta{=}0.5)$
CIFAR10	0.1	$64.12_{\pm 1.42}$	$66.57_{\pm 1.43}$
	0.3	$63.31_{\pm 0.29}$	$\mathbf{69.88}_{\pm 0.03}$
	0.5	$63.07_{\pm 2.38}$	$67.12_{\pm 1.85}$
	w/o	$\mathbf{65.52}_{\pm 0.86}$	$67.23_{\pm 0.66}$
CIFAR100	0.1	$34.71_{\pm 0.16}$	$37.67_{\pm 0.14}$
	0.3	$33.49_{\pm 0.24}$	$36.99_{\pm 0.16}$
	0.5	$33.21_{\pm 0.31}$	$\mathbf{38.06}_{\pm 0.21}$
	w/o	$\mathbf{35.27}_{\pm 0.11}$	$36.98_{\pm 0.41}$
CINIC10	0.1	$39.85_{\pm 0.34}$	$40.97_{\pm 0.22}$
	0.3	$40.11_{\pm 0.21}$	$\mathbf{41.63}_{\pm 0.21}$
	0.5	$40.22_{\pm 0.36}$	$41.25_{\pm 0.18}$
	w/o	$\mathbf{41.46}_{\pm 0.55}$	$41.19_{\pm 0.27}$

Table 3: Exploratory impact of Weight Divergence (WD) regularization on CIFAR-10, CIFAR-100, and CINIC-10.

Substituting equation 25, we obtain:

$$\langle g_{\text{new}} + \lambda g_{\text{glob}}, g_{\text{glob}} \rangle = 0 \quad \Rightarrow \quad \lambda = -\frac{\langle g_{\text{new}}, g_{\text{glob}} \rangle}{\|g_{\text{glob}}\|^2 + \epsilon}.$$

Hence, the optimal projected gradient is:

$$g_{\text{proj}} = g_{\text{new}} - \frac{\langle g_{\text{new}}, g_{\text{glob}} \rangle}{\|g_{\text{glob}}\|^2 + \epsilon} \, g_{\text{glob}}, \tag{26}$$

matching Eq. equation 26. Thus, the derived gradient projection update guarantees that local model updates do not negatively affect global knowledge retention.

B Full Algorithm Description of FedProj

The full algorithm description of FedProj is presented in Algorithm 1.

C Ablation Studies

C.1 Exploratory Study: Weight Divergence Regularization

The ensemble distillation process is inherently noisy, since it leverages public data that may differ significantly from the private client datasets. To explore whether an additional constraint could stabilize the global model against this noise, we experimented with a weight divergence (WD) penalty that encourages global parameters to remain close to the averaged client model. Formally, given global model parameters $\boldsymbol{\theta}_g$ and all participating client parameters $\{\boldsymbol{\theta}_k\}_{k=1}^{K}$, we define:

$$\mathcal{L}_{\text{div}} = \sum_{k=1}^{K} \left\| \boldsymbol{\theta}_k - \boldsymbol{\theta}_g \right\|_2^2.$$

Table 3 presents the effect of WD regularization on server-side performance for CIFAR-10, CIFAR-100, and CINIC-10 under different Dirichlet heterogeneity settings. For CIFAR-10, omitting the regularizer ($\alpha = 0$) achieves the highest accuracy for $\beta = 0.3$, while a moderate coefficient ($\alpha = 0.3$) performs best for $\beta = 0.5$. In CIFAR-100, $\alpha = 0.5$ yields the strongest performance for $\beta = 0.5$, whereas no regularizer is preferable for $\beta = 0.3$. CINIC-10 shows minimal variation across all choices, indicating low sensitivity to this penalty.

Algorithm 1 FedProj: Federated Learning with Gradient Projection and Distillation

---

Require: Number of rounds T, learning rates $\eta_{\text{local}}, \eta_{\text{distill}}$, local epochs E, distillation epochs E_d, public dataset $\mathcal{D}_{\text{pub}}$, memory size M, temperature τ, regularization α

1: Initialize global model $\boldsymbol{\theta}_g^{(0)}$
2: **for** $t = 0, \dots, T - 1$ **do**
3:      Sample client subset $\mathcal{S}_t$
4:      Sample memory buffer $\mathcal{M}_t \subset \mathcal{D}_{\text{pub}}$, $|\mathcal{M}_t| = M$
5:      **if** $t > 0$ **then**
6:          Compute ensemble on memory: $\mathbf{Z}_{\text{ens}}^{(t)}(\mathbf{x}) \leftarrow \frac{1}{|\mathcal{S}_{t-1}|} \sum_{k \in \mathcal{S}_{t-1}} f(\mathbf{x}; \boldsymbol{\theta}_k^{(t)})$ for $\mathbf{x} \in \mathcal{M}_t$
7:      **end if**
8:      **for** all $k \in \mathcal{S}_t$ **in parallel do**
9:          $\boldsymbol{\theta}_k \leftarrow \boldsymbol{\theta}_g^{(t)}$
10:          **for** epoch $e = 1, \dots, E$ **do**
11:              **for** mini-batch $(\mathbf{x}, \mathbf{y}) \subseteq \mathcal{D}_k$ **do**
12:                  $\mathbf{g}_{\text{local}} \leftarrow \nabla_{\boldsymbol{\theta}_k} \ell(f(\mathbf{x}; \boldsymbol{\theta}_k), \mathbf{y})$
13:                  **if** $t > 0$ **then**
14:                      $\mathbf{g}_{\text{mem}} \leftarrow \nabla_{\boldsymbol{\theta}_k} \left[\frac{1}{M} \sum_{\mathbf{x}_m \in \mathcal{M}_t} \text{KL} \left(\sigma(\mathbf{Z}_{\text{ens}}^{(t)}(\mathbf{x}_m)) \| \sigma(f(\mathbf{x}_m; \boldsymbol{\theta}_k)) \right) \right]$
15:                  **else**
16:                      $\mathbf{g}_{\text{mem}} \leftarrow \nabla_{\boldsymbol{\theta}_k} \left[\frac{1}{M} \sum_{(\mathbf{x}_m, \mathbf{y}_m) \in \mathcal{M}_t} \ell(f(\mathbf{x}_m; \boldsymbol{\theta}_k), \mathbf{y}_m) \right]$
17:                  **end if**
18:                  $\mathbf{g}_{\text{proj}} \leftarrow \mathbf{g}_{\text{local}} - \frac{\langle \mathbf{g}_{\text{local}}, \mathbf{g}_{\text{mem}} \rangle}{\|\mathbf{g}_{\text{mem}}\|_2^2 + \epsilon} \mathbf{g}_{\text{mem}}$
19:                  $\boldsymbol{\theta}_k \leftarrow \boldsymbol{\theta}_k - \eta_{\text{local}} \mathbf{g}_{\text{proj}}$
20:              **end for**
21:          **end for**
22:          $\boldsymbol{\theta}_k^{(t+1)} \leftarrow \boldsymbol{\theta}_k$
23:      **end for**
24:      *// Server aggregation & distillation*
25:      $\boldsymbol{\theta}_g^{\text{avg}} \leftarrow \sum_{k \in \mathcal{S}_t} \frac{|\mathcal{D}_k|}{\sum_{j \in \mathcal{S}_t} |\mathcal{D}_j|} \boldsymbol{\theta}_k^{(t+1)}$
26:      $\boldsymbol{\theta}_g \leftarrow \boldsymbol{\theta}_g^{\text{avg}}$
27:      **for** epoch $e_d = 1, \dots, E_d$ **do**
28:          **for** mini-batch $\mathbf{X} \subseteq \mathcal{D}_{\text{pub}}$ **do**
29:              $\mathbf{Z}_{\text{teacher}} \leftarrow \frac{1}{|\mathcal{S}_t|} \sum_{k \in \mathcal{S}_t} f(\mathbf{X}; \boldsymbol{\theta}_k^{(t+1)})$
30:              $\mathbf{Z}_{\text{student}} \leftarrow f(\mathbf{X}; \boldsymbol{\theta}_g)$
31:              $\mathcal{L}_{\text{KD}} \leftarrow \tau^2 \cdot \text{KL}(\sigma(\mathbf{Z}_{\text{student}}/\tau), \sigma(\mathbf{Z}_{\text{teacher}}/\tau))$
32:              $\mathcal{L}_{\text{div}} \leftarrow \alpha \|\boldsymbol{\theta}_g - \boldsymbol{\theta}_g^{(t)}\|_2^2$ {Optional}
33:              $\boldsymbol{\theta}_g \leftarrow \boldsymbol{\theta}_g - \eta_{\text{distill}} \nabla_{\boldsymbol{\theta}_g} [\mathcal{L}_{\text{KD}} + \mathcal{L}_{\text{div}}]$
34:          **end for**
35:      **end for**
36:      $\boldsymbol{\theta}_g^{(t+1)} \leftarrow \boldsymbol{\theta}_g$
37: **end for**
Ensure: Global model $\boldsymbol{\theta}_g^{(T)}$

C.2   Reliance on Public Dataset

We systematically varied the public dataset size from 10,000 to 60,000 samples and evaluated performance under two data heterogeneity settings (Dirichlet $\beta = 0.3$ and $\beta = 0.5$). Each experiment was run with three random seeds, and we report the mean $\pm$ standard deviation. Results are summarized in Table 4.

Our analysis reveals several key observations. First, we observe diminishing returns when scaling public data size: the most significant improvement occurs when increasing from 10K to 20K samples, yielding a 2.9% gain for $\beta = 0.3$, whereas gains beyond 20K samples are marginal. Interestingly, even a relatively small public

Figure 3: Average training loss across communication rounds for different datasets with Dirichlet $\beta = 0.3$.

Public dataset size	$\beta = 0.3$	$\beta = 0.5$
10,000	62.49 ± 0.63	68.22 ± 0.41
20,000	65.39 ± 0.16	68.91 ± 0.73
30,000	64.41 ± 0.67	68.70 ± 1.04
40,000	64.49 ± 1.71	68.91 ± 0.61
60,000	65.52 ± 0.86	69.98 ± 0.03

Table 4: Performance analysis across different public dataset sizes.

dataset of 10K samples achieves competitive performance, with 62.49% accuracy at $\beta = 0.3$, highlighting the sufficiency of modest data resources in many scenarios. Furthermore, data heterogeneity plays a critical role: less heterogeneous settings ($\beta = 0.5$) consistently achieve better performance and stability across all public dataset sizes. Finally, we identify a practical regime at 20K–30K public samples, which provides the best trade-off between performance and data requirements, making it well-suited for real-world federated learning deployments. These findings demonstrate that our server-side knowledge distillation approach is robust across a range of FL conditions, requiring only moderate amounts of public data to achieve strong performance even under high heterogeneity.

C.3 Training Dynamics and Convergence Stability

Figure 3 illustrates the training loss dynamics across communication rounds for CIFAR-10, CIFAR-100, and CINIC-10 under strong data heterogeneity ($\beta = 0.3$). FedProj consistently demonstrates superior convergence stability compared to all baselines. Notably, FedAvg exhibits severe oscillations and catastrophic spikes—particularly evident in CIFAR-100 around round 50, where loss abruptly increases from 0.15 to 0.30—indicating substantial forgetting of previously learned knowledge during local training. In contrast, FedProj maintains smooth, monotonic convergence across all datasets, with minimal variance after the initial rounds. This stability is especially pronounced on CIFAR-100, where the increased number of classes (100 vs. 10) exacerbates heterogeneity-induced forgetting. While other methods such as FedProx, FedDF, and MOON achieve moderate stability, they still exhibit noticeable fluctuations throughout training. The consistent stability of FedProj across diverse datasets empirically validates our hypothesis that explicit preservation of global decision boundaries through gradient projection effectively mitigates catastrophic forgetting in federated learning under non-IID data.