TARPO: Token-Wise Latent-Explicit Reasoning via Action-Routing Policy Optimization

Abstract

Latent reasoning has emerged as a promising alternative to discrete Chain-of-Thought (CoT) in large language models (LLMs), enabling more expressive reasoning by operating over continuous representations. However, the inherently deterministic nature of continuous representations limits policy exploration in reinforcement learning (RL). To address this, we propose TARPO (Token-Wise Latent-Explicit Reasoning via Action-Routing Policy Optimization), a pure RL framework that adaptively switches between discrete token generation and continuous latent reasoning at each step. TARPO introduces a lightweight action head router that observes the current hidden state and samples a routing decision from a binary mode-selection space, preserving the stochasticity of discrete token sampling from the vocabulary. The LLM backbone and router are jointly optimized end-to-end with a shared group-relative advantage signal. Extensive experiments across Qwen2.5 (from 1.5B to 7B) and Llama-3.1-8B backbones demonstrate that TARPO consistently outperforms existing explicit and latent reasoning RL baselines across diverse benchmarks. Further analysis shows that TARPO learns adaptive token-wise switching behaviors while maintaining stable training dynamics. Our code is available at https://anonymous.4open.science/r/TARPO-DF5A.

1 Introduction

Large Language Models (LLMs) have demonstrated remarkable reasoning capabilities under the Chain-of-Thought (CoT) paradigm (Wei et al., 2022; Guo et al., 2025; Kim et al., 2025). However, their reliance on discrete token generation introduces a fundamental bottleneck: high-dimensional hidden states must be collapsed into a single token at each step, limiting expressiveness and information capacity (Hao et al., 2024). Latent reasoning has recently emerged as a promising paradigm (Zhu et al., 2025; Chen et al., 2025). By shifting reasoning from discrete tokens to continuous representations, it enables more expressive and efficient reasoning trajectories.

Unlike discrete token sampling which is inherently stochastic, continuous representations are naturally deterministic, whether formulated as raw hidden states (Hao et al., 2024; Wang et al., 2026) or probability-weighted embedding mixtures (Zhang et al., 2026). This lack of native randomness fundamentally limits policy exploration in reinforcement learning (RL).

To address this exploration bottleneck, existing studies have mainly pursued two directions: reparameterization-based exploration and latent-explicit hybrid reasoning. One line of work applies reparameterization techniques (Tan et al., 2026; Butt et al., 2025; Zheng and Lee, 2025) to inject stochasticity in continuous representations, typically through Gaussian or Gumbel noise. Another line of research seeks to preserve the inherent diversity of discrete token distributions through hybrid architectures (Yue et al., 2026; Tang et al., 2026; Shi et al., 2025; Zhao et al., 2026), which combine latent reasoning with discrete token generation via dense integration or mode switching. However, existing switching approaches often rely on rigid heuristic rules (Shi et al., 2025; Xu et al., 2026) or supervised initialization (Gurung et al., 2025; Zhao et al., 2026). Consequently, there remains a critical gap for a lightweight, end-to-end RL framework capable of adaptive fine-grained mode switching.

In this paper, we propose TARPO (**T**oken-Wise Latent-Explicit Reasoning via **A**ction-**R**outing **P**olicy **O**ptimization), a pure RL framework that enables token-wise transitions between discrete and latent reasoning mode. Specifically, we introduce a lightweight action head router that observes the current hidden state to dynamically determine, at each step, whether the next reasoning

unit should be constructed from a discrete token embedding or a continuous latent representation. Importantly, by formulating this routing decision as a choice within a discrete action space, our approach leverages the intrinsic stochasticity of routing policies to induce exploration over reasoning modes. Following the GRPO (Shao et al., 2024) paradigm, we jointly optimize the action head router and the LLM backbone end-to-end using a shared advantage signal. This unified objective enables the model to autonomously learn adaptive reasoning strategies without relying on heuristic rules or supervised initialization. Extensive experiments across Qwen2.5 backbones (from 1.5B to 7B) demonstrate that TARPO outperforms existing latent reasoning RL baselines while cross-architecture evaluation on Llama-3.1-8B confirms its generalization on three mathematical benchmarks. Out-of-distribution results on Qwen2.5-3B further show improved generalization and token efficiency, and our analysis reveals adaptive switching between discrete and latent reasoning.

The main contributions of this work are summarized as follows:

- We propose TARPO, a pure reinforcement learning framework for token-wise latent-explicit reasoning, which adaptively switches between discrete token generation and continuous latent reasoning.

- We formulate reasoning-mode selection as a learnable action-routing policy and introduce a joint optimization objective that end-to-end trains the router and the LLM backbone.

- Extensive experiments and analyses demonstrate that TARPO consistently outperforms existing explicit and latent reasoning RL baselines, while learning adaptive switching behaviors across diverse benchmarks.

2 Related Work

2.1 From Discrete CoT to Latent Reasoning

Standard Chain-of-Thought (CoT) (Kojima et al., 2022; Wei et al., 2022) elicits reasoning through discrete tokens, which imposes an information bottleneck that limits representational capacity (Hao et al., 2024). To overcome this, recent work shifts reasoning into the latent space (Zhu et al., 2025; Chen et al., 2025; Shen et al., 2025; Su et al., 2025). Within this paradigm, continuous latent reasoning methods condition reasoning steps directly on transformer hidden states (Hao et al., 2024; Wang et al., 2026; Geiping et al., 2026) or probability-weighted token embedding mixtures (Zhang et al., 2026). For instance, CO-CONUT (Hao et al., 2024) directly feeds hidden states into subsequent steps to enable parallel path exploration, while System-1.5 (Wang et al., 2026) adaptively reuses these representations via dynamic shortcuts. However, directly utilizing raw hidden states often causes representation manifold mismatch (Zhang et al., 2026; Yue et al., 2026) and catastrophic forgetting (Xu et al., 2025). Consequently, most recent architectures adopt token embedding mixtures. Nevertheless, these continuous representations remain inherently deterministic, limiting the intrinsic exploration capability required for reinforcement learning.

2.2 Exploration in Latent Reasoning RL

Reparameterization-Based Exploration. This line of work applies reparameterization techniques to introduce stochasticity into continuous representations, enabling policy exploration and gradient-based optimization. For instance, some recent methods inject Gaussian noise into compressed latent variables (Tan et al., 2026; Zhang et al., 2025) or continuous token embeddings (Butt et al., 2025). Meanwhile, other approaches (Wu et al., 2025; Zheng and Lee, 2025; Zhou et al., 2026; Deng et al., 2026) apply the Gumbel-Softmax trick to derive probabilistic soft-token distributions.

Latent-Explicit Hybrid Reasoning. As an alternative to reparameterization, this line of work seeks to fuse explicit discrete tokens with continuous latent representations, preserving the intrinsic stochasticity of discrete token sampling. One paradigm constructs a dense representation within a continuous space at each decoding step. For instance, HRPO (Yue et al., 2026) blends hidden state representations with token embeddings via a learnable gate, while Multiplex Thinking (Tang et al., 2026) aggregates multiple independently sampled tokens into a single continuous token. Distinct from these dense integration approaches, another branch explores selective reasoning mode switching along the discrete trajectory. However, existing frameworks typically rely on rigid heuristics such as token entropy (Shi et al., 2025; Xu et al., 2026; Fu and Luo, 2026; Lv et al., 2026) or heavily supervised initialization (Fu et al., 2025; Gurung et al., 2025; Zhao et al., 2026), which limit autonomous exploration.

Figure 1: Overview of the TARPO framework. (a) During reasoning, a lightweight Action Head receives the current hidden state and routes the next step to either discrete token generation (hard) or continuous latent reasoning (soft). (b) The framework is trained end-to-end with a shared group-relative advantage signal, which jointly updates the LLM backbone and the action head from sampled hybrid rollouts.

Motivated by these limitations, TARPO introduces a token-wise action-routing mechanism that learns adaptive mode switching entirely through reinforcement learning. Unlike prior hybrid methods that rely on fixed heuristics or supervised initialization, TARPO formulates reasoning-mode selection as a learnable discrete routing policy over a binary action space, enabling end-to-end optimization of the routing head and LLM backbone within a unified RL objective.

3 Methodology

3.1 Problem Formulation

We formulate token-wise latent-explicit reasoning as a sequential decision process. At step t, the state s_t corresponds to the current context history $s_t = (x, u_1, u_2, \ldots, u_{t-1})$, where x is the initial user prompt and each reasoning unit u_i is either a discrete token embedding or a continuous latent representation.

To enable adaptive transitions between explicit and latent reasoning, we define a binary routing decision space $\mathcal{D} = \{\text{hard}, \text{soft}\}$ and a joint action space:

$$\mathcal{A} = \{\text{soft}\} \cup (\{\text{hard}\} \times \mathcal{V}), \quad (1)$$

where $\mathcal{V}$ is the vocabulary, hard denotes explicit token reasoning, and soft denotes latent reasoning in continuous space. At each step, the routing policy ρ_θ over $\mathcal{D}$ first selects the reasoning mode, and the language policy π_θ over $\mathcal{V}$ is applied only when hard is chosen. Together, they define the full action distribution over $\mathcal{A}$, determining how the next reasoning unit u_t is constructed and appended to the context history.

3.2 Token-Wise Routing for Latent and Explicit Reasoning

As shown in Figure 1a, we introduce a lightweight action head on top of the LLM backbone to route the reasoning mode at each token step. Given the final hidden state, the action head predicts a binary routing action that determines whether the next reasoning unit is constructed from a discrete token embedding or a continuous latent vector.

The Routing Policy. Let $h_t \in \mathbb{R}^d$ denote the hidden state produced by the final transformer layer at step t. We instantiate the router as a lightweight linear projection head that directly maps the hidden state into a categorical distribution over the reasoning actions. The routing policy ρ_θ is parameterized as:

$$\rho_\theta(\cdot|h_t) = \text{Softmax}(\mathbf{W}_r h_t + \mathbf{b}_r) \quad (2)$$

where $\mathbf{W}_r \in \mathbb{R}^{2 \times d}$ and $\mathbf{b}_r \in \mathbb{R}^2$ are learnable parameters. During training, we sample the routing decision $d_t \sim \rho_\theta(\cdot \mid h_t)$ to encourage structural exploration. At inference time, the router supports both stochastic and deterministic routing strategies. We initialize the action-head bias $\mathbf{b}_r$ to b_0 to mildly favor hard routing, consistent with the model's preference, which we further discuss in Section 4.4 and Appendix B.

Hybrid State Transition. The routing decision determines how the next unit u_t is constructed. Specifically, if d_t selects explicit reasoning, the model appends the discrete token embedding $u_t = \mathbf{E}(v_t)$; otherwise, it constructs a latent unit by a sparse weighted sum over the top-k tokens:

$$u_t = \begin{cases} \mathbf{E}(v_t), & \text{if } d_t = \text{hard}, \\ \sum_{i \in \mathcal{K}_t} w_t^{(i)} \mathbf{E}(v^{(i)}), & \text{if } d_t = \text{soft}, \end{cases} \quad (3)$$

where $\mathcal{K}_t$ denotes the top-k token set and $w_t^{(i)}$ is normalized by the softmax over the corresponding logits. This hybrid routing is applied only during the thinking phase.

3.3 Action-Routing Policy Optimization

We optimize TARPO with an online group-relative policy optimization objective over hybrid reasoning trajectories. For each prompt, we sample a group of trajectories and assign each trajectory a scalar outcome reward based on the final generated answer. We normalize the rewards within each group and use the same group-relative advantage signal to optimize both the LLM backbone and the action head router.

Let r_i denote the reward of the i-th sampled trajectory in a group. The shared group-relative advantage is computed as:

$$\hat{A}_i = \frac{r_i - \mu_r}{\sigma_r + \epsilon}, \quad (4)$$

where μ_r and σ_r denote the mean and standard deviation of the sampled rewards within the group, respectively.

Given the generated tokens $y_{i,1:T}$ and routing decisions $d_{i,1:T}$, we jointly optimize the backbone policy and the routing policy. Here, $\mathcal{L}_{\text{tok}}^{(i)}$ denotes the token-generation objective of the LLM backbone for the i-th trajectory, $\mathcal{L}_{\text{act}}^{(i)}$ denotes the action-routing objective of the router, and $\mathcal{L}_{\text{KL}}^{(i)}$ denotes the KL regularization term. The overall objective averages over the sampled group:

$$\mathcal{L}_{\text{TARPO}} = \frac{1}{G} \sum_{i=1}^{G} \left[\mathcal{L}_{\text{tok}}^{(i)} + \lambda \mathcal{L}_{\text{act}}^{(i)} + \beta \mathcal{L}_{\text{KL}}^{(i)} \right], \quad (5)$$

where λ controls the contribution of the routing objective and β is the base coefficient for the KL penalty. Let $\delta_t = \rho_\theta(\text{Hard} \mid h_t)$ denote the probability of taking the hard path at step t:

$$\mathcal{L}_{\text{KL}}^{(i)} = \frac{1}{T} \sum_{t=1}^{T} \Big[\delta_t \, D_{\text{KL}}(\pi_\theta(\cdot \mid s_t) \,\|\, \pi_{\text{ref}}(\cdot \mid s_t))$$

$$+ \alpha \, D_{\text{KL}}(\rho_\theta(\cdot \mid h_t) \,\|\, \rho_{\text{ref}}(\cdot \mid h_t)) \Big], \quad (6)$$

where α controls the relative strength of the KL regularization applied to the action head. Setting $\alpha = 0$ removes the action KL entirely, which we analyze in Section 4.4 and Appendix B.

The token-generation and routing objectives are optimized using the shared advantage signal:

$$\mathcal{L}_{\text{tok}}^{(i)} = -\frac{1}{T_i} \sum_{t=1}^{T_i} \mathbf{1}_t \log \pi_\theta(v_{i,t} \mid s_{i,t}) \, \hat{A}_i, \quad (7)$$

$$\mathcal{L}_{\text{act}}^{(i)} = -\frac{1}{T_i} \sum_{t=1}^{T_i} \log \rho_\theta(d_{i,t} \mid h_{i,t}) \, \hat{A}_i, \quad (8)$$

where $\mathbf{1}_t = \mathbf{1}[d_{i,t} = \text{Hard}]$ indicates that the router selects the hard pattern at step t.

This objective jointly updates the LLM backbone and the action head router, encouraging successful reasoning trajectories while learning adaptive latent-explicit routing patterns.

4 Experiment

4.1 Experimental Settings

Training & Testing Settings. We conduct experiments primarily on three backbones including Qwen2.5-1.5B-Instruct, Qwen2.5-3B-Instruct, and Qwen2.5-7B-Instruct. We further provide supplementary experiments on Llama-3.1-8B-Instruct to evaluate the cross-architecture generalization of TARPO. For in-domain evaluation, models trained on GSM8K are evaluated on GSM8K, while models trained on MATH are evaluated on MATH, MATH500, AMC23, and OlympiadBench. For out-of-distribution (OOD) evaluation, we train on the DAPO-MATH-17k (Yu et al., 2026) dataset and evaluate on the scientific reasoning benchmarks GPQA-Diamond (Rein et al., 2023) and ARC-C (Clark et al., 2018), as well as the code generation benchmark HumanEval (Chen et al., 2021). We follow the overall training framework and implementation setup of HRPO (Yue et al., 2026). Detailed training configurations and generation settings are provided in Appendix A.

Baselines. We compare TARPO with both representative training-free and RL-based reasoning paradigms. For training-free baselines, we include: (1) **CoT**, standard Chain-of-Thought

Method	GSM8K		MATH		MATH500		AMC23		Olympiad		Average	
	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32
					Qwen2.5-1.5B-Instruct							
CoT	60.89	95.53	31.66	78.90	31.76	78.60	18.83	70.00	14.13	49.04	31.45	74.41
Pure Latent	60.53	65.50	25.29	37.20	26.51	38.60	15.86	20.00	12.21	17.33	28.08	35.73
Entropy-Routed	60.66	93.10	25.29	72.04	27.10	71.80	13.98	55.00	12.65	46.67	27.94	67.72
GRPO	69.04	96.66	47.82	81.22	48.56	81.20	**26.80**	77.50	16.42	**50.37**	41.73	77.39
HRPO	69.71	96.66	48.99	**82.34**	49.80	82.60	25.78	72.50	**16.51**	48.44	42.16	76.51
TARPO (Ours)	**70.76**	**96.97**	**49.71**	82.28	49.71	**83.40**	25.47	**80.00**	16.13	48.89	**42.36**	**78.31**
					Qwen2.5-3B-Instruct							
CoT	73.50	96.97	55.64	85.00	56.02	84.40	36.48	82.50	22.83	54.07	48.89	80.59
Pure Latent	73.84	78.92	55.45	59.70	56.70	60.20	**43.20**	45.00	**24.85**	28.00	50.81	54.36
Entropy-Routed	73.91	95.53	54.75	83.36	55.57	82.20	37.58	80.00	22.99	53.04	48.96	78.83
GRPO	82.55	**97.57**	59.86	84.72	**60.85**	84.40	38.67	87.50	23.58	54.07	53.10	81.65
HRPO	82.75	97.42	**59.97**	85.06	60.64	**85.00**	38.83	85.00	23.80	55.26	53.20	81.55
TARPO (Ours)	**83.23**	96.97	59.75	**85.20**	60.57	84.80	40.23	**90.00**	24.27	**57.04**	**53.61**	**82.80**
					Qwen2.5-7B-Instruct							
CoT	87.97	**97.73**	61.16	87.30	61.51	86.00	44.22	90.00	25.73	56.15	56.12	83.43
Pure Latent	88.40	90.90	56.78	68.66	59.50	70.80	48.52	60.00	27.55	34.52	56.15	64.98
Entropy-Routed	88.07	97.04	54.02	82.96	53.91	81.39	41.56	82.50	26.58	**56.74**	52.83	80.13
GRPO	89.87	97.42	70.05	88.02	69.86	**87.80**	51.72	87.50	**30.96**	53.78	62.49	82.90
HRPO	**90.13**	97.42	**70.25**	88.20	69.78	87.60	51.17	85.00	30.75	53.19	62.42	82.28
TARPO (Ours)	89.94	97.27	70.22	**88.22**	70.26	87.80	**53.52**	**95.00**	30.69	54.22	**62.92**	**84.50**

Table 1: Main results on the reasoning benchmarks. We compare our method with discrete baselines and prior latent reasoning methods across different base models. The best results overall are highlighted in bold. P@k denotes Pass@k accuracy.

Method	GSM8K		MATH500		AMC23	
	P@1	P@32	P@1	P@32	P@1	P@32
			Llama-3.1-8B-Instruct			
CoT	77.78	**96.82**	35.48	77.20	16.17	**77.50**
GRPO	82.98	**96.82**	45.77	81.80	21.56	70.00
TARPO	**84.25**	95.91	**47.65**	**83.20**	**22.97**	62.50

Table 2: Generalization performance on the Llama-3.1-8B-Instruct architecture. Models are trained on the MATH dataset.

Method	GSM8K			MATH500		
	Greedy	P@1	P@32	Greedy	P@1	P@32
CoT	75.82	73.50	96.97	56.60	56.02	84.40
GRPO	83.70	82.53	**97.73**	61.60	**60.85**	84.40
GRPO*	**84.00**	**83.00**	97.20	59.00	57.10	83.60
Soft Tokens*	82.90	81.90	95.40	54.70	54.60	80.30
TARPO	83.24	82.44	97.12	**62.00**	60.57	**84.80**

Table 3: Comparison with the reparameterization-based method on Qwen2.5-3B-Instruct. We train on the same MATH dataset. Results marked with * are taken from Butt et al. (2025).

prompting; (2) **Pure Latent**, a basic latent reasoning mechanism in which all reasoning steps are performed with soft tokens; and (3) **Entropy-Routed**, a hybrid latent reasoning strategy that uses token entropy heuristics to trigger mode switching, inspired by prior entropy-guided routing methods (Shi et al., 2025). Specifically, at each token step, if the token entropy exceeds a predefined threshold (set to 0.5 in our implementation), the next step is constructed using a soft token. For RL-based baselines, we compare against: (4) **GRPO** (Shao et al., 2024) as a representative discrete RL baseline; and (5) **HRPO** (Yue et al., 2026) as a representative hybrid latent RL baseline, where a gating mechanism fuses discrete token embeddings and continuous representations at each step. We additionally include partial comparisons with reparameterization-based latent RL methods, such as **Soft Tokens** (Butt et al., 2025).

Metrics. We report pass@1 and pass@32 as the primary evaluation metrics, where pass@1 is averaged over 32 sampled generations. For OOD benchmarks, we additionally report the average number of generated tokens, accounting for both discrete and latent tokens in TARPO. Additional detailed statistics are provided in Appendix C.

Method	GPQA-Diamond			ARC-C			HumanEval			Average		
	P@1	P@32	#Tok	P@1	P@32	#Tok	P@1	P@32	#Tok	P@1	P@32	#Tok
CoT	26.83	**92.93**	410.6	74.05	98.21	106.2	59.68	90.24	271.4	53.52	**93.79**	262.7
Pure Latent	27.26	37.37	405.6	70.57	78.16	97.1	60.19	82.32	261.4	52.67	65.95	254.7
Entropy-Routed	28.30	90.91	373.2	71.09	96.25	95.4	58.31	90.24	260.5	52.57	92.47	243.0
GRPO	28.03	83.33	608.5	74.78	98.12	272.4	58.86	**92.07**	355.6	53.89	91.17	412.2
HRPO	27.51	88.38	603.3	**75.06**	97.44	277.8	59.51	90.85	340.5	54.03	92.22	407.2
TARPO	**28.41**	90.91	**568.3**	74.01	**98.89**	189.4	**63.62**	88.41	**256.1**	**55.35**	92.74	**337.9**

Table 4: Out-of-distribution (OOD) generalization evaluation results of Qwen2.5-3B-Instruct. We report pass@1, pass@32, and generated tokens on GPQA-Diamond, ARC-C, and HumanEval datasets.

Method	GSM8K		MATH		MATH500		AMC23		Olympiad		Average	
	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32	P@1	P@32
Qwen2.5-1.5B-Instruct												
GRPO	69.04	96.66	47.82	81.22	48.56	81.20	**26.80**	77.50	16.42	**50.37**	41.73	77.39
w/ Pure Latent	**71.21**	71.57	48.16	48.98	48.97	49.20	17.50	17.50	**16.56**	17.63	40.48	40.98
w/ Entropy Routing	70.23	94.24	47.21	78.54	48.04	79.20	24.53	70.00	16.13	46.37	41.23	73.67
TARPO	70.76	**96.97**	**49.71**	**82.28**	**49.71**	**83.40**	25.47	**80.00**	16.13	48.89	**42.36**	**78.31**
Qwen2.5-3B-Instruct												
GRPO	82.55	**97.57**	**59.86**	84.72	**60.85**	84.40	38.67	87.50	23.58	54.07	53.10	81.65
w/ Pure Latent	82.64	83.40	59.44	60.48	60.65	61.60	39.69	40.00	23.66	24.89	53.22	54.07
w/ Entropy Routing	82.94	95.98	59.53	83.72	60.64	83.80	38.67	77.50	24.25	52.44	53.21	78.69
TARPO	**83.23**	96.97	59.75	**85.20**	60.57	**84.80**	**40.23**	**90.00**	**24.27**	**57.04**	**53.61**	**82.80**

Table 5: Ablation study on the reasoning benchmarks. We compare TARPO against GRPO and two GRPO-based ablated variants with different latent inference strategies: *w/ Pure Latent*, which performs all reasoning steps in latent space, and *w/ Entropy Routing*, which switches to latent space based on a fixed entropy threshold.

4.2 Results

In-Domain Performance. We report the in-domain results in Table 1. Overall, TARPO surpasses both training-free baselines and RL-based methods across the three Qwen2.5 backbones. Averaged over the three scales, TARPO improves GRPO by 0.52% and 1.22% in Pass@1 and Pass@32, respectively, and outperforms HRPO by 0.37% and 1.76%. These results confirm that incorporating token-wise action routing provides a more effective and stable optimization landscape.

OOD Generalization. We evaluate the Qwen2.5-3B-Instruct model on GPQA-Diamond, ARC-C, and HumanEval for out-of-distribution generalization. As shown in Table 4, TARPO achieves the highest average Pass@1 (55.35%), with a notable 4.76% improvement over GRPO on HumanEval. Furthermore, TARPO significantly improves token efficiency, reducing the average generated tokens to 337.9 compared to over 400 for baseline RL methods, thereby maintaining concise reasoning trajectories.

Cross-Architecture Generalization. We further evaluate TARPO on the Llama-3.1-8B-Instruct backbone to assess its cross-architecture robustness. As shown in Table 2, TARPO achieves the best Pass@1 across all three benchmarks, outperforming GRPO by 1.27%, 1.88%, and 1.41% on GSM8K, MATH500, and AMC23 respectively. TARPO also attains the highest Pass@32 on MATH500, indicating strong generalization across backbones.

Comparison with Reparameterization-Based Methods. We additionally conduct a partial comparison with Soft Tokens (Butt et al., 2025), a reparameterization-based latent reasoning RL baseline. As shown in Table 3, TARPO achieves strong overall performance, improving MATH500 Pass@32 from 80.30% to 84.80%.

4.3 Ablation Study

To evaluate the effectiveness of the learnable action-routing mechanism, we compare TARPO against GRPO and GRPO-based ablated variants with different latent inference strategies: (1) **w/ Pure Latent**, where all reasoning steps are per-

(a) Training curves of Qwen2.5-1.5B-Instruct on MATH.

(b) Training curves of Qwen2.5-7B-Instruct on GSM8K.

Figure 2: Comparison of training curves between TARPO and baselines (GRPO, HRPO) across different model scales and datasets. From left to right, the panels display Training Entropy, Training Tokens (counting both hard and soft tokens for TARPO), and Training Rewards.

formed in the continuous latent space using soft tokens; and (2) **w/ Entropy Routing**, which switches from discrete tokens to latent reasoning only when the current token entropy exceeds a pre-defined threshold (0.5 in our implementation).

As shown in Table 5, TARPO consistently out-performs both ablated variants. For Qwen2.5-3B-Instruct, TARPO achieves the highest average Pass@1 of 53.61% and Pass@32 of 82.80%. Since soft-token reasoning is inherently determin-istic, **w/ Pure Latent** can only rely on the fi-nal answer generation stage for stochastic explo-ration, which leads to a substantial drop in aver-age Pass@32 to 54.07%. In contrast, **w/ Entropy Routing** depends on a fixed heuristic trigger, mak-ing its switching behavior less adaptive. These re-sults indicate that a learnable routing policy pro-vides a more adaptive mechanism for balancing discrete and latent reasoning.

4.4 Training Dynamics and Analysis

Entropy and Completion Length. As shown in Figure 2, we track token entropy, completion length, and rewards during optimization to under-stand the training dynamics. On the 1.5B model trained on MATH in Figure 2a, TARPO consis-tently produces shorter completions while achiev-ing rewards comparable to HRPO and slightly higher than GRPO, indicating better token effi-ciency at similar performance. On the 7B model trained on GSM8K in Figure 2b, HRPO exhibits an entropy rise in the later training stage, whereas TARPO largely follows the GRPO trajectory but maintains a moderately higher entropy level near convergence, suggesting a better balance between exploration and efficiency.

Action Head Bias and KL. To further analyze the internal dynamics of the learnable routing mechanism, we investigate the impact of the ac-tion head initial bias (b_0) and the action KL penalty using Qwen2.5-3B-Instruct on the MATH dataset. Specifically, under the penalty-free setting (w/o Action KL), Figure 3a and 3b show that differ-ent initial bias settings result in different soft to-ken ratios and reward dynamics during training, indicating that the router actively adapts its reason-ing preference under RL optimization. Figure 3c shows the effect of the action KL penalty under the initial bias setting of $b_0 = [2.2, 0]$, comparing the default ($\alpha = 1$, w/ Action KL) and penalty-free ($\alpha = 0$, w/o Action KL) baselines. The ex-perimental results show that, with action KL regu-

(a) Impact of Initial Bias on Soft Ratio (b) Impact of Initial Bias on Reward (c) Effect of Action KL on Entropy

Figure 3: Analysis of TARPO action head bias initialization and KL (Qwen2.5-3B-Instruct on MATH). (a) and (b) show the impact of the initial bias (b_0) on the soft token ratio and training reward. (c) illustrates the effect of the action KL penalty on token entropy.

Figure 4: A case study on a MATH500 problem. (a) GRPO outputs with token entropy highlighted in blue. (b) TARPO outputs with soft probability highlighted in color.

larization, the token entropy of TARPO follows a controlled decreasing trajectory and converges to a slightly higher level than GRPO.

Soft Token Selection in the Case Study. As shown in Figure 4, we present a MATH500 case study to illustrate TARPO's soft-token selection during reasoning. Since the selected soft tokens are not human-readable, we display their corresponding hard-token placeholders for visualization. In this case, GRPO makes an incorrect simplification at "2(x−5)=4", whereas TARPO correctly preserves the cross-multiplication step "2(x−5)=4\cdot3" and reaches the correct solution. The highlighted tokens further show that GRPO's high-entropy positions are mainly structural transition words such as "will" and "Now we need", while TARPO assigns higher soft probability to key mathematical tokens, such as equations and operators.

5 Conclusion

In this paper, we presented TARPO, a pure reinforcement learning framework that enables token-wise latent-explicit reasoning through a lightweight action-routing policy. Following the GRPO training paradigm, TARPO jointly optimizes the routing head and the LLM backbone with a shared advantage signal, allowing the model to adaptively switch between hard token generation and soft latent reasoning without relying on heuristic rules or supervised initialization. Extensive experiments demonstrate that TARPO consistently improves reasoning performance over existing latent reasoning RL methods, while also achieving better token efficiency and strong generalization on out-of-distribution benchmarks.

Limitations

While TARPO demonstrates consistent improvements over existing baselines, we discuss two primary limitations of the current study.

First, regarding the experimental scope, our empirical evaluation is constrained by available computational resources, limiting our exploration to models up to 8B parameters. Although we extensively evaluated TARPO on the Qwen2.5 series and validated cross-architecture generalization on Llama-3.1-8B-Instruct, the largest backbone explored in this work contains 8B parameters. Whether TARPO maintains its effectiveness and training stability at substantially larger scales (e.g., 30B parameters or beyond) remains an open question.

Second, from a methodological perspective, the continuous latent representations in TARPO are constructed via a top-k probability-weighted mixture of token embeddings. While the action head router successfully introduces token-wise structural exploration over reasoning modes (discrete vs. continuous), the generation process within the soft mode itself remains deterministic. A promising direction for future work is to integrate TARPO with reparameterization techniques, such as applying the Gumbel-Softmax trick or injecting Gaussian noise into the continuous representations, to complement our structural routing with representation-level exploration.

References

Natasha Butt, Ariel Kwiatkowski, Ismail Labiad, Julia Kempe, and Yann Ollivier. 2025. Soft tokens, hard truths. *arXiv preprint arXiv:2509.19170*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Xinghao Chen, Anhao Zhao, Heming Xia, Xuan Lu, Hanlin Wang, Yanjun Chen, Wei Zhang, Jian Wang, Wenjie Li, and Xiaoyu Shen. 2025. Reasoning beyond language: A comprehensive survey on latent chain-of-thought reasoning. *arXiv preprint arXiv:2505.16782*.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*.

Jingcheng Deng, Zihao Wei, Liang Pang, Junhong Wu, Shicheng Xu, Zenghao Duan, and Huawei Shen. 2026. Latent-grpo: Group relative policy optimization for latent reasoning. *arXiv preprint arXiv:2604.27998*.

Renyu Fu and Guibo Luo. 2026. Selar: Selective latent reasoning in large language models. *arXiv preprint arXiv:2604.08299*.

Tianyu Fu, Yichen You, Zekai Chen, Guohao Dai, Huazhong Yang, and Yu Wang. 2025. Think-at-hard: Selective latent iterations to improve reasoning language models. *arXiv preprint arXiv:2511.08577*.

Jonas Geiping, Sean McLeish, Neel Jain, John Kirchenbauer, Siddharth Singh, Brian Bartoldson, Bhavya Kailkhura, Abhinav Bhatele, and Tom Goldstein. 2026. Scaling up test-time compute with latent reasoning: A recurrent depth approach. *Advances in Neural Information Processing Systems*, 38:41340–41391.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Alexander Gurung, Nikolay Malkin, and Mirella Lapata. 2025. Lightweight latent reasoning for narrative tasks. *arXiv preprint arXiv:2512.02240*.

Shibo Hao, Sainbayar Sukhbaatar, DiJia Su, Xian Li, Zhiting Hu, Jason Weston, and Yuandong Tian. 2024. Training large language models to reason in a continuous latent space. *arXiv preprint arXiv:2412.06769*.

Juno Kim, Denny Wu, Jason D Lee, and Taiji Suzuki. 2025. Metastable dynamics of chain-of-thought reasoning: Provable benefits of search, rl and distillation. In *International Conference on Machine Learning*, pages 30791–30825. PMLR.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Fangrui Lv, Lei Wang, Ruixin Hong, Yong Du, Xiangyu Wu, Tingting Gao, Guorui Zhou, and Changshui Zhang. 2026. Beyond tokens: Dynamic latent reasoning via semantic residual refinement. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 32383–32391.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2023. Gpqa: A graduate-level google-proof q&a benchmark. *arXiv preprint arXiv:2311.12022*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Xuan Shen, Yizhou Wang, Yufa Zhou, Xiangxi Shi, Pu Zhao, Yanzhi Wang, and Jiuxiang Gu. 2025. Efficient reasoning with hidden thinking. *arXiv preprint arXiv:2501.19201*.

Dachuan Shi, Abedelkadir Asi, Keying Li, Xiangchi Yuan, Leyan Pan, Wenke Lee, and Wen Xiao. 2025. Swireasoning: Switch-thinking in latent and explicit for pareto-superior reasoning llms. *arXiv preprint arXiv:2510.05069*.

DiJia Su, Hanlin Zhu, Yingchen Xu, Jiantao Jiao, Yuandong Tian, and Qinqing Zheng. 2025. Token assorted: Mixing latent and text tokens for improved language model reasoning. *arXiv preprint arXiv:2502.03275*.

Wenhui Tan, Jiaze Li, Jianzhong Ju, Zhenbo Luo, Ruihua Song, and Jian Luan. 2026. Think silently, think fast: Dynamic latent compression of llm reasoning chains. *Advances in Neural Information Processing Systems*, 38:4646–4668.

Yao Tang, Li Dong, Yaru Hao, Qingxiu Dong, Furu Wei, and Jiatao Gu. 2026. Multiplex thinking: Reasoning via token-wise branch-and-merge. *arXiv preprint arXiv:2601.08808*.

Xiaoqiang Wang, Suyuchen Wang, Yun Zhu, and Bang Liu. 2026. System-1.5 reasoning: Traversal in language and latent spaces with dynamic shortcuts. *Advances in Neural Information Processing Systems*, 38:65328–65351.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Junhong Wu, Jinliang Lu, Zixuan Ren, Gangqiang Hu, Zhi Wu, Dai Dai, and Hua Wu. 2025. Llms are single-threaded reasoners: Demystifying the working mechanism of soft thinking. *arXiv preprint arXiv:2508.03440*.

Xin Xu, Tong Yu, Xiang Chen, Haoliang Wang, Julian McAuley, and Saayan Mitra. 2026. Thinkrouter: Efficient reasoning via routing thinking between latent and discrete spaces. *arXiv preprint arXiv:2602.11683*.

Yige Xu, Xu Guo, Zhiwei Zeng, and Chunyan Miao. 2025. Softcot: Soft chain-of-thought for efficient reasoning with llms. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 23336–23351.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, and 1 others. 2026. Dapo: An open-source llm reinforcement learning system at scale. *Advances in Neural Information Processing Systems*, 38:113222–113244.

Zhenrui Yue, Bowen Jin, Huimin Zeng, Honglei Zhuang, Zhen Qin, Jinsung Yoon, Lanyu Shang, Jiawei Han, and Dong Wang. 2026. Hybrid latent reasoning via reinforcement learning. *Advances in Neural Information Processing Systems*, 38:5501–5530.

Yang Zhang, Wenxin Xu, Xiaoyan Zhao, Wenjie Wang, Fuli Feng, Xiangnan He, and Tat-Seng Chua. 2025. Reinforced latent reasoning for llm-based recommendation. *arXiv preprint arXiv:2505.19092*.

Zhen Zhang, Xuehai He, Weixiang Yan, Ao Shen, Chenyang Zhao, and Xin Wang. 2026. Soft thinking: Unlocking the reasoning potential of llms in continuous concept space. *Advances in Neural Information Processing Systems*, 38:168990–169012.

Yiran Zhao, Yuhui Xu, Doyen Sahoo, Caiming Xiong, and Junnan Li. 2026. Learning to reason over continuous tokens with reinforcement learning. In *The Fourteenth International Conference on Learning Representations*.

Zhi Zheng and Wee Sun Lee. 2025. Soft-grpo: Surpassing discrete-token llm reinforcement learning via gumbel-reparameterized soft-thinking policy optimization. *arXiv preprint arXiv:2511.06411*.

Yuyan Zhou, Jiarui Yu, Hande Dong, Zhezheng Hao, Hong Wang, Jianqing Zhang, and Qiang Lin. 2026. Lepo: Latent reasoning policy optimization for large language models. *arXiv e-prints*, pages arXiv–2604.

Rui-Jie Zhu, Tianhao Peng, Tianhao Cheng, Xingwei Qu, Jinfa Huang, Dawei Zhu, Hao Wang, Kaiwen Xue, Xuanliang Zhang, Yong Shan, Tianle Cai, Taylor Kergan, Assel Kembay, Andrew Smith, Chenghua Lin, Binh Nguyen, Yuqi Pan, Yuhong Chou, Zefan Cai, and 14 others. 2025. A survey on latent reasoning. *Preprint*, arXiv:2507.06203.

A Implementation Details

For fair comparison, we follow the training framework and implementation setup of HRPO (Yue et al., 2026), which is built upon TRL and the Unsloth acceleration library[1]. All models are trained for 1 epoch using the 8-bit AdamW optimizer with a cosine learning rate scheduler and a 10% warmup ratio. All experiments are conducted on a single NVIDIA H800 80GB GPU. Leveraging the Unsloth acceleration framework, training Llama-3.1-8B-Instruct on MATH requires approximately 44 hours.

Hyperparameter	Value
Algorithm	TARPO
Epochs	1
Optimizer	AdamW 8bit
Optimizer Momentum β_1, β_2	0.9, 0.99
Weight Decay	0.1
Learning Rate (LLM)	5e-6 / 2e-6
Learning Rate (Action Head)	1e-4 / 2e-6
TARPO Token KL β	0.005
TARPO Action KL α	1.0
Action Bias b_0	2.2 / 4.6
Action Temperature	1.0
Temperature	0.5
Group Size g	4 / 8
Soft Token Top-k	30
Max Gradient Norm	0.1
Total Train Batch Size	32 / 64
LR Scheduler	Cosine with Warmup
Warmup Ratio	0.1
Precision (WA)	BF16-mixed
LoRA Settings	
LoRA Modules	query, key, value, dense
LoRA Rank r	32
LoRA α	64

Table 6: Hyperparameter settings of TARPO.

Detailed hyperparameter settings of TARPO are summarized in Table 6. In addition, several hyperparameters are adjusted according to the dataset and backbone scale. Specifically, the rollout group size g is set to 4 for GSM8K and 8 for MATH and DAPO-MATH-17k. For the Qwen-based models, the backbone learning rate is set to 5e-6, while the action head learning rate is set to 1e-4. For the Llama-3.1-8B-Instruct model, we apply a smaller learning rate of 2e-6 for both the backbone and the action head. The maximum prompt and completion lengths used during training and testing are summarized in Table 7. For GSM8K, MATH, and MATH500, we follow the evaluation length settings used in HRPO (Yue et al., 2026). For

---

[1] https://github.com/unslothai/unsloth

---

additional benchmarks not evaluated in HRPO, we adopt task-specific settings. In particular, when evaluating Llama-3.1-8B-Instruct, we set the prompt and completion lengths to 512 and 1024 for GSM8K, and 2048 and 2048 for MATH500.

Phase	Dataset	Prompt	Completion
Training	GSM8K	1024	1024
	MATH	1024	1024
	DAPO-MATH-17k	1024	2048
Testing	GSM8K	512	512
	MATH	512	1024
	MATH500	512	1024
	AMC23	2048	2048
	OlympiadBench	4096	4096
	GPQA-Diamond	1024	1024
	ARC-C	1024	1024
	HumanEval	2048	2048

Table 7: Maximum prompt and completion lengths across different datasets for training and testing phases.

We present the exact prompts utilized within the TARPO framework to facilitate reproducibility. As with our experimental configuration, these templates follow HRPO (Yue et al., 2026). Specifically, Figure 5 illustrates the prompt template applied to all mathematical reasoning tasks, including GSM8K, MATH, MATH500, AMC23, OlympiadBench, and DAPO-MATH-17k. Additionally, we provide the specific prompts for our out-of-distribution evaluations, with GPQA-Diamond and ARC-C detailed in Figure 6, and HumanEval in Figure 7.

B Routing Hyperparameter Analysis

We conduct a systematic analysis of two routing hyperparameters in TARPO: the initial action-head bias (b_0) and the action KL regularization coefficient (α).

Figures 8 and 9 show the training entropy, token usage, and reward dynamics under different configurations on GSM8K. A stronger hard-routing bias ($b_0 = [4.6, 0]$) results in lower soft-token usage and slower entropy decay, while a weaker bias ($b_0 = [2.2, 0]$) encourages more aggressive latent exploration during early training. Enabling action KL regularization stabilizes the routing dynamics and mitigates premature collapse to degenerate routing behaviors. In contrast, removing action KL leads to more unstable entropy and token-usage trajectories in several settings.

Tables 8 and 9 further show that action KL generally improves training stability and down-

> **Example Prompt for Mathematical Reasoning**
>
> <|im_start|>system
> A conversation between User and Assistant. The user asks a question, and the assistant solves it. The assistant first thinks about the reasoning process in the mind and then provides the user with the answer. The final answer is provided after the #### tag, i.e., {reasoning process} #### {answer}.<|im_end|>
> <|im_start|>user
> A robe takes 2 bolts of blue fiber and half that much white fiber. How many bolts in total does it take?<|im_end|>
> <|im_start|>assistant

Figure 5: Example Prompt for Mathematical Reasoning in TARPO.

stream performance, particularly under weaker hard-routing initialization. The 7B model is relatively insensitive to the choice of b_0, whereas the 1.5B model exhibits slightly higher sensitivity. Based on these observations, we use $b_0 = [2.2, 0]$ with action KL for 3B-scale experiments and $b_0 = [4.6, 0]$ for the remaining scales.

C Additional Experimental Statistics

We provide additional statistical results to complement the main evaluation in Section 4. Specifically, we report Maj@32 (M@32), i.e., the majority-voting accuracy over 32 sampled generations. A question is counted as correct if the most frequent generated answer among the 32 samples matches the ground truth.

In addition, we report the standard deviation (SD) and 95% confidence intervals (CIs) computed over question-level Avg@32 accuracies, where Avg@32 denotes the fraction of correct samples among 32 generations for each question. The confidence intervals are computed using normal approximation.

In-Domain Benchmarks. Tables 11 and 12 report M@32 together with the SD and 95% CIs of question-level Avg@32 accuracies across all in-domain reasoning benchmarks for three Qwen2.5 backbones. TARPO consistently achieves M@32 scores comparable to or higher than those of GRPO and HRPO across all scales, while maintaining similar or lower variability in Avg@32 accuracies. The confidence intervals of RL-trained methods (GRPO, HRPO, TARPO) are generally well separated from those of training-free methods (CoT and Entropy-Routed), suggesting that the ob-

served improvements are unlikely to be explained solely by sampling variance. The Pure Latent method consistently exhibits the highest variability in question-level Avg@32 accuracies across benchmarks. This observation is consistent with our analysis in Section 4.3: since stochasticity is concentrated mainly at the final answer-generation stage, the model exhibits larger variance across sampled generations, which also leads to substantially degraded M@32 performance.

Out-of-Distribution Benchmarks. Table 13 extends the OOD evaluation in Table 4 by reporting M@32 together with the SD and 95% CIs of Avg@32 accuracies on GPQA-Diamond, ARC-C, and HumanEval for Qwen2.5-3B-Instruct. On the HumanEval benchmark, TARPO achieves the highest M@32 of 61.59, indicating that adaptive routing also performs well under majority-voting evaluation on code generation tasks.

Cross-Architecture Generalization. Table 14 reports M@32 together with the SD and 95% CIs of Avg@32 accuracies for Llama-3.1-8B-Instruct on GSM8K, MATH500, and AMC23. TARPO outperforms GRPO in M@32 across all three benchmarks. Moreover, the confidence intervals on MATH500 and AMC23 are well separated, supporting the cross-architecture robustness conclusion discussed in Section 4.2.

D Additional Training Curves

To complement the training dynamics presented in Section 4.4, we provide additional training curves for the backbone and dataset combinations not shown in the main paper. All figures report train-

> **Example Prompt for GPQA-Diamond and ARC-C**
>
> <|im_start|>system
> A conversation between User and Assistant. The user asks a multiple-choice question, and the assistant solves it. The assistant first thinks about the reasoning process in the mind and then provides the user with the answer. The final answer is provided after the #### tag, and MUST be exactly one of the option letters (A, B, C, or D). i.e., {reasoning process} #### {option letter}.<|im_end|>
> <|im_start|>user
> Question: A class plans an investigation to see which brand of light bulb lasts the longest. Which of these steps should come first?
>
> Options:
> A. Repeat the investigation.
> B. Write a report of the results.
> C. Make a table for recording data.
> D. Make daily observations of the light bulbs.<|im_end|>
> <|im_start|>assistant

Figure 6: Example Prompt for GPQA-Diamond and ARC-C in TARPO.

Bias	Act-KL	GSM8K			MATH			MATH500			AMC23			OlympiadBench		
		P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32
							Qwen2.5-3B-Instruct									
[4.6, 0]	✗	82.07	97.19	89.69	60.27	85.21	70.43	61.01	86.40	71.40	38.91	85.00	57.50	23.98	54.37	35.11
[4.6, 0]	✓	82.91	97.19	90.22	60.06	85.10	69.96	60.51	86.20	70.80	38.98	82.50	55.00	23.85	54.67	35.56
[2.2, 0]	✗	82.75	97.12	89.84	59.46	85.60	70.70	60.22	86.40	69.80	38.75	85.00	57.50			
[2.2, 0]	✓	83.23	96.97	89.99	59.75	85.20	70.18	60.57	84.80	69.20	40.23	90.00	52.50	24.27	57.04	34.96

Table 8: Ablation of Action Head Bias and Action KL in TARPO on In-Domain Benchmarks.

ing entropy, training tokens, and training rewards across optimization steps. Training tokens include both discrete and latent tokens in TARPO.

As shown in Figures 10, 11, and 12, TARPO exhibits consistent training behavior across these remaining backbone-dataset combinations. On Qwen2.5-7B-Instruct trained on MATH, TARPO consistently produces the shortest completion lengths throughout training while maintaining rewards comparable to HRPO and GRPO. This is consistent with the token-efficiency advantage observed at the 1.5B scale in the main paper. The entropy trajectories of the three methods also remain closely aligned, suggesting that the action-routing mechanism does not destabilize optimization at larger model scales. On Qwen2.5-3B-Instruct trained on DAPO-MATH-17k, TARPO similarly achieves competitive reward convergence with

lower token usage than the baselines. On Llama-3.1-8B-Instruct trained on MATH, TARPO maintains higher training entropy than GRPO while achieving higher rewards and shorter completions at convergence, suggesting that the routing mechanism preserves effective exploration during training.

E Licenses

For base LLMs, datasets, and frameworks, we list their licenses in Table 15.

Figure 7: Example Prompt for HumanEval in TARPO.

Bias	Act-KL	GSM8K			MATH			MATH500			AMC23			OlympiadBench		
		P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32	P@1	P@32	M@32
								Qwen2.5-7B-Instruct								
$[4.6, 0]$	✓	89.92	97.27	93.18	70.22	88.22	77.04	70.26	87.80	76.20	53.52	95.00	65.00	30.69	54.22	43.11
$[2.2, 0]$	✓	89.82	97.50	93.18	69.93	88.28	76.98	69.91	88.20	77.60	52.03	90.00	62.50	30.56	54.22	42.07
								Qwen2.5-1.5B-Instruct								
$[4.6, 0]$	✓	69.96	96.59	83.09	49.71	82.28	63.04	49.71	83.40	64.20	23.98	75.00	40.00	16.13	48.89	26.07
$[2.2, 0]$	✓	68.65	96.97	82.41	47.58	81.80	61.06	48.45	83.60	61.60	22.66	72.50	37.50			

Table 9: In-Domain Ablation of Action Head Bias in TARPO with Action KL Enabled.

(a) Training Entropy. (b) Training Tokens. (c) Training Rewards.

Figure 8: Effect of action head initial bias (b_0) and action KL regularization on Qwen2.5-7B-Instruct trained on GSM8K, under four configurations combining two bias settings ($b_0 = [2.2, 0]$ and $b_0 = [4.6, 0]$) with and without action KL penalty.

| (a) Training Entropy. | (b) Training Tokens. | (c) Training Rewards. |

Figure 9: Effect of action head initial bias (b_0) and action KL regularization on Qwen2.5-3B-Instruct trained on GSM8K.

Bias	Act-KL	GPQA-Diamond				ARC-C				HumanEval			
		P@1	P@32	M@32	#Tok	P@1	P@32	M@32	#Tok	P@1	P@32	M@32	#Tok
Qwen2.5-3B-Instruct													
$[4.6, 0]$	×	28.09	88.38	30.30	532.3	74.01	98.89	84.04	189.4	60.25	89.63	55.49	301.7
$[4.6, 0]$	✓	28.41	90.91	29.29	568.3	74.55	97.87	85.49	213.7	63.62	88.41	61.59	256.1

Table 10: OOD effect of Action KL in TARPO under fixed bias initialization.

| (a) Training Entropy. | (b) Training Tokens. | (c) Training Rewards. |

Figure 10: Training curves of Qwen2.5-3B-Instruct on DAPO-MATH-17k. From left to right: Training Entropy, Training Tokens (counting both hard and soft tokens for TARPO), and Training Rewards.

| (a) Training Entropy. | (b) Training Tokens. | (c) Training Rewards. |

Figure 11: Training curves of Qwen2.5-7B-Instruct on MATH.

Method	GSM8K		MATH		MATH500		AMC23		Olympiad	
	M@32	SD	M@32	SD	M@32	SD	M@32	SD	M@32	SD
Qwen2.5-1.5B-Instruct										
CoT	74.53	0.344	51.42	0.303	49.60	0.309	**42.50**	0.218	24.59	0.241
Pure Latent	62.02	0.470	27.96	0.396	29.20	0.406	17.50	0.353	14.22	0.311
Entropy-Routed	68.01	0.376	40.78	0.294	41.00	0.311	30.00	0.230	22.81	0.226
GRPO	83.09	0.333	61.72	0.394	63.00	0.389	**42.50**	0.296	26.52	0.277
HRPO	83.17	0.331	61.88	0.395	61.40	0.394	**42.50**	0.288	**27.70**	0.280
TARPO (Ours)	**84.69**	0.325	**63.04**	0.399	**64.20**	0.397	**42.50**	0.286	26.07	0.279
Qwen2.5-3B-Instruct										
CoT	88.40	0.288	70.40	0.383	71.00	0.383	50.00	0.349	34.67	0.335
Pure Latent	76.27	0.414	57.00	0.482	57.40	0.483	45.00	0.487	28.74	0.424
Entropy-Routed	81.43	0.329	66.42	0.397	67.00	0.401	**52.50**	0.348	33.48	0.340
GRPO	**90.22**	0.285	71.10	0.403	**71.20**	0.404	**52.50**	0.354	35.41	0.341
HRPO	89.76	0.286	**70.70**	0.403	69.80	0.401	**52.50**	0.352	**37.04**	0.342
TARPO (Ours)	89.99	0.286	70.18	0.403	69.20	0.406	**52.50**	0.357	34.96	0.345
Qwen2.5-7B-Instruct										
CoT	92.65	0.243	74.44	0.376	73.80	0.379	62.50	0.349	**43.85**	0.331
Pure Latent	89.92	0.307	66.12	0.444	68.20	0.440	60.00	0.453	35.85	0.421
Entropy-Routed	91.58	0.259	67.50	0.390	65.35	0.399	57.50	0.358	39.85	0.352
GRPO	**93.33**	0.240	76.94	0.391	76.00	0.394	62.50	0.383	42.96	0.398
HRPO	93.18	0.238	76.74	0.391	76.00	0.395	62.50	0.389	42.22	0.397
TARPO (Ours)	93.03	0.241	**77.04**	0.391	**76.20**	0.393	**65.00**	0.370	43.11	0.393

Table 11: Detailed performance statistics including Maj@32 (M@32, majority voting accuracy over 32 samples) and Standard Deviation (SD) on in-domain reasoning benchmarks across the Qwen2.5-Instruct model family (1.5B, 3B, and 7B). The best Maj@32 results for each model scale are highlighted in bold.

(a) Training Entropy.   (b) Training Tokens.   (c) Training Rewards.

Figure 12: Training curves of Llama-3.1-8B-Instruct on MATH.

Method	GSM8K	MATH	MATH500	AMC23	Olympiad
Qwen2.5-1.5B-Instruct					
CoT	[59.03, 62.74]	[30.82, 32.50]	[29.05, 34.46]	[12.09, 25.57]	[12.31, 15.95]
Pure Latent	[57.99, 63.06]	[24.20, 26.39]	[22.95, 30.07]	[4.93, 26.79]	[9.86, 14.56]
Entropy-Routed	[58.63, 62.69]	[25.29, 26.92]	[24.37, 29.83]	[6.86, 21.10]	[10.95, 14.36]
GRPO	[67.24, 70.83]	[46.73, 48.92]	[45.16, 51.97]	[17.61, 35.98]	[14.33, 18.50]
HRPO	[67.93, 71.50]	[47.89, 50.09]	[46.35, 53.25]	[16.85, 34.72]	[14.40, 18.63]
TARPO (Ours)	[69.01, 72.52]	[48.61, 50.82]	[46.23, 53.18]	[15.11, 32.86]	[14.03, 18.23]
Qwen2.5-3B-Instruct					
CoT	[71.94, 75.05]	[54.58, 56.70]	[52.66, 59.37]	[25.67, 47.30]	[20.30, 25.35]
Pure Latent	[71.61, 76.08]	[54.11, 56.79]	[52.46, 60.94]	[28.11, 58.30]	[21.65, 28.04]
Entropy-Routed	[72.13, 75.69]	[53.65, 55.85]	[52.06, 59.09]	[26.80, 48.36]	[20.43, 25.55]
GRPO	[81.01, 84.09]	[58.74, 60.97]	[57.31, 64.39]	[27.70, 49.65]	[21.01, 26.15]
HRPO	[81.20, 84.29]	[58.86, 61.09]	[57.12, 64.15]	[27.93, 49.72]	[21.22, 26.37]
TARPO (Ours)	[81.69, 84.78]	[58.64, 60.87]	[57.01, 64.13]	[29.16, 51.31]	[21.67, 26.87]
Qwen2.5-7B-Instruct					
CoT	[86.66, 89.28]	[60.12, 62.20]	[58.19, 64.84]	[33.41, 55.03]	[23.24, 28.23]
Pure Latent	[86.75, 90.05]	[55.55, 58.01]	[55.64, 63.36]	[34.48, 62.55]	[24.38, 30.73]
Entropy-Routed	[86.67, 89.46]	[52.94, 55.10]	[50.43, 57.39]	[30.47, 52.65]	[23.92, 29.24]
GRPO	[88.57, 91.17]	[68.96, 71.13]	[66.40, 73.31]	[39.84, 63.60]	[27.96, 33.97]
HRPO	[88.85, 91.42]	[69.17, 71.33]	[66.32, 73.24]	[39.11, 63.23]	[27.75, 33.74]
TARPO (Ours)	[88.64, 91.24]	[69.14, 71.30]	[66.81, 73.71]	[42.05, 64.98]	[27.73, 33.65]

Table 12: 95% Confidence Intervals (CI) for Pass@1 accuracy on in-domain reasoning benchmarks across the Qwen2.5-Instruct model family (1.5B, 3B, and 7B).

Method	GPQA-Diamond			ARC-C			HumanEval		
	M@32	SD	95% CI	M@32	SD	95% CI	M@32	SD	95% CI
Qwen2.5-3B-Instruct									
CoT	28.79	0.216	[23.83, 29.84]	**86.26**	0.270	[72.50, 75.60]	52.44	0.342	[0.536, 0.641]
Pure Latent	28.28	0.413	[21.50, 33.01]	72.95	0.426	[68.13, 73.01]	56.71	0.377	[54.43, 65.96]
Entropy-Routed	**31.82**	0.259	[24.70, 31.90]	79.69	0.319	[69.26, 72.92]	54.27	0.357	[52.85, 63.77]
GRPO	28.79	0.265	[24.33, 31.73]	82.94	0.290	[73.12, 76.45]	50.00	0.318	[53.99, 63.73]
HRPO	27.78	0.248	[24.05, 30.97]	83.62	0.284	[73.43, 76.68]	58.54	0.332	[54.43, 64.59]
TARPO	29.29	0.252	[24.90, 31.92]	85.49	0.274	[72.99, 76.12]	**61.59**	0.351	[58.26, 68.99]

Table 13: Out-of-distribution (OOD) evaluation results for Qwen2.5-3B-Instruct on GPQA-Diamond, ARC-C, and HumanEval, reporting Maj@32 (M@32), Standard Deviation (SD), and 95% Confidence Interval (CI). The best overall Maj@32 results are highlighted in bold.

Method	GSM8K			MATH500			AMC23		
	M@32	SD	95% CI	M@32	SD	95% CI	M@32	SD	95% CI
Llama-3.1-8B-Instruct									
CoT	89.16	0.282	[76.26, 79.30]	53.80	0.334	[32.55, 38.40]	37.50	0.216	[9.48, 22.86]
GRPO	88.93	0.286	[81.44, 84.53]	59.80	0.391	[42.35, 49.20]	35.00	0.298	[12.32, 30.80]
TARPO	**89.76**	0.284	[82.72, 85.78]	**61.40**	0.395	[44.19, 51.11]	**42.50**	0.316	[13.19, 32.75]

Table 14: Cross-architecture generalization results on Llama-3.1-8B-Instruct, reporting Maj@32 (M@32), Standard Deviation (SD), and 95% Confidence Interval (CI) on GSM8K, MATH500, and AMC23.

Table 15: A summary of licenses.

Resources	Type	License	URL
Qwen2.5-1.5B-Instruct	Base LLM	Apache-2.0	https://huggingface.co/Qwen/Qwen2.5-1.5B-Instruct
Qwen2.5-3B-Instruct	Base LLM	Qwen-Research License	https://huggingface.co/Qwen/Qwen2.5-3B-Instruct
Qwen2.5-7B-Instruct	Base LLM	Apache-2.0	https://huggingface.co/Qwen/Qwen2.5-7B-Instruct
Llama-3.1-8B-Instruct	Base LLM	Llama 3.1 Community License Agreement	https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct
HRPO	RL-framework	Not Specified	https://github.com/Yueeeeeeee/HRPO
TRL	RL-framework	Apache-2.0	https://github.com/huggingface/trl
Unsloth	Training-framework	Apache-2.0, AGPL-3.0	https://github.com/unslothai/unsloth
GSM8K	Dataset	MIT	https://github.com/openai/grade-school-math
MATH	Dataset	MIT	https://github.com/hendrycks/math
MATH500	Dataset	MIT	https://github.com/hendrycks/math
DAPO-MATH-17k	Dataset	Not Specified	https://huggingface.co/datasets/open-r1/DAPO-Math-17k-Processed
AMC23	Dataset	Available Online	https://github.com/eric-ai-lab/Soft-Thinking
OlympiadBench	Dataset	MIT	https://github.com/zz1358m/SofT-GRPO-master
GPQA-Diamond	Dataset	MIT	https://github.com/eric-ai-lab/Soft-Thinking
ARC-C	Dataset	Apache-2.0	https://github.com/eric-ai-lab/Soft-Thinking
HumanEval	Dataset	MIT	https://github.com/eric-ai-lab/Soft-Thinking