CLOSED-FORM SAMPLE PROBING FOR LEARNING GENERATIVE MODELS IN ZERO-SHOT LEARNING

ABSTRACT

Generative model based approaches have led to significant advances in zero-shot learning (ZSL) over the past few-years. These approaches typically aim to learn a conditional generator that synthesizes training samples of classes conditioned on class definitions. The final zero-shot learning model is then obtained by training a supervised classification model over the real and/or synthesized training samples of seen and unseen classes, combined. Therefore, naturally, the generative model needs to produce not only relevant samples, but also those that are sufficiently *rich* for classifier training purposes, which is handled by various heuristics in existing works. In this paper, we introduce a principled approach for training generative models *directly* for training data generation purposes. Our main observation is that the use of closed-form models opens doors to end-to-end training thanks to differentiability of the solvers. In our approach, at each generative model update step, we fit a task-specific closed-form ZSL model from generated samples, and measure its loss on novel samples all within the compute graph, a procedure that we refer to as *sample probing*. In this manner, the generator receives feedback directly based on the value of its samples for model training purposes. Our experimental results show that the proposed sample probing approach improves the ZSL results even when integrated into state-of-the-art generative models.

1 INTRODUCTION

Zero-shot Learning (ZSL) has recently received a great interest for being one of the promising paradigms towards building very large vocabulary (visual) understanding models with limited training data. The problem of ZSL can be summarized as the task of transferring information across classes such that the instances of *unseen* classes, with no training examples, can be recognized at test time, based on the information provided by the training samples of *seen* classes. Similarly, the term *Generalized Zero-shot Learning* (GZSL) (Chao et al., 2016; Xian et al., 2018a) is used to refer to a practically more valuable variant of ZSL where both seen and unseen classes may appear at test time. GZSL brings in additional challenges since GZSL models need to produce class confidence scores that are comparable across all classes.

Recent work shows that hallucinating unseen class samples through statistical generative models can be an effective strategy (Mishra et al., 2017; Xian et al., 2018b; 2019; Sariyildiz & Cinbis, 2019; Zhu et al., 2018; Schonfeld et al., 2019; Arora et al., 2018; Elhoseiny & Elfeki, 2019; Narayan et al., 2020). These approaches rely on generative models conditioned on *class embeddings*, obtained from auxiliary semantic knowledge, such as visual attributes (Xian et al., 2019), class name word embeddings (Schonfeld et al., 2019), or textual descriptions (Zhu et al., 2018). The resulting synthetic examples, typically in combination with existing real seen class examples, are then used for training a supervised classifier.

In generative GZSL approaches, the *quality* of class-conditional samples is crucial for building accurate recognition models. It is not straight-forward to formally define the criteria of *good training samples*. Arguably, however, samples need to be (i) realistic (*e.g.* free from unwanted artifacts), (ii) relevant (*i.e.* belong to the desired class distribution) and (iii) informative (*i.e.* contain examples defining class boundaries) in order to train an accurate classifier. Clearly, a primary factor here towards obtaining such high-quality samples is the training objective driving the conditional generative model training process.

Figure 1: Illustration of the proposed framework for the end-to-end *sample probing* of conditional generative models. At each training iteration, we take synthetic training examples for some subset of seen classes (*probe-train classes*) from the conditional generative models, train a closed-form solvable zero-shot learning model (*sample probing ZSL model*) over them and evaluate it on the real examples of a different subset of seen classes (*probe-validation classes*). The resulting cross-entropy loss of the probing model is used as a loss term for the generative model update.

In this work, we aim to address the problem of training data generating models via an end-to-end mechanism that we call *sample probing*.[1] Our main goal is to *directly* evaluate the ability of a generative model in synthesizing training examples. To this end, we observe that we can leverage classification models with closed-form solvers to efficiently measure the quality of training samples, in an end-to-end manner. More specifically, we formulate a simple yet powerful meta-learning approach: at each training iteration, (i) take a set of samples from the generative model for a randomly selected subset of classes, (ii) train a zero-shot *probing model* using only the synthesized samples, and (iii) evaluate the probing model on real samples from the training set. We then use the loss value as an end-to-end training signal for updating the generative model parameters. Since we specifically focus on probing models with exact closed-form solutions, the probing model optimization simplifies into a differentiable linear algebraic expression and takes part as a differentiable unit within the compute graph. A graphical summary of the proposed training scheme is given in Figure 1.

In the rest of the paper, we first provide an overview of related work, and explain our approach in detail. We then present a through experimental evaluation on GZSL benchmarks in Section 4, where the results show that sample probing yields improvements when introduced into state-of-the-art baselines. We conclude with final remarks in Section 5.

2 RELATED WORK

The generalized zero-shot learning problem has been introduced by Xian et al. (2017) and Chao et al. (2016). The extensive study in Xian et al. (2018a) has shown that the success of methods can greatly vary across zero-shot and generalized zero-shot learning problems. The additional challenge in the generalized case is the need for deciding whether an input test sample belongs to a seen or unseen class. Discriminative training of ZSL models, such as those based on bilinear compatibility functions (Weston et al., 2011; Frome et al., 2013), are likely to yield higher confidence scores for seen classes. To alleviate this problem, a few recent works have proposed ways to regularize discriminative models towards producing comparable confidence scores across all classes and avoid over-fitting, *e.g.* Jiang et al. (2019); Liu et al. (2018); Chou et al. (2021b).

Generative approaches to zero-shot learning naturally address the confidence score calibration problem. However, in general, generative modeling corresponds to a more sophisticated task than learning discriminant functions only (Vapnik & Vapnik, 1998). In this context, the problem is further complicated by the need of predicting zero-shot class distributions. To tackle this challenging task, a variety of techniques have been proposed (Mishra et al., 2017; Xian et al., 2018b; 2019; Sariyildiz & Cinbis, 2019; Zhu et al., 2018; Schonfeld et al., 2019; Arora et al., 2018; Elhoseiny & Elfeki, 2019; Narayan et al., 2020) by adapting generative models, such as VAEs (Kingma & Welling,

---

[1]Our use of the *sample probing* term is not closely related to the natural language model analysis technique known as *probing* (Belinkov et al., 2017; Peters et al., 2018; Hewitt & Liang, 2019).

2014; Rezende et al., 2014) and GANs (Goodfellow et al., 2014). To enforce class conditioning, the state-of-the-art approaches use a mixture of heuristics: Xian et al. (2018b) uses the loss of a pre-trained classifier over the generated samples during training. Narayan et al. (2020) additionally uses the loss of a sample-to-attribute regressor, in combination with a feedback mechanism motivated from *feedback networks* (Zamir et al., 2017). Sariyildiz & Cinbis (2019) uses *projection discriminator* (Miyato & Koyama, 2018) and *gradient matching loss* as a gradient based similarity measure for comparing real versus synthetic data distributions. None of these generative ZSL approaches, however, directly measure the *value* of the generated samples *for training* classification models. The main difficulty lies in the need for back-propagating over long compute chains, which is both inefficient and prone to gradient vanishing problems. To the best of our knowledge, we introduce the first end-to-end solution to this problem by the idea of using probing models with closed-form solvers to monitor the sample quality for model training purposes.

Our approach is effectively a *meta-learning* (Snell et al., 2017) scheme. Meta-learning is a prominent idea in few-shot learning, where the goal is to learning to build predictive models from a limited number of samples. The main motivation is the idea that general-purpose classification models may behave suboptimally when only few training samples are provided. A variety of meta-learning driven few-shot learning models have been proposed, such as meta-models that transform few samples to classifiers (Gidaris & Komodakis, 2018; Snell et al., 2017), set-to-set transformations for improving sample representations (Ye et al., 2020; Bronskill et al., 2020), fast adaptation networks for few examples (Finn et al., 2017; Rusu et al., 2019; Nichol et al., 2018). In contrast to such mainstream *learning to classify* and *learning to adapt* approaches, we aim to address the problem of *learning to generate training examples* for GZSL.

There are only few and recent studies that aim to tackle generative ZSL via meta-learning principles. Verma et al. (2020; 2021) embrace the learning-to-adapt framework of MAML (Finn et al., 2017), which originally aims to learn the optimal initialization for few-shot adaptation. The MAML steps are incorporated by iteratively applying a single-step update to the generative model using the generative model (VAE/GAN) loss terms, and then back-propagating over the re-computed generative loss terms on new samples from a disjoint subset of classes using the single-step updated model. Our approach differs fundamentally, as we propose to use the discriminative guidance of ZSL models fully-trained directly from generated sample batches. In another work, Yu et al. (2020) proposes an *episodic training*-like approach with periodically altered training sets and losses during training, to learn non-stochastic mappings between the class-embeddings and class-centers. Chou et al. (2021a), similarly inspired from meta-learning and mixup regularization (Zhang et al., 2018), proposes to train a novel discriminative ZSL model over episodically defined virtual training classes obtained by linearly mixing classes. Neither of these approaches learn sample generating models, therefore, they have no direct relation to our work focusing on the problem of measuring the sample quality for ZSL model training purposes, with end-to-end discriminative guidance.

The use of recognition models with closed-form solvers has attracted prior interest in various contexts. Notably, Romera-Paredes & Torr (2015) proposes the ESZSL model as a simple and effective ZSL formulation. We leverage the closed-form solvability of the ESZSL model as part of our approach. Bertinetto et al. (2019) utilizes ridge-regression based task-specific few-shot learners within a discriminative meta-learning framework. In a similar fashion, Bhat et al. (2020); Liu et al. (2020) tackle the problem of *video object segmentation* (VOS) and use ridge regression based task-specific segmentation models within a meta-learning framework. None of these approaches aim to use recognition models with closed form solvers to form guidance for generative model training.

Finally, we note that meta-learning based approaches have also been proposed for a variety of different problems, such as learning-to-optimize (Li & Malik, 2016; Chen et al., 2017) and long-tail classification (Liu et al., 2019; Ren et al., 2020).

3 METHOD

In this section, we first formally define the generalized zero-shot learning problem and then define a mathematical framework to summarize the core training dynamics of mainstream generative GZSL approaches. We then express our approach in the context of this mathematical framework.

3.1 PROBLEM DEFINITION

In zero-shot learning, the goal is to learn a classification model that can recognize the test instances of *unseen* classes $\mathcal{Y}_u$, which has no training examples, based on the model learned over the training examples provided for the disjoint set of *seen* classes $\mathcal{Y}_s$. We refer to the class-limited training set by $\mathcal{D}_{\text{tr}}$, which consists of sample and class label pairs $(x \in \mathcal{X}, y \in \mathcal{Y}_s)$. The space $\mathcal{X}$ may in practice refer to raw images or more commonly the feature representations of images, typically obtained using a pre-trained ConvNet. In generalized zero-shot learning, the goal is build the classification model using the training data set $\mathcal{D}_{\text{tr}}$, such that the model can recognize both seen and unseen class samples at test time. For simplicity, we restrict our discussion to the GZSL problem setting below.

In order to enable the recognition of unseen class instances, it is necessary to have visually-relevant prior knowledge about classes so that classes can visually be related to each other. Such prior knowledge is delivered by the mapping $\psi : \mathcal{Y} \rightarrow \mathcal{A}$, where $\mathcal{A}$ expresses the prior knowledge space. In most cases, the prior knowledge is provided as d_ψ-dimensional vector-space embeddings of classes, obtained using visual attributes, taxonomies, class names combined with word embedding models, the textual descriptions of classes combined with language models, see *e.g.* Akata et al. (2015). Following the common terminology, we refer to ψ as the *class embedding* function.

Generative GZSL. In our work, we focus on generative approaches to GZSL. The main goal is to learn a conditional generative model $G : \mathcal{A} \times \mathcal{Z} \rightarrow \mathcal{X}$, which takes some class embedding $a \in \mathcal{A}$ and stochasticity-inducing noise input z, and yields a synthetic sample $x \in \mathcal{X}$. Once such a generative model is learned, synthetic training examples for all classes can simply be sampled from the G-induced distribution P_G, and the final classifier over $\mathcal{Y}$ can be obtained using any standard supervised classification model. We refer to the trainable parameters of the model G by θ_G.

As summarized in Section 2, existing approaches vary greatly in terms of their generative model formulation details. For the purposes of our presentation, most of these generative GZSL works (if not all) can be summarized as the iterative minimization of some loss function that acts on the outputs of the generative model:

$$L_G = \mathop{\mathbb{E}}_{(x,a)\sim\mathcal{D}_{\text{tr}}} \left[\ell_G \left(G(a, z_x), a \right) \right] \tag{1}$$

where z_x refers to the noise input associated with the training sample (x, y) and ℓ_G is the generative model learning loss. $(x, a) \sim \mathcal{D}_{\text{tr}}$ is shorthand notation for $(x, \psi(y)) \sim \mathcal{D}_{\text{tr}}$ At each iteration the goal is to reduce L_G approximated over a mini-batch of real samples and their class embeddings.

In our notation, we deliberately keep certain details simple. Most noticeably, z_x greatly varies across models. For example, in the case of a conditional GAN model, $z_x \sim p(z)$ can simply be a sample from a simple prior distribution $p(z)$ (Xian et al., 2018b; Sariyildiz & Cinbis, 2019; Elhoseiny & Elfeki, 2019). In contrast, in the case of variational training, z_x is the latent code sampled from a variational posterior, *i.e.* $z_x \sim q(z|x)$, where the variational posterior $q(z|x)$ is given by a variational encoder network trained jointly with G (Narayan et al., 2020; Xian et al., 2019).

Another important simplification that we intentionally make in Eq. (1) is the fact that we define the generative model learning loss ℓ_G as a function of generator output and class embedding, to emphasize its sample-realisticity and class-relevance estimation goals. However, the exact domain of ℓ_G heavily depends on its details, which typically consists of multiple terms and/or (adversarially) trained models. In most of the state-of-the-art approaches, this term is a combination of VAE reconstruction loss (Xian et al., 2019), conditional or unconditional adversarial discriminator network (Xian et al., 2018b; Narayan et al., 2020; Sariyildiz & Cinbis, 2019; Xian et al., 2019), a sample-to-class classifier for measuring class relevance (Xian et al., 2018b) and sample-to-embedding mappings (Narayan et al., 2020). The loss L_G may also incorporate additional regularization terms, such as ℓ_2 regularization or a gradient penalty term (Sariyildiz & Cinbis, 2019).

In the following, we explain our sample probing approach for generative model training as an additional term that can, in principle, be used in conjunction with virtually any of the mainstream generative zero-shot learning formulations.

Figure 2: The compute graph view of the proposed approach, at some training iteration t. The upper half shows sampling from the generative model and the lower half shows sample probing model loss. Circles denote generator and probing model parameters. Blue arrows show the back-propagation path for updating the generative model. Best viewed in color.

3.2 SAMPLE PROBING AS GENERATIVE MODEL GUIDANCE

The problem that we aim to address is enforcement of G to learn to produce samples maximally beneficial for zero-shot model training purposes. We approach this problem through a *learning to generate training samples* perspective, where we aim to monitor the quality of the generative model through the synthetic class samples it provides.

In construction of our approach, at each training iteration t, we first randomly select a subset of $Y_{\text{pb-tr}}^t \subset \mathcal{Y}$ of seen classes. We refer to these classes as *probe-train* classes. This subset defines the set of classes that are used for training the iteration-specific *probing model* over the synthetic samples. More specifically, we first take samples from the generative model with the parameters θ_G^t for these classes, and fully train a temporary zero-shot learning model over them using regularized loss minimization:

$$\Gamma^t = \arg\min_{\Gamma} \mathbb{E}_{x = G(z, a \sim A_{\text{pb-tr}}^t)} \left[\ell_{\text{pb}} \left(f_{\text{pb}}(x, a), a \right) \right] \tag{2}$$

where f_{pb} is the scoring function of the temporary probing model parameterized by Γ and ℓ_{pb} is its training loss. $A_{\text{pb-tr}}^t$ is the set of class embeddings of classes in $Y_{\text{pb-tr}}^t$. Regularization term over Γ is not shown explicitly for brevity.

The result of Eq. (2), gives us a purely synthetic sample driven model Γ^t, which we leverage as a way to estimate the success of the generator in synthesizing training examples. For this purpose, we sample real examples from the training set $\mathcal{D}_{\text{tr}}$ as validation examples for the probe model. Since we use a (G)ZSL model as the probing model, we can evaluate the model on examples of the classes not used for training the model. Therefore, we sample these probe-validation examples from the remaining classes $Y_{\text{pb-val}} = \mathcal{Y}_s \setminus Y_{\text{pb-tr}}^t$, *i.e.* the classes with real training examples but unused for probe model training, and use softmax cross-entropy loss over these samples as the probing loss:

$$L_{\text{pb}} = -\mathbb{E}_{(x,y) \sim \mathcal{D}_{\text{pb-val}}} \left[\log p(y|x; \Gamma^t) \right] \tag{3}$$

where $\mathcal{D}_{\text{pb-val}} \subset \mathcal{D}_{\text{tr}}$ is the data subset of classes $Y_{\text{pb-val}}$. $p(y|x; \Gamma^t)$ is the target class likelihood obtained by applying softmax to $f_{\text{pb}}(x, \psi(y); \Gamma^t)$ scores over the set of target class set. Here, as target class set, one can use only the classes in $Y_{\text{pb-val}}$ (ZSL probing) or those in both $Y_{\text{pb-tr}}$ and $Y_{\text{pb-val}}$ (GZSL probing). We treat this decision as a hyper-parameter and tune on the validation set. We further investigate this distinction in Section 4.

We use a weighted combination of L_{pb} and L_G, as our final loss function. Therefore, the gradients $\nabla_{\theta_G} L_{\text{pb}}$ act effectively as the training signal for guiding G towards yielding training examples that results in (G)ZSL probing models with minimal empirical loss.

3.3 Closed-form probe model

A critical part of construction is the need for a probing model where minimization of Eq. (2) is both efficient and differentiable, so that the solver itself can be a part of the compute graph. Probing models that require iterative gradient descent based optimization are unlikely to be suitable as one would need to make a large number of probing model updates for each single G update step, which is both inefficient and prone to gradient vanishing problems. We propose address this problem through the use a ZSL model that can be efficiently fit using a closed-form solution.

For this purpose, we opt to use the ESZSL (Romera-Paredes & Torr, 2015). The model is formalized by the following minimization problem:

$$\min_{\Gamma} \|X^{\mathrm{T}}\Gamma A - Y\|_{\mathrm{Fro}}^2 + \Omega(\Gamma) \tag{4}$$

where $X \in R^{d_x \times m}$ and $A \in R^{d_\psi \times m}$ represent the feature and class embeddings corresponding to m input training examples, $\Gamma \in R^{d_x \times d_\psi}$ is the compatibility model matrix, and $\Omega(\Gamma)$ is the regularization function, defined as:

$$\Omega(\Gamma) = \lambda_x \|\Gamma A\|_{\mathrm{Fro}}^2 + \lambda_a \|X^{\mathrm{T}}\Gamma\|_{\mathrm{Fro}}^2 + \lambda_n \|\Gamma\|_{\mathrm{Fro}}^2 \tag{5}$$

where $\lambda_x, \lambda_a, \lambda_n$ correspond to term weights.

When the regularization term weights are set such that $\lambda_n = \lambda_x \lambda_a$, the optimal solution to Eq. (4) can be computed in a closed-form:

$$\Gamma^\star = (XX^{\mathrm{T}} + \lambda_x I)^{-1} XYA^{\mathrm{T}}(AA^{\mathrm{T}} + \lambda_a I)^{-1} \tag{6}$$

This approach was originally proposed as a standalone label-embedding based ZSL model in Romera-Paredes & Torr (2015), with the practical advantage of having an efficient solver. Here, we re-purpose this approach as a probing model in our framework, where the fact that the model is solvable in closed-form is critically important, enabling the idea of end-to-end sample probing. For this purpose, we utilize the solver given by Eq. (6) as the implementation of Eq. (2), which takes a set of synthetic training sample and estimates the corresponding probing model parameters.

A summary of the final approach, from a compute graph point of view, is given in Figure 2.

4 Experiments

In this section, we explain our experimental setup, discuss our main results and present an analysis of the approach.

Datasets. We use the four mainstream GZSL benchmark datasets to evaluate our model: Caltech-UCSD-Birds (CUB) (Wah et al., 2011), SUN Attribute (SUN) (Patterson & Hays, 2012), Animals with Attributes2 (AWA2, more simply AWA) (Xian et al., 2018a) and Oxford Flowers (FLO) (Nilsback & Zisserman, 2008). CUB is a medium scale fine-grained dataset consisting of 200 classes consisting of bird species. The dataset contains 11.758 images together with 312 dimensional attribute annotations for each bird class. SUN is a fine-grained dataset that contains 14.340 images together with 102 dimensional attributes. AWA is a coarse grained dataset with 30.475 images of 50 animal classes with 85-dimensional attributes. FLO is a medium-scale fine-grained dataset with 102 classes and 1024-dimensional attributes. In accordance with the state-of-the-art, we use the class embeddings and the second version of the splits proposed by Xian et al. (2018a).

In our experiments, we use the image features extracted from ResNet-101 backbone pretrained on ImageNet 1K. In the experiments based on *fine-tuned* representations, we use the backbone finetuned with the training images of seen classes, as in Xian et al. (2019); Narayan et al. (2020).

Evaluation metrics. We evaluate the models in terms of GZSL-u, GZSL-s and h-score (H) values, as defined in Xian et al. (2018a). The h-score, which is the harmonic mean of GZSL-u and GZSL-s results, aims to measure how well a model is able to recognize seen and unseen classes collectively.

Hyper-parameter tuning policy. In our preliminary studies, we observe that final GZSL performance, especially in terms of h-score, of most models strongly depend on the selection of the hyper-parameters. We also observe that there is no widely-accepted policy on how the hyper-parameters of

Table 1: **Comparison to TF-VAEGAN (Narayan et al., 2020) based state-of-the-art baseline on CUB, FLO, SUN and AWA datasets.** We tune the number of training iterations of TF-VAEGAN using our own hyper-parameter tuning policy to make results comparable. The lower and upper parts present results with and without fine-tuned representations. The results are reported in terms of top-1 accuracy over unseen (u) and seen (s) classes, and their harmonic mean (H).

		CUB			FLO			SUN			AWA		
		u	s	**H**	u	s	**H**	u	s	**H**	u	s	**H**
-	TF-VAEGAN	**53.9**	58.4	56.0	59.4	78.3	67.5	42.9	39.3	41.0	54.4	**75.2**	63.2
	Ours	51.1	**63.3**	**56.6**	**63.5**	**83.2**	**72.1**	**44.0**	**39.7**	**41.7**	**55.2**	74.7	**63.5**
FT	TF-VAEGAN	**64.2**	72.7	68.2	70.0	91.3	79.2	46.5	**41.7**	**44.0**	41.7	**90.2**	57.0
	Ours	63.1	**76.1**	**69.0**	**70.2**	**91.7**	**79.5**	**47.8**	40.6	43.9	**45.6**	87.6	**60.0**

GZSL models shall be tuned. It is a rather common practice in the GZSL literature to either directly report the hyper-parameters used in experiments without an explanation on the tuning strategy or simply refer to *tuning on validation set*, which we find a vaguely-defined policy as (i) Xian et al. (2018a) defines an unseen-class only validation split, which does not allow monitoring the h-score, and, (ii) it is unclear which metric one should use to measure performance of a (G)ZSL model for model selection purposes.

Therefore, to (at least) obtain comparable results in our own experiments, we use the following policy to tune the hyper-parameters of our approach and our baselines: we first leave-out 20% of train class samples as *val-seen* samples. We periodically train a supervised classifier by taking synthetic samples from the generative model, and evaluate it on the validation set, consisting of the aforementioned *val-seen* samples plus the *val-unseen* samples that comes from splits defined in the benchmarks. We choose the hyper-parameter combination with the highest h-score on the validation set. We obtain final models by re-training the generative model from scratch on the training and validation examples combined, using the selected hyper-parameters.

4.1 MAIN RESULTS

In this subsection, we present our main experimental results. As we observe that the results are heavily influenced from hyper-parameter tuning strategy, our main goal throughout our experiments is the validation of the proposed sample probing idea by incorporating it into a strong baseline and then comparing results that are obtained via the same experimental methodology.

For this purpose, below, we present our main results based on the state-of-the-art baseline based on TF-VAEGAN (Narayan et al., 2020). We then present additional results based on a simpler conditional Wasserstein GAN (Arjovsky et al., 2017; Miyato & Koyama, 2018) (cWGAN) baseline. Finally, we also present a comparison against the state-of-the-art results.

TF-VAEGAN results. We take the main generative GZSL approach of the recent work TF-VAEGAN (Narayan et al., 2020) as our state-of-the-art baseline to compare against. We use the version of the model without *feedback loop* (Narayan et al., 2020), for simplicity, as the model yields excellent performance with and without feedback loops. We take all hyper-parameters of TF-VAEGAN from the original repository and keep them fixed. We only re-tune the number of training iterations of the original model using our hyper-parameter tuning policy, to make the results comparable, as it is unclear how the original values were obtained. We also tune all additional hyper-parameters of our model using the same policy.

The results are presented in Table 1. In the upper half of the table, we report results with the original ConvNet representations and in the lower half, we use the fine-tuned representations. Using the original representations, we observe consistent improvements in h-scores on all data sets, as well as in most of the unseen and seen class accuracy values. Using the fine-tuned representations, we observe improvements in GZSL h-scores in three out of four data sets, with a slight degradation on SUN (44.0 to 43.9) Overall, these improvements over an already strong and state-of-the-art baseline validates the effectiveness of the proposed sample probing approach.

Table 2: Comparison against conditional Wasserstein GAN (Arjovsky et al., 2017; Miyato & Koyama, 2018) (cWGAN) based baseline on the CUB data set.

	u	s	**H**
CWGAN	45.1	**53.1**	48.7
Ours	**48.2**	52.4	**50.2**

Table 3: **Comparison against state-of-the-art generative model based GZSL on CUB, FLO, SUN and AWA datasets.** Results obtained with the proposed features are reported, together with the results obtained with fine-tuned features under fine-tuned (FT). The results are reported in terms of top-1 accuracy of unseen (u) and seen (s) classes, together with their harmonic mean (H).

		CUB			FLO			SUN			AWA		
		u	s	**H**	u	s	**H**	u	s	**H**	u	s	**H**
	f-CLSWGAN (Xian et al., 2018b)	3.7	57.7	49.7	59.0	73.8	65.6	42.6	36.6	39.4	57.9	61.4	59.6
	Cycle-WGAN (Felix et al., 2018)	47.9	59.3	53.0	61.6	69.2	65.2	**47.2**	33.8	39.4	**59.6**	63.4	59.8
-	LisGAN (Li et al., 2019)	46.5	57.9	51.6	57.7	**83.8**	68.3	42.9	37.8	40.2	52.6	**76.3**	62.3
	f-VAEGAN (Xian et al., 2019)	48.4	60.1	53.6	56.8	74.9	64.6	45.1	38.0	41.3	57.6	70.6	**63.5**
	TF-VAEGAN (Narayan et al., 2020)	53.9	58.4	56.0	59.4	78.3	67.5	42.9	39.3	41.0	54.4	75.2	63.2
	Meta-VGAN (Verma et al., 2021)	**55.2**	48.0	53.2	-	-	-	-	-	-	57.4	70.5	**63.5**
	Ours	51.1	**63.3**	**56.6**	**63.5**	83.2	**72.1**	44.0	**39.7**	**41.7**	55.2	74.7	**63.5**
	f-VAEGAN (Xian et al., 2019)	63.2	75.6	68.9	-	-	-	**50.1**	37.8	43.1	**57.1**	76.1	**65.2**
FT	TF-VAEGAN (Narayan et al., 2020)	**64.2**	72.7	68.2	70.0	91.3	79.2	46.5	**41.7**	**44.0**	41.7	**90.2**	57.0
	Ours	63.1	**76.1**	**69.0**	**70.2**	**91.7**	**79.5**	47.8	40.6	43.9	45.6	87.6	60.0

cWGAN results. As a second validation, we now compare against the conditional Wasserstein GAN (Arjovsky et al., 2017; Miyato & Koyama, 2018) (cWGAN) based baseline on the CUB data set. We follow the specifics of the model defined in Sariyildiz & Cinbis (2019) for the baseline model, and, introduce our approach and hyper-parameter tunining methodology on top of it. The results are presented in Table 2. Again, we observe a consistent improvement in h-score, providing a second verification for the model.

Comparison to the state-of-the-art. In Table 3 we compare our results with the state-of-the-art generative approaches for GZSL. During training, we select our best model based on the validation results and report test results on models that gives best validation scores. For consistency and to keep the baseline comparable to our results, we again report our own results for TF-VAEGAN, without feedback loop and using our hyper-parameter tunining policy, but do acknowledge that the original paper (Narayan et al., 2020) reports higher results. The upper part of the table contains results with the original image representations, and the lower part contains those based on fine-tuned representations.

From the results without fine-tuning, we observe that the proposed sample probing based generative model yields state-of-the-art h-scores in all CUB, FLO, SUN and AWA datasets. We also observe competitive results in terms of individual unseen and seen class accuracy values. When compared against results using fine-tuned representations, we again observe state-of-the-art h-scores on CUB and FLO datasets, with a close second on SUN. On AWA, we observe that f-VAEGAN achieves the highest results with a significant margin over our TF-VAEGAN based baseline, where the sample probing improves the baseline yet still achieves a score below that of f-VAEGAN. Overall, while it is hardly fair to compare models with significant implementation details, these results suggests the overall competitiveness of the obtained data generating models with sample probing.

4.2 ANALYSIS

ZSL vs GZSL loss in sample probing loss. In Table 4, we present a comparison of our approach when two different types of losses (*zsl-loss* and *gzsl-loss*) used in its training. They differ from each other in terms of classes among which the real examples of probe-validation classes are classified, during the evaluation of sample probing ZSL model. *zsl-loss* indicates that the examples of probe-validation classes are classified among only probe-validation classes, whereas, *gzsl-loss*

Table 4: Comparison of the ZSL vs GZSL based sample probing losses.

| | Generalized Zero-Shot Learning | | | | | |
| | zsl-loss | | | gzsl-loss | | |
	u	*s*	**H**	*u*	*s*	**H**
CUB	50.5	**63.6**	56.3	**51.1**	63.3	**56.6**
FLO	62.4	**83.8**	71.5	**63.5**	83.2	**72.1**
AWA	55.2	**74.7**	63.5	**55.6**	72.8	63.0
SUN	44.0	**39.7**	**41.7**	**46.0**	36.9	41.0

Table 5: Comparison of mean per-class Frechet Distance between real and generated unseen class samples on CUB, AWA and FLO datasets for TF-VAEGAN and Our approach. Lower is better.

(Frechet distance)	**CUB**	**AWA**	**FLO**
TF-VAEGAN	21.5	18.5	31.0
Ours	**19.8**	**17.9**	**30.1**

indicates that the examples of probe-validation classes are classified among both probe-train and probe-validation classes. We observe that using either one during the evaluation of sample probing ZSL model, brings its own characteristic results (Table 4). On all datasets, using *zsl-loss* increases the seen accuracy while using *gzsl-loss* increases the unseen accuracy. We choose among these two options using our same hyper-parameter tunining policy, on the validation set.

Effect of sample probing loss weight. Figure 3 shows the validation and test set h-score values obtained as a function of sample probing loss weight. In the test set results, we observe an overall increasing performance trend with larger loss weights, upto the weight 6, highlighting the contribution of sample probing loss. The optimal weight with respect to the validation and the test sets, however, differs. This observation provides as an example for the difficulty of tuning the ZSL model based on validation set. We set the loss weight to 5 following our hyper-parameter tuning policy, which yields almost 0.5 lower than the maximum test-set score observed for this single hyper-parameter.

Figure 3: The effect of sample probing weight on the CUB dataset.

Quantitative analysis of sample quality. Since it is hard to visualize statistical details of generated features, we quantitatively evaluate the sample quality using Frechet (Wasserstein-2) Distance (also used in FID metric for GANs). In Table 5 we provide a comparison for TF-VAEGAN and our approach for respective mean per-class Frechet distances between real and synthetic samples of unseen classes on three datasets. The results show that sample probing helps generator to generate more realistic samples compared to TF-VAEGAN for unseen classes.

5 CONCLUSIONS

We propose a principled (generalized) zero-shot learning approach, namely sample probing, which makes use of closed-form ZSL models in generative model training by providing a direct feedback for generator with the evaluation of real samples of unseen classes and results in an improvement of the overall quality of generated samples. Our method works in an end-to-end manner and it can be easily integrated into any mainstream generative zero-shot learning framework. Experiments on four datasets show that sample probing improves the recognition results.

Reproducibility statement. We discuss the problem of model selection in GZSL, and the difficulty of making fair comparison across GZSL models in Section 4. We believe that these are open problems in GZSL research. We also clearly explain our hyper-parameter tuning policy, which we use in our experiments. We provide our source code, implementing the main model, as a supplemen-

tary material to provide reproducibility. You can find how we process the data in meta_dset.py and util.py, the ESZSL implementation in eszsl.py, final classifier in classifier.py, main training code in train_tfvaegan_inductive_sample_probing.py, and the models in model.py. README.txt includes a brief explanation on how to run an experiment. We are committed to releasing a complete repository upon acceptance.

REFERENCES

Zeynep Akata, Scott Reed, Daniel Walter, Honglak Lee, and Bernt Schiele. Evaluation of Output Embeddings for Fine-Grained Image Classification. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 2927–2936, 2015.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proc. Int. Conf. Mach. Learn.*, pp. 214–223. PMLR, 2017.

Gundeep Arora, Vinay Kumar Verma, Ashish Mishra, and Piyush Rai. Generalized zero-shot learning via synthesized examples. *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 4281–4289, 2018.

Yonatan Belinkov, Nadir Durrani, Fahim Dalvi, Hassan Sajjad, and James Glass. What do neural machine translation models learn about morphology? *arXiv preprint arXiv:1704.03471*, 2017.

Luca Bertinetto, Philip H S Torr, João Henriques, and Andrea Vedaldi. Meta-Learning with Differentiable Closed-Form Solvers. In *ICLR*, pp. 15, 2019.

Goutam Bhat, Felix Järemo Lawin, Martin Danelljan, Andreas Robinson, Michael Felsberg, Luc Van Gool, and Radu Timofte. Learning What to Learn for Video Object Segmentation. In *Proc. European Conf. on Computer Vision*, May 2020.

John Bronskill, Jonathan Gordon, James Requeima, Sebastian Nowozin, and Richard E. Turner. Tasknorm: Rethinking batch normalization for meta-learning. In *Proc. Int. Conf. Mach. Learn.*, volume 119 of *Proceedings of Machine Learning Research*, pp. 1153–1164. PMLR, 2020. URL http://proceedings.mlr.press/v119/bronskill20a.html.

Wei-Lun Chao, Soravit Changpinyo, Boqing Gong, and Fei Sha. An Empirical Study and Analysis of Generalized Zero-Shot Learning for Object Recognition in the Wild. In *Proc. European Conf. on Computer Vision*, 2016.

Yutian Chen, Matthew W Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P Lillicrap, Matt Botvinick, and Nando Freitas. Learning to learn without gradient descent by gradient descent. In *Proc. Int. Conf. Mach. Learn.*, pp. 748–756, 2017.

Yu-Ying Chou, Hsuan-Tien Lin, and Tyng-Luh Liu. Adaptive and generative zero-shot learning. In *Proc. Int. Conf. Learn. Represent.*, 2021a.

Yu-Ying Chou, Hsuan-Tien Lin, and Tyng-Luh Liu. Adaptive and Generative Zero-Shot Learning. In *Proc. Int. Conf. Learn. Represent.*, pp. 14, 2021b.

Mohamed Elhoseiny and Mohamed Elfeki. Creativity Inspired Zero-Shot Learning. In *Proc. IEEE Int. Conf. on Computer Vision*, April 2019.

Rafael Felix, B. G. Vijay Kumar, Ian Reid, and Gustavo Carneiro. Multi-modal Cycle-consistent Generalized Zero-Shot Learning. In *Proc. European Conf. on Computer Vision*, July 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1126–1135. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/finn17a.html.

Andrea Frome, Greg S. Corrado, Jon Shlens, Samy Bengio, Jeff Dean, and Tomas Mikolov. DeViSE: A Deep Visual-Semantic Embedding Model. In *Proc. Adv. Neural Inf. Process. Syst.*, pp. 2121–2129, 2013.

Spyros Gidaris and Nikos Komodakis. Dynamic few-shot visual learning without forgetting. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 4367–4375, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger (eds.), *Proc. Adv. Neural Inf. Process. Syst.*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/5ca3e9b122f61f8f06494c97b1afccf3-Paper.pdf.

John Hewitt and Percy Liang. Designing and Interpreting Probes with Control Tasks. In *Proc. of the Empiricial Methods in Natural Language Processing*, September 2019.

Huajie Jiang, Ruiping Wang, Shiguang Shan, and Xilin Chen. Transferable Contrastive Network for Generalized Zero-Shot Learning. In *Proc. IEEE Int. Conf. on Computer Vision*, August 2019.

Diederik P Kingma and Max Welling. Stochastic gradient vb and the variational auto-encoder. In *Proc. Int. Conf. Learn. Represent.*, volume 19, 2014.

Jingjing Li, Mengmeng Jing, Ke Lu, Zhengming Ding, Lei Zhu, and Zi Huang. Leveraging the invariant side of generative zero-shot learning. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 7402–7411, 2019.

Ke Li and Jitendra Malik. Learning to optimize. *arXiv preprint arXiv:1606.01885*, 2016.

Shichen Liu, Mingsheng Long, Jianmin Wang, and Michael I Jordan. Generalized Zero-Shot Learning with Deep Calibration Network. In *Proc. Adv. Neural Inf. Process. Syst.*, pp. 2005–2015, 2018.

Yu Liu, Lingqiao Liu, Haokui Zhang, Hamid Rezatofighi, Qingsen Yan, and Ian Reid. Meta learning with differentiable closed-form solver for fast video object segmentation. In *IEEE/RSJ Int. Conf. on Intelligent Robots and Systems (IROS)*, pp. 8439–8446. IEEE, 2020.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X. Yu. Large-Scale Long-Tailed Recognition in an Open World. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 2532–2541, Long Beach, CA, USA, June 2019.

Ashish Mishra, M. Shiva Krishna Reddy, Anurag Mittal, and Hema A. Murthy. A Generative Model For Zero Shot Learning Using Conditional Variational Autoencoders. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog. Workshops*, September 2017.

Takeru Miyato and Masanori Koyama. cGANs with Projection Discriminator. In *Proc. Int. Conf. Learn. Represent.*, February 2018.

Sanath Narayan, Akshita Gupta, Fahad Shahbaz Khan, Cees G. M. Snoek, and Ling Shao. Latent Embedding Feedback and Discriminative Features for Zero-Shot Classification. In *Proc. European Conf. on Computer Vision*, pp. 479–495, 2020.

Alex Nichol, Joshua Achiam, and John Schulman. On First-Order Meta-Learning Algorithms. *arXiv e-prints*, art. arXiv:1803.02999, March 2018.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *Indian Conference on Computer Vision, Graphics and Image Processing*, Dec 2008.

G. Patterson and J. Hays. Sun attribute database: Discovering, annotating, and recognizing scene attributes. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 2751–2758, 2012. doi: 10.1109/CVPR.2012.6247998.

Matthew Peters, Mark Neumann, Luke Zettlemoyer, and Wen-tau Yih. Dissecting contextual word embeddings: Architecture and representation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, October-November 2018.

Jiawei Ren, Cunjun Yu, Shunan Sheng, Xiao Ma, Haiyu Zhao, Shuai Yi, and Hongsheng Li. Balanced Meta-Softmax for Long-Tailed Visual Recognition. In *Proc. Adv. Neural Inf. Process. Syst.*, November 2020.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *Proc. Int. Conf. Mach. Learn.*, pp. 1278–1286. PMLR, 2014.

Bernardino Romera-Paredes and Philip HS Torr. An embarrassingly simple approach to zero-shot learning. In *Proc. Int. Conf. Mach. Learn.*, pp. 2152–2161, 2015.

Andrei A. Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. In *Proc. Int. Conf. Learn. Represent.*, 2019. URL https://openreview.net/forum?id=BJgklhAcK7.

Mert Bulent Sariyildiz and Ramazan Gokberk Cinbis. Gradient matching generative networks for zero-shot learning. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 2168–2178, 2019.

Edgar Schonfeld, Sayna Ebrahimi, Samarth Sinha, Trevor Darrell, and Zeynep Akata. Generalized Zero- and Few-Shot Learning via Aligned Variational Autoencoders. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 8239–8247, Long Beach, CA, USA, June 2019.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Proc. Adv. Neural Inf. Process. Syst.*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/cb8da6767461f2812ae4290eac7cbc42-Paper.pdf.

V Vapnik and V Vapnik. *Statistical Learning Theory 156–160*. Wiley, New York, 1998.

Vinay Kumar Verma, Dhanajit Brahma, and Piyush Rai. Meta-Learning for Generalized Zero-Shot Learning. *AAAI Conference on Artificial Intelligence*, 34(04):6062–6069, April 2020. ISSN 2374-3468, 2159-5399.

Vinay Kumar Verma, Ashish Mishra, Anubha Pandey, Hema A Murthy, and Piyush Rai. Towards Zero-Shot Learning With Fewer Seen Class Examples. In *WACV*, pp. 11, 2021.

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical Report CNS-TR-2011-001, California Institute of Technology, 2011.

Jason Weston, Samy Bengio, and Nicolas Usunier. Wsabie: Scaling up to large vocabulary image annotation. 2011.

Yongqin Xian, Bernt Schiele, and Zeynep Akata. Zero-Shot Learning - The Good, the Bad and the Ugly. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, March 2017.

Yongqin Xian, Christoph H Lampert, Bernt Schiele, and Zeynep Akata. Zero-shot learning—a comprehensive evaluation of the good, the bad and the ugly. *IEEE Trans. Pattern Anal. Mach. Intell.*, 41(9):2251–2265, 2018a.

Yongqin Xian, Tobias Lorenz, Bernt Schiele, and Zeynep Akata. Feature generating networks for zero-shot learning. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, 2018b.

Yongqin Xian, Saurabh Sharma, Bernt Schiele, and Zeynep Akata. f-vaegan-d2: A feature generating framework for any-shot learning. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 10275–10284, 2019.

Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 8808–8817, 2020.

Yunlong Yu, Zhong Ji, Jungong Han, and Zhongfei Zhang. Episode-Based Prototype Generating Network for Zero-Shot Learning. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 14032–14041, Seattle, WA, USA, June 2020.

Amir R Zamir, Te-Lin Wu, Lin Sun, William B Shen, Bertram E Shi, Jitendra Malik, and Silvio Savarese. Feedback networks. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 1308–1317, 2017.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *Proc. Int. Conf. Learn. Represent.*, 2018.

Yizhe Zhu, Mohamed Elhoseiny, Bingchen Liu, Xi Peng, and Ahmed Elgammal. A Generative Adversarial Approach for Zero-Shot Learning from Noisy Texts. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 1004–1013, Salt Lake City, UT, USA, June 2018.