Generalizable Imitation Learning from Observation via Inferring Goal Proximity

Youngwoon Lee[1][*][†]   Andrew Szot[2][*]   Shao-Hua Sun[1]   Joseph J. Lim[1][‡]
[1]University of Southern California   [2]Georgia Institute of Technology

Abstract

Task progress is intuitive and readily available task information that can guide an agent closer to the desired goal. Furthermore, a progress estimator can generalize to new situations. From this intuition, we propose a simple yet effective imitation learning from observation method for a goal-directed task using a learned goal proximity function as a task progress estimator, for better generalization to unseen states and goals. We obtain this goal proximity function from expert demonstrations and online agent experience, and then use the learned goal proximity as a dense reward for policy training. We demonstrate that our proposed method can robustly generalize compared to prior imitation learning methods on a set of goal-directed tasks in navigation, locomotion, and robotic manipulation, even with demonstrations that cover only a part of the states.

1   Introduction

Humans are effective at learning a task from demonstrations and applying the learned behaviors to other situations. We achieve this by extracting the underlying structure of the task when observing others fulfilling the task, instead of simply memorizing the demonstrator's low-level actions [4, 18]. This high-level task structure generalizes to new situations and thus helps us to quickly learn the task in new situations. One intuitive and readily available instance of such high-level task structure is *task progress*, measuring how much of the task the agent completed. Inspired by this insight, we propose a novel imitation learning method that utilizes task progress for better generalization to unseen states and goals.

Typical learning from demonstration (LfD) approaches [13, 35] greedily imitate the expert policy and thus suffer from accumulated errors causing a drift away from states seen in the demonstrations [38]. To make the imitation policy more robust to states not in demonstrations, adversarial imitation learning methods [14, 17] encourage the agent to stay near the expert trajectories using a learned reward that distinguishes expert and agent behaviors. However, such learned reward functions often overfit to the expert demonstrations by learning spurious correlations between task-irrelevant features and expert/agent labels [52], and thus suffer from generalization to slightly different initial and goal configurations from the ones seen in the demonstrations (e.g. holdout goal regions or larger perturbation in goal sampling).

To learn a more generalizable and informative reward from demonstrations, we propose an imitation learning from observation (LfO) method, which learns a task progress estimator and uses the task progress estimate as a dense reward for training a policy as illustrated in Figure 1. Unlike discriminating expert and agent behaviors by predicting *binary* labels in prior adversarial imitation learning methods, which is prone to overfitting to task-irrelevant features, the task progress estimator is

---

*Equal contribution. Correspondence to: `lee504@usc.edu` and `aszot3@gatech.edu`
†This work was partially carried out during an internship at NAVER AI Lab.
‡AI Advisor at NAVER AI Lab.

Figure 1: In goal-directed tasks, states on an expert trajectory have increasing proximity toward the goal as the expert makes progress towards fulfilling a task. Inspired by this intuition, we propose to learn a proximity function f_ϕ from expert demonstrations and agent experience, which predicts *goal proximity* (i.e. an estimate of temporal distance to the goal). Then, using this proximity function, we train a policy π_θ to progressively move to states with higher *predicted goal proximity (italicized numbers)* and eventually reach the goal. We alternate these two learning phases to improve both the proximity function and policy, leading to not only better generalization but also superior performance.

required to learn more task-relevant information to precisely predict the task progress on a *continuous* scale. Hence, it can generalize better to unseen states and provide more informative rewards.

As a measure of progress in goal-directed tasks, we define *goal proximity*, which is an estimate of temporal distance to the goal (i.e. the number of actions required to reach the goal) and entails all semantic information about how to reach the goal. We then train a *proximity function* to predict the goal proximity from expert demonstrations and agent experience. This proximity function acts as a dense reward to guide a reinforcement learning agent to reach states with high proximity, leading to the goal. In this paper, we focus on learning the proximity function and policy in a state space shared by the expert and learner, and leave generalizing to different embodiments as future work.

However, the predicted goal proximity can still be inaccurate on states not in the demonstrations, resulting in unstable policy learning. To improve the accuracy of the proximity function, we continually update it with trajectories from both the expert and learning agent. In addition, we penalize trajectories with the uncertainty of the proximity prediction to prevent the policy from exploiting inaccurate high proximity predictions. By leveraging the agent experience and predicting proximity function uncertainty, the proposed method achieves more efficient and stable policy learning.

The main contribution of this paper is an LfO algorithm for goal-directed tasks with better generalization to new goals or states not in demonstrations using goal proximity that informs an agent of the task progress. Together with a difference-based reward and uncertainty penalty of goal proximity estimation, our method provides more informative and robust rewards. Our extensive experiments show that the policy learned with the goal proximity function generalizes better than the state-of-the-art LfO algorithms on various goal-directed tasks, including navigation, locomotion, and robotic manipulation. Moreover, our method shows comparable results with LfD methods which learn from expert actions and a goal-conditioned imitation learning method which uses a sparse task reward.

2 Related Work

Imitation learning [39] aims to leverage expert demonstrations to acquire skills. While behavioral cloning [35] is simple but effective with a large number of demonstrations, it suffers from compounding errors caused by covariate shift [38]. On the other hand, inverse reinforcement learning (IRL) [1, 29, 51] estimates the underlying reward from demonstrations and trains a policy through reinforcement learning (RL) with this reward, which can better handle the compounding errors. Specifically, generative adversarial imitation learning (GAIL) [17] shows improved demonstration efficiency by training a discriminator to distinguish expert and agent transitions and using the discriminator output as a reward for policy training. GoalGAIL [9] further improves sample efficiency for goal-directed tasks by relabeling transitions [2] and using true environment rewards.

While these imitation learning algorithms require expert actions, imitation learning from observation (LfO) approaches learn from state-only demonstrations, such as videos and kinesthetic demonstrations.

To imitate demonstrations without expert actions, inverse dynamics models [30, 33, 46], reachability functions [23], or learned reward functions [11, 26, 41, 42] can be learned and used for policy training, but training such models requires a large amount of quality data or additional test-time demonstrations. On the other hand, state-only adversarial imitation learning [47] can imitate from a few demonstrations.

However, in such adversarial imitation learning approaches, the discriminator tends to find spurious associations between task-irrelevant features and expert/agent labels [52]. This becomes problematic when the agent encounters unseen states and the discriminator erroneously assigns agent behaviors low scores based on these task-irrelevant features, providing a poor reward for the agent. To overcome finding spurious associations, in addition to discriminating expert and agent trajectories, we propose to also estimate the proximity to the goal, which requires more task-relevant information and thus generalizes better to new states.

Temporal progress estimation has shown its effectiveness as an auxiliary reward for RL [10, 24, 27] and decision making criteria [3, 6, 8]. However, these methods learn the progress estimator only from the given demonstrations. This hinders policy learning when the progress estimator fails to generalize to agent experience, allowing the agent to exploit inaccurate progress predictions for higher reward. Moreover, greedily choosing an action with the highest predicted temporal progress [3, 6, 8] could lead to low long-term returns. By incorporating online updates, uncertainty estimates, and a difference-based proximity reward, our method robustly learns from demonstrations to solve goal-directed tasks without access to expert actions or the true environment reward.

3 Method

In this paper, we address the problem of LfO for goal-directed tasks with a focus on generalization to states or goals not covered in the demonstrations. Adversarial LfO methods [47, 49] suggest learning a reward function that penalizes agent state transitions deviating from the expert trajectories. However, these learned reward functions often focus on task-irrelevant features [52] and do not generalize to states not in the demonstrations, leading to unsuccessful policy training.

To learn a generalizable reward, we propose to leverage task progress information freely available in demonstrations, in terms of *goal proximity*, which estimates temporal distance to the goal (i.e. number of actions required to reach the goal). Predicting precise goal proximity on a continuous scale, rather than simply distinguishing expert and agent states, requires the model to capture task-relevant information, allowing the proximity prediction to generalize to states not in the demonstrations (Section 3.2). Then, a policy learns to reach states with higher proximity prediction, leading to the goal (Section 3.3). Moreover, we propose to use the uncertainty of the proximity prediction to prevent the policy from exploiting over-optimistic proximity predictions and yielding undesired behaviors.

3.1 Preliminaries

We formulate our problem as a Markov decision process [44] defined through a tuple $(\mathcal{S}, \mathcal{A}, R, P, \rho_0, \gamma)$ of the state space $\mathcal{S}$, action space $\mathcal{A}$, reward function $R(s, a, s')$, transition distribution $P(s'|s, a)$, initial state distribution ρ_0, and discounting factor γ. We define a policy $\pi(a|s)$ that maps from a state s to an action a and correspondingly moves an agent to a new state s' according to the transition probability $P(s'|s, a)$. The policy is trained to maximize the sum of discounted rewards, $\mathbb{E}_{(s_0, a_0, \ldots, s_{T_i}) \sim \pi} \left[\sum_{t=0}^{T_i - 1} \gamma^t R(s_t, a_t, s_{t+1}) \right]$, where T_i is the variable episode length.

In imitation learning, the learner receives a fixed set of N expert demonstrations, $\mathcal{D}^e = \{\tau_1^e, \ldots, \tau_N^e\}$. In this paper, we specifically consider the LfO setup where each demonstration τ_i^e is a sequence of states. Moreover, we assume that goal information is explicitly or implicitly included in the state s, and all demonstrations are successful; therefore, the final state of each trajectory achieves the task goal.

3.2 Learning Goal Proximity Function

To effectively leverage expert demonstrations and generalize to new states or new goals, learning a generalizable reward function is essential. In goal-directed tasks, an estimate of how close an agent is to the goal can be utilized as a dense and direct learning signal. Moreover, predicting the

continuous goal proximity requires understanding the task structure and thus encourages finding more task-relevant features, resulting in better generalization.

Therefore, instead of learning to simply discriminate agent and expert trajectories, we propose to learn a *goal proximity function*, $f : \mathcal{S} \rightarrow [0, 1]$, which predicts *goal proximity* of a state s, which is a discounted value based on the temporal distance to the goal (i.e. inversely proportional to the number of actions required to reach the goal). In this paper, we define goal proximity as the exponentially discounted proximity $f(s_t) = \delta^{(T_i - t)}$, where $\delta \in (0, 1)$ is a discounting factor and T_i is the episode length. Note that the goal proximity function measures the temporal distance, not the spatial distance, between the current and goal states. Therefore, a single proximity value can entail all information about the task, goal, and any roadblocks. There are alternative ways to define goal proximity, such as linearly discounted proximity [24] and ranking-based proximity [5, 6]. But, in this paper, we use the exponentially discounted proximity as it performs better across most tasks (see appendix, Figure 8).

We train a goal proximity function f_ϕ parameterized by ϕ to minimize the following objective:

$$\mathcal{L}_\phi = \mathbb{E}_{\tau_i^e \sim \mathcal{D}^e, s_t \sim \tau_i^e} \left[f_\phi(s_t) - \delta^{(T_i - t)} \right]^2. \tag{1}$$

Since the goal proximity function trained only on expert demonstrations can overfit to the data, we further train the goal proximity function with online agent experience by setting the target proximity of states in agent trajectories to 0, similar to adversarial imitation learning methods [17]:

$$\mathcal{L}_\phi = \mathbb{E}_{\tau_i^e \sim \mathcal{D}^e, s_t \sim \tau_i^e} \left[f_\phi(s_t) - \delta^{(T_i - t)} \right]^2 + \mathbb{E}_{\tau \sim \pi_\theta, s_t \sim \tau} \left[f_\phi(s_t) \right]^2. \tag{2}$$

By learning to predict the goal proximity, f_ϕ not only learns to discriminate agent and expert trajectories (i.e. predict 0 proximity for an agent trajectory and positive proximity for an expert trajectory) but also acquires the task information about temporal progress entailed in the trajectories. From this freely available additional supervision, the proximity function is required to learn task-relevant features. Hence, the resulting proximity function generalizes better to unseen states and provides more informative learning signals to the policy as empirically shown in Section 4.

Due to the lack of environment reward, *successful* agent experience is also used as negative examples for proximity function training, and thus the proximity function learns to predict low goal proximity even for successful trajectories. However, early stopping and learning rate decay can ease this problem [52], and the optimal proximity function still outputs the average of expert and agent labels, which is $\delta^{(T_i - t)}/2$ for ours and 0.5 for GAIL [14].

3.3 Training Policy with Proximity Reward

In a goal-directed task, a policy π_θ aims to get close to and eventually reach the goal. We can formalize this objective as maximizing the difference-based *proximity reward* R_ϕ, the increase in goal proximity, at every timestep, which corresponds to making consistent progress towards the goal:

$$R_\phi(s_t, s_{t+1}) = f_\phi(s_{t+1}) - f_\phi(s_t). \tag{3}$$

Given the proximity reward R_ϕ, the policy is trained to maximize the expected discounted return:

$$\mathbb{E}_{(s_0, \ldots, s_{T_i}) \sim \pi_\theta} \left[\sum_{t=0}^{T_i - 1} \gamma^t R_\phi(s_t, s_{t+1}) \right]. \tag{4}$$

However, a policy trained with the proximity reward can sometimes acquire undesired behaviors by exploiting over-optimistic proximity predictions on states not seen in the expert demonstrations. This becomes critical when the expert demonstrations are limited and cannot sufficiently cover the state space. To avoid inaccurate predictions leading an agent to undesired states, we propose to (1) fine-tune the proximity function with online agent experience to reduce optimistic proximity predictions; and (2) penalize agent trajectories with high uncertainty in goal proximity prediction.

To alleviate the effect of inaccurate proximity estimation in policy training, we discourage the policy from visiting states with uncertain proximity estimates. Specifically, we model the uncertainty $U_\phi(s_t)$ as the disagreement of an ensemble of proximity functions by computing the standard deviation of their outputs [22, 31]. Then, we use this estimated uncertainty to penalize exploration of states with

(a) NAVIGATION   (b) MAZE2D   (c) ANT REACH (d) FETCH PICK (e) FETCH PUSH (f) HAND ROTATE

Figure 2: Six goal-directed tasks are used for our experiments. (a) The agent must navigate across rooms to reach the goal. (b) The agent needs to navigate the maze to reach the goal. (c) The ant agent must walk towards the flag. (d, e) The robotic arm is required to pick up or push the block towards the goal (red). (f) The dexterous robot hand needs to rotate the block in-hand to the desired rotation.

high uncertainty. The proximity estimate $f_\phi(s_t)$ is the average prediction of the ensemble. With the uncertainty penalty, the modified proximity reward can be written as:

$$R_\phi(s_t, s_{t+1}) = f_\phi(s_{t+1}) - f_\phi(s_t) - \lambda \cdot U_\phi(s_{t+1}), \tag{5}$$

where λ is a tunable hyperparameter to balance the proximity reward and uncertainty penalty. A larger λ results in more conservative exploration outside the states covered by the expert demonstrations.

In summary, we propose to learn a goal proximity function to robustly provide a reward signal on states or goals not covered by demonstrations. We train the goal proximity function to estimate how close the current state is to the goal, and train a policy to maximize the goal proximity while avoiding states with uncertain proximity predictions. We jointly train the proximity function and policy as described in appendix, Algorithm 1.

4 Experiments

In this paper, we propose a generalizable LfO algorithm that leverages task progress information (i.e. goal proximity) freely acquired from demonstrations. Hence, in our experiments, we aim to answer the following questions: (1) Does our method lead to policies that generalize better to states and goals not in the demonstrations? (2) How does our method's efficiency and performance compare against prior work in LfO and LfD? (3) What factors contribute to the performance of our method? To answer these questions we consider diverse goal-directed tasks: navigation, locomotion, and robotic manipulation.

4.1 Experimental Setup

To demonstrate the improved generalization capabilities of policies trained with the goal proximity, we benchmark our method under two different setups: expert demonstrations are collected from (1) only a fraction of the possible initial and goal states (e.g. 25%, 50% coverage) and (2) initial states with smaller amounts of noise. These generalization experimental setups serve to mimic the reality that expert demonstrations may be collected in a different setting from agent learning. For instance, due to the cost of demonstration collection, the demonstrations may poorly cover the state space, which corresponds to the setup (1). Likewise, in the setup (2), demonstrations may be collected in controlled circumstances with little noise. Then, an agent in an actual environment would encounter more noise than presented in the demonstrations, leading to a wider initial state distribution.

In our experiments, we use the discounting factor $\delta = 0.95$ for the goal proximity. We use an ensemble of 5 proximity functions to model uncertainty across all tasks. For policy optimization, we use PPO [40], which is widely used in LfO and LfD methods, and its hyperparameters are tuned for each method and task (see appendix, Table 2). Each baseline implementation is verified against the results reported in its original paper. We train each task with 5 random seeds and report mean and standard deviation. See Section F for further implementation details.

4.2 Baselines

We compare our method to the state-of-the-art methods in LfO (BCO, GAIfO, GAIfO-s) as well as LfO with reward (GoalGAIL) and LfD (BC, GAIL, SQIL) approaches, which require additional supervisions, such as task reward and expert actions:

Figure 3: Goal completion rates of our method and baselines. The agent must generalize to a wider state and goal distributions than seen in the demonstrations. Demonstrations cover only a part of states (a, b) or are generated with less noise (c, d, e, f). Our method learns more stably, faster, and achieves higher goal completion rates than prior LfO methods. Moreover, our method outperforms the LfD baselines in NAVIGATION, FETCH tasks, and MAZE2D, and achieves comparable results in ANT REACH. GoalGAIL performs well in MAZE2D since it can easily acquire environment rewards.

- **BCO** [46] learns an inverse dynamics model from environment interaction to provide action labels in demonstrations for behavioral cloning.
- **GAIfO** [47] trains a discriminator with state transitions (s, s'), instead of (s, a) as in GAIL.
- **GAIfO-s** [49] learns a discriminator based off a single state, not a state transition as with GAIfO.
- **GoalGAIL** [9] uses goal reaching reward and relabeling to improve sample efficiency of GAIL.
- **BC** [35] fits a policy to the demonstration state-action pairs (s, a) with supervised learning.
- **GAIL** [17] is an adversarial imitation learning with a discriminator trained on state-action pairs (s, a) from both expert and agent.
- **SQIL** [37] is a sample-efficient imitation learning method which adds expert transitions (s, a) with reward 1 to the replay buffer of off-policy RL and assigns 0 reward to all agent experience.

4.3 Navigation

We first examine the NAVIGATION task between four rooms shown in Figure 2a to demonstrate generalization capability of our method, and visualize the learned goal proximity function. The agent observes the $19 \times 19 \times 4$ 2D map of the maze and moves in one of four directions. In this task, the agent starting and goal positions are randomly sampled (see an example in appendix, Figure 12). We provide 250 expert demonstrations obtained using a shortest path algorithm. During demonstration collection, we hold out 0%, 25%, 50%, and 75% of the possible agent starting and goal positions uniformly at random. In contrast, during agent learning and evaluation, start and goal positions are sampled from all possible positions.

Figure 3a shows that our method achieves near 100% success rate in 2M environment steps even with demonstrations only covering 25% of starting and goal states, while other LfO methods fail to learn the task. Although BC, GAIL, and BCO achieve success rates of about 60%, 30%, and 35%, respectively, they show limited generalization to unseen configurations. This result shows that the learned goal proximity function generalizes well to unseen configurations.

Figure 4d visualizes the proximity function trained with 50% coverage demonstrations and 250k steps of agent training. Our proximity function predicts high proximity near the goal and lower proximity when the agent is farther away from the goal. This demonstrates that our proximity function can learn

| (a) 100% coverage | (b) 75% coverage | (c) 50% coverage | (d) Proximity heatmap |

Figure 4: Analyzing the effect of improved generalization as the cause for performance increase in our method. (a) Performance with no generalization required. (b, c) Performance with increasing difference between start and goal distributions of demonstrations and agent learning. (d) Visualization of the learned proximity function for a fixed goal (green) in the 50% coverage case. The proximity function was evaluated for every state on the grid; lighter cells correspond to states with higher estimated proximity to the goal.

the semantic, non-euclidean relationship between high-dimensional observations and goals. Since the proximity function is conditioned on the state, similar states are likely to have similar predicted proximity, and thus the proximity function learns a spatially consistent measure of proximity from temporal supervision. Moreover, as the task progress is a relative position within a trajectory, both slow and fast demonstrations result in the same task progress. More visualizations can be found in appendix, Section E.

Finally, we investigate our hypothesis that the goal proximity function allows for greater generalization, which results in better performance with smaller demonstration coverages. We compare the cases where extreme (25% coverage), moderate (50% and 75% coverage), and no generalization (100% coverage) are required. Figure 3a and Figure 4 show that our method consistently achieves almost 100% success rates in 2M steps across all coverages and is not as affected by the increasingly difficult generalization settings as baselines. In contrast, all LfO baselines struggle to learn the task when the demonstrations do not cover all configurations. LfD methods also shows limited generalization in 25% coverage since the discriminator can easily learn spurious associations between the actions and labels, which hurts generalization to new actions. This supports our hypothesis that the goal proximity function is able to capture the task structure and therefore, generalize better to unseen configurations.

4.4 Maze2D

We further evaluate our method in MAZE2D [15] with the medium maze, a continuous version of NAVIGATION. The agent observes its position, velocity, and goal position, and then outputs an x- and y-velocity to navigate the maze. The agent starting and goal positions are randomly sampled. We collect 100 demonstrations (18k transitions) using a planner from Fu et al. [15].

Our method outperforms LfO baselines over all demonstration coverages (see appendix, Figure 7). More importantly, in the low coverage case, our method outperforms BC, which has access to expert actions, as shown in Figure 3b. This could be because our proximity function generalizes well whereas BC is not robust to unseen states under small demonstration coverages. On the other hand, GoalGAIL shows the best performance regardless of coverages as the task can be easily solved with the sparse reward and goal relabeling, which is not available for our method and other baselines.

4.5 Ant Locomotion

In ANT REACH [16], the quadruped ant is tasked to reach a randomly generated goal, which is along the perimeter of a half circle of radius 5 m centered around the ant (see Figure 2c). The 132D state consists of joint angle, velocity, contact force, and the goal position relative to the agent. We collect 1k demonstrations (25k transitions) using the pre-trained policy (trained for 40M steps). When demonstrations are collected, no noise is added to the initial pose of the ant whereas random noise is added to the initial pose during policy learning, which requires the reward functions to generalize to unseen states.

(a) NAVIGATION 50% (b) FETCH PICK 1.75x (c) FETCH PUSH 1.75x (d) ANT REACH 0.03

Figure 5: Analysis of the contribution of goal proximity function, uncertainty penalty, and reward formulation to the performance. "Prox" uses the goal proximity function while "GAIfO-s" does not. "+Diff" uses $R(s_t, s_{t+1}) = f(s_{t+1}) - f(s_t)$ and "+Abs" uses $R(s_t) = f(s_t)$ as a reward. "+Uncert" adds the uncertainty penalty to the reward. "+Ensemble" uses an ensemble for the discriminator.

In Figure 3c, with 0.05 added noise, our method achieves 35% success rate while BCO, GAIfO, and GAIfO-s achieve 1%, 2%, and 7%, respectively. This result illustrates the importance of learning proximity as opposed to discriminating expert and agent states for generalization to unseen states. The performance of GAIfO and GAIfO-s drops drastically with larger joint angle randomness as shown in appendix, Figure 7. As ANT REACH is not as sensitive to noise in actions compared to other tasks, BC and GAIL show superior results but our method still achieves comparable performance.

4.6 Robotic Manipulation

We evaluate our method in two robotic manipulation tasks with the 7-DoF Fetch robotics arm: FETCH PICK and FETCH PUSH [34]. The robot must grasp and move a block to a target position for FETCH PICK, and push a block to a target position for FETCH PUSH. The 16D state consists of the gripper pose, object pose, the gripper pose relative to the object, and goal position. Both the initial and target positions of the block are randomly initialized. We generate 1k demonstrations using a hard-coded policy, consisting of 33k and 28k transitions for FETCH PICK and FETCH PUSH, respectively. The policy is trained in an environment with larger noise applied to the starting and target block positions.

In FETCH PICK, our method achieves about 80% success rate outperforming all baselines, despite LfD methods learning with expert actions (see Figure 3d). The best performing baseline BC only obtains around 40% success rate. The high variance in performance between seeds comes from the difficulty of learning the grasping behavior with large noise. In FETCH PUSH, our method outperforms baselines in generalization to unseen states by achieving more than 90% success rate (see Figure 3e). This shows that our proximity function is able to accelerate policy learning in continuous control environments with superior generalization capability.

4.7 Dexterous Hand Manipulation

We evaluate our method in a challenging in-hand object manipulation task [34], HAND ROTATE as shown in Figure 2f. In HAND ROTATE, a 24-DoF Shadow Dexterous Hand must in-hand rotate a block to a target z-axis rotation. The state consists of the agent's joint angles and velocities, object pose, and the target rotation. Due to the high dimension of the state (68D) and action space (20D), HAND ROTATE is extremely challenging for both RL and IL without dense reward. We therefore ease the task by constraining the possible initial and target z rotations to $\left[-\frac{\pi}{32}, \frac{\pi}{32}\right]$ and $\left[\frac{\pi}{3}, \frac{\pi}{2}\right]$. We collect 10k demonstrations (98k transitions) using a pre-trained policy (trained for 8M steps).

In Figure 3f, GAIfO-s performs well because its reward function is biased to provide large negative rewards encouraging the agent to end the episode early which is only possible by succeeding. In contrast, our difference-based reward is designed to provide positive rewards, which does not exploit this task property, and performs poorly even with an additional constant penalty -0.005 every step. To test the generalization capability of our proximity function, we additionally examine a variant of our method (Ours-GAIL), which uses the same reward formulation as GAIfO-s, $\log f_\phi(s_t) - \log(1 - f_\phi(s_t))$. With this biased reward function, our method outperforms both GAIfO-s and GAIL, which verifies the benefit of our proximity function in generalization to noisy environments. While BC achieves the high success rate with 10x more demonstrations compared to other tasks, SQIL shows poor performance due to the lack of the negative reward bias.

| (a) Uncertainty penalty λ | (b) Proximity function design | (c) Baseline regularization |

Figure 6: Ablation of our method and comparison to a regularized baseline on FETCH PICK 1.75x to investigate (a) effects of uncertainty penalty coefficient λ; (b) effects of proximity function design and online/offline training; and (c) generalization capability of a regularization technique and our proximity function.

4.8 Ablation Study

Dissecting proximity reward We analyze the contribution of the proximity function, reward formulation, and uncertainty penalty to our method's performance across four tasks in Figure 5. Adding uncertainty to GAIfO-s (GAIfO-s+Uncert) produced a 18.4% boost in average success rate compared to regular GAIfO-s. Proximity supervision, without the uncertainty penalty, resulted in a 66.7% increase in average performance over GAIfO-s with the difference-based reward $f(s_{t+1}) - f(s_t)$ (Prox+Diff) and 25.8% with the absolute reward $f(s_t)$ (Prox+Abs). This higher performance means **modeling proximity is more important than the uncertainty penalty** for our method.

Although we choose difference-based reward with exponentially discounted goal proximity, the goal proximity can be either linear or exponential discounting, and both can be used for either a difference-based or absolute reward, which perform differently across tasks. For example, the difference-based proximity reward is better for policy learning than the absolute proximity reward except on ANT REACH and HAND ROTATE, where the bias of the absolute reward [20] helps the agent survive longer and reach the goal. This is a fundamental problem in IRL, where inductive bias in reward functions is crucial and varies by tasks [20]. Nonetheless, our extensive experiments (Figure 5, 6b, 8) show that our goal proximity reward provides a more stable and generalizable learning signal than baselines under the same reward bias.

Moreover, we found that **the uncertainty penalty and proximity function have a synergistic interaction**. Combining both the proximity and uncertainty gives a 68.7% increase with the difference-based reward (Prox+Diff+Uncert) and 26.4% increase with the absolute reward (Prox+Abs+Uncert). The uncertainty penalty is especially important for the proximity function as it models fine-grain temporal information where inaccuracies can be easily exploited, as opposed to the binary classification of other adversarial imitation learning methods.

Ensemble networks Next, we study if the robustness of our method comes from the use of ensemble networks or task progress. We verify this by applying ensemble of discriminators to the best performing baseline, GAIfO-s. Figure 5 shows that GAIfO-s with ensemble networks (GAIfO-s+Ensemble) only achieves 19.6% higher success rates, but this is still 39.7% lower than our method on average. Therefore, **the use of task progress is key** to learn a generalizable reward, not the use of ensemble networks.

Regularization of discriminators In our experiments above, we show that our goal proximity function is generalizable to unseen states and goals, which leads to successful imitation learning. We verify whether standard regularization techniques, such as spectral normalization [28], can also provide the same generalization benefit. In the FETCH PICK 1.75x noise setting (Figure 6c), GAIfO-s without regularization struggles to learn, achieving only a 1.43% success rate. Not surprisingly, applying spectral normalization [28] to the discriminator of GAIfO-s improves the success rate to 14.56%, which suggests that generalization of the reward function is key to imitation learning with insufficient demonstration coverage. Despite this improvement, our method performs much better at 75.45% success. In summary, **predicting goal proximity enables significantly better**

generalization than regularization on the baselines. Figure 10 in appendix show similar results across most other tasks.

Uncertainty penalty coefficient λ In Figure 6a, we investigate how the uncertainty penalty coefficient λ affects the performance, showing that our method performs the best with $\lambda = 0.001$. A higher or lower λ yields worse performance since a higher λ prevents exploring unseen states while a lower λ encourages exploiting uncertain predictions.

Proximity function training   In Figure 6b, we test the importance of online and offline training of the proximity function. Note that we update the policy with online interactions in both scenarios. The result shows that **online proximity function update is crucial** for our method as the agent fails without online update. Meanwhile, no pre-training, Ours (No Offline), slows down training. Similar results can be observed across all tasks (see appendix, Figure 8).

Our ablation experiments show that (1) goal proximity generalizes better and is more informative for policy learning; (2) the difference-based proximity reward generally performs better than the absolute one; and (3) the uncertainty penalty boosts the performance of our method. In conclusion, all three components of proximity, difference-based reward, and uncertainty are crucial for our method.

5   Conclusion

We propose a generalizable learning from observation (LfO) method inspired by how humans acquire generalizable task information and learn skills in new situations by watching others performing goal-directed tasks. We specifically propose to use task progress, which is intuitive and readily available task information that can guide an agent closer to the goal. Inspired by this insight, we learn a goal proximity function and utilize it as a dense reward for policy learning. We hypothesize that predicting the task progress requires more task-relevant information than estimating an occupancy measure [17], and thus generalizes to states not seen in the demonstrations. Our extensive experiments on navigation, locomotion, and robotic manipulation show that our goal proximity function improves generalization in imitation learning, which results in better performance compared to LfO methods and comparable performance with LfD methods which learn from expert actions.

In imitation learning, the *generalization* ability can include generalization to (1) unseen states and goals, (2) new visual environments (e.g. background), (3) unseen objects, and (4) different embodiments (e.g. humans to robots or different dynamics). In this paper, we focus on generalization to (1) unseen states and goals. This is especially important in imitation learning when the number of demonstrations is not sufficient to cover all possible states and goals. This is very common in imitation learning due to costly demonstration collection. Our approach suggests an effective way of using the demonstrations with limited coverage by learning the generalizable goal proximity reward.

Generalization to a different environment and embodiment is another important research direction and this is indeed our immediate future work. Recent advances in generalizable representation learning [42, 43, 48], robust policy learning [19, 21], and cross-domain correspondence [50] enable us to train a policy that generalizes to new environments and embodiments. Yet, these approaches are orthogonal and complementary to our method as our goal proximity function can be trained on top of the learned representations [19, 21, 42, 43, 48, 50]. We believe that our method can be combined with these approaches and improve their performance with better demonstration efficiency and additional supervision about task progress.

Societal Impact   Our method aims to increase the ability of autonomous agents, such as robots and self-driving cars, to imitate experts (e.g. humans) from observation alone. This enables autonomous agents to utilize data even without expert actions, such as kinesthetic demonstrations and video demonstrations. Ultimately, it could allow autonomous agents to acquire skills even from watching Youtube videos. Since our method learns from experts, it inherits any biases of the demonstrator, such as sub-optimal or unsafe behaviors. Additionally, demonstrations are an easy and intuitive way to specify behaviors, its potential for automation is a threat to job security. However, we overall see enormous benefit with this technology increasing human quality of life and automating difficult jobs.

Acknowledgments and Disclosure of Funding

This research is partially supported by the Annenberg Fellowship from USC and the funding from National Science Foundation (NSF NRI-2024768) and NAVER AI Lab. We thank members of the USC CLVR lab for constructive feedback.

References

[1] P. Abbeel and A. Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *International Conference on Machine Learning*, 2004.

[2] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. In *Advances in Neural Information Processing Systems*, 2017.

[3] D. Angelov, Y. Hristov, M. Burke, and S. Ramamoorthy. Composing diverse policies for temporally extended tasks. *IEEE Robotics and Automation Letters*, 5(2):2658–2665, 2020.

[4] H. Bekkering, A. Wohlschlager, and M. Gattis. Imitation of gestures in children is goal-directed. *The Quarterly Journal of Experimental Psychology: Section A*, 53(1):153–164, 2000.

[5] D. S. Brown, W. Goo, P. Nagarajan, and S. Niekum. Extrapolating beyond suboptimal demonstrations via inverse reinforcement learning from observations. *International Conference on Machine Learning*, 2019.

[6] M. Burke, K. Lu, D. Angelov, A. Straižys, C. Innes, K. Subr, and S. Ramamoorthy. Learning robotic ultrasound scanning using probabilistic temporal ranking. *arXiv preprint arXiv:2002.01240*, 2020.

[7] M. Chevalier-Boisvert, L. Willems, and S. Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

[8] H.-T. L. Chiang, J. Hsu, M. Fiser, L. Tapia, and A. Faust. Rl-rrt: Kinodynamic motion planning via learning reachability estimators from rl policies. *IEEE Robotics and Automation Letters*, 2019.

[9] Y. Ding, C. Florensa, M. Phielipp, and P. Abbeel. Goal-conditioned imitation learning. In *Neural Information Processing Systems*, 2019.

[10] A. D. Edwards and C. L. Isbell. Perceptual values from observation. *arXiv preprint arXiv:1905.07861*, 2019.

[11] A. D. Edwards, C. L. Isbell, and A. Takanishi. Perceptual reward functions. *arXiv preprint arXiv:1608.03824*, 2016.

[12] C. Finn, P. Christiano, P. Abbeel, and S. Levine. A connection between generative adversarial networks, inverse reinforcement learning, and energy-based models. *NeurIPS Workshop on Adversarial Training*, 2016.

[13] C. Finn, X. Y. Tan, Y. Duan, T. Darrell, S. Levine, and P. Abbeel. Deep spatial autoencoders for visuomotor learning. In *IEEE International Conference on Robotics and Automation*, 2016.

[14] J. Fu, K. Luo, and S. Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *International Conference on Learning Representations*, 2018.

[15] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[16] D. Ghosh, A. Singh, A. Rajeswaran, V. Kumar, and S. Levine. Divide and conquer reinforcement learning. In *International Conference on Learning Representations*, 2018.

[17] J. Ho and S. Ermon. Generative adversarial imitation learning. In *Advances in Neural Information Processing Systems*, 2016.

[18] N. J. Hodges, A. M. Williams, S. J. Hayes, and G. Breslin. What is modelled during observational learning? *Journal of sports sciences*, 25(5):531–545, 2007.

[19] S. James, A. J. Davison, and E. Johns. Transferring end-to-end visuomotor control from simulation to real world for a multi-stage task. In *Conference on Robot Learning*, pages 334–343, 2017.

[20] I. Kostrikov, K. K. Agrawal, D. Dwibedi, S. Levine, and J. Tompson. Discriminator-actor-critic: Addressing sample inefficiency and reward bias in adversarial imitation learning. In *International Conference on Learning Representations*, 2019.

[21] A. Kumar, Z. Fu, D. Pathak, and J. Malik. Rma: Rapid motor adaptation for legged robots. In *Robotics: Science and Systems*, 2021.

[22] B. Lakshminarayanan, A. Pritzel, and C. Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, 2017.

[23] Y. Lee, E. S. Hu, Z. Yang, and J. J. Lim. To follow or not to follow: Selective imitation learning from observations. In *Conference on Robot Learning*, 2019.

[24] Y. Lee, S.-H. Sun, S. Somasundaram, E. S. Hu, and J. J. Lim. Composing complex skills by learning transition policies. In *International Conference on Learning Representations*, 2019.

[25] T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

[26] Y. Liu, A. Gupta, P. Abbeel, and S. Levine. Imitation from observation: Learning to imitate behaviors from raw video via context translation. In *IEEE International Conference on Robotics and Automation*, 2018.

[27] M. J. Mataric. Reward functions for accelerated learning. In *Machine learning proceedings 1994*, pages 181–189. Elsevier, 1994.

[28] T. Miyato, T. Kataoka, M. Koyama, and Y. Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.

[29] A. Y. Ng and S. J. Russell. Algorithms for inverse reinforcement learning. In *International Conference on Machine Learning*, 2000.

[30] S. Niekum, S. Osentoski, G. Konidaris, S. Chitta, B. Marthi, and A. G. Barto. Learning grounded finite-state representations from unstructured demonstrations. *The International Journal of Robotics Research*, 34(2):131–157, 2015.

[31] I. Osband, C. Blundell, A. Pritzel, and B. Van Roy. Deep exploration via bootstrapped dqn. In *Advances in Neural Information Processing Systems*, 2016.

[32] A. Paszke, S. Gross, S. Chintala, G. Chanan, E. Yang, Z. DeVito, Z. Lin, A. Desmaison, L. Antiga, and A. Lerer. Automatic differentiation in PyTorch. In *NIPS Autodiff Workshop*, 2017.

[33] D. Pathak, P. Mahmoudieh, M. Luo, P. Agrawal, D. Chen, F. Shentu, E. Shelhamer, J. Malik, A. A. Efros, and T. Darrell. Zero-shot visual imitation. In *International Conference on Learning Representations*, 2018.

[34] M. Plappert, M. Andrychowicz, A. Ray, B. McGrew, B. Baker, G. Powell, J. Schneider, J. Tobin, M. Chociej, P. Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.

[35] D. A. Pomerleau. Alvinn: An autonomous land vehicle in a neural network. In *Advances in Neural Information Processing Systems*, 1989.

[36] R. Rafailov, T. Yu, A. Rajeswaran, and C. Finn. Visual adversarial imitation learning using variational models. *arXiv preprint arXiv:2107.08829*, 2021.

[37] S. Reddy, A. D. Dragan, and S. Levine. SQIL: Imitation learning via reinforcement learning with sparse rewards. In *International Conference on Learning Representations*, 2020.

[38] S. Ross, G. Gordon, and D. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *International Conference on Artificial Intelligence and Statistics*, 2011.

[39] S. Schaal. Learning from demonstration. In *Advances in Neural Information Processing Systems*, 1997.

[40] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[41] P. Sermanet, K. Xu, and S. Levine. Unsupervised perceptual rewards for imitation learning. *Robotics: Science and Systems*, 2017.

[42] P. Sermanet, C. Lynch, Y. Chebotar, J. Hsu, E. Jang, S. Schaal, S. Levine, and G. Brain. Time-contrastive networks: Self-supervised learning from video. In *IEEE International Conference on Robotics and Automation*, 2018.

[43] A. Srinivas, A. Jabri, P. Abbeel, S. Levine, and C. Finn. Universal planning networks: Learning generalizable representations for visuomotor control. In *International Conference on Machine Learning*, pages 4732–4741, 2018.

[44] R. S. Sutton. *Temporal credit assignment in reinforcement learning*. PhD thesis, University of Massachusetts Amherst, 1984.

[45] G. Swamy, S. Choudhury, J. A. Bagnell, and S. Wu. Of moments and matching: A game-theoretic framework for closing the imitation gap. In *International Conference on Machine Learning*, pages 10022–10032, 2021.

[46] F. Torabi, G. Warnell, and P. Stone. Behavioral cloning from observation. In *International Joint Conference on Artificial Intelligence*, 2018.

[47] F. Torabi, G. Warnell, and P. Stone. Generative adversarial imitation from observation. *arXiv preprint arXiv:1807.06158*, 2018.

[48] T. Wang, R. Liao, J. Ba, and S. Fidler. Nervenet: Learning structured policy with graph neural networks. In *International Conference on Learning Representations*, 2018.

[49] C. Yang, X. Ma, W. Huang, F. Sun, H. Liu, J. Huang, and C. Gan. Imitation learning from observations by minimizing inverse dynamics disagreement. In *Neural Information Processing Systems*, 2019.

[50] G. Zhang, L. Zhong, Y. Lee, and J. J. Lim. Policy transfer across visual and dynamics domain gaps via iterative grounding. In *Robotics: Science and Systems*, 2021.

[51] B. D. Ziebart, A. L. Maas, J. A. Bagnell, and A. K. Dey. Maximum entropy inverse reinforcement learning. In *Association for the Advancement of Artificial Intelligence*, 2008.

[52] K. Zolna, S. Reed, A. Novikov, S. G. Colmenarej, D. Budden, S. Cabi, M. Denil, N. de Freitas, and Z. Wang. Task-relevant adversarial imitation learning. In *Conference on Robot Learning*, 2020.

A   Comparison with GAIL and Its Variants

Our method shares a similar adversarial training process with GAIL [17]. First of all, similar to the discriminator in GAIfO-s [49], our proximity function takes only the current state as input. However, rather than training the discriminator to classify expert from agent, we train the proximity function to regress to the proximity labels which are 0 for agent and the time discounted value between 0 and 1 for expert. Our reward formulation also differs from GAIL approaches which gives a log probability reward based on the discriminator output. We instead incorporate a proximity estimation uncertainty penalty and a difference-based proximity reward as shown in Equation 3.

B   Failure of GAIfO and SQIL

We found that SQIL training is unstable and often collapses after some amount of training steps (see Ant experiments in Figure 7). Similar trends can be observed in the original paper [37] and other recent papers [36, 45]. We hypothesize that GAIfO easily overfits to demonstrations compared to other baselines (e.g. GAIfO-s) since GAIfO conditions its discriminator on both the current and next observations.

We evaluated these methods with the demonstrations from the same initial and goal state distributions in the first column of Figure 7. Even though they are trained for the same goal distributions as the demonstrations, they still overfit to the demonstration states and thus cannot generalize to unseen states encountered during online rollouts for most tasks.

C   Analysis on Generalization of Our Method and Baselines

By learning to predict the goal proximity, the proximity function not only learns to discriminate expert and agent states but also models task progress, which encourages acquiring task-relevant information. With this additional supervision on learning goal proximity, we expect the proximity function to provide a more informative learning signal to the policy and generalize better to unseen states than baselines which easily overfit the reward function to expert demonstrations. To analyze how well our method and the baselines can generalize to unseen states, we vary the difference between the states encountered in expert demonstrations and agent training as described in Section 4.

One way we vary the difference between expert demonstrations and agent learning is restricting the expert demonstrations to only cover parts of the state space. For NAVIGATION and MAZE2D, we show results for expert demonstrations that cover 100%, 75%, 50%, and 25% of the state space. For the discrete state space in NAVIGATION, we restrict expert demonstrations to the fraction of possible agent start and goal configurations. For MAZE2D, we break the maze into 6×6 cells and sample a part of the cells for starting states and another part for goal states.

Likewise, we also measure generalization by adding more noise to the initial state during agent learning. On FETCH PICK, FETCH PUSH, ANT REACH, and HAND ROTATE we show results for four different noise settings. For the two FETCH tasks, the 2D sampling region of the object and goal is scaled by the noise factor. For ANT REACH, uniform noise scaled by the noise factor is added to the initial joint angles, whereas the demonstrations have no noise. For HAND ROTATE, uniform noise scaled by the noise factor is added to the possible initial and target object pose. If our method allows for greater generalization from the expert demonstrations, our method should perform well even under states different than those in the expert demonstrations.

The results of our method and baselines across varying degrees of generalization are shown in Figure 7. Note that the results in the main paper are for 1.75x noise in FETCH PICK and FETCH PUSH, 0.05 noise in ANT REACH, 0.35 noise in HAND REACH, and 25% coverage in Maze2D. Across both harder and easier generalization, our method demonstrates more consistent performance compared to baseline methods. While GAIfO-s performs well on high coverage or low noise, which require little generalization in agent learning, its performance deteriorates as the expert demonstration coverage decreases.

Figure 7: Analyzing generalization to unseen states from expert demonstrations. NAVIGATION and MAZE2D tasks are tested with different coverages of state spaces in demonstrations, while FETCH, ANT REACH, and HAND ROTATE tasks are tested in more noisy environments. The number indicates the amount of additional noise in agent learning compared to that in the expert demonstrations, with more noise requiring harder generalization. The noise level increases from left to right.

D   Further Ablations

We include additional ablations to further highlight the advantages of our main proposed method over its variants. We evaluate against the same ablations proposed in the main paper (Figure 6b), but across all environments. We present all these results in Figure 8.

Our method shows the best performance in the majority of environments. In all tasks, incorporating online updates is crucial since the proximity function can overfit to expert trajectories and poorly generalize to agent trajectories. Updating the proximity function with online agent experience lowers the proximity prediction outside of the expert trajectories and thus leads an agent to follow the expert. Our method with the uncertainty penalty shows superior performance in FETCH PICK and HAND ROTATE, while it performs similarly with our method without the uncertainty penalty in other environments. Our method using the linear proximity function achieves similar to or slightly lower performance than the exponential proximity function used in the main paper. Offline pre-training of the proximity function is also helpful in most environments.

We also compare to an ablation which learns the proximity function through a ranking-based loss similar to Brown et al. [5], Burke et al. [6]. However, we empirically found it to be ineffective and difficult to train. This ranking-based loss uses the criterion that for two states from an expert trajectory s_{t_1}, s_{t_2}, the proximities should obey $f(s_{t_1}) < f(s_{t_2})$ if $t_1 < t_2$. We therefore train the proximity function with the cross entropy loss $-\sum_{t_i < t_j} \log \frac{\exp f_\phi(s_{t_j})}{\exp f_\phi(s_{t_i}) + \exp f_\phi(s_{t_j})}$. We incorporate agent experience by adding an additional loss which ranks expert states above agent states for randomly sampled pairs of expert and agent states (s_e, s_a) through the cross-entropy loss:

$$- \sum_{s_a \sim D^e, s_e \sim \pi_\theta} \log \frac{\exp f_\phi(s_e)}{\exp f_\phi(s_a) + \exp f_\phi(s_e)}. \tag{6}$$

Unlike the discounting factor in the discounting-based proximity function, the ranking-based training requires no hyperparameters. However, as shown in Figure 8, the lack of supervision on ground truth proximity scores results in less meaningful predicted proximity and a worse learning signal for the agent, which could explain its poor performance.

We also show results for applying spectral normalization [28] to GAIfO-s [47] in Figure 10 across all tasks. While regularizing the GAIfO-s discriminator can consistently improve its performance, it still cannot generalize as well as our method for the majority of tasks. As mentioned in Section 4.7,

Figure 8: Ablation on proximity function design and online/offline proximity function training. We compare our method to the proximity function with actions as input or with a ranking-based objective (Equation 6). Our method shows consistently superior or comparable performance over all ablations.

(a) FETCH PICK 1.75x δ ablation (b) FETCH PUSH 1.75x δ ablation

Figure 9: Analyzing different choices of the proximity discounting factor δ for training the proximity function. The model learns similarly well over a range of δ values around 0.95, but struggles for too large or too small δ.

(a) NAVIGATION 50% (b) ANT 0.03 (c) MAZE 50%

(d) FETCH PICK 1.75x (e) FETCH PUSH 1.75x (f) HAND ROTATE 0.35

Figure 10: Effect of applying spectral normalization to the GAIfO-s baseline compared to the performance of our method. While regularization helps GAIfO-s, it still is outperformed by our method in the majority of tasks.

GAIfO-s has a bias to provide negative rewards encouraging the agent to end the episode early, which is a desirable property for the HAND ROTATE task. Vanilla GAIfO-s therefore performs better than our method in this environment, and spectral normalization for the discriminator further improves GAIfO-s performance.

E Qualitative Results

It is important for agent learning that the proximity function gives higher values for states that are temporally closer to the goal. To verify this intuition, we visualize the proximity values predicted by the proximity function in a successful episode from agent learning in Figure 11. In Figure 11, we can observe that the predicted proximity increases as the agent moves closer to the goal (except HAND ROTATE). This provides an example of the proximity function generalizing to agent experience and providing a meaningful reward signal for agent learning.

We notice that while the predictions increase as the agent nears the goal, the proximity prediction values are often low (<0.1) as shown in Figure 11c. These low values are mostly predicted for the states not covered in the demonstrations due to the adversarial online training of the proximity

(a) ANT REACH

(b) MAZE2D

(c) FETCH PICK

(d) FETCH PUSH

(e) HAND ROTATE

Figure 11: Visualizing the proximity predictions for a successful trajectory from agent learning. Four informative frames are selected from the overall trajectory and the predicted proximity value is displayed below. The proximity prediction visualization for NAVIGATION can be found in Figure 4d.

function. During online proximity function training, we label agent experience with 0 proximity and therefore proximity predictions get lower, especially for states not in the demonstrations.

For HAND ROTATE, the proximity function fails to predict increasing proximity for states near the goal as an agent cannot learn to imitate the exact expert trajectories. Instead, due to the negatively biased reward, the agent finds a new way to solve the task as discussed in Section 4.7 and therefore achieves low proximity predictions even for successful trajectories as shown in Figure 11e. However, our method still provides relatively higher proximity values near goal states compared to baseline methods, which leads our agent to achieve higher performance in noisy environments.

F   Implementation Details

We use PyTorch [32] for our implementation and all experiments are conducted on a workstation with an Intel Xeon E5-2640 v4 CPU and a NVIDIA Titan Xp GPU. Most adversarial imitation learning methods and our method are trained for around 3 hours with 32 parallel workers. GoalGAIL and SQIL training takes around 48 hours since they use off-policy optimization with a single worker.

F.1   Environment Details

In this section, we summarize details of the six goal-directed tasks discussed in this paper. For all environments, the starting and goal states are randomly initialized. All units in this section are in meters and radians unless otherwise specified. The summary of observation spaces, action spaces, and episode lengths are described in Table 1. To evaluate the generalization capability of our method and baselines, we constrain the coverage of expert demonstrations or add additional starting state noise during agent learning as discussed in Section C.

Figure 12: The goals of the expert demonstrations in red for the NAVIGATION 25% holdout setting.

NAVIGATION [7]   In NAVIGATION, the state consists of a one-hot vector for each grid cell encoding wall, empty space, agent, or goal. NAVIGATION has four discrete actions for moving in four directions. We collect 250 expert demonstrations using the shortest path algorithm, BFS search. The 25% holdout region is visualized in Figure 12.

MAZE2D [15]   In MAZE2D, the state consists of the agent's 2D position, velocity, and the goal position. The point mass agent moves around the maze by controlling the continuous value of its (x, y) velocity. The only modification in this environment from `maze2d-medium-v1` [15] is the episode length reduced from 600 to 400. We collect 100 expert demonstrations using a planner provided by Fu et al. [15].

ANT REACH [16]   In ANT REACH the state consists of joint angle, velocity, force and the relative goal position, and the agent is controlled using joint torque control. We collect 1,000 demonstrations using an expert policy trained using PPO [40] based on the reward function $R(s, a) = 1 - 0.2 \cdot ||p_{ant} - p_{goal}||_2 - 0.005 \cdot ||a||_2^2$, where p_{ant} and p_{goal} are (x, y)-positions of the ant and goal, respectively, and a is an action. Please refer to the code for more details.

FETCH PICK and FETCH PUSH [34]   The actions in the FETCH experiments use 3-D end-effector position control and 1-D continuous control for the gripper (fixed for FETCH PUSH). A 16-dimensional state in FETCH tasks consists of the relative position of the goal from the object, relative position of the end-effector to the object, and robot joint state. We found that not including the velocity information was beneficial for all learning from observation approaches in FETCH tasks. In FETCH PICK, we generate 1,000 demonstrations by hard coding the Sawyer Robot to first reach above the object, then reach down and grasp, and finally move to the target position. Similarly, in FETCH PUSH, we collect 664 demonstrations by hard coding the Sawyer to reach behind the object and then execute a planar push towards to the goal.

HAND ROTATE [34]   The original task `HandManipulateBlockRotateZ-v0` proposed in Plappert et al. [34] is challenging to solve without reward due to its large and combinatorial state space and large action space. Hence, we reduce the initial and goal z rotations of the block to $[-\frac{\pi}{32}, \frac{\pi}{32}]$ and $[\frac{\pi}{3}, \frac{\pi}{2}]$. The 68-D state space consists of the agent's joint angles and velocities, and object pose. The 20-D action space is for joint torque control of 24-DoF Shadow Dexterous Hand. We collect 10,000 demonstrations using an expert policy trained with DDPG+HER [2] using a sparse reward.

F.2   Network Architectures

Actor and critic networks: We use the same architecture for actor and critic networks except for the output layer where the actor network outputs an action distribution while the critic network outputs a critic value. For NAVIGATION, the actor and critic network consists of $CONV(3, 2, 16) - ReLU -$

$MaxPool(2, 2) - CONV(3, 2, 32) - ReLU - CONV(3, 2, 64)$ followed by two fully-connected layers with hidden layer size 64, where $CONV(k, s, c)$ represents a c-channel convolutional layer with kernel size k and stride s. For other tasks, we model the actor and critic networks as two separate 3-layer MLPs with hidden layer size 256. For the continuous control tasks, the last layer of the actor MLP has two heads to output the mean and standard deviation of a Gaussian distribution which an action is sampled from. We use the ReLU activation for NAVIGATION and $\tanh$ for other tasks.

Goal proximity function and discriminator: The goal proximity function and discriminator use a CNN encoder (the same CNN architecture as the actor and critic networks) followed by a hidden layer of size 64 for NAVIGATION and a 3-layer MLP with a hidden layer of size 64 for other tasks. When measuring the uncertainty of predictions, we use an ensemble of 5 networks.

F.3 Training Details

For our method and all baselines except BC [35] and BCO [46], we train policies using PPO [40]. The hyperparameters for policy training are shown in Table 2, while the hyperparameters for the proximity and discriminator function are shown in Table 3. For our method, we found it helpful to normalize the reward based on the moving average and standard deviation of returns. We also did so for baselines when it helped.

For hyperparameter tuning, we searched over entropy coefficients $\{0.0001, 0.001, 0.01\}$, state normalization $\{\text{True}, \text{False}\}$, uncertainty coefficient $\{0.0001, 0.001, 0.01, 0.1\}$, learning rates $\{0.0001, 0.0003, 0.001\}$, and reward normalization $\{\text{True}, \text{False}\}$.

In BC, the demonstrations were split into 80% training data and 20% validation data. The policy was trained on the training data until the validation loss stopped decreasing. The policy is then evaluated for 1,000 episodes to get an average success rate.

In GAIfO-s and GAIL, we use the reward form of $\log D(s) - \log(1 - D(s))$ and $\log D(s, a) - \log(1 - D(s, a))$, respectively, from Finn et al. [12], Fu et al. [14].

For GoalGAIL [9], we use the default hyperparameters used in the original implementation. For the policy network, we use a deterministic policy for DDPG [25] and use the $\tanh$ activation to normalize the policy output between $[-1, 1]$. We update the policy and critic every 2 environment steps and the discriminator every 10 environment steps to prevent overfitting.

Algorithm 1 Imitation learning with learned goal proximity

Require: Expert demonstrations $\mathcal{D}^e = \{\tau_1^e, \ldots, \tau_N^e\}$
 1: Initialize goal proximity function f_ϕ and policy π_θ
 2: **for** $i = 0, 1, ..., M$ **do**
 3:     Sample expert demonstration $\tau^e \sim \mathcal{D}^e$
 4:     Update f_ϕ with τ^e to minimize Equation 1   ▷ Offline proximity function training
 5: **end for**
 6: **for** $i = 0, 1, ..., L$ **do**
 7:     Rollout trajectories $\tau_i = (s_0, \ldots, s_{T_i})$ with π_θ
 8:     Compute proximity reward $R_\phi(s_t, s_{t+1})$ for $(s_t, s_{t+1}) \sim \tau_i$ using Equation 5
 9:     Update π_θ using any RL algorithm   ▷ Policy training
10:     Update f_ϕ with τ_i and $\tau^e \sim \mathcal{D}^e$ to minimize Equation 2   ▷ Online proximity function training
11: **end for**

Table 1: Environment details. In NAVIGATION and MAZE2D, the goal and agent are randomly initialized anywhere on the grid. In ANT REACH, the angle of the goal and the velocity of the agent are randomly initialized. The goal and object noise in FETCH describes the amount of uniform noise applied to the (x, y) coordinates of the object and goal. In HAND ROTATE, the state and goal noises are applied to the initial and goal object rotations.

	State	Action	Goal noise	State noise	Episode len.	# demos
NAVIGATION	$(19, 19, 4)$	4	-	-	50	250
MAZE2D	6	2	-	-	600	100
ANT REACH	132	8	$\theta \in [0, \pi]$	$v \in [\pm.005]$	50	1,000
FETCH PICK	16	4	$(x, y) \in [\pm.02, \pm.05]$		50	1,000
FETCH PUSH	16	3	$(x, y) \in [\pm.02, \pm.05]$		60	664
HAND ROTATE	68	20	$\theta \in [\frac{\pi}{2}, \frac{\pi}{3}]$	$\theta \in [\pm\frac{\pi}{32}]$	50	10,000

Table 2: PPO hyperparameters used for baselines and our method.

Hyperparameter	Value
Learning Rate	3e-4
Learning Rate Decay	Linear decay
# Mini-batches	4 (NAVIGATION), 32 (others)
# Epochs per Update	4 (NAVIGATION), 10 (others)
Discount Factor γ	0.99
Rollout Size	16,000 (ANT REACH), 4,096 (others)
Entropy Coefficient	0.01 (NAVIGATION), 0.001 (others)
State Normalization	False (NAVIGATION), True (others)

Table 3: Hyperparameters for goal proximity functions (ours) and discriminators (baselines).

Hyperparameter	Value
# Networks for Ensemble	5
# Epochs for Pre-training	5
Discount Factor δ	0.95 (exponential), $1/H$ (linear)
Uncertainty Coefficient λ	0.001 (FETCH), 0.01 (others)
Learning Rate (ours)	1e-3 (NAVIGATION, FETCH, MAZE2D), 1e-4 (ANT REACH, HAND ROTATE)
Learning Rate (baselines)	1e-4
Batch Size	32 (NAVIGATION), 128 (others)
# Updates per Agent Update	1
Experience Buffer Size	16,000 (ANT REACH), 4,096 (others)
Reward Norm. (ours)	True
Reward Norm. (baselines)	True (FETCH), False (others)